

FAU RTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO
1426	05-00079-00-SW	DUPAGE	22	2
STA. NONE		TO STA. NONE		
FED. ROAD DIST. NO. 1	ILLINOIS	FED. AID PROJECT		
CONTRACT NO. 83981				

GENERAL NOTES

CONTRACTOR SHALL NOTIFY THE VILLAGE OF VILLA PARK PUBLIC WORKS DEPARTMENT AT (630) 834-8505 A MINIMUM OF TWENTY-FOUR (24) HOURS IN ADVANCE FOR INSPECTIONS.

CONTRACTOR SHALL MAINTAIN A MINIMUM OF ONE (1) SET OF APPROVED CONSTRUCTION PLANS ON THE SITE AT ALL TIMES.

ALL PAVING, CURB & GUTTER, DRIVEWAYS, AND SIDEWALKS, INCLUDING EARTHWORK REQUIRED FOR PREPARATION OF SUBGRADE, SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE ILLINOIS DEPARTMENT OF TRANSPORTATION'S "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION," CURRENT EDITION AND SUPPLEMENTS, EXCEPT AS MODIFIED TO CONFORM WITH VILLAGE OF VILLA PARK REQUIREMENTS.

CONTRACTOR SHALL PROVIDE FOR THE IMMEDIATE REMOVAL OF ANY MUD AND/OR DEBRIS THAT IS DEPOSITED ONTO ANY STREET(S), DRIVEWAY(S) OR SIDEWALK(S) AS A RESULT OF CONSTRUCTION. THIS WORK SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT

ALL CONSTRUCTION PERSONNEL WILL BE REQUIRED TO WEAR STRONG YELLOW/GREEN VESTS HAVING FLUORESCENT ORANGE STRIPES AND HARD HATS AT ALL TIMES WHILE ON THE CONSTRUCTION SITES. COMPLIANCE WITH THIS REQUIREMENT SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGE OF VILLA PARK. BEFORE STARTING ANY EXCAVATING THE CONTRACTOR SHALL CONTACT "JULIE" AT (800) 892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, CABLE, GAS, OR OTHER FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED)

BARRICADES: THE CONTRACTOR SHALL PROVIDE AND INSTALL TWO (2) WEIGHTED SANDBAGS ON EACH TYPE I OR TYPE II BARRICADE USED. ONE (1) WEIGHTED SAND BAG SHALL BE USED ACROSS EACH BOTTOM RAIL.

SIDEWALK NOTES

ALL SIDEWALK TO BE REMOVED SHALL BE SAWCUT FULL DEPTH THE ENTIRE LENGTH OF REMOVAL. THIS WORK SHALL BE CONSIDERED INCIDENTAL TO SIDEWALK REMOVAL.

ALL PCC SIDEWALK SHALL BE CONSTRUCTED OF IDOT CLASS SI PORTLAND CEMENT CONCRETE.

ALL SIDEWALKS SHALL BE PROMPTLY BACKFILLED AND PROTECTED FROM POTENTIAL DAMAGE AND VANDALISM.

MINIMUM TRANSVERSE SLOPE OF PROPOSED SIDEWALK SHALL BE 1/8" / FT (1%) TYPICAL.
 MAXIMUM TRANSVERSE SLOPE OF PROPOSED SIDEWALK SHALL BE 1/4" / FT (2%) TYPICAL.

ALL PROPOSED SIDEWALKS SHALL MEET EXISTING WIDTHS.


HOT-MIX ASPHALT MIXTURE REQUIREMENTS		
MIXTURE TYPE	AC TYPE	AIR VOIDS
HOT-MIX ASPHALT DRIVEWAY PAVEMENT HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50, IL 9.5mm	PG 64-22	4% @ 50 Gyr.

THE UNIT WEIGHT USED TO CALCULATE ALL HMA SURFACE MIXTURE QUANTITIES IS 112 LBS/SQ YD/IN.

* WHEN RAP EXCEEDS 20%, THE NEW ASPHALT BINDER IN THE MIX SHALL BE PG 58-22.

SUMMARY OF QUANTITIES

NUMBER	DESCRIPTION	ABBREVIATION	UNITS	QUANTITY SFTY-1B
20200100	EARTH EXCAVATION	EARTH EXCAVATION	CU YD	689
25000400	NITROGEN FERTILIZER NUTRIENT	NITROGEN FERT NUTR	POUND	13
25000500	PHOSPHORUS FERTILIZER NUTRIENT	PHOSPHORUS FERT NUTR	POUND	13
25000600	POTASSIUM FERTILIZER NUTRIENT	POTASSIUM FERT NUTR	POUND	13
25200110	SODDING, SALT TOLERANT	SODDING SALT TOLERANT	SQ YD	1,334
25200200	SUPPLEMENTAL WATERING	SUPPLE WATERING	UNIT	1
31101200	SUB-BASE GRANULAR MATERIAL, TYPE B 4"	SUB GRAN MAT B 4	SQ YD	3,500
40603335	HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50	HMA SC "D" N50	TON	30
42300200	PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 6 INCH	PCC DRIVEWAY PAVT 6	SQ YD	80
42400200	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	PC CONC SIDEWALK 5	SQ FT	30,000
42400800	DETECTABLE WARNINGS	DETECTABLE WARNINGS	SQ FT	424
44000200	DRIVEWAY PAVEMENT REMOVAL	DRIVE PAVEMENT REM	SQ YD	550
44000600	SIDEWALK REMOVAL	SIDEWALK REM	SQ FT	1,000
67100100	MOBILIZATION	MOBILIZATION	L SUM	1
70102620	TRAFFIC CONTROL AND PROTECTION, STANDARD 701501	TR CONT & PROT 701501	L SUM	1
70102640	TRAFFIC CONTROL AND PROTECTION, STANDARD 701801	TR CONT & PROT 701801	L SUM	1
X2110100	TOPSOIL FURNISH AND PLACE, SPECIAL	TOPSOIL F & P SPL	CU YD	43
XX000406	BRICK PAVER REMOVAL AND REPLACEMENT	BRICK PAVER REM & REP	SQ FT	36
XX001621	BRICK PAVER REMOVAL	BRICK PAVER REMOVAL	SQ FT	90
XX006998	GRAVEL REMOVAL	GRAVEL REMOVAL	SQ YD	43
Z0013798	CONSTRUCTION LAYOUT	CONSTRUCTION LAYOUT	L SUM	1

 <p>VILLAGE OF VILLA PARK ENGINEERING DIVISION 20 SOUTH ARDMORE AVENUE VILLA PARK, ILLINOIS 60181-2696</p>	<p>REVISIONS</p> <table border="1"> <tr> <th>NAME</th> <th>DATE</th> </tr> <tr> <td>PER IDOT REVIEW</td> <td>03/03/08</td> </tr> <tr> <td>PER IDOT REVIEW</td> <td>06/03/09</td> </tr> <tr> <td>PER IDOT REVIEW</td> <td>07/10/09</td> </tr> </table>		NAME	DATE	PER IDOT REVIEW	03/03/08	PER IDOT REVIEW	06/03/09	PER IDOT REVIEW	07/10/09	<p>VILLAGE OF VILLA PARK, ILLINOIS</p> <p>GENERAL NOTES</p> <p>SUMMARY OF QUANTITIES</p> <p>MADISON STREET</p> <p>SHEET 1 OF 2</p> <p>SCALE: NONE DATE: 11/07/2007</p> <p>DRAWN BY: K.L.M. CHECKED BY: V.I.V.</p>
	NAME	DATE									
	PER IDOT REVIEW	03/03/08									
	PER IDOT REVIEW	06/03/09									
PER IDOT REVIEW	07/10/09										
<p>PHONE (630) 834-8505 FAX (630) 834-8509</p>											
<p>YDAS JURKEK, P.E. - VILLAGE ENGINEER</p>											