

AGGREGATE SURFACE COURSE, TYPE B							35101400
LOCATION	LT/RT	WIDTH	LENGTH	CU YD	CONVERSION 2.05 TON/CU YD	QUANTITY TON	
WALNUT STREET							
STA.	11+28.73	RT	24.0'	6.7'	3.6	7.3	
STA.	12+53.23	LT	24.0'	14.2'	8.3	16.9	
TOTAL=						24	

BITUMINOUS CONCRETE PAVEMENT PATCHING										Z0004300
LOCATION							WIDTH FEET	LENGTH FEET	DEPTH INCHES	QUANTITY TON
ASH STREET										
STA.	29+67.00	25.7' RT	TO	STA.	30+04.88	20.6' RT	3	38	5	21.1
STA.	32+81.30	15.2' RT	TO	STA.	32+85.59	26.2' LT	3	32	5	17.8
TOTAL=										39

HOT-MIX ASPHALT BASE COURSE WIDENING, 6"							35600700	
LOCATION						LT/RT	WIDTH	QUANTITY SQ YD
WALNUT STREET								
STA.	11+46.22	TO	STA.	13+01.00	LT	2' TO 5'	56.2	
STA.	11+47.34	TO	STA.	13+01.00	RT	2' TO 6'	79.4	
MAPLE ROW								
STA.	13+01.00	TO	STA.	15+86.00	LT	4'	147.2	
STA.	13+01.00	TO	STA.	15+86.00	RT	6.5'	195.7	
MORGAN STREET								
STA.	15+86.00	TO	STA.	18+82.20	RT	2.5' TO 5'	103.3	
ASH STREET								
STA.	30+02.00	TO	STA.	31+17.00	LT	4' TO 7'	91.4	
STA.	30+02.00	TO	STA.	31+17.00	RT	2' TO 5'	64.6	
STA.	31+17.00	TO	STA.	32+88.33	LT	3.0' TO 5.0'	72.4	
TOTAL=							810	

STORM SEWER PVC (SDR 26), 12"								XX003360
LOCATION							QUANTITY FOOT	
MAPLE ROW								
STA.	13+25.00	17' RT	TO	STA.	13+25.00	17' LT	34	
STA.	13+25.00	17' LT	TO	STA.	15+79.73	17.5' LT	264	
STA.	15+79.73	17.5' LT	TO	STA.	16+25.00	9.2' RT	53	
MORGAN STREET								
STA.	18+63.77	8.5' RT	TO	STA.	18+63.77	1.5' LT	10	
ASH STREET								
STA.	29+67.00	25.7' RT	TO	STA.	30+04.88	20.6' RT	38	
STA.	30+04.88	20.6' RT	TO	STA.	30+20.36	13.7' RT	17	
STA.	32+81.19	13.3' RT	TO	STA.	32+87.23	24.0' LT	38	
TOTAL=							454	

INLETS, TYPE B, TYPE 1 FRAME, OPEN LID				60240210
LOCATION	LT/RT	OFFSET FEET	QUANTITY EACH	
MORGAN STREET				
STA.	18+63.77	LT	1.8'	1
ASH STREET				
STA.	32+87.23	LT	24.0'	1
TOTAL=			2	

CONCRETE CURB, TYPE B						60600605
LOCATION					LT/RT	QUANTITY FOOT
MORGAN STREET						
STA.	16+22.59	TO	STA.	16+42.59	RT	20.0
TOTAL=					20	