


FRAMING PLAN



- NOTES:**
- Two hardened washers required for each set of oversized holes.
 - All diaphragms shall be installed as steel is erected and secured with erection pins and bolts except as otherwise noted. Individual diaphragms at supports may be temporarily disconnected to install bearing anchor rods.
 - Load carrying components designated "NTR" shall conform to the Impact Testing Requirements, Zone 2.

benesch
engineers · scientists · planners

Alfred Benesch & Company
205 North Michigan Avenue, Suite 2400
Chicago, Illinois 60601
312-565-0450 Job No. 10093

FILE NAME = 0161000_60J16_025.Framingplan.dgn

USER NAME = jsurber	DESIGNED - JDM	REVISED -
PLOT SCALE =	CHECKED - RMM	REVISED -
PLOT DATE = 12/20/2012	DRAWN - MAK	REVISED -
	CHECKED - RMM	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**FRAMING PLAN
STRUCTURE NO. 016-1000/1001**

SHEET NO. SA25 OF SA40 SHEETS

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
372	2013-038B-R	COOK	821	273
CONTRACT NO. 60J16			ILLINOIS FED. AID PROJECT	

X:\100005\10093\Eng_Docs_Phase_1\1001_1st_Ave_over_47th_St\Final\0161000_60J16_025.Framingplan.dgn 7/29/2014 2:00:30 PM