

FAP 885 (IL 146) PAVEMENT RESURFACING SCHEDULE
CONTINUED

LOCATION STATION TO STATION				LENGTH	ROADWAY WIDTH	ROADWAY AREA	HOT-MIX ASP. SURF. REMOV. 2 1/4"	TEMP RAMP	HOT-MIX ASP. SUR. CSE., MIX C, N 90 (1 1/2"	LEVELING BINDER (MM), IL-9.5mm, N90 (1"	BIT. MAT. (PRIME COAT)
				FOR INFORMATIONAL PURPOSE ONLY							
				(FT)	(FT)	(SQ YD)					
1654+09.72	TO	1657+49.13	339	24	905	905	14	77	39	611	
OMIT SN 076-0005 - STA 1657+49.13 TO STA 1661+37.17											
1661+37.17	TO	1663+18.00	181	24	482	482	14	41	21	326	
CITY LIMITS - STA 1663+18											
1663+18.00	TO	1664+59.00	141	24	376	376	14	32	16	254	
OMIT EX LEVEE - STA 1664+59 TO STA 1665+11											
1665+11.00	TO	1665+62.18	51	24	136	136	14	12	6	93	
EQ STA 1665+62.18 (BK) = STA 1667+09.59 (AH)											
1667+09.59	TO	1673+73.00	663	24	1769	1769		150	75	1194	
EQ STA 1674+17.61 (BK) = STA 1266+34.00 (AH) INTERSECTION OF IL 146 WITH MAIN ST. IN GOLCONDA.											
	1673+73.00	TO	1266+10.00			489	489	15	42	21	330
LT.	1674+17.61							15			
LT.	1266+34.00							14			
TOTALS						139,358	205	11774	5895	94,078	