INDEX OF SHEETS

SHEET NO	DESCRIPTION
1	COVER SHEET
2	SIGNTURE SHEET
3	INDEX OF SHEETS, STANDARDS, AND MIX DESIGNS
4	GENERAL NOTES, COMMITMENTS
5-6	SUMMARY OF QUANTITIES
7-9	TYPICAL SECTIONS
10	PAVEMENT RESURFACING SCHEDULE
11-13	PAVEMENT MARKING SCHEDULE
14	RAISED REFLECTIVE MARKERS SCHEDULES
15	DETAIL: TEMPORARY HOT-MIX ASPHALT TRANSITIONS
16	DETAIL: UNEVEN LANES SIGN
17	DETAIL: ROUGH GROOVED SURFACE SIGN

HIGHWAY STANDARDS

000001-06 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001006 DECIMAL OF AN INCH AND OF A FOOT
442201-03 CLASS C & D PATCHES
701001-02 OFF-RD OPERATIONS, 2L, 2W, MORE THAN 15* (4.5 m) AWAY
701006-05 OFF-RD OPERATIONS, 2L, 2W, 15* (4.5 m) TO 24'' (600 mm) FROM PAVEMENT EDGE
701011-04 OFF-RD MOVING OPERATIONS, 2L, 2W, DAY ONLY
701301-04 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701306-03 LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS DAY ONLY, FOR SPEEDS ¢ 45 MPH
701311-03 LANE CLOSURE, 2L, 2W, MOVING OPERATIONS - DAY ONLY
701336-06 LANE CLOSURE, 2L, 2W, WORK AREAS IN SERIES, FOR SPEEDS ¢ 45 MPH
701901-03 TRAFFIC CONTROL DEVICES
780001-04 TYPICAL PAVEMENT MARKINGS
781001-03 TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

MIXTURE REQUIREMENTS SHALL BE PREPARED AS DIRECTED BELOW:

Locations	Hot-Mix Asphalt Surface Course and Incidental HMA Surfacing
Mixture Use(s):	Hot-Mix Asphalt Surface Course, Mix C, N90
AC/PG:	PG64-22
ABR % (Max):	See Special Provision
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture (Gradation Mixture)	IL-9.5 mm
Friction Aggregate:	C Surface
Quality Management Program:	QCP

Locations	Hot-Mix Asphalt Leveling Binder Course
Mixture Use(s):	Hot-Mix Asphalt Leveling Binder, N90, IL-9.5mm Fine Grade
AC/PG:	PG64-22
ABR % (Max):	See Special Provision
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture (Gradation Mixture)	IL-9.5mm Fine Grade
Friction Aggregate:	None
Quality Management Program:	QCP

Locations	Pavement Patching
Mixture Use(s):	Hot-Mix Asphalt Binder Course, N90, IL-19.0mm Fine Grade
AC/PG:	PG64-22
ABR % (Max):	See Special Provision
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture (Gradation Mixture)	IL-19.0mm Fine Grade
Friction Aggregate:	None
Quality Management Program:	QC/QA