

"W" = Top bars spacing + 4"


7 - 1 - 10
------------

R-27

1170 SOUTH HOUBOLT ROAD	USER NAME = brianf	DESIGNED - RRD	REVISED		TEMPORARY CONCRETE BARRIER	F.A.I. SECTION	COUNTY TOTAL SHEET
JOLIET, ILLINOIS 60431			REVISED	STATE OF ILLINOIS	STRUCTURE NO. 016–0587	55 22-1HB-R	COOK/DUPAGE 161 92
STRAND (815) 744-4200	PLOT SCALE =	50	REVISED	DEPARTMENT OF TRANSPORTATION			CONTRACT NO. 60K77
ASSOCIATES® IDFPR NO. 184-001273	PLOT DATE = 1/29/2013	CHECKED - RRD	REVISED		SHEET NO. 4 OF 42 SHEETS	ILLINOIS FED.	AID PROJECT

## NOTES

Detail I - With Bar Splicer or Couplers: Connect one (1) 1" x 7' 'x "W" steel P to the top layer of couplers with  $2 \cdot {}^{5}_{8}$ "  $\phi$  bolts screwed to coupler at approximate Q of each barrier panel. Detail II - With Extended Reinforcement Bars: Connect one (1) 1" x 7" x "W" steel ₱ to the concrete slab or concrete wearing surface with 2-5<sub>8</sub>" \$ Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate & of each barrier panel. Cost of anchorage is included with Temporary Concrete Barrier. The 1" x 7" x "W" plate shall not be removed until stage II construction forms and all reinforcement bars are in place and the concrete is ready



\* Required only with Detail II