









**LEGEND**

-  WORK AREA
-  IMPACT ATTENUATORS, TEMPORARY (FULLY REDIRECTIVE, NARROW), TEST LEVEL 3
-  TEMPORARY CONCRETE BARRIER
-  DRUM WITH STEADY BURN MONODIRECTIONAL LIGHT
-  DIRECTION INDICATOR BARRICADE WITH STEADY BURN MONODIRECTIONAL LIGHT
-  TYPE II BARRICADES OR DRUMS
-  SIGN
-  ARROW BOARD

**STAGE II CONSTRUCTION:**

1. CLOSE INSIDE LANES OF US ROUTE 30 / IL 56 AS SHOWN IN THE PLANS AND IN ACCORDANCE WITH HIGHWAY STANDARDS 701400-05, 701402-09, AND 701411-08.
2. PERFORM INSIDE LANE STRUCTURAL AND APPROACH REPAIRS AS SHOWN IN THE PLANS.
3. REMOVE TEMPORARY PAVEMENT PLACED IN STAGE I ALONG US ROUTE 30 / IL 56 IN ACCORDANCE WITH HIGHWAY STANDARD 701411-08.
4. APPLY PERMANENT PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKERS AS SHOWN IN THE PROPOSED PAVEMENT MARKING PLANS IN ACCORDANCE WITH HIGHWAY STANDARD 701426-04.

**NOTES:**

1. FIRST TWO WARNING SIGNS IN EACH DIRECTION REQUIRE MONO-DIRECTIONAL FLASHING BEACONS.
2. FOR DRUM/BARRICADE SPACING SEE APPLICABLE HIGHWAY STANDARD.

