

WB PGL (Line No. 10)

Location	Station	Offset from WB PGL F.A.I. 57/70	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection & Grinding
Bk. of W. Abutment	2291+67.60	0.00	631.63	631.65
⊘ Bearing W. Abut.	2291+69.55	0.00	631.64	631.66
A	2291+79.55	0.00	631.67	631.74
B	2291+89.55	0.00	631.69	631.83
C	2291+99.55	0.00	631.72	631.91
D	2292+09.55	0.00	631.74	631.98
E	2292+19.55	0.00	631.76	632.04
F	2292+29.55	0.00	631.78	632.08
G	2292+39.55	0.00	631.80	632.10
H	2292+49.55	0.00	631.81	632.10
I	2292+59.55	0.00	631.82	632.09
J	2292+69.55	0.00	631.83	632.07
K	2292+79.55	0.00	631.84	632.04
L	2292+89.55	0.00	631.85	632.01
M	2292+99.55	0.00	631.85	631.97
N	2293+09.55	0.00	631.85	631.94
O	2293+19.55	0.00	631.85	631.91
P	2293+29.55	0.00	631.85	631.89
Q	2293+39.55	0.00	631.85	631.87
⊘ Bearing Pier	2293+49.47	0.00	631.84	631.86
R	2293+59.47	0.00	631.83	631.88
S	2293+69.47	0.00	631.82	631.89
T	2293+79.47	0.00	631.81	631.91
U	2293+89.47	0.00	631.79	631.94
V	2293+99.47	0.00	631.78	631.98
W	2294+09.47	0.00	631.76	632.01
X	2294+19.47	0.00	631.73	632.05
Y	2294+29.47	0.00	631.71	632.07
Z	2294+39.47	0.00	631.69	632.09
AA	2294+49.47	0.00	631.66	632.09
BB	2294+59.47	0.00	631.63	632.08
CC	2294+69.47	0.00	631.60	632.05
DD	2294+79.47	0.00	631.56	632.00
EE	2294+89.47	0.00	631.53	631.93
FF	2294+99.47	0.00	631.49	631.83
GG	2295+09.47	0.00	631.45	631.73
HH	2295+19.47	0.00	631.40	631.61
II	2295+29.47	0.00	631.36	631.49
JJ	2295+39.47	0.00	631.31	631.38
⊘ Bearing E. Abut.	2295+45.81	0.00	631.28	631.30
Bk. of E. Abutment	2295+47.76	0.00	631.27	631.29

Girder 8 (Line No. 11)

Location	Station	Offset from WB PGL F.A.I. 57/70	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection & Grinding
Bk. of W. Abutment	2291+64.93	4.35	631.53	631.55
⊘ Bearing W. Abut.	2291+66.88	4.35	631.54	631.56
A	2291+76.88	4.35	631.57	631.64
B	2291+86.88	4.35	631.59	631.73
C	2291+96.88	4.35	631.62	631.81
D	2292+06.88	4.35	631.64	631.88
E	2292+16.88	4.35	631.67	631.94
F	2292+26.88	4.35	631.68	631.98
G	2292+36.88	4.35	631.70	632.00
H	2292+46.88	4.35	631.72	632.01
I	2292+56.88	4.35	631.73	632.00
J	2292+66.88	4.35	631.74	631.98
K	2292+76.88	4.35	631.75	631.95
L	2292+86.88	4.35	631.76	631.92
M	2292+96.88	4.35	631.76	631.88
N	2293+06.88	4.35	631.76	631.85
O	2293+16.88	4.35	631.76	631.82
P	2293+26.88	4.35	631.76	631.80
Q	2293+36.88	4.35	631.76	631.78
⊘ Bearing Pier	2293+46.81	4.35	631.75	631.77
R	2293+56.81	4.35	631.74	631.79
S	2293+66.81	4.35	631.73	631.80
T	2293+76.81	4.35	631.72	631.83
U	2293+86.81	4.35	631.71	631.86
V	2293+96.81	4.35	631.69	631.89
W	2294+06.81	4.35	631.67	631.93
X	2294+16.81	4.35	631.65	631.96
Y	2294+26.81	4.35	631.63	631.99
Z	2294+36.81	4.35	631.60	632.01
AA	2294+46.81	4.35	631.57	632.01
BB	2294+56.81	4.35	631.55	632.00
CC	2294+66.81	4.35	631.51	631.97
DD	2294+76.81	4.35	631.48	631.92
EE	2294+86.81	4.35	631.44	631.84
FF	2294+96.81	4.35	631.41	631.75
GG	2295+06.81	4.35	631.37	631.65
HH	2295+16.81	4.35	631.33	631.53
II	2295+26.81	4.35	631.28	631.41
JJ	2295+36.81	4.35	631.24	631.30
⊘ Bearing E. Abut.	2295+43.14	4.35	631.20	631.22
Bk. of E. Abutment	2295+45.09	4.35	631.20	631.22

Girder 9 (Line No. 12)

Location	Station	Offset from WB PGL F.A.I. 57/70	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection & Grinding
Bk. of W. Abutment	2291+59.41	13.35	631.33	631.35
⊘ Bearing W. Abut.	2291+61.37	13.35	631.33	631.35
A	2291+71.37	13.35	631.36	631.44
B	2291+81.37	13.35	631.39	631.53
C	2291+91.37	13.35	631.42	631.61
D	2292+01.37	13.35	631.44	631.68
E	2292+11.37	13.35	631.47	631.74
F	2292+21.37	13.35	631.49	631.78
G	2292+31.37	13.35	631.50	631.81
H	2292+41.37	13.35	631.52	631.81
I	2292+51.37	13.35	631.54	631.81
J	2292+61.37	13.35	631.55	631.79
K	2292+71.37	13.35	631.56	631.76
L	2292+81.37	13.35	631.56	631.73
M	2292+91.37	13.35	631.57	631.69
N	2293+01.37	13.35	631.57	631.66
O	2293+11.37	13.35	631.58	631.63
P	2293+21.37	13.35	631.57	631.61
Q	2293+31.37	13.35	631.57	631.60
⊘ Bearing Pier	2293+41.29	13.35	631.57	631.59
R	2293+51.29	13.35	631.56	631.60
S	2293+61.29	13.35	631.55	631.62
T	2293+71.29	13.35	631.54	631.65
U	2293+81.29	13.35	631.53	631.68
V	2293+91.29	13.35	631.51	631.71
W	2294+01.29	13.35	631.49	631.75
X	2294+11.29	13.35	631.47	631.78
Y	2294+21.29	13.35	631.45	631.81
Z	2294+31.29	13.35	631.43	631.83
AA	2294+41.29	13.35	631.40	631.84
BB	2294+51.29	13.35	631.37	631.83
CC	2294+61.29	13.35	631.34	631.80
DD	2294+71.29	13.35	631.31	631.75
EE	2294+81.29	13.35	631.28	631.68
FF	2294+91.29	13.35	631.24	631.59
GG	2295+01.29	13.35	631.20	631.48
HH	2295+11.29	13.35	631.16	631.36
II	2295+21.29	13.35	631.12	631.24
JJ	2295+31.29	13.35	631.07	631.14
⊘ Bearing E. Abut.	2295+37.62	13.35	631.04	631.06
Bk. of E. Abutment	2295+39.58	13.35	631.03	631.05