

**Midwest Testing Services, Inc.**  
3705 Progress Blvd.  
Peru, IL 61354

**BORING LOG**

Sheet 2 of 3

Phone: 815-223-6696  
Fax: 815-223-6659  
E-Mail: Midwest@TheRamp.net


Client: Hutchison Engineering, Inc.  
Project Name: Sec. 98-26104-00-BR & Sec 98-25104-00-BR  
Project Site: Stockland / Sheldon Road Districts  
Iroquois County, Illinois

Boring No. B-2  
Surface Elev. 99.70  
Auger Depth 61' Rotary Depth NA  
Start Date 05/28/05 Finish Date 05/28/05

Location: 6' Lt. Centerline Station 59+70

| (DEPTH)<br>ELEV. | DESCRIPTION OF MATERIALS  | Graphic Log | Depth in feet | SAMPLES    |             |          |                 |               |              | Dry Density (PCF) | DRILLED BY                        | REMARKS |
|------------------|---------------------------|-------------|---------------|------------|-------------|----------|-----------------|---------------|--------------|-------------------|-----------------------------------|---------|
|                  |                           |             |               | Sample No. | Sample Type | Qu (TSF) | N Value (Blows) | Bulge / Shear | Moisture (%) |                   | Randy Safranski<br>Diedrich D-120 |         |
| 78.70            |                           |             |               |            |             |          |                 |               |              |                   |                                   |         |
| 77.70            |                           |             | 22            |            |             |          |                 |               |              |                   |                                   |         |
| 76.70            | Very Stiff Gray Clay Till |             | 23            | 9          | SS          | 2.3      | 14              | B             | 18           |                   |                                   |         |
| 75.70            |                           |             | 24            |            |             |          |                 |               |              |                   |                                   |         |
| 74.70            |                           |             | 25            | 10         | SS          | 2.3      | 15              | B             | 17           |                   |                                   |         |
| 73.70            |                           |             | 26            |            |             |          |                 |               |              |                   |                                   |         |
| 72.70            |                           |             | 27            |            |             |          |                 |               |              |                   |                                   |         |
| 71.70            |                           |             | 28            | 11         | SS          | 2.8      | 15              | B             | 18           |                   |                                   |         |
| 70.70            |                           |             | 29            |            |             |          |                 |               |              |                   |                                   |         |
| 69.70            |                           |             | 30            |            |             |          |                 |               |              |                   |                                   |         |
| 68.70            |                           |             | 31            | 12         | SS          | 2.5      | 16              | B             | 18           |                   |                                   |         |
| 67.70            |                           |             | 32            |            |             |          |                 |               |              |                   |                                   |         |
| 66.70            | Medium Gray Silt          |             | 33            | 13         | SS          | —        | 18              | —             | 22           |                   |                                   |         |
| 65.70            |                           |             | 34            |            |             |          |                 |               |              |                   |                                   |         |
| 64.70            |                           |             | 35            | 14         | SS          | —        | 15              | —             | 23           |                   |                                   |         |
| 63.70            |                           |             | 36            |            |             |          |                 |               |              |                   |                                   |         |
| 62.70            |                           |             | 37            |            |             |          |                 |               |              |                   |                                   |         |
| 61.70            |                           |             | 38            | 15         | SS          | —        | 16              | —             | 22           |                   |                                   |         |
| 60.70            |                           |             | 39            |            |             |          |                 |               |              |                   |                                   |         |
| 59.70            |                           |             | 40            | 16         | SS          | —        | 16              | —             | 22           |                   |                                   |         |
| 58.70            |                           |             | 41            |            |             |          |                 |               |              |                   |                                   |         |

Groundwater Data: Static water level after auger removal - Elevation - 78.5.



**Midwest Testing Services, Inc.**  
3705 Progress Blvd.  
Peru, IL 61354

**BORING LOG**

Sheet 3 of 3

Phone: 815-223-6696  
Fax: 815-223-6659  
E-Mail: Midwest@TheRamp.net

Client: Hutchison Engineering, Inc.  
Project Name: Sec. 98-26104-00-BR & Sec 98-25104-00-BR  
Project Site: Stockland / Sheldon Road Districts  
Iroquois County, Illinois

Boring No. B-2  
Surface Elev. 99.70  
Auger Depth 61' Rotary Depth NA  
Start Date 05/28/05 Finish Date 05/28/05

Location: 6' Lt. Centerline Station 59+70

| (DEPTH)<br>ELEV. | DESCRIPTION OF MATERIALS                                | Graphic Log | Depth in feet | SAMPLES    |             |          |                 |               |              | Dry Density (PCF) | DRILLED BY                        | REMARKS |
|------------------|---|-------------|---------------|------------|-------------|----------|-----------------|---------------|--------------|-------------------|-----------------------------------|---------|
|                  |   |             |               | Sample No. | Sample Type | Qu (TSF) | N Value (Blows) | Bulge / Shear | Moisture (%) |                   | Randy Safranski<br>Diedrich D-120 |         |
| 57.70            |   |             |               |            |             |          |                 |               |              |                   |                                   |         |
| 56.70            | Very Stiff Gray Clay Till                               |             | 43            | 17         | SS          | 2.4      | 14              | B             | 18           |                   |                                   |         |
| 55.70            |   |             | 44            |            |             |          |                 |               |              |                   |                                   |         |
| 54.70            | Medium Gray Fine Sand                                   |             | 45            | 18         | SS          | —        | 20              | —             | —            |                   |                                   |         |
| 53.70            |   |             | 46            |            |             |          |                 |               |              |                   |                                   |         |
| 52.70            |   |             | 47            |            |             |          |                 |               |              |                   |                                   |         |
| 51.70            |   |             | 48            | 19         | SS          | —        | 12              | —             | —            |                   |                                   |         |
| 50.70            |   |             | 49            |            |             |          |                 |               |              |                   |                                   |         |
| 49.70            | Hard Brownish Gray Silty Clay Loam Till With Sand Seams |             | 50            | 20         | SS          | 4.9      | 36              | S             | 13           |                   |                                   |         |
| 48.70            |   |             | 51            |            |             |          |                 |               |              |                   |                                   |         |
| 47.70            |   |             | 52            |            |             |          |                 |               |              |                   |                                   |         |
| 46.70            |   |             | 53            | 21         | SS          | 4.5      | 31              | B             | 14           |                   |                                   |         |
| 45.70            |   |             | 54            |            |             |          |                 |               |              |                   |                                   |         |
| 44.70            |   |             | 55            |            |             |          |                 |               |              |                   |                                   |         |
| 43.70            |   |             | 56            | 22         | SS          | 5.3      | 35              | S             | 13           |                   |                                   |         |
| 42.70            |   |             | 57            |            |             |          |                 |               |              |                   |                                   |         |
| 41.70            |   |             | 58            | 23         | SS          | 5.5      | 37              | S             | 13           |                   |                                   |         |
| 40.70            |   |             | 59            |            |             |          |                 |               |              |                   |                                   |         |
| 39.70            |   |             | 60            |            |             |          |                 |               |              |                   |                                   |         |
| 38.70            |   |             | 61            | 24         | SS          | 4.4      | 32              | B             | 15           |                   |                                   |         |
| 37.70            |   |             | 62            |            |             |          |                 |               |              |                   |                                   |         |

Groundwater Data: Static water level after auger removal - Elevation - 78.5.

SOIL BORING LOGS  
T.R. 251 OVER COON CREEK  
SECTION 98-26104-01-BR / 98-25104-01-BR  
IROQUOIS COUNTY  
STATION 59+90.00