



SOIL BORING LOG

Page 1 of 2

Date 8/25/08

ROUTE 09-0078-00-PV DESCRIPTION On West approach to Fox River Bridge LOGGED BY DM

SECTION 09-0078-00-PV LOCATION On West approach to Fox River Bridge

COUNTY McHenry County DRILLING METHOD Hollow Stem Auger HAMMER TYPE Automatic

Table with columns for Depth (ft), Blows (16"), Blows (30"), and Soil Description. Includes data for borings 1-10 and 11-20.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer). The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T205) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Page 2 of 2

Date 8/25/08

ROUTE 09-0078-00-PV DESCRIPTION On West approach to Fox River Bridge LOGGED BY DM

SECTION 09-0078-00-PV LOCATION On West approach to Fox River Bridge

COUNTY McHenry County DRILLING METHOD Hollow Stem Auger HAMMER TYPE Automatic

Table with columns for Depth (ft), Blows (16"), Blows (30"), and Soil Description. Continuation of boring data from page 1.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer). The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T205) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Page 1 of 2

Date 8/26/08

ROUTE 09-0078-00-PV DESCRIPTION On West Bank of Fox River LOGGED BY DM

SECTION 09-0078-00-PV LOCATION On West Bank of Fox River

COUNTY McHenry County DRILLING METHOD Hollow Stem Auger HAMMER TYPE Automatic

Table with columns for Depth (ft), Blows (16"), Blows (30"), and Soil Description. Includes data for borings 1-10 and 11-20.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer). The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T205) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Page 2 of 2

Date 8/26/08

ROUTE 09-0078-00-PV DESCRIPTION On West Bank of Fox River LOGGED BY DM

SECTION 09-0078-00-PV LOCATION On West Bank of Fox River

COUNTY McHenry County DRILLING METHOD Hollow Stem Auger HAMMER TYPE Automatic

Table with columns for Depth (ft), Blows (16"), Blows (30"), and Soil Description. Continuation of boring data from page 1.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer). The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T205) BBS, from 137 (Rev. 8-99)

DESIGNED SSM
CHECKED RCD
DRAWN WJH
CHECKED RCD



SOIL BORING LOGS
STRUCTURE NO. 056-3190

WB CHARLES J. MILLER ROAD BRIDGE
DATE: 7/23/12
SHEET NO. S-36
SECTION 09-00372-00-PW
COUNTY McHENRY
TOTAL SHEETS 252 SHEET NO. 159
CONTRACT NO. 63633
FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT