



3/4" φ stainless steel U-bolt.  
Provide two washers and two hexagon locknuts. (4)  
1 3/16" x 2" slots on 12" φ pipe.  
(4 slots required per pipe)




**DETAIL A**




**SECTION A-A**

As an alternate to bolts, may use galvanized drive-fit caps installed after galvanizing frame.



**SECTION B-B**



**SIDE ELEVATION**

**END ELEVATION**

**TRUSS SUPPORT DETAILS**

(12" φ Pipe-Type III-A Truss)  
\*\* One butt welded joint is allowed only on one post per support frame. If used, weld procedure must be pre-approved by Engineer and joint shall receive 100% RT or UT (tension criteria) at Contractor's expense.

Support Design Loads: See Base Sheet OS-A-1 for design and loading criteria.  
Load combinations checked include deadload plus:  
a) 100% wind normal to sign, 20% parallel to sign  
b) 60% wind normal to sign, 30% parallel to sign

- In lieu of fabricated handhole frame as shown, may cut from 2" plate (rolling direction vertical). All cut faces to be ground to ANSI Roughness of 500 μin or less.
- Galvanizing vent holes of adequate size shall be provided on underside at each end of bracing pipes. Alternately, holes may be provided in wall of pipe column. All vent holes shall be drilled and de-burred, typ.
- Steel pipe, plate, carbon steel handhole covers and rolled sections shall be hot dip galvanized after fabrication. Painting is not permitted. See Base Sheet OS-A-1.
- See General Notes for fasteners.
- Dimensions shown are based on selection criteria in the Sign Structures Manual. Nonstandard applications must have dimensions verified or amended as appropriate.
- "H" based on 15'-0" or actual sign height, whichever is greater.

\* For dynamic message sign installations, provide upper and lower handholes in both legs of each support frame.

Structure Number	Station	Support		Pipe Wall Thickness	H (6)	A
		Left	Right			
4S0901074L100.3	495+10.00	X		0.33"	25.95'	16.80'
4S0901074L100.3	495+10.00		X	0.33"	28.12'	18.97'
4S0901074L100.5	508+15.00	X		0.33"	28.80'	19.65'
4S0901074L100.5	508+15.00		X	0.33"	30.95'	21.80'
*4S0901074L104.3						

\*See ITS plans for existing plans for relocated sign structure.

**benesch**  
engineers · scientists · planners  
Alfred Benesch & Company  
205 North Michigan Avenue, Suite 2400  
Chicago, Illinois 60601  
312-565-0450 Job No. 10056

**OS4-A-8a** 6-1-12

FILE NAME :	USER NAME :	DESIGNED :	REVISD :
xxxxxx_68620_09_fm5.dgn	mbecker	MFB	-
		CHECKED :	REVISD :
		XXX	-
		PLOT SCALE :	REVISD :
		RJT	-
		PLOT DATE :	REVISD :
		7/16/2012	-

**STATE OF ILLINOIS**  
**DEPARTMENT OF TRANSPORTATION**

**OVERHEAD SIGN STRUCTURES - SUPPORT FRAME**  
**FOR TYPE III-A ALUMINUM TRUSS**

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
74	90-[14R(14HB-4,14,14HVB)BR]	TAZEWELL	2433	1629
CONTRACT NO. 68620				

SHEET NO. SS9 OF SS32 SHEETS

ILLINOIS FED. AID PROJECT

x:\10000s\10056\engineer-ing-documents-phase-1\signstructures\phase-1\signstructures\final\xxxxxxx\_68620\_09\_fm5.dgn

7:32:58 AM

7/16/2012