



POSTED SPEED LIMIT	DISTANCE BETWEEN SIGNS "D"
40 MPH or less	200 FT. (60 m)
45-50 MPH	350 FT. (105 m)
55 MPH	500 FT. (150 m)

**GENERAL NOTES**

This special detail is used at any time, any vehicle, equipment, workers or their activities require a stationary, intermittent or continuous moving operation within 15 feet (5 m) of the traffic lane, where the average speed is 1 mph (2 km) or less.

\* Minimum distance "D" is shown in the Advance Warning Sign Spacing Table. If the work is a moving operation, the maximum distance "D" may be extended to 1/2 the length required for one normal working day's operation or 4 miles (6.4 km), whichever is less.

If the work operation does not exceed 60 minutes, traffic control may be in accordance with I.D.O.T. Highway Standard 701301.

**SYMBOLS**

- WORK AREA
- SIGN ON PORTABLE OR PERMANENT SUPPORT
- FLAGGER WITH TRAFFIC CONTROL SIGN WHEN REQUIRED

**MODIFIED STANDARD 701011**

**LakeCounty**  
Division of Transportation

APPROVED BY: A. KHAWAJA  
DATE: 01/20/2003

TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES  
HIGHWAY CONSTRUCTION, CONTRACT MAINTENANCE  
AND UTILITY OPERATIONS

TWO LANE, TWO WAY, OFF-ROAD OPERATIONS  
DAY ONLY OPERATIONS

LC7008

REVISIONS	DATE

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION  
**FAU 2647 - BUTTERFIELD ROAD**  
**MODIFIED STANDARD 701011**

SCALE: NONE  
DATE: 12/2/2005

DRAWN BY: N/A  
CHECKED BY: N/A