



# Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

September 7, 2011

SUBJECT: FAP Route 627 (IL 71)  
Section (I-1) I  
LaSalle County  
Contract No. 66B47  
Item No. 23, September 23, 2011 Letting  
Addendum A

## NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

1. Revised pages 5 & 6 of the Special Provisions.

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

Scott E. Stitt, P.E.  
Acting Engineer of Design and Environment

A handwritten signature in cursive script, appearing to read "Ted B. Walschleger", followed by the letters "P.E." in a smaller font.

By: Ted B. Walschleger, P. E.  
Engineer of Project Management

cc: Eric Therkildsen, Region 2, District 3; Mike Renner; D.Carl Puzey;  
Estimates

TBW:MS:jc

At the beginning of each work day, all permanent "Speed Limit" signs located within the work zone shall be removed or covered. This work shall be coordinated with the lane closure according to Traffic Control and Protection, Standard 701201 by promptly establishing a reduced posted speed zone when the lane closure is put into effect and promptly reinstating the posted speed zone when the lane closure is removed at the end of each work day.

The work zone speed limit signs and end work zone speed limit signs shown in advance of and at the end of the lane closure shall be used whenever the closure is in effect.

Method of Measurement. This work will be measured for payment as follows:

- (a) Contract Quantities. The requirement for use of contract quantities shall be according to Article 202.07(a) of the Standard Specifications.
- (b) Measured Quantities. This work shall be measured for payment per each.

Relocation of the signs or traffic control devices when required will not be measured for payment.

Basis of Payment. This work will be paid for at the contract unit price per each for TRAFFIC CONTROL AND PROTECTION, STANDARD 701201 (SPECIAL) which price shall include all materials, labor and equipment to furnish, install, maintain, relocate and removal of work zone traffic control and protection including all signs, traffic control devices, message boards, speed limit and end work zone speed limit signs.

Any relocation of the signs directed by the Engineer during construction will not be paid for separately, but shall be included in the cost of the Traffic control and Protection Standard 701201 (Special) and no further compensation will be allowed.

Additional flaggers required as directed by the Engineer will be paid for according to the requirements of Article 109.04 of the Standard Specifications.

## **CONCRETE STRUCTURE TO BE CLEANED**

Description. This work consists of cleaning an existing submerged concrete structure including adjacent areas at the ends of the structure and disposal of all removed materials.

### **CONSTRUCTION REQUIREMENTS**

Cleaning. Cleaning shall consist of the complete removal of all native and organic materials and obstructions such as streambed sediment, stone, riprap, gravel, trees, driftwood, shrubs, saplings, bushes, roots, stumps other vegetation and any foreign and objectionable materials from the interior of a submerged structure as well as areas adjacent to the openings of the structure to permit access to the structure interior.

The Contractor shall conduct his cleaning operations from the existing roadway. All vehicles and equipment with driving capabilities shall not be permitted off the paved roadway surface. Placement of the Contractor's non-driving equipment off the roadway surface shall be placed at the direction and with the approval of the Engineer.

Revised 09/07/2011

Placement of any material, equipment or barrier to prevent the free flow of the existing waterway channel shall be strictly prohibited.

After all cleaning operations have been completed the structure shall be in such condition to be capable of conducting a thorough structural inspection of all concrete surfaces including adjacent apertures of a submerged structure.

All areas disturbed by the Contractor's operations shall be restored to its original condition. All labor, materials and equipment used for the purpose of restoring existing slopes or embankments shall not be paid for separately but shall be included in the cost of "Clean Existing Structure" and no additional compensation will be allowed.

Material Disposal. Removed materials shall be disposed of off the right of way according to Article 202.03 of the Standard Specifications.

Method of Measurement. This work will be measured for payment as follows:

- (a) Contract Quantities. The requirement for use of contract quantities shall be according to Article 202.07(a) of the Standard Specifications.
- (b) Measured Quantities. This work will be measured for payment per each.

Basis of Payment. This work shall be paid for at the contract unit price per each for CLEAN EXISTING STRUCTURE which price shall be payment in full to complete this work.

## **STRUCTURAL INSPECTION**

Description. This work shall consist of conducting a thorough structural inspection of an existing submerged concrete structure and providing written and electronic documentation of the condition of all exposed concrete surfaces including adjacent concrete apertures of the existing concrete structure at the location as shown on the plans.

### **CONSTRUCTION REQUIREMENTS**

General. This work shall be according to all Federal, State and Local laws and regulations governing structural inspections and underwater inspections. In addition, the Contractor shall be in accordance with all regulations and requirements of the Association of Diving Contractors International (ADCI), Illinois Department of Transportation (IDOT) and Occupational Safety and Health Administration (OSHA).

The Contractor shall conduct a thorough and complete inspection of all accessible concrete surfaces of the structure including wing walls and adjacent concrete apertures upstream and downstream of the structure.

At the completion of the structural inspection, the Contractor shall submit to the department written and video documentation of the inspection.

Method of Measurement. This work will be measured for payment as follows:

- (a) Contract Quantities. The requirement for use of contract quantities shall be according to Article 202.07(a) of the Standard Specifications.
- (b) Measured Quantities. This work will be measured for payment per Lump Sum.

Revised 09/07/2011