Bid Submittal Guidelines and Checklist

In effort to eliminate confusion and to standardize the bid submission process the Contracts Unit of the Division of Highways has created the following standard guidelines and checklist for submitting bids at all IDOT lettings.

This information has been compiled from questions received from contractors and from inconsistencies noted on bids received at the bid openings. If you have additional questions please refer to the contact information listed below.

Questions: pre-letting up to execution of the contract

| Contractor/Subcontractor pre-qualification | 217-782-3413 |
|---|--------------|
| Small Business, Disadvantaged Business Enterprise (DBE) | 217-785-4611 |
| Contracts, Bids, Letting process or Internet downloads | 217-785-0230 |
| Estimates Unit | 217-785-3483 |

Questions: following contract execution

| Including Subcontractor documentation, payments | 217-782-3413 |
|---|--------------|
| Railroad Insurance | 217-785-0275 |

Standard Guidelines for Submitting Bids

- All pages should be single sided.
- Use the Cover Page that is provided in the Bid Proposal (posted on the IDOT Web Site) as the first page of your submitted bid. This page has the Item number in the upper left-hand corner and lines provided for your company name and address in the upper right-hand corner.
- Do not use report covers, presentation folders or special bindings and do not staple multiple times on left side like a book. Use only 1 staple in the upper left hand corner. Make sure all elements of your bid are stapled together including the bid bond or guaranty check (if required).
- Do not include any certificates of eligibility, your authorization to bid, Addendum Letters or affidavit of availability.
- Do not include the Subcontractor Documentation with your bid (pages i iii and pages a g). This documentation is submitted only if you are awarded the contract.
- Use the envelope cover sheet (provided with the proposal) as the cover for the proposal envelope.
- Do not rely on overnight services to deliver your proposal prior to 10 AM on letting day. It will not be accepted if it is delivered after 10 AM.
- Do not submit your Substance Abuse Prevention Program (SAPP) with your bid. This form is to be submitted to the district engineer at the pre-construction conference if you are awarded the contract.

The Bid Letting is now available in streaming Audio/Video from the IDOT Web Site. A link to the stream will be placed on the main page of the current letting on the day of the Letting. The stream will not begin until 10 AM. The actual reading of the bids does not begin until approximately 10:20 AM.

Following the Letting, the As-Read Tabulation of Bids will be posted by the end of the day. You will find the link on the main page of the current letting.

If you are the apparent low-bidder, there is nothing further for you to do until the contract is officially awarded to your company. If your bid is not within the engineer's estimate it does not mean that the bid will be rejected. The award or rejection of the bids that are not within the engineer's estimate will be determined at the Awards Meeting. The Awards Meeting is usually held approximately two weeks after the letting. The responsive and responsible low-bidders of those contracts recommended for award will be notified by mail.

Use the following checklist to assure completeness and the correct order in assembling your bid

| Cover page followed by the Pay Items. If you are using special software or a CBID to generate your schedule of prices, <u>do not include the blank schedule of prices.</u> |
|---|
| Page 4 (Item 9) – Check "Yes" if you will use a subcontractor. Include the subcontractor name, address and the dollar amount (if over \$25,000). If you will use subcontractor(s) but are uncertain who or the dollar amount; check "Yes" but leave the lines blank. |
| After page 4, insert your Cost Adjustments for Steel, Bituminous and Fuel (if applicable), and your State Board of Elections Business Registration (if applicable). |
| Page 10 (Paragraph J) – Check Yes or No whether your company has any business in Iran. |
| Page 10 (Paragraph K) – list the Union Local Name and number or certified training programs that you have in place. Do not include certificates with your bid. Keep the certificates in your office in case they are requested by IDOT. |
| Page 11 (Paragraph L) Insert a copy of your State Board of Elections Business Registration after page 4 of the bid proposal. Only include the page that has the date stamp on it. Do not include any other certificates or forms showing that you are an Illinois business. |
| Page 11 (Paragraph M) – Indicate if your company has hired a lobbyist in connection with the job for which you are submitting the bid proposal. |
| Page 12 (Paragraph C) – This is a work sheet to determine if a completed Form A is required. It is not part of the form and you do not need to make copies for each Form A that is filled out. |
| Pages 14-17 (Form A) – One Form A (4 pages) is required for each applicable person in your company. Copies of the Forms can be used and only need to be changed when the financial information changes. The certification signature and date must be original for each letting. Do not staple the forms together. |
| If you are not required to submit Form A; complete the first section (page 14) with your company information and then sign and date the Not Applicable statement on page 17. |
| Page 18 (Form B) This Form is for disclosing active and pending contracts with agencies <u>other than</u> IDOT. The Department already has your company Affidavit of Availability (BC 57) on file showing all current and pending IDOT contracts. Do not attach or reference the BC 57 on Form B. If you check YES to having other current or pending contracts outside of IDOT; list the agency followed by the contract number on the form or reference an additional information sheet and insert it after the form. |
| Page 20 (Workforce Projection) – Be sure to include the Duration of the Project. It is acceptable to use the phrase "Per Contract Specifications". |
| Bid Bond – Submit your bid bond using the current Bid Bond Form provided in the proposal package. The Power of Attorney page should be stapled to the Bid Bond. If you are using an electronic bond, include your bid bond number on the form and attach the Proof of Insurance printed from the Surety 2000 Web Site. |
| Disadvantaged Business Utilization plan and/or Good Faith Effort – The last item in your bid should be the DBE Utilization Plan (SBE 2026), DBE Participation Statement (SBE 2025) and supporting paperwork. If you have documentation for a Good Faith Effort, it should follow the SBE Forms |

If you plan to submit a bid directly to the Department of Transportation

PREQUALIFICATION

Any contractor who desires to become pre-qualified to bid on work advertised by IDOT must submit the properly completed pre-qualification forms to the Bureau of Construction no later that 4:30 p.m. prevailing time twenty-one days prior to the letting of interest. This pre-qualification requirement applies to first time contractors, contractors renewing expired ratings, contractors maintaining continuous pre-qualification or contractors requesting revised ratings. To be eligible to bid, existing pre-qualification ratings must be effective through the date of letting.

REQUESTS FOR AUTHORIZATION TO BID

Contractors wanting to bid on items included in a particular letting must submit the properly completed "Request for Authorization to Bid/or Not For Bid Status" (BDE 124) and the ORIGINAL "Affidavit of Availability" (BC 57) to the proper office no later than 4:30 p.m. prevailing time, three (3) days prior to the letting date. This does not apply to Small Business Set-Asides.

WHO CAN BID?

Bids will be accepted from only those companies that request and receive written **Authorization to Bid** from IDOT's Central Bureau of Construction. This does not apply to Small Business Set-Asides.

WHAT CONSTITUTES WRITTEN AUTHORIZATION TO BID?: When a prospective prime bidder submits a "Request for Authorization to Bid/or Not For Bid Status" (BDE 124) he/she must indicate at that time which items are being requested For Bidding purposes. Only those items requested For Bidding will be analyzed. After the request has been analyzed, the bidder will be issued an Authorization to Bid or Not for Bid Report, approved by the Central Bureau of Construction that indicates which items have been approved For Bidding. If Authorization to Bid cannot be approved, the Authorization to Bid or Not for Bid Report will indicate the reason for denial.

ABOUT AUTHORIZATION TO BID: Firms that have not received an authorization form within a reasonable time of complete and correct original document submittal should contact the department as to status. This is critical in the week before the letting. These documents must be received three days before the letting date. Firms unsure as to authorization status should call the Prequalification Section of the Bureau of Construction at the number listed at the end of these instructions.

ADDENDA AND REVISIONS: It is the contractor's responsibility to determine which, if any, addenda or revisions pertain to any project they may be bidding. Failure to incorporate all relevant addenda or revisions may cause the bid to be declared unacceptable.

Each addendum will be placed with the contract number. Addenda and revisions will also be placed on the Addendum/Revision Checklist and each subscription service subscriber will be notified by e-mail of each addendum and revision issued.

The Internet is the Department's primary way of doing business. The subscription server e-mails are an added courtesy the Department provides. It is suggested that bidders check IDOT's website at http://www.dot.il.gov/desenv/delett.html before submitting final bid information.

IDOT IS NOT RESPONSIBLE FOR ANY E-MAIL FAILURES.

Addenda Questions may be directed to the Plans and Contracts Office at (217)782-7806 or D&Econtracts@dot.il.gov

Technical Questions about downloading these files may be directed to Tim Garman (217)524-1642 or Timothy.Garman@illinois.gov.

WHAT MUST BE INCLUDED WHEN BIDS ARE SUBMITTED?: Bidders need not return the entire proposal when bids are submitted. That portion of the proposal that must be returned includes the following:

- 1. All documents from the Proposal Cover Sheet through the Proposal Bid Bond
- 2. Other special documentation and/or information that may be required by the contract special provisions

All proposal documents, including Proposal Guaranty Checks or Proposal Bid Bonds, should be stapled together to prevent loss when bids are processed by IDOT personnel.

ABOUT SUBMITTING BIDS: It is recommended that bidders deliver bids in person to insure they arrive at the proper location prior to the time specified for the receipt of bids. Any bid received at the place of letting after the time specified will not be accepted.

WHO SHOULD BE CALLED IF ASSISTANCE IS NEEDED?

| Questions Regarding | Call |
|--|--------------|
| Prequalification and/or Authorization to Bid | 217/782-3413 |
| Preparation and submittal of bids | 217/782-7806 |
| Mailing of plans and proposals | 217/782-7806 |

ADDENDUMS AND REVISIONS TO THE PROPOSAL FORMS

Bidders should verify that they have received and incorporated any addendum and/or revision prior to submitting their bid. Failure by the bidder to include an addendum or revision could result in a bid being rejected as irregular.

NEED NOT RETURN THE ENTIRE PROPOSAI (See instructions inside front cover)

BIDDERS

| Proposal Submitted By | |
|-----------------------|--|
| Name | |
| Address | |
| City | |

Letting September 23, 2011

NOTICE TO PROSPECTIVE BIDDERS

This proposal can be used for bidding purposes by only those companies that request and receive written AUTHORIZATION TO BID from IDOT's Central Bureau of Construction. This does not apply to Small Business Set-Asides.

(SEE INSTRUCTIONS ON THE INSIDE OF COVER)

Notice to Bidders, Specifications, Proposal, Contract and Contract Bond



Springfield, Illinois 62764

Contract No. 93554
ADAMS County
Section 08-00307-00-TL (Quincy)
Route FAU 7807 (Maine Street)
Project M-SRTS-4008(089)
District 6 Construction Funds

| PLEASE MARK THE APPROPRIATE BOX BELOW: | |
|--|--|
| ☐ A <u>Bid Bond</u> is included. | |
| ☐ A <u>Cashier's Check</u> or a <u>Certified Check</u> is included | |
| | |

| Prepared by | F |
|---------------------------------------|-----------|
| Checked by | - |
| (Printed by authority of the State of | Illinois) |

INSTRUCTIONS

ABOUT IDOT PROPOSALS: All proposals issued by IDOT are potential bidding proposals. Each proposal contains all Certifications and Affidavits, a Proposal Signature Sheet and a Proposal Bid Bond. In addition, this proposal contains new statutory requirements applicable to the use of subcontractors and, in particular, includes the <u>State Required Ethical Standards Governing Subcontractors</u> to be signed and incorporated into all subcontracts.

WHO CAN BID?: Bids will be accepted from only those companies that request and receive written Authorization to Bid from IDOT's Central Bureau of Construction. To request authorization, a potential bidder <u>must complete and submit Part B of the Request for Authorization to Bid/or Not For Bid Status form (BDE 124) and submit an original Affidavit of Availability (BC 57).</u> This does not apply to Small Business Set-Asides.

WHAT CONSTITUTES WRITTEN AUTHORIZATION TO BID?: When a prospective prime bidder submits a "Authorization to Bid or Not for Bid" form, he/she must indicate at that time which items are being requested For Bidding purposes. Only those items requested For Bidding will be analyzed. After the request has been analyzed, the bidder will be issued a Authorization to Bid or Not for Bid Report, approved by the Central Bureau of Construction, that indicates which items have been approved For Bidding. If Authorization to Bid cannot be approved, the Authorization to Bid or Not for Bid Report will indicate the reason for denial. If a contractor has requested to bid but has not received a Authorization to Bid or Not for Bid Report, they should contact the Central Bureau of Construction in advance of the letting date.

WHAT MUST BE INCLUDED WHEN BIDS ARE SUBMITTED?: Bidders need not return the entire proposal when bids are submitted. That portion of the proposal that must be returned includes the following:

- 1. All documents from the Proposal Cover Sheet through the Proposal Bid Bond
- 2. Other special documentation and/or information that may be required by the contract special provisions

All proposal documents, including Proposal Guaranty Checks or Proposal Bid Bonds, should be stapled together to prevent loss when bids are processed by IDOT personnel.

ABOUT SUBMITTING BIDS: It is recommended that bidders deliver bids in person to insure they arrive at the proper location prior to the time specified for the receipt of bids. Any bid received at the place of letting after the time specified will not be accepted.

WHO SHOULD BE CALLED IF ASSISTANCE IS NEEDED?

Questions Regarding Call

Prequalification and/or Authorization to Bid 217/782-3413 Preparation and submittal of bids 217/782-7806



PROPOSAL

TO THE DEPARTMENT OF TRANSPORTATION

| 1. | Proposal of |
|----|--|
| Та | xpayer Identification Number (Mandatory) for the improvement identified and advertised for bids in the Invitation for Bids as: |
| | Contract No. 93554 ADAMS County Section 08-00307-00-TL (Quincy) Project M-SRTS-4008(089) Route FAU 7807 (Maine Street) District 6 Construction Funds |

Reconstruct the intersection of Maine Street at 33rd Street to include sidewalks and traffic signal replacement and the resurfacing of Maine Street from 30th Street to 36th Street in the city of Quincy.

2. The undersigned bidder will furnish all labor, material and equipment to complete the above described project in a good and workmanlike manner as provided in the contract documents provided by the Department of Transportation. This proposal will become part of the contract and the terms and conditions contained in the contract documents shall govern performance and payments.

- 3. ASSURANCE OF EXAMINATION AND INSPECTION/WAIVER. The undersigned further declares that he/she has carefully examined the proposal, plans, specifications, addenda form of contract and contract bond, and special provisions, and that he/she has inspected in detail the site of the proposed work, and that he/she has familiarized themselves with all of the local conditions affecting the contract and the detailed requirements of construction, and understands that in making this proposal he/she waives all right to plead any misunderstanding regarding the same.
- 4. **EXECUTION OF CONTRACT AND CONTRACT BOND.** The undersigned further agrees to execute a contract for this work and present the same to the department within fifteen (15) days after the contract has been mailed to him/her. The undersigned further agrees that he/she and his/her surety will execute and present within fifteen (15) days after the contract has been mailed to him/her contract bond satisfactory to and in the form prescribed by the Department of Transportation, in the penal sum of the full amount of the contract, guaranteeing the faithful performance of the work in accordance with the terms of the contract.
- 5. **PROPOSAL GUARANTY.** Accompanying this proposal is either a bid bond on the department form, executed by a corporate surety company satisfactory to the department, or a proposal guaranty check consisting of a bank cashier's check or a properly certified check for not less than 5 per cent of the amount bid or for the amount specified in the following schedule:

| <u>A</u> | mount o | of Bid | Proposal <u>Guaranty</u> | <u>Am</u> | ount c | Proposal <u>of Bid</u> <u>Guaranty</u> |
|-------------|---------|-------------|-----------------------------|--------------|--------|---|
| Up to | | \$5,000 | \$150 | \$2,000,000 | to | \$3,000,000 \$100,000 |
| \$5,000 | to | \$10,000 | \$300 | \$3,000,000 | to | \$5,000,000 \$150,000 |
| \$10,000 | to | \$50,000 | \$1,000 | \$5,000,000 | to | \$7,500,000 \$250,000 |
| \$50,000 | to | \$100,000 | \$3,000 | \$7,500,000 | to | \$10,000,000 \$400,000 |
| \$100,000 | to | \$150,000 | \$5,000 | \$10,000,000 | to | \$15,000,000 \$500,000 |
| \$150,000 | to | \$250,000 | \$7,500 | \$15,000,000 | to | \$20,000,000 \$600,000 |
| \$250,000 | to | \$500,000 | \$12,500 | \$20,000,000 | to | \$25,000,000\$700,000 |
| \$500,000 | to | \$1,000,000 | \$25,000 | \$25,000,000 | to | \$30,000,000 \$800,000 |
| \$1,000,000 | to | \$1,500,000 | \$50,000 | \$30,000,000 | to | \$35,000,000 \$900,000 |
| \$1,500,000 | to | \$2,000,000 | \$75,000 | over | | \$35,000,000 \$1,000,000 |

Bank cashier's checks or properly certified checks accompanying proposals shall be made payable to the Treasurer, State of Illinois, when the state is awarding authority; the county treasurer, when a county is the awarding authority; or the city, village, or town treasurer, when a city, village, or town is the awarding authority.

If a combination bid is submitted, the proposal guaranties which accompany the individual proposals making up the combination will be considered as also covering the combination bid.

| The amount of the proposal guaranty check is | \$(|). If this proposal is accepted |
|--|--|-------------------------------------|
| and the undersigned shall fail to execute a contract bond as required herein, it | is hereby agreed that the amount of th | e proposal guaranty shall become |
| he property of the State of Illinois, and shall be considered as payment of dam | nages due to delay and other causes su | iffered by the State because of the |
| ailure to execute said contract and contract bond; otherwise, the bid bond sh | nall become void or the proposal guara | nty check shall be returned to the |
| undersigned. | | |

County ___

Mark the proposal cover sheet as to the type of proposal guaranty submitted.

| | | | RETURN WITH BID | |
|----|--|--|--|---|
| 6. | combination, combination by proportion to the combination to the combination to the combination, the combination is a combination of the co | he/she oid spe the bid | S. The undersigned further agrees that if awarded the contract will perform the work in accordance with the requirements of ecified in the schedule below, and that the combination bid submitted for the same. If an error is found to exist in the gross a combination, the combination bid shall be corrected as provide | each individual proposal comprising th hall be prorated against each section is s sum bid for one or more of the individua |
| | | | ombination bid is submitted, the schedule below must be cong the combination. | ompleted in each proposal |
| | | | e bids are submitted for one or more of the sections compri ion bid must be submitted for each alternate. | sing the combination, a |
| | | | Schedule of Combination Bids | |
| Со | mbination | | | Combination Bid |
| | No. | | Sections Included in Combination | Dollars Cents |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| 7. | schedule of pr all extensions schedule are a is an error in t will be made of The schedule | rices for and stands approxime extending for a displaying the control of the cont | ICES. The undersigned bidder submits herewith, in accordary the items of work for which bids are sought. The unit prices is summations have been made. The bidder understands that imate and are provided for the purpose of obtaining a gross surpusion of the unit prices, the unit prices shall govern. Payment to ractual quantities of work performed and accepted or materials tities of work to be done and materials to be furnished may be in the contract. | bid are in U.S. dollars and cents, and the quantities appearing in the bid on for the comparison of bids. If there to the contractor awarded the contract of furnished according to the contract. |
| 8. | provides that | a pers | D BUSINESS IN ILLINOIS. Section 20-43 of the Illinois Processon (other than an individual acting as a sole proprietor) must of Illinois prior to submitting the bid. | |
| 9. | The services | of a si | ubcontractor will or may be used. | |
| | Check bo Check bo | | es 🗌 o 🔲 | |
| | | | ontractors with subcontracts with an annual value of more than stress, and the dollar allocation for each subcontractor. | \$25,000, the contract shall include |
| | | | | |

10. **EXECUTION OF CONTRACT**: The Department of Transportation will, in accordance with the rules governing Department procurements, execute the contract and shall be the sole entity having the authority to accept performance and make payments under the contract. Execution of the contract by the Chief Procurement Officer or the State Purchasing Officer is for approval of the procurement process and execution of the contract by the Department. Neither the Chief Procurement Officer nor the State Purchasing Officer shall be responsible for administration of the contract or determinations respecting performance or payment there under except as otherwise permitted in the Illinois Procurement Code.

STATE JOB #- C-40-084-09 PPS NBR - 6-10504-0000

ILLINOIS DEPARTMENT OF TRANSPORTATION SCHEDULE OF PRICES CONTRACT NUMBER - 93554

| - II - I | 32.000 X | UNIT | REE REMOV OV | 010021 |
|--|----------|---------------------|---|-------------------|
| - 11 - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | 6.00 | FOOT | AINT CURB | 03620 |
| 11 | 1.000 | EAC | DEO VEH DET SYS | 0033072 |
| | 1.000 | L SU | ONSTRUCTION LAYOUT | 001379 |
| | 8 1 | | PED PUSH-BUTTON SPL | 8800101 |
| — 11 ————————————————————————————————— | 24.000 | FOOT | URETH PAVT MK LINE | 7800680 |
| | 198.000 | F00 | URETH PAVT MK LINE 12 | 7800650 |
| - II - | 228.000 | FO | URETH PAVT MK LINE | 7800620 |
| | 83.200 | ו דרו | URETHANE PM LT-SY | 7800605 |
| — II — | 1.00 | L SUM | TC-PROT 701701 SPL | 7010234 |
| 1 | 45.000 | ו דד ו | LK FENCE REM & RE | 64030 |
| | 109.000 | . 0 : | ONC CURB TB SPL | 606100 |
| - (1 | 0.700 | ACR | EDING CL 1 SPL | 250090 |
| | 1.000 | EAC | M VEH SIGNL CONT SYS | |
| - II | Ō | SQ F | ABLE WRNING SPL | X00772 |
| UNIT PRICE TOTAL PRICE DOLLARS CENTS DOLLARS CTS | QUANTITY | MEASURE | PAY ITEM DESCRIPTION | ITEM NUMBER |
| PROJECT NUMBER ROUTE S-4008/089/000 FAU 7807 | M-SR1 | ION NUMBER (QUINCY) | VAME CODE DIST SECT SECT O8-00307-00-TL | COUNTY N ADAMS |

ILLINOIS DEPARTMENT OF TRANSPORTATION EC SCHEDULE OF PRICES RU CONTRACT NUMBER - 93554

| | 148.00 | Q | DETECTABLE | 10080 |
|---|----------|-----------------|----------------------|-----------------|
| - 11 - | 68.000 | | PC CONC SIDEWALK 4 | 10010 |
| - 11 | 2.000 | SQ Y | PCC DRIVEWAY PAVT 8 | 30040 |
| - 11 | 63.000 | SQ Y | PCC DRIVEWAY PAVT 6 | 300200 |
| - 11 - 1 1 - 13 - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | 982.000 | TON | P HMA SC "D" N50 | 303E |
| 11 | 83.000 | TON | MA BC IL-19.0 N50 | 503080 |
| - 11 | 37.000 | SQ YD | TEMPORARY RAMP | 500990 |
| - II | 1.000 | i Гт 1 | CONSTRUC TEST STRI | 600895 |
| - 11 - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | 23.400 | TON | AGG PR CT | 600300 |
| - II | .800 | TON | BIT MATLS PR CT | 00200 |
| — II — I | 796.000 | SQ YD | SUB GRAN MAT A 12 | 100910 |
| II | 646.000 | SQ YD | SUB GRAN MAT A 4 | 10030 |
| 11 — | 100.000 | OUND | EMP EROS CONTR | 0002 |
| - II | 0.700 | ACR | LCH METHOD 1 | 10010 |
| - 11 | 00 | ·~ | H EXCAVATION | 20010 |
| UNIT PRICE TOTAL PRICE DOLLARS CENTS DOLLARS CTS | QUANTITY | UNIT OF MEASURE | PAY ITEM DESCRIPTION | I TEM NUMBER |

ILLINOIS DEPARTMENT OF TRANSPORTATION SCHEDULE OF PRICES CONTRACT NUMBER - 93554

| | | 00 | SUM | TR CONT & PROT 701701 |)2635 |
|--|---------------------|-----------|--------------------|-----------------------|-----------------|
| | | 00 | L SUM | TR CONT & PROT 70160 | 2625 |
| 11 1 1 1 1 1 1 1 1 1 | | 00 | L SUM | TR CONT & PROT 701502 |)2622 |
| - II | | 00 | L SUM | MOBILIZATION | 00100 |
| 11 | [| 1,102.0 | FOOT | COMB CC&G TB6.12 | 03800 |
| 11 11 11 11 11 11 11 11 11 11 11 11 11 | | 2.000 | AC | MAN ADJUST | 55500 |
| - II - 1 | | 3.000 | EACH | FIRE HYDNT REM & REPL | 00510 |
| | | 3.000 | EACH | WATER VALVES ADJUST | 09210 |
| - II | | 50.00 | SQ YD | CL D PATCH T2 8 | 01741 |
| 11 - | | 30.000 | SQ YD | CL D PATCH T1 8 | 01737 |
| | | 6,355.000 | SQ FT | SIDEWALK REM | 00600 |
| 11 - 11 - 11 - 11 - 11 - 11 - 11 - 11 | | 1,114.00 | FOOT | COMB CURB GUTTER REM | 00500 |
| | | 19.000 | FOOT | CURB REM | 0030 |
| | | 655.000 | SQ YD | IVE PAVEMENT REM | 0020 |
| - 11 | | .000 | Q . Y | MA SURF REM 1 | 00 |
| ICE TOTAL PRICE CENTS DOLLARS CTS | UNIT PRI DOLLARS | QUANTITY | UNIT OF MEASURE | PAY ITEM DESCRIPTION | I TEM NUMBER |

ILLINOIS DEPARTMENT OF TRANSPORTATION SCHEDULE OF PRICES CONTRACT NUMBER - 93554 ECMS002 DTGECM03 ECMR003 PAGE RUN DATE - 08/04/11 RUN TIME - 190105

| - II | : -x- | SQ FT | PAVT MARKING REMOVAL | 100 |
|--|-------------|----------------------|-----------------------|-----------------|
| - 11 | . 000 X | F00 | REF PL PM TB INL L2 | 8004280 |
| - II - I | 954.000 X | FOOT | PREF PL PM TB INL L12 | 8004250 |
| II | 436.800 X | FT | PREF PL PM TB INL L&S | 8004200 |
| - 11 | 671.000 X | FOOT | THPL PVT MK LINE 6 | 8000400 |
| - II - I | 5,901.000 X | FOOT | THPL PVT MK LINE 5. | 00300 |
| - II - | 47.500 X | SQ FT | SIGN PANEL T2 | 2000200 |
| - II - I | ,475.000 X | SQ F | WORK ZONE PAVT MK RE | 0301000 |
| - 11 | 217.000 X | FOOT | TEMP PVT MK LINE 24 | 0300280 |
| - II - | 1,152.000 X | FOOT | TEMP PVT MK LINE 12 | 0300260 |
| | 671.000 X | FOOT | TEMP PVT MK LINE 6 | 0300240 |
| - 11 | 6,129.000 X | F00T | TEMP PVT MK LINE 5 | 0300230 |
| - II | 520.000 X | SQ FT | TEMP PVT MK LTR & SYM | 30021 |
| - 13 | 1,440.000 X | FOOT | SHORT TERM PAVT MKING | 0300100 |
| - 11 | 1.000 X | US | TR CONT & PROT 701801 | 01026 |
| UNIT PRICE TOTAL PRICE DOLLARS CENTS DOLLARS CTS | QUANTITY | UNIT OF MEASURE | PAY ITEM DESCRIPTION | I TEM NUMBER |

FAU 7807 08-00307-00-TL (QUINCY) ADAMS

ILLINOIS DEPARTMENT OF TRANSPORTATION SCHEDULE OF PRICES CONTRACT NUMBER - 93554

ISPORTATION ECMS002 DTGECM03 ECMR003 PAGE RUN DATE - 08/04/11 8554 RUN TIME - 190105

| S | | NIT O | | UNIT PRIC | Œ | TOTAL PRICE | |
|----------|----------------------|---------|-----------|----------------------------------|---|---|-------------|
| NUMBER | PAY ITEM DESCRIPTION | MEASURE | QUANTITY | DOLLARS | CENTS _ | | CTS |
| 00100 | ELECT SERV INSTALL | ΕA | 1.000 X | | - 11 | | |
| 10004 | CON T 1 1/4 GALVS | F00 | 21.000 | 1 | - 11 - 1 | ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! | 1 1 1 |
| 1000500 | ON T 1 1/2 GALVS | 00 | 000 | | - - | | 1 |
| 1012600 | CON T 2 PVC | FOOT | 84.000 | | 1 1 — | 1 1 1 1 1 1 1 | ı |
| 1270 | ON T 2 1/2 PVC | F00 | 000 | ! ! ! ! ! ! ! | - 11 — | 1 1 1 1 1 1 | 1 1 |
| 1012800 | CON T 3 PVC | F00T | 45.000 | ! ! ! ! ! ! ! | - - | ! 1 1 1 1 1 1 | - 1 |
| 101290 | CON T 3 1/2 PVC | FOOT | 9.000 X | 1 1 1 1 1 1 1 | 1 - - - | 1 1 1 1 | - 1 |
| 1013000 | CON T 4 PVC | FOOT | 88.000 | 1 1 1 1 1 1 1 | 1 1 1 — II — | | 1 |
| 1013100 | CON T 5 PVC | FOOT | 52.000 | | : : : : - :: | 1 1 1 1 1 1 | 1 |
| 1013200 | CON T 6 PVC | 001 | 47.000 | | 1 1 1 1 - 11 - | | 1 |
| 1021380 | ON P 5 PVC | FOOT | 62.000 | | 1 1 1 - 11 - | | t |
| 1021390 | ON P 6 PVC | 00 | 46.000 | | - | 1 1 1 1 1 1 | ı |
| 1400100 | HANDHOLE | AC | 4.000 | | - II - | ; ; ; ; ; ; ; ; | - 1 |
| 14003 | BL HANDHOLE | ACH | 1.000 | 1 1 1 1 1 1 | ! ! ! | 1 1 1 1 1 1 1 | 1 |
| 1700315 | C C EPR RHW 3-1C 1 | FOOT | 697.000 X | 1 | : : : : : : : : : | 1 2 3 1 1 | |
| | | | | | <u> </u> | | |

ILLINOIS DEPARTMENT OF TRANSPORTATION SCHEDULE OF PRICES CONTRACT NUMBER - 93554

| II III | 612.000 X | FOOT | ELCBL C EGRDC 6 | 0190 |
|---|-----------|------------------------|-----------------------|-----------------|
| - II - | 79.000 | 00 | ELCBL C SERV 6 3 | 73018 |
| - H | 9.000 | 00 | ELCBL C COMM 18 3 | 730170 |
| - 11 - | 683.000 | F00 | ELCBL C COMM 14 3PR | 730158 |
| - II - | 00.000 | F00 | ELCBL C SIGNAL 14 7C | 730125 |
| - 11 | 1,857.000 | FOOT | ELCBL C SIGNAL 14 5C | 7301245 |
| II | 2,256.000 | FOOT | ELCBL C SIGNAL 14 3 | 730 |
| - 11 | 5.000 | FOOT | L C SIGNAL 12 9C | 7301165 |
| - II - | 1.000 | EACH | TRANSCEIVER | 5900100 |
| | 0 1 | ו 🗩 ו | FAC T4 CAB | 5700200 |
| - 11 | 1.000 | EACH | REM POLE FDN | 4200804 |
| - II | 1.000 | EACH | REM LT UNIT SALV | 4200500 |
| - II | 0 | EACH | LT CONT PEDM 240V 100 | 2500335 |
| - II - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | | EACH | LUM SV MM PC 250W | 10425 |
| - 11 | 420.000 X | F.00 | & BKFIL F ELEC | 81900200 |
| UNIT PRICE TOTAL PRICE DOLLARS CENTS DOLLARS CTS | QUANTITY | UNIT OF MEASURE | PAY ITEM DESCRIPTION | I TEM NUMBER |

FAU 7807 08-00307-00-TL (QUINCY) ADAMS

ILLINOIS DEPARTMENT OF TRANSPORTATION SCHEDULE OF PRICES CONTRACT NUMBER - 93554

| - II - | 20.000 X | C | S BACKPLATE | 20010 |
|--|--------------|-----------------|-----------------------|-----------------|
| H - H - H - H - H - H - H - H - H - H - | 8.000 X | EACH | ED SH P LED 1F BM C | 1028 |
| | 0 | EAC | SH P LED 2F 1-3 1-5BM | 260 |
| | 00 - X- | EAC | SH P LED 1F 5S MAW | 040160 |
| i | 4.000 X | EACH | SH P LED 1F 3S MAM | 040090 |
| | | EACH | SH P LED 1F 3S BM | 04007 |
| II | -×- | FOOT | CONC FDN TY E 36D | 800415 |
| | 3.000 | 00 | CONC FDN TY C | 800150 |
| | 00 | F00 | CONC FDN TY A | |
| - it - | 00 - X- | EACH | STL COMB MAA&P 44 | 7702950 |
| | 00 | EACH | STL COMB MAA&P 34 | 770290 |
| - 11 | 1.000 | EAC | MAA & P 40 | 770024 |
| - 11 | 1.000 | EAC | MAA & P 36 | 0022 |
| - 11 - | 0 | AC | S POST A 1 | 750270 |
| 11 | .000 | C | S POST A 1 | 50268 |
| UNIT PRICE TOTAL PRICE DOLLARS CENTS DOLLARS CTS | QUANTITY - | UNIT OF MEASURE | PAY ITEM DESCRIPTION | I TEM NUMBER |

ECMS002 DTGECM03 ECMR003 PAGE RUN DATE - 08/04/11 RUN TIME - 190105

ω

| | | | | | · | |
|-------------------------|---------------|--------|-----------|---------|----------------------|----------|
| | | | 6.000 X | EACH | | 89502385 |
| | | ! > | 3.000 X | EACH | EX | 89502380 |
| | ! !! | - ×- | 1.000 X | EACH | EXT | 89502375 |
| | - II - | | 543.000 X | FOOT | REM ELCBL FR CON | 89502300 |
| TOTAL PRICE DOLLARS CTS | DOLLARS CENTS | DOLLA | QUANTITY | MEASURE | PAY ITEM DESCRIPTION | NUMBER |

(C)

- EACH PAY ITEM SHOULD HAVE A UNIT PRICE AND A TOTAL PRICE.
- THE UNIT PRICE SHALL GOVERN IF NO TOTAL PRICE IS SHOWN OR IF THERE IS A DISCREPANCY BETWEEN THE PRODUCT OF THE UNIT PRICE MULTIPLIED BY THE QUANTITY.
- IF A UNIT PRICE IS OMITTED, THE TOTAL PRICE WILL BE DIVIDED BY THE QUANTITY IN ORDER TO ESTABLISH A UNIT PRICE.
- A BID MAY BE DECLARED UNACCEPTABLE IF NEITHER A UNIT PRICE NOR A TOTAL PRICE IS SHOWN.

STATE REQUIRED ETHICAL STANDARDS GOVERNING CONTRACT PROCUREMENT: ASSURANCES, CERTIFICATIONS AND DISCLOSURES

I. GENERAL

- **A.** Article 50 of the Illinois Procurement Code establishes the duty of all State chief procurement officers, State purchasing officers, and their designees to maximize the value of the expenditure of public moneys in procuring goods, services, and contracts for the State of Illinois and to act in a manner that maintains the integrity and public trust of State government. In discharging this duty, they are charged by law to use all available information, reasonable efforts, and reasonable actions to protect, safeguard, and maintain the procurement process of the State of Illinois.
- **B.** In order to comply with the provisions of Article 50 and to carry out the duty established therein, all bidders are to adhere to ethical standards established for the procurement process, and to make such assurances, disclosures and certifications required by law. Except as otherwise required in subsection III, paragraphs J-M, by execution of the Proposal Signature Sheet, the bidder indicates that each of the mandated assurances have been read and understood, that each certification is made and understood, and that each disclosure requirement has been understood and completed.
- **C.** In addition to all other remedies provided by law, failure to comply with any assurance, failure to make any disclosure or the making of a false certification shall be grounds for the chief procurement officer to void the contract, or subcontract, and may result in the suspension or debarment of the bidder or subcontractor.

II. ASSURANCES

The assurances hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder.

A. Conflicts of Interest

1. The Illinois Procurement Code provides in pertinent part:

Section 50-13. Conflicts of Interest.

- (a) Prohibition. It is unlawful for any person holding an elective office in this State, holding a seat in the General Assembly, or appointed to or employed in any of the offices or agencies of state government and who receives compensation for such employment in excess of 60% of the salary of the Governor of the State of Illinois, or who is an officer or employee of the Capital Development Board or the Illinois Toll Highway Authority, or who is the spouse or minor child of any such person to have or acquire any contract, or any direct pecuniary interest in any contract therein, whether for stationery, printing, paper, or any services, materials, or supplies, that will be wholly or partially satisfied by the payment of funds appropriated by the General Assembly of the State of Illinois or in any contract of the Capital Development Board or the Illinois Toll Highway authority.
- (b) Interests. It is unlawful for any firm, partnership, association or corporation, in which any person listed in subsection (a) is entitled to receive (i) more than 7 1/2% of the total distributable income or (ii) an amount in excess of the salary of the Governor, to have or acquire any such contract or direct pecuniary interest therein.
- (c) Combined interests. It is unlawful for any firm, partnership, association, or corporation, in which any person listed in subsection (a) together with his or her spouse or minor children is entitled to receive (i) more than 15%, in the aggregate, of the total distributable income or (ii) an amount in excess of 2 times the salary of the Governor, to have or acquire any such contract or direct pecuniary interest therein.
- (d) Securities. Nothing in this Section invalidates the provisions of any bond or other security previously offered or to be offered for sale or sold by or for the State of Illinois.
- (e) Prior interests. This Section does not affect the validity of any contract made between the State and an officer or employee of the State or member of the General Assembly, his or her spouse, minor child or any combination of those persons if that contract was in existence before his or her election or employment as an officer, member, or employee. The contract is voidable, however, if it cannot be completed within 365 days after the officer, member, or employee takes office or is employed.

The current salary of the Governor is \$177,412.00. Sixty percent of the salary is \$106,447.20.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-13, or that an effective exemption has been issued by the Board of Ethics to any individual subject to the Section 50-13 prohibitions pursuant to the provisions of Section 50-20 of the Code and Executive Order Number 3 (1998). Information concerning the exemption process is available from the Department upon request.

B. Negotiations

1. The Illinois Procurement Code provides in pertinent part:

Section 50-15. Negotiations.

- (a) It is unlawful for any person employed in or on a continual contractual relationship with any of the offices or agencies of State government to participate in contract negotiations on behalf of that office or agency with any firm, partnership, association, or corporation with whom that person has a contract for future employment or is negotiating concerning possible future employment.
- 2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-15, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

C. Inducements

1. The Illinois Procurement Code provides:

Section 50-25. Inducement. Any person who offers or pays any money or other valuable thing to any person to induce him or her not to bid for a State contract or as recompense for not having bid on a State contract is guilty of a Class 4 felony. Any person who accepts any money or other valuable thing for not bidding for a State contract or who withholds a bid in consideration of the promise for the payment of money or other valuable thing is guilty of a Class 4 felony.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-25, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

D. Revolving Door Prohibition

1. The Illinois Procurement Code provides:

Section 50-30. Revolving door prohibition. Chief procurement officers, State purchasing officers, procurement compliance monitors, their designees whose principal duties are directly related to State procurement, and executive officers confirmed by the Senate are expressly prohibited for a period of 2 years after terminating an affected position from engaging in any procurement activity relating to the State agency most recently employing them in an affected position for a period of at least 6 months. The prohibition includes, but is not limited to: lobbying the procurement process; specifying; bidding; proposing bid, proposal, or contract documents; on their own behalf or on behalf of any firm, partnership, association, or corporation. This Section applies only to persons who terminate an affected position on or after January 15, 1999.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-30, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

E. Reporting Anticompetitive Practices

1. The Illinois Procurement Code provides:

Section 50-40. Reporting anticompetitive practices. When, for any reason, any vendor, bidder, contractor, chief procurement officer, State purchasing officer, designee, elected official, or State employee suspects collusion or other anticompetitive practice among any bidders, offerors, contractors, proposers, or employees of the State, a notice of the relevant facts shall be transmitted to the Attorney General and the chief procurement officer.

2. The bidder assures the Department that it has not failed to report any relevant facts concerning the practices addressed in Section 50-40 which may involve the contract for which the bid is submitted.

F. Confidentiality

1. The Illinois Procurement Code provides:

Section 50-45. Confidentiality. Any chief procurement officer, State purchasing officer, designee, or executive officer who willfully uses or allows the use of specifications, competitive bid documents, proprietary competitive information, proposals, contracts, or selection information to compromise the fairness or integrity of the procurement, bidding, or contract process shall be subject to immediate dismissal, regardless of the Personnel code, any contract, or any collective bargaining agreement, and may in addition be subject to criminal prosecution.

2. The bidder assures the Department that it has no knowledge of any fact relevant to the practices addressed in Section 50-45 which may involve the contract for which the bid is submitted.

G. Insider Information

1. The Illinois Procurement Act provides:

Section 50-50. Insider information. It is unlawful for any current or former elected or appointed State official or State employee to knowingly use confidential information available only by virtue of that office or employment for actual or anticipated gain for themselves or another person.

2. The bidder assures the Department that it has no knowledge of any facts relevant to the practices addressed in Section 50-50 which may involve the contract for which the bid is submitted.

III. CERTIFICATIONS

The certifications hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder. Section 50-2 of the Illinois Procurement Code provides that every person that has entered into a multi-year contract and every subcontractor with a multi-year subcontract shall certify, by July 1 of each fiscal year covered by the contract after the initial fiscal year, to the responsible chief procurement officer whether it continues to satisfy the requirements of Article 50 pertaining to the eligibility for a contract award. If a contractor or subcontractor is not able to truthfully certify that it continues to meet all requirements, it shall provide with its certification a detailed explanation of the circumstances leading to the change in certification status. A contractor or subcontractor that makes a false statement material to any given certification required under Article 50 is, in addition to any other penalties or consequences prescribed by law, subject to liability under the Whistleblower Reward and Protection Act for submission of a false claim.

A. Bribery

1. The Illinois Procurement Code provides:

Section 50-5. Bribery.

- (a) Prohibition. No person or business shall be awarded a contract or subcontract under this Code who:
 - (1) has been convicted under the laws of Illinois or any other state of bribery or attempting to bribe an officer or employee of the State of Illinois or any other state in that officer's or employee's official capacity; or
 - (2) has made an admission of guilt of that conduct that is a matter of record but has not been prosecuted for that conduct.
- (b) Businesses. No business shall be barred from contracting with any unit of State or local government, or subcontracting under such a contract, as a result of a conviction under this Section of any employee or agent of the business if the employee or agent is no longer employed by the business and:
 - (1) the business has been finally adjudicated not guilty; or
 - (2) the business demonstrates to the governmental entity with which it seeks to contract, or which is signatory to the contract which the subcontract relates, and that entity finds that the commission of the offense was not authorized, requested, commanded, or performed by a director, officer, or high managerial agent on behalf of the business as provided in paragraph (2) of subsection (a) of Section 5-4 of the Criminal Code of 1961.
- (c) Conduct on behalf of business. For purposes of this Section, when an official, agent, or employee of a business committed the bribery or attempted bribery on behalf of the business and in accordance with the direction or authorization of a responsible official of the business, the business shall be chargeable with the conduct.
- (d) Certification. Every bid submitted to and contract executed by the State, and every subcontract subject to Section 20-120 of the Procurement Code shall contain a certification by the contractor or the subcontractor, respectively, that the contractor or subcontractor is not barred from being awarded a contract or subcontract under this Section and acknowledges that the chief procurement officer may declare the related contract void if any certifications required by this Section are false. A contractor who makes a false statement, material to the certification, commits a Class 3 felony.
- 2. The contractor or subcontractor certifies that it is not barred from being awarded a contract under Section 50.5.

B. Felons

1. The Illinois Procurement Code provides:

Section 50-10. Felons. Unless otherwise provided, no person or business convicted of a felony shall do business with the State of Illinois or any State agency, or enter into a subcontract, from the date of conviction until 5 years after the date of completion of the sentence for that felony, unless no person held responsible by a prosecutorial office for the facts upon which the conviction was based continues to have any involvement with the business.

3. Certification. Every bid submitted to and contract executed by the State and every subcontract subject to Section 20-120 of the Procurement Code shall contain a certification by the bidder or contractor or subcontractor, respectively, that the bidder, contractor, or subcontractor is not barred from being awarded a contract or subcontract under this Section and acknowledges that the chief procurement officer may declare the related contract void if any of the certifications required by this Section are false.

C. Debt Delinquency

1. The Illinois Procurement Code provides:

Section 50-11 and 50-12. Debt Delinquency.

The contractor or bidder or subcontractor, respectively, certifies that it, or any affiliate, is not barred from being awarded a contract or subcontract under the Procurement Code. Section 50-11 prohibits a person from entering into a contract with a State agency, or entering into a subcontract, if it knows or should know that it, or any affiliate, is delinquent in the payment of any debt to the State as defined by the Debt Collection Board. Section 50-12 prohibits a person from entering into a contract with a State agency, or entering into a subcontract, if it, or any affiliate, has failed to collect and remit Illinois Use Tax on all sales of tangible personal property into the State of Illinois in accordance with the provisions of the Illinois Use Tax Act. The bidder or contractor or subcontractor, respectively, further acknowledges that the chief procurement officer may declare the related contract void if this certification is false or if the bidder, contractor, or subcontractor, or any affiliate, is determined to be delinquent in the payment of any debt to the State during the term of the contract.

D. Prohibited Bidders, Contractors and Subcontractors

1. The Illinois Procurement Code provides:

Section 50-10.5 and 50-60(c). Prohibited bidders, contractors and subcontractors.

The bidder or contractor or subcontractor, respectively, certifies in accordance with 30 ILCS 500/50-10.5 that no officer, director, partner or other managerial agent of the contracting business has been convicted of a felony under the Sarbanes-Oxley Act of 2002 or a Class 3 or Class 2 felony under the Illinois Securities Law of 1953 or if in violation of Subsection (c) for a period of five years from the date of conviction. Every bid submitted to and contract executed by the State and every subcontract subject to Section 20-120 of the Procurement Code shall contain a certification by the bidder, contractor, or subcontractor, respectively, that the bidder, contractor, or subcontractor is not barred from being awarded a contract or subcontract under this Section and acknowledges that the chief procurement officer shall declare the related contract void if any of the certifications completed pursuant to this Section are false.

E. Section 42 of the Environmental Protection Act

The bidder or contractor or subcontractor, respectively, certifies in accordance with 30 ILCS 500/50-12 that the bidder, contractor, or subcontractor, is not barred from being awarded a contract or entering into a subcontract under this Section which prohibits the bidding on or entering into contracts with the State of Illinois or a State agency, or entering into any subcontract, that is subject to the Procurement Code by a person or business found by a court or the Pollution Control Board to have committed a willful or knowing violation of Section 42 of the Environmental Protection Act for a period of five years from the date of the order. The bidder or contractor or subcontractor, respectively, acknowledges that the chief procurement officer may declare the contract void if this certification is false.

F. Educational Loan

- 1. Section 3 of the Educational Loan Default Act provides:
- § 3. No State agency shall contract with an individual for goods or services if that individual is in default, as defined in Section 2 of this Act, on an educational loan. Any contract used by any State agency shall include a statement certifying that the individual is not in default on an educational loan as provided in this Section.
- 2. The bidder, if an individual as opposed to a corporation, partnership or other form of business organization, certifies that the bidder is not in default on an educational loan as provided in Section 3 of the Act.

G. Bid-Rigging/Bid Rotating

- 1. Section 33E-11 of the Criminal Code of 1961 provides:
- § 33E-11. (a) Every bid submitted to and public contract executed pursuant to such bid by the State or a unit of local government shall contain a certification by the prime contractor that the prime contractor is not barred from contracting with any unit of State or local government as a result of a violation of either Section 33E-3 or 33E-4 of this Article. The State and units of local government shall provide the appropriate forms for such certification.
- (b) A contractor who makes a false statement, material to the certification, commits a Class 3 felony.

A violation of Section 33E-3 would be represented by a conviction of the crime of bid-rigging which, in addition to Class 3 felony sentencing, provides that any person convicted of this offense or any similar offense of any state or the United States which contains the same elements as this offense shall be barred for 5 years from the date of conviction from contracting with any unit of State or local government. No corporation shall be barred from contracting with any unit of State or local government as a result of a conviction under this Section of any employee or agent of such corporation if the employee so convicted is no longer employed by the corporation and: (1) it has been finally adjudicated not guilty or (2) if it demonstrates to the governmental entity with which it seeks to contract and that entity finds that the commission of the offense was neither authorized, requested, commanded, nor performed by a director, officer or a high managerial agent in behalf of the corporation.

A violation of Section 33E-4 would be represented by a conviction of the crime of bid-rotating which, in addition to Class 2 felony sentencing, provides that any person convicted of this offense or any similar offense of any state or the United States which contains the same elements as this offense shall be permanently barred from contracting with any unit of State or local government. No corporation shall be barred from contracting with any unit of State or local government as a result of a conviction under this Section of any employee or agent of such corporation if the employee so convicted is no longer employed by the corporation and: (1) it has been finally adjudicated not guilty or (2) if it demonstrates to the governmental entity with which it seeks to contract and that entity finds that the commission of the offense was neither authorized, requested, commanded, nor performed by a director, officer or a high managerial agent in behalf of the corporation.

2. The bidder certifies that it is not barred from contracting with the Department by reason of a violation of either Section 33E-3 or Section 33E-4.

H. International Anti-Boycott

- 1. Section 5 of the International Anti-Boycott Certification Act provides:
- § 5. State contracts. Every contract entered into by the State of Illinois for the manufacture, furnishing, or purchasing of supplies, material, or equipment or for the furnishing of work, labor, or services, in an amount exceeding the threshold for small purchases according to the purchasing laws of this State or \$10,000.00, whichever is less, shall contain certification, as a material condition of the contract, by which the contractor agrees that neither the contractor nor any substantially-owned affiliated company is participating or shall participate in an international boycott in violation of the provisions of the U.S. Export Administration Act of 1979 or the regulations of the U.S. Department of Commerce promulgated under that Act.
- 2. The bidder makes the certification set forth in Section 5 of the Act.

I. Drug Free Workplace

- 1. The Illinois "Drug Free Workplace Act" applies to this contract and it is necessary to comply with the provisions of the "Act" if the contractor is a corporation, partnership, or other entity (including a sole proprietorship) which has 25 or more employees.
- 2. The bidder certifies that if awarded a contract in excess of \$5,000 it will provide a drug free workplace by:
- (a) Publishing a statement notifying employees that the unlawful manufacture, distribution, dispensation, possession or use of a controlled substance, including cannabis, is prohibited in the contractor's workplace; specifying the actions that will be taken against employees for violations of such prohibition; and notifying the employee that, as a condition of employment on such contract, the employee shall abide by the terms of the statement, and notify the employer of any criminal drug statute conviction for a violation occurring in the workplace no later than five (5) days after such conviction.
- (b) Establishing a drug free awareness program to inform employees about the dangers of drug abuse in the workplace; the contractor's policy of maintaining a drug free workplace; any available drug counseling, rehabilitation, and employee assistance programs; and the penalties that may be imposed upon employees for drug violations.
- (c) Providing a copy of the statement required by subparagraph (1) to each employee engaged in the performance of the contract and to post the statement in a prominent place in the workplace.
- (d) Notifying the Department within ten (10) days after receiving notice from an employee or otherwise receiving actual notice of the conviction of an employee for a violation of any criminal drug statute occurring in the workplace.
- (e) Imposing or requiring, within 30 days after receiving notice from an employee of a conviction or actual notice of such a conviction, an appropriate personnel action, up to and including termination, or the satisfactory participation in a drug abuse assistance or rehabilitation program approved by a federal, state or local health, law enforcement or other appropriate agency.
- (f) Assisting employees in selecting a course of action in the event drug counseling, treatment, and rehabilitation is required and indicating that a trained referral team is in place.
- (g) Making a good faith effort to continue to maintain a drug free workplace through implementation of the actions and efforts stated in this certification.

J. <u>Disclosure of Business Operations in Iran</u>

Section 50-36 of the Illinois Procurement Code, 30ILCS 500/50-36 provides that each bid, offer, or proposal submitted for a State contract shall include a disclosure of whether or not the Company acting as the bidder, offeror, or proposing entity, or any of its corporate parents or subsidiaries, within the 24 months before submission of the bid, offer, or proposal had business operations that involved contracts with or provision of supplies or services to the Government of Iran, companies in which the Government of Iran has any direct or indirect equity share, consortiums or projects commissioned by the Government of Iran, or companies involved in consortiums or projects commissioned by the Government of Iran and either of the following conditions apply:

- (1) More than 10% of the Company's revenues produced in or assets located in Iran involve oil-related activities or mineral-extraction activities; less than 75% of the Company's revenues produced in or assets located in Iran involve contracts with or provision of oil-related or mineral-extraction products or services to the Government of Iran or a project or consortium created exclusively by that government; and the Company has failed to take substantial action.
- (2) The Company has, on or after August 5, 1996, made an investment of \$20 million or more, or any combination of investments of at least \$10 million each that in the aggregate equals or exceeds \$20 million in any 12-month period, which directly or significantly contributes to the enhancement of Iran's ability to develop petroleum resources of Iran.

The terms "Business operations", "Company", "Mineral-extraction activities", "Oil-related activities", "Petroleum resources", and "Substantial action" are all defined in the Code.

Failure to make the disclosure required by the Code shall cause the bid, offer or proposal to be considered not responsive. The disclosure will be considered when evaluating the bid, offer, or proposal or awarding the contract. The name of each Company disclosed as doing business or having done business in Iran will be provided to the State Comptroller.

| Check the appropriate statement: |
|--|
| // Company has no business operations in Iran to disclose. |
| / Company has business operations in Iran as disclosed the attached document |

K. Apprenticeship and Training Certification (Does not apply to federal aid projects)

In accordance with the provisions of Section 30-22 (6) of the Illinois Procurement Code, the bidder certifies that it is a participant, either as an individual or as part of a group program, in the approved apprenticeship and training programs applicable to each type of work or craft that the bidder will perform with its own forces. The bidder further certifies for work that will be performed by subcontract that each of its subcontractors submitted for approval either (a) is, at the time of such bid, participating in an approved, applicable apprenticeship and training program; or (b) will, prior to commencement of performance of work pursuant to this contract, begin participation in an approved apprenticeship and training program applicable to the work of the subcontract. The Department, at any time before or after award, may require the production of a copy of each applicable Certificate of Registration issued by the United States Department of Labor evidencing such participation by the contractor and any or all of its subcontractors. Applicable apprenticeship and training programs are those that have been approved and registered with the United States Department of Labor. The bidder shall list in the space below, the official name of the program sponsor holding the Certificate of Registration for all of the types of work or crafts in which the bidder is a participant and that will be performed with the bidder's forces. Types of work or craft work that will be subcontracted shall be included and listed as subcontract work. The list shall also indicate any type of work or craft job category that does not have an applicable apprenticeship or training program. The bidder is responsible for making a complete report and shall make certain that each type of work or craft job category that will be utilized on the project as reported on the Construction Employee Workforce Projection (Form BC-1256) and returned with the bid is accounted for and listed.

| NA-FEDERAL | | |
|------------|--|--|
| | | |
| | | |

The requirements of this certification and disclosure are a material part of the contract, and the contractor shall require this certification provision to be included in all approved subcontracts. In order to fulfill this requirement, it shall not be necessary that an applicable program sponsor be currently taking or that it will take applications for apprenticeship, training or employment during the performance of the work of this contract.

L. Political Contributions and Registration with the State Board of Elections

Sections 20-160 and 50-37 of the Illinois Procurement Code regulate political contributions from business entities and any affiliated entities or affiliated persons bidding on or contracting with the state. Generally under Section 50-37, any business entity, and any affiliated entity or affiliated person of the business entity, whose current year contracts with all state agencies exceed an awarded value of \$50,000, are prohibited from making any contributions to any political committees established to promote the candidacy of the officeholder responsible for the awarding of the contracts or any other declared candidate for that office for the duration of the term of office of the incumbent officeholder or a period 2 years after the termination of the contract, whichever is longer. Any business entity and affiliated entities or affiliated persons whose state contracts in the current year do not exceed an awarded value of \$50,000, but whose aggregate pending bids and proposals on state contracts exceed \$50,000, either alone or in combination with contracts not exceeding \$50,000, are prohibited from making any political contributions to any political committee established to promote the candidacy of the officeholder responsible for awarding the pending contract during the period beginning on the date the invitation for bids or request for proposals is issued and ending on the day after the date of award or selection if the entity was not awarded or selected. Section 20-160 requires certification of registration of affected business entities in accordance with procedures found in Section 9-35 of The Election Code.

By submission of a bid, the contractor business entity acknowledges and agrees that it has read and understands Sections 20-160 and 50-37 of the Illinois Procurement Code, and that it makes the following certification:

The undersigned business entity certifies that it has registered as a business with the State Board of Elections and acknowledges a continuing duty to update the registration in accordance with the above referenced statutes. A copy of the certificate of registration shall be submitted with the bid. The bidder is cautioned that the Department will not award a contract without submission of the certificate of registration.

These requirements and compliance with the above referenced statutory sections are a material part of the contract, and any breach thereof shall be cause to void the contract under Section 50-60 of the Illinois Procurement Code. This provision does not apply to Federal-aid contracts

M. Lobbyist Disclosure

Section 50-38 of the Illinois Procurement Code requires that any bidder or offeror on a State contract that hires a person required to register under the Lobbyist Registration Act to assist in obtaining a contract shall:

- (i) Disclose all costs, fees, compensation, reimbursements, and other remunerations paid or to be paid to the lobbyist related to the contract.
- (ii) Not bill or otherwise cause the State of Illinois to pay for any of the lobbyist's costs, fees, compensation, reimbursements, or other remuneration, and
- (iii) Sign a verification certifying that none of the lobbyist's costs, fees, compensation, reimbursements, or other remuneration were billed to the State.

This information, along with all supporting documents, shall be filed with the agency awarding the contract and with the Secretary of State. The chief procurement officer shall post this information, together with the contract award notice, in the online Procurement Bulletin.

Pursuant to Subsection (c) of this Section, no person or entity shall retain a person or entity to attempt to influence the outcome of a procurement decision made under the Procurement Code for compensation contingent in whole or in part upon the decision or procurement. Any person who violates this subsection is guilty of a business offense and shall be fined not more than \$10,000.

Bidder acknowledges that it is required to disclose the hiring of any person required to register pursuant to the Illinois Lobbyist Registration Act (25 ILCS 170) in connection with this contract.

| • | | · | |
|---|----|--|-----------|
| | | Bidder has not hired any person required to register pursuant to the Illinois Lobbyist Registration Act in connection vaccontract. | with this |
| | Or | | |
| | | Bidder has hired the following persons required to register pursuant to the Illinois Lobbyist Registration Act in connection contract: | with the |
| | | address of person:ees, compensation, reimbursements and other remuneration paid to said person: | |
| | | | |
| | | | |

IV. DISCLOSURES

A. The disclosures hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder. The bidder further certifies that the Department has received the disclosure forms for each bid.

The chief procurement officer may void the bid, contract, or subcontract, respectively, if it is later determined that the bidder or subcontractor rendered a false or erroneous disclosure. A contractor or subcontractor may be suspended or debarred for violations of the Procurement Code. Furthermore, the chief procurement officer may void the contract and the surety providing the performance bond shall be responsible for completion of the contract.

B. Financial Interests and Conflicts of Interest

1. Section 50-35 of the Illinois Procurement Code provides that all bids of more than \$25,000 shall be accompanied by disclosure of the financial interests of the bidder. This disclosed information for the successful bidder, will be maintained as public information subject to release by request pursuant to the Freedom of Information Act, filed with the Procurement Policy Board, and shall be incorporated as a material term of the contract. Furthermore, pursuant to Section 5-5, the Procurement Policy Board may review a proposal, bid, or contract and issue a recommendation to void a contract or reject a proposal or bid based on any violation of the Procurement Code or the existence of a conflict of interest as provided in subsections (b) and (d) of Section 50-35.

The financial interests to be disclosed shall include ownership or distributive income share that is in excess of 5%, or an amount greater than 60% of the annual salary of the Governor, of the bidding entity or its parent entity, whichever is less, unless the contractor or bidder is a publicly traded entity subject to Federal 10K reporting, in which case it may submit its 10K disclosure in place of the prescribed disclosure. If a bidder is a privately held entity that is exempt from Federal 10K reporting, but has more than 200 shareholders, it may submit the information that Federal 10K companies are required to report, and list the names of any person or entity holding any ownership share that is in excess of 5%. The disclosure shall include the names, addresses, and dollar or proportionate share of ownership of each person making the disclosure, their instrument of ownership or beneficial relationship, and notice of any potential conflict of interest resulting from the current ownership or beneficial interest of each person making the disclosure having any of the relationships identified in Section 50-35 and on the disclosure form.

The current annual salary of the Governor is \$177,412.00.

In addition, all disclosures shall indicate any other current or pending contracts, proposals, leases, or other ongoing procurement relationships the bidding entity has with any other unit of state government and shall clearly identify the unit and the contract, proposal, lease, or other relationship.

2. <u>Disclosure Forms</u>. Disclosure Form A is attached for use concerning the individuals meeting the above ownership or distributive share requirements. Subject individuals should be covered each by one form. In addition, a second form (Disclosure Form B) provides for the disclosure of current or pending procurement relationships with other (non-IDOT) state agencies. **The forms must be included with each bid.**

C. <u>Disclosure Form Instructions</u>

Form A Instructions for Financial Information & Potential Conflicts of Interest

If the bidder is a publicly traded entity subject to Federal 10K reporting, the 10K Report may be submitted to meet the requirements of Form A. If a bidder is a privately held entity that is exempt from Federal 10K reporting, but has more than 200 shareholders, it may submit the information that Federal 10K companies are required to report, and list the names of any person or entity holding any ownership share that is in excess of 5%. If a bidder is not subject to Federal 10K reporting, the bidder must determine if any individuals are required by law to complete a financial disclosure form. To do this, the bidder should answer each of the following questions. A "YES" answer indicates Form A must be completed. If the answer to each of the following questions is "NO", then the NOT APPLICABLE STATEMENT on Form A must be signed and dated by a person that is authorized to execute contracts for the bidding company. Note: These questions are for assistance only and are not required to be completed.

| 1. | Does anyone in your organization have a direct or beneficial ownership share of greater than 5% of the bidding entity or parent entity? YES NO |
|----|--|
| 2. | Does anyone in your organization have a direct or beneficial ownership share of less than 5%, but which has a value greater than 60% of the annual salary of the Governor? YESNO |
| 3. | Does anyone in your organization receive more than 60% of the annual salary of the Governor of the bidding entity's or parent entity's distributive income? YES NO |
| 4. | Does anyone in your organization receive greater than 5% of the bidding entity's or parent entity's total distributive income, but which is less than 60% of the annual salary of the Governor? YES NO |
| | (Note: Only one set of forms needs to be completed <u>per person per bid</u> even if a specific individual would require a yes answer to more than one question.) |
| | answer to any of these questions requires the completion of Form A. The bidder must determine each individual in the bidding entity or |

A "YES" answer to any of these questions requires the completion of Form A. The bidder must determine each individual in the bidding entity or the bidding entity's parent company that would cause the questions to be answered "Yes". Each form must be signed and dated by a person that is authorized to execute contracts for your organization. **Photocopied or stamped signatures are not acceptable**. The person signing can be, but does not have to be, the person for which the form is being completed. The bidder is responsible for the accuracy of any information provided.

If the answer to each of the above questions is "NO", then the <u>NOT APPLICABLE STATEMENT</u> of Form A must be signed and dated by a person that is authorized to execute contracts for your company.

Form B: Instructions for Identifying Other Contracts & Procurement Related Information

Disclosure Form B must be completed for each bid submitted by the bidding entity. Note: Checking the <u>NOT APPLICABLE STATEMENT</u> on Form A <u>does not</u> allow the bidder to ignore Form B. Form B must be completed, checked, and dated or the bidder may be considered nonresponsive and the bid will not be accepted.

The Bidder shall identify, by checking Yes or No on Form B, whether it has any pending contracts (including leases), bids, proposals, or other ongoing procurement relationship with any other (non-IDOT) State of Illinois agency. If "No" is checked, the bidder only needs to complete the check box on the bottom of Form B. If "Yes" is checked, the bidder must do one of the following:

Option I: If the bidder did not submit an Affidavit of Availability to obtain authorization to bid, the bidder must list all non-IDOT State of Illinois agency pending contracts, leases, bids, proposals, and other ongoing procurement relationships. These items may be listed on Form B or on an attached sheet(s). Do not include IDOT contracts. Contracts with cities, counties, villages, etc. are not considered State of Illinois agency contracts and are not to be included. Contracts with other State of Illinois agencies such as the Department of Natural Resources or the Capital Development Board must be included. Bidders who submit Affidavits of Availability are suggested to use Option II.

Option II: If the bidder is required and has submitted an Affidavit of Availability in order to obtain authorization to bid, the bidder may write or type "See Affidavit of Availability" which indicates that the Affidavit of Availability is incorporated by reference and includes all non-IDOT State of Illinois agency pending contracts, leases, bids, proposals, and other ongoing procurement relationships. For any contracts that are not covered by the Affidavit of Availability, the bidder must identify them on Form B or on an attached sheet(s). These might be such things as leases.

ILLINOIS DEPARTMENT OF TRANSPORTATION

Form A Financial Information & Potential Conflicts of Interest Disclosure

| Contractor Name | | |
|------------------|---------------|---------------------------|
| Legal Address | | |
| Legal Address | | |
| City, State, Zip | | |
| | | |
| Telephone Number | Email Address | Fax Number (if available) |
| | | |

Disclosure of the information contained in this Form is required by the Section 50-35 of the Illinois Procurement Code (30 ILCS 500). Vendors desiring to enter into a contract with the State of Illinois must disclose the financial information and potential conflict of interest information as specified in this Disclosure Form. This information shall become part of the publicly available contract file. This Form A must be completed for bids in excess of \$25,000, and for all open-ended contracts. A publicly traded company may submit a 10K disclosure (or equivalent if applicable) in satisfaction of the requirements set forth in Form A. See Disclosure Form Instructions.

The current annual salary of the Governor is \$177,412.00.

DISCLOSURE OF FINANCIAL INFORMATION

 Disclosure of Financial Information. The individual named below has an interest in the BIDDER (or its parent) in terms of ownership or distributive income share in excess of 5%, or an interest which has a value of more than 60% of the annual salary of the Governor. (Make copies of this form as necessary and attach a separate Disclosure Form A for each individual meeting these requirements)

| FOR II | NDIVIDUAL (| type or print information) | | |
|--------|------------------|-----------------------------------|-------------|-------------------------------------|
| I | NAME: | | | |
| 1 | ADDRESS _ | | | |
| | | | | |
| • | Type of owner | ship/distributable income share | : | |
| ; | stock | sole proprietorship | Partnership | other: (explain on separate sheet): |
| (| % or \$ value of | ownership/distributable income sh | are: | |

- **2. Disclosure of Potential Conflicts of Interest.** Check "Yes" or "No" to indicate which, if any, of the following potential conflict of interest relationships apply. If the answer to any question is "Yes", please attach additional pages and describe.
 - (a) State employment, currently or in the previous 3 years, including contractual employment of services. Yes No

If your answer is yes, please answer each of the following questions.

- 1. Are you currently an officer or employee of either the Capitol Development Board or the Illinois State Toll Highway Authority?

 Yes No ___
- Are you currently appointed to or employed by any agency of the State of Illinois? If you are currently appointed to or employed by any agency of the State of Illinois, and your annual salary exceeds 60% of the annual salary of the Governor provide the name the State agency for which you are employed and your annual salary.

| 3. | If you are currently appointed to or employed by any agency of the Salary exceeds 60% of the annual salary of the Governor, are you e (i) more than 7 1/2% of the total distributable income of your firr corporation, or (ii) an amount in excess of 100% of the annual salary | ntitled to receive n, partnership, association or |
|---------------------|--|---|
| 4. | If you are currently appointed to or employed by any agency of the Salary exceeds 60% of the annual salary of the Governor, are you a or minor children entitled to receive (i) more than 15% in aggregate of your firm, partnership, association or corporation, or (ii) an amour salary of the Governor? | nd your spouse of the total distributable income |
| | employment of spouse, father, mother, son, or daughter, including corprevious 2 years. | ntractual employment for services |
| If your | answer is yes, please answer each of the following questions. | YesNo |
| 1. | Is your spouse or any minor children currently an officer or employee Board or the Illinois State Toll Highway Authority? | of the Capitol Development YesNo |
| 2. | Is your spouse or any minor children currently appointed to or employ of Illinois? If your spouse or minor children is/are currently appointe agency of the State of Illinois, and his/her annual salary exceeds 6 annual salary of the Governor, provide the name of the spouse and/of the State agency for which he/she is employed and his/her annual | d to or employed by any 0% of the or minor children, the name |
| 3. | If your spouse or any minor children is/are currently appointed to or estate of Illinois, and his/her annual salary exceeds 60% of the annual are you entitled to receive (i) more than 71/2% of the total distributable firm, partnership, association or corporation, or (ii) an amount in excannual salary of the Governor? | ll salary of the Governor, e income of your |
| 4. | If your spouse or any minor children are currently appointed to or er State of Illinois, and his/her annual salary exceeds 60% of the annual and your spouse or any minor children entitled to receive (i) more that aggregate of the total distributable income from your firm, partnership (ii) an amount in excess of two times the salary of the Governor? | salary of the Governor, are you an 15% in the |
| unit of I | e status; the holding of elective office of the State of Illinois, the governocal government authorized by the Constitution of the State of Illinoicurrently or in the previous 3 years. | |
| | nship to anyone holding elective office currently or in the previous 2 years daughter. | ears; spouse, father, mother, YesNo |
| America of the S | tive office; the holding of any appointive government office of the State, or any unit of local government authorized by the Constitution of the State of Illinois, which office entitles the holder to compensation in exceptage of that office currently or in the previous 3 years. | e State of Illinois or the statues |
| . , | nship to anyone holding appointive office currently or in the previous 2 daughter. | years; spouse, father, mother, YesNo |
| (g) Employ | ment, currently or in the previous 3 years, as or by any registered lob | byist of the State government. YesNo |

| son, or daughter. | YesNo |
|--|---|
| (i) Compensated employment, currently or in the previous committee registered with the Secretary of State or any action committee registered with either the Secretary of | county clerk of the State of Illinois, or any political |
| (j) Relationship to anyone; spouse, father, mother, son, or last 2 years by any registered election or re-election cor county clerk of the State of Illinois, or any political actio State or the Federal Board of Elections. | nmittee registered with the Secretary of State or any n committee registered with either the Secretary of |
| | Yes No |
| 3. Communication Disclosure. | |
| Disclose the name and address of each lobbyist and other Section 2 of this form, who is has communicated, is commemployee concerning the bid or offer. This disclosure is a for accuracy throughout the process and throughout the te on the line below: | unicating, or may communicate with any State officer or continuing obligation and must be promptly supplemented |
| Name and address of person(s): | |
| | |
| | |

4. Debarment Disclosure. For each of the persons identified under Sections 2 and 3 of this form, disclose whether any of the following has occurred within the previous 10 years: debarment from contracting with any governmental

entity; professional licensure discipline; bankruptcies; adverse civil judgments and administrative findings; and criminal felony convictions. This disclosure is a continuing obligation and must be promptly supplemented for accuracy throughout the procurement process and term of the contract. If no person is identified, enter "None" on the line below: Name of person(s): Nature of disclosure: APPLICABLE STATEMENT This Disclosure Form A is submitted on behalf of the INDIVIDUAL named on previous page. Under penalty of perjury, I certify the contents of this disclosure to be true and accurate to the best of my knowledge. Completed by: Signature of Individual or Authorized Representative Date NOT APPLICABLE STATEMENT Under penalty of perjury, I have determined that no individuals associated with this organization meet the criteria that would require the completion of this Form A. This Disclosure Form A is submitted on behalf of the CONTRACTOR listed on the previous page. Signature of Authorized Representative Date

The bidder has a continuing obligation to supplement these disclosures under Sec. 50-35 of the Procurement Code.

ILLINOIS DEPARTMENT OF TRANSPORTATION

Form B Other Contracts & Procurement Related Information Disclosure

| Contractor Name | | |
|---|---|---------------------------------|
| Legal Address | | |
| City, State, Zip | | |
| Telephone Number | Email Address | Fax Number (if available) |
| Disclosure of the information contained in this Act (30 ILCS 500). This information shall become completed for bids in excess of \$25,000, a | come part of the publicly available of | |
| DISCLOSURE OF OTHER O | CONTRACTS AND PROCUREMEN | NT RELATED INFORMATION |
| 1. Identifying Other Contracts & Procure has any pending contracts (including leases any other State of Illinois agency: Yes _ If "No" is checked, the bidder only needs to | s), bids, proposals, or other ongoing No | g procurement relationship with |
| 2. If "Yes" is checked. Identify each such information such as bid or project number (a INSTRUCTIONS: | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| THE FOLI | LOWING STATEMENT MUST BE | CHECKED |
| | | |
| | Signature of Authorized Representative | Date |

SPECIAL NOTICE TO CONTRACTORS

The following requirements of the Illinois Department of Human Rights' Rules and Regulations are applicable to bidders on all construction contracts advertised by the Illinois Department of Transportation:

CONSTRUCTION EMPLOYEE UTILIZATION PROJECTION

- (a) All bidders on construction contracts shall complete and submit, along with and as part of their bids, a Bidder's Employee Utilization Form (Form BC-1256) setting forth a projection and breakdown of the total workforce intended to be hired and/or allocated to such contract work by the bidder including a projection of minority and female employee utilization in all job classifications on the contract project.
- (b) The Department of Transportation shall review the Employee Utilization Form, and workforce projections contained therein, of the contract awardee to determine if such projections reflect an underutilization of minority persons and/or women in any job classification in accordance with the Equal Employment Opportunity Clause and Section 7.2 of the Illinois Department of Human Rights' Rules and Regulations for Public Contracts adopted as amended on September 17, 1980. If it is determined that the contract awardee's projections reflect an underutilization of minority persons and/or women in any job classification, it shall be advised in writing of the manner in which it is underutilizing and such awardee shall be considered to be in breach of the contract unless, prior to commencement of work on the contract project, it submits revised satisfactory projections or an acceptable written affirmative action plan to correct such underutilization including a specific timetable geared to the completion stages of the contract.
- (c) The Department of Transportation shall provide to the Department of Human Rights a copy of the contract awardee's Employee Utilization Form, a copy of any required written affirmative action plan, and any written correspondence related thereto. The Department of Human Rights may review and revise any action taken by the Department of Transportation with respect to these requirements.



Contract No. 93554
ADAMS County
Section 08-00307-00-TL (Quincy)
Project M-SRTS-4008(089)
Route FAU 7807 (Maine Street)
District 6 Construction Funds

| PART I. IDENTIFIC | ATION | | | | | | | | | | | | | | | | | |
|---|--|--|------------------|--------------------|-----------|----------|---------|-------------|----------|------------|--------|-----------------|------|-------------|--------------|-------------|----------|---------------|
| Dept. Human Rights | s # | | | | | | _ Du | ration o | of Proj | ect: _ | | | | | | | | |
| Name of Bidder: | | | | | | | | | | | | | | | | | | |
| PART II. WORKFO A. The undersigned which this contract wo projection including a p | bidder hark is to be | as analyz e perform | ed mir ed, an | d for th d fema | ne locati | ons fro | m whice | ch the b | idder re | ecruits | employ | ees, and he | ereb | v subm | its the foll | owir con | g workfo | n orce |
| | | TOTA | AL Wo | rkforce | Projec | tion for | Contra | act | | | | | | C | CURRENT | | | S |
| | | | | MIN | ORITY I | EMPLO | YEES | | | TR | AINEES | | | | TO BE | | | |
| JOB CATEGORIES | _ | TAL OYEES | BL | ACK | HISP | ANIC | _ | HER IOR. | | REN- ES | ON T | HE JOB INEES | | | TAL OYEES | | | RITY DYEES |
| | М | F | М | F | М | F | М | F | М | F | М | F | | М | F | | М | F |
| OFFICIALS (MANAGERS) | | | | | | | | | | | | | | | | | | |
| SUPERVISORS | | | | | | | | | | | | | | | | | | |
| FOREMEN | | | | | | | | | | | | | | | | | | |
| CLERICAL | | | | | | | | | | | | | | | | | | |
| EQUIPMENT OPERATORS | | | | | | | | | | | | | | | | | | |
| MECHANICS | | | | | | | | | | | | | | | | | | |
| TRUCK DRIVERS | | | | | | | | | | | | | | | | | | |
| IRONWORKERS | | | | | | | | | | | | | | | | | | |
| CARPENTERS | | | | | | | | | | | | | | | | | | |
| CEMENT MASONS | | | | | | | | | | | | | | | | | | |
| ELECTRICIANS | | | | | | | | | | | | | | | | | | |
| PIPEFITTERS, PLUMBERS | | | | | | | | | | | | | | | | | | |
| PAINTERS | | | | | | | | | | | | | | | | | | |
| LABORERS, SEMI-SKILLED | | | | | | | | | | | | | | | | | | |
| LABORERS, UNSKILLED | | | | | | | | | | | | | | | | | | |
| TOTAL | | | | | | | | | | | | | | | | | | |
| | | BLE C | | | | | | | - | | Γ | FOR | DFF | PARTM | 1ENT USE | : Or | IΙΥ | |
| | | aining Pro | ojectio | n for C | ontract | | | | 4 | | | 1 010 | | / 11 X 1 IV | | - 011 | | |
| EMPLOYEES | _ | TAL | - | ٠ | | | _ | THER | | | | | | | | | | |
| IN | | OYEES | | ACK | | ANIC | 4 | NOR. | 4 | | | | | | | | | |
| TRAINING APPRENTICES | M | F | M | F | M | F | M | F | 1 | | | | | | | | | |
| ON THE IOD | | | 1 | 1 | 1 | 1 | + | 1 | + | | | | | | | | | |

Please specify race of each employee shown in Other Minorities column.

*Other minorities are defined as Asians (A) or Native Americans (N).

TRAINEES

Note: See instructions on page 2

BC 1256 (Rev. 12/11/08)

Contract No. 93554 ADAMS County Section 08-00307-00-TL (Quincy) Project M-SRTS-4008(089) Route FAU 7807 (Maine Street) District 6 Construction Funds

PART II. WORKFORCE PROJECTION - continued

| B. | | uded in "Total Employees" under Table A is the total number of new hires that would be employed in the nt the undersigned bidder is awarded this contract. | | | | | | | |
|-------------|--|--|---|--|--|--|--|--|--|
| | The under | rsigned bidder projects that: (number) | | new hires would be | | | | | |
| | recruited f | from the area in which the contract proje | ect is located; and/or (number) | ea in which the bidder's principal | | | | | |
| | office or ba | ase of operation is located. | would be recruited from the di | od in milon the blader o principal | | | | | |
| C. | | n "Total Employees" under Table A is a ed bidder as well as a projection of nun | | | | | | | |
| | be directly | rsigned bidder estimates that (number) remployed by the prime contractor and by subcontractors. | that (number) | persons will persons will be | | | | | |
| PART I | II. AFFIRM | IATIVE ACTION PLAN | | | | | | | |
| A. | utilization in any job commence (geared to utilization a | rsigned bidder understands and agrees projection included under PART II is decategory, and in the event that the underement of work, develop and submit a work the completion stages of the contract) are corrected. Such Affirmative Action retment of Human Rights. | etermined to be an underutilizat ersigned bidder is awarded this ritten Affirmative Action Plan in whereby deficiencies in minorit | ion of minority persons or women contract, he/she will, prior to cluding a specific timetable y and/or female employee | | | | | |
| B. | submitted | rsigned bidder understands and agrees herein, and the goals and timetable incomplete of the contract specifications. | | | | | | | |
| Compa | any | | Telephone Numb | per | | | | | |
| Addres | SS | | | | | | | | |
| | | NOTICE REG | GARDING SIGNATURE | | | | | | |
| | | ature on the Proposal Signature Sheet will only if revisions are required. | | The following signature block needs | | | | | |
| Signat | ure: 🗌 | | Title: | Date: | | | | | |
| Instruction | ons: All t | tables must include subcontractor personnel in ac | ddition to prime contractor personnel. | | | | | | |
| Table A | (Tal | lude both the number of employees that would ble B) that will be allocated to contract work, and buld include all employees including all minorities, | d include all apprentices and on-the-job | trainees. The "Total Employees" column | | | | | |
| Table B | | lude all employees currently employed that will be rently employed. | e allocated to the contract work includir | ng any apprentices and on-the-job trainees | | | | | |
| Table C | - Indi | icate the racial breakdown of the total apprentices | s and on-the-job trainees shown in Tab | le A. | | | | | |
| | | | | DO 4050 (D 40/44/00) | | | | | |

ADDITIONAL FEDERAL REQUIREMENTS

In addition to the Required Contract Provisions for Federal-Aid Construction Contracts (FHWA 1273), all bidders make the following certifications.

- A. By the execution of this proposal, the signing bidder certifies that the bidding entity has not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action, in restraint of free competitive bidding in connection with the submitted bid. This statement made by the undersigned bidder is true and correct under penalty of perjury under the laws of the United States.
- B. <u>CERTIFICATION, EQUAL EMPLOYMENT OPPORTUNITY:</u>

| 1. | Have you participated in any previous contracts or subcontracts subject to the equal opportunity clause. YES NO |
|----|---|
| 2. | If answer to #1 is yes, have you filed with the Joint Reporting Committee, the Director of OFCC, any Federal agency, or the former President's Committee on Equal Employment Opportunity, all reports due under the applicable filing requirements of those organizations? YES NO |

Contract No. 93554 ADAMS County Section 08-00307-00-TL (Quincy) Project M-SRTS-4008(089) Route FAU 7807 (Maine Street) District 6 Construction Funds

PROPOSAL SIGNATURE SHEET

The undersigned bidder hereby makes and submits this bid on the subject Proposal, thereby assuring the Department that all requirements of the Invitation for Bids and rules of the Department have been met, that there is no misunderstanding of the requirements of paragraph 3 of this Proposal, and that the contract will be executed in accordance with the rules of the Department if an award is made on this bid.

| | Firm Name | |
|--|------------------------|--|
| (IF AN INDIVIDUAL) | Signature of Owner | |
| | Business Address | |
| | | |
| | | |
| | Firm Name | |
| | Ву | |
| (IF A CO-PARTNERSHIP) | Business Address | |
| | | |
| | | Name and Address of All Members of the Firm: |
| | | |
| | | |
| | Corporate Name | |
| | | |
| (IF A CORPORATION) | | Signature of Authorized Representative |
| , | | Typed or printed name and title of Authorized Representative |
| | | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, |
| | Attest | Signature |
| (IF A JOINT VENTURE, USE THIS SECTION | 5 | ŭ |
| FOR THE MANAGING PARTY AND THE SECOND PARTY SHOULD SIGN BELOW) | Business Address | |
| | | |
| | Corporate Name | |
| | | |
| (IF A JOINT VENTURE) | -, | Signature of Authorized Representative |
| | | Typed or printed name and title of Authorized Penrocentative |
| | | Typed or printed name and title of Authorized Representative |
| | Attest | |
| | | Signature |
| | Business Address | |
| If more than two parties are in the joint venture. | nlesse attach an addit | ional signature sheet |

Illinois Department of Transportation

Return with Bid

Division of Highways Proposal Bid Bond

(Effective November 1, 1992)

| | | | item No. | |
|--|---|--|--|---|
| | | | Letting Date | |
| KNOW ALL MEN BY THESE PRESE | ENTS, That We | | | |
| | · — | | | |
| as PRINCIPAL, and | | | | |
| as FRINCIFAL, and | | | | |
| hold igintly appearally and firmly have | and unto the CTATE OF | III I INOIC in the namel of | um of E norment of the total hid | as SURETY, are |
| held jointly, severally and firmly bou specified in Article 102.09 of the "Sta is the lesser sum, well and truly to administrators, successors and assig | andard Specifications for be paid unto said STATE | Road and Bridge Constru | ction" in effect on the date of invi | tation for bids, whichever |
| THE CONDITION OF THE FOR STATE OF ILLINOIS, acting throug Number and Letting Date indicated a | h the Department of Tra | | ne PRINCIPAL has submitted a bi rovement designated by the Tra | |
| NOW, THEREFORE, if the De and as specified in the bidding and cafter award by the Department, the including evidence of the required i performance of such contract and for failure of the PRINCIPAL to make the to the Department the difference not which the Department may contract void, otherwise, it shall remain in full | contract documents, subrements, subrements and present the prompt payment of required DBE submission to exceed the penalty howith another party to pe | mit a DBE Utilization Plan nto a contract in accordant of providing such bond as of labor and material furn on or to enter into such co ereof between the amour | nce with the terms of the bidding specified with good and sufficient shed in the prosecution thereof; ntract and to give the specified boats at specified in the bid proposal ar | y the Department; and if, and contract documents ent surety for the faithful or if, in the event of the and, the PRINCIPAL pays and such larger amount for |
| IN THE EVENT the Department paragraph, then Surety shall pay the payment within such period of time, the expenses, including attorney's fees, it | penal sum to the Departr the Department may bring | ment within fifteen (15) da g an action to collect the | amount owed. Surety is liable to | Surety does not make full |
| In TESTIMONY WHEREOF, th | ne said PRINCIPAL and t | the said SURETY have ca | used this instrument to be signed | by |
| their respective officers this | day of | | A.D., . | |
| PRINCIPAL | | SURET | <u> </u> | |
| (Company Na | me) | | (Company Name) | |
| _ | ne) | Dv. | (Company Name) | |
| By(Signatur | e & Title) | By: | (Signature of Attorney | -in-Fact) |
| | Notary Cei | rtification for Principal and | 1 Surety | |
| STATE OF ILLINOIS, | noully cel | i incution for 1 finespur und | Survey | |
| County of | | | | |
| I, | | , a Notary P | ublic in and for said County, do he | ereby certify that |
| | | and | | |
| - | (Insert names of individua | als signing on behalf of PF | RINCIPAL & SURETY) | |
| who are each personally known to mand SURETY, appeared before me tand voluntary act for the uses and pu | his day in person and acl | | | |
| Given under my hand and nota | arial seal this | day of | | A.D |
| My commission expires | | | | |
| · <u>-</u> | | | Notary Pub | |
| In lieu of completing the above sect marking the check box next to the S and the Principal and Surety are firm | ignature and Title line be | elow, the Principal is ensu | uring the identified electronic bid | bond has been executed |
| | | | | |
| Electronic Bid Bond ID# | Company / Bidde | er Name | Signature a | and Title |



DBE Utilization Plan

(1) Policy

It is public policy that disadvantaged businesses as defined in 49 CFR Part 26 and the Special Provision shall have the maximum opportunity to participate in the performance of contracts financed in whole or in part with Federal or State funds. Consequently the requirements of 49 CFR Part 26 apply to this contract.

(2) Obligation

Date

The contractor agrees to ensure that disadvantaged businesses as defined in 49 CFR Part 26 and the Special Provision have the maximum opportunity to participate in the performance of contracts or subcontracts financed in whole or in part with Federal or State funds. The contractor shall take all necessary and reasonable steps in accordance with 49 CFR Part 26 and the Special Provision to ensure that said businesses have the maximum opportunity to compete for and perform under this contract. The contractor shall not discriminate on the basis of race, color, national origin or sex in the award and performance of contracts.

| (3) Pro | ject and Bid Identification | | | |
|-----------|---|---|---|---|
| Comple | te the following information concerning the project and bid: | | | |
| Route | | Total Bid | | |
| Section | | Contract DBE Goal | | |
| Project | | | (Percent) | (Dollar Amount) |
| County | | | | |
| Letting I | Date | | | |
| Contrac | t No. | | | |
| Letting I | tem No. | | | |
| (4) Ass | surance | | | |
| | in my capacity as an officer of the undersigned bidder (or bidder my company: (check one) Meets or exceeds contract award goals and has provided door Disadvantaged Business Participation percent Attached are the signed participation statements, forms SBE ause of each business participating in this plan and assuring the work of the contract. Failed to meet contract award goals and has included good fair provided participation as follows: Disadvantaged Business Participation percent The contract goals should be accordingly modified or waived, support of this request including good faith effort. Also attacher required by the Special Provision evidencing availability and u business will perform a commercially useful function in the wo | eumented participation as for 2025, required by the Spectat each business will perfort ith effort documentation to reach are the signed participation of each business participation of the contract. | ollows: ial Provision evide m a commercially meet the goals and required by the Sp tion statements, fo pating in this plan a | ncing availability and useful function in the d that my company has becial Provision in 1 ms SBE 2025, and assuring that each |
| Bv | Company | The "as read" Low Bidder is re Submit only one utilization pla | | • |
| • | | submitted in accordance with | | uunzauon pian shan be |
| Title | | Bureau of Small Business Ent | | cal Let Projects |

The Department of Transportation is requesting disclosure of information that is necessary to accomplish the purpose as outlined under State and Federal law. Disclosure of this information is **REQUIRED**. Failure to provide any information will result in the contract not being awarded. This form has been approved by the State Forms Manager Center.

Springfield, Illinois 62764

Local Agency

| | of Transportation | D | BE Participatio | n Statement |
|---|---|---|--|--|
| Subcontrac | tor Registration | L | etting | |
| Participation | on Statement | It | em No. | |
| (1) Instruct | ions | C | Contract | |
| be submitte | nust be completed for each disadvantaged business pared in accordance with the special provision and will be a pace is needed complete an additional form for the firm | ttached to the Ut | | |
| Pay Item No. | Description | Quantity | Unit Price | Total |
| | | | | |
| | | | | |
| | | | | |
| | | | Total | |
| (4) Commitr The undersi has agreed execute a c statement n that comple | ment igned certify that the information included herein is true to perform a commercially useful function in the work of ontract with the prime contractor. The undersigned furthary be made without prior approval from the Department and accurate information regarding actual work perforwided to the Department. | and correct, and f the contract ite ther understand t nt's Bureau of Sr ormed on this pro | I that the DBE firm m(s) listed above that no changes to nall Business Ente | n listed below and to o this erprises and |
| | - | _ | | |
| Title | Title | e | | |
| Date | Dat | e | | |
| Contact | Cor | ntact Person | | |
| Phone | Pho | one | | |
| Firm Name | Firr | n Name | | |
| Address _ | Add | dress | | |
| City/State/Z | City City | //State/Zip | | |
| | | | E | |

The Department of Transportation is requesting disclosure of information that is necessary to accomplish the statutory purpose as outlined under the state and federal law. Disclosure of this information is **REQUIRED**. Failure to provide any information will result in the contract not being awarded. This form has been approved by the State Forms Management Center.

SBE 2025 (Rev. 11/03/09)

WC

PROPOSAL ENVELOPE



PROPOSALS

for construction work advertised for bids by the Illinois Department of Transportation

| Item No. | Item No. | Item No. |
|----------|----------|----------|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

Submitted By:

| Name: | |
|-----------|--|
| Address: | |
| | |
| | |
| Phone No. | |

Bidders should use an IDOT proposal envelope or affix this form to the front of a 10" x 13" envelope for the submittal of bids. If proposals are mailed, they should be enclosed in a second or outer envelope addressed to:

Engineer of Design and Environment - Room 326 Illinois Department of Transportation 2300 South Dirksen Parkway Springfield, Illinois 62764

NOTICE

Individual bids, including Bid Bond and/or supplemental information if required, should be securely stapled.

CONTRACTOR OFFICE COPY OF CONTRACT SPECIFICATIONS

NOTICE

None of the following material needs to be returned with the bid package unless the special provisions require documentation and/or other information to be submitted.

Contract No. 93554
ADAMS County
Section 08-00307-00-TL (Quincy)
Project M-SRTS-4008(089)
Route FAU 7807 (Maine Street)
District 6 Construction Funds



SUBCONTRACTOR DOCUMENTATION

Public Acts 96-0795 and 96-0920, enacted substantial changes to the provisions of the Illinois Procurement Code (30 ILCS 500). Among the changes are provisions affecting subcontractors. The Contractor awarded this contract will be required as a material condition of the contract to implement and enforce the contract requirements applicable to subcontractors approved in accordance with article 108.01 of the Standard Specifications for Road and Bridge Construction.

If the Contractor seeks approval of subcontractors to perform a portion of the work, and approval is granted by the Department, the Contractor shall provide a copy of the subcontract to the Chief Procurement Officer within 20 calendar days after execution of the subcontract.

The subcontract shall contain the certifications required to be made by subcontractors pursuant to Article 50 of the Illinois Procurement Code. This Notice to Bidders includes a document incorporating all required subcontractor certifications and disclosures for use by the Contractor in compliance with this mandate. The document is entitled <u>State Required Ethical Standards Governing Subcontractors</u>.

STATE ETHICAL STANDARDS GOVERNING SUBCONTRACTORS

Article 50 of the Illinois Procurement Code establishes the duty of all State chief procurement officers, State purchasing officers, and their designees to maximize the value of the expenditure of public moneys in procuring goods, services, and contracts for the State of Illinois and to act in a manner that maintains the integrity and public trust of State government. In discharging this duty, they are charged by law to use all available information, reasonable efforts, and reasonable actions to protect, safeguard, and maintain the procurement process of the State of Illinois.

The certifications hereinafter made by the subcontractor are each a material representation of fact upon which reliance is placed should the Department approve the subcontractor. The chief procurement officer may terminate or void the subcontract approval if it is later determined that the bidder or subcontractor rendered a false or erroneous certification.

Section 50-2 of the Illinois Procurement Code provides that every person that has entered into a multi-year contract and every subcontractor with a multi-year subcontract shall certify, by July 1 of each fiscal year covered by the contract after the initial fiscal year, to the responsible chief procurement officer whether it continues to satisfy the requirements of Article 50 pertaining to the eligibility for a contract award. If a contractor or subcontractor is not able to truthfully certify that it continues to meet all requirements, it shall provide with its certification a detailed explanation of the circumstances leading to the change in certification status. A contractor or subcontractor that makes a false statement material to any given certification required under Article 50 is, in addition to any other penalties or consequences prescribed by law, subject to liability under the Whistleblower Reward and Protection Act for submission of a false claim.

A. Bribery

1. The Illinois Procurement Code provides:

Section 50-5. Bribery.

- (a) Prohibition. No person or business shall be awarded a contract or subcontract under this Code who:
 - (1) has been convicted under the laws of Illinois or any other state of bribery or attempting to bribe an officer or employee of the State of Illinois or any other state in that officer's or employee's official capacity; or
 - (2) has made an admission of guilt of that conduct that is a matter of record but has not been prosecuted for that conduct.
- (b) Businesses. No business shall be barred from contracting with any unit of State or local government, or subcontracting under such a contract, as a result of a conviction under this Section of any employee or agent of the business if the employee or agent is no longer employed by the business and:
 - (1) the business has been finally adjudicated not guilty; or
 - (2) the business demonstrates to the governmental entity with which it seeks to contract, or which is signatory to the contract to which the subcontract relates, and that entity finds that the commission of the offense was not authorized, requested, commanded, or performed by a director, officer, or high managerial agent on behalf of the business as provided in paragraph (2) of subsection (a) of Section 5-4 of the Criminal Code of 1961.
- (c) Conduct on behalf of business. For purposes of this Section, when an official, agent, or employee of a business committed the bribery or attempted bribery on behalf of the business and in accordance with the direction or authorization of a responsible official of the business, the business shall be chargeable with the conduct.
- (d) Certification. Every bid submitted to and contract executed by the State, and every subcontract subject to Section 20-120 of the Procurement Code shall contain a certification by the contractor or the subcontractor, respectively, that the contractor or subcontractor is not barred from being awarded a contract or subcontract under this Section and acknowledges that the chief procurement officer may declare the related contract void if any certifications required by this Section are false. A contractor who makes a false statement, material to the certification, commits a Class 3 felony.
- 2. The contractor or subcontractor certifies that it is not barred from being awarded a contract under Section 50.5.

B. Felons

1. The Illinois Procurement Code provides:

Section 50-10. Felons. Unless otherwise provided, no person or business convicted of a felony shall do business with the State of Illinois or any State agency, or enter into a subcontract, from the date of conviction until 5 years after the date of completion of the sentence for that felony, unless no person held responsible by a prosecutorial office for the facts upon which the conviction was based continues to have any involvement with the business.

2. Certification. Every bid submitted to and contract executed by the State and every subcontract subject to Section 20-120 of the Procurement Code shall contain a certification by the bidder or contractor or subcontractor, respectively, that the bidder, contractor, or subcontractor is not barred from being awarded a contract or subcontract under this Section and acknowledges that the chief procurement officer may declare the related contract void if any of the certifications required by this Section are false.

C. Debt Delinquency

1. The Illinois Procurement Code provides:

Section 50-11 and 50-12. Debt Delinquency.

The contractor or bidder or subcontractor, respectively, certifies that it, or any affiliate, is not barred from being awarded a contract or subcontract under the Procurement Code. Section 50-11 prohibits a person from entering into a contract with a State agency, or entering into a subcontract, if it knows or should know that it, or any affiliate, is delinquent in the payment of any debt to the State as defined by the Debt Collection Board. Section 50-12 prohibits a person from entering into a contract with a State agency, or entering into a subcontract, if it, or any affiliate, has failed to collect and remit Illinois Use Tax on all sales of tangible personal property into the State of Illinois in accordance with the provisions of the Illinois Use Tax Act. The bidder or contractor or subcontractor, respectively, further acknowledges that the chief procurement officer may declare the related contract void if this certification is false or if the bidder, contractor, or subcontractor, or any affiliate, is determined to be delinquent in the payment of any debt to the State during the term of the contract.

D. Prohibited Bidders, Contractors and Subcontractors

1. The Illinois Procurement Code provides:

Section 50-10.5 and 50-60(c). Prohibited bidders, contractors and subcontractors.

The bidder or contractor or subcontractor, respectively, certifies in accordance with 30 ILCS 500/50-10.5 that no officer, director, partner or other managerial agent of the contracting business has been convicted of a felony under the Sarbanes-Oxley Act of 2002 or a Class 3 or Class 2 felony under the Illinois Securities Law of 1953 or if in violation of Subsection (c) for a period of five years from the date of conviction. Every bid submitted to and contract executed by the State and every subcontract subject to Section 20-120 of the Procurement Code shall contain a certification by the bidder, contractor, or subcontractor, respectively, that the bidder, contractor, or subcontractor is not barred from being awarded a contract or subcontract under this Section and acknowledges that the chief procurement officer shall declare the related contract void if any of the certifications completed pursuant to this Section are false.

E. Section 42 of the Environmental Protection Act

The bidder or contractor or subcontractor, respectively, certifies in accordance with 30 ILCS 500/50-12 that the bidder, contractor, or subcontractor, is not barred from being awarded a contract or entering into a subcontract under this Section which prohibits the bidding on or entering into contracts with the State of Illinois or a State agency, or entering into any subcontract, that is subject to the Procurement Code by a person or business found by a court or the Pollution Control Board to have committed a willful or knowing violation of Section 42 of the Environmental Protection Act for a period of five years from the date of the order. The bidder or contractor or subcontractor, respectively, acknowledges that the chief procurement officer may declare the contract void if this certification is false.

The undersigned, on behalf of the subcontracting company, has read and understands the above certifications and makes the certifications as required by law.

| Name of Subcontracting Company | |
|------------------------------------|------|
| Name of Subcontracting Company | |
| | |
| Authorized Officer | Date |

SUBCONTRACTOR DISCLOSURES

I. DISCLOSURES

A. The disclosures hereinafter made by the subcontractor are each a material representation of fact upon which reliance is placed. The subcontractor further certifies that the Department has received the disclosure forms for each subcontract.

The chief procurement officer may void the bid, contract, or subcontract, respectively, if it is later determined that the bidder or subcontractor rendered a false or erroneous disclosure. A contractor or subcontractor may be suspended or debarred for violations of the Procurement Code. Furthermore, the chief procurement officer may void the contract or subcontract.

B. Financial Interests and Conflicts of Interest

1. Section 50-35 of the Illinois Procurement Code provides that all subcontracts with a total value of \$25,000 or more, from subcontractors identified in Section 20-120 of the Illinois Procurement Code, shall be accompanied by disclosure of the financial interests of the subcontractor. This disclosed information for the subcontractor, will be maintained as public information subject to release by request pursuant to the Freedom of Information Act, filed with the Procurement Policy Board, and shall be incorporated as a material term of the Prime Contractor's contract. Furthermore, pursuant to this Section, the Procurement Policy Board may recommend to allow or void a contract or subcontract based on a potential conflict of interest.

The financial interests to be disclosed shall include ownership or distributive income share that is in excess of 5%, or an amount greater than 60% of the annual salary of the Governor, of the subcontracting entity or its parent entity, whichever is less, unless the subcontractor is a publicly traded entity subject to Federal 10K reporting, in which case it may submit its 10K disclosure in place of the prescribed disclosure. If a subcontractor is a privately held entity that is exempt from Federal 10K reporting, but has more than 200 shareholders, it may submit the information that Federal 10K companies are required to report, and list the names of any person or entity holding any ownership share that is in excess of 5%. The disclosure shall include the names, addresses, and dollar or proportionate share of ownership of each person making the disclosure, their instrument of ownership or beneficial relationship, and notice of any potential conflict of interest resulting from the current ownership or beneficial interest of each person making the disclosure having any of the relationships identified in Section 50-35 and on the disclosure form.

The current annual salary of the Governor is \$177,412.00.

In addition, all disclosures shall indicate any other current or pending contracts, subcontracts, proposals, leases, or other ongoing procurement relationships the subcontracting entity has with any other unit of state government and shall clearly identify the unit and the contract, subcontract, proposal, lease, or other relationship.

2. <u>Disclosure Forms</u>. Disclosure Form A is attached for use concerning the individuals meeting the above ownership or distributive share requirements. Subject individuals should be covered each by one form. In addition, a second form (Disclosure Form B) provides for the disclosure of current or pending procurement relationships with other (non-IDOT) state agencies.

C. Disclosure Form Instructions

Form A Instructions for Financial Information & Potential Conflicts of Interest

If the subcontractor is a publicly traded entity subject to Federal 10K reporting, the 10K Report may be submitted to meet the requirements of Form A. If a subcontractor is a privately held entity that is exempt from Federal 10K reporting, but has more than 200 shareholders, it may submit the information that Federal 10K companies are required to report, and list the names of any person or entity holding any ownership share that is in excess of 5%. If a subcontractor is not subject to Federal 10K reporting, the subcontractor must determine if any individuals are required by law to complete a financial disclosure form. To do this, the subcontractor should answer each of the following questions. A "YES" answer indicates Form A must be completed. If the answer to each of the following questions is "NO", then the NOT APPLICABLE STATEMENT on the second page of Form A must be signed and dated by a person that is authorized to execute contracts for the subcontracting company. Note: These questions are for assistance only and are not required to be completed.

| 1. | Does anyone in your organization have a direct or beneficial ownership share of greater than 5% of the bidding entity or parent entity? YES NO |
|----|---|
| 2. | Does anyone in your organization have a direct or beneficial ownership share of less than 5%, but which has a value greater than 60% of the annual salary of the Governor? YES NO |
| 3. | Does anyone in your organization receive more than 60% of the annual salary of the Governor of the subcontracting entity's or parent entity's distributive income? YES NO |
| | (Note: Distributive income is, for these purposes, any type of distribution of profits. An annual salary is not distributive income.) |
| 4. | Does anyone in your organization receive greater than 5% of the subcontracting entity's or parent entity's total distributive income, but which is less than 60% of the annual salary of the Governor? YES NO |
| | (Note: Only one set of forms needs to be completed <u>per person per subcontract</u> even if a specific individual would require a yes answer to more than one question.) |
| | |

A "YES" answer to any of these questions requires the completion of Form A. The subcontractor must determine each individual in the subcontracting entity or the subcontracting entity's parent company that would cause the questions to be answered "Yes". Each form must be signed and dated by a person that is authorized to execute contracts for your organization. **Photocopied or stamped signatures are not acceptable**. The person signing can be, but does not have to be, the person for which the form is being completed. The subcontractor is responsible for the accuracy of any information provided.

If the answer to each of the above questions is "NO", then the <u>NOT APPLICABLE STATEMENT</u> on page 2 of Form A must be signed and dated by a person that is authorized to execute contracts for your company.

Form B: Instructions for Identifying Other Contracts & Procurement Related Information

Disclosure Form B must be completed for each subcontract submitted by the subcontracting entity. Note: Checking the <u>NOT APPLICABLE</u> <u>STATEMENT</u> on Form A <u>does not</u> allow the subcontractor to ignore Form B. Form B must be completed, checked, and dated or the subcontract will not be approved.

The Subcontractor shall identify, by checking Yes or No on Form B, whether it has any pending contracts, subcontracts, leases, bids, proposals, or other ongoing procurement relationship with any other (non-IDOT) State of Illinois agency. If "No" is checked, the subcontractor only needs to complete the check box on the bottom of Form B. If "Yes" is checked, the subcontractor must list all non-IDOT State of Illinois agency pending contracts, subcontracts, leases, bids, proposals, and other ongoing procurement relationships. These items may be listed on Form B or on an attached sheet(s). Contracts with cities, counties, villages, etc. are not considered State of Illinois agency contracts and are not to be included. Contracts or subcontracts with other State of Illinois agencies such as the Department of Natural Resources or the Capital Development Board must be included.

ILLINOIS DEPARTMENT OF TRANSPORTATION

Form A Subcontractor: Financial Information & Potential Conflicts of Interest Disclosure

| Subcontractor Name | | |
|--------------------|---------------|-----------------------------|
| | | |
| Legal Address | | |
| Legal Address | | |
| | | |
| City, State, Zip | | |
| | | |
| Telephone Number | Email Address | Fax Number (if available) |
| | 2 | · ax · ramsor (ii aramasio) |
| | | |

Disclosure of the information contained in this Form is required by the Section 50-35 of the Illinois Procurement Code (30 ILCS 500). Subcontractors desiring to enter into a subcontract of a State of Illinois contract must disclose the financial information and potential conflict of interest information as specified in this Disclosure Form. This information shall become part of the publicly available contract file. This Form A must be completed for subcontracts with a total value of \$25,000 or more, from subcontractors identified in Section 20-120 of the Illinois Procurement Code, and for all open-ended contracts. A publicly traded company may submit a 10K disclosure (or equivalent if applicable) in satisfaction of the requirements set forth in Form A. See Disclosure Form Instructions.

The current annual salary of the Governor is \$177,412.00.

DISCLOSURE OF FINANCIAL INFORMATION

1. Disclosure of Financial Information. The individual named below has an interest in the SUBCONTRACTOR (or its parent) in terms of ownership or distributive income share in excess of 5%, or an interest which has a value of more than 60% of the annual salary of the Governor. (Make copies of this form as necessary and attach a separate Disclosure Form A for each individual meeting these requirements)

| NAME: | | | |
|-------------|---|----------------|------------------------------------|
| ADDRESS | | | |
| | | | |
| | | | |
| Type of own | nership/distributable income share |): | |
| Type of own | nership/distributable income share sole proprietorship | e: Partnership | other: (explain on separate sheet) |

- **2. Disclosure of Potential Conflicts of Interest.** Check "Yes" or "No" to indicate which, if any, of the following potential conflict of interest relationships apply. If the answer to any question is "Yes", please attach additional pages and describe.
- (a) State employment, currently or in the previous 3 years, including contractual employment of services.

 Yes ____No ___

If your answer is yes, please answer each of the following questions.

- Are you currently an officer or employee of either the Capitol Development Board or the Illinois State
 Toll Highway Authority?
 Yes ___No __
- 2. Are you currently appointed to or employed by any agency of the State of Illinois? If you are currently appointed to or employed by any agency of the State of Illinois, and your annual salary exceeds 60% of the annual salary of the Governor, provide the name the State agency for which you are employed and your annual salary. ______

| If you are currently appointed to or employed by any agency of the salary exceeds 60% of the annual salary of the Governor, are you (i) more than 7 1/2% of the total distributable income of your fir corporation, or (ii) an amount in excess of 100% of the annual sala | entitled to receive m, partnership, association or |
|--|--|
| 4. If you are currently appointed to or employed by any agency of the salary exceeds 60% of the annual salary of the Governor, are you or minor children entitled to receive (i) more than 15 % in the ag income of your firm, partnership, association or corporation, or (ii) the salary of the Governor? | and your spouse gregate of the total distributable |
| (b) State employment of spouse, father, mother, son, or daughter, including in the previous 2 years. | • • |
| If your answer is yes, please answer each of the following questions. | YesNo |
| Is your spouse or any minor children currently an officer or employ Board or the Illinois State Toll Highway Authority? | ree of the Capitol Development YesNo |
| 2. Is your spouse or any minor children currently appointed to or emp of Illinois? If your spouse or minor children is/are currently a agency of the State of Illinois, and his/her annual salary exce annual salary of the Governor, provide the name of your spouse ar of the State agency for which he/she is employed and his/her annual salary. | appointed to or employed by any eeds 60% of the nd/or minor children, the name |
| 3. If your spouse or any minor children is/are currently appointed to a State of Illinois, and his/her annual salary exceeds 60% of the annuare you entitled to receive (i) more than 71/2% of the total distribut firm, partnership, association or corporation, or (ii) an amount annual salary of the Governor? | ual salary of the Governor, able income of your |
| 4. If your spouse or any minor children are currently appointed to or State of Illinois, and his/her annual salary exceeds 60% of the annuare you and your spouse or minor children entitled to receive (i) aggregate of the total distributable income of your firm, partnersh (ii) an amount in excess of two times the salary of the Governor? | ual salary of the Governor, more than 15 % in the |
| | YesNo |
| (c) Elective status; the holding of elective office of the State of Illinois, the government authorized by the Constitution of the State of Illin Illinois currently or in the previous 3 years. | |
| (d) Relationship to anyone holding elective office currently or in the previous 2 son, or daughter. | 2 years; spouse, father, mother, YesNo |
| (e) Appointive office; the holding of any appointive government office of the S America, or any unit of local government authorized by the Constitution of of the State of Illinois, which office entitles the holder to compensation in the discharge of that office currently or in the previous 3 years. | the State of Illinois or the statutes |
| (f) Relationship to anyone holding appointive office currently or in the previous son, or daughter. | s 2 years; spouse, father, mother, YesNo |
| (g) Employment, currently or in the previous 3 years, as or by any registered | lobbyist of the State government. YesNo |
| | |

| (h) | Relationship to anyone who is or was a registered lobbyist in the previous 2 years; spouse, father, mother, son, or daughter. YesNo | |
|----------------|--|----|
| (i) | Compensated employment, currently or in the previous 3 years, by any registered election or reelection committee registered with the Secretary of State or any county clerk of the State of Illinois, or any political action committee registered with either the Secretary of State or the Federal Board of Elections. Yes No | |
| (j) | Relationship to anyone; spouse, father, mother, son, or daughter; who was a compensated employee in the ast 2 years by any registered election or re-election committee registered with the Secretary of State or any county clerk of the State of Illinois, or any political action committee registered with either the Secretary of State or the Federal Board of Elections. | |
| | YesNo | |
| 3. | Communication Disclosure. | |
| Se en su | close the name and address of each lobbyist and other agent of the bidder or offeror who is not identified in a ction 2 of this form, who is has communicated, is communicating, or may communicate with any State officer cloyee concerning the bid or offer. This disclosure is a continuing obligation and must be promptly plemented for accuracy throughout the process and throughout the term of the contract. If no person is ntified, enter "None" on the line below: | or |
| | Name and address of person(s): | |
| | | |
| | | |
| | | _ |

4. Debarment Disclosure. For each of the persons identified under Sections 2 and 3 of this form, disclose whether any of the following has occurred within the previous 10 years: debarment from contracting with any governmental entity; professional licensure discipline; bankruptcies; adverse civil judgments and administrative findings; and criminal felony convictions. This disclosure is a continuing obligation and must be promptly

supplemented for accuracy throughout the procurement process and term of the contract. If no person is identified, enter "None" on the line below: Name of person(s): Nature of disclosure: APPLICABLE STATEMENT This Disclosure Form A is submitted on behalf of the INDIVIDUAL named on previous page. Under penalty of perjury, I certify the contents of this disclosure to be true and accurate to the best of my knowledge. Completed by: Signature of Individual or Authorized Officer Date **NOT APPLICABLE STATEMENT** Under penalty of perjury, I have determined that no individuals associated with this organization meet the criteria that would require the completion of this Form A. This Disclosure Form A is submitted on behalf of the SUBCONTRACTOR listed on the previous page. Signature of Authorized Officer Date

ILLINOIS DEPARTMENT OF TRANSPORTATION

Form B Subcontractor: Other Contracts & Procurement Related Information Disclosure

| Subcontractor Name | | | | | | |
|--|---------------------------------|-------------------------------|--|--|--|--|
| Legal Address | | | | | | |
| City, State, Zip | | | | | | |
| Telephone Number | Email Address | Fax Number (if available) | | | | |
| Disclosure of the information contained in this Form is required by the Section 50-35 of the Illinois Procurement Act (30 ILCS 500). This information shall become part of the publicly available contract file. This Form B must be completed for subcontracts with a total value of \$25,000 or more, from subcontractors identified in Section 20-120 of the Illinois Procurement Code, and for all open-ended contracts. | | | | | | |
| DISCLOSURE OF OTHER CONTRA | CTS, SUBCONTRACTS, AND PRO | OCUREMENT RELATED INFORMATION | | | | |
| 1. Identifying Other Contracts & Procurement Related Information. The SUBCONTRACTOR shall identify whether it has any pending contracts, subcontracts, including leases, bids, proposals, or other ongoing procurement relationship with any other State of Illinois agency: Yes No If "No" is checked, the subcontractor only needs to complete the signature box on the bottom of this page. | | | | | | |
| 2. If "Yes" is checked. Identify each such information such as bid or project number (a INSTRUCTIONS: | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| THE FOLLO | WING STATEMENT MUST BE CH | IECKED | | | | |
| | | | | | | |
| | Signature of Authorized Officer | Date | | | | |

Illinois Department of Transportation

NOTICE TO BIDDERS

- 1. TIME AND PLACE OF OPENING BIDS. Sealed proposals for the improvement described herein will be received by the Department of Transportation at the Harry R. Hanley Building, 2300 South Dirksen Parkway, in Springfield, Illinois until 10:00 o'clock a.m., September 23, 2011. All bids will be gathered, sorted, publicly opened and read in the auditorium at the Department of Transportation's Harry R. Hanley Building shortly after the 10:00 a.m. cut off time.
- **2. DESCRIPTION OF WORK**. The proposed improvement is identified and advertised for bids in the Invitation for Bids as:

Contract No. 93554
ADAMS County
Section 08-00307-00-TL (Quincy)
Project M-SRTS-4008(089)
Route FAU 7807 (Maine Street)
District 6 Construction Funds

Reconstruct the intersection of Maine Street at 33rd Street to include sidewalks and traffic signal replacement and the resurfacing of Maine Street from 30th Street to 36th Street in the city of Quincy.

- 3. INSTRUCTIONS TO BIDDERS. (a) This Notice, the invitation for bids, proposal and letter of award shall, together with all other documents in accordance with Article 101.09 of the Standard Specifications for Road and Bridge Construction, become part of the contract. Bidders are cautioned to read and examine carefully all documents, to make all required inspections, and to inquire or seek explanation of the same prior to submission of a bid.
 - (b) State law, and, if the work is to be paid wholly or in part with Federal-aid funds, Federal law requires the bidder to make various certifications as a part of the proposal and contract. By execution and submission of the proposal, the bidder makes the certification contained therein. A false or fraudulent certification shall, in addition to all other remedies provided by law, be a breach of contract and may result in termination of the contract.
- 4. AWARD CRITERIA AND REJECTION OF BIDS. This contract will be awarded to the lowest responsive and responsible bidder considering conformity with the terms and conditions established by the Department in the rules, Invitation for Bids and contract documents. The issuance of plans and proposal forms for bidding based upon a prequalification rating shall not be the sole determinant of responsibility. The Department reserves the right to determine responsibility at the time of award, to reject any or all proposals, to readvertise the proposed improvement, and to waive technicalities.

By Order of the Illinois Department of Transportation

Gary Hannig, Secretary

CONTRACT 93554

INDEX FOR SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS

Adopted January 1, 2011

This index contains a listing of SUPPLEMENTAL SPECIFICATIONS and frequently used RECURRING SPECIAL PROVISIONS.

ERRATA

Standard Specifications for Road and Bridge Construction (Adopted 1-1-07) (Revised 1-1-11)

SUPPLEMENTAL SPECIFICATIONS

| Std. S | <u>Page No.</u> | |
|---------|---|--|
| 201 | Clearing, Tree Removal and Protection | |
| 205 | Embankment | |
| 251 | Mulch | |
| 253 | Planting Woody Plants | |
| 280 | Temporary Erosion Control | |
| 406 | Hot-Mix Asphalt Binder and Surface Course | |
| 420 | Portland Cement Concrete Pavement | |
| 443 | Reflective Crack Control Treatment | |
| 501 | Removal of Existing Structures | |
| 502 | Excavation for Structures | |
| 503 | Concrete Structures | |
| 504 | Precast Concrete Structures | |
| 505 | Steel Structures | |
| 508 | Reinforcement Bars | |
| 540 | Box Culverts | |
| 581 | Waterproofing Membrane System | |
| 606 | Concrete Gutter, Curb, Median, and Paved Ditch | |
| 630 | Steel Plate Beam Guardrail | |
| 633 | Removing and Reerecting Guardrail and Terminals | |
| 637 | Concrete Barrier | |
| 664 | Chain Link Fence | |
| 669 | Removal and Disposal of Regulated Substances | |
| 672 | Sealing Abandoned Water Wells | |
| 701 | Work Zone Traffic Control and Protection | |
| 720 | Sign Panels and Appurtenances | |
| 721 | Sign Panel Overlay | |
| 722 | Demountable Sign Legend Characters and Arrows | |
| 726 | Mile Post Marker Assembly | |
| 733 | Overhead Sign Structures | |
| 780 | Pavement Striping | |
| 782 | Prismatic Reflectors | |
| 783 | Pavement Marking and Marker Removal | |
| 801 | Electrical Requirements | |
| 805 | Electrical Service Installation – Traffic Signals | |
| 821 | Roadway Luminaires | |
| 836 | Pole Foundation | |
| 838 | Breakaway Devices | |
| 843 | Removal of Navigational Obstruction Warning Lighting System | |
| 862 | Uninterruptable Power Supply | |
| 873 | Electric Cable | |
| 878 | Traffic Signal Concrete Foundation | |
| 1003 | Fine Aggregates | |
| 1003 | Coarse Aggregates | |
| | Stone and Broken Concrete | |
| 1005 | | |
| 1006 | Metals | |
| 1008 | Structural Steel Coatings | |
| 1010 | Finely Divided Materials | |
| 1020 | Portland Cement Concrete | |
| 4111777 | L ANCESTA L UEDA MISTATISME | |

| 1024 | Nonshrink Grout | 78 |
|------|-------------------------------------|-----|
| 1026 | Concrete Sealer | 79 |
| 1030 | Hot-Mix Asphalt | 80 |
| 1032 | Bituminous Materials | 87 |
| 1042 | Precast Concrete Products | 90 |
| 1062 | Reflective Crack Control System | 92 |
| 1069 | Pole and Tower | 94 |
| 1074 | Control Equipment | 97 |
| 1076 | Wire and Cable | 102 |
| 1077 | Post and Foundation | 103 |
| 1080 | Fabric Materials | 105 |
| 1081 | Materials for Planting | 106 |
| 1083 | Elastomeric Bearings | 108 |
| 1090 | Sign Base | 109 |
| 1091 | Sign Face | 111 |
| 1092 | Sign Legend and Supplemental Panels | 119 |
| 1093 | Sign Supports | 120 |
| 1094 | Overhead Sign Structures | 122 |
| 1095 | Pavement Markings | 128 |
| 1097 | Reflectors | 136 |
| 1101 | General Equipment | 137 |
| 1102 | Hot-Mix Asphalt Equipment | 138 |
| 1103 | Portland Cement Concrete Equipment | 140 |
| 1105 | Pavement Marking Equipment | 141 |
| 1106 | Work Zone Traffic Control Devices | 143 |
| | | |

RECURRING SPECIAL PROVISIONS

The following RECURRING SPECIAL PROVISIONS indicated by an "X" are applicable to this contract and are included by reference:

| | CK S | SHEET# | <u>AGE</u> |
|------------|------|--|------------|
| <u>NO.</u> | v | Additional State Deguirements For Foderal Aid Construction Contracts | |
| 1 | Х | Additional State Requirements For Federal-Aid Construction Contracts (Eff. 2-1-69) (Rev. 1-1-10) | 145 |
| 2 | x | Subletting of Contracts (Federal-Aid Contracts) (Eff. 1-1-88) (Rev. 5-1-93) | 148 |
| 3 | X | EEO (Eff. 7-21-78) (Rev. 11-18-80) | 149 |
| 4 | ^ | Specific Equal Employment Opportunity Responsibilities | |
| • | | Non Federal-Aid Contracts (Eff. 3-20-69) (Rev. 1-1-94) | 159 |
| 5 | | Required Provisions - State Contracts (Eff. 4-1-65) (Rev. 1-1-10) | 164 |
| 6 | | Reserved | 169 |
| 7 | | Reserved | 170 |
| 8 | | Haul Road Stream Crossings, Other Temporary Stream Crossings, and | |
| | | In-Stream Work Pads (Eff. 1-2-92) (Rev. 1-1-98) | 171 |
| 9 | | Construction Layout Stakes Except for Bridges (Eff. 1-1-99) (Rev. 1-1-07) | |
| 10 | Χ | Construction Layout Stakes (Eff. 5-1-93) (Rev. 1-1-07) | 175 |
| 11 | | Use of Geotextile Fabric for Railroad Crossing (Eff. 1-1-95) (Rev. 1-1-07) | |
| 12 | | Subsealing of Concrete Pavements (Eff. 11-1-84) (Rev. 1-1-07) | |
| 13 | | Hot-Mix Asphalt Surface Correction (Eff. 11-1-87) (Rev. 1-1-09) | 104 |
| 14 | | Pavement and Shoulder Resurfacing (Eff. 2-1-00) (Rev. 1-1-09) | 100 |
| 15 | | PCC Partial Depth Hot-Mix Asphalt Patching (Eff. 1-1-98) (Rev. 1-1-07) | 190 |
| 16 | | Patching with Hot-Mix Asphalt Overlay Removal (Eff. 10-1-95) (Rev. 1-1-07) | 100 |
| 17 | | PVC Pipeliner (Eff. 4-1-04) (Rev. 1-1-07) | |
| 18 19 | | Pipe Underdrains (Eff. 9-9-87) (Rev. 1-1-07) | |
| 20 | | Guardrail and Barrier Wall Delineation (Eff. 12-15-93) (Rev. 1-1-97) | |
| 21 | | Bicycle Racks (Eff. 4-1-94) (Rev. 1-1-07) | |
| 22 | | Temporary Modular Glare Screen System (Eff. 1-1-00) (Rev. 1-1-07) | 200 |
| 23 | | Temporary Portable Bridge Traffic Signals (Eff. 8-1-03) (Rev. 1-1-07) | |
| 24 | | Work Zone Public Information Signs (Eff. 9-1-02) (Rev. 1-1-07) | |
| 25 | | Night Time Inspection of Roadway Lighting (Eff. 5-1-96) | |
| 26 | | English Substitution of Metric Bolts (Eff. 7-1-96) | |
| 27 | | English Substitution of Metric Reinforcement Bars (Eff. 4-1-96) (Rev. 1-1-03) | 207 |
| 28 | | Calcium Chloride Accelerator for Portland Cement Concrete (Eff. 1-1-01) | |
| 29 | | Reserved | |
| 30 | Х | Quality Control of Concrete Mixtures at the Plant | |
| | | (Eff. 8-1-00) (Rev. 1-1-11) | 210 |
| 31 | | Quality Control/Quality Assurance of Concrete Mixtures | |
| | | (Eff. 4-1-92) (Rev. 1-1-11) | 218 |
| 32 | | Asbestos Bearing Pad Removal (Eff. 11-1-03) | 230 |
| 33 | | Asbestos Hot-Mix Asphalt Surface Removal (Eff. 6-1-89) (Rev. 1-1-09) | 231 |
| | | LOCAL ROADS AND STREETS RECURRING SPECIAL PROVISIONS | |
| | | LUCAL ROADS AND STREETS RECORDING SPECIAL PROVISIONS | |
| LRS | 1 | Reserved | 233 |
| LRS | | Furnished Excavation (Eff. 1-1-99) (Rev. 1-1-07) | . 234 |
| LRS | | Work Zone Traffic Control (Eff. 1-1-99) (Rev. 1-1-10) | . 235 |
| LRS | | ☐ Flaggers in Work Zones (Eff. 1-1-99) (Rev 1-1-07) | |
| LRS | | Contract Claims (Eff. 1-1-02) (Rev. 1-1-07) | . 237 |
| LRS | | Bidding Requirements and Conditions for Contract Proposals (Eff. 1-1-02) | 238 |
| LRS | 7 | Bidding Requirements and Conditions for Material Proposals (Eff. 1-1-02) (Rev. 1-1-03) | 244 |
| LRS | 8 | Reserved | . 250 |
| LRS | 9 | ☐ Bituminous Surface Treatments (Eff. 1-1-99) (Rev. 1-1-11) | 251 |
| LRS | | Reserved | . 252 |
| LRS | | Employment Practices (Eff. 1-1-99) | . 253 |
| LRS | | Wages of Employees on Public Works (Eff. 1-1-99) (Rev. 1-1-10) | . 255 |
| LRS | | Selection of Labor (Eff. 1-1-99) | . 256 |
| LRS | | Paving Brick and Concrete Paver Pavements and Sidewalks (Eff. 1-1-04) (Rev. 1-1-09) | . 257 |
| LRS | | Partial Payments (Eff. 1-1-07) | 260 |
| LRS | | Protests on Local Lettings (Eff. 1-1-07) | 261 |
| LRS | 17 | Substance Abuse Prevention Program (Eff. 1-1-08) (Rev. 1-8-08) | 262 |

Route: Section: Project No.: FAU 7807 / FAU 7829 08-00307-00-TL M-SRTS-4008(089)

County:

Adams Local Agency: City of Quincy

TABLE OF CONTNENTS

| DESCRIPTION OF WORK | . 1 |
|--|---------|
| COMPLETION DATE | . 1 |
| CONTRACTOR COOPERATION | . 1 |
| TRAFFIC CONTROL PLAN | . 2-3 |
| LANDSCAPING | 4 |
| SAW CUTTING | . 4 |
| WATER MAIN | . 4-6 |
| WATER VALVES TO BE ADJUSTED | . 6 |
| FIRE HYDRANTS TO BE REMOVED AND REPLACED | . 6-7 |
| FULL-ACTUATED CONTROLLER AND TYPE IV CABINET | |
| PVC CONDUIT | . 8 |
| STEEL COMBINATION MAST ARM ASSEMBLY AND POLE | . 8 |
| PEDESTRIAN SIGNAL HEAD, POLYCARBONATE, LED, BRACKET MOUNTED WITH COUNTDOWN TIMER | . 8-9 |
| REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT | . 9 |
| EMERGENCY VEHICLE SIGNAL CONTROL SYSTEM | . 9-10 |
| SEEDING, CLASS 1, SPECIAL | .11 |
| CONCRETE CURB, TYPE B (SPECIAL) | . 11 |
| CHAIN LINK FENCE TO BE REMOVED AND RE-ERECTED | . 11 |
| PEDESTRIAN PUSH-BUTTON, SPECIAL | 12 |
| DETECTABLE WARNINGS (SPECIAL) | 12 |
| VIDEO VEHICLE DETECTION YSTEM | . 13-16 |
| PAINT CURB | 16 |
| CTATUS OF LITH ITIES TO BE AD ILISTED | 17 |

INDEX LOCAL ROADS AND STREETS SPECIAL PROVISIONS

| LR SD 12 □ Slab Movement Detection Device Nov. 11, 1984 Jan. 1, 2007 LR SD 13 □ Required Cold Milled Surface Texture Nov. 1, 1987 Jan. 1, 2007 LR 105 18 □ Cooperation with Utilities Jan. 1, 1999 Jan. 1, 2007 LR 107-2 □ Railroad Protective Liability Insurance for Local Lettings Mar. 1, 2005 Aug. 1, 2007 LR 107-4 21 □ Insurance Feb. 1, 2007 Aug. 1, 2007 LR 107-6 □ Selection of Labor Aug. 1, 2010 Aug. 1, 2010 LR 108 □ Combination Bids Jan. 1, 1994 Mar. 1, 2005 LR 212 □ Shaping Roadway Aug. 1, 1969 Jan. 1, 2007 LR 355-1 □ Asphalt Stabilized Base Course, Road Mix or Traveling Plant Mix Oct. 1, 1973 Jan. 1, 2007 LR 400-1 □ Bituminous Streated Earth Surface Jan. 1, 2007 Jan. 1, 2007 LR 403-2 □ Bituminous Streated Earth Surface Jan. 1, 2007 Jan. 1, 2007 LR 406 □ Filling HMA Core Holes with Non-shrink Grout< | LR# | Pg# | | Special Provision Title | Effective | Revised |
|---|-----------|-----|-------------|---|---------------|--------------|
| R SD406 | LR SD 12 | • | | Slab Movement Detection Device | Nov. 11, 1984 | Jan. 1, 2007 |
| LR 105 18 Cooperation with Utilities Jan. 1, 1999 Jan. 1, 2007 LR 107-4 21 Insurance Feb. 1, 2007 Aug. 1, 2006 LR 107-6 Selection of Labor Aug. 1, 2010 Aug. 1, 2010 LR 108 Combination Bids Jan. 1, 1994 Mar. 1, 2005 LR 212 Shaping Roadway Aug. 1, 1969 Jan. 1, 2007 LR 355-1 Asphalt Stabilized Base Course, Road Mix or Traveling Plant Mix Oct. 1, 1973 Jan. 1, 2007 LR 400-1 Bituminous Treated Earth Surface Jan. 1, 2007 Jan. 1, 2008 LR 400-2 Bituminous Surface Mixture (Class B) Jan. 1, 2008 LR 403-2 Bituminous Flot Mix Sand Seal Coat Feb. 20, 1963 Jan. 1, 2007 LR 406 Filling HMA Core Holes with Non-shrink Grout Jan. 1, 2008 Jan. 1, 2007 LR 420 PCC Pavement (Special) May 12, 1964 Jan. 2, 2007 LR 451 Crack Filling Bituminous Pavement with Fiber-Asphalt Oct. 1, 1991 Jan. 1, 2007 LR 503-2 Furnishing Class SI Concrete Oct. 1, 1993 Jan. 1, 2007 LR 503-2 Fur | LR SD 13 | | | Required Cold Milled Surface Texture | Nov. 1, 1987 | Jan. 1, 2007 |
| Railroad Protective Liability Insurance for Local Lettings Mar. 1, 2005 Jan. 1, 2006 | LR SD406 | | | Safety Edge | April 1, 2011 | |
| Railroad Protective Liability Insurance for Local Lettings Mar. 1, 2005 Jan. 1, 2007 | LR 105 | 18 | \boxtimes | Cooperation with Utilities | Jan. 1, 1999 | Jan. 1, 2007 |
| LR 107-6 Selection of Labor Aug. 1, 2010 LR 108 Combination Bids Jan. 1, 1994 Mar. 1, 2005 LR 212 Shaping Roadway Aug. 1, 1969 Jan. 1, 2002 LR 355-1 Asphalt Stabilized Base Course, Road Mix or Traveling Plant Mix Oct. 1, 1973 Jan. 1, 2007 LR 355-2 Asphalt Stabilized Base Course, Plant Mix Feb. 20, 1963 Jan. 1, 2007 LR 400-1 Bituminous Treated Earth Surface Jan. 1, 2007 Jan. 1, 2008 LR 400-2 Bituminous Surface Mixture (Class B) Jan. 1, 2008 LR 402 Salt Stabilized Surface Course Feb. 20, 1963 Jan. 1, 2007 LR 403-2 Bituminous Hot Mix Sand Seal Coat Aug. 1, 1969 Jan. 1, 2007 LR 406 Filling HMA Core Holes with Non-shrink Grout Jan. 1, 2008 PCC Pavement (Special) May 12, 1964 Jan. 1, 2007 LR 442 Bituminous Patching Mixtures for Maintenance Use Jan. 1, 2004 Jun. 1, 2007 LR 503-1 Crack Filling Bituminous Pavement with Fiber-Asphalt Oct. 1, 1973 Jan. 1, 2007 LR 503-2 Furnishing Class SI Concrete (Short Load) Jan. 1, 1989 Jan. 1, 2002 LR 542 Pipe Culverts, Type (Furni | LR 107-2 | | | Railroad Protective Liability Insurance for Local Lettings | Mar. 1, 2005 | Jan. 1, 2006 |
| LR 107-6 Selection of Labor Aug. 1, 2010 LR 108 Combination Bids Jan. 1, 1994 Mar. 1, 2005 LR 212 Shaping Roadway Aug. 1, 1969 Jan. 1, 2002 LR 355-1 Asphalt Stabilized Base Course, Road Mix or Traveling Plant Mix Oct. 1, 1973 Jan. 1, 2007 LR 355-2 Asphalt Stabilized Base Course, Plant Mix Feb. 20, 1963 Jan. 1, 2007 LR 400-1 Bituminous Treated Earth Surface Jan. 1, 2007 Jan. 1, 2008 LR 400-2 Bituminous Surface Mixture (Class B) Jan. 1, 2008 LR 402 Salt Stabilized Surface Course Feb. 20, 1963 Jan. 1, 2007 LR 403-2 Bituminous Hot Mix Sand Seal Coat Aug. 1, 1969 Jan. 1, 2007 LR 406 Filling HMA Core Holes with Non-shrink Grout Jan. 1, 2008 PCC Pavement (Special) May 12, 1964 Jan. 1, 2007 LR 442 Bituminous Patching Mixtures for Maintenance Use Jan. 1, 2004 Jun. 1, 2007 LR 503-1 Crack Filling Bituminous Pavement with Fiber-Asphalt Oct. 1, 1973 Jan. 1, 2007 LR 503-2 Furnishing Class SI Concrete (Short Load) Jan. 1, 1989 Jan. 1, 2002 LR 542 Pipe Culverts, Type (Furni | LR 107-4 | 21 | \boxtimes | Insurance | Feb. 1, 2007 | Aug. 1, 2007 |
| LR 212 Shaping Roadway Aug. 1, 1969 Jan. 1, 2002 LR 355-1 Asphalt Stabilized Base Course, Road Mix or Traveling Plant Mix Oct. 1, 1973 Jan. 1, 2007 LR 355-2 Asphalt Stabilized Base Course, Plant Mix Feb. 20, 1963 Jan. 1, 2007 LR 400-1 Bituminous Treated Earth Surface Jan. 1, 2007 Jan. 1, 2008 LR 400-2 Bituminous Surface Mixture (Class B) Jan. 1, 2008 LR 402 Salt Stabilized Surface Course Feb. 20, 1963 Jan. 1, 2007 LR 403-2 Bituminous Hot Mix Sand Seal Coat Aug. 1, 1969 Jan. 1, 2007 LR 406 Filling HMA Core Holes with Non-shrink Grout Jan. 1, 2008 Jan. 1, 2008 LR 420 PCC Pavement (Special) May 12, 1964 Jan. 2, 2007 LR 442 Bituminous Patching Mixtures for Maintenance Use Jan. 1, 2004 Jun. 1, 2007 LR 451 Crack Filling Bituminous Pavement with Fiber-Asphalt Oct. 1, 1991 Jan. 1, 2007 LR 503-2 Furnishing Class SI Concrete Oct. 1, 1973 Jan. 1, 2002 LR 542 Pipe Culverts, Type (Furnished) Sep. 1, 1964 Jan. 1, 2007 LR 702 Calcium Chloride Applied Jan. 1, 2004 | LR 107-6 | | | Selection of Labor | | |
| Asphalt Stabilized Base Course, Road Mix or Traveling Plant Mix | LR 108 | | | Combination Bids | | Mar. 1, 2005 |
| LR 355-2 Asphalt Stabilized Base Course, Plant Mix Feb. 20, 1963 Jan. 1, 2007 LR 400-1 Bituminous Treated Earth Surface Jan. 1, 2007 Jan. 1, 2008 LR 400-2 Bituminous Surface Mixture (Class B) Jan. 1, 2008 LR 402 Salt Stabilized Surface Course Feb. 20, 1963 Jan. 1, 2007 LR 403-2 Bituminous Hot Mix Sand Seal Coat Aug. 1, 1969 Jan. 1, 2007 LR 406 Filling HMA Core Holes with Non-shrink Grout Jan. 1, 2008 LR 420 PCC Pavement (Special) May 12, 1964 Jan. 2, 2007 LR 442 Bituminous Patching Mixtures for Maintenance Use Jan. 1, 2004 Jun. 1, 2007 LR 451 Crack Filling Bituminous Pavement with Fiber-Asphalt Oct. 1, 1991 Jan. 1, 2007 LR 503-1 Furnishing Class SI Concrete Oct. 1, 1973 Jan. 1, 2007 LR 503-2 Furnishing Class SI Concrete (Short Load) Jan. 1, 1989 Jan. 1, 2002 LR 503-2 Pipe Culverts, Type (Furnished) Sep. 1, 1964 Jan. 1, 2007 LR 663 Calcium Chloride Applied Jun. 1, 1958 Jan. 1, 2007 LR 702 Co | LR 212 | | | Shaping Roadway | | Jan. 1, 2002 |
| LR 400-1 Bituminous Treated Earth Surface Jan. 1, 2007 Jan. 1, 2008 LR 400-2 Bituminous Surface Mixture (Class B) Jan. 1, 2008 LR 402 Salt Stabilized Surface Course Feb. 20, 1963 Jan. 1, 2007 LR 403-2 Bituminous Hot Mix Sand Seal Coat Aug. 1, 1969 Jan. 1, 2007 LR 406 Filling HMA Core Holes with Non-shrink Grout Jan. 1, 2008 LR 420 PCC Pavement (Special) May 12, 1964 Jan. 2, 2007 LR 442 Bituminous Patching Mixtures for Maintenance Use Jan. 1, 2004 Jun. 1, 2007 LR 451 Crack Filling Bituminous Pavement with Fiber-Asphalt Oct. 1, 1991 Jan. 1, 2007 LR 503-1 Furnishing Class SI Concrete Oct. 1, 1973 Jan. 1, 2002 LR 503-2 Furnishing Class SI Concrete (Short Load) Jan. 1, 1989 Jan. 1, 2002 LR 542 Pipe Culverts, Type (Furnished) Sep. 1, 1964 Jan. 1, 2007 LR 663 Calcium Chloride Applied Jun. 1, 1958 Jan. 1, 2007 LR 1004 Coarse Aggregate for Bituminous Surface Treatment Jan. 1, 2004 Jun. 1, 2007 LR 1030-1 Emulsified Asphalts Jan. 1, 2007 Feb. 7, 2008 | LR 355-1 | | | Asphalt Stabilized Base Course, Road Mix or Traveling Plant Mix | Oct. 1, 1973 | Jan. 1, 2007 |
| Bituminous Surface Mixture (Class B) | LR 355-2 | | | Asphalt Stabilized Base Course, Plant Mix | Feb. 20, 1963 | Jan. 1, 2007 |
| LR 402 Salt Stabilized Surface Course Feb. 20, 1963 Jan. 1, 2007 LR 403-2 Bituminous Hot Mix Sand Seal Coat Aug. 1, 1969 Jan. 1, 2007 LR 406 Filling HMA Core Holes with Non-shrink Grout Jan. 1, 2008 LR 420 PCC Pavement (Special) May 12, 1964 Jan. 2, 2007 LR 442 Bituminous Patching Mixtures for Maintenance Use Jan. 1, 2004 Jun. 1, 2007 LR 451 Crack Filling Bituminous Pavement with Fiber-Asphalt Oct. 1, 1991 Jan. 1, 2007 LR 503-1 Furnishing Class SI Concrete Oct. 1, 1973 Jan. 1, 2002 LR 503-2 Furnishing Class SI Concrete (Short Load) Jan. 1, 1989 Jan. 1, 2002 LR 542 Pipe Culverts, Type (Furnished) Sep. 1, 1964 Jan. 1, 2007 LR 663 Calcium Chloride Applied Jun. 1, 1958 Jan. 1, 2007 LR 702 Construction and Maintenance Signs Jan. 1, 2004 Jun. 1, 2007 LR 1030 Growth Curve Mar. 1, 2008 Jan. 1, 2007 LR 1032-1 Emulsified Asphalts Jan. 1, 2007 Feb. 7, 2008 LR 1095 Fast-Dry Pavement Marking Paint Black (Lead Free Waterborne April 1, 2011 < | LR 400-1 | | | Bituminous Treated Earth Surface | Jan. 1, 2007 | Jan. 1, 2008 |
| LR 403-2 Bituminous Hot Mix Sand Seal Coat Aug. 1, 1969 Jan. 1, 2007 LR 406 Filling HMA Core Holes with Non-shrink Grout Jan. 1, 2008 LR 420 PCC Pavement (Special) May 12, 1964 Jan. 2, 2007 LR 442 Bituminous Patching Mixtures for Maintenance Use Jan. 1, 2004 Jun. 1, 2007 LR 451 Crack Filling Bituminous Pavement with Fiber-Asphalt Oct. 1, 1991 Jan. 1, 2007 LR 503-1 Furnishing Class SI Concrete Oct. 1, 1973 Jan. 1, 2002 LR 503-2 Furnishing Class SI Concrete (Short Load) Jan. 1, 1989 Jan. 1, 2002 LR 542 Pipe Culverts, Type (Furnished) Sep. 1, 1964 Jan. 1, 2007 LR 663 Calcium Chloride Applied Jun. 1, 1958 Jan. 1, 2007 LR 702 Construction and Maintenance Signs Jan. 1, 2004 Jun. 1, 2007 LR 1030 Coarse Aggregate for Bituminous Surface Treatment Jan. 1, 2002 Jan. 1, 2007 LR 1032-1 Emulsified Asphalts Jan. 1, 2007 Feb. 7, 2008 LR 1095 Fast-Dry Pavement Marking Paint Black (Lead Free Waterborne April 1, 2011 | LR 400-2 | | | Bituminous Surface Mixture (Class B) | Jan. 1, 2008 | |
| LR 406 Filling HMA Core Holes with Non-shrink Grout Jan. 1, 2008 LR 420 PCC Pavement (Special) May 12, 1964 Jan. 2, 2007 LR 442 Bituminous Patching Mixtures for Maintenance Use Jan. 1, 2004 Jun. 1, 2007 LR 451 Crack Filling Bituminous Pavement with Fiber-Asphalt Oct. 1, 1991 Jan. 1, 2007 LR 503-1 Furnishing Class SI Concrete Oct. 1, 1973 Jan. 1, 2002 LR 503-2 Furnishing Class SI Concrete (Short Load) Jan. 1, 1989 Jan. 1, 2002 LR 542 Pipe Culverts, Type (Furnished) Sep. 1, 1964 Jan. 1, 2007 LR 663 Calcium Chloride Applied Jun. 1, 1958 Jan. 1, 2007 LR 702 Construction and Maintenance Signs Jan. 1, 2004 Jun. 1, 2007 LR 1004 Coarse Aggregate for Bituminous Surface Treatment Jan. 1, 2002 Jan. 1, 2007 LR 1030 Growth Curve Mar. 1, 2008 Jan. 1, 2010 LR 1032-1 Emulsified Asphalts Jan. 1, 2007 Feb. 7, 2008 LR 1095 Fast-Dry Pavement Marking Paint Black (Lead Free Waterborne April 1, 2011 | LR 402 | | | Salt Stabilized Surface Course | · · | • |
| LR 420 PCC Pavement (Special) May 12, 1964 Jan. 2, 2007 LR 442 Bituminous Patching Mixtures for Maintenance Use Jan. 1, 2004 Jun. 1, 2007 LR 451 Crack Filling Bituminous Pavement with Fiber-Asphalt Oct. 1, 1991 Jan. 1, 2007 LR 503-1 Furnishing Class SI Concrete Oct. 1, 1973 Jan. 1, 2002 LR 503-2 Furnishing Class SI Concrete (Short Load) Jan. 1, 1989 Jan. 1, 2002 LR 542 Pipe Culverts, Type (Furnished) Sep. 1, 1964 Jan. 1, 2007 LR 663 Calcium Chloride Applied Jun. 1, 1958 Jan. 1, 2007 LR 702 Construction and Maintenance Signs Jan. 1, 2004 Jun. 1, 2007 LR 1004 Coarse Aggregate for Bituminous Surface Treatment Jan. 1, 2002 Jan. 1, 2007 LR 1030 Growth Curve Mar. 1, 2008 Jan. 1, 2007 LR 1032-1 Emulsified Asphalts Jan. 1, 2007 Feb. 7, 2008 LR 1095 Fast-Dry Pavement Marking Paint Black (Lead Free Waterborne April 1, 2011 Type) Type) April 1, 2011 | LR 403-2 | | | Bituminous Hot Mix Sand Seal Coat | | Jan. 1, 2007 |
| LR 442 | LR 406 | | | Filling HMA Core Holes with Non-shrink Grout | Jan. 1, 2008 | |
| LR 451 | LR 420 | | | | | |
| LR 503-1 Furnishing Class SI Concrete Oct. 1, 1973 Jan. 1, 2002 LR 503-2 Furnishing Class SI Concrete (Short Load) Jan. 1, 1989 Jan. 1, 2002 LR 542 Pipe Culverts, Type (Furnished) Sep. 1, 1964 Jan. 1, 2007 LR 663 Calcium Chloride Applied Jun. 1, 1958 Jan. 1, 2007 LR 702 Construction and Maintenance Signs Jan. 1, 2004 Jun. 1, 2007 LR 1004 Coarse Aggregate for Bituminous Surface Treatment Jan. 1, 2002 Jan. 1, 2007 LR 1030 Growth Curve Mar. 1, 2008 Jan. 1, 2010 LR 1032-1 Emulsified Asphalts Jan. 1, 2007 Feb. 7, 2008 LR 1032-2 Multigrade Cold Mix Asphalt Jan. 1, 2007 Feb. 1, 2007 LR 1095 Fast-Dry Pavement Marking Paint Black (Lead Free Waterborne Type) April 1, 2011 April 1, 2011 | LR 442 | | | | | |
| LR 503-2 ☐ Furnishing Class SI Concrete (Short Load) Jan. 1, 1989 Jan. 1, 2002 LR 542 ☐ Pipe Culverts, Type (Furnished) Sep. 1, 1964 Jan. 1, 2007 LR 663 ☐ Calcium Chloride Applied Jun. 1, 1958 Jan. 1, 2007 LR 702 ☐ Construction and Maintenance Signs Jan. 1, 2004 Jun. 1, 2007 LR 1004 ☐ Coarse Aggregate for Bituminous Surface Treatment Jan. 1, 2002 Jan. 1, 2007 LR 1030 ☐ Growth Curve Mar. 1, 2008 Jan. 1, 2010 LR 1032-1 ☐ Emulsified Asphalts Jan. 1, 2007 Feb. 7, 2008 LR 1032-2 ☐ Multigrade Cold Mix Asphalt Jan. 1, 2007 Feb. 1, 2007 LR 1095 ☐ Fast-Dry Pavement Marking Paint Black (Lead Free Waterborne Type) April 1, 2011 | LR 451 | | | Crack Filling Bituminous Pavement with Fiber-Asphalt | | · |
| LR 542 Pipe Culverts, Type (Furnished) Sep. 1, 1964 Jan. 1, 2007 LR 663 Calcium Chloride Applied Jun. 1, 1958 Jan. 1, 2007 LR 702 Construction and Maintenance Signs Jan. 1, 2004 Jun. 1, 2007 LR 1004 Coarse Aggregate for Bituminous Surface Treatment Jan. 1, 2002 Jan. 1, 2007 LR 1030 Growth Curve Mar. 1, 2008 Jan. 1, 2010 LR 1032-1 Emulsified Asphalts Jan. 1, 2007 Feb. 7, 2008 LR 1032-2 Multigrade Cold Mix Asphalt Jan. 1, 2007 Feb. 1, 2007 LR 1095 Fast-Dry Pavement Marking Paint Black (Lead Free Waterborne April 1, 2011 Type) | LR 503-1 | | | Furnishing Class SI Concrete | Oct. 1, 1973 | Jan. 1, 2002 |
| LR 663 | LR 503-2 | | | | • | • |
| LR 702 | LR 542 | | | | | · |
| LR 1004 | LR 663 | | | Calcium Chloride Applied | · | |
| LR 1030 Growth Curve Mar. 1, 2008 Jan. 1, 2010 LR 1032-1 Emulsified Asphalts Jan. 1, 2007 Feb. 7, 2008 LR 1032-2 Multigrade Cold Mix Asphalt Jan. 1, 2007 LR 1095 Fast-Dry Pavement Marking Paint Black (Lead Free Waterborne Type) Mar. 1, 2008 Jan. 1, 2010 Feb. 7, 2008 Feb. 1, 2007 | | | | | • | • |
| LR 1032-1 | LR 1004 | | | Coarse Aggregate for Bituminous Surface Treatment | - | • |
| LR 1032-2 | LR 1030 | | | Growth Curve | | |
| LR 1095 | LR 1032-1 | | | | • | • |
| Type) | | | | | • | Feb. 1, 2007 |
| | LR 1095 | | | | April 1, 2011 | |
| LR 1102 | | | _ | | | |
| | LR 1102 | | Ш | Road Mix or Traveling Plan Mix Equipment | Jan. 1, 2007 | |

BDE SPECIAL PROVISIONS For the August 5 and September 23, 2011 Lettings

The following special provisions indicated by an "x" are applicable to this contract. An * indicates a new or revised special provision for the letting.

| File Name | <u>Pg #</u> | | Special Provision Title | <u>Effective</u> | Revised |
|---|--|----------------------------|--|--|---|
| 80240 | <u> </u> | | Above Grade Inlet Protection | July 1, 2009 | |
| 80099 | | | Accessible Pedestrian Signals (APS) | April 1, 2003 | Jan. 1, 2007 |
| 80186 | | | Alkali-Silica Reaction for Cast-in-Place Concrete | Aug. 1, 2007 | Jan. 1, 2009 |
| 80213 | 22 | X | Alkali-Silica Reaction for Precast and Precast Prestressed Concrete | Jan. 1, 2009 | , |
| 80207 | 25 | X | Approval of Proposed Borrow Areas, Use Areas, and/or Waste Areas | Nov. 1, 2008 | Nov. 1, 2010 |
| 0020. | | | (NOTE: This special provision was previously named "Approval of Proposed | • | , |
| | | | Borrow Areas, Use Areas, and/or Waste Areas Inside Illinois State Borders".) | | |
| 80192 | | | Automated Flagger Assistance Device | Jan. 1, 2008 | |
| 80173 | 26 | X | Bituminous Materials Cost Adjustments | Nov. 2, 2006 | April 1, 2009 |
| 80241 | | | Bridge Demolition Debris | July 1, 2009 | |
| 50261 | | | Building Removal-Case I (Non-Friable and Friable Asbestos) | Sept. 1, 1990 | April 1, 2010 |
| 50481 | | | Building Removal-Case II (Non-Friable Asbestos) | Sept. 1, 1990 | April 1, 2010 |
| 50491 | | | Building Removal-Case III (Friable Asbestos) | Sept. 1, 1990 | April 1, 2010 |
| 50531 | | | Building Removal-Case IV (No Asbestos) | Sept. 1, 1990 | April 1, 2010 |
| 80166 | 29 | X | Cement | Jan. 1, 2007 | April 1, 2011 |
| 80260 | 32 | Χ | Certification of Metal Fabricator | July 1, 2010 | |
| 80198 | | | Completion Date (via calendar days) | April 1, 2008 | |
| 80199 | | | Completion Date (via calendar days) Plus Working Days | April 1, 2008 | |
| 80094 | 33 | _ X_ | Concrete Admixtures | Jan. 1, 2003 | April 1, 2009 |
| 80215 | | | Concrete Joint Sealer | Jan. 1, 2009 | |
| 80226 | | | Concrete Mix Designs | April 1, 2009 | |
| 80261 | | | Construction Air Quality – Diesel Retrofit | June 1, 2010 | |
| 80237 | 37 | <u> X</u> | Construction Air Quality – Diesel Vehicle Emissions Control | April 1, 2009 | July 1, 2009 |
| 80239 | 39 | <u> </u> | Construction Air Quality – Idling Restrictions | April 1, 2009 | |
| 80227 | | | Determination of Thickness | April 1, 2009 | |
| | | | 1 | A !! 4 0007 | |
| 80177 | | | Digital Terrain Modeling for Earthwork Calculations | April 1, 2007 | 0.00 |
| * 80029 | 41 | Х | Disadvantaged Business Enterprise Participation | Sept. 1, 2000 | Aug. 2. 2011 |
| * 80029 80177 | 41 | Х | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic | Sept. 1, 2000 April 1, 2011 | |
| * 80029 80177 80179 | 41 | X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A | Sept 1, 2000 April 1, 2011 April 1, 2007 | Jan. 1, 2011 |
| * 80029 80177 80179 80205 | | | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 | Jan. 1, 2011 Jan. 1, 2011 |
| * 80029 80177 80179 80205 80189 | 51 | X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 | Jan. 1, 2011 |
| 80029 80177 80179 80205 80189 80228 | | | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances | Sept 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 | Jan. 1, 2011 Jan. 1, 2011 |
| 80029 80177 80179 80205 80189 80228 80249 | 51 53 | X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates | Sept 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 | Jan. 1, 2011 Jan. 1, 2011 |
| 80029 80177 80179 80205 80189 80228 80249 80265 | 51 53 54 | XXX | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate | April 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 | 51 53 | X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 | 51 53 54 | XXX | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 | 51 53 54 58 | X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2007 Jan. 1, 2007 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 | 51 53 54 58 | X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2007 Jan. 1, 2008 Nov. 1, 2009 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80246 | 51 53 54 58 62 63 | X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2008 Nov. 1, 2009 Jan. 1, 2010 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80246 80250 | 51 53 54 58 62 63 64 | X X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints Hot-Mix Asphalt – Drop-Offs | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2008 Nov. 1, 2009 Jan. 1, 2010 Jan. 1, 2010 Jan. 1, 2010 Jan. 1, 2010 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80246 80250 80250 | 51 53 54 58 62 63 | X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints Hot-Mix Asphalt – Drop-Offs Hot-Mix Asphalt – Fine Aggregate | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2008 Nov. 1, 2009 Jan. 1, 2010 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80246 80250 80259 80109 | 51 53 54 58 62 63 64 | X X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints Hot-Mix Asphalt – Drop-Offs Hot-Mix Asphalt – Fine Aggregate Impact Attenuators | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2008 Nov. 1, 2009 Jan. 1, 2010 Jan. 1, 2010 Jan. 1, 2010 April 1, 2010 April 1, 2010 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 April 1, 2009 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80246 80250 80259 80109 80110 | 51 53 54 58 62 63 64 | X X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints Hot-Mix Asphalt – Fine Aggregate Impact Attenuators Impact Attenuators, Temporary | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2008 Nov. 1, 2009 Jan. 1, 2010 Jan. 1, 2010 April 1, 2010 April 1, 2010 Nov. 1, 2003 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 April 1, 2009 Nov. 1, 2008 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80246 80250 80259 80109 80110 80252 | 51 53 54 58 62 63 64 | X X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints Hot-Mix Asphalt – Drop-Offs Hot-Mix Asphalt – Fine Aggregate Impact Attenuators | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2008 Nov. 1, 2009 Jan. 1, 2010 Jan. 1, 2010 April 1, 2010 April 1, 2010 Nov. 1, 2003 Nov. 1, 2003 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 April 1, 2009 Nov. 1, 2008 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80246 80250 80259 80109 80110 | 51 53 54 58 62 63 64 | X X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints Hot-Mix Asphalt – Fine Aggregate Impact Attenuators Impact Attenuators, Temporary Improved Subgrade | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2007 Jan. 1, 2009 Jan. 1, 2009 Jan. 1, 2010 April 1, 2010 April 1, 2010 Nov. 1, 2003 Nov. 1, 2003 Jan. 1, 2010 Jan. 1, 2011 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 April 1, 2009 Nov. 1, 2008 Jan. 1, 2007 Jan. 2, 2011 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80246 80250 80259 80109 80110 80252 | 51 53 54 58 62 63 64 | X X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints Hot-Mix Asphalt – Fine Aggregate Impact Attenuators Impact Attenuators Impact Attenuators, Temporary Improved Subgrade Lane Closure, Multilane, Intermittent or Moving Operation, for Speeds ≤ 40 MPH Liquidated Damages | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2007 Jan. 1, 2009 Jan. 1, 2009 Jan. 1, 2010 April 1, 2010 April 1, 2010 Nov. 1, 2003 Nov. 1, 2003 Nov. 1, 2003 Jan. 1, 2010 Jan. 1, 2011 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 April 1, 2009 Nov. 1, 2008 Jan. 1, 2007 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80250 80259 80110 80252 80266 | 51 53 54 58 62 63 64 65 | X X X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints Hot-Mix Asphalt – Fine Aggregate Impact Attenuators Impact Attenuators Impact Attenuators, Temporary Improved Subgrade Lane Closure, Multilane, Intermittent or Moving Operation, for Speeds ≤ 40 MPH | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2009 Jan. 1, 2009 Jan. 1, 2010 April 1, 2010 April 1, 2010 April 1, 2010 Nov. 1, 2003 Nov. 1, 2003 Jan. 1, 2010 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2011 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 April 1, 2009 Nov. 1, 2008 Jan. 1, 2007 Jan. 2, 2011 April 1, 2011 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80250 80259 80110 80252 80266 | 51 53 54 58 62 63 64 65 | X X X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints Hot-Mix Asphalt – Fine Aggregate Impact Attenuators Impact Attenuators Impact Attenuators, Temporary Improved Subgrade Lane Closure, Multilane, Intermittent or Moving Operation, for Speeds ≤ 40 MPH Liquidated Damages | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2007 Jan. 1, 2009 Jan. 1, 2010 Jan. 1, 2010 April 1, 2010 April 1, 2010 Nov. 1, 2003 Nov. 1, 2003 Nov. 1, 2003 Jan. 1, 2010 Jan. 1, 2011 Jan. 1, 2011 April 1, 2009 Jan. 1, 2011 Jan. 1, 2011 June 15, 1999 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 April 1, 2009 Nov. 1, 2008 Jan. 1, 2007 Jan. 2, 2011 April 1, 2011 Jan. 1, 2009 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80250 80250 80110 80252 80266 80230 80267 80045 80203 | 51 53 54 58 62 63 64 65 | X X X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints Hot-Mix Asphalt – Drop-Offs Hot-Mix Asphalt – Fine Aggregate Impact Attenuators Impact Attenuators, Temporary Improved Subgrade Lane Closure, Multilane, Intermittent or Moving Operation, for Speeds ≤ 40 MPH Liquidated Damages Long-Span Guardrail over Culvert Material Transfer Device Metal Hardware Cast into Concrete | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2007 Jan. 1, 2009 Jan. 1, 2010 Jan. 1, 2010 April 1, 2010 April 1, 2010 Nov. 1, 2003 Nov. 1, 2003 Nov. 1, 2003 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2011 Jan. 1, 2011 Jan. 1, 2011 June 15, 1999 April 1, 2008 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 April 1, 2009 Nov. 1, 2008 Jan. 1, 2007 Jan. 2, 2011 April 1, 2011 Jan. 1, 2009 April 1, 2009 |
| 80029 80177 80179 80205 80189 80228 80249 80265 80229 80169 80194 80245 80250 80250 80159 80110 80252 80266 | 51 53 54 58 62 63 64 65 | X X X X X X | Disadvantaged Business Enterprise Participation Drainage and Inlet Protection Under Traffic Engineer's Field Office Type A Engineer's Field Office Type B Equipment Rental Rates Flagger at Side Roads and Entrances Frames and Grates Friction Aggregate Fuel Cost Adjustment High Tension Cable Median Barrier HMA – Hauling on Partially Completed Full-Depth Pavement Hot-Mix Asphalt – Anti-Stripping Additive Hot-Mix Asphalt – Density Testing of Longitudinal Joints Hot-Mix Asphalt – Drop-Offs Hot-Mix Asphalt – Fine Aggregate Impact Attenuators Impact Attenuators, Temporary Improved Subgrade Lane Closure, Multilane, Intermittent or Moving Operation, for Speeds ≤ 40 MPH Liquidated Damages Long-Span Guardrail over Culvert Material Transfer Device | Sept. 1, 2000 April 1, 2011 April 1, 2007 Aug. 1, 2008 Aug. 2, 2007 April 1, 2009 Jan. 1, 2010 Jan. 1, 2011 April 1, 2009 Jan. 1, 2007 Jan. 1, 2007 Jan. 1, 2009 Jan. 1, 2010 Jan. 1, 2010 April 1, 2010 April 1, 2010 Nov. 1, 2003 Nov. 1, 2003 Nov. 1, 2003 Jan. 1, 2010 Jan. 1, 2011 Jan. 1, 2011 April 1, 2009 Jan. 1, 2011 Jan. 1, 2011 June 15, 1999 | Jan. 1, 2011 Jan. 1, 2011 Jan. 2, 2008 July 1, 2009 April 1, 2009 Nov. 1, 2008 Jan. 1, 2007 Jan. 2, 2011 April 1, 2011 Jan. 1, 2009 |

| 80253 | | | Movable Traffic Barrier | Jan. 1, 2010 | Jan. 1, 2011 |
|----------------|-----|----------------|--|---------------|-----------------------|
| | | | (NOTE: This Special Provision was previously named "Moveable | | |
| | | | Traffic Barrier System".) | | |
| 80262 | 71 | X | Mulch and Erosion Control Blankets | Nov. 1, 2010 | April 1, 2011 |
| | | | (Note: the Special Provision was previously named "Mulch") | | |
| 80180 | | | National Pollutant Discharge Elimination System / Erosion and Sediment | April 1, 2007 | Nov. 1, 2009 |
| | | | Control Deficiency Deduction | | |
| 80208 | | | Nighttime Work Zone Lighting | Nov. 1, 2008 | |
| 80231 | 75 | X | Pavement Marking Removal | April 1, 2009 | |
| 80254 | 76 | X | Pavement Patching | Jan. 1, 2010 | |
| 80022 | 77 | X | Payments to Subcontractors | June 1, 2000 | Jan. 1, 2006 |
| 80232 | | | Pipe Culverts | April 1, 2009 | April 1, 2010 |
| 80263 | | | Planting Perennial Plants | Jan. 1, 2011 | |
| 80210 | | | Portland Cement Concrete Inlay or Overlay | Nov. 1, 2008 | |
| 80217 | | | Post Clips for Extruded Aluminum Signs | Jan. 1, 2009 | |
| 80268 | 79 | X | Post Mounting of Signs | Jan. 1, 2011 | |
| 80171 | | | Precast Handling Holes | Jan. 1, 2007 | |
| 80218 | | | Preventive Maintenance – Bituminous Surface Treatment | Jan. 1, 2009 | April 1, 2009 |
| * 80219 | | | Preventive Maintenance - Cape Seal | Jan. 1, 2009 | Aug. 1, 2011 |
| * 80220 | | 100 | Preventive Maintenance - Micro-Surfacing | Jan. 1, 2009 | Aug. 1, 2011 |
| 80221 | | | Preventive Maintenance - Slurry Seal | Jan. 1, 2009 | |
| 80015 | | | Public Convenience and Safety | Jan. 1, 2000 | |
| 34261 | | | Railroad Protective Liability Insurance | Dec. 1, 1986 | Jan. 1, 2006 |
| 80157 | | | Railroad Protective Liability Insurance (5 and 10) | Jan. 1, 2006 | • |
| 80247 | | | Raised Reflective Pavement Markers | Nov. 1, 2009 | April 1, 2010 |
| 80172 | 80 | X | Reclaimed Asphalt Pavement (RAP) | Jan. 1, 2007 | Jan. 1, 2011 |
| 80224 | | | Restoring Bridge Approach Pavements Using High-Density Foam | Jan. 1, 2009 | |
| 80271 | | | Safety Edge | April 1, 2011 | |
| 80131 | 88 | X | Seeding | July 1, 2004 | July 1, 2010 |
| 80264 | | | Selection of Labor | July 2, 2010 | , , , |
| 80152 | | | Self-Consolidating Concrete for Cast-In-Place Construction | Nov. 1, 2005 | July 1, 2010 |
| 80132 | 91 | X | Self-Consolidating Concrete for Precast Products | July 1, 2004 | July 1, 2010 |
| 80127 | • | — | Steel Cost Adjustment | April 2, 2004 | April 1, 2009 |
| * 80255 | | | Stone Matrix Asphalt | Jan. 1, 2010 | Aug. 1, 2011 |
| 80234 | | | Storm Sewers | April 1, 2009 | April 1, 2010 |
| 80143 | 93 | X | Subcontractor Mobilization Payments | April 2, 2005 | April 1, 2011 |
| 80075 | ••• | | Surface Testing of Pavements | April 1, 2002 | Jan. 1, 2007 |
| 80087 | 94 | X | Temporary Erosion Control | Nov. 1, 2002 | Jan. 1, 2011 |
| 80225 | 0-1 | | Temporary Raised Pavement Marker | Jan. 1, 2009 | oun. 1, 2011 |
| 80256 | | | Temporary Water Filled Barrier | Jan. 1, 2010 | Jan. 1, 2011 |
| 00230 | | | (NOTE: This special provision was previously named "Temporary | oun. 1, 2010 | 0011. 1, 20 11 |
| | | | Longitudinal Traffic Barrier System".) | | |
| 80257 | | | Traffic Barrier Terminal, Type 6 | Jan. 1, 2010 | |
| * 80273 | QR | Х | | Aug. 1, 2011 | |
| 80269 | yy. | 2.5 | Traffic Control Surveillance | Jan. 1, 2011 | |
| 20338 | | | Training Special Provisions | Oct. 15, 1975 | |
| 80258 | 99 | X | Truck Mounted/Trailer Mounted Attenuators | Jan. 1, 2010 | |
| 80270 | 00 | -^- | Utility Coordination and Conflicts | April 1, 2011 | |
| 80270 | | <u> </u> | Working Days | Jan. 1, 2002 | |
| 000 <i>1</i> I | | | T Mounting pays | Jan. 1, 2002 | |

The following special provisions have been deleted from use:

80243 American Recovery and Reinvestment Act Provisions

80236 American Recovery and Reinvestment Act Signing

81238 Monthly Employment Report

The following special provisions are in the 2011 Supplemental Specifications and Recurring Special Provisions:

| File Name | Special Provision Title | New Location | <u>Effective</u> | Revised |
|-----------|--|-----------------------------|------------------|---------------|
| 80214 | Concrete Gutter, Type A | Article 606.07 | Jan. 1, 2009 | |
| 80178 | Dowel Bars | Article 1006.11 | April 1, 2007 | Jan. 1, 2008 |
| 80201 | Hot-Mix Asphalt Plant Test Frequency | Article 1030.05 | April 1, 2008 | Jan. 1, 2010 |
| 80251 | Hot-Mix Asphalt – QC/QA Acceptance Criteria | Article 1030.05 | Jan. 1, 2010 | |
| 80202 | Hot-Mix Asphalt – Transportation | Article 1030.08 | April 1, 2008 | |
| 80196 | Mast Arm Assembly and Pole | Article 1077.03 | Jan. 1, 2008 | Jan. 1, 2009 |
| 80182 | Notification of Reduced Width | Article 701.06 | April 1, 2007 | |
| 80069 | Organic Zinc-Rich Paint System | Article 1008.05 | Nov. 1, 2001 | Jan. 1, 2010 |
| 80216 | Partial Exit Ramp Closure for Freeway/Expressway | Section 701 | Jan. 1, 2009 | |
| 80209 | Personal Protective Equipment | Article 701.12 | Nov. 1, 2008 | |
| 80119 | Polyurea Pavement Marking | Sections 780, 1095 and 1105 | April 1, 2004 | Jan. 1, 2009 |
| 80170 | Portland Cement Concrete Plants | Article 1020.11 | Jan. 1, 2007 | |
| 80211 | Prismatic Curb Reflectors | Articles 782.03 and 1097.04 | Nov. 1, 2008 | |
| 80223 | Ramp Closure for Freeway/Expressway | Section 701 | Jan. 1, 2009 | |
| 80183 | Reflective Sheeting on Channelizing Devices | Article 1106.02 | April 1, 2007 | Nov. 1, 2008 |
| 80206 | Reinforcement Bars – Storage and Protection | Article 508.03 | Aug. 1, 2008 | April 1, 2009 |
| 80176 | Thermoplastic Pavement Marking | Article 1095.01 | Jan. 1, 2007 | |

The following special provisions require additional information from the designer. The additional information needs to be included in a separate document attached to this check sheet. The Project Development and Implementation section will then include the information in the applicable special provision. The Special Provisions are:

- Bridge Demolition Debris
- Building Removal-Case I
- Building Removal-Case II
- Building Removal-Case III
- Building Removal-Case IV
- Completion Date
- Completion Date Plus Working Days
- DBE Participation

- Material Transfer Device
- Railroad Protective Liability Insurance
- Training Special Provisions
- Working Days



The following Special Provisions supplement the "Standard Specifications for Road and Bridge Construction", Adopted January 1, 2007 and Highways", and the "Manual of Test Procedures For Materials" in effect on the date of invitation of bids, and the Supplemental Specifications and Recurring Special Provisions indicated on the Check Sheet included here in which apply to and govern the construction of City of Quincy's FAU 7807 (CH 30 / Maine Street) and FAU 7829 (33rd Street), Section 08-00307-00-TL, Project M-SRTS-4008(089), and in case of conflict with any part, or parts, of said Specifications, the said Special Provisions shall take precedence and shall govern.

DESCRIPTION OF WORK

This improvement to FAU 7807 (CH 30 / Maine Street) consists of hot-mix asphalt resurfacing of Maine Street from 50 feet west of 30th Street to 300 feet west of 36th Street, hot-mix asphalt resurfacing of 30th Street from 100 feet south of Maine Street to 50 feet north of Maine Street, constructing new PCC sidewalk along the north side of Maine Street at various locations, replacing entrances that do not meet ADA requirements along the north side of Maine Street, constructing a new south leg at the 33rd Street intersection, constructing a new right turn lane on the west leg of the 33rd Street intersection, installing new traffic signals at the 33rd Street intersection, restriping Maine Street, and other miscellaneous improvements within the project limits in Quincy, IL. This contract will involve grading, HMA resurfacing, HMA pavement, concrete curb and gutter, PCC sidewalk, PCC driveways, traffic signals, lighting, pavement marking, and other miscellaneous items necessary to complete this section.

COMPLETION DATE

All PCC sidewalk, PCC driveways, grading, curb and gutter, pavement widening, hot-mix asphalt surfacing, and traffic signals shall be completed by August 24, 2012. After the completion date, an additional 10 working days will be allowed to complete pavement striping, seeding, and other miscellaneous items.

If the Contractor fails to complete the required work by the completion date or within the number of additional working days stated herein, he/she shall be liable to the Department for liquidated damages in accordance with Article 108.09 of the Standard Specifications and any other additional special provision which may be attached herein which supplements Article 108.09. The Contractor will also be liable for additional items of work made necessary by not meeting the completion date or additional working days allowed. Such items include, but are not restricted to, temporary pavement marking, temporary erosion control, and temporary seeding.

Stage 2 construction activities as shown in the plans are to take place during Quincy High School's summer break which is estimated to be from May 28, 2012, through August 24, 2012. If the Contractor wishes to begin work on Stage 2 items prior to the summer break, the Contractor shall request in writing approval from the City Engineer and the Superintendant of School District No. 172, Adams County, IL. This request shall describe what activities will take place, what the disruption to normal vehicle and pedestrian traffic will be, and the anticipated time period. The Contractor shall not begin this work until approval is granted from the City Engineer and the Superintendant of School District No. 172, Adams County, IL.

CONTRACTOR COOPERATION

The attention of the Contractor is directed to the fact that additional contracts will be in force during the duration of this contract.

The Quincy School District No. 172 will be reconstructing the entrance into the Quincy Senior High School parking lot under a separate project. This project will tie into the south leg of the Maine Street and 33rd street intersection at Station 4+36.13. This project will take place during the summer of 2012. This project will be phase 1 of 2 phases to reconstruct the entire Quincy Senior High School and Baldwin School east parking lots.

Page 1 of 17 Printed on 6/23/2011 9:45:04 AM

TRAFFIC CONTROL PLAN

Traffic Control shall be in accordance with the applicable sections of the Standard Specifications for Road and Bridge Construction, the applicable guidelines contained in the Illinois Manual on Uniform Traffic Control devices for Streets and Highways, these Special Provisions, any special details and Highway Standards contained herein and in the plans.

Special attention is called to Article 107.09 and Sections 701 through 703 of the Standard Specifications for Road and Bridge Construction and the following Highway Standards relating to traffic control:

701502

701606

701701

701801

701901

All Advance Warning signs shall be new or in like new condition at the start of the project.

The Contractor shall be responsible for the traffic devices at all times during the construction activities. The contractor shall coordinate the items of work in order to keep traffic hazards to a minimum.

All required fluorescent orange signs shall be 48 x 48 inches on this project.

All staggered Type III barricades shall be equipped with bi-directional steady burning Type A lights and have high intensity striping on both sides.

The Contractor shall furnish, install, and maintain applicable traffic control devices in accordance with the herein referenced standards and specifications, or as directed by the Engineer. During construction, materials and equipment shall be located sufficiently off the pavement edge, unless applicable traffic control measures are provided, to adequately warn and protect the motoring public through the construction zone. All materials and equipment shall be removed from a closed lane of traffic at the end of each work day.

Sign posts must be 4" x 4" wood posts according to Article 1007.05. The use of metal posts will not be permitted.

Uneven Lanes signs (W8-11 48"x48") shall be placed a minimum of 100 feet prior to bituminous surface removal and paving operations that create a difference in elevation between adjacent traffic lanes and as directed by the Engineer. Cost shall be included in the contract bid price for the traffic control standard in effect. The maximum difference between lanes shall be 2".

Bump Signs. The Contractor shall furnish and erect W8-1(O) 48"x48" "Bump" signs at each end of the project and all affected side roads as directed by the Engineer. Cost shall be included in the contract bid price for the traffic control standard in effect.

Emergency Services Coordination. The Contractor shall be required to notify the Resident Engineer at least 48 hours prior to lane closures, or the closure of street pavements on this proposed improvement. The Contractor shall also be responsible for notifying the 911 Center of any closing by calling the non-emergency number 222-9360. The Center in turn will notify the other community emergency services. Information requested will include date of closure, expected length of closure, and the names of two individuals with telephone numbers to be reached in case of emergency. Failure of the Contractor to notify the 911 Center in advance of a street closure will be grounds for enforcement and penalties under appropriate City Ordinances.

The City of Quincy Engineering Department will be responsible during the duration of this project for notifying the United States Postal Service of the proposed construction to insuring continued service. The Engineering Department will also be responsible for contacting other community services such as school bus routes and senior citizen services to insure their continued operation with the least impact of the affected residences.

Residential & Commercial Coordination: The Contractor shall be required to provide 48 hour advance notice to any residence losing the usage of their driveway entrance(s) due to construction activities.

The Contractor shall be required to provide 72 hour advance notice to any commercial enterprise losing the usage of their driveway entrance(s) due to construction activities.

Residential Entrances: Maximum closure of any residential driveway shall be 21 calendar days.

Page 2 of 17 Printed on 6/23/2011 9:45:04 AM

Commercial Entrances: Maximum closure of any commercial driveway shall be 21 calendar days. When multiple entrances serve a commercial property, only one of those commercial entrances shall be closed at a time.

School Entrances: When Quincy High School and / or Baldwin Intermediate School is in normal session all entrances to school property off of Maine Street shall remain open at all times. During summer break, a minimum of one (1) entrance to school property off of Maine Street shall remain open at all times.

Stage Construction. A sequence of stage construction is provided in the plans as a guide to the Contractor. This sequence may be altered and modified by the Contractor with approval from the Engineer. The Contractor is responsible for the planning and execution of this project, which is subject to the approval of the Engineer.

The majority of the construction of the south leg of the 33rd Street and Maine Street intersection shall take place during the Quincy High School's summer break. This time period is estimated to be from May 28th, 2012, through August 24th, 2012.

Street Closures: All streets shall remain open to through traffic at all times.

Arrow Boards. Arrow boards will not be required in this contract. Any arrow boards provided by the Contractor will not be paid for.

Traffic Signals: Traffic signals at the intersections of 30th Street & Maine and 36th Street & Maine shall remain fully operational at all times during the construction period. Coordination between the signals may be disrupted.

The traffic signal at the intersection of 33rd Street & Maine shall remain in operation during Stage 1 and as long as reasonably possible during Stage 2. Upon deactivation of the existing signals, traffic control at the intersection will be stop controlled at all three legs.

<u>Traffic Control and Protection, Standard 701502</u> This traffic control and protection will be used for milling and paving operations.

<u>Traffic Control and Protection, Standard 701606</u> This traffic control and protection will be used for construction operations that encroach into the outer eastbound and west bound lanes of Maine Street. Provide 8' minimum separation from drop-offs greater than 12" (4' minimum required for drop-offs in excess of 3").

<u>Traffic Control and Protection, Standard 701701</u> This traffic control and protection will be used for construction operations at the intersection of 33rd Street and Maine Street.

<u>Traffic Control and Protection, Standard 701801</u> This traffic control and protection will be used for construction operations requiring the closure of sidewalks.

<u>Traffic Control and Protection, Standard 701701, Special</u> This traffic control and protection will be used for construction operations at the intersection of 30rd Street and Maine Street as shown in the plans. Traffic control and protection under at this intersection will be measured for payment on a lump sum basis.

<u>Payment for Traffic Control and Protection:</u> Traffic control and protection at the intersection of 30th Street and Maine Street will be paid for at the contract lump sum price for TRAFFIC CONTROL AND PROTECTION, STANDARD 701701, SPECIAL.

Other traffic control standards referenced in the plans shall be implemented per plan notes, or as directed by the Engineer, and paid for in accordance with the Standard Specifications.

Temporary signs, barricades, and drums for traffic control will be considered to be included in the contract unit price of the traffic control and pay items included in the contract. The temporary signs, barricades, and drums shall remain the property of the Contractor.

Flagger protection is required when closing a lane for less than one full day.

Maintaining all weather access will not be measured for payment.

Furnishing, placing, and removing all other traffic control and protection required will not be measured for payment.

Page 3 of 17 Printed on 6/23/2011 9:45:04 AM

LANDSCAPING

Care shall be taken by the Contractor to avoid disturbing the existing landscaping plants and items near the limits of construction. The Contractor shall repair or replace any damaged landscaping plants or other material at no additional cost to the Department.

SAW CUTTING

Saw cutting for the various removal pay items in the contract will not be measured for payment. The cost of saw cutting will be included in the unit price for the respective removal pay item.

WATER MAIN

This work shall consist of furnishing and installing water main, fittings, and thrust blocks in accordance with Section 561 of the Standard Specifications, as directed by the City of Quincy Department of Utilities / Field Operations, and specified herein.

Materials:

WATER PIPE:

Water pipe shall comply with provisions of Section 40 of the *Standard Specifications for Water & Sewer Main Construction in Illinois – Fifth Edition* for the type, class strength coatings and linings of the pipe as shown on the Plans and as described herein:

- 1. Polyvinyl Chloride (PVC) Pipe
 - a. Conform to latest revisions of AWWA C900
 - b. Min. Class 200.
 - c. Pressure slip joints with elastomeric seals (gaskets) complying with ASTM F477.
- 2. Ductile Iron Pipe (DIP)
 - a. Conform to latest revisions of ANSI A 21.51 (AWWA C151), tar seal coated
 - b. Cement Lined Per ANSI A 21.4 (AWWA C-104)
 - c. Pressure Class 200 unless otherwise noted
 - d. Mechanical or rubber ring (slip seal or push on) joints
- 3. Copper Service Pipe
 - a. Type K conforming to ASTM B-88 and B-251
 - b. Outside diameter conforming to ASTM B-251 Table 2
 - c. 1 inch diameter unless otherwise noted

FITTINGS (3" THRU 48"):

- A. Fittings shall comply with provisions of Section 40-2.05A of the Standard Specifications for Water & Sewer Main Construction in Illinois Fifth Edition and the following:
 - Cast or Ductile Iron
 - a. Meeting ANSI A 21.10 (AWWA C110) or ANSI A21.53 (AWWA C153), and ANSI A21.11 (AWWA C111)
 - b. Minimum working pressure same as pipe being joined
 - c. Cement Lined per ANSI A21.4 (AWWA C104)
 - d. Mechanical Joints unless otherwise noted.

STOPS

- A. Comply with Article 40-2.06c of the Standard Specifications and the following:
 - 1. Corporation Stops:
 - a. 1" AWWA (Mueller "CC") threaded inlet
 - b. 1" Flared copper pipe outlet
 - c. Acceptable Materials
 - 1. Mueller H-15000

Page 4 of 17 Printed on 6/23/2011 9:45:04 AM

- 2. Approved Equal
- Curb Stops:
 - a: 1" Inlet and Outlet flared copper
 - b. Acceptable Materials
 - 1. Mueller H-15204
 - 2. Approved Equal

BOXES AND LIDS:

- A. Comply with Section 44 of Standard Specifications for Water & Sewer Main Construction in Illinois Fifth Edition, and the following:
 - Curb Boxes
 - Cast Iron construction, extension type with one piece lid, stationary shut off rod, and arch type box.
 - b. Acceptable Materials
 - 1. Mueller H-10314 Series
 - Approved Equal
 - 2. Valve Boxes
 - a. Cast Iron construction
 - b. Two section screw type with availability to add extensions to increase lengths. Inside diameter of 5 1/4"
 - c. Covers with "WATER" cast into the lid
 - d. Acceptable Materials
 - 1. Clow F-2454 and F-2475
 - 2. Approved Equal
 - Post Indicator
 - a. Cast Iron construction
 - b. Two section type for adjustment
 - c. Window opening with words "OPEN" and "SHUT" indicating valve position
 - d. Acceptable Materials
 - 1. Clow 2945A
 - 2. Approved Equal

<u>Depth of Cover</u>: The water main shall be laid at the elevations shown on the plans or at a minimum of 4'-0" (4'-6" preferred) of cover over the top of the pipe from final grade.

Pipe Installation:

- 1. The pipe shall be installed in strict accordance with the manufacturer recommendations, Section 41 of the Standard Specifications for Water & Sewer Main Construction in Illinois Fifth Edition and the following.
- Installation of PVC pipe shall comply to the requirements of ASTM D2774:
- 3. The trench width shall be in accordance with Article 20-2.03 of the Standard Specifications for Water & Sewer Main Construction in Illinois Fifth Edition.
- 4. The trench bottom shall be constructed relatively smooth and free from large stones, large dirt clods and any frozen material prior to placement of the pipe.

<u>Thrust Blocking:</u> Blocking to prevent movement of lines under pressure at bends, tees, caps, valves and hydrants shall be Portland Cement Concrete, a minimum of 12" thick, placed between solid ground and the fittings, and shall be anchored in such a manner that pipe and fittings joints will be accessible for repairs. The concrete shall have a minimum 28-day compressive strength of 3500 psi.

All bends of 11-1/4 degrees or greater, and all tees and plugs shall be thrust protected to prevent movement of the lines under pressure as shown on the Plans.

<u>Testing</u>: The pipe and appurtenances shall be tested in accordance with Section 41-2.12 of the *Standard Specifications for Water & Sewer Main Construction in Illinois – Fifth Edition*.

<u>Disinfecting</u>: The pipe and appurtenances shall be disinfected in accordance with Section 41-2.13 of the *Standard Specifications for Water & Sewer Main Construction in Illinois – Fifth Edition* and the following:

The Contractor shall take and deliver bacteriological samples to the Quincy Water Department (QWD) facility at 2nd and Vermont St., Quincy, IL for analysis. The QWD will perform at no cost to the Contractor the analysis for the initial two

Page 5 of 17 Printed on 6/23/2011 9:45:04 AM

samples for each section to be tested. Cost for resampling and analysis required due to failure of the initial samples, will be at the expense of the Contractor.

<u>Guarantee:</u> The Contractor shall guarantee that all material and work on the water main, the backfill, and all related appurtenances, including the restoration of all street pavements, shall be free from defects of materials and labor and remain in good condition for a period of one (1) year from the date of Letter of Acceptance of the project.

WATER VALVES TO BE ADJUSTED

This work shall consist of adjusting water valve boxes and / or curb stop boxes to the proposed grade in accordance with Section 561 and 602 of the Standard Specifications and the Special Provision for WATER MAIN.

The existing valve box casting and lid may be reused unless damaged. If the casting is damaged during construction, in the opinion of the Engineer, the Contractor shall replace the box and/or lid at his/her expense.

<u>Basis of Payment</u>: This work will be paid for at the contract unit price per each for WATER VALVES TO BE ADJUSTED which price shall include all materials, excavation and backfill, except excavation in rock.

Excavation in rock will be paid for separately in accordance with Article 109.04 of the Standard Specifications.

FIRE HYDRANTS TO BE REMOVED AND REPLACED

This work shall consist of removing existing fire hydrants and furnishing and installing new fire hydrants, with 6" water main lead-in, thrust blocks, concrete ring, and necessary appurtenances in accordance with Sections 561 & 564 of the Standard Specifications, the Special Provision for WATER MAIN, the details in the Plans and directed by the City of Quincy Department of Utilities / Field Operations.

Materials:

Water main shall be in accordance with the Special Provision for WATER MAIN.

VALVES:

- A. Comply with Section 42 of the Standard Specifications for Water & Sewer Main Construction in Illinois Fifth Edition, the latest revisions of AWWA C-509 for Resilient-Seated Gate Valves and the following:
 - 1. Valve stem to be of high tensile bronze or other approved materials with a three (3) O-ring seal and two (2) inch square operating nut.
 - 2. Valves to open by turning right (clockwise).
 - 3. Mechanical Joints unless otherwise noted. (MJ x FL for Tapping Valves)
 - 4. Acceptable Valves:
 - a. Mueller A-2360
 - b. Kennedy Ken-Seal
 - c. Approved Equal

SADDLES AND SLEEVES:

- A. Comply with Section 46 of the Standard Specifications for Water & Sewer Main Construction in Illinois Fifth Edition and the following:
 - 1. Service Saddles
 - a. Bronze Body Construction
 - b. 1" AWWA "CC" Threads
 - c. Mueller Double Strap H-16000 Series of the main size specified
 - Tapping Sleeves
 - a. All stainless steel construction with Buna-N ASTM D2200 gasket
 - b. Verify size of main to be sleeved
 - c. Acceptable Materials

- 1. Ford FAST Stainless Sleeve
- 2. Smith Blair Series 663
- Approved Equal

HYDRANTS

- A. Comply with Section 45 of the Standard Specifications for Water & Sewer Main Construction in Illinois Fifth Edition, the latest revisions of AWWA C-502 and the following:
 - 1. Compression type main valve (5 1/4") closing with line pressure. Main valve and seat ring shall be removable through upper barrel from above ground. Main valve assembly to include automatic drain valve. Bronze seat ring shall be threaded directly into bronze bushing or drain ring and O ring sealed. Upper valve plate, seat ring and drain ring shall be made of bronze, forming an all bronze drainway.
 - 2. Provide two (2) 2 1/2" hose nozzles and one (1) 4 1/2" pumper nozzle w/ National Standard Hose Coupling threads. Center Steamer at least 18" from ground line.
 - 3. Threaded and metal to metal bearing surfaces in bonnet sealed from line pressure by minimum of three (3) "O" ring stem seals.
 - 4. Provide metal weather shield to protect operation nut from freezing.
 - 5. Verified cap and operating nut to match Owner's standard
 - 6. Open left (counter-clockwise) Quincy Std.
 - 7. "Traffic" model design permitting rotation of upper barrel 360°.
 - 8. Six (6) inch mechanical joint inlet connection. Mechanical joint shoe to be enlarged type for Class D cast iron or centrifugal cast pipe by changing the gasket. Inside of mechanical joint shoe to be epoxy coated. Transition gaskets provided for PVC connections.
 - 9. Aboveground color to be green / yellow.
 - 10. Bury depth five (5) feet unless otherwise noted.
 - 11. Acceptable hydrants:
 - a. Mueller Super Centurion 200
 - b. Kennedy Guardian
 - c. Approved Equal

Hydrants shall be located outside the edge of the proposed sidewalks.

<u>Thrust Blocking:</u> Blocking to prevent movement of lines under pressure at bends, tees, caps, valves and hydrants shall be Portland Cement Concrete, a minimum of 12" thick, placed between solid ground and the fittings, and shall be anchored in such a manner that pipe and fittings joints will be accessible for repairs. The concrete shall have a minimum 28-day compressive strength of 3500 psi.

<u>Basis of Payment:</u> This work will be paid for at the contract unit price each for FIRE HYDRANTS TO BE REMOVED AND REPLACED. This price shall be payment in full for all excavation, furnishing all materials, wiping joints, installing thrust blocks, and installing concrete ring.

FULL-ACTUATED CONTROLLER AND TYPE IV CABINET

This work shall conform to the requirements of Sections 857, 1073, and 1074 of the Standard Specifications and the following additions or exceptions.

The traffic actuated solid state digital controller furnished and installed by the Contractor must be able to communicate with an existing Econolite ASC 2M-1000 master controller.

<u>Basis of Payment</u>: This work will be paid for at the contract unit price per each for FULL-ACTUATED CONTROLLER AND TYPE IV CABINET.

PVC CONDUIT

This work shall consist of furnishing and installing a conduit of the type and size specified in accordance with Sections 810 and 1088.01(b) or 1088.01(c) of the Standard Specifications for Road and Bridge Construction except as described herein.

PVC Conduits: When it is necessary to connect PVC conduit to steel conduit a heavy wall set screw connector with a PVC female adapter shall be installed and sealed by duct seal and plastic tape.

When conduit is installed in the excavation in back of curb, the conduit shall be installed below driveway and entrances at a depth which will prevent the conduit from protruding into the entrance pavement material.

<u>PVC Conduit</u>, <u>Pushed</u>: The term pushed shall cover both the pushed and bored method of installing conduit. The contractor shall utilize the boring method to install the conduit for the term PUSHED.

In the event that latent subsurface physical conditions are encountered which prevents the conduit pilot hole from being augured or pushed through the entire conduit run in three (3) sincere attempts, as determined by the Engineer, compensation for the proposed conduit run will be as follows:

- 1. The Department will delete the contract specified method of payment for the subject conduit run.
- 2. The Department will pay for the installation of the conduit run and the three unsuccessful attempts to install the conduit run, under Article 109.04 of the Standard Specification on the force account basis.
- 3. The Engineer will determine the method to be utilized to install the conduit run.

Splices between existing and new conduit shall not be measured for payment.

<u>Basis of Payment</u>: This work will be paid for at the contract unit price per foot for CONDUIT, of the size, installation method, and type specified, which price shall be payment in full for furnishing and installing the conduit and fittings complete.

STEEL COMBINATION MAST ARM ASSEMBLY AND POLE

This work shall conform to the requirements of Sections 834 and 1085 of the Standard Specifications and the following additions or exceptions.

The combination mast arm assembly shall be supplied with a twin tenon mounting for the two luminaries as indicated on the plans.

<u>Basis of Payment:</u> This work will be paid for at the contract unit price each for STEEL COMBINATION MAST ARM ASSEMBLY AND POLE of the arm length specified.

PEDESTRIAN SIGNAL HEAD, POLYCARBONATE, LED, BRACKET MOUNTED WITH COUNTDOWN TIMER

This work shall consist of furnishing and installing a pedestrian signal head with countdown timer and with the number of faces indicated on the plans in accordance with Sections 881 and 1078.02 of the Standard Specifications for Road and Bridge Construction and the following additions or exceptions.

Optical Unit: The optical unit shall be compliant with Section 4E.07 of the 2009 MUTCD All Walk and Don't Walk indications shall be illuminated with light emitting diodes (LED). The LED's shall display a portland orange filled hand and a lunar white filled walking person. All countdown number indications shall consist of two (2) rows of LED's displaying portland orange numerals and shall have a minimum height of 6 inches. The countdown timer shall be capable of automatically adjusting to the programmed intervals in the traffic signal controller. LED modules shall conform to ITE specifications and standards for LED vehicle traffic signal modules and the following:

1) The LED module shall operate between -40° F and +165° F throughout an operating voltage of 80VAC to 135VAC.

- 2) The lens of each indication shall be tinted with a wavelength-matched color or textured to reduce sun phantom effect and enhance on/off contrast. The tinting shall be uniform across the lens face. If a polymeric lens is supplied, a surface coating shall be applied to provide abrasion resistance.
- 3) LED modules shall not contain Aluminum Gallium Arsenide (AlGaAs) LED's.
- 4) LED modules shall provide constant light output under power. Modules with dimming capabilities shall have the option disabled or set to a non-dimming operation.
- 5) In an event of a power outage, light output from the LED module shall cease instantaneously.
- 6) The LED module shall have a minimum life expectancy of 5 years.

<u>Warranty Provisions:</u> The LED modules which exhibit luminous intensities less than the minimum values specified with in the first 60 months of the date of delivery shall be promptly replaced or repaired by the manufacturer at no cost to the State or the City.

<u>Basis of Payment:</u> This item will be paid for at the contract unit price each for PEDESTRIAN SIGNAL HEAD, POLYCARBONATE, LED, BRACKET MOUNTED WITH COUNTDOWN TIMER with the number of faces indicated on the plans for supplying, installing and placing into operation the pedestrian signal head.

REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT

This work shall consist of removing the existing traffic signal equipment and disposal as listed on the plans and directed by the Engineer in accordance with Section 873 of the Standard Specifications, with the following exceptions or additions.

All existing mast arms, traffic signal posts, signal heads, pedestrian push buttons, and controllers shall be salvaged and become the property of the City of Quincy and will be stockpiled at the City Hall Annex, 706 Maine Street (rear), Quincy, IL.

Method of Measurement: Removal of existing traffic signal equipment shall be measured per each intersection specified.

<u>Basis of Payment:</u> This work will be paid for at the contract unit price each for REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT, which price shall include removal of all traffic signal items and stockpiling of specified equipment at the site specified.

EMERGENCY VEHICLE SIGNAL CONTROL SYSTEM

<u>Description:</u> This work shall consist of furnishing and installing an emergency vehicle priority system with necessary connections for proper operation.

The system shall employ infrared communication to verify the presence of authorized priority vehicles. The infrared communication will request the traffic signal controller to advance and/or hold a desired traffic signal display selected from phases normally available and as shown in the plans.

<u>Materials:</u> The emergency vehicle priority system shall be microprocessor based and shall be in accordance with NEMA Standards for Traffic Control Systems and the following:

The unit shall consist of a matched system code secured infrared detector, necessary cabling and a signal discriminator. The Infrared Detector shall provide the following:

- (a) A lightweight and weatherproof unit capable of sensing and transforming pulsed infrared energy into electrical signals for use by the signal discrimination equipment.
- (b) Capability of mounting on mast arms or pedestals.
- (c) Capability of accepting infrared signals from one or two directions and providing single or dual electrical output signal(s).
- (d) Availability in three configurations:
 - (1) Uni-directional with one output channel.
 - (2) Bi-directional with one output channel.
 - (3) Bi-directional with two output channels.
- (e) Aiming of the infrared sensing inputs for skewed approaches or slight curves.

- (f) A built-in terminal block for wiring connections.
- (g) Ability to receive power from the signal discriminator with internal voltage regulation to operate from 18 to 37 volts DC.
- (h) Responsiveness to a clear lens date-encoded emitter with 0.84 (+or- 10%) Joules of energy output per flash at a distance of 2,500 feet (762m) under clear atmospheric conditions or 1,800 feet (549m) when emitter is configured with a visible light filter. Distances shall be comparable day or night.
- (i) Delivery of the necessary electrical signal to the signal discriminator via a detector cable up to 1,000 feet (305m) in length.

The Signal Discriminator shall provide the following:

- (a) Compatibility with NEMA TS2 Type 1 controllers.
- (b) A plug-in, two or four channel, multiple-priority device installed directly into a card rack within the controller cabinet.
- (c) Powered from 115 volts (95 volts AC to 135 volts AC) and 60Hz mains with an internal, regulated power supply that supports up to four infrared detectors.
- (d) Default range values re-settable by switches in the front panel.
- (e) Capability of two levels of discrimination of data-encoded infrared signals as follows:
 - (1) Verification of the presence of the base infrared signal of either 14.03509HZ +or- 0.01773Hz for Command priority, or 9.63855Hz +or- 0.00836Hz for Advantage priority.
 - (2) Determination of when vehicles are within the prescribed range.
- (f) A card edge connector including primary infrared detector inputs and power outputs.
- (g) One opto-isolated NPN output per channel that provides the following electrical signal to the appropriate pin on the card edge connector:
 - (1) 6.25Hz +or- 0.1Hz 50% on/duty square wave in response to an Advantage priority call.
 - (2) A steady ON in response to a Command priority calls.
- (h) Accommodation of two methods for setting intensity thresholds (emitter range) for high and low priority signals:
 - (1) Using a data-encoded emitter with range setting capability.
 - (2) Using any encoded emitter while manipulating the front panel switches.
- (i) A solid state POWER ON LED indicator that flashes to indicate unit diagnostic mode and illuminates steadily to indicate proper operation.
- (j) Internal diagnostics to test for proper operation and a display of fault information using the front panel LED indicators when a fault is detected.
- (k) Command (High) and Advantage (Low) solid state LED indicators for each channel to display active calls.
- (I) A test switch for each channel to test proper operation of Command and Advantage priority.
- (m) Write-on pads to allow identification of the phase and channel.
- (n) Capacity to functionally test connected detector circuits with non-functional detector circuits indicated via front panel LED's.

<u>Warranty.</u> The manufacturer shall warrant the unit from defective workmanship and/or materials during the first two- (2) years of operation from date installed.

<u>Basis of Payment:</u> The Signal Processor and detectors as shown in the plans will be paid for at the contract unit price per each for EMERGENCY VEHICLE SIGNAL CONTROL SYSTEM for each location which price shall include installation in the controller cabinet and on mast arms complete with necessary connections for proper operation.

SEEDING, CLASS 1, SPECIAL

This work shall consist of seeding and fertilizing disturbed earth surfaces in accordance with Section 250 of the Standard Specifications with the following additions and exceptions.

Amend Article 250.04 to include:

Fertilizer shall be applied at the rate of 270 pounds per acre at a proportion of 90 pounds of nitrogen, 90 pounds of phosphorus, and 90 pounds of potassium per acre. Fertilizer shall be applied by an approved mechanical spreader with the minimum being a walk-behind dispenser. Fertilizer shall be applied prior to the tilling operation. Dispensing fertilizer with hand shovels will not be allowed.

Revise Article 250.05:

All stones, boulders, debris and similar material larger than one (I) inch in diameter shall be removed from the application area prior to tilling. The seed bed shall be tilled to a minimum depth of three (3) inches with all tilling to be done by a mechanical tiller, the minimum being a walk-behind rotary garden tiller. After tilling, the seed bed shall be hand raked and all stones larger than 1/2 inch and all dirt clods larger than one (1) inch shall be removed.

Revise Article 250.06 (a):

Seeding operations for new construction (bare earth) shall be April 1 to June 30 or September 1 to December 15.

<u>Seeding Mixture:</u> The seeding mixture shall be 140 pounds of Kentucky Bluegrass per acre, 20 pounds of Creeping Red Fescue per acre and 200 pounds of Perennial Ryegrass per acre. The seed mixture shall be applied by an approved mechanical spreader with the minimum being a walk-behind dispenser. As an alternative, hydro-seeding will be allowed.

After seeding the seedbed shall be rolled by a hand-operated steel roller filled with water or hand-operated solid steel roller of sufficient weight to provide proper compaction. Applying the seed mixture by hand will not be allowed.

A cultipacker will not be required.

Applying and furnishing the fertilizer will be considered incidental to this pay item.

Basis of Payment: This work will be paid for at the contract unit price bid per acre for SEEDING, CLASS 1 (SPECIAL).

CONCRETE CURB, TYPE B (SPECIAL)

This work shall consist of constructing concrete curb in accordance with Section 606 of the Standard Specifications and as shown in the plans.

Method of Measurement: Concrete curb will be measured for payment in feet along the face of the concrete curb.

Reinforcement will not be measured for payment.

Basis of Payment: This work will be paid for at the contract unit price per foot for CONCRETE CURB, TYPE B (SPECIAL).

CHAIN LINK FENCE TO BE REMOVED AND RE-ERECTED

This work shall consist of removing and reinstalling existing chain link fence in accordance with Section 664 of the Standard Specifications and as shown in the plans at Station 106±44 RT.

Existing posts set in concrete shall be replaced and set in new concrete.

<u>Method of Measurement:</u> Chain link fence to be removed and re-erected will be measured for payment in feet along the top of the relocated fence.

<u>Basis of Payment</u>: This work will be paid for at the contract unit price per foot for CHAIN LINK FENCE TO BE REMOVED AND RE-ERECTED. This work will include all necessary accessories and concrete footings.

Page 11 of 17 Printed on 6/23/2011 9:45:04 AM

PEDESTRIAN PUSH-BUTTON, SPECIAL

This work shall conform to the requirements of Sections 888 and 1074.02 of the Standard Specifications and the following additions or exceptions.

Pedestrian pushbuttons shall be at least 2 in. (50 mm) in diameter or width. The force required to activate the pushbutton shall be no greater than 3.5 lb (15.5 N).

<u>Signage:</u> A sign shall be located immediately above the pedestrian pushbutton and parallel to the crosswalk controlled by the pushbutton. The sign shall resemble either of the following:





<u>Tactile Arrow:</u> A tactile arrow, pointing in the direction of travel controlled by a pushbutton, shall be provided either on the pushbutton or its sign. This arrow shall meet the requirements of Section X02.5.1.4 of the U.S. Access Board's "Public Rights-of-way Access Advisory Committee Report, 2001".

Basis of Payment: This work will be paid for at the contract unit price each for PEDESTRIAN PUSH-BUTTON, SPECIAL.

DETECTABLE WARNINGS (SPECIAL)

This work shall consist of furnishing and installing detectable warnings in accordance with Section 424 of the Standard Specifications and specified herein.

The detectable warnings at Maine Street Station 115+71 LT shall be black in color to match the existing detectable warnings on the west side of the entrance.

All other detectable warnings on the project shall be in accordance with Section 424 of the Standard Specifications.

<u>Basis of Payment</u>: This work will be paid for at the contract unit price per square foot for DETECTABLE WARNINGS (SPECIAL).

ļ.

VIDEO VEHICLE DETECTION SYSTEM

Revised: August 1, 2002

This work shall consist of furnishing, installing and placing into operation a vehicle detection system, which detects vehicles by processing video images and providing detection outputs to a traffic signal controller. The video detection system shall be of the same manufacture as approved within the City of Quincy, which is Econolite Control Products. This equipment shall meet the NEMA environmental, power and surge ratings as set forth in NEMA TS1 and TS2 Specifications.

Mounting Hardware: Fastened and mounting arms and other items attached to the mast arm structure shall be suitable for the weight supported and shall be compatible with the structural material. All steel hardware shall be hot-dipped galvanized. Hardware for stainless steel boxes and other stainless steel items shall be stainless steel.

Hardware: The machine vision sensors shall be four integrated imaging CCD arrays with optics, high-speed, color, imageprocessing hardware and a CPU bundled into a sealed enclosure. The environmental enclosure shall be waterproof and dust-tight to NEMA-4 specifications, and shall be pressurized with dry nitrogen to 5 ± 1 psi. The enclosure shall allow the machine vision sensor to operate satisfactorily over an ambient temperature range from -34 degrees C to +60 degrees C while exposed to precipitation as well as direct sunlight. The enclosure shall allow the image sensor horizon to be rotated during field installation. The enclosure shall include a provision at the rear of the enclosure for connection of the factoryfabricated power, communications and video signal cable. Input power to the environmental enclosure shall be 24 VAC/DC and either 50 or 60 Hz. A heater shall be at the front of the enclosure to prevent the formation of ice and condensation in cold weather, as well as to assure proper operation of the lens' iris mechanism. The heater shall not interfere with the operation of the image sensor electronics, and it shall not cause interference with the video signal. The enclosure shall be light-colored and shall include a sun shield to minimize solar heating and glare. The front edge of the sunshield shall protrude beyond the front edge of the environmental enclosure and shall include provision to divert water flow to the sides of the sunshield. The amount of overhang of the sunshield shall be adjustable to prevent direct sunlight from entering the lens or hitting the faceplate. The total weight of the image sensor in the environmental enclosure with sunshield shall be less than 2.7 kg (6 pounds). When operating in the environmental enclosure with the power, communication and video signal cable connected, the image sensor shall meet FCC class B and CE requirements for electromagnetic interference emissions.

The CCD arrays shall be directly controlled by the CPU, thus providing high video quality for detection that has virtually no noise to degrade detection performance.

The optics and camera electronics shall be directly controlled for optimal illumination for traffic detection. The lens shall be pre-focused at the factory, as required for operation. It shall be possible for the user to focus the lens, as required for operation. The machine vision sensor shall operate at a maximum rate of 30 frames per second when configured for the NTSC (US) color video standard. The machine vision sensor shall process a minimum of twenty detector zones placed anywhere in the field of view of the sensor. The video output shall have the ability to selectively show overlaid graphics indicating the current real-time detection state of each individual detector defined in the video. The sensor output NTSC color video shall be viewed with any compatible video-display device.

Sensor Hardware: The machine vision sensor shall use medium resolution color image sensors as the video source for real-time vehicle detection using either NTSC or PAL formats. As a minimum each image sensor shall produce images with a CCD sensing element with horizontal resolution of at least 500 lines and vertical resolution of at least 350 lines. Images shall be output as video conforming to NTSC or PAL specifications and provide software JPEG video compression with a useable video and resolvable features in the video image when those features have luminance levels as low as 0.1 lux at night. Useable video and resolvable features in the video image shall also be produced when those features have luminance levels as high 10,000 lux during the day.

Useable video and resolvable features in the video image shall be produced when the ratio of the luminance of the resolved features in any single video frame is 300:1. The sensor shall provide direct real-time iris and shutter speed control, be usable for video surveillance, provide an optical filter and appropriate electronic circuitry in the sensor to suppress "blooming" effects at night, and have gamma for the image sensor present at the factory to a value of 1.0.

<u>Sensor Optics</u>: The machine vision sensor shall be equipped with an integrated zoom lens with zoom and focus capabilities that can be changed using either configuration computer software or a hand-held controller.

<u>Functional:</u> The machine vision sensor shall be able to be programmed with a variety of detector types that perform specific functions selectable by software. Detector types shall include stopline detectors capable of providing presence of moving vehicle detection based upon phase status, presence detectors, directional presence, and input detectors. Additionally,

Page 13 of 17 Printed on 6/23/2011 9:45:04 AM BLR 11310 (Rev. 7/05)

phase green or red shall be displayed. The unit shall monitor a programmable contrast detector and apply video loss timing parameters to the output by implementing minimum, maximum, or user defined fixed time recall the assigned phase(s). The detector shall be capable of having Boolean logic applied to multiple detectors or a minimum number of detectors out of a total present, prior to placing a call.

Detector features shall include:

- a. Count detection outputs traffic volume statistics and generates traffic counts and occupancy.
- b. Presence detection indicate presence of a vehicle, stopped vehicle, or vehicles traveling in the wrong direction.
- c. Speed detection provide vehicle counts, speed, length, and classification.
- d. Detector function combines outputs of multiple detectors via Boolean logic functions.
- e. Label displays information on the machine vision video output and passes input information to other detectors.
- f. Detector Station collects and reports traffic data gathered over specified time intervals.
- g. Incident detection monitor traffic parameters for conditions that indicate an incident has occurred, such as an accident or a stalled vehicle that results in a sudden reduction in roadway capacity or throughput.
- h. Schedulers define plans that can be used by other detectors to specify different parameters for each time-of-day plan.
- I. Contrast Loss detection monitor the quality of the video image that the machine vision sensor is processing.
- j. Speed Alarm generates alarm outputs based on user-defined algorithms using speed.

<u>External Interfaces:</u> The external interfaces to the machine vision sensor shall include a detector port specifically to exchange detector state data with the cabinet interface devices, differential color video output, and 24 VAC/DC power to operate the sensor.

Sensor Field Interface Equipment: A communications panel shall be provided with each machine vision sensor for installation. The communications panel shall provide a terminal block for terminating power and four twisted-pair wiring to the image sensor.

Supervisor Communications Port: There shall be a supervisor communications port to configure and provide general communications. The machine vision sensor shall use an RS-485 multi-drop-network protocol to facilitate communications via a network of rack cards to a remote or local PC client/server application. The communications port shall allow the user to update the embedded software with a new software release and interact with a PC client/server application for all of the various detection requests supported by the machine vision sensor. The communications protocol over the supervisor communications port shall be the UDP/IP message packet and routing standard. This protocol shall be used throughout the field network of machine vision sensors, hubs and the host PC server application.

Detector I/O Port: The machine vision sensor detector port shall provide a dedicated, RS-485, half-duplex interface between the machine vision sensor and a detector port master such as a card rack or TS2 mini-hub. The real-time state of phase inputs shall be transmitted to the machine vision sensor. The machine vision sensor shall exchange input and output state data with the detector port master every 100 ms. The communications protocol shall be UDP/IP over the single twisted-pair wiring. A detector port master such as a TS2 mini-hub shall subsequently translate the detection states in an electrically compatible manner to a traffic signal controller:

- (1) The interface card immediately upon receipt of the state change shall apply single pin state outputs and each on or off pulse shall be guaranteed a minimum pulse width of 100 ms.
- (2) Speed outputs from 2 pins shall reflect the true output of the delay proportional to measured speed within ±1 ms.

Differential Video: The machine vision sensor shall output full motion video using a differential video port in either NTSC or PAL format. The differential video shall be transmitted over a single twisted pair.

Power: The machine vision sensor shall operate on 24 VAC/DC, 50/60 Hz at a maximum of 25 watts. The camera and processor electronics shall consume a maximum of 10 watts. The remaining 15 watts shall support an enclosure heater.

Sensor Operations Log: The machine vision sensor shall maintain a non-volatile operations log, which minimally contains:

- a. Revision numbers for the current machine vision sensor hardware and software components in operation.
- b. Title and comments for the detector configuration.
- c. Date and time the last detector configuration was downloaded to the machine vision sensor.
- d. Date and time the operation log was last cleared.
- e. Date and time communications were opened or closed with the machine vision sensor.
- f. Date and time of last power-up.
- g. Time-stamped, self-diagnosed hardware, and software errors that shall aid in system maintenance and troubleshooting.

BLR 11310 (Rev. 7/05)

<u>Sensor Vehicle Detection Performance:</u> The real time detection performance of the machine vision sensor shall be optimized by following the guidelines for the traffic application including, machine vision sensor mounting location; the number of traffic lanes to monitor; the sizing, placement, and orientation of vehicle detectors; traffic approaching and/or departing from the sensor's field of view; and minimizing the effects of lane changing maneuvers.

Detection Zone Placement: The video detection system shall provide flexible detection zone placement anywhere and at any orientation within the field of view of the machine vision sensor. Preferred detector configurations shall be detection zones placed across lanes of traffic for optimal count accuracy, detection zones placed parallel to lanes of traffic for optimal presence detection accuracy of moving or stopped vehicles. A single detection zone shall be able to replace one or more conventional detector loops connected in series. Detection zones shall be able to be overlapped for optimal road coverage. In addition, selective groups of detectors shall be able to be logically combined into a single output by using optional delay and extend timing and signal state information. Optimal detection shall be achieved when the machine vision sensor placement provides an unobstructed view of each traffic lane where vehicle detection is required. Obstructions are not limited to fixed objects. Obstruction of the view can also occur when vehicles from a lane nearer to the sensor obscure the view of the roadway of a lane further away from the sensor.

<u>Detection Zone Programming:</u> Placement of detection zones shall be by means of a portable or desktop computer using the Windows 95, 98, Millennium, Windows NT 4.0, or 2000 operating systems, a keyboard, and a mouse. The VGA monitor shall be able to show the detection zones superimposed on images of traffic scenes. The mouse and keyboard shall be used to place, size, and orient detection zones to provide optimal road coverage for vehicle detection; modify detector parameters for site geometry to optimize performance; edit previously defined detector configurations; adjust the detection zone size and placement; add detectors for additional traffic applications; reprogram the sensor for different traffic applications, changes in installation site geometry, or traffic rerouting.

It shall be possible to download detector configurations from the computer to the machine vision sensor; upload the current detector configuration that is running in the machine vision sensor; back up detector configurations by saving them to the computer's removable or fixed disks; perform the above upload, store, and retrieve functions for video snapshots of the machine vision sensors' view.

Optimal Detection: The video detection system shall provide optimal detection of vehicle passage and presence when the machine vision sensor is mounted 30 ft. or higher above the roadway, the image sensor is adjacent to the desired coverage area and the distance to the farthest detection zone locations is not greater than 10 times the mounting height of the machine vision sensor.

The machine vision sensor shall be able to view either approaching or departing traffic or both in the same field of view. The machine vision sensor, when placed at a mounting height that minimizes vehicle image occlusion and equipped with a lens to match the width of the road shall be able to monitor a maximum of 6 to 8 traffic lanes simultaneously.

<u>Detection Zone Operation:</u> The machine vision sensor's real-time detection operation shall be verifiable through the following means:

- a. View the video output of the sensor with any standard video display device (monitor).
- b. The video output of the machine vision sensor (differential twisted pair) shall be capable of selectively transmitting:
 - (1) Camera video only.
 - (2) Analog video overlaid with the current real-time detection state of each detector.
 - (3) Camera video with overlaid, scaled cross-hairs that are used for aiming the sensor (during installation).
 - (4) Individual detectors shall have the option of being hidden.
- c .Electrically monitor assigned contact closure pinouts from a detector port master such as a TS2 Mini-Hub interface card, or Detector Rack interface card. Each pin of an interface card shall have one associated LED output to reflect its output state.
- d. View the associated output LED state on the detector port master:
 - (1) An LED shall be ON when its assigned detector output or signal controller phase input is on.
 - (2) An LED shall be OFF when its assigned detector or signal controller input is off.

Count Detection Performance: Using a machine vision sensor installed within the optimal viewing specifications described above for count station traffic applications the system shall be able to accurately count vehicles with at least 96%accuracy under normal operating conditions (day and night) and at least 93%accuracy under adverse conditions. Adverse conditions are combinations of weather and lighting conditions that result from shadows, fog, rain, snow, etc.

<u>Demand Presence Detection Performance:</u> Using a machine vision sensor installed within the optimal viewing specifications described above for intersection control applications the system shall be able to accurately provide demand presence

Page 15 of 17 Printed on 6/23/2011 9:45:04 AM BLR 11310 (Rev. 7/05)

detection. The demand presence accuracy shall be based on the ability to enable a protected turning movement on an intersection stop line, when a demand exists. The probability of not detecting a vehicle for demand presence shall be less than 1-percent error under all operating conditions. In the presence of adverse conditions, the machine vision sensor shall minimize extraneous (false) protected movement calls to less than 7 %.

Speed Detection Performance: The machine vision sensor shall accurately measure average (arithmetic mean) speed of multiple vehicles with more than 98% accuracy under all operating conditions for approaching and departing traffic. The average speed measurement shall include more than 10 vehicles in the sample to ensure statistical significance. Optimal speed detection performance requires the sensor location to follow the specifications described above for count station traffic applications with the exception that the sensor must be higher than 40 feet. The machine vision sensor shall accurately measure individual vehicle speeds with more than 95% accuracy under all operating conditions for vehicles approaching the sensor (viewing the front end of vehicles), 90% accuracy for vehicles departing from the sensor (viewing the rear end of vehicles). These specifications shall apply to vehicles that travel through both the count and speed detector pair and shall not include partial detection situations created by lane changing maneuvers.

Sensor Electrical: The video output of the machine vision sensor shall be isolated from earth ground. All video connections from the sensor to the interface panel shall also be isolated from earth ground. The video output, communication, and power stages of the sensor shall include transient protection to prevent damage to the sensor due to voltage transients occurring on the cable leading from the machine vision sensor to other field terminations. Connections for video, communications and power shall be made to the image sensor using a single 18-pin circular metal shell connector (Bendix PT07C-14-18P or equivalent). The mating cable shall use a right-angle shell. The machine vision sensor shall have passed requirements for and received the CE mark. The power to the sensor shall be fused in the controller cabinet.

<u>Auxiliary Equipment</u>: The system shall be supplied with a color 10-inch monitor in the controller cabinet to display a camera field of view with detection areas overlaid. The input to the monitor shall be selectable from any of the cameras in the system via a push button selector device.

<u>Training:</u> The supplier of the video detection system shall provide two days of training to maintenance and engineering personnel in the operation, setup and maintenance of the video detection system.

Method of Measurement: Basis of Payment: This work will be paid for at the contract unit price each for VIDEO VEHICLE DETECTION SYSTEM, which price shall be payment in full for furnishing, installing, and placing into operation the equipment specified and all necessary mounting arms and hardware to the satisfaction of the Engineer.

PAINT CURB

This work shall consist of furnishing and applying pavement marking to the concrete curb in accordance with Section 780 of the Standard Specifications, BDE Special Provision for Moisture Cured Urethane Paint System and as shown in the plans.

Method of Measurement: Painting of the concrete curb will be measured for payment in feet along the face of the concrete curb.

Basis of Payment: This work will be paid for at the contract unit price per foot for PAINT CURB.

STATUS OF UTILITIES TO BE ADJUSTED

All utilities are to be contacted through the JULIE system at 1-800-892-0123

| Name and Address of Utility | | Туре | Location | Estimated Date Relocation Completed |
|--------------------------------|---|-------------------------------------|------------|-------------------------------------|
| 1. | Ameritech 6th and Broadway Quincy, Illinois 62301 | Telephone Appurtenances | Entire Job | Prior / During Construction |
| 2. | Ameren/CIPS 7th & Jersey Street Quincy, Illinois 62301 | Electric and Gas Lines | Entire Job | Prior / During Construction |
| 3. | City of Quincy Central Services Dept City Hall, 730 Maine Quincy, Illinois 62301 | Water Mains and Appurtenances | Entire Job | By Contractor |
| 4. | City of Quincy Central Services Dept City Hall, 730 Maine Quincy, Illinois 62301 | Sanitary and Storm Sewers | Entire Job | By Contractor |
| 5. | Insight Communication 2930 State Street Quincy, Illinois 62301 | s Cablevision Lines | Entire Job | Prior/ During Construction |
| 6. _. | Adams Telcom, Inc. 405 Emminga Road P.O. Box 248 Golden, Illinois 62339 | Fiber Optic Lines | Entire Job | Prior/ During Construction |

The above represents the best information of the City and is included solely for the convenience of the bidder. The applicable provisions of Articles 105.07 and 107.20 of the Standard Specifications for Road and Bridge Construction shall apply.

The Contractor should notify the Engineer, in writing, of any utility adjustment or removal which has not been completed as required for the Contractor's operations. A request, for an extension of time only, will be considered to the extent the Contractor's operations were affected.

State of Illinois Department of Transportation Bureau of Local Roads and Streets

SPECIAL PROVISION FOR COOPERATION WITH UTILITIES

Effective: January 1, 1999 Revised: January 1, 2007

All references to Sections or Articles in this specification shall be construed to mean specific Section or Article of the Standard Specifications for Road and Bridge Construction, adopted by the Department of Transportation.

Replace Article 105.07 of the Standard Specifications with the following:

"105.07 Cooperation with Utilities. The adjustment of utilities consists of the relocation, removal, replacement, rearrangements, reconstruction, improvement, disconnection, connection, shifting, new installation or altering of an existing utility facility in any manner.

When the plans or special provisions include information pertaining to the location of underground utility facilities, such information represents only the opinion of the Department as to the location of such utilities and is only included for the convenience of the bidder. The Department assumes no responsibility in respect to the sufficiency or the accuracy of the information shown on the plans relative to the location of the underground utility facilities.

Utilities which are to be adjusted shall be adjusted by the utility owner or the owner's representative or by the Contractor as a contract item. Generally, arrangements for adjusting existing utilities will be made by the Department prior to project construction; however, utilities will not necessarily be adjusted in advance of project construction and, in some cases, utilities will not be removed from the proposed construction limits. When utility adjustments must be performed in conjunction with construction, the utility adjustment work will be shown on the plans and/or covered by Special Provisions.

When the Contractor discovers a utility has not been adjusted by the owner or the owner's representative as indicated in the contract documents, or the utility is not shown on the plans or described in the Special Provisions as to be adjusted in conjunction with construction, the Contractor shall not interfere with said utility, and shall take proper precautions to prevent damage or interruption of the utility and shall promptly notify the Engineer of the nature and location of said utility.

All necessary adjustments, as determined by the Engineer, of utilities not shown on the plans or not identified by markers, will be made at no cost to the Contractor except traffic structures, light poles, etc., that are normally located within the proposed construction limits as hereinafter defined will not be adjusted unless required by the proposed improvement.

- (a) Limits of Proposed Construction for Utilities Paralleling the Roadway. For the purpose of this Article, limits of proposed construction for utilities extending in the same longitudinal direction as the roadway, shall be defined as follows:
 - (1) The horizontal limits shall be a vertical plane, outside of, parallel to, and 600 mm (2 ft) distant at right angles from the plan or revised slope limits.
 - In cases where the limits of excavation for structures are not shown on the plans, the horizontal limits shall be a vertical plane 1.2 m (4 ft) outside the edges of structure footings or the structure where no footings are required.
 - (2) The upper vertical limits shall be the regulations governing the roadbed clearance for the specific utility involved.
 - (3) The lower vertical limits shall be the top of the utility at the depth below the proposed grade as prescribed by the governing agency or the limits of excavation, whichever is less.
 - (b) Limits of Proposed Construction for Utilities Crossing the Roadway. For the purpose of this Article, limits of proposed construction for utilities crossing the roadway in a generally transverse direction shall be defined as follows:
 - (1) Utilities crossing excavations for structures that are normally made by trenching such as sewers, underdrains, etc. and all minor structures such as manholes, inlets, foundations for signs, foundations for traffic signals, etc., the limits shall be the space to be occupied by the proposed permanent construction unless otherwise required by the regulations governing the specific utility involved.
 - (2) For utilities crossing the proposed site of major structures such as bridges, sign trusses, etc., the limits shall be as defined above for utilities extending in the same general direction as the roadway.

The Contractor may make arrangements for adjustment of utilities outside of the limits of proposed construction provided the Contractor furnishes the Department with a signed agreement with the utility owner covering the adjustments to be made. The cost of any adjustments made outside the limits of proposed construction shall be the responsibility of the Contractor unless otherwise provided.

The Contractor shall request all utility owners to field locate their facilities according to Article 107.31. The Engineer may make the request for location from the utility after receipt of notice from the Contractor. On request, the Engineer will make an inspection to verify that the utility company has field located its facilities, but will not assume responsibility for the accuracy of such work. The Contractor shall be responsible for maintaining the excavations or markers provided by the utility owners. This field location procedure may be waived if the utility owner has stated in writing to the Department it is satisfied the construction plans are sufficiently accurate. If the utility owner does not submit such statement to the Department, and they do not field locate their facilities in both horizontal and vertical alignment, the Engineer will authorize the Contractor in writing to proceed to locate the facilities in the most economical and reasonable manner, subject to the approval of the Engineer, and be paid according to Article 109.04.

The Contractor shall coordinate with any planned utility adjustment or new installation and the Contractor shall take all precautions to prevent disturbance or damage to utility facilities. Any failure on the part of the utility owner, or their representative, to proceed with any planned utility adjustment or new installation shall be reported promptly by the Contractor to the Engineer orally and in writing.

The Contractor shall take all necessary precautions for the protection of the utility facilities. The Contractor shall be responsible for any damage or destruction of utility facilities resulting from neglect, misconduct, or omission in the Contractor's manner or method of execution or nonexecution of the work, or caused by defective work or the use of unsatisfactory materials. Whenever any damage or destruction of a utility facility occurs as a result of work performed by the Contractor, the utility company will be immediately notified. The utility company will make arrangements to restore such facility to a condition equal to that existing before any such damage or destruction was done.

It is understood and agreed that the Contractor has considered in the bid all of the permanent and temporary utilities in their present and/or adjusted positions.

No additional compensation will be allowed for any delays, inconvenience, or damage sustained by the Contractor due to any interference from the said utility facilities or the operation of relocating the said utility facilities.

State of Illinois Department of Transportation Bureau of Local Roads and Streets

SPECIAL PROVISION FOR INSURANCE

Effective: February 1, 2007 Revised: August 1, 2007

All references to Sections or Articles in this specification shall be construed to mean specific Section or Article of the Standard Specifications for Road and Bridge Construction, adopted by the Department of Transportation.

The Contractor shall name the following entities as additional insured under the Contractor's general liability insurance policy in accordance with Article 107.27:

City of Quincy, Illinois

The entities listed above and their officers, employees, and agents shall be indemnified and held harmless in accordance with Article 107.26.

ALKALI-SILICA REACTION FOR PRECAST AND PRECAST PRESTRESSED CONCRETE (BDE)

Effective: January 1, 2009

<u>Description</u>. This special provision is intended to reduce the risk of a deleterious alkali-silica reaction in precast and precast prestressed concrete exposed to humid or wet conditions. The special provision is not intended or adequate for concrete exposed to potassium acetate, potassium formate, sodium acetate or sodium formate. The special provision shall not apply to the dry environment (humidity less than 60 percent) found inside buildings for residential or commercial occupancy. The special provision shall also not apply to cast-in-place concrete.

Aggregate Expansion Values. Each coarse and fine aggregate will be tested by the Department for alkali reaction according to ASTM C 1260. The test will be performed with Type I or II cement having a total equivalent alkali content (Na₂O + 0.658K₂O) of 0.90 percent or greater. The Engineer will determine the assigned expansion value for each aggregate, and these values will be made available on the Department's Alkali-Silica Potential Reactivity Rating List. The Engineer may differentiate aggregate based on ledge, production method, gradation number, or other factors. An expansion value of 0.05 percent will be assigned to limestone or dolomite coarse aggregates and 0.03 percent to limestone or dolomite fine aggregates (manufactured stone sand); however the Department reserves the right to perform the ASTM C 1260 test.

Aggregate Groups. Each combination of aggregates used in a mixture will be assigned to an aggregate group. The point at which the coarse aggregate and fine aggregate expansion values intersect in the following table will determine the group.

| | AGGREGATE | GROUPS | | | |
|--|--|-----------------|-----------|--|--|
| Coarse Aggregate or Coarse Aggregate Blend | Fine Aggregate or Fine Aggregate Blend | | | | |
| ASTM C 1260 Expansion | ASTM C 1260 Expansion | | | | |
| | ≤ 0.16% | > 0.16% - 0.27% | > 0.27% | | |
| ≤ 0.16% | Group I | Group II | Group III | | |
| > 0.16% - 0.27% | Group II | Group II | Group III | | |
| > 0.27% | Group III | Group III | Group IV | | |

<u>Mixture Options</u>. Based upon the aggregate group, the following mixture options shall be used; however, the Department may prohibit a mixture option if field performance shows a deleterious alkali-silica reaction or Department testing indicates the mixture may experience a deleterious alkali-silica reaction.

Group I - Mixture options are not applicable. Use any cement or finely divided mineral.

Group II - Mixture options 1, 2, 3, 4, or 5 shall be used.

Group III - Mixture options 1, 2 and 3 combined, 4, or 5 shall be used.

Group IV - Mixture options 1, 2 and 4 combined, or 5 shall be used.

a) Mixture Option 1. The coarse or fine aggregates shall be blended to place the material in a group that will allow the selected cement or finely divided mineral to be used.

When a coarse or fine aggregate is blended, the weighted expansion value shall be calculated separately for the coarse and fine aggregate as follows:

Weighted Expansion Value = $(a/100 \times A) + (b/100 \times B) + (c/100 \times C) + ...$

Where: a, b, c... = percentage of aggregate in the blend; A, B, C...= expansion value for that aggregate.

- b) Mixture Option 2. A finely divided mineral shall be used as described in 1), 2), 3), or 4) that follow. The replacement ratio is defined as "finely divided mineral:portland cement".
 - 1) Class F Fly Ash. For Class PC concrete, precast products, and PS concrete, Class F fly ash shall replace 15 percent of the portland cement at a minimum replacement ratio of 1.5:1.
 - 2) Class C Fly Ash. For Class PC Concrete, precast products, and Class PS concrete, Class C fly ash with 18 percent to less than 26.5 percent calcium oxide content, and less than 2.0 percent loss on ignition, shall replace 20 percent of the portland cement at a minimum replacement ratio of 1:1; or at a minimum replacement ratio of 1.25:1 if the loss on ignition is 2.0 percent or greater. Class C fly ash with less than 18 percent calcium oxide content shall replace 20 percent of the portland cement at a minimum replacement ratio of 1.25:1.
 - 3) Ground Granulated Blast-Furnace Slag. For Class PC concrete, precast products, and Class PS concrete, ground granulated blast-furnace slag shall replace 25 percent of the portland cement at a minimum replacement ratio of 1:1:
 - 4) Microsilica or High Reactivity Metakaolin. Microsilica solids or high reactivity metakaolin shall be added to the mixture at a minimum 25 lb/cu yd (15 kg/cu m) or 27 lb/cu yd (16 kg/cu m) respectively.
- c) Mixture Option 3. The cement used shall have a maximum total equivalent alkali content (Na₂O + 0.658K₂O) of 0.60 percent. When aggregate in Group II is involved, any finely divided mineral may be used with a portland cement.
- d) Mixture Option 4. The cement used shall have a maximum total equivalent alkali content (Na₂O + 0.658K₂O) of 0.45 percent. When aggregate in Group II or III is involved, any finely divided mineral may be used with a portland cement.
- e) Mixture Option 5. The proposed cement or finely divided mineral may be used if the ASTM C 1567 expansion value is ≤ 0.16 percent when performed on the aggregate in

the concrete mixture with the highest ASTM C 1260 test result. The ASTM C 1567 test will be valid for two years, unless the Engineer determines the materials have changed significantly. The 0.20 percent autoclave expansion limit in ASTM C 1567 shall not apply.

If during the two year time period the Contractor needs to replace the cement, and the replacement cement has an equal or lower total equivalent alkali content $(Na_2O + 0.658K_2O)$, a new ASTM C 1567 test will not be required.

Testing. If an individual aggregate has an ASTM C 1260 expansion value > 0.16 percent, an ASTM C 1293 test may be performed by the Contractor to evaluate the Department's ASTM C 1260 test result. The ASTM C 1293 test shall be performed with Type I or II cement having a total equivalent alkali content (Na₂O + 0.658K₂O) of 0.80 percent or greater. The interior vertical wall of the ASTM C 1293 recommended container (pail) shall be half covered with a wick of absorbent material consisting of blotting paper. If the testing laboratory desires to use an alternate container or wick of absorbent material, ASTM C 1293 test results with an alkali-reactive aggregate of known expansion characteristics shall be provided to the Engineer for review and approval. If the expansion is less than 0.040 percent after one year, the aggregate will be assigned an ASTM C 1260 expansion value of 0.08 percent that will be valid for two years, unless the Engineer determines the aggregate has changed significantly.

The Engineer reserves the right to verify a Contractor's ASTM C 1293 or 1567 test result. The Engineer will not accept the result if the precision and bias for the test methods are not met.

The laboratory performing the ASTM C 1567 test shall either be accredited by the AASHTO Materials Reference Laboratory (AMRL) for ASTM C 227 under Portland Cement or Aggregate; or shall be inspected for Hydraulic Cement - Physical Tests by the Cement and Concrete Reference Laboratory (CCRL) and shall be approved by the Department. The laboratory performing the ASTM C 1293 test shall be inspected for Portland Cement Concrete by CCRL and shall be approved by the Department.

APPROVAL OF PROPOSED BORROW AREAS, USE AREAS, AND/OR WASTE AREAS (BDE)

Effective: November 1, 2008 Revised: November 1, 2010

Replace the first paragraph of Article 107.22 of the Standard Specifications with the following:

"All proposed borrow areas, including commercial borrow areas; use areas, including, but not limited to temporary access roads, detours, runarounds, plant sites, and staging and storage areas; and/or waste areas are to be designated by the Contractor to the Engineer and approved prior to their use. Such areas outside the State of Illinois shall be evaluated, at no additional cost to the Department, according to the requirements of the state in which the area lies; and approval by the authority within that state having jurisdiction for such areas shall be forwarded to the Engineer. Such areas within Illinois shall be evaluated as described herein.

A location map delineating the proposed borrow area, use area, and/or waste area shall be submitted to the Engineer for approval along with an agreement from the property owner granting the Department permission to enter the property and conduct cultural and biological resource reconnaissance surveys of the site for archaeological resources, threatened or endangered species or their designated essential habitat, wetlands, prairies, and savannahs. The type of location map submitted shall be a topographic map, a plat map, or a 7.5 minute quadrangle map. Submittals shall include the intended use of the site and provide sufficient detail for the Engineer to determine the extent of impacts to the site. The Engineer will initiate cultural and biological resource reconnaissance surveys of the site, as necessary, at no cost to the Contractor. The Engineer will advise the Contractor of the expected time required to complete all surveys. If the proposed area is within 150 ft (45 m) of the highway right-of-way, a topographic map of the proposed site will be required as specified in Article 204.02."

BITUMINOUS MATERIALS COST ADJUSTMENTS (BDE) (RETURN FORM WITH BID)

Effective: November 2, 2006

Revised: April 1, 2009

<u>Description</u>. Bituminous material cost adjustments will be made to provide additional compensation to the Contractor, or credit to the Department, for fluctuations in the cost of bituminous materials when optioned by the Contractor. The adjustments shall apply to permanent and temporary hot-mix asphalt (HMA) mixtures, bituminous surface treatments (cover and seal coats), and pavement preservation type surface treatments. The adjustments shall not apply to bituminous prime coats, tack coats, crack filling/sealing, or joint filling/sealing.

The bidder shall indicate on the attached form whether or not this special provision will be part of the contract and submit the completed form with his/her bid. Failure to submit the form, or failure to fill out the form completely, shall make this contract exempt of bituminous materials cost adjustments.

Method of Adjustment. Bituminous materials cost adjustments will be computed as follows.

 $CA = (BPI_P - BPI_L) \times (\%AC_V / 100) \times Q$

Where: CA = Cost Adjustment, \$.

BPI_P = Bituminous Price Index, as published by the Department for the month the work is performed, \$/ton (\$/metric ton).

BPI_L = Bituminous Price Index, as published by the Department for the month prior to the letting, \$/ton (\$/metric ton).

 $\% AC_V = \text{Percent of virgin Asphalt Cement in the Quantity being adjusted.}$ For HMA mixtures, the % AC $_V$ will be determined from the adjusted job mix formula. For bituminous materials applied, a performance graded or cutback asphalt will be considered to be 100% AC $_V$ and undiluted emulsified asphalt will be considered to be 65% AC $_V$.

Q = Authorized construction Quantity, tons (metric tons) (see below).

For HMA mixtures measured in square yards: Q, tons = A x D x (G_{mb} x 46.8) / 2000. For HMA mixtures measured in square meters: Q, metric tons = A x D x (G_{mb} x 24.99) / 1000. When computing adjustments for full-depth HMA pavement, separate calculations will be made for the binder and surface courses to account for their different G_{mb} and % AC_{V}

For bituminous materials measured in gallons: Q, tons = $V \times 8.33$ lb/gal x SG / 2000 For bituminous materials measured in liters: Q, metric tons = $V \times 1.0$ kg/L x SG / 1000

Where: A = Area of the HMA mixture, sq yd (sq m).

D = Depth of the HMA mixture, in. (mm).

G_{mb} = Average bulk specific gravity of the mixture, from the approved mix design.

V = Volume of the bituminous material, gal (L).

SG = Specific Gravity of bituminous material as shown on the bill of lading.

<u>Basis of Payment</u>. Bituminous materials cost adjustments may be positive or negative but will only be made when there is a difference between the BPI_L and BPI_P in excess of five percent, as calculated by:

Percent Difference = $\{(BPI_L - BPI_P) \div BPI_L\} \times 100$

Bituminous materials cost adjustments will be calculated for each calendar month in which applicable bituminous material is placed; and will be paid or deducted when all other contract requirements for the work placed during the month are satisfied. The adjustments shall not apply during contract time subject to liquidated damages for completion of the entire contract.

Return With Bid

ILLINOIS DEPARTMENT OF TRANSPORTATION

OPTION FOR BITUMINOUS MATERIALS COST ADJUSTMENTS

The bidder shall submit this completed form with his/her bid. Failure to submit the form, or failure to fill out the form completely, shall make this contract exempt of bituminous materials cost adjustments. After award, this form, when submitted, shall become part of the contract.

| Contract No | o.: <u></u> | | | | · . |
|-------------|-------------|--------------|--------------------------|----------------------------|---------|
| Company N | lame: | | | | <u></u> |
| Contractor | 's Optio | 1: | | | |
| ls your com | pany opt | ing to inclu | de this special provisio | n as part of the contract? | |
| | Yes | | No 🗌 | , | |
| Signature: | | | | Date: | |

CEMENT (BDE)

Effective: January 1, 2007 Revised: April 1, 2011

Revise Section 1001 of the Standard Specifications to read:

"SECTION 1001. CEMENT

1001.01 Cement Types. Cement shall be according to the following.

(a) Portland Cement. Acceptance of portland cement shall be according to the current Bureau of Materials and Physical Research's Policy Memorandum, "Portland or Blended Cement Acceptance Procedure for Qualified and Non-Qualified Plants".

Portland cement shall be according to AASHTO M 85, and shall meet the standard physical and chemical requirements. The Contractor has the option to use any type of portland cement listed in AASHTO M 85 unless a specific cement is specified for a construction item. Inorganic processing additions shall be limited to granulated blast-furnace slag according to the chemical requirements of AASHTO M 302, Class C or F fly ash according to the chemical requirements of AASHTO M 295, and cement kiln dust.

(b) Portland-Pozzolan Cement. Acceptance of portland-pozzolan cement shall be according to the current Bureau of Materials and Physical Research's Policy Memorandum, "Portland or Blended Cement Acceptance Procedure for Qualified and Non-Qualified Plants".

Portland-pozzolan cement shall be according to AASHTO M 240 and shall meet the standard physical and chemical requirements. The Contractor has the option to use portland-pozzolan cement unless a specific cement is specified for a construction item. Inorganic processing additions shall be limited to granulated blast-furnace slag according to the chemical requirements of AASHTO M 302, Class C or F fly ash according to the chemical requirements of AASHTO M 295, and cement kiln dust. The pozzolan constituent for Type IP using Class F fly ash shall be a maximum of 25 percent of the weight (mass) of the portland-pozzolan cement. The pozzolan constituent for Type IP using Class C fly ash shall be a maximum of 30 percent of the weight (mass) of the portland-pozzolan cement. The pozzolan constituent for Type IP using microsilica or high-reactivity metakaolin shall be a maximum of ten percent. The pozzolan constituent for Type IP using other materials shall have the approval of the Engineer.

Portland-pozzolan cement may be used in concrete mixtures when the air temperature is below 40 °F (4 °C), but the Engineer may request a trial batch of the concrete mixture to show the mix design strength requirement will be met.

(c) Portland Blast-Furnace Slag Cement. Acceptance of portland blast-furnace slag cement shall be according to the current Bureau of Materials and Physical Research's Policy

Memorandum, "Portland or Blended Cement Acceptance Procedure for Qualified and Non-Qualified Plants".

Portland blast-furnace slag cement shall be according to AASHTO M 240 and shall meet the standard physical and chemical requirements. The Contractor has the option to use portland blast-furnace slag cement unless a specific cement is specified for a construction item. Inorganic processing additions shall be limited to granulated blast-furnace slag according to the chemical requirements of AASHTO M 302, Class C or F fly ash according to the chemical requirements of AASHTO M 295, and cement kiln dust. The blast-furnace slag constituent for Type IS shall be a maximum of 35 percent of the weight (mass) of the portland blast-furnace slag cement.

Portland blast-furnace slag cement may be used in concrete mixtures when the air temperature is below 40 °F (4 °C), but the Engineer may request a trial batch of the concrete mixture to show the mix design strength requirement will be met.

- (d) Rapid Hardening Cement. Rapid hardening cement shall be used according to Article 1020.04 or when approved by the Engineer. The cement shall be on the Department's current "Approved List of Packaged, Dry, Rapid Hardening Cementitious Materials for Concrete Repairs", and shall be according to the following.
 - (1) The cement shall have a maximum final set of 25 minutes, according to Illinois Modified AASHTO T 131.
 - (2) The cement shall have a minimum compressive strength of 2000 psi (13,800 kPa) at 3.0 hours, 3200 psi (22,100 kPa) at 6.0 hours, and 4000 psi (27,600 kPa) at 24.0 hours, according to Illinois Modified AASHTO T 106.
 - (3) The cement shall have a maximum drying shrinkage of 0.050 percent at seven days, according to Illinois Modified ASTM C 596.
 - (4) The cement shall have a maximum expansion of 0.020 percent at 14 days, according to Illinois Modified ASTM C 1038.
 - (5) The cement shall have a minimum 80 percent relative dynamic modulus of elasticity; and shall not have a weight (mass) gain in excess of 0.15 percent or a weight (mass) loss in excess of 1.0 percent, after 100 cycles, according to Illinois Modified AASHTO T 161, Procedure B.
- (e) Calcium Aluminate Cement. Calcium aluminate cement shall be used according to Article 1020.04 or when approved by the Engineer. The cement shall meet the standard physical requirements for Type I cement according to AASHTO M 85, except the time of setting shall not apply. The chemical requirements shall be determined according to AASHTO T 105 and shall be as follows: minimum 38 percent aluminum oxide (Al₂O₃), maximum 42 percent calcium oxide (CaO), maximum 1 percent magnesium oxide

- (MgO), maximum 0.4 percent sulfur trioxide (SO₃), maximum 1 percent loss on ignition, and maximum 3.5 percent insoluble residue.
- **1001.02 Uniformity of Color.** Cement contained in single loads or in shipments of several loads to the same project shall not have visible differences in color.
- **1001.03 Mixing Brands and Types.** Different brands or different types of cement from the same manufacturing plant, or the same brand or type from different plants shall not be mixed or used alternately in the same item of construction unless approved by the Engineer.
- **1001.04 Storage.** Cement shall be stored and protected against damage, such as dampness which may cause partial set or hardened lumps. Different brands or different types of cement from the same manufacturing plant, or the same brand or type from different plants shall be kept separate."

CERTIFICATION OF METAL FABRICATOR (BDE)

Effective: July 1, 2010

Revise Article 106.08 of the Standard Specifications to read:

"106.08 Certification of Metal Fabricator. All fabricators performing work on metal components of structures shall be certified under the appropriate category of the AISC Quality Certification Program as follows.

- (a) Fabricators of the main load carrying steel components of welded plate girder, box girder, truss, and arch structures shall be certified under Category MBr (Major Steel Bridges).
- (b) Fabricators of the main load carrying steel components of rolled beam structures, either simple span or continuous, and overhead sign structures shall be certified under Category SBr (Simple Steel Bridges).

Fabricators of steel or other non-ferrous metal components of structures not certified under (a) or (b) above shall be certified under the program for Bridge and Highway Metal Component Manufacturers."

CONCRETE ADMIXTURES (BDE)

Effective: January 1, 2003 Revised: April 1, 2009

Replace the first paragraph of Article 1020.05(b) of the Standard Specifications to read:

"(b) Admixtures. The use of admixtures to increase the workability or to accelerate the hardening of the concrete will be permitted when approved by the Engineer. Admixture dosages shall result in the mixture meeting the specified plastic and hardened properties. The Department will maintain an Approved List of Corrosion Inhibitors. Corrosion inhibitor dosage rates shall be according to Article 1020.05(b)(12). Department will also maintain an Approved List of Concrete Admixtures, and an admixture technical representative shall be consulted when determining an admixture dosage from this list. The dosage shall be within the range indicated on the approved list unless the influence by other admixtures, jobsite conditions (such as a very short haul time), or other circumstances warrant a dosage outside the range. The Engineer shall be notified when a dosage is proposed outside the range. To determine an admixture dosage, air temperature, concrete temperature, cement source and quantity, finely divided mineral sources(s) and quantity, influence of other admixtures, haul time, placement conditions, and other factors as appropriate shall be considered. Engineer may request the Contractor to have a batch of concrete mixed in the lab or field to verify the admixture dosage is correct. An admixture dosage or combination of admixture dosages shall not delay the initial set of concrete by more than one hour. When a retarding admixture is required or appropriate for a bridge deck or bridge deck overylay pour, the initial set time shall be delayed until the deflections due to the concrete dead load are no longer a concern for inducing cracks in the completed work. However, a retarding admixture shall not be used to further extend the pour time and justify the alteration of a bridge deck pour sequence.

When determining water in admixtures for water/cement ratio, the Contractor shall calculate 70 percent of the admixture dosage as water, except a value of 50 percent shall be used for a latex admixture used in bridge deck latex concrete overlays."

Revise Section 1021 of the Standard Specifications to read:

"SECTION 1021. CONCRETE ADMIXTURES

1021.01 General. Admixtures shall be furnished in liquid form ready for use. The admixtures shall be delivered in the manufacturer's original containers, bulk tank trucks or such containers or tanks as are acceptable to the Engineer. Delivery shall be accompanied by a ticket which clearly identifies the manufacturer and trade name of the material. Containers shall be readily identifiable as to manufacturer and trade name of the material they contain.

Corrosion inhibitors will be maintained on the Department's Approved List of Corrosion Inhibitors. All other concrete admixture products will be maintained on the Department's

Approved List of Concrete Admixtures. For the admixture submittal, a report prepared by an independent laboratory accredited by the AASHTO Materials Reference Laboratory (AMRL) for Portland Cement Concrete shall be provided. The report shall show the results of physical tests conducted no more than five years prior to the time of submittal, according to applicable specifications. However, for corrosion inhibitors the ASTM G 109 test information specified in ASTM C 1582 is not required to be from and independent lab. All other information in ASTM C 1582 shall be from and independent lab.

Tests shall be conducted using materials and methods specified on a "test" concrete and a "reference" concrete, together with a certification that no changes have been made in the formulation of the material since the performance of the tests. Per the manufacturer's option, the cement content for all required tests shall either be according to applicable specifications or 5.65 cwt/cu yd (335 kg/cu m). Compressive strength test results for six months and one year will not be required.

Prior to the approval of an admixture, the Engineer reserves the right to request a sample for testing. The test and reference concrete mixtures tested by the Engineer will contain a cement content of 5.65 cwt/cu yd (335 kg/cu m). For freeze-thaw testing, the Department will perform the test according to AASHTO T 161, Procedure B. The flexural strength test will be performed according to AASHTO T 177. If the Engineer decides to test the admixture, the manufacturer shall submit AASHTO T 197 water content and set time test results on the standard cement used by the Department. The test and reference concrete mixture shall contain a cement content of 5.65 cwt/cu yd (335 kg/cu m). The manufacturer may select their lab or an independent lab to perform this testing. The laboratory is not required to be accredited by AASHTO.

The manufacturer shall include in the submittal the following admixture information: the manufacturing range for specific gravity, the midpoint and manufacturing range for residue by oven drying, and the manufacturing range for pH. The submittal shall also include an infrared spectrophotometer trace no more than five years old.

For air-entraining admixtures according to Article 1021.02, the specific gravity allowable manufacturing range shall be established by the manufacturer and the test method shall be according to ASTM C 494. For residue by oven drying and pH, the allowable manufacturing range and test methods shall be according to ASTM C 260.

For admixtures according to Articles 1021.03, 1021.04, 1021.05, 1021.06, and 1021.07, the pH allowable manufacturing range shall be established by the manufacturer and the test method shall be according to ASTM E 70. For specific gravity and residue by oven drying, the allowable manufacturing range and test methods shall be according to ASTM C 494.

When test results are more than seven years old, the manufacturer shall re-submit the infrared spectrophotometer trace and the report prepared by an independent laboratory accredited by AASHTO.

All admixtures, except chloride-based accelerators, shall contain a maximum of 0.3 percent chloride by weight (mass).

Random field samples may be taken by the Department to verify an admixture meets specification. A split sample will be provided to the manufacturer if requested. Admixtures that do not meet specification requirements or an allowable manufacturing range established by the manufacturer shall be replaced with new material.

1021.02Air-Entraining Admixtures. Air-entraining admixtures shall be according to AASHTO M 154.

1021.03 Retarding and Water-Reducing Admixtures. The admixture shall be according to the following.

- (a) The retarding admixture shall be according to AASHTO M 194, Type B (retarding) or Type D (water-reducing and retarding).
- (b) The water-reducing admixture shall be according to AASHTO M 194, Type A.
- (c) The high range water-reducing admixture shall be according to AASHTO M 194, Type F (high range water-reducing) or Type G (high range water-reducing and retarding).
- **1021.04Accelerating Admixtures.** The admixture shall be according to AASHTO M 194, Type C (accelerating) or Type E (water reducing and accelerating).
- **1021.05Self-Consolidating Admixtures.** The self-consolidating admixture system shall consist of either a high range water-reducing admixture only or a high range water-reducing admixture combined with a separate viscosity modifying admixture. The one or two component admixture system shall be capable of producing a concrete mixture that can flow around reinforcement and consolidate under its own weight without additional effort and without segregation.

The high range water-reducing admixture shall be according to AASHTO M 194, Type F.

The viscosity modifying admixture shall be according to ASTM C 494, Type S (specific performance).

- **1021.06Rheology-Controlling Admixture.** The rheology-controlling admixture shall be capable of producing a concrete mixture with a lower yield stress that will consolidate easier for slipform applications used by the Contractor. The rheology-controlling admixture shall be according to ASTM C 494, Type S (specific performance).
- **1021.07Corrosion Inhibitor.** The corrosion inhibitor shall be according to one of the following.

- (a) Calcium Nitrite. The corrosion inhibitor shall contain a minimum 30 percent calcium nitrite by weight (mass) of solution, and shall comply with the requirements of AASHTO M 194, Type C (accelerating).
- (b) Other Materials. The corrosion inhibitor shall be according to ASTM C 1582."

CONSTRUCTION AIR QUALITY - DIESEL VEHICLE EMISSIONS CONTROL (BDE)

Effective: April 1, 2009 Revised: July 1, 2009

<u>Diesel Vehicle Emissions Control</u>. The reduction of construction air emissions shall be accomplished by using cleaner burning diesel fuel. The term "equipment" refers to any and all diesel fuel powered devices rated at 50 hp and above, to be used on the project site in excess of seven calendar days over the course of the construction period on the project site (including any "rental" equipment).

All equipment on the jobsite, with engine ratings of 50 hp and above, shall be required to: use Ultra Low Sulfur Diesel fuel (ULSD) exclusively (15 ppm sulfur content or less).

Diesel powered equipment in non-compliance will not be allowed to be used on the project site, and is also subject to a notice of non-compliance as outlined below.

The Contractor shall submit copies of monthly summary reports and include certified copies of the ULSD diesel fuel delivery slips for diesel fuel delivered to the jobsite for the reporting time period, noting the quantity of diesel fuel used.

If any diesel powered equipment is found to be in non-compliance with any portion of this specification, the Engineer will issue the Contractor a notice of non-compliance and identify an appropriate period of time, as outlined below under environmental deficiency deduction, in which to bring the equipment into compliance or remove it from the project site.

Any costs associated with bringing any diesel powered equipment into compliance with these diesel vehicle emissions controls shall be considered as included in the contract unit prices bid for the various items of work involved and no additional compensation will be allowed. The Contractor's compliance with this notice and any associated regulations shall also not be grounds for a claim.

<u>Environmental Deficiency Deduction</u>. When the Engineer is notified, or determines that an environmental control deficiency exists, he/she will notify the Contractor in writing, and direct the Contractor to correct the deficiency within a specified time period. The specified time-period, which begins upon Contractor notification, will be from 1/2 hour to 24 hours long, based on the urgency of the situation and the nature of the deficiency. The Engineer shall be the sole judge regarding the time period.

The deficiency will be based on lack of repair, maintenance and diesel vehicle emissions control.

If the Contractor fails to correct the deficiency within the specified time frame, a daily monetary deduction will be imposed for each calendar day or fraction thereof the deficiency continues to exist. The calendar day(s) will begin when the time period for correction is exceeded and end

with the Engineer's written acceptance of the correction. The daily monetary deduction will be \$1,000.00 for each deficiency identified.

If a Contractor or subcontractor accumulates three environmental deficiency deductions in a contract period, the Contractor will be shutdown until the deficiency is corrected. Such a shutdown will not be grounds for any extension of contract time, waiver of penalties, or be grounds for any claim.

CONSTRUCTION AIR QUALITY - IDLING RESTRICTIONS (BDE)

Effective: April 1, 2009

Idling Restrictions. The Contractor shall establish truck-staging areas for all diesel powered vehicles that are waiting to load or unload material at the jobsite. Staging areas shall be located where the diesel emissions from the equipment will have a minimum impact on adjacent sensitive receptors. The Department will review the selection of staging areas, whether within or outside the existing highway right-of-way, to avoid locations near sensitive areas or populations to the extent possible. Sensitive receptors include, but are not limited to, hospitals, schools, residences, motels, hotels, daycare facilities, elderly housing and convalescent facilities. Diesel powered engines shall also be located as far away as possible from fresh air intakes, air conditioners, and windows. The Engineer will approve staging areas before implementation.

Diesel powered vehicle operators may not cause or allow the motor vehicle, when it is not in motion, to idle for more than a total of 10 minutes within any 60 minute period, except under any of the following circumstances:

- 1) The motor vehicle has a gross vehicle weight rating of less than 8000 lb (3630 kg).
- 2) The motor vehicle idles while forced to remain motionless because of on-highway traffic, an official traffic control device or signal, or at the direction of a law enforcement official.
- 3) The motor vehicle idles when operating defrosters, heaters, air conditioners, or other equipment solely to prevent a safety or health emergency.
- 4) A police, fire, ambulance, public safety, other emergency or law enforcement motor vehicle, or any motor vehicle used in an emergency capacity, idles while in an emergency or training mode and not for the convenience of the vehicle operator.
- 5) The primary propulsion engine idles for maintenance, servicing, repairing, or diagnostic purposes if idling is necessary for such activity.
- 6) A motor vehicle idles as part of a government inspection to verify that all equipment is in good working order, provided idling is required as part of the inspection.
- 7) When idling of the motor vehicle is required to operate auxiliary equipment to accomplish the intended use of the vehicle (such as loading, unloading, mixing, or processing cargo; controlling cargo temperature; construction operations, lumbering operations; oil or gas well servicing; or farming operations), provided that this exemption does not apply when the vehicle is idling solely for cabin comfort or to operate non-essential equipment such as air conditioning, heating, microwave ovens, or televisions.
- 8) When the motor vehicle idles due to mechanical difficulties over which the operator has no control.
- 9) The outdoor temperature is less than 32 °F (0 °C) or greater than 80 °F (26 °C).

When the outdoor temperature is greater than or equal to 32 °F (0 °C) or less than or equal to 80 °F (26 °C), a person who operates a motor vehicle operating on diesel fuel shall not cause or allow the motor vehicle to idle for a period greater than 30 minutes in any 60 minute period while waiting to weigh, load, or unload cargo or freight, unless the vehicle is in a line of vehicles that regularly and periodically moves forward.

The above requirements do not prohibit the operation of an auxiliary power unit or generator set as an alternative to idling the main engine of a motor vehicle operating on diesel fuel.

<u>Environmental Deficiency Deduction</u>. When the Engineer is notified, or determines that an environmental control deficiency exists based on non-compliance with the idling restrictions, he/she will notify the Contractor, and direct the Contractor to correct the deficiency.

If the Contractor fails to correct the deficiency a monetary deduction will be imposed. The monetary deduction will be \$1,000.00 for each deficiency identified.

DISADVANTAGED BUSINESS ENTERPRISE PARTICIPATION (BDE)

Effective: September 1, 2000 Revised: August 2, 2011

<u>FEDERAL OBLIGATION</u>. The Department of Transportation, as a recipient of federal financial assistance, is required to take all necessary and reasonable steps to ensure nondiscrimination in the award and administration of contracts. Consequently, the federal regulatory provisions of 49 CFR Part 26 apply to this contract concerning the utilization of disadvantaged business enterprises. For the purposes of this Special Provision, a disadvantaged business enterprise (DBE) means a business certified by the Department in accordance with the requirements of 49 CFR Part 26 and listed in the Illinois Unified Certification Program (IL UCP) DBE Directory.

STATE OBLIGATION. This Special Provision will also be used by the Department to satisfy the requirements of the Business Enterprise for Minorities, Females, and Persons with Disabilities Act, 30 ILCS 575. When this Special Provision is used to satisfy state law requirements on 100 percent state-funded contracts, the federal government has no involvement in such contracts (not a federal-aid contract) and no responsibility to oversee the implementation of this Special Provision by the Department on those contracts. DBE participation on 100 percent state-funded contracts will not be credited toward fulfilling the Department's annual overall DBE goal required by the US Department of Transportation to comply with the federal DBE program requirements.

<u>CONTRACTOR ASSURANCE</u>. The Contractor makes the following assurance and agrees to include the assurance in each subcontract that the Contractor signs with a subcontractor.

The Contractor, subrecipient, or subcontractor shall not discriminate on the basis of race, color, national origin, or sex in the performance of this contract. The Contractor shall carry out applicable requirements of 49 CFR Part 26 in the award and administration of contracts funded in whole or in part with federal or state funds. Failure by the Contractor to carry out these requirements is a material breach of this contract, which may result in the termination of this contract or such other remedy as the recipient deems appropriate.

OVERALL GOAL SET FOR THE DEPARTMENT. As a requirement of compliance with 49 CFR Part 26, the Department has set an overall goal for DBE participation in its federally assisted contracts. That goal applies to all federal-aid funds the Department will expend in its federally assisted contracts for the subject reporting fiscal year. The Department is required to make a good faith effort to achieve the overall goal. The dollar amount paid to all approved DBE companies performing work called for in this contract is eligible to be credited toward fulfillment of the Department's overall goal.

CONTRACT GOAL TO BE ACHIEVED BY THE CONTRACTOR. This contract includes a specific DBE utilization goal established by the Department. The goal has been included because the Department has determined that the work of this contract has subcontracting opportunities that may be suitable for performance by DBE companies. The determination is

based on an assessment of the type of work, the location of the work, and the availability of DBE companies to do a part of the work. The assessment indicates that, in the absence of unlawful discrimination, and in an arena of fair and open competition, DBE companies can be expected to perform 10.00 % of the work. This percentage is set as the DBE participation goal for this contract. Consequently, in addition to the other award criteria established for this contract, the Department will only award this contract to a bidder who makes a good faith effort to meet this goal of DBE participation in the performance of the work. A bidder makes a good faith effort for award consideration if either of the following is done in accordance with the procedures set for in this Special Provision:

- (a) The bidder documents that enough DBE participation has been obtained to meet the goal: or
- (b) The bidder documents that a good faith effort has been made to meet the goal, even though the effort did not succeed in obtaining enough DBE participation to meet the goal.

<u>DBE LOCATOR REFERENCES</u>. Bidders shall consult the IL UCP DBE Directory as a reference source for DBE-certified companies. In addition, the Department maintains a letting and item specific DBE locator information system whereby DBE companies can register their interest in providing quotes on particular bid items advertised for letting. Information concerning DBE companies willing to quote work for particular contracts may be obtained by contacting the Department's Bureau of Small Business Enterprises at telephone number (217)785-4611, or by visiting the Department's website at www.dot.il.gov.

BIDDING PROCEDURES. Compliance with this Special Provision is a material bidding requirement. The failure of the bidder to comply will render the bid not responsive.

- (a) The bidder shall submit a Disadvantaged Business Utilization Plan on Department forms SBE 2025 and 2026 with the bid.
- (b) The Utilization Plan shall indicate that the bidder either has obtained sufficient DBE participation commitments to meet the contract goal or has not obtained enough DBE participation commitments in spite of a good faith effort to meet the goal. The Utilization Plan shall further provide the name, telephone number, and telefax number of a responsible official of the bidder designated for purposes of notification of plan approval or disapproval under the procedures of this Special Provision.
- (c) The Utilization Plan shall include a DBE Participation Commitment Statement, Department form SBE 2025, for each DBE proposed for the performance of work to achieve the contract goal. For bidding purposes, submission of the completed SBE 2025 forms, signed by the DBEs and faxed to the bidder will be acceptable as long as the original is available and provided upon request. All elements of information indicated on the said form shall be provided, including but not limited to the following:
 - (1) The names and addresses of DBE firms that will participate in the contract;

- (2) A description, including pay item numbers, of the work each DBE will perform;
- (3) The dollar amount of the participation of each DBE firm participating. The dollar amount of participation for identified work shall specifically state the quantity, unit price, and total subcontract price for the work to be completed by the DBE. If partial pay items are to be performed by the DBE, indicate the portion of each item, a unit price where appropriate and the subcontract price amount;
- (4) DBE Participation Commitment Statements, form SBE 2025, signed by the bidder and each participating DBE firm documenting the commitment to use the DBE subcontractors whose participation is submitted to meet the contract goal;
- (5) if the bidder is a joint venture comprised of DBE companies and non-DBE companies, the plan must also include a clear identification of the portion of the work to be performed by the DBE partner(s); and,
- (6) If the contract goal if not met, evidence of good faith efforts.

GOOD FAITH EFFORT PROCEDURES. The contract will not be awarded until the Utilization Plan submitted by the apparent successful bidder is approved. All information submitted by the bidder must be complete, accurate and adequately document that enough DBE participation has been obtained or document that good faith efforts of the bidder, in the event enough DBE participation has not been obtained, before the Department will commit to the performance of the contract by the bidder. The Utilization Plan will be approved by the Department if the Utilization Plan documents sufficient commercially useful DBE work performance to meet the contract goal or the bidder submits sufficient documentation of a good faith effort to meet the contract goal pursuant to 49 CFR Part 26, Appendix A. The Utilization Plan will not be approved by the Department if the Utilization Plan does not document sufficient DBE participation to meet the contract goal unless the apparent successful bidder documented in the Utilization Plan that it made a good faith effort to meet the goal. This means that the bidder must show that all necessary and reasonable steps were taken to achieve the contract goal. Necessary and reasonable steps are those which, by their scope, intensity and appropriateness to the objective, could reasonably be expected to obtain sufficient DBE participation, even if they were not successful. The Department will consider the quality, quantity, and intensity of the kinds of efforts that the bidder has made. Mere pro forma efforts, in other words, efforts done as a matter of form, are not good faith efforts; rather, the bidder is expected to have taken genuine efforts that would be reasonably expected of a bidder actively and aggressively trying to obtain DBE participation sufficient to meet the contract goal.

(a) The following is a list of types of action that the Department will consider as part of the evaluation of the bidder's good faith efforts to obtain participation. These listed factors are not intended to be a mandatory checklist and are not intended to be exhaustive. Other factors or efforts brought to the attention of the Department may be relevant in appropriate cases, and will be considered by the Department.

- (1) Soliciting through all reasonable and available means (e.g. attendance at pre-bid meetings, advertising and/or written notices) the interest of all certified DBE companies that have the capability to perform the work of the contract. The bidder must solicit this interest within sufficient time to allow the DBE companies to respond to the solicitation. The bidder must determine with certainty if the DBE companies are interested by taking appropriate steps to follow up initial solicitations.
- (2) Selecting portions of the work to be performed by DBE companies in order to increase the likelihood that the DBE goals will be achieved. This includes, where appropriate, breaking out contract work items into economically feasible units to facilitate DBE participation, even when the prime Contractor might otherwise prefer to perform these work items with its own forces.
- (3) Providing interested DBE companies with adequate information about the plans, specifications, and requirements of the contract in a timely manner to assist them in responding to a solicitation.
- (4) a. Negotiating in good faith with interested DBE companies. It is the bidder's responsibility to make a portion of the work available to DBE subcontractors and suppliers and to select those portions of the work or material needs consistent with the available DBE subcontractors and suppliers, so as to facilitate DBE participation. Evidence of such negotiation includes the names, addresses, and telephone numbers of DBE companies that were considered; a description of the information provided regarding the plans and specifications for the work selected for subcontracting; and evidence as to why additional agreements could not be reached for DBE companies to perform the work.
 - b. A bidder using good business judgment would consider a number of factors in negotiating with subcontractors, including DBE subcontractors, and would take a firm's price and capabilities as well as contract goals into consideration. However, the fact that there may be some additional costs involved in finding and using DBE companies is not in itself sufficient reason for a bidder's failure to meet the contract DBE goal, as long as such costs are reasonable. Also the ability or desire of a bidder to perform the work of a contract with its own organization does not relieve the bidder of the responsibility to make good faith efforts. Bidders are not, however, required to accept higher quotes from DBE companies if the price difference is excessive or unreasonable.
- (5) Not rejecting DBE companies as being unqualified without sound reasons based on a thorough investigation of their capabilities. The bidder's standing within its industry, membership in specific groups, organizations, or associations and political or social affiliations (for example union vs. non-union employee status) are not legitimate causes for the rejection or non-solicitation of bids in the bidder's efforts to meet the project goal.

- (6) Making efforts to assist interested DBE companies in obtaining bonding, lines of credit, or insurance as required by the recipient or Contractor.
- (7) Making efforts to assist interested DBE companies in obtaining necessary equipment, supplies, materials, or related assistance or services.
- (8) Effectively using the services of available minority/women community organizations; minority/women contractors' groups; local, state, and federal minority/women business assistance offices; and other organizations as allowed on a case-by-case basis to provide assistance in the recruitment and placement of DBE companies.
- (b) If the Department determines that the apparent successful bidder has made a good faith effort to secure the work commitment of DBE companies to meet the contract goal, the Department will award the contract provided that it is otherwise eligible for award. If the Department determines that the bidder has failed to meet the requirements of this Special Provision or that a good faith effort has not been made, the Department will notify the responsible company official designated in the Utilization Plan that the bid is not responsive. The notification shall include a statement of reasons for the determination.
- (c) The bidder may request administrative reconsideration of a determination adverse to the bidder within the five working days after the receipt of the notification date of the determination by delivering the request to the Department of Transportation, Bureau of Small Business Enterprises, Contract Compliance Section, 2300 South Dirksen Parkway, Room 319, Springfield, Illinois 62764 (Telefax: (217)785-1524). Deposit of the request in the United States mail on or before the fifth business day shall not be deemed delivery. The determination shall become final if a request is not made and delivered. A request may provide additional written documentation and/or argument concerning the issues raised in the determination statement of reasons, provided the documentation and arguments address efforts made prior to submitting the bid. The request will be forwarded to the Department's Reconsideration Officer. The Reconsideration Officer will extend an opportunity to the bidder to meet in person in order to consider all issues of documentation and whether the bidder made a good faith effort to meet the goal. After the review by the Reconsideration Officer, the bidder will be sent a written decision within ten working days after receipt of the request for consideration, explaining the basis for finding that the bidder did or did not meet the goal or make adequate good faith efforts to do so. A final decision by the Reconsideration Officer that a good faith effort was made shall approve the Utilization Plan submitted by the bidder and shall clear the contract for award. A final decision that a good faith effort was not made shall render the bid not responsive.

<u>CALCULATING DBE PARTICIPATION</u>. The Utilization Plan values represent work anticipated to be performed and paid for upon satisfactory completion. The Department is only able to count toward the achievement of the overall goal and the contract goal the value of payments made for the work actually performed by DBE companies. In addition, a DBE must perform a commercially useful function on the contract to be counted. A commercially useful function is

generally performed when the DBE is responsible for the work and is carrying out its responsibilities by actually performing, managing, and supervising the work involved. The Department and Contractor are governed by the provisions of 49 CFR Part 26.55(c) on questions of commercially useful functions as it affects the work. Specific counting guidelines are provided in 49 CFR Part 26.55, the provisions of which govern over the summary contained herein.

- (a) DBE as the Contractor: 100 percent goal credit for that portion of the work performed by the DBE's own forces, including the cost of materials and supplies. Work that a DBE subcontracts to a non-DBE does not count toward the DBE goals.
- (b) DBE as a joint venture Contractor: 100 percent goal credit for that portion of the total dollar value of the contract equal to the distinct, clearly defined portion of the work performed by the DBE's own forces.
- (c) DBE as a subcontractor: 100 percent goal credit for the work of the subcontract performed by the DBE's own forces, including the cost of materials and supplies, excluding the purchase of materials and supplies or the lease of equipment by the DBE subcontractor from the prime Contractor or its affiliates. Work that a DBE subcontractor in turn subcontracts to a non-DBE does not count toward the DBE goal.
- (d) DBE as a trucker: 100 percent goal credit for trucking participation provided the DBE is responsible for the management and supervision of the entire trucking operation for which it is responsible. At least one truck owned, operated, licensed, and insured by the DBE must be used on the contract. Credit will be given for the following:
 - (1) The DBE may lease trucks from another DBE firm, including an owner-operator who is certified as a DBE. The DBE who leases trucks from another DBE receives credit for the total value of the transportation services the lessee DBE provides on the contract.
 - (2) The DBE may also lease trucks from a non-DBE firm, including from an owner-operator. The DBE who leases trucks from a non-DBE is entitled to credit only for the fee or commission is receives as a result of the lease arrangement.
- (e) DBE as a material supplier:
 - (1) 60 percent goal credit for the cost of the materials or supplies purchased from a DBE regular dealer.
 - (2) 100 percent goal credit for the cost of materials of supplies obtained from a DBE manufacturer.
 - (3) 100 percent credit for the value of reasonable fees and commissions for the procurement of materials and supplies if not a regular dealer or manufacturer.

CONTRACT COMPLIANCE. Compliance with this Special Provision is an essential part of the contract. The Department is prohibited by federal regulations from crediting the participation of a DBE included in the Utilization Plan toward either the contract goal or the Department's overall goal until the amount to be applied toward the goals has been paid to the DBE. The following administrative procedures and remedies govern the compliance by the Contractor with the contractual obligations established by the Utilization Plan. After approval of the Utilization Plan and award of the contract, the Utilization Plan and individual DBE Participation Statements become part of the contract. If the Contractor did not succeed in obtaining enough DBE participation to achieve the advertised contract goal, and the Utilization Plan was approved and contract awarded based upon a determination of good faith, the total dollar value of DBE work calculated in the approved Utilization Plan as a percentage of the awarded contract value shall become the amended contract goal. All work indicated for performance by an approved DBE shall be performed, managed, and supervised by the DBE executing the Participation Statement.

- (a) <u>NO AMENDMENT</u>. No amendment to the Utilization Plan may be made without prior written approval from the Department's Bureau of Small Business Enterprises. All requests for amendment to the Utilization Plan shall be submitted to the Department of Transportation, Bureau of Small Business Enterprises, Contract Compliance Section, 2300 South Dirksen Parkway, Room 319, Springfield, Illinois 62764. Telephone number (217)785-4611. Telefax number (217)785-1524.
- (b) <u>TERMINATION OR REPLACEMENT</u>. The Contractor shall not terminate or replace a DBE listed on the approved Utilization Plan, or perform with other forces work designated for a listed DBE except as provided in the Special Provision.
- (c) CHANGES TO WORK. Any deviation from the DBE condition-of-award or contract plans, specifications, or special provisions must be approved, in writing, by the Department as provided elsewhere in the Contract. The Contractor shall notify affected DBEs in writing of any changes in the scope of work which result in a reduction in the dollar amount condition-of-award to the contract. Where the revision includes work committed to a new DBE subcontractor, not previously involved in the project, then a Request for Approval of Subcontractor, Department form BC 260A, must be signed and submitted. If the commitment of work is in the form of additional tasks assigned to an existing subcontract, than a new Request for Approval of Subcontractor shall not be required. However, the Contractor must document efforts to assure that the existing DBE subcontractor is capable of performing the additional work and has agreed in writing to the change.
- (d) <u>ALTERNATIVE WORK METHODS</u>. In addition to the above requirements for reductions in the condition of award, additional requirements apply to the two cases of Contractorinitiated work substitution proposals. Where the contract allows alternate work methods which serve to delete or create underruns in condition of award DBE work, and the Contractor selects that alternate method or, where the Contractor proposes a substitute work method or material that serves to diminish or delete work committed to a DBE and replace it with other work, then the Contractor must demonstrate one of the following:

- (1) That the replacement work will be performed by the same DBE (as long as the DBE is certified in the respective item of work) in a modification of the condition of award; or
- (2) That the DBE is aware that its work will be deleted or will experience underruns and has agreed in writing to the change. If this occurs, the Contractor shall substitute other work of equivalent value to a certified DBE or provide documentation of good faith efforts to do so; or
- (3) That the DBE is not capable of performing the replacement work or has declined to perform the work at a reasonable competitive price. If this occurs, the Contractor shall substitute other work of equivalent value to a certified DBE or provide documentation of good faith efforts to do so.
- (e) TERMINATION AND REPLACEMENT PROCEDURES. The Contractor shall not terminate or replace a DBE subcontractor listed in the approved Utilization Plan without prior written consent. This includes, but is not limited to, instances in which the Contractor seeks to perform work originally designated for a DBE subcontractor with its own forces or those of an affiliate, a non-DBE firm, or with another DBE firm. Written consent will be granted only if the Bureau of Small Business Enterprises agrees, for reasons stated in its concurrence document, that the Contractor has good cause to terminate or replace the DBE firm. Before transmitting to the Bureau of Small Business Enterprises any request to terminate and/or substitute a DBE subcontractor, the Contractor shall give notice in writing to the DBE subcontractor, with a copy to the Bureau, of its intent to request to terminate and/or substitute, and the reason for the request. The Contractor shall give the DBE five days to respond to the Contractor's notice. The DBE so notified shall advise the Bureau and the Contractor of the reasons, if any, why it objects to the proposed termination of its subcontract and why the Bureau should not approve the Contractor's action. If required in a particular case as a matter of public necessity, the Bureau may provide a response period shorter than five days.

For purposes of this paragraph, good cause includes the following circumstances:

- (1) The listed DBE subcontractor fails or refuses to execute a written contract;
- (2) The listed DBE subcontractor fails or refuses to perform the work of its subcontract in a way consistent with normal industry standards. Provided, however, that good cause does not exist if the failure or refusal of the DBE subcontractor to perform its work on the subcontract results from the bad faith or discriminatory action of the prime contractor;
- (3) The listed DBE subcontractor fails or refuses to meet the prime Contractor's reasonable, nondiscriminatory bond requirements;

- (4) The listed DBE subcontractor becomes bankrupt, insolvent, or exhibits credit unworthiness;
- (5) The listed DBE subcontractor is ineligible to work on public works projects because of suspension and debarment proceedings pursuant 2 CFR Parts 180, 215 and 1,200 or applicable state law.
- (6) You have determined that the listed DBE subcontractor is not a responsible contractor:
- (7) The listed DBE subcontractor voluntarily withdraws from the projects and provides to you written notice of its withdrawal;
- (8) The listed DBE is ineligible to receive DBE credit for the type of work required;
- (9) A DBE owner dies or becomes disabled with the result that the listed DBE contractor is unable to complete its work on the contract;
- (10) Other documented good cause that compels the termination of the DBE subcontractor. Provided, that good cause does not exist if the prime Contractor seeks to terminate a DBE it relied upon to obtain the contract so that the prime Contractor can self-perform the work for which the DBE contractor was engaged or so that the prime Contractor can substitute another DBE or non-DBE contractor after contract award.

When a DBE is terminated, or fails to complete its work on the Contract for any reason the Contractor shall make a good faith effort to find another DBE to substitute for the original DBE to perform at least the same amount of work under the contract as the terminated DBE to the extent needed to meet the established Contract goal.

(f) PAYMENT RECORDS. The Contractor shall maintain a record of payments for work performed to the DBE participants. The records shall be made available to the Department for inspection upon request. After the performance of the final item of work or delivery of material by a DBE and final payment therefore to the DBE by the Contractor, but not later than thirty calendar days after payment has been made by the Department to the Contractor for such work or material, the Contractor shall submit a DBE Payment Agreement on Department form SBE 2115 to the Regional Engineer. If full and final payment has not been made to the DBE, the DBE Payment Agreement shall indicate whether a disagreement as to the payment required exists between the Contractor and the DBE or if the Contractor believes that the work has not been satisfactorily completed. If the Contractor does not have the full amount of work indicated in the Utilization Plan performed by the BDE companies indicated in the Utilization Plan and after good faith efforts are reviewed, the Department may deduct from contract payments to the Contractor the amount of the goal not achieved as liquidated and ascertained damages. The Contractor may request an administrative

reconsideration of any amount deducted as damages pursuant to subsection (h) of this part.

- (g) <u>ENFORCEMENT</u>. The Department reserves the right to withhold payment to the Contractor to enforce the provisions of this Special Provision. Final payment shall not be made on the contract until such time as the Contractor submits sufficient documentation demonstrating achievement of the goal in accordance with this Special Provision or after liquidated damages have been determined and collected.
- (h) <u>RECONSIDERATION</u>. Notwithstanding any other provision of the contract, including but not limited to Article 109.09 of the Standard Specifications, the Contractor my request administrative reconsideration of a decision to deduct the amount of the goal not achieved as liquidated damages. A request to reconsider shall be delivered to the Contract Compliance Section and shall be handled and considered in the same manner as set forth in paragraph (c) of "Good Faith Effort Procedures" of this Special Provision, except a final decision that a good faith effort was not made during contract performance to achieve the goal agreed to in the Utilization Plan shall be the final administrative decision of the Department.

EQUIPMENT RENTAL RATES (BDE)

Effective: August 2, 2007 Revised: January 2, 2008

Replace the second and third paragraphs of Article 105.07(b)(4)a. of the Standard Specifications with the following:

"Equipment idled which cannot be used on other work, and which is authorized to standby on the project site by the Engineer, will be paid for according to Article 109.04(b)(4)."

Replace Article 109.04(b)(4) of the Standard Specifications with the following:

- "(4) Equipment. Equipment used for extra work shall be authorized by the Engineer. The equipment shall be specifically described, be of suitable size and capacity for the work to be performed, and be in good operating condition. For such equipment, the Contractor will be paid as follows.
 - a. Contractor Owned Equipment. Contractor owned equipment will be paid for by the hour using the applicable FHWA hourly rate from the "Equipment Watch Rental Rate Blue Book" (Blue Book) in effect when the force account work begins. The FHWA hourly rate is calculated as follows.

FHWA hourly rate = (monthly rate/176) x (model year adj.) x (Illinois adj.) + EOC

Where: EOC = Estimated Operating Costs per hour (from the Blue Book)

The time allowed will be the actual time the equipment is operating on the extra work. For the time required to move the equipment to and from the site of the extra work and any authorized idle (standby) time, payment will be made at the following hourly rate: 0.5 x (FHWA hourly rate - EOC).

All time allowed shall fall within the working hours authorized for the extra work.

The rates above include the cost of fuel, oil, lubrication, supplies, small tools, necessary attachments, repairs, overhaul and maintenance of any kind, depreciation, storage, overhead, profits, insurance, and all incidentals. The rates do not include labor.

The Contractor shall submit to the Engineer sufficient information for each piece of equipment and its attachments to enable the Engineer to determine the proper equipment category. If a rate is not established in the Blue Book for a particular piece of equipment, the Engineer will establish a rate for that piece of equipment that is consistent with its cost and use in the industry.

b. Rented Equipment. Whenever it is necessary for the Contractor to rent equipment to perform extra work, the rental and transportation costs of the equipment plus five percent for overhead will be paid. In no case shall the rental rates exceed those of established distributors or equipment rental agencies.

All prices shall be agreed to in writing before the equipment is used."

-80189

FLAGGER AT SIDE ROADS AND ENTRANCES (BDE)

Effective: April 1, 2009

Revise the second paragraph of Article 701.13(a) of the Standard Specifications to read:

"The Engineer will determine when a side road or entrance shall be closed to traffic. A flagger will be required at each side road or entrance remaining open to traffic within the operation where two-way traffic is maintained on one lane of pavement. The flagger shall be positioned as shown on the plans or as directed by the Engineer."

Revise the first and second paragraph of Article 701.20(i) of the Standard Specifications to read:

"Signs, barricades, or other traffic control devices required by the Engineer over and above those specified will be paid for according to Article 109.04. All flaggers required at side roads and entrances remaining open to traffic including those that are shown on the Highway Standards and/or additional barricades required by the Engineer to close side roads and entrances will be paid for according to Article 109.04."

FRICTION AGGREGATE (BDE)

Effective: January 1, 2011

Revise Article 1004.01(a)(4) of the Standard Specifications to read:

- "(4) Crushed Stone. Crushed stone shall be the angular fragments resulting from crushing undisturbed, consolidated deposits of rock by mechanical means. Crushed stone shall be divided into the following, when specified.
 - a. Carbonate Crushed Stone. Carbonate crushed stone shall be either dolomite or limestone. Dolomite shall contain 11.0 percent or more magnesium oxide (MgO). Limestone shall contain less than 11.0 percent magnesium oxide (MgO).
 - b. Crystalline Crushed Stone. Crystalline crushed stone shall be either metamorphic or igneous stone, including but is not limited to, quartzite, granite, rhyolite and diabase."

Revise Article 1004.03(a) of the Standard Specifications to read:

"1004.03 Coarse Aggregate for Hot-Mix Asphalt (HMA). The aggregate shall be according to Article 1004.01 and the following.

(a) Description. The coarse aggregate for HMA shall be according to the following table.

| Use | Mixture | Aggregates Allowed |
|------------------|---------------------------------------|---|
| Class A | Seal or Cover | Allowed Alone or in Combination: |
| | | Gravel Crushed Gravel Carbonate Crushed Stone Crystalline Crushed Stone Crushed Sandstone Crushed Slag (ACBF) Crushed Steel Slag Crushed Concrete |
| HMA All Other | Stabilized Subbase or Shoulders | Allowed Alone or in Combination: Gravel Crushed Gravel Carbonate Crushed Stone Crystalline Crushed Stone Crushed Sandstone Crushed Slag (ACBF) Crushed Steel Slag ^{1/} Crushed Concrete |

| Use | Mixture | Aggregates Allowed | |
|------------------------------|---|---|---|
| HMA High ESAL Low ESAL | Binder IL-25.0, IL-19.0, or IL-19.0L SMA Binder | Allowed Alone or in Combination: Crushed Gravel Carbonate Crushed Stone ^{2/} Crystalline Crushed Stone Crushed Sandstone Crushed Slag (ACBF) Crushed Concrete ^{3/} | |
| HMA High ESAL Low ESAL | C Surface and Leveling Binder IL-12.5,IL-9.5, or IL-9.5L SMA Ndesign 50 Surface | Allowed Alone or in Combination: Crushed Gravel Carbonate Crushed Stone ^{2/} Crystalline Crushed Stone Crushed Sandstone Crushed Slag (ACBF) Crushed Steel Slag ^{4/} Crushed Concrete ^{3/} | |
| HMA High ESAL | D Surface and Leveling Binder IL-12.5 or IL-9.5 SMA Ndesign 50 Surface | Allowed Alone or in Combination: Crushed Gravel Carbonate Crushed Stone (other than Limestone) ^{2/} Crystalline Crushed Stone Crushed Sandstone Crushed Slag (ACBF) ^{5/} Crushed Steel Slag ^{4/5/} Crushed Concrete ^{3/} | |
| | | Other Combinations Al Up to 25% Limestone 50% Limestone 75% Limestone | lowed: With Dolomite Any Mixture D aggregate other than Dolomite Crushed Slag (ACBF) ^{5/} or Crushed |

| Use | Mixture | Aggregates Allowed | | |
|------------------|---|--|---|--|
| HMA High ESAL | E Surface IL-12.5 or IL-9.5 SMA Ndesign 80 Surface | Allowed Alone or in Combination: Crushed Gravel Crystalline Crushed Stone Crushed Sandstone Crushed Slag (ACBF) ^{5/} Crushed Steel Slag ^{5/} Crushed Concrete ^{3/} No Limestone. | | |
| | | Other Combinations A | llowed: | |
| | * . | Up to | With | |
| | | 50% Dolomite ^{2/} | Any Mixture E aggregate | |
| | | 75% Dolomite ^{2/} | Crushed Sandstone, Crushed Slag (ACBF) ^{5/} , Crushed Steel Slag ^{5/} , or Crystalline Crushed Stone | |
| | | 75% Crushed Gravel or Crushed Concrete ^{3/} | Crushed Sandstone, Crystalline Crushed Stone, Crushed Slag (ACBF) ^{5/} , or Crushed Steel Slag ^{5/} | |
| HMA | F Surface | Allowed Alone or in C | ombination: | |
| High ESAL | IL-12.5 or IL-9.5 SMA Ndesign 80 Surface | Crystalline Crushed Stone Crushed Sandstone Crushed Slag (ACBF) ^{5/} Crushed Steel Slag ^{5/} No Limestone. Other Combinations Allowed: | | |
| | | | | |
| | | Up to | With | |

| Use | Mixture | Aggregates Allowed | Aggregates Allowed | |
|-----|---------|---|---|--|
| | | 50% Crushed Gravel, Crushed Concrete ^{3/} , or Dolomite ^{2/} | Crushed Sandstone, Crushed Slag (ACBF) ^{5/} , Crushed Steel Slag ^{5/} , or Crystalline Crushed Stone | |

- 1/ Crushed steel slag allowed in shoulder surface only.
- 2/ Carbonate crushed stone shall not be used in SMA Ndesign 80. In SMA Ndesign 50, carbonate crushed stone shall not be blended with any of the other aggregates allowed alone in Ndesign 50 SMA binder or Ndesign 50 SMA surface.
- 3/ Crushed concrete will not be permitted in SMA mixes.
- 4/ Crushed steel slag shall not be used as leveling binder.
- 5/ When either slag is used, the blend percentages listed shall be by volume."

FUEL COST ADJUSTMENT (BDE) (RETURN FORM WITH BID)

Effective: April 1, 2009 Revised: July 1, 2009

<u>Description</u>. Fuel cost adjustments will be made to provide additional compensation to the Contractor, or a credit to the Department, for fluctuations in fuel prices when optioned by the Contractor. The bidder shall indicate on the attached form whether or not this special provision will be part of the contract and submit the completed form with his/her bid. Failure to submit the form or failure to indicate contract number, company name and sign and date the form shall make this contract exempt of fuel cost adjustments for all categories of work. Failure to indicate "Yes" for any category of work will make that category of work exempt from fuel cost adjustment.

General. The fuel cost adjustment shall apply to contract pay items as grouped by category. The adjustment shall only apply to those categories of work checked "Yes", and only when the cumulative plan quantities for a category exceed the required threshold. Adjustments to work items in a category, either up or down, and work added by adjusted unit price will be subject to fuel cost adjustment only when the category representing the added work was subject to the fuel cost adjustment. Added work paid for by time and materials will not be subject to fuel cost adjustment. Category descriptions and thresholds for application and the fuel usage factors which are applicable to each are as follows:

(a) Categories of Work.

- (1) Category A: Earthwork. Contract pay items performed under Sections 202, 204, and 206 including any modified standard or nonstandard items where the character of the work to be performed is considered earthwork. The cumulative total of all applicable item plan quantities shall exceed 25,000 cu yd (20,000 cu m). Included in the fuel usage factor is a weighted average 0.10 gal/cu yd (0.50 liters/cu m) factor for trucking.
- (2) Category B: Subbases and Aggregate Base Courses. Contract pay items constructed under Sections 311, 312 and 351 including any modified standard or nonstandard items where the character of the work to be performed is considered construction of a subbase or aggregate, stabilized or modified base course. The cumulative total of all applicable item plan quantities shall exceed 5000 tons (4500 metric tons). Included in the fuel usage factor is a 0.60 gal/ton (2.50 liters/metric ton) factor for trucking.
- (3) Category C: Hot-Mix Asphalt (HMA) Bases, Pavements and Shoulders. Contract pay items constructed under Sections 355, 406, 407 and 482 including any modified standard or nonstandard items where the character of the work to be performed is considered HMA bases, pavements and shoulders. The cumulative total of all applicable item plan quantities shall exceed 5000 tons (4500 metric tons). Included in the fuel usage factor is 0.60 gal/ton (2.50 liters/metric ton) factor for trucking.

- (4) Category D: Portland Cement Concrete (PCC) Bases, Pavements and Shoulders. Contract pay items constructed under Sections 353, 420, 421 and 483 including any modified standard or nonstandard items where the character of the work to be performed is considered PCC base, pavement or shoulder. The cumulative total of all applicable item plan quantities shall exceed 7500 sq yd (6000 sq m). Included in the fuel usage factor is 1.20 gal/cu yd (5.94 liters/cu m) factor for trucking.
- (5) Category E: Structures. Structure items having a cumulative bid price that exceeds \$250,000 for pay items constructed under Sections 502, 503, 504, 505, 512, 516 and 540 including any modified standard or nonstandard items where the character of the work to be performed is considered structure work when similar to that performed under these sections and not included in categories A through D.

(b) Fuel Usage Factors.

| English Units | | |
|--|--------|---------------------|
| Category | Factor | Units |
| A - Earthwork | 0.34 | gal / cu yd |
| B – Subbase and Aggregate Base courses | 0.62 | gal / ton |
| C – HMA Bases, Pavements and Shoulders | 1.05 | gal / ton |
| D - PCC Bases, Pavements and Shoulders | 2.53 | gal / cu yd |
| E - Structures | 8.00 | gal / \$1000 |
| Metric Units | | |
| Category | Factor | Units |
| A - Earthwork | 1.68 | liters / cu m |
| B – Subbase and Aggregate Base courses | 2.58 | liters / metric ton |
| C – HMA Bases, Pavements and Shoulders | 4.37 | liters / metric ton |
| D – PCC Bases, Pavements and Shoulders | 12.52 | liters / cu m |
| E – Structures | 30.28 | liters / \$1000 |
| | | |

(c) Quantity Conversion Factors.

| Category | Conversion | Factor |
|----------|------------------------------------|--|
| В | sq yd to ton sq m to metric ton | 0.057 ton / sq yd / in depth 0.00243 metric ton / sq m / mm depth |
| С | sq yd to ton sq m to metric ton | 0.056 ton / sq yd / in depth 0.00239 m ton / sq m / mm depth |
| D | sq yd to cu yd sq m to cu m | 0.028 cu yd / sq yd / in depth 0.001 cu m / sq m / mm depth |

Method of Adjustment. Fuel cost adjustments will be computed as follows.

 $CA = (FPI_P - FPI_L) \times FUF \times Q$

Where: CA = Cost Adjustment, \$

 FPI_P = Fuel Price Index, as published by the Department for the month the work is

performed, \$/gal (\$/liter)

FPI_L = Fuel Price Index, as published by the Department for the month prior to the

letting, \$/gal (\$/liter)

FUF = Fuel Usage Factor in the pay item(s) being adjusted

Q = Authorized construction Quantity, tons (metric tons) or cu yd (cu m)

The entire FUF indicated in paragraph (b) will be used regardless of use of trucking to perform the work.

Progress Payments. Fuel cost adjustments will be calculated for each calendar month in which applicable work is performed; and will be paid or deducted when all other contract requirements for the items of work are satisfied. The adjustments shall not apply during contract time subject to liquidated damages for completion of the entire contract.

Final Quantities. Upon completion of the work and determination of final pay quantities, an adjustment will be prepared to reconcile any differences between estimated quantities previously paid and the final quantities. The value for the balancing adjustment will be based on a weighted average of FPI_P and Q only for those months requiring the cost adjustment. The cost adjustment will be applicable to the final measured quantities of all applicable pay items.

<u>Basis of Payment</u>. Fuel cost adjustments may be positive or negative but will only be made when there is a difference between the FPI_L and FPI_P in excess of five percent, as calculated by:

Percent Difference = $\{(FPI_L - FPI_P) \div FPI_L\} \times 100$

Return With Bid

ILLINOIS DEPARTMENT OF TRANSPORTATION

OPTION FOR FUEL COST ADJUSTMENT

The bidder shall submit this completed form with his/her bid. Failure to submit the form or properly complete contract number, company name, and sign and date the form shall make this contract exempt of fuel cost adjustments in all categories. Failure to indicate "Yes" for any category of work at the time of bid will make that category of work exempt from fuel cost adjustment. After award, this form, when submitted shall become part of the contract.

| Contract No.: | | |
|---|----------|----------------------------------|
| Company Name: | | |
| Contractor's Option: | | |
| Is your company opting to include this special provisio following categories of work? | n as pai | rt of the contract plans for the |
| Category A Earthwork. | Yes | |
| Category B Subbases and Aggregate Base Courses | Yes | |
| Category C HMA Bases, Pavements and Shoulders | Yes | |
| Category D PCC Bases, Pavements and Shoulders | Yes | |
| Category E Structures | Yes | |
| Signature: | | Date: |

HOT-MIX ASPHALT - ANTI-STRIPPING ADDITIVE (BDE)

Effective: November 1, 2009

Revise the first and second paragraphs of Article 1030.04(c) of the Standard Specifications to read:

"(c) Determination of Need for Anti-Stripping Additive. The mixture designer shall determine if an additive is needed in the mix to prevent stripping. The determination will be made on the basis of tests performed according to Illinois Modified AASHTO T 283. To be considered acceptable by the Department as a mixture not susceptible to stripping, the conditioned to unconditioned split tensile strength ratio (TSR) shall be equal to or greater than 0.85 for 6 in. (150 mm) specimens. Mixtures, either with or without an additive, with TSRs less than 0.85 for 6 in. (150 mm) specimens will be considered unacceptable. Also, the conditioned tensile strength for mixtures containing an anti-strip additive shall not be lower than the original conditioned tensile strength determined for the same mixture without the anti-strip additive.

If it is determined that an additive is required, the additive may be hydrated lime, slaked quicklime, or a liquid additive, at the Contractor's option."

HOT-MIX ASPHALT - DENSITY TESTING OF LONGITUDINAL JOINTS (BDE)

Effective: January 1, 2010

<u>Description</u>. This work shall consist of testing the density of longitudinal joints as part of the quality control/quality assurance (QC/QA) of hot-mix asphalt (HMA). Work shall be according to Section 1030 of the Standard Specifications except as follows.

Quality Control/Quality Assurance (QC/QA). Delete the second and third sentence of the third paragraph of Article 1030.05(d)(3) of the Standard Specifications.

Add the following paragraphs to the end of Article 1030.05(d)(3) of the Standard Specifications:

"Longitudinal joint density testing shall be performed at each random density test location. Longitudinal joint testing shall be located at a distance equal to the lift thickness or a minimum of 2 in. (50 mm), from each pavement edge. (i.e. for a 4 in. (100 mm) lift the near edge of the density gauge or core barrel shall be within 4 in. (100 mm) from the edge of pavement.) Longitudinal joint density testing shall be performed using either a correlated nuclear gauge or cores.

- a. Confined Edge. Each confined edge density shall be represented by a one-minute nuclear density reading or a core density and shall be included in the average of density readings or core densities taken across the mat which represents the Individual Test.
- b. Unconfined Edge. Each unconfined edge joint density shall be represented by an average of three one-minute density readings or a single core density at the given density test location and shall meet the density requirements specified herein. The three one-minute readings shall be spaced ten feet apart longitudinally along the unconfined pavement edge and centered at the random density test location."

Revise the Density Control Limits table in Article 1030.05(d)(4) of the Standard Specifications to read:

| "Mixture Composition | Parameter | Individual Test | Unconfined Edge |
|----------------------|-------------------|---------------------------|-----------------|
| · | | (includes confined edges) | Joint Density |
| | • | | Minimum |
| IL-9.5, IL-12.5 | Ndesign ≥ 90 | 92.0 – 96.0% | 90.0% |
| IL-9.5,IL-9.5L, | Ndesign < 90 | 92.5 – 97.4% | 90.0% |
| IL-12.5 | | | |
| IL-19.0, IL-25.0 | Ndesign ≥ 90 | 93.0 – 96.0% | 90.0% |
| IL-19.0, IL-19.0L, | Ndesign < 90 | 93.0 - 97.4% | 90.0% |
| IL-25.0 | _ | | |
| SMA | Ndesign = 50 & 80 | 93.5 – 97.4% | 91.0% |
| All Other | Ndesign = 30 | 93.0 - 97.4% | 90.0%" |

HOT-MIX ASPHALT - DROP-OFFS (BDE)

Effective: January 1, 2010

Revise the third paragraph of Article 701.07 of the Standard Specifications to read:

"At locations where construction operations result in a differential in elevation exceeding 3 in. (75 mm) between the edge of pavement or edge of shoulder within 3 ft (900 mm) of the edge of the pavement and the earth or aggregate shoulders, Type I or II barricades or vertical panels shall be placed at 100 ft (30 m) centers on roadways where the posted speed limit is 45 mph or greater and at 50 ft (15 m) centers on roadways where the posted speed limit is less than 45 mph."

HOT-MIX ASPHALT - FINE AGGREGATE (BDE)

Effective: April 1, 2010

Add the following to the gradation tables of Article 1003.01(c) of the Standard Specifications:

| "FINE AGGREGATE GRADATIONS | | | | | |
|---|-----|-------|-------|--------|---------|
| Grad No. Sieve Size and Percent Passing | | | | | |
| Grad No. | 3/8 | No. 4 | No. 8 | No. 16 | No. 200 |
| FA 22 | 100 | 6/ | 6/ | 8±8 | 2±2 |

| FINE AGGREGATE GRADATIONS (Metric) | | | | | |
|------------------------------------|--------|---------|---------|---------|-------|
| Sieve Size and Percent Passing | | | | | |
| Grad No. | 9.5 mm | 4.75 mm | 2.36 mm | 1.18 mm | 75 µm |
| FA 22 | 100 | 6/ | 6/ | 8±8 | 2±2 |

6/ For the fine aggregate gradation FA 22, the aggregate producer shall set the midpoint percent passing, and the Department will apply a range of ± ten percent. The midpoint shall not be changed without Department approval."

Revise Article 1003.03(a) of the Standard Specifications to read:

"(a) Description. Fine aggregate for HMA shall consist of sand, stone sand, chats, slag sand, or steel slag sand. For gradation FA 22, uncrushed material will not be permitted."

Revise Article 1003.03(c) of the Standard Specifications to read:

"(c) Gradation. The fine aggregate gradation for all HMA shall be FA 1, FA 2, FA 20, FA 21, or FA 22.

Gradation FA 1, FA 2, or FA 3 shall be used when required for prime coat aggregate application for HMA."

LIQUIDATED DAMAGES (BDE)

Effective: April 1, 2009 Revised: April 1, 2011

Revise the table in Article 108.09 of the Standard Specifications to read:

| "Schedule of Deductions for Each Day of Overrun in Contract Time | | | | | |
|--|---|---------------------------------|-----------------------------------|--|--|
| Original Contract Amount Daily Charges | | | | | |
| From More To and Than Including | | Calendar Work Day Day | | | |
| \$ 0 100,000 500,000 1,000,000 | \$ 100,000 500,000 1,000,000 3,000,000 | \$ 475 750 1,025 1,275 | \$ 675 1,050 1,425 1,725 | | |
| 3,000,000 6,000,000 12,000,000 | 6,000,000 12,000,000 And over | 1,425 2,300 5,800 | 2,000 3,450 8,125" | | |

MOISTURE CURED URETHANE PAINT SYSTEM (BDE)

Effective: November 1, 2006 Revised: January 1, 2010

Add the following to Section 1008 of the Standard Specifications:

"1008.06 Moisture Cured Urethane Paint System. The moisture cured urethane paint system shall consist of an aromatic moisture cured urethane primer, an aromatic moisture cured urethane intermediate coat, and aliphatic moisture cured urethane finish coats. It is intended for field painting blast-cleaned existing structures.

(a) General Requirements.

- (1) Compatibility. Each coating in the system shall be supplied by the same paint manufacturer.
- (2) Toxicity. Each coating shall contain less than 0.01 percent lead in the dry film and no more than trace amounts of hexavalent chromium, cadmium, mercury or other toxic heavy metals.
- (3) Volatile Organics. The volatile organic compounds of each coating shall not exceed 2.8 lb/gal (340 g/L) as applied.

(b) Test Panel Preparation.

- (1) Substrate and Surface Preparation. Test panels shall be ASTM A 36, hot-rolled steel measuring 4 x 6 in. (100 x 150 mm). Panels shall be blast-cleaned per SSPC—SP5 white metal condition using recyclable metallic abrasive according to SSPC AB-3. The abrasive shall be a 60/40 mix of shot and grit. The shot shall be an SAE shot number S230 and the grit an SAE number G40. Hardness of the shot and grit shall be Rockwell C45. The anchor profile shall be 1.5-2.5 mils (40-65 microns) measured according to ASTM D 4417, Method C.
- (2) Application and Curing. All coatings shall be spray applied at the manufacturer's recommended film thickness. The coated panels shall be cured at least 30 days and not more than 45 days at 77 °F \pm 2 °F (25 °C \pm 2 °C) and 65 \pm 5 percent relative humidity.
- (3) Scribing. The test panels shall be scribed according to ASTM D 1654 with a single "X" mark centered on the panel. The rectangular dimensions of the scribe shall have a top width of 2 in. (50 mm) and a height of 4 in. (100 mm). The scribe cut shall expose the steel substrate as verified with a microscope.
- (4) Number of Panels. All testing shall be performed on triplicate panels.

- (c) Zinc-Rich Primer Requirements.
 - (1) Generic Type. This material shall be a single component zinc-rich aromatic moisture cured urethane primer. It shall be suitable for topcoating with urethanes.
 - (2) Zinc Dust. The zinc dust pigment shall be according to ASTM D 520, Type II.
 - (3) Slip Coefficient. The organic zinc coating shall meet a Class B AASHTO slip coefficient (0.50 or greater) for structural steel joints using ASTM A 325 (A 325M) or A 490 (A 490M) bolts.
 - (4) Adhesion. The adhesion to an abrasively blasted steel substrate shall not be less than 900 psi (6.2 MPa) when tested according to ASTM D 4541 Annex A4.
- (d) Intermediate Coat Requirements.
 - (1) Generic Type. This material shall be a single component aromatic moisture cured urethane. It shall be suitable as an intermediate coat over the primer and compatible with the finish coat.
 - (2) Color. The color of the intermediate coat shall provide a distinct contrast between the primer and the finish coat.
- (e) Urethane Finish Coat Requirements.
 - (1) Generic Type. This material shall be a single component aliphatic moisture cured urethane. It shall be suitable as a topcoat over the intermediate coat.
 - (2) Color and Hiding Power. The finish coat shall match Munsell Glossy Color 7.5G 4/8 Interstate Green, 2.5YR 3/4 Reddish Brown, 10B 3/6 Blue, or 5B 7/1 Gray. The color difference shall not exceed 3.0 Hunter Delta E Units. Color difference shall be measured by instrumental comparison of the designated Munsell standard to a minimum dry film thickness of 3 mils (75 microns) of sample coating produced on a test panel according to ASTM D 823, Practice E, Hand–Held, Blade Film Application. Color measurements shall be determined on a spectrophotometer with 45 degrees circumferential/zero degrees geometry, illuminant C, and two degrees observer angle. The spectrophotometer shall measure the visible spectrum from 380-720 nanometers with a wavelength interval and spectral bandpass of 10 nanometers.

The contrast ratio of the finish coat at 3 mils (75 microns) dry film thickness shall not be less than 0.99 when tested according to ASTM D 2805.

(3) Accelerated Weathering Resistance. Test panels shall be aluminum alloy measuring 12 x 4 in. (300 x 100 mm) prepared according to ASTM D 1730 Type A, Method 1 Solvent Cleaning. A minimum dry film thickness of 3 mils (75 microns) of

finish coat shall be applied to three test panels according to ASTM D 823, Practice E, Hand Held Blade Film Application. The coated panels shall be cured at least 30 days and not more than 45 days at 77 °F \pm 2 °F (25 °C \pm 2 °C) and 65 \pm 5 percent relative humidity. The panels shall be subjected to 300 hours of accelerated weathering using the light and water exposure apparatus (fluorescent UV - condensation type) as specified in ASTM G 53-96 and ASTM G 154 (equipped with UVB-313 lamps). The cycle shall consist of eight hours UV exposure at 140 °F (60 °C) followed by four hours of condensation at 104 °F (40 °C). After exposure, the panel shall be rinsed with clean water and allowed to dry at room temperature for one hour. The exposed panels shall not show a color change of more than 3 Hunter Delta E Units.

- (f) Three Coat System Requirements.
 - (1) Finish Coat Color. For testing purposes, the color of the finish coat shall match Federal Standard No 595, color chip 14062 (green).
 - (2) Salt Fog. When tested according to ASTM B 117 and evaluated according to AASHTO R 31, the paint system shall exhibit no spontaneous delamination and not exceed the following acceptance levels after 5,000 hours of salt fog exposure.

| Salt Fog Acceptance Criteria (max.) | | | | |
|--|--|---------------|--|--|
| Blister Conversion Value Rust Criteria | | | | |
| After 4000 Hours Maximum Creep | | Average Creep | | |
| 10 6 mm 2 mm | | | | |

(3) Cyclic Exposure. When tested according to ASTM D 5894 and evaluated according to AASHTO R 31, the paint system shall exhibit no spontaneous delamination and not exceed the following acceptance levels after 5,040 hours of cyclic exposure.

| Cyclic Exposure Acceptance Criteria (max.) | | | |
|--|---------------|---------------|--|
| Blister Conversion Value | Rust Criteria | | |
| .′ | Maximum Creep | Average Creep | |
| 10 | 13 mm | 7 mm | |

- (4) Adhesion. The adhesion to an abrasively blasted steel substrate shall not be less than 900 psi (6.2 MPa) when tested according to ASTM D 4541 Annex A4.
- (5) Freeze Thaw Stability. There shall be no reduction of adhesion, which exceeds the test precision, after 30 days of freeze/thaw/immersion testing. One 24 hour cycle shall consist of 16 hours of approximately -22 °F (-30 °C) followed by four hours of thawing at 122 °F (50 °C) and four hours tap water immersion at 77 °F (25 °C). The test panels shall remain in the freezer mode on weekends and holidays.
- (g) Qualification Samples and Tests. The manufacturer shall supply, to an independent test laboratory and to the Department, samples of the moisture cured zinc-rich urethane

primer, moisture cured urethane intermediate coat, and moisture cured aliphatic urethane finish coats for evaluation. Prior to approval and use, the manufacturer shall submit a notarized certification of the independent laboratory, together with results of all tests, stating that these materials meet the requirements as set forth herein. The certified test report shall state lots tested, manufacturer's name, product names, and dates of manufacture. New certified test results and samples for testing by the Department shall be submitted any time the manufacturing process or paint formulation is changed. All costs of testing, other than tests conducted by the Department, shall be borne by the manufacturer.

(h) Acceptance Samples and Certification. A 1 qt (1 L) sample of each lot of paint produced for use on state or local agency projects shall be submitted to the Department for testing, together with a manufacturer's certification. The certification shall state that the formulation for the lot represented is essentially identical to that used for qualification testing. All acceptance samples shall be witnessed by a representative of the Illinois Department of Transportation. The moisture cured zinc-rich primer, moisture cured urethane intermediate coat, and moisture cured aliphatic urethane finish coat shall not be used until tests are completed and they have met the requirements as set forth herein."

MULCH AND EROSION CONTROL BLANKETS (BDE)

Effective: November 1, 2010

Revised: April 1, 2011

Revise the first sentence of Article 251.03 of the Standard Specifications to read:

"Within 24 hours of seed placement, mulch by one of the following methods shall be placed on the areas specified."

Revise Article 251.03(b)(2) of the Standard Specifications to read:

"(2) Procedure 2. This procedure shall consist of stabilizing the straw with an approved mulch blower followed immediately by an overspray application of light-duty hydraulic mulch. The hydraulic mulch shall be according to Article 251.03(c) except that it shall be applied as a slurry of 900 lb (1020 kg) of mulch and 1000 gal (9500 L) of water per acre (hectare) using a hydraulic mulch applicator. The light-duty hydraulic mulch shall be agitated a minimum of five minutes before application and shall be agitated during application. The light-duty hydraulic mulch shall be applied from opposing directions to ensure even coverage."

Revise Article 251.03(c) of the Standard Specification to read:

"(c) Method 3. This method shall consist of the machine application of a light-duty hydraulic mulch. Seeding shall be conducted as a separate operation and shall not be added to the hydraulic mulch slurry. Hydraulic mulch shall not be applied when the ambient temperature is at or below freezing. To achieve full and even coverage, the hydraulic mulch shall be applied from two opposing directions. Mixing and application rates shall be according to the manufacturer's recommendations and meet the minimum application rates set in Article 1081.06(a)(2)."

Revise Article 251.03(d) of the Standard Specifications to read:

"(d) Method 3A. This method shall consist of the machine application of a heavy-duty hydraulic mulch. Seeding shall be conducted as a separate operation and shall not be added to the hydraulic mulch slurry. The hydraulic mulch shall not be applied when the ambient temperature is at or below freezing. To achieve full and even coverage, the hydraulic mulch shall be applied from two opposing directions. Mixing and application rates shall be according to the manufacturer's recommendations and meet the minimum application rates set in Article 1081.06(a)(2). The heavy-duty hydraulic mulch shall be applied using a mechanically agitated hydraulic mulching machine."

Add the following to Article 251.03 of the Standard Specifications:

"(e) Method 4. This method shall consist of applying compost combined with a performance additive designed to bind/stabilize the compost. The compost/performance additive

mixture shall be applied to the surface of the slope using a pneumatic blower at a depth of 2 in. (50 mm)."

Revise Article 251.04 of the Standard Specifications to read:

"251.04 Erosion Control Blanket. Erosion control blanket may be placed using either excelsior blanket or knitted straw blanket. Within 24 hours of seed placement, blanket shall be placed on the areas specified. Prior to placing the blanket, the areas to be covered shall be relatively free of rocks or clods over 1 1/2 in. (40 mm) in diameter, and sticks or other foreign material which will prevent the close contact of the blanket with the seed bed. If, as a result of rain, the prepared seed bed becomes crusted or eroded, or if eroded places, ruts, or depressions exist for any reason, the Contractor shall rework the soil until it is smooth and reseed such areas which are reworked.

After the area has been properly shaped, fertilized, and seeded, the blanket shall be laid out flat, evenly, and smoothly, without stretching the material. The excelsior and knitted straw blankets shall be placed so that the netting is on the top and the fibers are in contact with the soil. The heavy duty blankets shall be placed so that the heavy duty extruded plastic mesh is on the bottom.

For placement in ditches, the erosion control blanket shall be applied parallel to the centerline of the ditch so that there are no longitudinal seams within 2 ft (600 mm) of the bottom centerline of the ditch. The blanket shall be toed in on the upslope edge and shingled or overlapped with the flow.

On slopes, the blanket shall be applied either horizontally or vertically to the contour, toed in on the upslope edge, and shingled or overlapped with the flow.

When placed adjacent to the roadway, blankets shall be toed in along the edge of shoulder.

Anchoring the blankets shall be according to the manufacturer's specifications."

Revise Article 251.06(b) of the Supplemental Specifications to read:

"(b) Measured Quantities. Mulch Methods 1, 2, 3, 3A and 4 will be measured for payment in place in acres (hectares) of surface area mulched. Erosion control blanket, heavy duty erosion control blanket, and turf reinforcement mat will be measured for payment in place in square yards (square meters)."

Revise Article 251.07 of the Supplemental Specifications to read:

"251.07 Basis of Payment. This work will be paid for at the contract unit price per acre (hectare) for MULCH, METHOD 1; MULCH, METHOD 2; MULCH, METHOD 3; MULCH, METHOD 3A; MULCH, METHOD 4; and at the contract unit price per square yard (square meter) for EROSION CONTROL BLANKET, HEAVY DUTY EROSION CONTROL BLANKET, or TURF REINFORCEMENT MAT."

Revise Article 1081.06(a)(2) of the Standard Specifications to read:

"(2) Hydraulic Mulch. The mulch component shall be comprised of a minimum of 70 percent biodegradable material such as wood cellulose, paper fibers, straw or cotton and shall contain no growth or germination inhibiting factors. The remainder of the components shall consist of the manufacturer's choice of tackifiers and/or strengthening fibers needed to meet the performance specifications. Tackifiers shall be non-toxic and LC 50 test results shall be provided along with the manufacturer's certification. Hydraulic mulch shall disperse evenly and rapidly and remain in slurry when agitated with water. When uniformly applied, the slurry shall form an absorbent cover allowing percolation of water to the underlying surface. Hydraulic mulch shall be packaged in UV and moisture resistant factory labeled packages or bags with the net quantity of the packaged material plainly shown on each package. The biodegradable material shall be relatively free of glossy papers and shall not be water soluble. The hydraulic mulches shall be according to the following.

| Light-Duty Hydraulic Mulch | | |
|--|---------------------------|--|
| Property ^{1/} | Value | |
| Functional Longevity ^{2/} | 3 months | |
| Minimum Application Rates | 2000 lb/acre (2240 kg/ha) | |
| Typical Maximum Slope Gradient (V:H) | ≤ 1:3 | |
| Maximum Uninterrupted Slope Length | 50 ft (15 m) | |
| Maximum C Factor | 0.15 | |
| Minimum Vegetation Establishment ^{5/} | 200 % | |

| Heavy-Duty Hydraulic Mulch | | |
|---|---------------------------|--|
| Property ^{1/} Value | | |
| Functional Longevity ^{2/} | 12 months | |
| Minimum Application Rates | 3000 lb/acre (3360 kg/ha) | |
| Typical Maximum Slope Gradient (V:H) | ≤ 1:2 | |
| Maximum Uninterrupted Slope Length | 100 ft (30 m) | |
| Maximum C Factor ^{3/4/} | 0.02 | |
| Minimum Vegetation Establishment ⁵ | 400 % | |

- 1/ This table sets minimum requirements only. Refer to manufacturer recommendations for application rates, instructions, gradients, maximum continuous slope lengths and other site specific recommendations.
- 2/ Manufacturer's estimated time period, based upon field observations, that a material can be anticipated to provide erosion control as influenced by its composition and site-specific conditions.

- 3/ "C" Factor calculated as ratio of soil loss from HECP protected slope (tested at specified or greater gradient, h:v) to ratio of soil loss from unprotected (control) plot based on large-scale testing.
- 4/ Large-scale test methods shall be according to ASTM D 6459.
- 5/ Minimum vegetation establishment shall be calculated according to ASTM D 7322.

The manufacturer shall furnish a certification with each shipment of hydraulic mulch stating the number of packages or bags furnished and that the material complies with these requirements."

PAVEMENT MARKING REMOVAL (BDE)

Effective: April 1, 2009

Add the following to the end of the first paragraph of Article 783.03(a) of the Standard Specifications:

"The use of grinders will not be allowed on new surface courses."

PAVEMENT PATCHING (BDE)

Effective: January 1, 2010

Revise the first sentence of the second paragraph of Article 701.17(e)(1) of the Standard Specifications to read:

"In addition to the traffic control and protection shown elsewhere in the contract for pavement, two devices shall be placed immediately in front of each open patch, open hole, and broken pavement where temporary concrete barriers are not used to separate traffic from the work area."

PAYMENTS TO SUBCONTRACTORS (BDE)

Effective: June 1, 2000 Revised: January 1, 2006

Federal regulations found at 49 CFR §26.29 mandate the Department to establish a contract clause to require Contractors to pay subcontractors for satisfactory performance of their subcontracts and to set the time for such payments.

State law also addresses the timing of payments to be made to subcontractors and material suppliers. Section 7 of the Prompt Payment Act, 30 ILCS 540/7, requires that when a Contractor receives any payment from the Department, the Contractor shall make corresponding, proportional payments to each subcontractor and material supplier performing work or supplying material within 15 calendar days after receipt of the Department payment. Section 7 of the Act further provides that interest in the amount of two percent per month, in addition to the payment due, shall be paid to any subcontractor or material supplier by the Contractor if the payment required by the Act is withheld or delayed without reasonable cause. The Act also provides that the time for payment required and the calculation of any interest due applies to transactions between subcontractors and lower-tier subcontractors and material suppliers throughout the contracting chain.

This Special Provision establishes the required federal contract clause, and adopts the 15 calendar day requirement of the State Prompt Payment Act for purposes of compliance with the federal regulation regarding payments to subcontractors. This contract is subject to the following payment obligations.

When progress payments are made to the Contractor according to Article 109.07 of the Standard Specifications, the Contractor shall make a corresponding payment to each subcontractor and material supplier in proportion to the work satisfactorily completed by each subcontractor and for the material supplied to perform any work of the contract. The proportionate amount of partial payment due to each subcontractor and material supplier throughout the contracting chain shall be determined by the quantities measured or otherwise determined as eligible for payment by the Department and included in the progress payment to the Contractor. Subcontractors and material suppliers shall be paid by the Contractor within 15 calendar days after the receipt of payment from the Department. The Contractor shall not hold retainage from the subcontractors. These obligations shall also apply to any payments made by subcontractors and material suppliers to their subcontractors and material suppliers; and to all payments made to lower tier subcontractors and material suppliers throughout the contracting chain. Any payment or portion of a payment subject to this provision may only be withheld from the subcontractor or material supplier to whom it is due for reasonable cause.

This Special Provision does not create any rights in favor of any subcontractor or material supplier against the State or authorize any cause of action against the State on account of any payment, nonpayment, delayed payment, or interest claimed by application of the State Prompt Payment Act. The Department will not approve any delay or postponement of the 15 day requirement except for reasonable cause shown after notice and hearing pursuant to

Section 7(b) of the State Prompt Payment Act. State law creates other and additional remedies available to any subcontractor or material supplier, regardless of tier; who has not been paid for work properly performed or material furnished. These remedies are a lien against public funds set forth in Section 23(c) of the Mechanics Lien Act, 770 ILCS 60/23(c), and a recovery on the Contractor's payment bond according to the Public Construction Bond Act, 30 ILCS 550.

POST MOUNTING OF SIGNS (BDE)

Effective: January 1, 2011

Revise the second paragraph of Article 701.14 of the Standard Specifications to read:

"Post mounted signs shall be a breakaway design. The sign shall be within five degrees of vertical. Two posts shall be used for signs greater than 16 sq ft (1.5 sq m) in area or where the height between the sign and the ground exceeds 7 ft (2.1 m)."

RECLAIMED ASPHALT PAVEMENT (RAP) (BDE)

Effective: January 1, 2007 Revised: January 1, 2011

In Article 1030.02(g), delete the last sentence of the first paragraph in (Note 2).

Revise Section 1031 of the Standard Specifications to read:

"SECTION 1031. RECLAIMED ASPHALT PAVEMENT

1031.01 Description. Reclaimed asphalt pavement (RAP) is reclaimed asphalt pavement resulting from cold milling or crushing of an existing dense graded hot-mix asphalt (HMA) pavement. The Contractor shall supply written documentation that the RAP originated from routes or airfields under federal, state, or local agency jurisdiction.

1031.02 Stockpiles. The Contractor shall construct individual, sealed RAP stockpiles meeting one of the following definitions. No additional RAP shall be added to the pile after the pile has been sealed. Stockpiles shall be sufficiently separated to prevent intermingling at the base. Stockpiles shall be identified by signs indicating the type as listed below (i.e. "Homogeneous Surface").

Prior to milling, the Contractor shall request the District to provide verification of the quality of the RAP to clarify appropriate stockpile.

- (a) Fractionated RAP (FRAP). FRAP shall consist of RAP from Class I, Superpave (High ESAL), HMA (High ESAL), or equivalent mixtures. The coarse aggregate in FRAP shall be crushed aggregate and may represent more than one aggregate type and/or quality but shall be at least C quality. All FRAP shall be fractionated prior to testing by screening into a minimum of two size fractions with the separation occurring on or between the #4 (4.75 mm) and 1/2 in. (12.5 mm) sieves. Agglomerations shall be minimized such that 100 percent of the RAP in the coarse fraction shall pass one sieve size larger than the maximum sieve size specified for the mix the RAP will be used in.
- (b) Homogeneous. Homogeneous RAP stockpiles shall consist of RAP from Class I, Superpave (High ESAL), HMA (High ESAL), or equivalent mixtures and represent: 1) the same aggregate quality, but shall be at least C quality; 2) the same type of crushed aggregate (either crushed natural aggregate, ACBF slag, or steel slag); 3) similar gradation; and 4) similar asphalt binder content. If approved by the Engineer, combined single pass surface/binder millings may be considered "homogenous" with a quality rating dictated by the lowest coarse aggregate quality present in the mixture.
- (c) Conglomerate. Conglomerate RAP stockpiles shall consist of RAP from Class I, Superpave (High ESAL), HMA (High ESAL), or equivalent mixtures. The coarse aggregate in this RAP shall be crushed aggregate and may represent more than one aggregate type and/or quality but shall be at least C quality. This RAP may have an

inconsistent gradation and/or asphalt binder content prior to processing. All conglomerate RAP shall be processed prior to testing by crushing to where all RAP shall pass the 5/8 in. (16 mm) or smaller screen. Conglomerate RAP stockpiles shall not contain steel slag or other expansive material as determined by the Department.

- (d) Conglomerate "D" Quality (DQ). Conglomerate DQ RAP stockpiles shall consist of RAP from Class I, Superpave (High or Low ESAL), HMA (High or Low ESAL), or equivalent mixtures. The coarse aggregate in this RAP may be crushed or round but shall be at least D quality. This RAP may have an inconsistent gradation and/or asphalt binder content. Conglomerate DQ RAP stockpiles shall not contain steel slag or other expansive material as determined by the Department.
- (e) Non-Quality. RAP stockpiles that do not meet the requirements of the stockpile categories listed above shall be classified as "Non-Quality".

RAP/FRAP containing contaminants, such as earth, brick, sand, concrete, sheet asphalt, bituminous surface treatment (i.e. chip seal), pavement fabric, joint sealants, etc., will be unacceptable unless the contaminants are removed to the satisfaction of the Engineer. Sheet asphalt shall be stockpiled separately.

1031.03 Testing. When used in HMA, the RAP/FRAP shall be sampled and tested either during or after stockpiling.

For testing during stockpiling, washed extraction samples shall be run at the minimum frequency of one sample per 500 tons (450 metric tons) for the first 2000 tons (1800 metric tons) and one sample per 2000 tons (1800 metric tons) thereafter. A minimum of five tests shall be required for stockpiles less than 4000 tons (3600 metric tons).

For testing after stockpiling, the Contractor shall submit a plan for approval to the District proposing a satisfactory method of sampling and testing the RAP/FRAP pile either in-situ or by restockpiling. The sampling plan shall meet the minimum frequency required above and detail the procedure used to obtain representative samples throughout the pile for testing.

Before extraction, each field sample shall be split to obtain two samples of test sample size. One of the two test samples from the final split shall be labeled and stored for Department use. The Contractor shall extract the other test sample according to Department procedure. The Engineer reserves the right to test any sample (split or Department-taken) to verify Contractor test results.

Evaluation of Test Results. All of the extraction results shall be compiled and averaged for asphalt binder content and gradation and, when applicable G_{mm} . Individual extraction test results, when compared to the averages, will be accepted if within the tolerances listed below.

| Parameter | FRAP/Homogeneous /Conglomerate | Conglomerate "D" Quality |
|---------------|-----------------------------------|---------------------------|
| 1 in. (25 mm) | | ± 5 % |

| 1/2 in. (12.5 mm) | ± 8 % | ± 15 % |
|-------------------|-----------------------|---------|
| No. 4 (4.75 mm) | ±6% | ± 13 % |
| No. 8 (2.36 mm) | ± 5 % | |
| No. 16 (1.18 mm) | | ± 15 % |
| No. 30 (600 μm) | ± 5 % | |
| No. 200 (75 μm) | ± 2.0 % | ± 4.0 % |
| Asphalt Binder | ± 0.4 % ^{1/} | ± 0.5 % |
| G _{mm} | ± 0.03 | · |

1/ The tolerance for FRAP shall be \pm 0.3 %.

If more than 20 percent of the individual sieves are out of the gradation tolerances, or if more than 20 percent of the asphalt binder content test results fall outside the appropriate tolerances, the RAP/FRAP shall not be used in HMA unless the RAP/FRAP representing the failing tests is removed from the stockpile. All test data and acceptance ranges shall be sent to the District for evaluation.

With the approval of the Engineer, the ignition oven may be substituted for extractions according to the Illinois Test Procedure, "Calibration of the Ignition Oven for the Purpose of Characterizing Reclaimed Asphalt Pavement (RAP)".

1031.04 Quality Designation of Aggregate in RAP/FRAP.

- (a) The aggregate quality of the RAP for homogenous, conglomerate, and conglomerate "D" quality stockpiles shall be set by the lowest quality of coarse aggregate in the RAP stockpile and are designated as follows.
 - (1) RAP from Class I, Superpave (High ESAL)/HMA (High ESAL), or HMA (Low ESAL) IL-9.5L surface mixtures are designated as containing Class B quality coarse aggregate.
 - (2) RAP from Superpave (Low ESAL)/HMA (Low ESAL) IL-19.0L binder mixture is designated as Class D quality coarse aggregate.
 - (3) RAP from Class I, Superpave (High ESAL), or HMA (High ESAL) binder mixtures, bituminous base course mixtures, and bituminous base course widening mixtures are designated as containing Class C quality coarse aggregate.
 - (4) RAP from bituminous stabilized subbase and BAM shoulders are designated as containing Class D quality coarse aggregate.
- (b) The aggregate quality of FRAP shall be determined as follows.

- (1) If the Engineer has documentation of the quality of the FRAP aggregate, the Contractor shall use the assigned quality provided by the Engineer. If the quality is not known, the quality shall be determined according to Article 1031.04(b)(2).
- (2) Fractionated stockpiles containing plus #4 (4.75 mm) sieve coarse aggregate shall have a maximum tonnage of 5000 tons (4500 metric tons). The Contractor shall obtain a representative sample witnessed by the Engineer. The sample shall be a minimum of 50 lb (25 kg). The sample shall be extracted according to Illinois Modified AASHTO T 164 by a consultant prequalified by the Department for the specified testing. The consultant shall submit the test results along with the recovered aggregate to the District Office. The cost for this testing shall be paid by the Contractor. The District will forward the sample to the BMPR Aggregate Lab for MicroDeval Testing, according to Illinois Modified AASHTO T 327. A maximum loss of 15.0 percent will be applied for all HMA applications."

1031.05 Use of RAP/FRAP in HMA. The use of RAP/FRAP shall be a Contractor's option when constructing HMA in all contracts. The use of RAP/FRAP in HMA shall be as follows.

- (a) Coarse Aggregate Size. The coarse aggregate in all RAP shall be equal to or less than the nominal maximum size requirement for the HMA mixture to be produced.
- (b) Steel Slag Stockpiles. RAP stockpiles containing steel slag or other expansive material, as determined by the Department, shall be homogeneous and will be approved for use in HMA (High ESAL and Low ESAL) surface mixtures only.
- (c) Use in HMA Surface Mixtures (High and Low ESAL). RAP/FRAP stockpiles for use in HMA surface mixtures (High and Low ESAL) shall be FRAP or homogeneous in which the coarse aggregate is Class B quality or better.
- (d) Use in HMA Binder Mixtures (High and Low ESAL), HMA Base Course, and HMA Base Course Widening. RAP/FRAP stockpiles for use in HMA binder mixtures (High and Low ESAL), HMA base course, and HMA base course widening shall be FRAP, homogeneous, or conglomerate, in which the coarse aggregate is Class C quality or better.
- (e) Use in Shoulders and Subbase. RAP/FRAP stockpiles for use in HMA shoulders and stabilized subbase (HMA) shall be FRAP, homogeneous, conglomerate, or conglomerate DQ.
- (f) When the Contractor chooses the RAP option, the percentage of RAP shall not exceed the amounts indicated in the table below for a given N Design.

Max RAP Percentage

| HMA Mixtures 11, 3/ | Maximum % RAP | | |
|---------------------|-----------------|---------|---------|
| Ndesign | Binder/Leveling | Surface | Polymer |

| | Binder | | Modified |
|-----|-----------------------|-----------------------|----------|
| 30 | 30 | 30 | 10 |
| 50 | 25 | 15 | 10 |
| 70 | 15 / 25 ^{2/} | 10 / 15 ^{2/} | 10 |
| 90 | 10 | 10 | 10 |
| 105 | 10 | 10 | 10 |

- 1/ For HMA shoulder and stabilized subbase (HMA) N-30, the amount of RAP shall not exceed 50% of the mixture.
- 2/ Value of Max % RAP if homogeneous RAP stockpile of IL-9.5 RAP is utilized.
- 3/ When RAP exceeds 20 percent, the high and low virgin asphalt binder grades shall each be reduced by one grade (i.e. 25 percent RAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28). If warm mix asphalt (WMA) technology is utilized, and production temperatures do not exceed 275°°F (135°C) the grades shall be reduced as follows:

Overlavs:

When WMA contains between 20 and 30 percent RAP the high temperature shall be reduced by one grade (i.e. 25 percent RAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-22). When WMA contains 30 percent or more RAP the high and low temperature grades shall each be reduced by one grade (i.e. 35 percent RAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28).

Full Depth:

When WMA contains between 20 and 30 percent RAP, the low temperature shall be reduced by one grade (i.e. 25 percent RAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG64-28). When the WMA contains 30 percent or more RAP the high and low temperature grades shall each be reduced by one grade (i.e. 35 percent RAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28).

(g) When the Contractor chooses the FRAP option, the percentage of FRAP shall not exceed the amounts indicated in the table below for a given N Design.

Max FRAP Percentage

| HMA Mixtures 11, 2/ | Maximum % FRAP | | |
|---------------------|---------------------------|---------|---------------------|
| Ndesign | Binder/Leveling Binder | Surface | Polymer Modified |
| 30 | 35 | 35 | 10 |
| 50 | 30 | 25 | 10 |
| 70 | 25 | 20 | 10 |

| 90 | 20 | 15 | 10 |
|-----|----|------|----|
| 105 | 10 | 10 . | 10 |

- 1/ For HMA shoulder and stabilized subbase (HMA) N30, the amount of FRAP shall not exceed 50 percent of the mixture.
- 2/ When FRAP exceeds 20 percent, the high and low virgin asphalt binder grades shall each be reduced by one grade (i.e. 25 percent FRAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28). If warm mix asphalt (WMA) technology is utilized, and production temperatures do not exceed 275°°F (135°C) the grades shall be reduced as follows:

Overlays:

When WMA contains between 20 and 30 percent FRAP the high temperature shall be reduced by one grade (i.e. 25 percent FRAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-22). When WMA contains 30 percent or more FRAP the high and low temperature grades shall each be reduced by one grade (i.e. 35 percent FRAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28).

Full Depth:

When WMA contains between 20 and 30 percent FRAP, the low temperature shall be reduced by one grade (i.e. 25 percent FRAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG64-28). When the WMA contains 30 percent or more FRAP the high and low temperature grades shall each be reduced by one grade (i.e. 35 percent FRAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28).

1031.06 HMA Mix Designs. At the Contractor's option, HMA mixtures may be constructed utilizing RAP/FRAP material meeting the above detailed requirements.

RAP/FRAP designs shall be submitted for volumetric verification. If additional RAP/FRAP stockpiles are tested and found that no more than 20 percent of the results, as defined under "Testing" herein, are outside of the control tolerances set for the original RAP/FRAP stockpile and HMA mix design, and meets all of the requirements herein, the additional RAP/FRAP stockpiles may be used in the original mix design at the percent previously verified.

1031.07 HMA Production. The coarse aggregate in all RAP used shall be equal to or less than the nominal maximum size requirement for the HMA mixture being produced.

To remove or reduce agglomerated material, a scalping screen, gator, crushing unit, or comparable sizing device approved by the Engineer shall be used in the RAP feed system to remove or reduce oversized material. If material passing the sizing device adversely affects the mix production or quality of the mix, the sizing device shall be set at a size specified by the Engineer.

If the RAP/FRAP control tolerances or QC/QA test results require corrective action, the Contractor shall cease production of the mixture containing RAP/FRAP and either switch to the virgin aggregate design or submit a new RAP/FRAP design.

HMA plants utilizing RAP/FRAP shall be capable of automatically recording and printing the following information.

- (a) Dryer Drum Plants.
 - (1) Date, month, year, and time to the nearest minute for each print.
 - (2) HMA mix number assigned by the Department.
 - (3) Accumulated weight of dry aggregate (combined or individual) in tons (metric tons) to the nearest 0.1 ton (0.1 metric ton).
 - (4) Accumulated dry weight of RAP/FRAP in tons (metric tons) to the nearest 0.1 ton (0.1 metric ton).
 - (5) Accumulated mineral filler in revolutions, tons (metric tons), etc. to the nearest 0.1 unit.
 - (6) Accumulated asphalt binder in gallons (liters), tons (metric tons), etc. to the nearest 0.1 unit.
 - (7) Residual asphalt binder in the RAP/FRAP material as a percent of the total mix to the nearest 0.1 percent.
 - (8) Aggregate and RAP/FRAP moisture compensators in percent as set on the control panel. (Required when accumulated or individual aggregate and RAP/FRAP are printed in wet condition.)
- (b) Batch Plants.
 - (1) Date, month, year, and time to the nearest minute for each print.
 - (2) HMA mix number assigned by the Department.
 - (3) Individual virgin aggregate hot bin batch weights to the nearest pound (kilogram).
 - (4) Mineral filler weight to the nearest pound (kilogram).
 - (5) RAP/FRAP weight to the nearest pound (kilogram).
 - (6) Virgin asphalt binder weight to the nearest pound (kilogram).

(7) Residual asphalt binder in the RAP/FRAP material as a percent of the total mix to the nearest 0.1 percent.

The printouts shall be maintained in a file at the plant for a minimum of one year or as directed by the Engineer and shall be made available upon request. The printing system will be inspected by the Engineer prior to production and verified at the beginning of each construction season thereafter.

1031.08 RAP in Aggregate Surface Course and Aggregate Shoulders. The use of RAP in aggregate surface course and aggregate shoulders shall be as follows.

- (a) Stockpiles and Testing. RAP stockpiles may be any of those listed in Article 1031.02, except "Non-Quality" and "FRAP". The testing requirements of Article 1031.03 shall not apply.
- (b) Gradation. One hundred percent of the RAP material shall pass the 1 1/2 in. (37.5 mm) sieve. The RAP material shall be reasonably well graded from coarse to fine. RAP material that is gap-graded or single sized will not be accepted."

SEEDING (BDE)

Effective: July 1, 2004 Revised: July 1, 2010

Revise the following seeding mixtures shown in Table 1 of Article 250.07 of the Standard Specifications to read:

| | u. | Table 1 - SEEDING MIXTURES | |
|----|------------------------|--|-------------------------|
| | Class – Type | Seeds | lb/acre (kg/hectare) |
| 1A | Salt Tolerant | Bluegrass | 60 (70) |
| | Lawn Mixture 7/ | Perennial Ryegrass | 20 (20) |
| | - | Red Fescue | 20 (20) |
| | | (Audubon, Sea Link, or Epic) | , , |
| | | Hard Fescue | 20 (20) |
| | | (Rescue 911, Spartan II, or Reliant IV) | |
| | | Fults Salt Grass 1/ or Salty Alkaligrass | 60 (70) |
| 2 | Roadside Mixture 7/ | Tall Fescue | 100 (110) |
| | | (Inferno, Tarheel II, Quest, Blade | |
| | · | Runner, or Falcon IV) | • |
| | • | Perennial Ryegrass | 50 (55) |
| | | Creeping Red Fescue | 40 (50) |
| | | Red Top | 10 (10) |
| 2A | Salt Tolerant | Tall Fescue | 60 (70) |
| | Roadside Mixture 7/ | (Inferno, Tarheel II, Quest, Blade | (/ |
| | riodasias iriixiais i, | Runner, or Falcon IV) | |
| | | Perennial Ryegrass | 20 (20) |
| | | Red Fescue | 30 (20) |
| | • | (Audubon, Sea Link, or Epic) | 33 (23) |
| | | Hard Fescue | 30 (20) |
| | | (Rescue 911, Spartan II, or Reliant IV) | (/ |
| | | Fults Salt Grass 1/ or Salty Alkaligrass | 60 (70) |
| 3 | Northern Illinois | Elymus Canadensis | 5 (5) |
| | Slope Mixture 7/ | (Canada Wild Rye) | - (-) |
| | Ciopo Mixturo 17 | Perennial Ryegrass | 20 (20) |
| | | Alsike Cover 2/ | 5 (5) |
| | • | Desmanthus Illinoensis | 2 (2) |
| | | (Illinois Bundleflower) 2/, 5/ | - (-) |
| | | Andropogon Scoparius | 12 (12) |
| | | (Little Bluestem) 5/ | . – (. – / |
| | | Bouteloua Curtipendula | 10 (10) |
| | | (Side-Oats Grama) | (/ |
| | | Fults Salt Grass 1/ or Salty Alkaligrass | 30 (35) |
| | | Oats, Spring | 50 (55) |
| | | Slender Wheat Grass 5/ | 15 (15) |
| | | Buffalo Grass (Cody or Bowie) 4/, 5/, 9/ | 5 (5) |

| "Table 1 - SEEDING MIXTURES | | | | |
|-----------------------------|-------------------------------|---|----------|--|
| 6A | Salt Tolerant Conservation | Andropogon Scoparius (Little Bluestem) 5/ | 5 (5) | |
| | Mixture | Elymus Canadensis (Canada Wild Rye) 5/ | 2 (2) | |
| | | Buffalo Grass (Cody or Bowie) 4/, 5/, 9/ | 5 (5) | |
| | | Vernal Alfalfa 2/ | 15 (15) | |
| | | Oats, Spring | 48 (55) | |
| | | Fults Salt Grass 1/ or Salty Alkaligrass | 20 (20)" | |

Revise Note 7 of Table 1 – Seeding Mixtures of Article 250.07 of the Standard Specifications to read:

"7/ In Districts 1 through 6, the planting times shall be April 1 to June 15 and August 1 to November 1. In Districts 7 through 9, the planting times shall be March 1 to June 1 and August 1 to November 15. Seeding may be performed outside these dates provided the Contractor guarantees a minimum of 75 percent uniform growth over the entire seeded area(s) after a period of establishment. Inspection dates for the period of establishment will be as follows: Seeding conducted in Districts 1 through 6 between June 16 and July 31 will be inspected after April 15 and seeding conducted between November 2 and March 31 will be inspected after September 15. Seeding conducted in Districts 7 through 9 between June 2 and July 31 will be inspected after April 15 and seeding conducted between November 16 and February 28 will be inspected after September 15. The guarantee shall be submitted to the Engineer in writing prior to performing the work. After the period of establishment, areas not exhibiting 75 percent uniform growth shall be interseeded or reseeded, as determined by the Engineer, at no additional cost to the Department."

Revise the first paragraph of Article 1081.04(a) of the Standard Specifications to read:

"(a) Sampling and Testing. Each lot of seed furnished shall be tested by a State Agriculture Department (including other States) or by land grant college or university agricultural sections or by a Registered Seed Technologist. Germination testing of seed shall be accomplished within the 12 months prior to the seed being installed on the project."

Delete the last sentence of the first paragraph of Article 1081.04(c)(2) of the Standard Specifications.

Revise Table II of Article 1081.04(c)(6) of the Standard Specifications to read:

| | | - TAI | BLE II | | | |
|--|------|--------|--------|------|-----------------|-------|
| ······································ | Hard | | Pure | | Secondary * | |
| | Seed | Purity | Live | Weed | Noxious Weeds | |
| | % | % * | Seed % | % | No. per oz (kg) | |
| Variety of Seeds | Max. | Min. | Min. | Max. | Max. Permitted | Notes |
| Alfalfa | 20 | 92 | 89 | 0.50 | 6 (211) | 1/ |

| | | TAI | BLE II | | | |
|-----------------------------|------|-----------------|--------|------|-----------------|-------|
| | Hard | | Pure | | Secondary * | |
| | Seed | Purity | Live | Weed | . Noxious Weeds | |
| | % | % * | Seed % | % | No. per oz (kg) | |
| Variety of Seeds | Max. | Min. | Min. | Max. | Max. Permitted | Notes |
| Clover, Alsike | 15 | 92 | 87 | 0.30 | 6 (211) | 2/ |
| Red Fescue, Audubon | 0 | 97 | 82 | 0.10 | 3 (105) | - |
| Red Fescue, Creeping | - | 97 | 82 | 1.00 | 6 (211) | - |
| Red Fescue, Epic | - | [.] 98 | 83 | 0.05 | 1 (35) | - |
| Red Fescue, Sea Link | - | 98 | 83 | 0.10 | 3 (105) | - |
| Tall Fescue, Blade Runner | - | 98 | 83 | 0.10 | 2 (70) | - |
| Tall Fescue, Falcon IV | - | 98 | 83 | 0.05 | 1 (35) | |
| Tall Fescue, Inferno | 0 | 98 | 83 | 0.10 | 2 (70) | - |
| Tall Fescue, Tarheel II | - | 97 | 82 | 1.00 | 6 (211) | - |
| Tall Fescue, Quest | 0 | 98 | 83 | 0.10 | 2 (70) | |
| Fults Salt Grass | 0 | 98 | 85 | 0.10 | 2 (70) | - |
| Salty Alkaligrass | 0 | 98 | 85 | 0.10 | 2 (70) | |
| Kentucky Bluegrass | - | 97 | 80 | 0.30 | 7 (247) | 4/ |
| Oats | - | 92 | 88 | 0.50 | 2 (70) | 3/ |
| Redtop | - | 90 | 78 | 1.80 | 5 (175) | 3/ |
| Ryegrass, Perennial, Annual | - | 97 | 85 | 0.30 | 5 (175) | 3/ |
| Rye, Grain, Winter | - | 92 | 83 | 0.50 | 2 (70) | 3/ |
| Hard Fescue, Reliant IV | - | 98 | 83 | 0.05 | 1 (35) | - |
| Hard Fescue, Rescue 911 | 0 | 97 | 82 | 0.10 | 3 (105) | - |
| Hard Fescue, Spartan II | | 98 | 83 | 0.10 | 3 (105) | - |
| Timothy | - | 92 | 84 | 0.50 | 5 (175) | 3/ |
| Wheat, hard Red Winter | - | .92 | 89 | 0.50 | 2 (70) | 3/" |

Revise the first sentence of the first paragraph of Article 1081.04(c)(7) of the Standard Specifications to read:

"The seed quantities indicated per acre (hectare) for Prairie Grass Seed in Classes 3, 3A, 4, 4A, 6, and 6A in Article 250.07 shall be the amounts of pure, live seed per acre (hectare) for each species listed."

SELF-CONSOLIDATING CONCRETE FOR PRECAST PRODUCTS (BDE)

Effective: July 1, 2004 Revised: July 1, 2010

<u>Definition</u>. Self-consolidating concrete is a flowable mixture that does not require mechanical vibration for consolidation.

<u>Usage</u>. Self-consolidating concrete may be used for precast concrete products.

Materials. Materials shall be according to Section 1021 of the Standard Specifications.

Mix Design Criteria. The mix design criteria shall be as follows:

- (a) The minimum cement factor shall be according to Article 1020.04 of the Standard Specifications. If the maximum cement factor is not specified, it shall not exceed 7.05 cwt/cu yd (418 kg/cu m).
- (b) The maximum allowable water/cement ratio shall be according to Article 1020.04 of the Standard Specifications or 0.44, whichever is lower.
- (c) The slump requirements of Article 1020.04 of the Standard Specifications shall not apply.
- (d) The coarse aggregate gradations shall be CA 13, CA 14, CA 16, or a blend of these gradations. CA 11 may be used when the Contractor provides satisfactory evidence to the Engineer that the mix will not segregate. The fine aggregate proportion shall be a maximum 50 percent by weight (mass) of the total aggregate used.
- (e) The slump flow range shall be ± 2 in. (± 50 mm) of the Contractor target value, and within the overall Department range of 20 in. (510 mm) minimum to 28 in. (710 mm) maximum.
- (f) The visual stability index shall be a maximum of 1.
- (g) The J-ring value shall be a maximum of 4 in. (100 mm). The Contractor may specify a lower maximum in the mix design.
- (h) The L-box blocking ratio shall be a minimum of 60 percent. The Contractor may specify a higher minimum in the mix design.
- (i) The hardened visual stability index shall be a maximum of 1.

Mixing Portland Cement Concrete. In addition to Article 1020.11 of the Standard Specifications, the mixing time for central-mixed concrete shall not be reduced as a result of a mixer

performance test. Truck-mixed or shrink-mixed concrete shall be mixed in a truck mixer for a minimum of 100 revolutions.

Wash water, if used, shall be completely discharged from the drum or container before the succeeding batch is introduced.

The batch sequence, mixing speed, and mixing time shall be appropriate to prevent cement balls and mix foaming for central-mixed, truck-mixed, and shrink-mixed concrete.

<u>Placing and Consolidating</u>. The maximum distance of horizontal flow from the point of deposit shall be 25 ft (7.6 m), unless approved otherwise by the Engineer.

Concrete shall be rodded with a piece of lumber, conduit, or vibrator if the material has lost its fluidity prior to placement of additional concrete. The vibrator shall be the pencil head type with a maximum diameter or width of 1 in. (25 mm). Any other method for restoring the fluidity of the concrete shall be approved by the Engineer.

<u>Mix Design Approval</u>. The Contractor shall obtain mix design approval according to the Department's Policy Memorandum "Quality Control/Quality Assurance Program for Precast Concrete Products".

SUBCONTRACTOR MOBILIZATION PAYMENTS (BDE)

Effective: April 2, 2005 Revised: April 1, 2011

To account for the preparatory work and operations necessary for the movement of subcontractor personnel, equipment, supplies, and incidentals to the project site and for all other work or operations that must be performed or costs incurred when beginning work approved for subcontracting according to Article 108.01 of the Standard Specifications, the Contractor shall make a mobilization payment to each subcontractor.

This mobilization payment shall be made at least 14 days prior to the subcontractor starting work. The amount paid shall be equal to 3 percent of the amount of the subcontract reported on form BC 260A submitted for the approval of the subcontractor's work.

The mobilization payment to the subcontractor is an advance payment of the reported amount of the subcontract and is not a payment in addition to the amount of the subcontract; therefore, the amount of the advance payment will be deducted from future progress payments.

This provision shall be incorporated directly or by reference into each subcontract approved by the Department.

TEMPORARY EROSION CONTROL (BDE)

Effective: November 1, 2002 Revised: January 1, 2011

Add the following to Article 280.02 of the Standard Specifications to read:

| "(k) | Filter Fabric | 1080.03 |
|------|--------------------------|-----------------|
| (l) | Urethane Foam/Geotextile | 1081.15(i)" |

Revise the third paragraph of Article 280.03 of the Standard Specifications to read:

"Erosion control systems shall be installed prior to beginning any activities which will potentially create erodible conditions. Erosion control systems for areas outside the limits of construction such as storage sites, plant sites, waste sites, haul roads, and Contractor furnished borrow sites shall be installed prior to beginning soil disturbing activities at each area. These offsite systems shall be designed by the Contractor and be subject to the approval of the Engineer."

Add the following paragraph after the third paragraph of Article 280.03 of the Standard Specifications:

"The temporary erosion and sediment control systems shown on the plans represent the minimum systems anticipated for the project. Conditions created by the Contractor's operations, or for the Contractor's convenience, which are not covered by the plans, shall be protected as directed by the Engineer at no additional cost to the Department. Revisions or modifications of the erosion and sediment control systems shall have the Engineer's written approval."

Revise Article 280,04(a) of the Standard Specifications to read:

"(a) Temporary Ditch Checks. This system consists of the construction of temporary ditch checks to prevent siltation, erosion, or scour of ditches and drainage ways. Temporary ditch checks shall be constructed with products from the Department's approved list, rolled excelsior, or with aggregate placed on filter fabric when specified. Filter fabric shall be installed according to the requirements of Section 282. Riprap shall be placed according to Article 281.04. Manufactured ditch checks shall be installed according to the manufacturer's specifications. Spacing of ditch checks shall be such that the low point in the center of one ditch check is at the same elevation as the base of the ditch check immediately upstream. Temporary ditch checks shall be sufficiently long enough that the top of the device in the middle of the ditch is 6 in. (150 mm) lower than the bottom of the terminating ends of the ditch side slopes.

When rolled excelsior is used, each ditch check shall be installed and maintained such that the device is no less than 10 in. (250 mm) high at the point of overflow. Units

installed at a spacing requiring a height greater than 10 in. (250 mm) shall be maintained at the height for the spacing at which they were originally installed."

Revise the last sentence of the first paragraph Article 280.04(b) of the Standard Specifications to read:

"The barrier shall be constructed with rolled excelsior, silt filter fence, or urethane foam/geotextiles."

Revise the last sentence of the first paragraph of Article 280.04(g) of the Standard Specifications to read:

"The temporary mulch cover shall be installed according to Article 251.03 except for any reference to seeding."

Add the following to Article 280.04 of the Standard Specifications:

(h) Temporary Erosion Control Blanket. This system consists of temporarily installing erosion control blanket or heavy duty erosion control blanket over areas that are to be reworked during a later construction phase. Work shall be according to Article 251.04 except references to seeding and fertilizer shall not apply. When an area is to be reworked more than once, the blanket shall be carefully removed, properly stored, and then reinstalled over the same area."

Revise Article 280.07(b) of the Standard Specifications to read:

"(b) Temporary Ditch Checks. This work will be measured for payment along the long axis of the device in place in feet (meters) except for aggregate ditch checks which will be measured for payment in tons (metric tons). Payment will not be made for aggregate in excess of 108 percent of the amount specified by the Engineer."

Revise Article 280.07(f) of the Standard Specifications to read:

"(f) Temporary Mulch. This work will be measured for payment according to Article 251.05(b)."

Add the following to Article 280.07 of the Standard Specifications:

"(g) Temporary Erosion Control Blanket. This work will be measured for payment in place in square yards (square meters) of actual surface covered.

Add the following paragraph after the ninth paragraph of Article 280.07 of the Standard Specifications:

"Temporary or permanent erosion control systems required for areas outside the limits of construction will not be measured for payment."

Revise Article 280.08(b) of the Standard Specifications to read:

"(b) Temporary Ditch Checks. This work will be paid for at the contract unit price per foot (meter) for TEMPORARY DITCH CHECKS except for aggregate ditch checks which will be paid for at the contract unit price per ton (metric ton) for AGGREGATE DITCH CHECKS."

Revise Article 280.08(f) of the Standard Specifications to read:

"(f) Temporary Mulch. Temporary Mulch will be paid for according to Article 251.06."

Add the following to Article 280.08 of the Standard Specifications:

"(g) Temporary Erosion Control Blanket. Temporary Erosion Control Blanket will be paid for at the contract unit price per square yard (square meter) for TEMPORARY EROSION CONTROL BLANKET or TEMPORARY HEAVY DUTY EROSION CONTROL BLANKET.

The work of removing, storing, and reinstalling the blanket over areas to be reworked more than once will not be paid for separately but shall be included in the cost of the temporary erosion control blanket or temporary heavy duty erosion control blanket."

Delete the tenth (last) paragraph of Article 280.08 of the Standard Specifications.

Revise the second sentence of the first paragraph of Article 1081.15(e) of the Standard Specifications to read:

"The upstream facing of the aggregate ditch check shall be constructed of gradation CA 3. The remainder of the ditch check shall be constructed of gradation RR 3."

Revise Article 1081.15(f) of the Supplemental Specifications to read:

"(f) Rolled Excelsior. Rolled excelsior shall consist of an excelsior fiber filling totally encased inside netting and sealed with metal clips or knotted at the ends. The fiber density shall be a minimum of 1.24 lb/cu ft (20 kg/cu m) based on a moisture content of 22 percent at manufacturing. The netting shall be composed of a polyester or polypropylene material which retains 70 percent of its strength after 500 hours of exposure to sunlight. The maximum opening of the net shall be 1 x 1 in. (25 x 25 mm)."

Add the following to Article 1081.15 of the Standard Specifications:

"(i) Urethane Foam/Geotextile. Urethane foam/geotextile shall be triangular shaped having a minimum height of 10 in. (250 mm) in the center with equal sides and a minimum 20 in. (500 mm) base. The triangular shaped inner material shall be a low density urethane foam. The outer cover shall be a woven geotextile fabric placed around the

inner material and allowed to extend beyond both sides of the triangle a minimum of 18 in. (450 mm).

(1) The geotextile shall meet the following properties:

| Property | Value | Test Method |
|-------------------------------------|-----------------|-------------|
| Grab Tensile Strength Ib (N) (min.) | 124 (550) min. | ASTM D 4632 |
| Grab Elongation @ Brake (percent) | 15 min. | ASTM D 4632 |
| Burst Strength psi (kPa) | 280 (1930) min. | ASTM D 3786 |
| AOS (Sieve No.) | 30 min. | ASTM D 4751 |
| UV Resistance (500 hours) (percent) | 80 min. | ASTM D 4355 |

(2) The urethane foam shall meet the following properties:

| Property | Value | Test Method |
|----------------------------|------------------------|--------------|
| Density lb/cu ft (kg/cu m) | 1.0 ± 0.1 (16.0 ± 1.6) | ASTM D 3574 |
| Tensile Strength psi (kPa) | 10 (70) min. | ASTM D 3574 |
| Elongation (percent) | 125 min. | ASTM D 3574 |
| Tear Resistance Ib/in. | 1.25 (0.22) | ASTM D 3574" |
| (N/mm) | · · · · | |

TRAFFIC CONTROL DEFICIENCY DEDUCTION (BDE)

Effective: August 1, 2011

Revise the third sentence of the third paragraph of Article 105.03(b) of the Standard Specifications to read:

"The daily monetary deduction will be \$2,500."

TRUCK MOUNTED/TRAILER MOUNTED ATTENUATORS (BDE)

Effective: January 1, 2010

Revise Article 701.03(k) of the Standard Specifications to read:

Revise Article 701.15(h) of the Standard Specifications to read:

"(h) Truck Mounted/Trailer Mounted Attenuators (TMA). TMA units shall have a roll ahead distance in the event of an impact. The TMA shall be between 100 and 200 ft (30 and 60 m) behind the vehicle ahead or the workers. This distance may be extended by the Engineer.

TMA host vehicles shall have the parking brake engaged when stationary.

The driver and passengers of the TMA host vehicle should exit the vehicle if the TMA is to remain stationary for 15 minutes or more in duration."

Revise Article 1106.02(g) of the Standard Specifications to read:

"(g) Truck Mounted/Trailer Mounted Attenuators. The attenuator shall be a NCHRP 350 approved unit for Test Level 3. Test Level 2 may be used as directed by the Engineer for normal posted speeds less than or equal to 45 mph."

REQUIRED CONTRACT PROVISIONS FEDERAL-AID CONSTRUCTION CONTRACTS

| | | Page |
|-------|---|------|
| I. | General | 1 |
| II. | Nondiscrimination | 1 |
| III. | Nonsegregated Facilities | 3 |
| IV. | Payment of Predetermined Minimum Wage | 3 |
| ٧. | Statements and Payrolls | 5 |
| VI. | Record of Materials, Supplies, and Labor | 6 |
| VII. | Subletting or Assigning the Contract | 6 |
| VIII. | Safety: Accident Prevention | 7 |
| IX. | False Statements Concerning Highway Projects | 7 |
| X. | Implementation of Clean Air Act and Federal | |
| | . Water Pollution Control Act | 7 |
| XI. | Certification Regarding Debarment, Suspension, | |
| | Ineligibility, and Voluntary Exclusion | 8 |
| XII. | Certification Regarding Use of Contract Funds for | |
| | Lobbying | 9 |

ATTACHMENTS

A. Employment Preference for Appalachian Contracts (included in Appalachian contracts only)

I. GENERAL

- 1. These contract provisions shall apply to all word performed on the contract by the contractor's own organization and with the assistance of workers under the contractor's immediate superintendence and to all work performed on the contract by piecework, station work, or by subcontract.
- 2. Except as otherwise provided for in each section, the contractor shall insert in each subcontract all of the stipulations contained in these Required Contract Provisions, and further require their inclusion in any lower tier subcontract or purchase order that may in turn be made. The Required Contract Provisions shall not be incorporated by reference in any case. The prime contractor shall be responsible for compliance by any subcontractor or lower tier subcontractor with these Required Contract Provisions.
- 3. A breach of any of the stipulations contained in these Required Contract Provisions shall be sufficient grounds for termination of the contract.
- **4.** A breach of the following clauses of the Required Contract Provisions may also be grounds for debarment as provided in 29 CFR 5.12:

Section I, paragraph 2; Section IV, paragraphs 1, 2, 3, 4 and 7; Section V, paragraphs 1 and 2a through 2g.

- **5.** Disputes arising out of the labor standards provisions of Section IV (except paragraph 5) and Section V of these Required Contract Provisions shall not be subject to the general disputes clause of this contract. Such disputes shall be resolved in accordance with the procedures of the U.S. Department of Labor (DOL) as set forth in 29 CFR 5, 6 and 7. Disputes within the meaning of this clause include disputes between the contractor (or any of its subcontractors) and the contracting agency, the DOL, or the contractor's employees or their representatives.
- **6.** Selection of Labor: During the performance of this contract, the contractor shall not:
- a. Discriminate against labor from any other State, possession, or

territory of the United States (except for employment preference for

Appalachian contracts, when applicable, as specified in Attachment

A), or

b. Employ convict labor for any purpose within the limits of the project unless it is labor performed by convicts who are on parole.

supervised release, or probation.

II. NONDISCRIMINATION

(Applicable to all Federal-aid construction contracts and to all related subcontracts of \$10,000 or more.)

- 1. Equal Employment Opportunity: Equal employment opportunity (EEO) requirements not to discriminate and to take affirmative action to assure equal opportunity as set forth under laws, executive orders, rules, regulations (28 CFR 35, 29 CFR 1630 and 41 CFR 60 (and orders of the Secretary of Labor as modified by the provisions prescribed herein, and imposed pursuant to 23 U.S.C. 140 shall constitute the EEO and specific affirmative action standards for the contractor's project activities under this contract. The Equal Opportunity Construction Contract Specifications set forth under 41 CFR 60-4.3 and the provisions of the American Disabilities Act of 1990 (42 U.S.C. 12101 et seq.) set forth under 28 CFR 35 and 29 CFR 1630 are incorporated by reference in this contract. In the execution of this contract, the contractor agrees to comply with the following minimum specific requirement activities of EEO:
- ${\bf a.}\,$ The contractor will work with the State highway agency (SHA) and

the Federal Government in carrying out EEO obligations and in their

review of his/her activities under the contract.

 $\mbox{\bf b.}$ The contractor will accept as his operating policy the following

statement: "It is the policy of this Company to assure that applicants

are employed, and that employees are treated during employment,

without regard to their race, religion, sex, color, national origin, age or

disability. Such action shall include: employment, upgrading, demotion, or transfer; recruitment or recruitment advertising; layoff or

termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship, preapprenticeship.

and/or on-the-job-training."

- **2. EEO Officer:** The contractor will designate and make known to the SHA contracting officers an EEO Officer who will have the responsibility for an must be capable of effectively administering and promoting an active contractor program of EEO and who must be assigned adequate authority and responsibility to do so.
- 3. Dissemination of Policy: All members of the contractor's staff who are authorized to hire, supervise, promote, and discharge employees, or who recommend such action, or who are substantially involved in such action, will be made fully cognizant of, and will implement, the contractor's EEO policy and contractual responsibilities to provide EEO in each grade and classification of employment. To ensure that the above agreement will be met, the following actions will be taken as a minimum:
 - a. Periodic meetings of supervisory and personnel office employees will be conducted before the start of work and then not less often than once every six months, at which time the contractor's EEO policy and its implementation will be reviewed and explained. The meetings will be conducted by the EEO Officer.
 - **b.** All new supervisory or personnel office employees will be given a thorough indoctrination by the EEO Officer, covering all major aspects of the contractor's EEO obligations within thirty days following their reporting for duty with the contractor.
 - **c.** All personnel who are engaged in direct recruitment for the project will be instructed by the EEO Officer in the contractor's procedures for locating and hiring minority group employees.
 - d. Notices and posters setting forth the contractor's EEO policy will be placed in areas readily accessible to employees,

- applicants for employment and potential employees.
- **e.** The contractor's EEO policy and the procedures to implement such policy will be brought to the attention of employees by means of meetings, employee handbooks, or other appropriate means.
- **4. Recruitment:** When advertising for employees, the contractor will include in all advertisements for employees the notation: "An Equal Opportunity Employer." All such advertisements will be placed in publications having a large circulation among minority groups in the area from which the project work force would normally be derived.
 - **a.** The contractor will, unless precluded by a valid bargaining agreement, conduct systematic and direct recruitment through public and private employees referral sources likely to yield qualified minority group applicants. To meet this requirement, the contractor will identify sources of potential minority group employees, and establish which such identified sources procedures whereby minority group applicants may be referred to the contractor for employment consideration.
 - b. In the event the contractor has a valid bargaining agreement providing for exclusive hiring hall referrals, he is expected to observe the provisions of that agreement to the extent that the system permits the contractor's compliance with EEO contract provisions. (The DOL has held that where implementation of such agreements have the effect of discriminating against minorities or women, or obligates the contractor to do the same, such implementation violates Executive Order 11246, as amended.)
 - **c.** The contractor will encourage his present employees to refer minority group applicants for employment. Information and procedures with regard to referring minority group applicants will be discussed with employees.
- **5. Personnel Actions:** Wages, working conditions, and employee benefits shall be established and administered, and personnel actions of every type, including hiring, upgrading, promotion, transfer, demotion, layoff, and termination, shall be taken without regard to race, color, religion, sex, national origin, age or disability. The following procedures shall be followed:
 - a. The contractor will conduct periodic inspections of project sites to insure that working conditions and employee facilities do not indicate discriminatory treatment of project site personnel.
 - **b.** The contractor will periodically evaluate the spread of wages paid within each classification to determine any evidence of discriminatory wage practices.
 - c. The contractor will periodically review selected personnel actions in depth to determine whether there is evidence of discrimination. Where evidence is found, the contractor will promptly take corrective action. If the review indicates that the discrimination may extend beyond the actions reviewed, such corrective action shall include all affected persons.
 - d. The contractor will promptly investigate all complaints of alleged discrimination made to the contractor in connection with his obligations under this contract, will attempt to resolve such complaints, and will take appropriate corrective action within a reasonable time. If the investigation indicates that the discrimination may affect persons other than the complainant, such corrective action shall include such other persons. Upon completion of each investigation, the contractor will inform every complainant of all of his avenues of appeal.

6. Training and Promotion:

- **a.** The contractor will assist in locating, qualifying, and increasing the skills of minority group and women employees, and applicants for employment.
- b. Consistent with the contractor's work force requirements and as permissible under Federal and State regulations, the contractor shall make full use of training programs, i.e., apprenticeship, and on-the-job training programs for the geographical area of contract performance. Where feasible, 25 percent of apprentices or trainees in each occupation shall be

- in their first year of apprenticeship or training. In the event a special provision for training is provided under this contract, this subparagraph will be superseded as indicated in the special provision.
- **c.** The contractor will advise employees and applicants for employment of available training programs and entrance requirements for each.
- **d.** The contractor will periodically review the training and promotion potential of minority group and women employees and will encourage eligible employees to apply for such training and promotion.
- 7. Unions: If the contractor relies in whole or in part upon unions as a source of employees, the contractor will use his/her best efforts to obtain the cooperation of such unions to increase opportunities for minority groups and women within the unions, and to effect referrals by such unions of minority and female employees. Actions by the contractor either directly or through a contractor's association acting as agent will include the procedures set forth below:
 - a. The contractor will use best efforts to develop, in cooperation with the unions, joint training programs aimed toward qualifying more minority group members and women for membership in the unions and increasing the skills of minority group employees and women so that they may qualify for higher paying employment.
 - **b.** The contractor will use best efforts to incorporate an EEO clause into each union agreement to the end that such union will be contractually bound to refer applicants without regard to their race, color, religion, sex, national origin, age or disability.
 - **c.** The contractor is to obtain information as to the referral practices and policies of the labor union except that to the extent such information is within the exclusive possession of the labor union and such labor union refuses to furnish such information to the contractor, the contractor shall so certify to the SHA and shall set forth what efforts have been made to obtain such information.
 - **d.** In the event the union is unable to provide the contractor with a reasonable flow of minority and women referrals within the time limit set forth in the collective bargaining agreement, the contractor will, through independent recruitment efforts, fill the employment vacancies without regard to race, color, religion, sex, national origin, age or disability; making full efforts to obtain qualified and/or qualifiable minority group persons and women. (The DOL has held that it shall be no excuse that the union with which the contractor has a collective bargaining agreement providing for exclusive referral failed to refer minority employees.) In the event the union referral practice prevents the contractor from meeting the obligations pursuant to Executive Order 11246, as amended, and these special provisions, such contractor shall immediately notify the SHA.
- 8. Selection of Subcontractors, Procurement of Materials and Leasing of Equipment: The contractor shall not discriminate on the grounds of race, color, religion, sex, national origin, age or disability in the selection and retention of subcontractors, including procurement of materials and leases of equipment.
 - **a.** The contractor shall notify all potential subcontractors and suppliers of his/her EEO obligations under this contract.
- b. Disadvantaged business enterprises (DBE), as defined in 49 CFR 23, shall have equal opportunity to compete for and perform subcontracts which the contractor enters into pursuant to this contract. The contractor will use his best efforts to solicit bids from

and to utilize DBE subcontractors or subcontractors with meaningful $% \left(1\right) =\left(1\right) \left(1\right)$

minority group and female representation among their employees.

Contractors shall obtain lists of DBE construction firms from SHA

personnel.

- **c.** The contractor will use his best efforts to ensure subcontractor compliance with their EEO obligations.
- **9. Records and Reports:** The contractor shall keep such records as necessary to document compliance with the EEO requirements. Such records shall be retained for a period of three years following completion of the contract work and shall be available at reasonable times and places for inspection by authorized representatives of the SHA and the FHWA.
- **a.** The records kept by the contractor shall document the following:
- (1) The number of minority and non-minority group members and women employed in each work classification on the project;
 - **(2)** The progress and efforts being made in cooperation with unions, when applicable, to increase employment opportunities for minorities and women:
- (3) The progress and efforts being made in locating, hiring, training,
 - ning,
 qualifying, and upgrading minority and female employees; and
- (4) The progress and efforts being made in securing the services of

DBE subcontractors or subcontractors with meaningful minority and

female representation among their employees.

b. The contractors will submit an annual report to the SHA each July for the duration of the project, indicating the number of minority, women, and non-minority group employees currently engaged in each work classification required by the contract work. This information is to be reported on Form FHWA-1391. If on-the-job training is being required by special provision, the contractor will be required to collect and report training data.

III. NONSEGREGATED FACILITIES

(Applicable to all Federal-aid construction contracts and to all related subcontracts of \$10,000 or more.)

- a. By submission of this bid, the execution of this contract or subcontract, or the consummation of this material supply agreement or purchase order, as appropriate, the bidder, Federal-aid construction contractor, subcontractor, material supplier, or vendor, as appropriate, certifies that the firm does not maintain or provide for its employees any segregated facilities at any of its establishments, and that the firm does not permit its employees to perform their services at any location, under its control, where segregated facilities are maintained. The firm agrees that a breach of this certification is a violation of the EEO provisions of this contract. The firm further certifies that no employee will be denied access to adequate facilities on the basis of sex or disability.
- **b.** As used in this certification, the term "segregated facilities" means any waiting rooms, work areas, restrooms and washrooms, restaurants and other eating areas, timeclocks, locker rooms, and other storage or dressing areas, parking lots, drinking fountains, recreation or entertainment areas, transportation, and housing facilities provided for employees which are segregated by explicit directive, or are, in fact, segregated on the basis of race, color, religion, national origin, age or disability, because of habit, local custom, or otherwise. The only exception will be for the disabled when the demands for accessibility override (e.g. disabled parking).
- **c.** The contractor agrees that it has obtained or will obtain identical certification from proposed subcontractors or material suppliers prior to award of subcontracts or consummation of material supply agreements of \$10,000 or more and that it will retain such certifications in its files.

IV. PAYMENT OF PREDETERMINED MINIMUM WAGE

(Applicable to all Federal-aid construction contracts exceeding \$2,000 and to all related subcontracts, except for projects located

on roadways classified as local roads or rural minor collectors, which are exempt.)

1. General:

- a. All mechanics and laborers employed or working upon the site of the work will be paid unconditionally and not less often than once a week and without subsequent deduction or rebate on any account [except such payroll deductions as are permitted by regulations (29 CFR 3) issued by the Secretary of Labor under the Copeland Act (40 U.S.C. 276c)] the full amounts of wages and bona fide fringe benefits (or cash equivalents thereof) due at time of payment. The payment shall be computed at wage rates not less than those contained in the wage determination of the Secretary of Labor (hereinafter "the wage determination") which is attached hereto and made a part hereof, regardless of any contractual relationship which may be alleged to exist between the contractor or its subcontractors and such laborers and mechanics. The wage determination (including any additional classifications and wage rates conformed under paragraph 2 of this Section IV and the DOL poster (WH-1321) or Form FHWA-1495) shall be posted at all times by the contractor and its subcontractors at the site of the work in a prominent and accessible place where it can be easily seen by the workers. For the purpose of this Section, contributions made or costs reasonably anticipated for bona fide fringe benefits under Section 1(b)(2) of the Davis-Bacon Act (40 U.S.C. 276a) on behalf of laborers or mechanics are considered wages paid to such laborers or mechanics, subject to the provisions of Section IV, paragraph 3b, hereof. Also, for the purpose of this Section, regular contributions made or costs incurred for more than a weekly period (but not less often than quarterly) under plans, funds, or programs, which cover the particular weekly period, are deemed to be constructively made or incurred during such weekly period. Such laborers and mechanics shall be paid the appropriate wage rate and fringe benefits on the wage determination for the classification of work actually performed, without regard to skill, except as provided in paragraphs 4 and 5 of this Section IV.
- **b.** Laborers or mechanics performing work in more than one classification may be compensated at the rate specified for each classification for the time actually worked therein, provided, that the employer's payroll records accurately set forth the time spent in each classification in which work is performed.
- **c.** All rulings and interpretations of the Davis-Bacon Act and related acts contained in 29 CFR 1, 3, and 5 are herein incorporated by reference in this contract.

2. Classification:

- **a.** The SHA contracting officer shall require that any class of laborers or mechanics employed under the contract, which is not listed in the wage determination, shall be classified in conformance with the wage determination.
- **b.** The contracting officer shall approve an additional classification, wage rate and fringe benefits only when the following criteria have been met:
 - (1) the work to be performed by the additional classification requested is not performed by a classification in the wage determination;
- (2) the additional classification is utilized in the area by the construction industry;
- (3) the proposed wage rate, including any bona fide fringe benefits, bears a reasonable relationship to the wage rates contained in the wage determination; and
- **(4)** with respect to helpers, when such a classification prevails in the area in which the work is performed.
- **c.** If the contractor or subcontractors, as appropriate, the laborers and mechanics (if known) to be employed in the additional classification or their representatives, and the

contracting officer agree on the classification and wage rate (including the amount designated for fringe benefits where appropriate), a report of the action taken shall be sent by the contracting officer to the DOL, Administrator of the Wage and Hour Division, Employment Standards Administration, Washington, D.C. 20210. The Wage and Hour Administrator, or an authorized representative, will approve, modify, or disapprove every additional classification action within 30 days of receipt and so advise the contracting officer or will notify the contracting officer within the 30-day period that additional time is necessary.

- d. In the event the contractor or subcontractors, as appropriate, the laborers or mechanics to be employed in the additional classification or their representatives, and the contracting officer do not agree on the proposed classification and wage rate (including the amount designated for fringe benefits, where appropriate), the contracting officer shall refer the question, including the views of all interested parties and the recommendation of the contracting officer, to the Wage and Hour Administrator for determination. Said Administrator, or an authorized representative, will issue a determination within 30 days of receipt and so advised the contracting officer or will notify the contracting officer within the 30-day period that additional time is necessary.
- **e.** The wage rate (including fringe benefits where appropriate) determined pursuant to paragraph 2c or 2d of this Section IV shall be paid to all workers performing work in the additional classification from the first day on which work is performed in the classification.

3. Payment of Fringe Benefits:

 $\mbox{\bf a.}$ Whenever the minimum wage rate prescribed in the contract for a

class of laborers or mechanics includes a fringe benefit which is not

- expressed as an hourly rate, the contractor or subcontractors, as appropriate, shall either pay the benefit as stated in the wage determination or shall pay another bona fide fringe benefit or an hourly case equivalent thereof.
- b. If the contractor or subcontractor, as appropriate, does not make payments to a trustee or other third person, he/she may consider as a part of the wages of any laborer or mechanic the amount of any cost reasonably anticipated in providing bona fide fringe benefits under a plan or program, provided that the Secretary of Labor has found, upon the written request of the contractor, that the applicable standards of the Davis-Bacon Act have been met. The Secretary of Labor may require the contractor to set aside in a separate account assets for the meeting of obligations under the plan or program.

Apprentices and Trainees (Programs of the U.S. DOL) and Helpers:

a. Apprentices:

- (1) Apprentices will be permitted to work at less than the predetermined rate for the work they performed when they are employed pursuant to and individually registered in a bona fide apprenticeship program registered with the DOL, Employment and Training Administration, Bureau of Apprenticeship and Training, or with a State apprenticeship agency recognized by the Bureau, or if a person is employed in his/her first 90 days of probationary employment as an apprentice in such an apprenticeship program, who is not individually registered in the program, but who has been certified by the Bureau of Apprenticeship and Training or a State apprenticeship agency (where appropriate) to be eligible for probationary employment as an apprentice.
- (2) The allowable ratio of apprentices to journeyman-level employees on the job site in any craft classification shall not be greater than the ratio permitted to the contractor as to the entire work force under the registered program. Any

employee listed on a payroll at an apprentice wage rate, who is not registered or otherwise employed as stated above, shall be paid not less than the applicable wage rate listed in the wage determination for the classification of work actually performed. In addition, any apprentice performing work on the job site in excess of the ratio permitted under the registered program shall be paid not less than the applicable wage rate on the wage determination for the work actually performed. Where a contractor or subcontractor is performing construction on a project in a locality other than that in which its program is registered, the ratios and wage rates (expressed in percentages of the journeyman-level hourly rate) specified in the contractor's or subcontractor's registered program shall be observed.

(3) Every apprentice must be paid at not less than the rate specified in the registered program for the apprentice's level of progress, expressed as a percentage of the journeyman-level hourly rate specified in the applicable wage determination. Apprentices shall be paid fringe benefits in accordance with the provisions of the apprenticeship program. If the apprenticeship program does not specify fringe benefits, apprentices must be

the full amount of fringe benefits listed on the wage determination

for the applicable classification. If the Administrator for the Wage

and Hour Division determines that a different practice prevails for

the applicable apprentice classification, fringes shall be paid in accordance with that determination.

- (4) In the event the Bureau of Apprenticeship and Training, or a State apprenticeship agency recognized by the Bureau, withdraws approval of an apprenticeship program, the contractor or subcontractor will no longer be permitted to utilize apprentices at less than the applicable predetermined rate for the comparable work performed by regular employees until an acceptable program is approved.
- **b**. Trainees:

paid

- (1) Except as provided in 29 CFR 5.16, trainees will not be permitted to work at less than the predetermined rate for the work performed unless they are employed pursuant to and individually registered in a program which has received prior approval, evidenced by formal certification by the DOL, Employment and Training Administration.
- (2) The ratio of trainees to journeyman-level employees on the job site shall not be greater than permitted under the plan approved by the Employment and Training Administration. Any employee listed on the payroll at a trainee rate who is not registered and participating in a training plan approved by the Employment and Training Administration shall be paid not less than the applicable wage rate on the wage determination for the classification of work actually performed. In addition, any trainee performing work on the job site in excess of the ratio permitted under the registered program shall be paid not less than the applicable wage rate on the wage determination for the work actually performed.
- (3) Every trainee must be paid at not less than the rate specified in the approved program for his/her level of progress, expressed as a percentage of the journeyman-level hourly rate specified in the applicable wage determination. Trainees shall be paid fringe benefits in accordance with the provisions of the trainee program. If the trainee program does not mention fringe benefits, trainees shall be paid the full amount of fringe benefits listed on the wage determination unless the Administrator of the Wage and Hour Division determines that there is an apprenticeship program associated with the corresponding journeyman-level wage rate on the wage determination which provides for less than full fringe benefits for apprentices, in which cases such trainees shall receive the same fringe benefits as apprentices.
 - (4) In the event the Employment and Training Administration

withdraws approval of a training program, the contractor or subcontractor will no longer be permitted to utilize trainees at less than the applicable predetermined rate for the work performed until an acceptable program is approved.

c. Helpers:

Helpers will be permitted to work on a project if the helper classification is specified and defined on the applicable wage determination or is approved pursuant to the conformance procedure set forth in Section IV. 2. Any worker listed on a payroll at a helper wage rate, who is not a helper under a approved definition, shall be paid not less than the applicable wage rate on the wage determination for the classification of work actually performed.

5. Apprentices and Trainees (Programs of the U.S. DOT):

Apprentices and trainees working under apprenticeship and skill training programs which have been certified by the Secretary of Transportation as promoting EEO in connection with Federal-aid highway construction programs are not subject to the requirements of paragraph 4 of this Section IV. The straight time hourly wage rates for apprentices and trainees under such programs will be established by the particular programs. The ratio of apprentices and trainees to journeymen shall not be greater than permitted by the terms of the particular program.

6. Withholding:

The SHA shall upon its own action or upon written request of an authorized representative of the DOL withhold, or cause to be withheld, from the contractor or subcontractor under this contract or any other Federal contract with the same prime contractor or any other Federally-assisted contract subject to Davis-Bacon prevailing wage requirements which is held by the same prime contractor, as much of the accrued payments or advances as may be considered necessary to pay laborers and mechanics, including apprentices, trainee's and helpers, employed by the contractor or any subcontractor the full amount of wages required by the contract. In the event of failure to pay any laborer or mechanic, including any apprentice, trainee, or helper, employed or working on the site of the work, all or part of the wages required by the contract, the SHA contracting officer may, after written notice to the contractor, take such action as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds until such violations have ceased.

7. Overtime Requirements:

No contractor or subcontractor contracting for any part of the contract work which may require or involve the employment of laborers, mechanics, watchmen, or guards (including apprentices, trainees, and helpers described in paragraphs 4 and 5 above) shall require or permit any laborer, mechanic, watchman, or guard in any workweek in which he/she is employed on such work, to work in excess of 40 hours in such workweek unless such laborer, mechanic, watchman, or guard receives compensation at a rate not less than one-and-one-half times his/her basic rate of pay for all hours worked in excess of 40 hours in such workweek.

8. Violation:

Liability for Unpaid Wages; Liquidated Damages: In the event of any violation of the clause set forth in paragraph 7 above, the contractor and any subcontractor responsible thereof shall be liable to the affected employee for his/her unpaid wages. In addition, such contractor and subcontractor shall be liable to the United States (in the case of work done under contract for the District of Columbia or a territory, to such District or to such territory) for liquidated damages. Such liquidated damages shall be computed with respect to each individual laborer, mechanic, watchman, or guard employed in violation of the clause set forth in paragraph 7, in the sum of \$10 for each calendar day on which such employee was required or

permitted to work in excess of the standard work week of 40 hours without payment of the overtime wages required by the clause set forth in paragraph 7.

9. Withholding for Unpaid Wages and Liquidated Damages:

The SHA shall; upon its own action or upon written request of any authorized representative of the DOL withhold, or cause to be withheld, from any monies payable on account of work performed by the contractor or subcontractor under any such contract or any other Federal contract with the same prime contractor, or any other Federally-assisted contract subject to the Contract Work Hours and Safety Standards Act, which is held by the same prime contractor, such sums as may be determined to be necessary to satisfy any liabilities of such contractor or subcontractor for unpaid wages and liquidated damages as provided in the clause set forth in paragraph 8 above.

V. STATEMENTS AND PAYROLLS

(Applicable to all Federal-aid construction contracts exceeding \$2,000 and to all related subcontracts, except for projects located on roadways classified as local roads or rural collectors, which are exempt.)

1. Compliance with Copeland Regulations (29 CFR 3):

The contractor shall comply with the Copeland Regulations of the Secretary of Labor which are herein incorporated by reference.

2. Payrolls and Payroll Records:

- a. Payrolls and basic records relating thereto shall be maintained by the contractor and each subcontractor during the course of the work and preserved for a period of 3 years from the date of completion of the contract for all laborers, mechanics, apprentices, trainees, watchmen, helpers, and guards working at the site of the work.
- b. The payroll records shall contain the name, social security number, and address of each such employee: his or her correct classification; hourly rates of wages paid (including rates of contributions or costs anticipated for bona fide fringe benefits or cash equivalent thereof the types described in Section 1(b)(2)(B) of the Davis Bacon Act); daily and weekly number of hours worked; deductions made; and actual wages paid. In addition, for Appalachian contracts, the payroll records shall contain a notation indicating whether the employee does, or does not, normally reside in the labor area as defined in Attachment A, paragraph 1. Whenever the Secretary of Labor, pursuant to Section IV, paragraph 3b, has found that the wages of any laborer or mechanic include the amount of any costs reasonably anticipated in providing benefits under a plan or program described in Section 1(b)(2)(B) of the Davis Bacon Act, the contractor and each subcontractor shall maintain records which show that the commitment to provide such benefits is enforceable, that the plan or program is financially responsible, that the plan or program has been communicated in writing to the laborers or mechanics affected, and show the cost anticipated or the actual cost incurred in providing benefits. Contractors or subcontractors employing apprentices or trainees under approved programs shall maintain written evidence of the registration of apprentices and trainees, and ratios and wage rates prescribed in the applicable programs. c. Each contractor and subcontractor shall furnish, each week
- in which any contractor work is performed, to the SHA resident engineer a payroll of wages paid each of its employees (including apprentices trainees, and helpers, described in Section IV, paragraphs 4 and 5, and watchmen and guards engaged on work during the preceding weekly payroll period). The payroll submitted shall set out accurately and completely

all of the information required to be maintained under paragraph 2b of this Section V. This information may be submitted in any form desired. Optional Form WH-347 is available for this purpose and may be purchased from the Superintendent of Documents (Federal stock number 029-005-0014-1), U.S. Government Printing Office, Washington, D.C. 20402. The prime contractor is responsible for submitting payroll copies of all subcontractors.

- d. Each payroll submitted shall be accompanied by a "Statement of Compliance," signed by the Contractor or subcontractor or his/her agent who pays or supervises the payment of the persons employed under the contract and shall certify the following:
- (1) that the payroll for the payroll period contains the information required to be maintained under paragraph 2b of this Section V and that such information is correct and complete;
- (2) that such laborer or mechanic (including each helper, apprentice, and trainee) employed on the contract during the payroll period has been paid the full weekly wages earned, without rebate, either directly or indirectly, and that no deductions have been made either directly or indirectly from the full wages earned, other than permissible deductions as set forth in the Regulations, 29 CFR 3;
- (3) that each laborer or mechanic has been paid not less that the applicable wage rate and fringe benefits or cash equivalent for
- the classification of worked performed, as specified in the applicable
- wage determination incorporated into the contract.
- **e**. The weekly submission of a properly executed certification set forth on the reverse side of Optional Form WH-347 shall satisfy the requirement for submission of the "Statement of Compliance" required by paragraph 2d of this Section V.
- f. The falsification of any of the above certifications may subject the contractor to civil or criminal prosecution under 18 U/S. C. 1001 and 31 U.S.C. 231.
- g. The contractor or subcontractor shall make the records required under paragraph 2b of this Section V available for inspection, copying, or transcription by authorized representatives of the SHA, the FHWA, or the DOL, and shall permit such representatives to interview employees during working hours on the job. If the contractor or subcontractor fails to submit the required records or to make them available, the SHA, the FHWA, the DOL, or all may, after written notice to the contractor, sponsor, applicant, or owner, take such actions as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds. Furthermore, failure to submit the required records upon request or to make such records available may be grounds for debarment action pursuant to 29 CFR 5.12.

VI. RECORD OF MATERIALS, SUPPLIES, AND LABOR

- 1. On all federal-aid contracts on the national highway system, except those which provide solely for the installation of protective devices at railroad grade crossings, those which are constructed on a force account or direct labor basis, highway beautification contracts, and contracts for which the total final construction cost for roadway and bridge is less than \$1,000,000 (23 CFR 635) the contractor shall:
 - a. Become familiar with the list of specific materials and supplies contained in Form FHWA-47, "Statement of Materials and Labor Used by Contractor of Highway Construction Involving Federal Funds," prior to the commencement of work under this contract.
 - b. Maintain a record of the total cost of all materials and supplies purchased for and incorporated in the work, and also of the quantities of those specific materials and supplies listed on Form FHWA-47, and in the units shown on Form FHWA-47.
 - c. Furnish, upon the completion of the contract, to the SHA resident engineer on /Form FHWA-47 together with the data

- required in paragraph 1b relative to materials and supplies, a final labor summary of all contract work indicating the total hours worked and the total amount earned.
- **2**. At the prime contractor's option, either a single report covering all contract work or separate reports for the contractor and for each subcontract shall be submitted.

VII. SUBLETTING OR ASSIGNING THE CONTRACT

- 1. The contractor shall perform with its own organization contract work amounting to not less than 30 percent (or a greater percentage if specified elsewhere in the contract) of the total original contract price, excluding any specialty items designated by the State. Specialty items may be performed by subcontract and the amount of any such specialty items performed may be deducted from the total original contract price before computing the amount of work required to be performed by the contractors' own organization (23 CFR 635).
 - a. "Its own organization" shall be construed to include only workers employed and paid directly by the prime contractor and equipment owned or rented by the prime contractor, with or without operators. Such term does not include employees or equipment of a subcontractor, assignee, or agent of the prime contractor.
 - b. "Specialty Items" shall be construed to be limited to work that requires highly specialized knowledge, abilities, or equipment not ordinarily available in the type of contracting organizations qualified and expected to bid on the contract as a whole and in general are to be limited to minor components of the overall contract.
- 2. The contract amount upon which the requirements set forth in paragraph 1 of Section VII is computed includes the cost of material and manufactured products which are to be purchased or produced by the contractor under the contract provisions.
- 3. The contractor shall furnish (a) a competent superintendent or supervisor who is employed by the firm, has full authority to direct performance of the work in accordance with the contract requirements, and is in charge of all construction operations (regardless of who performs the work) and (b) such other of its own organizational resources (supervision, management, and engineering services) as the SHA contracting officer determines is necessary to assure the performance of the contract.
- 4. No portion of the contract shall be sublet, assigned or otherwise disposed of except with the written consent of the SHA contracting officer, or authorized representative, and such consent when given shall not be construed to relieve the contractor of any responsibility for the fulfillment of the contract. Written consent will be given only after the SHA has assured that each subcontract is evidenced in writing and that it contains all pertinent provisions and requirements of the prime contract.

VIII. SAFETY: ACCIDENT PREVENTION

- 1. In the performance of this contract the contractor shall comply with all applicable Federal, State, and local laws governing safety, health, and sanitation (23 CFR 635). The contractor shall provide all safeguards, safety devices and protective equipment and take any other needed actions as it determines, or as the SHA contracting officer may determine, to be reasonably necessary to protect the life and health of employees on the job and the safety of the public and to protect property in connection with the performance of the work covered by the contract.
- 2. It is a condition of this contract, and shall be made a condition of each subcontract, which the contractor enters into pursuant to this contract, that the contractor and any subcontractor shall not permit any employee, in performance of the contract, to work in

surroundings or under conditions which are unsanitary, hazardous or dangerous to his/her health or safety, as determined under construction safety and health standards (29 CFR 1926) promulgated by the Secretary of Labor, in accordance with Section 107 of the Contract Work Hours and Safety Standards Act (40 U.S. C. 333).

3. Pursuant to 29 CFR 1926.3, it is a condition of this contract that the Secretary of Labor or authorized representative thereof, shall have right of entry to any site of contract performance to inspect or investigate the matter of compliance with the construction safety and health standards and to carry out the duties of the Secretary under Section 107 of the Contract Work Hours and Safety Standards Act (40 U.S.C. 333).

IX. FALSE STATEMENTS CONCERNING HIGHWAY PROJECTS

In order to assure high quality and durable construction in conformity with approved plans and specifications and a high degree of reliability on statements and representations made by engineers, contractors, suppliers, and workers on Federal-aid highway projects, it is essential that all persons concerned with the project perform their functions as carefully, thoroughly, and honestly as possible. Willful falsification, distortion, or misrepresentation with respect to any facts related to the project is a violation of Federal law. To prevent any misunderstanding regarding the seriousness of these and similar acts, the following notice shall be posted on each Federal-aid highway project (23 CFR 635) in one or more places where it is readily available to all persons concerned with the project:

NOTICE TO ALL PERSONNEL ENGAGED ON FEDERAL-AID HIGHWAY PROJECTS

18 U.S.C. 1020 reads as follows:

"Whoever, being an officer, agent or employee of the United States, or of any State or Territory, or whoever, whether a person, association, firm, or corporation, knowingly makes any false statement, false representation, or false report as to the character, quality, quantity, or cost of the material used or to be used, or the quantity or quality of the work performed or to be performed, or the cost thereof in connection with the submission of plans, maps, specifications, contracts, or costs of construction on any highway or related project submitted for approval to the Secretary of Transportation; or

Whoever knowingly makes any false statement, false representation, false report or false claim with respect to the character, quality, quantity, or cost of any work performed or to be performed, or materials furnished or to be furnished, in connection with the construction of any highway or related project approved by the Secretary of Transportation; or

Whoever knowingly makes any false statement or false representation as to material fact in any statement, certificate, or report submitted pursuant to provisions of the Federal-aid Roads Act approved July 1, 1916, (39 Stat. 355), as amended and supplemented;

Shall be fined not more than \$10,000 or imprisoned not more than 5 years or both."

X. IMPLEMENTATION OF CLEAN AIR ACT AND FEDERAL WATER POLLUTION CONTROL ACT

(Applicable to all Federal-aid construction contracts and to all related subcontracts of \$100,000 or more).

By submission of this bid or the execution of this contract, or

subcontract, as appropriate, the bidder, Federal-aid construction contractor, or subcontractor, as appropriate, will be deemed to have stipulated as follows:

- 1. That any facility that is or will be utilized in the performance of this contract, unless such contract is exempt under the Clean Air Act, as amended (42 U.S.C. 1857 et seq., as amended by Pub.L. 91-604), and under the Federal Water Pollution Control Act, as amended (33 U.S.C. 1251 et seq., as amended by Pub.L. 92-500), Executive Order 11738, and regulations in implementation thereof (40 CFR 15) is not listed, on the date of contract award, on the U.S. Environmental Protection Agency (EPA) List of Violating Facilities pursuant to 40 CFR 15.20.
- 2. That the firm agrees to comply and remain in compliance with all the requirements of Section 114 of the Clean Air Act and Section 308 of the Federal Water Pollution Control Act and all regulations and guidelines listed thereunder.
- **3.** That the firm shall promptly notify the SHA of the receipt of any communication from the Director, Office of Federal Activities, EPA indicating that a facility that is or will be utilized for the contract is under consideration to be listed on the EPA List of Violating Facilities.
- **4.** That the firm agrees to include or cause to be included the requirements of paragraph 1 through 4 of this Section X in every nonexempt subcontract, and further agrees to take such action as the government may direct as a means of enforcing such requirements.

XI. CERTIFICATION REGARDING DEBARMENT, SUSPENSION, INELIGIBILITY AND VOLUNTARY EXCLUSION

1. Instructions for Certification - Primary Covered Transactions:

a. By signing and submitting this proposal, the prospective

(Applicable to all Federal-aid contracts - 49 CFR 29)

- primary participant is providing the certification set out below.

 b. The inability of a person to provide the certification set out below will not necessarily result in denial of participation in this covered transaction. The prospective participant shall submit an an explanation of why it cannot provide the certification set out below. The certification or explanation will be considered in corporation with the department or agreeable determination.
- an an explanation of why it cannot provide the certification set out below. The certification or explanation will be considered in connection with the department or agency's determination whether to enter into this transaction. However, failure of the prospective primary participant to furnish a certification or an explanation shall disqualify such a person from participation in this transaction.
- **c.** The certification in this clause is a material representation of fact upon which reliance was placed when the department or agency determined to enter into this transaction. If it is later determined that the prospective primary participant knowingly rendered an erroneous certification, in addition to other remedies available to the Federal Government, the department or agency may terminate this transaction for cause of default.
- d. The prospective primary participant shall provide immediate written notice to the department or agency to whom this proposal is

submitted if any time the prospective primary participant learns that

its certification was erroneous when submitted or has become erroneous by reason of changed circumstances.

e. The terms "covered transaction," "debarred," "suspended," "ineligible," "lower tier covered transaction," "participant," "person," "primary covered transaction," "principal," "proposal," and "voluntarily excluded," as used in this clause, have the meanings set out in the Definitions and Coverage sections of rules implementing Executive Order 12549. You may contact the department or agency to which this proposal

is submitted for assistance in obtaining a copy of those regulations.

- f. The prospective primary participant agrees by submitting this proposal that, should the proposed covered transaction be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department or agency entering into this transaction.
- g. The prospective primary participant further agrees by submitting this proposal that it will include the clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Lower Tier Covered Transaction," provided by the department or agency entering into this covered transaction, without modification in all lower tier covered transactions

and in all solicitations for lower tier covered transactions.

h. A participant in a covered transaction may rely upon a certification of a prospective participant in a lower tier covered transaction that is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. A participant may decide the method and frequency by which it determines the eligibility of its principals. Each participant may, but is not required to, check the nonprocurement portion of the "Lists of

Parties Excluded from Federal Procurement or Nonprocurement Programs" (Nonprocurement List) which is compiled by the General Services Administration.

i. Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of participant is not required to exceed that which is normally possessed by a prudent person

in the ordinary course of business dealings.

i. Except for transactions authorized under n

j. Except for transactions authorized under paragraph f of these instructions, if a participant in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible, or voluntarily excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department or agency may terminate this transaction for cause or default.

Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Primary Covered Transactions

- 1. The prospective primary participant certifies to the best of its knowledge and belief, that it and its principals:
 - **a.** Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from covered transactions by any Federal department or agency;
 - b. Have not within a 3-year period preceding this proposal been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain, or performing a public (Federal, State or local) transaction or contract under a public transaction; violation of Federal or State antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction of records, making false statements, or receiving stolen property;
 - c. Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (Federal, State or local) with commission of any of the offenses enumerated in paragraph 1b of this certification; and
 - d. Have not within a 3-year period preceding this application/proposal had one or more public transactions (Federal, State or local) terminated for cause or default.
- 2. Where the prospective primary participant is unable to certify

to any of the statements in this certification, such prospective participant shall attach an explanation to this proposal.

2. Instructions for Certification - Lower Tier Covered Transactions:

(Applicable to all subcontracts, purchase orders and other lower tier transactions of \$25,000 or more - 49 CFR 29)

- **a**. By signing and submitting this proposal, the prospective lower tier is providing the certification set out below.
- **b.** The certification in this clause is a material representation of fact upon which reliance was placed when this transaction was entered into. If it is later determined that the prospective lower tier participant knowingly rendered an erroneous certification, in addition to other remedies available to the Federal Government, the department, or agency with which this transaction originated may pursue available remedies, including suspension and/or debarment.
- **c.** The prospective lower tier participant shall provide immediate written notice to the person to which this proposal is submitted if at any time the prospective lower tier participant learns that its certification was erroneous by reason of changed circumstances.
- d. The terms "covered transaction," "debarred,"
 "suspended," "ineligible," "primary covered transaction,"
 "participant," "person," "principal," "proposal," and
 "voluntarily excluded," as used in this clause, have the
 meanings set out in the Definitions and Coverage sections of
 rules implementing Executive Order 12549. You may contact
 the person to which this proposal is submitted for assistance in
 obtaining a copy of those regulations.
- **e.** The prospective lower tie participant agrees by submitting this proposal that, should the proposed covered transaction be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department or agency with which this transaction originated.
- f. The prospective lower tier participant further agrees by submitting this proposal that it will include this clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Lower Tier Covered Transaction," without modification, in all lower tier covered transactions and in all solicitations for lower tier covered transactions.
- **g.** A participant in a covered transaction may rely upon a certification of a prospective participant in a lower tier covered transaction that is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. A participant may decide the method and frequency by which it determines the eligibility of its principals. Each participant may, but is not required to, check the Nonprocurement List.
- h. Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of participant is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealing.
- i. Except for transactions authorized under paragraph e of these instructions, if a participant in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible, or voluntarily excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department or agency with which this transaction originated may pursue available remedies, including suspension and/or debarment.

* * * * *

Certification Regarding Debarment, Suspension, Ineligibility And Voluntary Exclusion-Lower Tier Covered Transactions:

- 1. The prospective lower tier participant certifies, by submission of this proposal, that neither it nor its principals is presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participation in this transaction by any Federal department or agency.
- 2. Where the prospective lower tier participant is unable to certify to any of the statements in this certification, such prospective participant shall attach an explanation to this proposal.

* * * * * *

XII. CERTIFICATION REGARDING USE OF CONTRACT FUNDS FOR LOBBYING

(Applicable to all Federal-aid construction contracts and to all related subcontracts which exceed \$100,000 - 49 CFR 20)

- 1. The prospective participant certifies, by signing and submitting this bid or proposal, to the best of his or her knowledge and belief, that:
 - a. No Federal appropriated funds have been paid or will be paid, by or on behalf of the undersigned, to any person for influencing or attempting to influence an officer or employee of any Federal agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with the awarding of any Federal contract, the making of any Federal grant, the making of any Federal loan, the entering into of any cooperative agreement, and the extension, continuation, renewal, amendment, or modification of any Federal contract, grant, loan, or cooperative agreement.
 - b. If any funds other than Federal appropriated funds have been paid or will be paid to any person for influencing or attempting to influence an officer or employee of any Federal agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with this Federal contract, grant, loan, or cooperative agreement, the undersigned shall complete and submit Standard Form-LLL, "Disclosure Form to Report Lobbying," in accordance with its instructions.
- 2. This certification is a material representation of fact upon which reliance was placed when this transaction was made or entered into. Submission of this certification is a prerequisite for making or entering into this transaction imposed by 31 U.S.C. 1352. Any person who fails to file the required certification shall be subject to a civil penalty of not less than \$10,000 and not more than \$100,000 for each such failure.
- **3.** The prospective participant also agrees by submitting his or her bid or proposal that he or she shall require that the language of this certification be included in all lower tier subcontracts, which exceed \$100,000 and that all such recipients shall certify and disclose accordingly.

MINIMUM WAGES FOR FEDERAL AND FEDERALLY ASSISTED CONSTRUCTION CONTRACTS

This project is funded, in part, with Federal-aid funds and, as such, is subject to the provisions of the Davis-Bacon Act of March 3, 1931, as amended (46 Sta. 1494, as amended, 40 U.S.C. 276a) and of other Federal statutes referred to in a 29 CFR Part 1, Appendix A, as well as such additional statutes as may from time to time be enacted containing provisions for the payment of wages determined to be prevailing by the Secretary of Labor in accordance with the Davis-Bacon Act and pursuant to the provisions of 29 CFR Part 1. The prevailing rates and fringe benefits shown in the General Wage Determination Decisions issued by the U.S. Department of Labor shall, in accordance with the provisions of the foregoing statutes, constitute the minimum wages payable on Federal and federally assisted construction projects to laborers and mechanics of the specified classes engaged on contract work of the character and in the localities described therein.

General Wage Determination Decisions, modifications and supersedes decisions thereto are to be used in accordance with the provisions of 29 CFR Parts 1 and 5. Accordingly, the applicable decision, together with any modifications issued, must be made a part of every contract for performance of the described work within the geographic area indicated as required by an applicable DBRA Federal prevailing wage law and 29 CFR Part 5. The wage rates and fringe benefits contained in the General Wage Determination Decision shall be the minimum paid by contractors and subcontractors to laborers and mechanics.

NOTICE

The most current **General Wage Determination Decisions** (wage rates) are available on the IDOT web site. They are located on the Letting and Bidding page at http://www.dot.state.il.us/desenv/delett.html.

In addition, ten (10) days prior to the letting, the applicable Federal wage rates will be e-mailed to subscribers. It is recommended that all contractors subscribe to the Federal Wage Rates List or the Contractor's Packet through IDOT's subscription service.

PLEASE NOTE: if you have already subscribed to the Contractor's Packet you will automatically receive the Federal Wage Rates.

The instructions for subscribing are at http://www.dot.state.il.us/desenv/subsc.html.

If you have any questions concerning the wage rates, please contact IDOT's Chief Contract Official at 217-782-7806.