

SCHEDULE OF DRAINAGE STRUCTURES

STR. #	STATION	OFFSET	RIM ELEVATION	CB, TA, 4D TIF OL	CB, TA, 4D T8G	CB, TA, 4D T20 F&G	CB, TA, 5D TIF OL	CB, TA, 5D T20 F&G	CB, TC, 2D T20 F&G	MH, TA, 4D TIF CL	MH TA 5D TIF CL	MH TA 6D TIF CL	DR STR T1 W/2 T20 F&G	DR STR T2 W/2 T22 F&G	INLET, TYPE B, TIF OL	INLET, TYPE B, T 20 F&G	INVERT ELEVATION	TEMP SOIL RET. SYSTEM (SQ FT)
17-02	1460+35.00	-57.00	-2.15			1											-8.87N, -8.03S, -9.10E, -9.00W	
17-03	1460+50.00	-58.00	-2.14			1											-8.73N, -8.83S	
17-04	1460+35.00	-53.00	-2.14								1						-9.89S, -9.11W, -10.39E,	
17-05	NOT USED																	
17-06	1460+20.00	9.00	-2.13												1		-7.96N,	162
17-07	1460+35.00	8.00	-2.14			1											-8.02N, -8.02S, -8.27W,	162
17-08	1460+55.00	9.00	-2.13												1		-7.96S,	
17-09	1461+14.00	8.00	-1.93			1											-7.76S,	162
17-10	1460+14.00	-58.00	-2.14			1											-8.56S, -8.46W	
17-11	1463+31.00	-56.00	0.11			1											-6.25S, -6.5NE, -6.25W	
17-12	1463+31.00	8.00	0.11			1											-5.72W,	162
17-13	1463+46.00	-52.00	0.42								1						-7.82N, -6.56SW, -6.02SE	
17-14	1465+13.00	-56.00	1.8			1											-4.13SE, -4.03W	
17-15	1465+08.00	-52.00	2.04														-8.34S, -8.84E, -4.23NW,	
17-16	NOT USED																	
17-17	1465+08.00	8.00	1.76			1											-4.07N	
17-18	1460+35.00	3.00	-1.9														-10.57N, -10.47W, -8.3E,	
17-19	1462+76.00	-56.00	-0.16			1											-6.00N	
18-01	1469+30.00	-56.00	1.9			1											-4.25E, -4.15W	
18-02	1469+28.00	8.00	1.91			1											-3.92W,	162
18-03	1469+57.00	-52.00	1.9								1						-7.98N, -7.73S,	
18-04	1471+11.00	-56.00	0.14			1											-5.69NE,	
18-05	1471+18.00	-52.00	0.26								1						-9.89N, -9.29S, -5.79W, -6.03E,	
18-06	1471+18.00	8.00	0.1			1											-5.73W,	162
18-07	1469+28.00	-52.50	2.09							1							-7.54N, -4.26W, -4.21E,	
19-01	1472+92.00	8.00	-1.66			1											-7.49NW,	162
19-02	1473+04.00	-56.00	-1.73			1											-7.56NE,	
19-03	1473+10.00	-51.00	-1.52								1						-9.13N, -11.09S, -11.84E, -7.66SW,	
19-04	1473+11.00	3.00	-1.52														-11.96W, -12.16E, -7.59SE, -8.49NE	
19-05	1473+62.00	9.00	-1.91			1											-8.11N, -8.21S,	162
19-06	1473+75.00	8.00	-1.91			1											-7.8N, -8.05S,	162
19-07	1473+90.00	9.00	-1.91												1		-7.74S,	162
19-08	NOT USED																	
19-09	1473+62.00	-57.00	-1.91												1		-7.84N, -7.74W	
19-10	1473+75.00	-56.00	-1.91			1											-7.8N, -7.94S, -8.19E,	
19-11	1473+90.00	-57.00	-1.91														-7.74S,	
19-12	1473+80.00	-51.00	-1.67							1							-8.57N, -8.92S, -8.29W,	
19-13	1474+58.00	8.00	-1.67			1											-7.5W,	162
19-14	1474+51.00	-51.00	-1.47							1							-8.05S, -7.66W, -7.8E,	
19-15	1474+58.00	-56.00	-1.67			1											-7.60E, -7.50W	
19-16	1476+03.00	-51.00	-0.03							1							-7.13N, -6.24W, -6.33E,	
19-17	1476+03.00	8.00	-0.23			1											-6.06W,	49
19-18	1475+98.00	-56.00	-0.28			1											-6.21NE, -6.11W	
19-19	1477+81.00	-56.00	1.64			1											-4.29E, -4.19W	
19-20	1477+81.00	4.50	1.78			1											-4.05N,	
19-21	1477+90.00	-51.00	1.98								1						-6.95N, -8.13S, -9.13E, -4.39SW,	
19-22	1477+93.00	3.00	2.01								1						-4.15S, -9.19W, -9.29E,	
19-23	1476+45.00	-51.00	0.39							1							-7.42N, -7.32S,	
20-01	1478+75.00	-51.00	2.89								1						-6.68N, -6.78S,	
20-02	1479+78.00	-51.00	4								1						-6N, -6.5S, -2.26W, -2.25E,	
20-03	1479+78.00	-56.00	3.76			1											-2.16E, -2.06W	
20-04	1479+78.00	5.00	3.88			1											-1.95W,	63
20-05	1481+55.00	-56.00	5.65			1											-0.28E, -0.18W	
20-06	1481+55.00	5.00	5.81			1											-0.02W,	90
20-07	1481+55.00	-51.00	5.89								1						-5.14N, -5.24S, -0.38W, -0.31E,	
20-08	1483+55.00	-51.00	8.03														-3.6N, -4.35S, 2.00W, 1.85E,	
20-09	1483+55.00	-56.00	7.79			1											2.04E, 2.14W	
20-10	1483+55.00	5.00	7.95			1											2.12W,	162
20-11	1481+18.00	-51.00	5.49								1						-5.36N, -5.46S,	
21-01	1485+69.00	-51.00	10.16														-2.44S, 3.96W, 3.86E,	
21-02	1485+69.00	-56.00	9.92			1											3.99E, 4.09W	
21-03	1485+69.00	6.00	10			1											4.17W,	162
22-01	1490+69.00	-56.00	9.91			1											3.98E, 4.08W	
22-02	1490+69.00	6.00	9.99			1											4.16W,	162
22-03	1490+73.00	-51.00	10.12								1						-2.3N, 3.85W, 3.98E,	
22-04	1492+66.00	6.00	8.12			1											2.29W,	162



NOTE:  
OFFSET FOR DRAINAGE STRUCTURES IS TO THE CENTER OF THE FRAME AND GRATE.

REVISIONS	
NAME	DATE
ADDENDUM	8/12/05
ADDENDUM	9/16/05

ILLINOIS DEPARTMENT OF TRANSPORTATION  
 F.A.I. 94/90 (DAN RYAN EXPRESSWAY)  
 31ST STREET TO 71ST STREET  
 SB EXPRESS LANE RECONSTRUCTION  
 DRAINAGE SCHEDULE  
 PROPOSED DRAINAGE STRUCTURES  
 SCALE: 1" = N.T.S. DRAWN BY: MJJ  
 DATE: 7/7/05 CHECKED BY: LPN

I:\Projects\9490\Drawings\9490-136.dwg  
 20/14/2005 11:02:49 AM