

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION



SOIL BORING LOG

Date 10/6/04

ROUTE Il 47 DESCRIPTION Over West Fork of Mazon River LOGGED BY Larry Meyers
SECTION 119BR-2 LOCATION NE 1/4, SEC. 33, TWP. 32, RNG. 7E, 3rd PM
COUNTY Grundy DRILLING METHOD Hollow Stem Auger HAMMER TYPE Automatic

STRUCT. NO.	Station	BORING NO.	Station	Offset	Ground Surface Elev.	DEPTH	BL	UCS	MOIST	Surface Water Elev.	Stream Bed Elev.	Groundwater Elev.	First Encounter	Upon Completion	After	Hrs.	DEPTH	BL	UCS	MOIST
						(ft)	(/6")	(tsf)	(%)	ft	ft	ft	ft	ft	ft		(ft)	(/6")	(tsf)	(%)
					587.54					572.48										

File Name and/or Number
Latitude and Longitude

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)
BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Date 10/6/04

ROUTE Il 47 DESCRIPTION Over West Fork of Mazon River LOGGED BY Larry Meyers
SECTION 119BR-2 LOCATION NE 1/4, SEC. 33, TWP. 32, RNG. 7E, 3rd PM
COUNTY Grundy DRILLING METHOD Hollow Stem Auger HAMMER TYPE Automatic

STRUCT. NO.	Station	BORING NO.	Station	Offset	Ground Surface Elev.	DEPTH	BL	UCS	MOIST	Surface Water Elev.	Stream Bed Elev.	Groundwater Elev.	First Encounter	Upon Completion	After	Hrs.	DEPTH	BL	UCS	MOIST
						(ft)	(/6")	(tsf)	(%)	ft	ft	ft	ft	ft	ft		(ft)	(/6")	(tsf)	(%)
					587.54					572.48										

File Name and/or Number
Latitude and Longitude

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)
BBS, from 137 (Rev. 8-99)

BORING LOGS
IL 47 OVER WEST FORK MAZON RIVER
FAP ROUTE 326 - SECTION 119BR-2
GRUNDY COUNTY
STATION 466+07.00
STRUCTURE NO. 032-0116

Eastport Business Center 1
100 Lanter Court, Suite 1
Collinsville, Illinois 62234
618-345-2200

OATES ASSOCIATES
Consulting Engineers Design Firm License No. 184.001115