

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
22	135W-2; RS-5	FULTON	282	26
STA.		TO STA.		
FED. ROAD DIST. NO. 4 ILLINOIS FED. AID PROJECT				

RESURFACING TABLE (1 OF 2)

LOCATION	WIDTH	LENGTH	AREA	HOT-MIX ASPHALT SURFACE REMOVAL				TEMPORARY RAMP	BITUMINOUS MATERIALS PRIME COAT	AGGREGATE MATERIALS PRIME COAT	STRIP REFLECTIVE CRACK CONTROL TREATMENT	HOT-MIX ASPHALT BINDER COURSE IL-19.0, N50				POLY LVL BNDR MACHINE METHOD IL-4.75 N50	HOT-MIX ASPHALT SURFACE COURSE MIX "E", N50	INCIDENTAL HOT-MIX ASPHALT SURFACING	HOT-MIX ASPHALT SHOULDERS			AGGREGATE SHOULDERS TYPE B					
				BUTT JOINT	0.5"	2"	VAR DEPTH					NEW PAV'T	WIDEN	NEW VERT CURVE	UNDER CCC&G				LEFT SIDE	RIGHT SIDE	RIGHT SIDE	LEFT SIDE	RIGHT SIDE				
				SQ YD	SQ YD	SQ YD	SQ YD					TON	TON	TON	TON				TON	TON	TON	TON	TON	TON	TON	TON	TON
159+95 TO 160+25	22	30	73.3	73.3				12.2	0.04	0.2					2.1	6.2											
160+25 TO 164+25	24 TO 38	400	1377.8		1377.8				0.72	4.1	800		246.4		77.4	116.2			222.2	222.2			45.6	45.6			
164+25 TO 185+44	38	2119	8946.9		8946.9				4.65	26.8	4238		2320.5		502.1	754			1177.2	1177.2			241.6	241.6			
185+44 TO 188+44	38	300	1266.7		1266.7				0.66	3.8	600		184.8		71.1	106.8			166.7	166.7			34.2	34.2			
188+44 TO 198+34	36	990	3960		3960				2.06	11.9					222.3	333.8			660	660			53.4	112.9			
198+34 TO 199+15	48	81	432		432				0.22	1.3	81		17.3		6.7	24.2	36.4				54			9.2			
199+15 TO 200+71	48 TO 36	156	728		728				0.38	2.2	156		47.2		9.3	40.8	61.3				104			17.8			
200+71 TO 202+82	38	211	890.9		890.9				0.46	2.7	422		173.3		50	75.1			117.2	117.2			24.1	24.1			
202+82 TO 224+90	38	2208	9322.7		9322.7				4.85	28	4416		2418		523.2	785.7			1226.7	1226.7			214	206.7			
224+90 TO 229+00	38	410	1731.1		1731.1				0.9	5.2	820		449		97.2	145.9						285.6	46.7	17.1			
229+00 TO 239+76	38	1076	4543.1		4543.1				2.36	13.6	2152		1178.3		255	382.9			597.8	597.8			122.7	122.7			
239+76 TO 242+74	42	298	1390.7		1390.7				0.72	4.2	596		428.3		19.1	78	117				165.6			34			
242+74 TO 252+11	48	937	4997.3		4997.3				2.6	15	1874		1667.4		98.5	279.8	419.8										
252+11 TO 253+49	48	138	736				736		0.38	2.2	276		245.6		17.7	41.2	61.8										
253+49 TO 265+50	48	1201	6405.3		6405.3				3.33	19.2	2402		2137.2		123.4	358.7	538										
265+50 TO 273+20	48	770	4106.7						2.14	12.3		2414.7			81.1	230	345										
273+20 TO 277+00	48	380	2026.7						1.05	6.1	760	676.2		598.1	36.9	113.5	170.2										
277+00 TO 277+50	48	50	266.7						0.14	0.8	100	86.4		16.4	6.4	14.9	22.4										
277+50 TO 282+28	48 TO 41	478	2356.3		2356.3				1.23	7.1	817		432.5		48.7	132	197.9										
282+28 TO 282+58	36	30	120	120				20	0.06	0.4					3.4	10.1											
SUBTOTALS (THIS PAGE)												3177.3	11945.8	614.5	447.8		4686.5	0		4167.8	4491.4		782.3	865.9			
TOTALS (THIS PAGE)				193.3	48349	0	736	32.2	28.95	167.1	20510		16185.4		3116.9	4686.5	0		0	8659.2	285.6	1648.2					

FURNISHING AND ERECTING RIGHT-OF-WAY MARKERS

LEFT		RIGHT	
LOCATION	EACH	LOCATION	EACH
188+53.00 60.00' LT	1	190+63.00 76.38' RT	1
189+24.00 86.00' LT	1	190+63.00 107.00' RT	1
190+05.06 86.00' LT	1	190+92.00 103.00' RT	1
190+06.41 60.00' LT	1	190+92.00 71.80' RT	1
212+00.00 60.00' LT	1	212+05.00 45.00' RT	1
212+50.00 80.00' LT	1	213+30.00 110.00' RT	1
213+30.00 80.00' LT	1	213+80.00 110.00' RT	1
214+00.00 60.00' LT	1	214+50.00 60.00' RT	1
215+00.00 60.00' LT	1	225+00.00 62.17' RT	1
215+50.00 66.00' LT	1	225+90.00 83.00' RT	1
219+50.00 66.00' LT	1	226+90.00 80.00' RT	1
220+00.00 50.00' LT	1	228+51.00 40.00' RT	1
222+00.00 50.00' LT	1	236+12.23 50.00' RT	1
222+05.00 55.00' LT	1	237+00.00 86.00' RT	1
223+58.00 55.00' LT	1	237+50.00 86.00' RT	1
223+63.00 50.00' LT	1	238+77.00 45.00' RT	1
224+13.79 50.00' LT	1	253+73.35 50.00' RT	1
225+26.00 77.00' LT	1	253+75.11 511.85' RT	1
226+00.00 77.00' LT	1	254+03.35 50.00' RT	1
227+13.60 60.00' LT	1	254+04.86 447.31' RT	1
237+11.00 50.00' LT	1	254+09.86 447.31' RT	1
237+11.00 55.00' LT	1	254+10.10 512.39' RT	1
237+40.00 55.00' LT	1		
237+40.00 50.00' LT	1		
SUBTOTAL LEFT	24	SUBTOTAL RIGHT	22
TOTAL		46	

EPOXY AND TEMPORARY PAVEMENT MARKINGS

LOCATION	LENGTH	4" WHITE						4" YELLOW		8"	12"	24"	LETTERS	RAISED REFLECTIVE PAVEMENT MARKERS		
		EOP + RTL		SOLID		DASH	YELLOW X-WALK	YELLOW DIAG	WHITE STOP BAR	AND SYMBOLS	1-WAY CRYSTAL	1-WAY AMBER	2-WAY AMBER			
		LT	RT	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	SQ FT	EACH	EACH	EACH			
159+95 TO 160+97	102	102	102	204												2
160+97 TO 163+72	275	275	275	1135				154						20		
163+72 TO 198+09	3437	3391	3483	6874	1718.5					530.4					172	
198+09 TO 199+15	106	106	106	318	53					62.4						
199+15 TO 245+85	4670	4738	4901	9340	2335					717.6					234	
245+85 TO 246+77	92	144	92			162			39							
246+77 TO 282+58	3581	3911	4174	7162	1790.5	72				561.6					180	
IL 78 A	850	850	850		212.5											
SUB TOTALS		13517	13983	25033	6109.5						0	20	588			
TOTALS				58642.5		234	154	39	1872			608				

SHORT TERM PAVEMENT MARKING

LOCATION	LENGTH	CL	SHLDR	ALL	WET TEMPORARY PAVEMENT MARKING TAPE, TYPE III 4 INCH	WORK ZONE PAVEMENT MARKING REMOVAL
		DASH	DIAG	APPS		
		FOOT	FOOT	FOOT	FOOT	SQ FT
159+95 TO 160+97	102	10.2	8			
160+97 TO 198+09	3712	742.4	296			
198+09 TO 199+15	106	31.8	16			
199+15 TO 279+00	7985	1597	632			
279+00 TO 282+58	358	71.6	144			
IL 78 A	850	85				
SUBTOTAL			3634			
X 2 APPLICATIONS					7268	
NEW PROFILE STAGE CONSTRUCTION (STAGES II + III)					5002	
NEW PROFILE STAGE CONSTRUCTION (STAGES IV + V)					4784	
TUNNEL AND RETAINING WALL STAGE CONSTRUCTION					1252	
TOTAL					7268	11038

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

Schedule of Quantities

SCALE: VERT. HORIZ. DATE

DRAWN BY CHECKED BY