

RT/LT	STATION TO STATION	EARTH EXCAVATION	EARTH EXCAVATION ADJ FOR SHRINKAGE (25%)	SEEDING, CLASS 2A	NITROGEN FERTILIZER NUTRIENT	PHOSPHOROUS FERTILIZER NUTRIENT	POTASSIUM FERTILIZER NUTRIENT	MULCH, METHOD 1 (FINAL SEEDING)	MULCH, METHOD 1 (EROSION CONTROL)
		CU YD	CU YD	ACRE	POUND	POUND	POUND	ACRE	ACRE
RT	1001+65 - 929+82	354.7	266.0	1.32	118.8	118.8	118.8	1.32	1.32
LT	930+18 - 859+07	351.2	263.4	1.31	117.9	117.9	117.9	1.31	1.31
RT	857+63 - 785+15	357.9	268.4	1.33	119.7	119.7	119.7	1.33	1.33
LT	784+03 - 739+54	219.7	164.8	0.82	73.8	73.8	73.8	0.82	0.82
RT	738+20 - 696+82	204.3	153.2	0.76	68.4	68.4	68.4	0.76	0.76
LT	695+90 - 644+56	253.5	190.1	0.94	84.6	84.6	84.6	0.94	0.94
RT	642+98 - 565+90	380.6	285.5	1.42	127.8	127.8	127.8	1.42	1.42
LT	566+30 - 509+00	283.0	212.3	1.05	94.5	94.5	94.5	1.05	1.05
TOTALS		2404.9	1803.7	8.95	805.5	805.5	805.5	8.95	8.95

THE EARTH EXCAVATION GENERATED BY THE PLACEMENT OF THE HMA SHOULDER (APPROXIMATELY 2401.7 CU YD) MAY BE USED AS FURNISHED EXCAVATION REQUIRED TO MEET THE 4:1 OR FLATTER SLOPE REQUIREMENT AS SHOWN IN THE PLANS. ADDITIONAL FURNISHED EXCAVATION REQUIRED BEYOND WHAT IS PROVIDED AS SHOWN ABOVE SHALL BE PAID FOR PER ARTICLE 109.04 OF THE STANDARD SPECIFICATIONS.

ANY EXCESS EARTH EXCAVATION SHALL BE DISPOSED OF BY THE CONTRACTOR PER SECTION 202 OF THE STANDARD SPECIFICATIONS.