



LOCATION 10

GSI Job No. 13032

SOIL BORING LOG

Page 1 of 1

Date 5/11/13

ROUTE I-90 (EB) DESCRIPTION Kennedy Expy EB at Austin Ave. Exit MP 82.5 LOGGED BY DM

SECTION LOCATION SEC. TWP. RNG. 3rd PM

COUNTY Cook DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME Automatic

Table with columns for DEPTH, BLOW COUNT, UNCONFINED COMPRESSIVE STRENGTH, and SOIL DESCRIPTION. Includes data for 6.0" ASPHALT, 7.0" CONCRETE and CLAY-brown & gray-stiff to hard.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T208) BBS, from 137 (Rev. 8-99)



LOCATION 11

GSI Job No. 13032

SOIL BORING LOG

Page 1 of 1

Date 5/11/13

ROUTE I-90 (EB) DESCRIPTION Kennedy Expy EB at Lawrence Ave. MP 83.9 LOGGED BY DM

SECTION LOCATION SEC. TWP. RNG. 3rd PM

COUNTY Cook DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME Automatic

Table with columns for DEPTH, BLOW COUNT, UNCONFINED COMPRESSIVE STRENGTH, and SOIL DESCRIPTION. Includes data for 6.0" ASPHALT, 9.0" CONCRETE and SAND with GRAVEL-gray-dense.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T208) BBS, from 137 (Rev. 8-99)

Vertical text on the left margin: H:\JCS2011\201302-44\CAD\Site\Site.dgn 5/11/2013 3:57:32 PM

Vertical text on the left margin: Z:\PROJECTS\2013\13032\GSAFF\PTB 156-009 WORK ORDER 44\_SIGN STRUCTURES\13032 BORING LOGS\13032 LOG.GPJ 6/18/13

Vertical text on the left margin: Z:\PROJECTS\2013\13032\GSAFF\PTB 156-009 WORK ORDER 44\_SIGN STRUCTURES\13032 BORING LOGS\13032 LOG.GPJ 6/18/13