DETAIL OF INERTIAL BARRIERS (70 MPH DESIGN - 70' MEDIAN) (48.8m) EDGE OF PAVEMENT P.I. OF SHOULDER C OF INERTIAL BARRIER SLOPE TO DRAIN C PIER -EXIST. MEDIAN OF OF INERTIAL BARRIER (SEE BASE DETAIL) SLOPE TO DRAIN P.I. OF SHOULDER GRADING AND SHAPING DETAIL EDGE OF PAVEMENT TRAFFIC GENERAL NOTES DESIGNER NOTES: 1. Include BDE Special Provision "Impact Attenuators" 2. Contact the Bridge Office about crash wall details if 3. Designer should review Median Drainage. 4. Verify Dist. STD No. for Design Speed & Median Width. 1. ALL 1:10 SLOPES SHOWN ON THIS DETAIL SHALL BE CONSTRUCTED 1:10 OR FLATTER. 2. THE SLOPES AS SHOWN ON THIS DETAIL SHALL APPLY TO BOTH ENDS OF THE BRIDGE 3. ATTENUATOR BASE AND BARREL ARRAY SHALL BE INSTALLED IN ACCORDANCE WITH STATE STANDARD 643001 AND MANUFACTURER'S SPECIFICATIONS 4. IN AREAS OF 1:10 SLOPES PRECEDING THE ATTENUATOR IN THE MEDIAN INSTALLATION, FOUR OR MORE WOOD POSTS SHALL BE PLACED AT 5' (1.5m) INTERVALS IN THE MEDIAN (, 42'-0" SEE SPECIAL PROVISIONS AND SCHEDULES. (12.8m) 12'-6" 29'-6" (9.0m) (3.8m) SECTION A-A EXISTING CROSS SECTION BASE DETAIL All slope ratios are expressed as units of vertical displacement to units of horizontal displacement All dimensions are in inches (millimeters) unless otherwise noted. 01-01-97 RENUM. F-3.02a, NEW REVISION BOX, REVISED T.P. 03-15-12 REMOVED BARRELS R.D. COUNTY

STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION

TITLE BOX, REVISED NOTES

M.A.

M.A.

08-02 REVISED & ADDED

10-16-06 REVISED TO 2007 SPEC.

MEDIAN SAND MODULE IMPACT ATTENUATOR

70' MEDIAN

NOT TO SCALE

CONTRACT NO.

CADD STD. 650006-D4 FED. ROAD DIST. NO. | ILLINOIS FED. AID PROJECT