



FOR MILLING AND RESURFACING

SECTION TOTAL SPEET SMEETS SM 537 R-1 COOK FEG. HOAD DIST. NO. \_ BLEWOIS FEO. AND PRIMEET





## TYPICAL BUTT JOINT AND BITUMINOUS TAPER FOR RESURFACING ONLY

\* PC CONCRETE, BITUMINOUS OR BITUMINOUS RESURFACED PAVEMENT.

## NOTES

- A: MAINLINE ROADWAYS AND MAJOR SIDE ROADS.
- B: MINOR SIDE ROADS.
- C: THE TEMP. RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING BITUMINOUS SURFACE.
- D: THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED BITUMINOUS COURSES.
- E: TAPER THE TEMP, RAMP AT A RATE OF 900 (3 ft.) PER INCH OF MILLING THICKNESS.
- F: INSTALLATION AND REMOVAL OF THE 1.35 m (4.5') TEMP, BIT, RAMP WILL BE PAID AS "BITUMINOUS SURFACE REMOVAL - BUTT JOINT".
- G: SEE ARTICLE 406.18 AND 406.24 OF THE STANDARD SPECIFICATIONS FOR "BITUMINOUS AND PCC SURFACE REMOVAL, BUTT JOINT".
- \* SEE TYPICAL SECTIONS FOR MILLING THICKNESS.

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE SHOWN.

ILLINOIS DEPARTMENT OF TRANSPORTATION

BUTT JOINT AND BITUMINOUS TAPER DETAILS

NAME

M. DE YONG

R, SHAH

DRAWN BY CHECKED BY

SCALE: NONE DATE PLOTTED: \$9DATE\$\$

DS-5

BD400-05 (VI=BD32)