

TABULATION OF RESURFACING QUANTITIES

40600980 BITUMINOUS SURFACE REMOVAL - BUTT JOINT
 40600200 BITUMINOUS MATERIALS (PRIME COAT)
 44300200 STRIP REFLECTIVE CRACK CONTROL TREATMENT
 X4066426 BITUMINOUS CONCRETE SURFACE COURSE SUPERPAVE, MIX D, N 70
 X4066770 LEVELING BINDER (MACHINE METHOD), SUPERPAVE, N 70

LOCATION	LENGTH	WIDTH	PAVEMENT AREA	BITUMINOUS SURFACE REMOVAL BUTT JOINT	BITUMINOUS MATERIALS (PRIME COAT)	STRIP REFLECTIVE CRACK CONTROL TREATMENT	BIT. CONC. SURFACE COURSE SUPERPAVE MIX D, N 70	LEVELING BINDER (MACHINE METHOD) SUPERPAVE N 70
	FT	FT	SQ FT	SY	TON	FOOT	TON	TON
70+70.00 TO 70+95.00	25	VARIES	675	75				
55+00 TO 70+95	1595	VARIES	44098		1.6	645.5	417	281
NORTH RAMP	VARIES	VARIES	8906		0.4		85	57
SOUTH RAMP	VARIES	VARIES	10385		0.4		99	67
TOTAL			64064	75	2.4	645.5	601	405

SCHEDULE OF GUARDRAIL QUANTITIES

63000000 STEEL PLATE BEAM GUARD RAIL, TYPE A
 63100085 TRAFFIC BARRIER TERMINAL, TYPE 6
 63100167 TRAFFIC BARRIER TERMINAL TYPE 1, SPECIAL (TANGENT)
 63100169 TRAFFIC BARRIER TERMINAL TYPE 1, SPECIAL (FLARED)
 78201000 TERMINAL MARKERS - DIRECT APPLIED
 28100105 STONE RIPRAP, CLASS A3

LOCATON	SPBGR TYPE A	TRAFFIC BARRIER TERM TYPE 6	TRAFFIC BARRIER TERM TYPE 1 SPECIAL (TANGENT)	TRAFFIC BARRIER TERM TYPE 1 SPECIAL (FLARED)	TERMINAL MARKER DIR. APPLIED	STONE RIPRAP CLASS A3
	FEET	EACH	EACH	EACH	EACH	SY
44+94 TO 46+52 LT	137.5					
44+86 TO 46+21 RT	112.5					
48+16 TO 50+28 LT	162.5					
47+85 TO 50+06 RT	162.5					
SN 098-6000 WB APPROACH	112.5			1	1	
SN 098-6000 EB TRAILING	62.5		1		1	
SN 098-6000		4				
SN 098-6001		4				
52+27 TO 52+79 LT						44
52+12 TO 52+79 RT						56
TOTAL	750.0	8	1	1	2	100

TABULATION OF PARTIAL DEPTH PATCHING

44200120 PAVEMENT PATCHING TYPE II, 10"
 44000120 BITUMINOUS REMOVAL OVER PATCHES 5"
 40601000 BITUMINOUS REPLACEMENT OVER PATCHES
 Z0028700 GRANULAR SUBGRADE REPLACEMENT
 Z0028415 GEOTECHNICAL REINFORCEMENT

LANE = 12'

STATION	LEFT LANE FT	RIGHT LANE FT	PAV'T PATCHING TYPE 2, 10"		BITUMINOUS REM. OVER PATCHES 5"		BITUMINOUS REPL. OVER PATCHES		GRANULAR SUBGRADE REPL. CY	GEOTECHNICAL REINFORCEMENT SY
			LEFT LANE SY	RIGHT LANE SY	LEFT LANE SY	RIGHT LANE SY	LEFT LANE TON	RIGHT LANE TON		
61+60	5	5	6.7	6.7	8.1	8.1	2.3	2.3	2.2	13.4
66+66		5		6.7		8.1		2.3	1.1	6.7
66+94	5		6.7		8.1		2.3		1.1	6.7
TOTAL			13.4	13.4	16.2	16.2	4.6	4.6	4.4	26.8

SCHEDULE OF BRIDGE APPROACH PAVEMENT

42001165 BRIDGE APPROACH PAVEMENT
 42001300 PROTECTIVE COAT

LOCATION	THICKNESS	PAY LIMIT	WIDTH	BRIDGE APPROACH PAVEMENT	PROTECTIVE COAT
	INCHES	FT	FT	SY	SY
S.N. 098-6001, WEST APPROACH	15	30	41.33	137.8	137.8
S.N. 098-6001, EAST APPROACH	15	30	41.33	137.8	137.8
S.N. 098-6000, WEST APPROACH	15	30	41.33	133.6	133.6
S.N. 098-6000, EAST APPROACH	15	30	41.33	133.6	133.6
TOTAL				542.8	542.8

SCHEDULE OF SUBBASE QUANTITIES

31100300 SUBBASE GRANULAR MATERIAL, TYPE A, 4"
 31100100 SUBBASE GRANULAR MATERIAL, TYPE A
 31200100 STABILIZED SUBBASE, 4"

LOCATION	GRANULAR SUBBASE TYPE A, 4"	GRANULAR SUBBASE TYPE A	STABILIZED SUBBASE 4"
	SQ YD	TON	SQ YD
55+00.00 TO 55+52.00	24		
55+52.00 TO 60+32.00	266.7		
60+32.00 TO 61+32.00	39		
44+94.88 TO 46+06.03		373.1	546
48+31.03 TO 49+85.95		520.0	761
52+49.71 TO 55+00.00		927.3	1357
NORTH RAMP		874.0	1279
SOUTH RAMP		1122.0	1642
TOTAL	329.7	3816.4	5585

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

SCHEDULE OF QUANTITIES

SCALE: VERT.
 HORIZ.
 DATE 08/25/2005
 DRAWN BY SWEET
 CHECKED BY ZELINSKAS