FOR INDEX OF SHEETS, HIGHWAY STANDARDS, AND DETAILS SEE SHEET NO. 2

PROJECT IS LOCATED IN THE VILLAGÉS OF ROUND LAKE BEACH, LAKE VILLA, AND ANTIOCH.

TRAFFIC DATA

0

ROUTE SEGMENT	SPEED (MPH)	ADT (2013)	CLASSIFICATION
IL ROUTE 83 FROM COUNTY HWY 31 / ROLLINS RD TO MILLSTONE DR	35	25,100	2 LANE OTHER PRINCIPAL ARTERIAL
IL ROUTE 83 FROM MILLSTONE DR TO COUNTY HWY 55 / MONAVILLE RD	45	25,100	2 LANE OTHER PRINCIPAL ARTERIAL
IL ROUTE 83 FROM COUNTY HWY 55 / MONAVILLE RD TO ENGLE DR	45	15,400	4 LANE OTHER PRINCIPAL ARTERIAL
IL ROUTE 83 FROM ENGLE DR TO IL ROUTE 132 / GRAND AVE	45	15,400	2 LANE OTHER PRINCIPAL ARTERIAL
IL ROUTE 83 FROM IL ROUTE 132 / GRAND AVE TO SQUIRE RD	35	13,000	4 LANE OTHER PRINCIPAL ARTERIAL
IL ROUTE 83 FROM SQUIRE RD TO PETITE LAKE RD	45	13,000	3 LANE OTHER PRINCIPAL ARTERIAL
IL ROUTE 83 FROM PETITE LAKE RD TO COUNTY HWY 18 / GRASS LAKE RD	50	13,000	2 LANE OTHER PRINCIPAL ARTERIAL
IL ROUTE 83 FROM COUNTY HWY 18 / GRASS LAKE RD TO IL ROUTE 173	40	11,900	3 LANE OTHER PRINCIPAL ARTERIAL
IL ROUTE 83 FROM IL ROUTE 173 TO LAKE ST	30	10,900	3 LANE OTHER PRINCIPAL ARTERIAL
IL ROUTE 83 FROM LAKE ST TO ORCHARD ST	30	10,900	2 LANE OTHER PRINCIPAL ARTERIAL
IL ROUTE 83 FROM ORCHARD ST TO NORTH AVE	20	13,900	3 LANE OTHER PRINCIPAL ARTERIAL

0 100' 200' 300' — 1"= 100'
0 10' 20' 30' — 1"= 10'
0 50' 100'
1"= 50'
0 50' 100'
1"= 40'
0 100' — 1"= 30'
0 50' 100' — 1"= 20'

FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.

J.U.L.I.E.
JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION
1–800–892–0123
OR 811


STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS


PLANS FOR PROPOSED FEDERAL AID HIGHWAY

FAP 0866 (IL RTE 83 /MILWAUKEE AVE./MAIN ST.)
MILLSTONE DRIVE TO COUNTY HWY 3 (NORTH AVE.)
TRAFFIC SIGNAL INTERCONNECT
SECTION: 12-00999-25-TL
PROJECT NO.: CMM-4003 (291)

LAKE COUNTY JOB NO.: C-91-245-14








PRINTED BY THE AUTHORITY OF THE STATE OF ILLINOIS

CHRISTOPHER B. BURKE ENGINEERING, LTD.
9575 W. Higgins Road, Suite 600
Rosemont, Illinois 60018
(847) 823-0500
PROFESSIONAL DESIGN FIRM No.: 184-001742



CONTRACT NO. 61A74

	INDEX OF SHEETS
1	TITLE SHEET
2	INDEX OF SHEETS, HIGHWAY STANDARDS, AND DETAILS
3	GENERAL NOTES SUMMARY OF QUANTITIES
5	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND MILLSTONE DRIVE
6	SCHEDULE OF QUANTITIES, CABLE PLAN, PHASE DESIGNATION DIAGRAM AND EMERGENCY VEHICLE PREEMPTION SEQUENCE IL ROUTE 83 AND MILLSTONE DRIVE
7	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND MONAVILLE ROAD
8	SCHEDULE OF QUANTITIES, CABLE PLAN, PHASE DESIGNATION DIAGRAM AND EMERGENCY VEHICLE PREEMPTION SEQUENCE IL ROUTE 83 AND MONAVILLE ROAD
9	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND ENGLE DRIVE
10	SCHEDULE OF QUANTITIES, CABLE PLAN, PHASE DESIGNATION DIAGRAM AND EMERGENCY VEHICLE PREEMPTION SEQUENCE IL ROUTE 83 AND ENGLE DRIVE
11	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND IL ROUTE 132 (GRAND AVE.) SHEET 1 OF 2
12	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND IL ROUTE 132 (GRAND AVE.) SHEET 2 OF 2
13	SCHEDULE OF QUANTITIES, CABLE PLAN, PHASE DESIGNATION DIAGRAM AND EMERGENCY VEHICLE PREEMPTION SEQUENCE IL ROUTE 83 AND IL ROUTE 132 (GRAND AVE.)
14	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND PETITE LAKE ROAD
15	SCHEDULE OF QUANTITIES, CABLE PLAN, PHASE DESIGNATION DIAGRAM AND EMERGENCY VEHICLE PREEMPTION SEQUENCE IL ROUTE 83 AND PETITE LAKE ROAD
16	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND GRASS LAKE ROAD
17	SCHEDULE OF QUANTITIES, CABLE PLAN IL ROUTE 83 AND GRASS LAKE ROAD
18	SEQUENCE OF OPERATION IL ROUTE 83 AND GRASS LAKE ROAD
19	RAILROAD PREEMPTION SEQUENCE OF OPERATION AND EMERGENCY VEHICLE SEQUENCE OF OPERATION IL ROUTE 83 AND GRASS LAKE ROAD
20	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND IL ROUTE 173 SHEET 1 OF 2
21	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND IL ROUTE 173 SHEET 2 OF 2
22	SCHEDULE OF QUANTITIES, CABLE PLAN IL ROUTE 83 AND IL ROUTE 173
23	SEQUENCE OF OPERATION IL ROUTE 83 AND IL ROUTE 173
24	EMERGENCY VEHICLE SEQUENCE OF OPERATION IL ROUTE 83 AND IL ROUTE 173
25	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND IL ROUTE 59 (LAKE ST.)
26	SCHEDULE OF QUANTITIES, CABLE PLAN, PHASE DESIGNATION DIAGRAM AND EMERGENCY VEHICLE PREEMPTION SEQUENCE IL ROUTE 83 AND IL ROUTE 59 (LAKE ST.
27	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND ORCHARD STREET
28-29	SCHEDULE OF QUANTITIES, CABLE PLAN, PHASE DESIGNATION DIAGRAM AND EMERGENCY VEHICLE PREEMPTION SEQUENCE IL ROUTE 83 AND ORCHARD STREET
30	TRAFFIC SIGNAL MODIFICATION PLAN IL ROUTE 83 AND NORTH AVE.
31	SCHEDULE OF QUANTITIES, CABLE PLAN IL ROUTE 83 AND NORTH AVE.
32	SEQUENCE OF OPERATION IL ROUTE 83 AND NORTH AVE.
33	EMERGENCY VEHICLE SEQUENCE OF OPERATION IL ROUTE 83 AND NORTH AVE.
34-45	INTERCONNECT PLAN
46	INTERCONNECT SCHEMATIC PLAN
47 48	FIBER TERMINATION / SPLICE COUNT AND PATCH PANEL COLOR CODE
49-50	FIBER SPLICING DIAGRAM CABINET DETAIL
51	CONDUIT ATTACHED TO STRUCTURE DETAIL
52-53	LCDOT STANDARD DETAILS
54-60	DISTRICT 1 STANDARD TRAFFIC SIGNAL DESIGN DETAILS
61	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS

CHRISTOPHER B. BURKE
9575 West Higgins Road, Suite 600
B Rosenont, Illinois 60018
(947) 823-0500

FILE NAME =

USER NAME = fberiso

PLOT SCALE = 1'
PLOT DATE = 9/5/2014

N:\LCDOT\120226\4 - IL 83\Traffic\INX_STD_sheets-IL83.dgn

DESIGNED - EAJ

CHECKED - GMZ
DATE -

FPB

DRAWN

REVISED

REVISED

REVISED REVISED

HIGHWAY STANDARDS

STD. No.	DESCRIPTION
000001-06	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001006	DECIMAL OF AN INCH AND OF A FOOT
701006-05	OFF-RD OPERATIONS, 2L, 2W, 15' (4.5 m) TO 24" (600 mm) FROM PAVEMENT EDGE
701101-04	OFF-RD OPERATIONS, MULTILANE, 15' (4.5 m) TO 24" (600 mm) FROM PAVEMENT EDGE
701701-09	URBAN LANE CLOSURE, MULTILANE INTERSECTION
701801-05	SIDEWALK, CORNER OR CROSSWALK CLOSURE
701901-03	TRAFFIC CONTROL DEVICES
814001-02	HANDHOLES
857001-01	STANDARD PHASE DESIGNATION DIAGRAMS AND PHASE SEQUENCES

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

INDE)	(OF	SHEETS	HIGHWA	Y STANDARDS,	F
			DETAILS	Note that the second se	0
1" = 20'	SHEET	NO OF	SHEETS STA	TO STA	-

		CONTRACT	NO.	61A74
366	12-00999-25-TL	LAKE	61	2
A.P	SECTION	COUNTY	TOTAL	SHEET NO.

GENERAL NOTES:

GENERAL

- 1) All construction shall be done according to the State of Illinois Standard Specifications for Road and Bridge Construction adopted Jan. 1, 2012; the Supplemental Specifications and Recurring Special Provisions, adopted Jan. 1, 2014; the Standards and Details shown on these plans; and the Special Provisions included in the contract documents.
- 2) The Contractor shall give notices and comply with applicable laws, ordinances, rules, regulations and lawful orders of all public authorities bearing on safety of persons or property or their protection from damage, injury or loss.
- 3) The Contractor shall notify the Engineer, Lake County Division of Transportation (847) 377-7400 and the IDOT Arterial Traffic Control Supervisor (847) 705-4470 a minimum of 72 hours in advance of beginning work. The Contractor shall also notify the other agencies (local) and utilities prior to construction.
- 4) The Contractor shall ensure all permits have been obtained prior to the commencement of work.
- 5) Before acceptance by the County and final payment, all work will be inspected and approved by the Engineer. Final payment will be made after all the Contractor's work has been approved and accepted.
- 6) The Contractor shall at all times provide Traffic Control and Protection. No work shall commence until the Traffic Control requirements are met. This shall be accomplished by the application of traffic control devices as required by the Standard Specifications, contract special provisions and as shown on the plans.
- 7) The contract documents (plan, special provisions, details and standards) are not intended to show every detail and/or all details of the work to be performed and/or the materials and equipment to be supplied. The intent of the contract documents is to illustrate the design and layout. The Contractor shall be knowledgeable and regularly engaged in the type of work described by the contract documents, and shall be responsible for understanding their intent. Any work performed or item of equipment to be supplied which is not specifically called for by the contract document, but which is necessary to provide a complete and successful working system shall be included in the Contractor's scope of work at no additional cost to the County.
- 8) The Contractor shall plan his/her work based on their own explorations and observations to determine soil conditions at the location of the proposed work.
- 9) The Contractor will be required to relocate or remove and replace signs which interfere with construction operations, and to temporarily reset all such signs during construction operations. This work will not be paid for separately, but shall be included in the cost of the contract. All work involving signs shall be governed by the following requirements:
- a) Signs shall not be moved until progress of work necessitates it.
- b) Every sign removed must be re-erected at a temporary location in a workmanlike manner and be visible to traffic for which it is intended. All such signs must be maintained straight and clean for the duration of the temporary setting. c) All signs shall be re-erected in permanent locations as the roadway is completed by LCDOT forces. Horizontal location from the edge of pavement shall be as designated by the engineer.
- d) All unused signs will be returned to the County.
- e) Longer posts may be required at some temporary or permanent sign locations to maintain proper sign elevations.
- 10) The Contractor is prohibited from transporrting soil off of state ROW. All soil must be graded to match existing ground levels.
- 11) Contractor shall maintain sufficient equipment, supplies, and materials on hand to confine, control, and dispose of any leaked drilling fluids due to frac-outs. All drilling operations to be suspended until containment is achieved.

1) It shall be the Contractor's responsibility to remove any and all materials and debris from the site that result from Construction operations, at no additional cost to the County. Removed pavement, sidewalk, curb, curb and gutter, unusable/unsalvageable materials, short term pavement markings, etc..., shall be disposed of outside the right-of-way according to Article 202.03 of the Standard Specifications at locations provided by the Contractor at no additional cost to the County.

DRAINAGE

1) CONSTRUCTION OPERATIONS: During construction operations the Contractor shall ensure positive site drainage at the conclusion of each day. Site drainage may be achieved by ditching, pumping, or any other method acceptable to the Engineer. During construction operations when any loose material is deposited in the flow line of ditches, gutters or drainage structures so the natural flow of water is obstructed, the material shall be removed at the close of each working day. At the conclusion of construction operations all drainage structures shall be free from all dirt and debris. This work will not be paid for separately but shall be considered included in the cost of the project.

MEASUREMENTS

1) Unless otherwise noted, locations shown on the plans are to the edge of pavernent, etc, are measured from the centerline. Flat tops and cones are to be eccentric. Station/offset labels and locations for flared end sections are to the outside end of the end sections.

MISCELLANEOUS

- 1) The Contractor shall provide access to the abutting properties at all times during construction of this project. Any cost incurred by the Contractor to meet this requirement that is not covered by a specific pay item will be included in the cost of the contract.
- 2) The Contractor shall be responsible for returning all existing areas (to remain) affected by construction activities, equipment, or laborers to the original undisturbed conditions. The Contractor shall also be responsible for protecting all new work until the completion of the contract.
- 3) Where new work is proposed to meeting existing features, it shall be the Contractor's responsibility to field check all dimensions and elevations and notify the Engineer of discrepancies before proceeding with construction.
- 4) Where proposed curb and/or curb and gutter meet existing curb and gutter, the proposed curb and gutter shall transition to the existing over a distance of ten feet or as directed by the Engineer. The transition length will be paid for at the contract unit price of the proposed curb and gutter.
- 5) All unballasted Type II barricades shall be installed as specified in the NCHRP 350 Letter for the device.
- 6) The Contractor's attention is called to the fact that some quantities are given in both summary form and on the plan sheets. Care should be taken to avoid duplication of quantities

- 7) All proposed handholes shall be located to limit the intrusion into the existing sidewalk. If this cannot be avoided the handhole shall be placed flush with the existing sidewalk system and the contractor shall replace the entire sidewalk area between joints, in accordance with Section 424 of the Standard Specifications for Road and Bridge Construction. The cost for the removal, excavation, and placement of sidewalk shall be included in the pay item: HANDHOLE or HEAVY DUTY HANDHOLE.
- 8) The Contractor shall repair, to the satisfaction of the Engineer, all damage to existing items not scheduled for removal. This work shall be done by the Contractor at the Contractor's own expense.
- 9) POLLUTION CONTROL: The Contractor shall be required to comply with all state and local regulations regarding air, water and noise pollution. The Contractor will not be allowed to build fires on the site.
- 10) ROW MONUMENTS: Where section and subsection monuments are encountered, the Engineer shall be notified before the monuments are removed. The Contractor shall carefully preserve all property marks and monuments until the owner, authorized surveyor or agent has witnessed or otherwise reference their location. Any right-of-way markers distributed by the Contractor's operations that are not scheduled for removal shall be reestablished by a Registered Land Surveyor at the Contractors expense.

UTILITIES


- 1) The locations of public and/or private utilities shown on the plans are approximate and their accuracy is not guaranteed. The Contractor shall be required to ascertain the exact location of such utilities so as not to damage them according to Article 107.31 of the Standard Specifications. The Contractor shall be responsible for contacting the utility owners so that their facilities may be adjusted or relocated if necessary prior to construction operations.
- 2) The Contractor shall be responsible for any damage or destruction of public or private property according to Article 107.20 of the Standard Specifications. The Contractor shall restore such property at his/her own expense. The Contractor shall use all necessary precautions and protective measures required to maintain existing utilities, sewers and appurtenances that must be kept in operation. In particular the Contractor shall take adequate measures to prevent the undermining of utilities and sewers which are still in service.
- 3) When the plans or special provisions include information pertaining to the location of existing utility facilities, such information only represents the opinion of the Engineer as to the location of such facilities and is only included for the Contractor's convenience. The Engineer and the County assume no responsibility for the sufficiency or accuracy of the information shown in the plan relating to the location of existing facilities or the manner in which they are to be removed or adjusted.
- 4) Coordination of all utility work involved in the construction area will be discussed at the preconstruction meeting. The Contractor is responsible for verifying the nature and status of all utility relocation work prior to the start of construction. The Contractor shall take appropriate measures to ensure that his/her construction activities do not interfere with utility facilities and relocation work. The Contractor's schedule should reflect construction sequencing which coordinates with all utility relocation work. The Contractor shall be required to adjust the sequence schedule of work to coordinate with the relocation schedule of conflicting utility companies.


FILE NAME =	USER NAME = [bariso	DESIGNED - EAJ	REVISED -	
N:\LCDOT\120226\4 - 1L 83\Traffig\GE	N_1U83.dgn	DRAWN - FPB	REVISED -	
	PLOT SCALE = 1'	CHECKED - GMZ	REVISED -	
	PLOT DATE = 9/5/2014	DATE -	REVISED -	

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

	SUMMARY OF QUANTITIES							CMAO EU	RUCTION TYPE CO	20% LOCAL				
CODE NO	ПЕМ		TOTAL	IL ROUTE 83 @	IL ROUTE 83 @	IL ROUTE 83 @	IL ROUTE 83 @	IL ROUTE 83 @ PETITE LAKE RD	THE DOLLETTE OF C	III DOLUME OO O	IL ROUTE 83 @ LAKE ST	IL ROUTE 83 @ ORCHARD ST	IL ROUTE 83 @ NORTH AVE	INTERCONNECT
67100100	MOBILIZATION	L SUM		WILLOTONE DIX	WOTAT VIELE TO	ENOLL BIX	IL NOOTE 132	TETTE LAKE NO	GRAGO LARL	IL ROOTE 173	LAKE 31	OKCHARD 31	NORTHAVE	
	TRAFFIC CONTROL AND PROTECTION, STANDARD 701701	L SUM												
	TRAFFIC CONTROL AND PROTECTION, STANDARD 701801	L SUM												
	UNDERGROUND CONDUIT, GALVANIZED STEEL, 2" DIA.		28,645											28,645
	CONDUIT ATTACHED TO STRUCTURE, 2" DIA., GALVANIZED STEEL	FOOT												
	JUNCTION BOX, STAINLESS STEEL, ATTACHED TO STRUCTURE, 24" X 24" X 10"													466
	HANDHOLE	EACH												2
	HEAVY-DUTY HANDHOLE	EACH												18
	MAINTENANCE OF EXISTING TRAFFIC SIGNAL INSTALLATION			1	1									33
	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1C	EACH		1	1	1	1	1	1	1	1	1	1	00.700
- N	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 TC		32,726	200										32,726
			1,325	303				270	194	213		152	193	
	DRILL EXISTING HANDHOLE	EACH												3
	DRILL EXISTING HEAVY DUTY HANDHOLE	EACH							9				Market State of the State of th	4
	MODIFY EXISTING CONTROLLER CABINET	EACH		1	1	1	1	1	1	1		1	1	
	REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT	EACH		1	1	1				1				
	INTERCEPT EXISTING CONDUIT	EACH	3											3
	FULL-ACTUATED CONTROLLER IN EXISTING CABINET	EACH	1	1										
	ELECTRIC CABLE IN CONDUIT, COAXIAL	FOOT	1,325	303				270	194	213		152	193	
X8730800	ELECTRIC CABLE IN CONDUIT, VIDEO, NO. 20 4 C	FOOT	1,325	303				270	194	213		152	193	·
XX005940	REMOTE CONTROLLED VIDEO SYSTEM	EACH	6	1				1	1	1		1	1	
XX006655	LAYER II (DATALINK) SWITCH	EACH	9	1	1	1		1	1	1	1	1	1	
XX007017	TERMINATE FIBER IN CABINET	EACH	42											
XX007018	LAYER III (NETWORK) SWITCH	EACH	1				1							
XX008246	FIBER OPTIC CABLE IN CONDUIT, 24 SINGLE MODE	FOOT	32,882											32,882
XX008253	VIDEO ENCODER	EACH	8	1	1	1		1	1	1		1	1	
XX008256	UPGRADE EXISTING CONTROLLER TO NTCIP SPECIAL	EACH	8		1	1		1	1	1	1	1	1	
XX008392	OUTDOOR RATED NETWORK CABLE	FOOT	425		163		78		68	63			53	
XX008935	BLUETOOTH DETECTOR	EACH	5		1		1		1	1			1	
Z0010688	CAMERA MOUNTING ASSEMBLY	EACH	4	1					1	1			1	
Z0013798	CONSTRUCTION LAYOUT	L SUM	1											
Z0033056	OPTIMIZE TRAFFIC SIGNAL SYSTEM	EACH	1											1
Z0048665	RAILROAD PROTECTIVE LIABILITY INSURANCE	L SUM	1											1
Z0076600	TRAINEES	HOUR	500											
Z0076604	TRAINEES TRAINING PROGRAM GRADUATE	HOUR	500											
Ø = CO1	NSTRUCTION CODE: 0042 * = SPECIALITY ITEM	MS		The second state of the se										
ME = T\120226\4 - 1L	USER NAME = e_jensen DESIGNED - EAJ REVI	SED -			SI	TATE OF ILLI	NOIS		ÇIII	MMARY OF	OLIANTITIES		IX1E.	SECTION (
	PLOT SCALE = 1' CHECKED - GMZ REVI	SED -					SPORTATION		1" = 20' SHEET N		S STA.	TO STA.		00999-25-TL CO


CHRISTOPHER B. BURKE ENGINEERING LTD. 6978 WEST Higgins Road, Suite 600
ER Reserved, limited 60018
ER7, 823-950018








m ell


FILE NAME =	USER NAME = fbariso	DESIGNED -	EAJ	REVISED -		SCHEDUI	E OF QUAI	ITITIES.	CABLE	PLAN, PHASE	DESIGNATION	F.A.P	SECTION	COUNTY	TOTAL	SHEET
N:\LCOOT\120226\4 - IL 83\Traffio\CA8_M	LSTONE.dgn	DRAWN -	FPB	REVISED -	STATE OF ILLINOIS	DIAGRAM	AND EM	ERGENC	Y VEHIC	LE PREEMPT	TION SEQUENCE	0866	12-0000-25-71	LAVE	SHEETS	NO.
	PLOT SCALE = 20"	CHECKED -	GMZ	REVISED -	DEPARTMENT OF TRANSPORTATION	IL ROUTE 83	MILWAUKE	E AVE.)	AND N	MILLSTONE D	R/HOME DEPOT ENT.	0000	12-00333-23-11	CONTRACT	NO 01	61474
	PLOT DATE = 9/5/2014	DATE -		REVISED -		SCALE: 1" = 20"	SHEET NO.	OF	SHEETS	STA.	TO STA.	FED. ROAD	DIST. NO. ILLINOIS FED.	AID PROJECT	140.	JIAIT



















FILE NAME = US	SER NAME = fberiso	DESIGNED - EAJ	REVISED -		TRAFFIC SIGNAL MODIFICATION PLAN	F.A.P	SECTION	COUNTY	TOTAL SHEET
N:\LC00T\120226\4 - IL 83\Traffic\MOD_GRANG	10_02.dgn	DRAWN - FPB	REVISED -	STATE OF ILLINOIS	IL ROUTE 83 (MILWAUKEE AVE.) AND	RIE.	12-0000-25-71	LAVE	SHEETS NO.
PL	LOT SCALE = 20°	CHECKED - GMZ	REVISED -	DEPARTMENT OF TRANSPORTATION	IL ROUTE 132 (GRAND AVE.) (SHEET 2 OF 2)	0000	12-00333-25-11	CONTRACT	NO. 61A74
PL	LOT DATE = 9/5/2014	DATE -	REVISED -		SCALE: 1" = 20' SHEET NO. OF SHEETS STA. TO STA.	FED. ROAD	D DIST, NO. ILLINOIS FED.	AID PROJECT	NO. DIATA











DEPARTMENT OF TRANSPORTATION

SCALE: 1" = 20' SHEET NO. OF SHEETS STA.

CHECKED

PLOT DATE = 9/5/2014

GMZ

REVISED

REVISED

TS 6970

CONTRACT NO. 61A74

EXISTING SEQUENCE OF OPERATION

MOVEMENT		5—	∮ √ 1			+	— 6 — 1	5 2	<u>→</u>		← 62 →			23	7	3		13	1 8			4	7			⁴ ↑ ↑ 8		F
PHASE		1	+ 5			1	+ 6	2	+ 5		2 + 6	Š			3 +	7		3 -	+ 8			4	+ 7			4 + 1	8	A
INTERVAL	1	2	3	4A	4B	5	6	7	8	9	10A	10B	11	12	13	14	15	16	17A	17B	18	19	20A	20B	21	22A	22B	S
CHANGE TO	/	1+6	2+5	2	+6	/	2+6	/	2+6		35	3+8 4+8		3+8	4+7	4+8 1+5, 1+6 2+5, 2+6		4+8	1.2	1+6 2+6		4+8		1+6		1+5, 2+5,	1+6 2+6	Н
IL. ROUTE 83 (MAIN ST.) N/B NEAR RIGHT AND FAR RIGHT MAST ARM SIGNALS	R	R	R	R	R	R	R	G	G	G	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
IL. ROUTE 83 (MAIN ST.) N/B END MAST ARM AND FAR LEFT SIGNALS	R → G	R → Y	R → G	R Y	R	R	R	G → G	G Y	G	Y	R	R	R	R	R	R	R	R	R	R	R.	R	R	R	R	R	R
IL. ROUTE 83 (MAIN ST.) S/B NEAR RIGHT AND FAR RIGHT MAST ARM SIGNALS	R	R	R	R	R	G	G	R	R	G	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
IL. ROUTE 83 (MAIN ST.) S/B END MAST ARM AND FAR LEFT SIGNALS	R → G	R → G	R Y	R • Y	R	G → G	G Y	R	R	G	Υ	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
GRASS LAKE ROAD E/B NEAR RIGHT AND FAR RIGHT MAST ARM SIGNAL	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	G	Y	R	G	Υ	R	R
GRASS LAKE ROAD E/B END MAST ARM AND FAR LEFT SIGNALS	R	R	R	R	R	R	R	R	R	R	R	R	R → G	R → Y	R → G	R → Y	R	R	R	R	G → G	G • Y	Y	R	G	Υ	R	R
GRASS LAKE ROAD W/B NEART RIGHT AND FAR RIGHT MAST ARM SIGNAL	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	G	Υ	R	R	R	R	R	G	Y	R	R
GRASS LAKE ROAD W/B END MAST ARM AND FAR LEFT SIGNALS	R	R	R	R	R	R	R	R	R	R	R	R	R → G	R → G	R → Y	R → Y	G → G	G Y	Υ	R	R	R	R	R	G	Υ	R	R

PHASES 2 + 6 SHALL BE PLACED ON RECALL

FILE SURVEYED PLOTTED GRADES CHECKED STRUCTURE OF STRUCTU

CHRISTOPHER B. BURKE 9575 West Higgins Road, Suite 800 (847) 823-0500

FILE NAME =	USER NAME = fbariso	DESIGNED - EAJ	REVISED -		SEQUENCE OF OPERATION	F.A.P	SECTION	COUNTY	TOTAL SHE
N:\LCDOT\120226\4 - IL 83\Traffic\5EQ.C	RASSLAKE_Ø1.dgn	DRAWN - FPB	REVISED -	STATE OF ILLINOIS		0866	12-00999-25-TL	LAKE	61 15
	PLOT SCALE = 1'	CHECKED - GMZ	REVISED -	DEPARTMENT OF TRANSPORTATION	IL ROUTE 83 (MAIN STREET) AND GRASS LAKE ROAD	0000	12 00333 23 TL	CONTRACT	T NO. 6147
PL07	PLOT DATE = 9/5/2014	DATE -	REVISED -		SCALE: 1" = 20' SHEET NO. OF SHEETS STA. TO STA.	FED. ROA	AD DIST. NO. ILLINOIS FED.	AID PROJECT	no. om

R

R

R

R

W/B

NEAR RIGHT AND FAR RIGHT MAST ARM SIGNAL

NEART RIGHT AND FAR RIGHT MAST ARM SIGNAL

END MAST ARM AND FAR LEFT SIGNALS

GRASS LAKE ROAD (WEST OF TRACKS)

END MAST ARM AND FAR LEFT SIGNALS

GRASS LAKE ROAD

GRASS LAKE ROAD

R

R

R

R

R

R

R

R

R

R

R

R

R

R

R

R

R

R

R

R R

R

R

B

NLT = "NO LEFT TURN" OR

3

A RAILROAD PREEMPTION SEQUENCE SHALL PROVIDE THE PROPER CLEARANCE INTERVAL TO RESUME THE NORMAL SEQUENCE OF OPERATION OR PROPER CLEARANCE INTERVAL TO DISPLAY AN EMERGENCY VEHICLE INTERVAL (IF APPLICABLE) AFTER RAILROAD PREEMPTION INTERVAL 5 IS TERMINATED.

3 \Diamond R \Diamond R 0 R \Diamond R 0 G \Diamond G \Diamond \Diamond G G \Diamond

CLEAR TO

NORMAL SEQUENCE

CLEAR

TO NORMAL

SEQUENCE

 \triangle

 \triangle

 \triangle

 \triangle

 \triangle

 \triangle

 \triangle

5

G

G

R

R

R

NLT

HOLD

2

G

G

G

G

R

R

R

R

PREEMPTOR PREEMPTOR NUMBER 3 NUMBER 4

1R

1T

R R

R R

R

R R

G

G

NLT NLT

1T

2

R

R

R

G

G

18

1T

1R

R

R

R

R

R

R

G

R

2

3

R

R

R

R

R

G

- G

NLT

21

1V

R

R

R

R

R

1U

1V

R

R

R

R

G

G

4

R

R

R

R

R

R

NLT NLT

21

1X

5

R G

R G

R

R

R

R

R

R

EMERGENCY VEHICLE SEQUENCE SHALL PROVIDE THE PROPER CLEARANCE INTERVAL TO RESUME THE NORMAL SEQUENCE OF OPERATION OR PROPER CLEARANCE INTERVAL TO DISPLAY A DIFFERENT EMERGENCY INTERVAL AFTER EMERGENCY VEHICLE INTERVAL 2 OR 3 IS TERMINATED.

TS 6970

CONTRACT NO. 61A74

COUNTY LAKE

SECTION

FILE NAME =	USER NAME = fbariso	DESIGNED - EAJ	REVISED -		RAILROAD	PREEMPTI	ON SEC	DUENCE	OF OPERA	TION AND
N:\LCDOT\120226\4 - IL 83\Traffic\SEQ_C	ASSLAKE_Ø2.dgn	DRAWN - FPB	REVISED -	STATE OF ILLINOIS	EMER	GENCY VEH	HICLE SE	EQUENC	E OF OPERA	ATION
	PLOT SCALE = 1'	CHECKED - GMZ	REVISED -	DEPARTMENT OF TRANSPORTATION	IL ROUTE	83 (MAIN	STREE	T) AND	GRASS LA	KE ROAD
	PLOT DATE = 9/5/2014	DATE -	REVISED -		SCALE: 1" = 20"	SHEET NO.	OF	SHEETS	STA.	TO STA.

R


R


R G


R

R

R







CHRISTOPHER B. BURKE
S973 West Higgins Road, Suite 800
Research, Illinois 60018
(847) 823-9500

EXISTING SEQUENCE OF OPERATION

MOVEMENT				5_	,	-1				- 6	1 2	-						> 6							3					3 8	↓		4 7					3 ↓ 1	1				F
PHASE				1 +	5				1 +	6		2 +	5				2 -	+ 6							3 +	7				3 +	8		4 +	7				4 -	F 8				L
INTERVAL	1	2A	2B	3A	38	3 4A	4B	5	6A	6B	7	8A	8B	9	10	11A	11B	12A	12B	13A	13B	14	15A	15B	16A	16B	17A	17B	18	19A	19B	20	21A	21B	22	23	24A	24B	25A	25B	26A	26B	A
CHANGE TO			1+6	2	; !+5	2	:+6	/	2	?+6	/	2	2+6	/ ₀	\/\\		+5 3+8 4+8	1-	+6	2	+5		3-	+8	4-	+7	4+	-8	/	4-	+8		4-	+8	0	/ ₀	1+6	+5 2+5 3+7		+8	4-	+7	Н
IL. ROUTE. 83 (MAIN ST.) N/B FAR RIGHT MAST ARM SIGNAL	R	R	R	R	R	R	R	R	R	R	G	G	G	G	G	Υ	R	Υ	R	G	G	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R.	R
IL. ROUTE. 83 (MAIN ST.) N/B END MAST ARM AND FAR LEFT SIGNALS	R → G	R	D	R		R G → Y	R	R	R	R	G → G	G •Y	G	G	G	Υ	R	Υ	R	G	G	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
IL. ROUTE. 83 (MAIN ST.) S/B FAR LEFT MAST ARM SIGNAL	R	R	R	R	R	R	R	G	G	G	R	R	R	G	G	Υ	R	G	G	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
IL. ROUTE, 83 (MAIN ST.) S/B END MAST ARM AND FAR LEFT SIGNALS	R ⊸ G	R		R • Y	R	R	R	G ⊸ G	G → Y	G	R	R	R	G	G	Υ	R	G	G	Υ	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
IL. ROUTE. 173 E/B FAR RIGHT MAST ARM SIGNAL	R	R	R	R	R		R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	G	G	G	G	Y	R	Υ	R	G	G	R
IL. ROUTE. 173 E/B END MAST ARM AND FAR LEFT SIGNALS	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R ⊸ G	R Y	R	R → G	R ⊸ G	R Y	R	R	R	R	G ⊸ G	G ⊸ Y	G	G	G	Y	R	Y	R	G	G	R
IL. ROUTE, 173 W/B FAR RIGHT MAST ARM SIGNAL	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	G	G	R	R	R	G	G	Y	R	G	G	Y	R	R
IL. ROUTE. 173 W/B END MAST ARM AND FAR LEFT SIGNALS	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R ⊸ G	R → G	R → G	R → Y	R	R Y	R	G ∢ G	G ⊸ Y	G	R	R	R	G	G	Y	R	G	G	Y	R	R
IL. ROUTE. 173 W/B FLASHING SIGNALS (EAST AND WEST OF RR TRACKS)	FL Y	FL Y	. FL Y	FL Y	F	L FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	DARK	DARK	DARK	FL Y	FL Y	FL Y	DARK	DARK	FL Y	FL Y	DARK	DARK	FL Y	FL Y	FL Y
PEDESTRIAN SIGNALS CROSSING IL RTE 173 ON WEST SIDE OF IL 83 (MAIN ST.)	Н	Н	Н	Н	Н	Н	Н	*P	•P	*P	Н	Н	Н	*P	**FH	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	H	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	D A
PEDESTRIAN SIGNALS CROSSING IL RTE 83 (MAIN ST.) ON NORTH SIDE OF IL 173	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	•P	*P	*P	Н	Н	Н	*P	**FH	Н	Н	Н	Н	Н	Н	R K

PHASE 2+6 SHALL BE PLACED ON RECALL.

- * TO APPEAR ONLY UPON PUSHBUTTON ACTUATION
- * * FLASHING "IS TO TERMINATE AT THE COMPLETION OF THE PEDESTRIAN INTERVAL CLEARANCE.
- ♦ THIS TO OR FLASHING TIME INTERVAL MAY FINISH TIMING IN THE BIDIRECTIONAL STRAIGHT THROUGH MOVEMENT IF THE LEFT ARROW TIME IS NOT SUFFICIENT TO COMPLETE" OR FLASHING" ("INTERVALS.
- "AND FLASHING" TIMINGS TO BE SET ONLY ON PHASES WHERE
- "AND FLASHING" ARE INDICATED IN THE SEQUENCE OF OPERATION.
- P = ILLUMINATED PERSON = WALK
- FH = ILLUMINATED FLASHING HAND = FLASHING DON'T WALK

H = ILLUMINATED SOLID HAND = DON'T WALK FL = FLASHING YELLOW

FILE NAME =	USER NAME = fberiso	DESIGNED - EAJ	REVISED -		SEQUENCE OF OPERATION	F.A.P	SECTION	COUNTY	TOTAL SHEET
N:\LCD01\120226\4 - IL 83\Troffi	ie\SEQ_IL173_01.dgn	DRAWN - FPB	REVISED -	STATE OF ILLINOIS		RIE.	12-00999-25-TL	1.445	SHEETS NO.
	PLOT SCALE = 1'	CHECKED - GMZ	REVISED -	DEPARTMENT OF TRANSPORTATION	IL ROUTE 83 (MAIN STREET) AND IL ROUTE 173	0000	12-00333-23-1L	CONTRACT	T NO. 61474
	PLOT DATE = 9/5/2014	DATE -	REVISED -		SCALE: 1" = 20' SHEET NO. OF SHEETS STA. TO STA.	FED ROA	DIST NO. THE INOTS FEE	AID PROJECT	NO. OIATH

ENGINEERING LTO. 1"L.A.N SQUEVEED NOTE BOOK ALGOMENT CHECKED NOCADO FILE NAME NOCADO FILE NAME			1 1 1 1 1 1 1 1 1		BY	DATE
E BOOK RIGHENT CHECKED TO OFFICE OF THE OFFICE OFFI	ш	ENGINEERING LTD.	PLAN	03		
OF WAY CHECKED			MOTE BOOK	SWENT CHECKED		ŀ
NO. CADD FILE NAME			WOLE BOOK	RT. OF WAY CHECKED		
			NO.	CADD FILE NAME		

CHRISTOPHER E

BY HECKED 0

NOTE BOOK

EXISTING EMERGENCY VEHICLE PREEMPTION SEQUENCE OF OPERATION

																																		NUMBER 3	NUMBER 4	
CHANGE FROM NORMAL SEQUENCE OF OPERATION INTERVAL NUMBER			1		5			5			7		7	9		9			14		18			18		- 2	20	2	0		22		22			CLEAR TO NORMAL SEQUENCE
EMERGENCY VEHICLE PREEMPTION SEQUENCE OF OPERATION INTERVAL NUMBER		1A	1B	1C	1D	1E	1F	1G	1H	1J	1K	1L	1M	1N	1P	10	1R	15	1T	1U	1V	1W	1X	1Y	1Z	1AA	1BB	1CC	1DD	1EE	1FF	1GG	1HH	2	3	
CHANGE TO EMERGENCY VEHICLE PREEMPTION SEQUENCE OF OPERATION INTERVAL NUMBER		1B	2 0R 3	1D	1E	2	1G	1H	3	1K	2	1M	3	2	10	1R	3	1T	2 0R 3	1V	1W	2	1Y	1Z	3	1BB	2	1DD	3	1FF	1GG	2	3			♦
IL. ROUTE. 83 (MAIN ST.) FAR RIGHT MAST ARM SIGNAL	3	R	R	R	R	R	R	R	R	G	G	Y	R	G	G	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	R	\Diamond
IL. ROUTE. 83 (MAIN ST.) END MAST ARM AND FAR LEFT SIGNALS	9 1	R → Y	R	R	R	R	R	R	R	G → Y	G	Υ	R	G	G	Υ	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	R	◊
IL. ROUTE. 83 (MAIN ST.) S/B FAR LEFT MAST ARM SIGNAL	3	R	R	G	G	G	G	Υ	R	R	R	R	R	G	G	Υ	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	R	♦
IL. ROUTE. 83 (MAIN ST.) S/E END MAST ARM AND FAR LEFT SIGNALS	8	R → Y	R	G • C	G Y	G	G	Υ	R	R	R	R	R	G	G	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	R	\Diamond
IL. ROUTE. 173 E/E FAR RIGHT MAST ARM SIGNAL	3	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	Y	R	G	G	G	Y	R	G	R	G	\Diamond
IL. ROUTE. 173 E/E END MAST ARM AND FAR LEFT SIGNAL	3	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	, R	R	R	R	R	R	R	Y	R	G → Y	G	G	Υ	R	G	R	G	♦
IL. ROUTE. 173 W/E FAR RIGHT MAST ARM SIGNAL	3	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	Y	R	G	G	G	R	R	R	R	G	Y	R	G	R	G	\Diamond
IL. ROUTE. 173 W/E END MAST ARM AND FAR LEFT SIGNALS	3	R	R	R	R.	R	R	R	R	R	R	R	R	R	R	R	R	R	, R	G	Y	R	G G	G T	G	R	R	R	R	G	Υ	R	G	R	G	\Q
IL. ROUTE. 173 W/B FLASHING SIGNALS (EAST AND WEST OF RR TRAC		FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	. FL	FL Y	DAR	KDARI	DAR	FL	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	DARK	FL Y	DARK	\Diamond
PEDESTRIAN SIGNALS CROSSING IL RTE 173 ON WEST SIDE OF IL 83 (MAIN ST.)		Н	Н	FH	Н	Н	FH	Н	Н	Н	Н	Н	Н	FH	FH	Н	Н	н	Н	Н	Н	Н	н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Ĥ
PEDESTRIAN SIGNALS CROSSING	2	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	FH	Н	Н	FH	Н	Н	Н	Н	Н	Н	FH	Н	Н	FH	Н	Н	Н

P = ILLUMINATED PERSON = WALK

FH = ILLUMINATED FLASHING HAND = FLASHING DON'T WALK

H = ILLUMINATED SOLID HAND = DON'T WALK

FL = FLASHING YELLOW


Y


♦ EMERGENCY VEHICLE SEQUENCE SHALL PROVIDE THE PROPER CLEARANCE INTERVAL TO RESUME THE NORMAL SEQUENCE OF OPERATION OR PROPER CLEARANCE INTERVAL TO DISPLAY A DIFFERENT EMERGENCY INTERVAL AFTER EMERGENCY VEHICLE INTERVAL 2 OR 3 IS TERMINATED.


TS 6950


PREEMPTOR PREEMPTOR


FILE NAME =	USER NAME = fbariso	DESIGNED - EAJ	REVISED -		EMERGENCY VEHICLE SEQUENCE OF OPERATION	F.A.P RTE.	SECTION	COUNTY	TOTAL SHEET SHEETS NO.
N:\LCDOT\120226\4 - IL 83\Traffic\SEQ_IL	173_02.dgn	DRAWN - FPB	REVISED -	STATE OF ILLINOIS	IL ROUTE 83 (MAIN STREET) AND IL ROUTE 173	0866	12-00999-25-TL	LAKE	61 24
	PLOT SCALE = 1'	CHECKED - GMZ	REVISED -	DEPARTMENT OF TRANSPORTATION	IL NUUTE 03 (INIAIN STREET) AND IL NUUTE 1/3			CONTRACT	NO. 61A74
	PLOT DATE = 9/5/2014	DATE	REVISED -		SCALE: 1" = 20' SHEET NO. OF SHEETS STA. TO STA.	FED. ROAD	DIST. NO. ILLINOIS FED.	. AID PROJECT	



















CHRISTOPHER B. BURKE
9575 West Higgins Road, Suite 600
Roamond, Illnois 60018
(647) 823-9500





RESTORATION OF WORK AREA, RESTORATION OF THE TRAFFIC SIGNAL WORK AREA SHALL BE INCLUDED IN THE COST FOR THE RELATED PAY ITEM SUCH AS FOUNDATION, CONDUIT, HANDHOLE, TRENCH AND BACKFILL ETC., AND NO EXTRA COMPENSATION SHALL BE ALLOWED. ALL ROADWAY SURFACES SUCH AS SHOULDERS, MEDIANS, SIDEWALKS, PAVEMENT, ETC. SHALL BE REPLACED IN KIND. ALL DAMAGE TO MOWED LAWNS SHALL BE REPLACED WITH AN APPROVED SOD. AND ALL DAMAGE TO UNMOWED FIELDS SHALL BE SEEDED IN ACCORDANCE WITH STANDARD SPECIFICATIONS 252 AND 250 RESPECTIVELY.

FILE NAME =	USER NAME = fbariso	DESIGNED - EAJ	REVISED -	PLANDER TREVENUES - TRAPER A STANDARDE TRAVES	TRAFFIC SIGNAL MODIFICATION PLAN	F.A.P	SECTION	COUNTY	TOTAL SHE
N:\LCDOT\120226\4 - IL 83\Traffig\MOD_N	RTH_02.dgn	DRAWN - FPB	REVISED -	STATE OF ILLINOIS	IL ROUTE 83 (MAIN ST.) AND NORTH AVENUE	0866	12-00999-25-TL	LAKE	61 3/
	PLOT SCALE = 20'	CHECKED - GMZ	REVISED -	DEPARTMENT OF TRANSPORTATION	(SHEET 2 OF 2)	0000		CONTRACT	T NO. 61A
	PLOT DATE = 9/5/2014	DATE -	REVISED -		SCALE: 1" = 20' SHEET NO. OF SHEETS STA. TO STA.	FED. ROA	D DIST. NO. ILLINOIS FED.	AID PROJECT	7,730



CHRISTOPHER B. BURKE ENGINEERING LTD. PLAN C 9575 West Higgins Road, Suite 600 NOTE BOOK NOTE BOOK NOTE BOOK	CHRISTOPHER B. BURKE ENGINEERING LTD. PLAN C 9575 West Higgins Read, Suite 600 NOTE BOOK NOTE BOOK NOTE BOOK	SURVEYED	PLOTTED ALIGNMENT CHECKED RY, OF WAY CHECKED ADD. FILE NAME
CHRISTOPHER B. BURKE ENGINEERING LTD. S575 West Higgins Road, Suite 600 R Rosenom, Illines 80018	CHRISTOPHER B. BURKE ENGINEERING LTD. C 9575 West Higgins Road, Suite 600 E Resembnd, lincus 60018 C 1823-0550	PLAN	NOTE BOOK
CHRIS CHRIS CHRIS ED 9575 West BROSEMONT (847) 823-3	C S 9575 West	KE ENGINEERING	
DATE	3182	TOPHER B. BUR	Higgins Road, Suite 600 Illinois 60018
	A.B.	CHRISTOPHER B. BUR	B Rosemont, Illinois 60018 (847) 823-0500

EXISTING SEQUENCE OF OPERATION

MOVEMENT >> Z		5	_•	—1	+++++	- → 	5 — 2 —	→			6			3	7			+	3 8	,			,	‡ ↓ ↓	•			1	↑ ↑ 1 8		F
PHASE		1	+ 5		1	+ 6	2	+ 5		2 -	+ 6			3 +	- 7			3	3 + 7	§ .				4 + 7				4 +	- 8		L
INTERVAL	1	2	3	4	5	6	7	8	9	10	11A	11B	12	13	14	15	16	17	18A	18B	18C	19	20	21A	21B	210	22	23	24A	24B	A S
CHANGE TO		1+6	2+5	2+6		2+6		2+6			1 2 3 2 6 C	3+8 4+8		3+8	4+7	4+8		4+8	1,255	+5 1+ +5 2+			4+8		.+5 1- ?+5 2-				1+5 2+5	1200000	Н
IL. ROUTE. 83 (MAIN ST.) N/B FAR RIGHT MAST ARM SIGNAL	R	R	R	R	R	R	G	G	G	G	Υ	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
IL. ROUTE. 83 (MAIN ST.) N/B END MAST ARM AND FAR LEFT SIGNALS	R → G	R ⊸ Y	R → G	R → Y	R	R	G ∢ G	G Y	G	G	Υ	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
IL. ROUTE. 83 (MAIN ST.) S/B FAR LEFT MAST ARM SIGNAL	R	R	R	R	G	G	R	R	G	G	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
IL. ROUTE. 83 (MAIN ST.) S/B END MAST ARM AND FAR LEFT SIGNALS	R → G	R ⊸ G	R → Y	R ⊸ Y	G ⊸ G	G → Y	R	R	G	G	Υ	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R
NORTH AVENUE E/B FAR RIGHT MAST ARM SIGNAL	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	G	G	Υ	R	G	G	Υ	R	R
NORTH AVENUE E/B END MAST ARM AND FAR LEFT SIGNALS	R	R	R	R	R	R	R	R	R	R	R	R	R ∢ G	R ▼Y	R ▼ G	R ▼ Y	R	R	R	R	R	G ⊸ G	G Y	G ⊸ G	Υ	R	G	G	Υ	R	R
NORTH AVENUE W/B FAR RIGHT MAST ARM SIGNAL	R	R	R	Ŗ	R	R	R	R	R	R	R	R	R	R	R	R	G	G	G	Υ	R	R	R	R	R	R	G	G	Υ	R .	R
NORTH AVENUE W/B END MAST ARM AND FAR LEFT SIGNALS	R	R	R	R	R	R	R	R	R	R	R	R	R → G	R ▼ G	R ▼ Y	R → Y	G ⊸ G	G Y	G ⊸ G	Υ	R	R	R	R	R	R	G	G	Υ	R	R
NORTH AVENUE W/B FLASHING SIGNALS (EAST & WEST OF RR TRACKS)	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	DARK	DARK	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	DARK	DARK	FL Y	FL Y	FL Y						
IL. ROUTE. 83 (MAIN ST.) FLASHING SIGNALS S/B NORTH AND SOUTH OF RR TRACKS	FL Y	FL Y	FL Y	FL Y	DARK	DARK	FL Y	FL Y	DARK	DARK	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y
PEDESTRIAN SIGNALS CROSSING IL RTE 83 (MAIN ST) ON NORTH SIDE OF NORTH AVE.	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	*P	*P	**FH	Н	Н	Н	Н	Н	Н	Н	*P	**FH	Н	Н	DAR.
PEDESTRIAN SIGNALS CROSSING IL RTE 83 (MAIN ST) ON SOUTH SIDE OF NORTH AVE.	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	*P	*P	**FH	Н	Н	*P	**FH	Н	Н	DAR.
PEDESTRIAN SIGNALS CROSSING NORTH AVENUE ON EAST SIDE OF IL ROUTE 83	Н	Н	Н	Н	Н	Н	*P	*P	*P	**FH	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	DAR,
PEDESTRIAN SIGNALS CROSSING NORTH AVENUE ON WEST SIDE OF IL ROUTE 83	Н	Н	Н	Н	*P	*P	Н	Н	*P	**FH	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	DAR.

* TO APPEAR ONLY UPON PUSHBUTTON ACTUATION

PHASE 2+6 SHALL BE PLACED ON RECALL.

- * * FLASHING " IS TO TERMINATE AT THE COMPLETION OF THE PEDESTRIAN INTERVAL CLEARANCE.
- ⊕ THIS MOOR FLASHING MOON INTERVAL MAY FINISH TIMING IN THE BIDIRECTIONAL STRAIGHT THROUGH MOVEMENT IF THE LEFT ARROW TIME IS NOT SUFFICIENT TO COMPLETE OR FLASHING INTERVALS.
- "AND FLASHING" TIMINGS TO BE SET ONLY ON PHASES WHERE
- "AND FLASHING" ARE INDICATED IN THE SEQUENCE OF OPERATION.
- FH = ILLUMINATED FLASHING HAND = FLASHING DON'T WALK

P = ILLUMINATED PERSON = WALK

H = ILLUMINATED SOLID HAND = DON'T WALK FL = FLASHING YELLOW

FILE NAME =	USER NAME = Fbariso	DESIGNED -	EAJ	REVISED -		SEQUENCE OF OPERATION	F.A.P	SECTION	COUNTY	TOTAL	SHEET
N:\LCDOT\120226\4 - 1L 83\Tra	offic\SEQ_NORTH_01.dgn	DRAWN -	FPB	REVISED -	STATE OF ILLINOIS		0866	12-00999-25-TI	LAKE	SHEE IS	32
	PLOT SCALE = 1'	CHECKED -	GMZ	REVISED -	DEPARTMENT OF TRANSPORTATION	IL ROUTE 83 (MAIN STREET) AND NORTH AVENUE	0000	12 00333 23 TE	CONTRACT	NO 6	51A74
	PLOT DATE = 9/5/2014	DATE -		REVISED -		SCALE: 1" = 20' SHEET NO DE SHEETS STA TO STA	CCD DOA	D DIST NO THE INOTE SEE	AID DON FOT	110.	2101.1

EXISTING EMERGENCY VEHICLE PREEMPTION SEQUENCE OF OPERATION

EXISTING EWERGENCY VEHICLE PREE	VIII III	UIV .	Luu	LINU	. 01	UF	LNA	TION																				PREEMPTOR NUMBER 3	PREEMPTOR NUMBER 4	
CHANGE FROM NORMAL SEQUENCE OF OPERATION INTERVAL NUMBER	1		5		5		7	7		7	9		9		12	1	6	1	6	1	9	1	9		22		22			CLEAR TO NORMAL SEQUENCE
EMERGENCY VEHICLE PREEMPTION SEQUENCE OF OPERATION INTERVAL NUMBER	1A	1B	10	10	18	E	1F	1G	1H	1J	1K	1L	1M	1P	10	1R	1S	1T	1U	1V	1W	1X	1Y	1Z	1AA	1BB	1CC	2	3	
CHANGE TO EMERGENCY VEHICLE PREEMPTION SEQUENCE OF OPERATION INTERVAL NUMBER	2 0R 3	1C	2	1	3	3	1G	2	1J	3	2	1M	1N	3	2 0R 3	15	2	1U	3	1W	2	1Y	3	1AA	1BB	2	3			◊
IL. ROUTE. 83 (MAIN ST.) FAR RIGHT MAST ARM SIGNAL	R	R	R	F	F	?	G	G	G	Y	G	G	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	R	◊
IL. ROUTE. 83 (MAIN ST.) END MAST ARM AND FAR LEFT SIGNALS	R •	R	R	F	F	۲ .	G → G	G → Y	G → G	Υ	G	G	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	R	◊
IL. ROUTE. 83 (MAIN ST.) S/E FAR LEFT MAST ARM SIGNAL	R	G	G	G	١	(R	R	R	R	G	G	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	R	\Q
IL, ROUTE, 83 (MAIN ST.) S/E END MAST ARM AND FAR LEFT SIGNALS	R	G Y	G G	0.00	_ ^	1	R	R	R	R	G	G	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G	R	♦
NORTH AVENUE E/E FAR RIGHT MAST ARM SIGNAL	R	R	R	R	F	?	R	R	R	R	R	R	R	R	R	R	R	R	R	G	Υ	G	G	G	Υ	R	G	R	G	◊
NORTH AVENUE E/E END MAST ARM AND FAR LEFT SIGNALS	R	R	R	F	F	3	R	R	R	R	R	R	R	R	R → Y	R	R	R	R	G → G	Υ	G → G	G → Y	G	Υ	R	G	R	G	◊
NORTH AVENUE W/FAR RIGHT MAST ARM SIGNAL	R	R	R	F	F	3	R	R	R	R	R	R	R	R	R	G	Υ	G	G	R	R	R	R	G	Υ	R	G	R	G	◊
NORTH AVENUE W/END MAST ARM AND FAR LEFT SIGNALS	R	R	R	F	F	3	R	R	R	R	R	R	R	R	R → Y	G G	Υ	G G	G Y	R	R	R	R	G	Υ	R	G	R	G	\Q
NORTH AVENUE W/FLASHING SIGNALS (EAST & WEST OF RR TRACKS)	FL Y	FL Y	FL Y	- F	- F	3937 1	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	DARK	FL Y	DARK	DARK	FL Y	FL Y	FL Y	FL Y	DARK	FL Y	FL Y	DARK	FL Y	DARK	\Q
IL. ROUTE. 83 (MAIN ST.) FLASHING SIGNALS S/NORTH AND SOUTH OF RR TRACKS	FL Y	DAR	KDAF	RKDA	RK F	L	FL Y	FL Y	FL Y	FL Y	DARK	DARK	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	FL Y	DARK	FL Y	◊
PEDESTRIAN SIGNALS CROSSING IL RTE 83 (MAIN ST) ON NORTH SIDE OF NORTH AVE.	Н	Н	Н	F	H	4	Н	Н	Н	Н	Н	Н	Н	Н	Н	FH	Н	FH	Н	Н	Н	Н	Н	FH	Н	Н	FH	Н	Н	◊
PEDESTRIAN SIGNALS CROSSING IL RTE 83 (MAIN ST) ON SOUTH SIDE OF NORTH AVE.	Н	Н	Н	F	F	+	Н	Н	Н	Н	Н	н	Н	Н	Н	Н	Н	Н	Н	FH	Н	FH	Н	FH	Н	Н	FH	Н	Н	◊
PEDESTRIAN SIGNALS CROSSING NORTH AVENUE ON EAST SIDE OF IL ROUTE 83	Н	Н	Н	F	H	4	FH	Н	FH	Н	FH	FH	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	◊
PEDESTRIAN SIGNALS CROSSING NORTH AVENUE ON WEST SIDE OF IL ROUTE 83	Ĥ	FH	Н	F	1 F	1	Н	Н	Н	Н	FH	FH	Н	Н	Н	Н	Н	Н	н	H	Н	Н	Н	Н	Н	Н	Н	Н	Н	◊

P = ILLUMINATED PERSON = WALK


FH = ILLUMINATED FLASHING HAND = FLASHING DON'T WALK


H = ILLUMINATED SOLID HAND = DON'T WALK


FL = FLASHING YELLOW


4710	


FILE NAME = NALCOOT\120226\4 - IL 83\Traffic\SEQ_N	USER NAME = fbariso	DESIGNED - EAJ	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	EMERGENCY VEHICLE SEQUENCE OF OPERATION		SECTION	COUNTY	TOTAL	SHEET
	DRTH_02.dgn	DRAWN - FPB	REVISED -			0866	12-0099-25-TI	LAVE	SHEETS	13 190.
	PLOT SCALE = 1'	CHECKED - GMZ	REVISED -		IL ROUTE 83 (MAIN STREET) AND NORTH AVENUE	0000	12-00999-25-11	CONTRACT	T NO C	NO. 61A74
	PLOT DATE = 9/5/2014	DATE -	REVISED -		SCALE: 1" = 20' SHEET NO. OF SHEETS STA. TO STA.	FED. ROA	D DIST. NO. ILLINOIS FED.	AID PROJECT		IAIA


















CHRISTOPHER B. BURKE S 9575 West Higgins Read. Sulte 600 (647) 823-0500


ILE NAME #	USER NAME = Floreso	DESIGNED - SRD	REVISED -			INTERC	ONNECT PL	AN	F.A.P	SECTION	COUNTY	TOTAL SHE
SYNCOUTY IS BUSINESS A - IL BOXTE OF FRENING IN	83.85.dgn	DRAWN - FPB	REVISED	STATE OF ILLINOIS	IL ROUTE 83 FRO	IL ROUTE 83 FROM MILLSTONE DRIVE TO NORTH AVENUE			NIE.	12_00999_35_TI	LAVE	SHEETS NO
PLOT SCALE PLOT DATE	PLDT SCALE = 58"	CHECKED - GMZ	REVISED	DEPARTMENT OF TRANSPORTATION			0000	12 00933 23 12		T NO. 614		
	PLOT DATE + 9/5/2814	DATE -	REVISED		SCALE: 1" = 50' SHEET NO. OF	(SHE	TS STA.	TO STA.	FED. ROAD	DIST, NO. ILLINOIS	FED. AID PROJECT	1 110. 0161












CHRISTOPHER B. BURKE C 9575 West Higgins Road. Suite 600 E 9777 823-0500



WOLDDTY128228/4 - H. 83%1-affickOvf.H	USER NAME - Chariso	DRAWN - FPB	REVISED -	STATE OF ILLINOIS	INTERCONNECT PLAN IL ROUTE 83 FROM MILLSTONE DRIVE TO NORTH AVENUE	RTE.	SECTION 12-00999-25-TI	LAKE	SHEETS	NO.
	PLUI SCALE = 80	CHECKED - GMZ	REVISED -	DEPARTMENT OF TRANSPORTATION	(SHEET 10 OF 12)	0000	12 00333 23 11	CONTRACT	NO. E	51A7
	PLG1 DATE = 9/5/2014	DATE	REVISED		SCALE: 1" = 50' SHEET NO. OF SHEETS STA. TO STA.	FED. ROAD DIS	IST. NO. ILLINOIS FED.	ATO PROJECT		





FILE NAME NATIONAL

USER NAME = Poeriso
II 83.12.dgn
PLDT SCALE = 52*

DESIGNED

DRAWN

CHECKED

DATE

SRD


GMZ

REVISED REVISED REVISED REVISED

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

INTERCONNECT PLAN
IL ROUTE 83 FROM MILLSTONE DRIVE TO NORTH AVENUE
(SHEET 12 OF 12)

SCALE: 1" = 50' SHEET NO. OF SHEETS STA. TO STA.



PATCH PANEL COLOR CODING

SINGLE MODE FIBER

F	IBER TERMIN	ATIONS COUNT		
	INCLUDED IN COST	OF FIBER OPTIC CABLE	BI	D ITEM
INTERSECTIONS	SPLICES	TERMINATIONS	SPLICES	TERMINATIONS
IL 83 AT NORTH AVENUE (CO. HWY 3)				6
IL 83 AT ORCHARD STREET				12
IL 83 AT LAKE STREET				12
IL 83 AT IL 173		12		6
IL 83 AT GRASS LAKE ROAD	6	12		
IL 83 AT PETITE LAKE ROAD	6	12		
IL 83 AT IL 132		24		
IL 132 AT DEEP LAKE ROAD				
IL 132 AT MUNN ROAD				
IL 132 AT GRANADA BLVD				
IL 132 AT SAND LAKE ROAD				
SAND LAKE ROAD AT BECK ROAD				
SAND LAKE ROAD AT US 45				
IL 83 AT ENGLE DRIVE	6	12		
IL 83 AT MONAVILLE ROAD	6	12		
IL 83 AT MILLSTONE DRIVE	6	6		6
IL 83 AT HOOK DRIVE				
TOTAL	30	90	0	42

BLUE
ORANGE
GREEN
BROWN
SLATE
WHITE
RED
BLACK
YELLOW
VIOLET
ROSE
AQUA

ALL SINGLE MODE PATCH PANEL CONNECTORS ARE TO BE TYPE SC BLUE with BLACK tracer

ORANGE with BLACK tracer

GREEN with BLACK tracer

BROWN with BLACK tracer

SLATE with BLACK tracer

WHITE with BLACK tracer

RED with BLACK tracer

PELLOW with BLACK tracer

YELLOW with BLACK tracer

VIOLET with BLACK tracer

ROSE with BLACK tracer

AQUA with BLACK tracer

ALL MULTIMODE PATCH PANEL CONNECTORS ARE TO BE TYPE ST


SCHEDULE OF QUANTITIES

TERMINATE FIBER IN CABINET

UNIT (

III.	QUANT
Н	42

FILE NAME I	USER NAME = Famouso	DESIGNED - EAJ	REVISED		FIBER TERMINATIONS /SPLICE COUNT	F.A.P	SECTION	COUNTY	TOTAL	SHEET
117651768 U = 1785555710031768	NOE1_IIB3_Fiber form Splide Countage	DRAWN - FPB	REVISED	STATE OF ILLINOIS		0866	12-00999-25-Ti	LAKE	61	47
	PLUT SCALE = 28	CHECKED GMZ	REVISED -	DEPARTMENT OF TRANSPORTATION	AND PATCH PANEL COLOR CODE	0000	12 00000 10 11	CONTRACT	T NO.	61A74
	PLUT DATE = 9/5/2014	DATE -	REVISED		SCALE: 1" = 20" SHEET NO. OF SHEETS STA. TO STA.	FED. ROA	D DIST, NO. ILLINOIS FED.	AID PROJECT	1101	72721



DESIGNED-DG REVISED- 2013.11.27

DRAWN-YM REVISEDCHECKED-DG REVISEDDATE 08/16/11

REVISEDDATE 08/16/11

REVISEDLAKE COUNTY
DIVISION OF TRANSPORTATION

LAKE COUNTY
DIVISION OF TRANSPORTATION


LAKE COUNTY
TRANSPORTATION


LAKE COUNTY
TRANSPORTATION

SHEET SHEETS

18.83 FROM MILLSTONE TO NORTH

L83 | 12-0049925-7L | CONTRACT NO. 6/1474






NOTES:


- 1. PIPE SUPPORT (HOT DIPPED GALVANIZED AFTER FABRICATION). MINIMUM SIZE EQUAL TO PIPE DIAMETER, MOUNT TO CHANNEL WITH TWO 3/8" STAINLESS STEEL CLAMPING NUTS, HEX HEAD CAP SCREW & LOCK WASHER, MOUNTED ON 5 FOOT CENTERS.
- 2. UNISTRUT P2000 STEEL CHANNEL (HOT DIPPED GALVANIZED AFTER FABRICATION), 10" LONG MOUNTED EXTERNALLY ON BRIDGE PARAPET. INSTALL ON 5'-0" CENTERS. ATTACH TO BRIDGE PARAPET WITH 1/2" DIA. EXPANSION ANCHORS, MIN. 2" LONG. EXPANSION ANCHOR SHALL BE HOT DIPPED GALVANIZED AFTER FABRICATION AND SHALL BE MADE BY PARABOLT, KWICK-BOLT OR
- 3. THE END 4'-0" SECTION OF WINGWALL/PARAPET SHALL BE KEPT FREE FROM ANY ATTACHMENTS TO AVOID CONFLICT FROM TRAFFIC BARRIER TERMINAL TYPE T6 ANCHORAGE ASSEMBLY.

SECTION

12-00999-25-TL

CONTRACT NO. 61A74






TRAFFIC SIGNAL LEGEND

				1								
<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED	ITEM		REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	R	\bowtie		EMERGENCY VEH	ICLE LIGHT DETECTOR	R	≪	₩	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE			
RAILROAD CONTROL CABINET			> ∢	CONFIRMATION	BEACON	R _{o-Q}	0-()	н	NO. 14 17 C, DICESS NOTED OTHERWISE			
COMMUNICATIONS CABINET	CC	ECC	[CC]	HANDHOLE		R			COAXIAL CABLE		—©—	<u> </u>
MASTER CONTROLLER		EMC	MC	MANDIOLL					WENDON OAR 5 FOR OAN 504		d	
MASTER MASTER CONTROLLER	R	[EMMC]	MMC	HEAVY DUTY HA	NDHOLE	RH	H	H	VENDOR CABLE FOR CAMERA		— <u>Ø</u> —	- ♥-
UNINTERRUPTABLE POWER SUPPLY	UPS	EUPS	UPS	DOUBLE HANDHO	LE	R 🔯			COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED		<u>–</u> ©–	<u>—6</u> —
SERVICE INSTALLATION, (P) POLE OR (G) GROUND MOUNT	-□ ^R	-D-P	- m -	JUNCTION BOX UNDERGROUND C	ONDUIT,		0	•	FIBER OPTIC CABLE NO. 62.5/125, MM12F		- <u>F</u>	
TELEPHONE CONNECTION (P) POLE OR (G) GROUND MOUNT	R	P	P	GALVANIZED ST	EEL (UC)				FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		-245	
STEEL MAST ARM ASSEMBLY AND POLE	R _O	0	•	AND CABLE	TATTON TO THE TATTON	11.		·	NO. BELLY IZS, MMIET SMIET		Ž	
ALUMINUM MAST ARM ASSEMBLY AND POLE	R Q	0	•	COMMON TRENCH				СТ	FIBER OPTIC CABLE NO. 62.5/125, MM12F SM24F		—36F)—	—36F)—
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE	^R O-¤——	0-pt	• × ·	2004/2004/2015 SE-2013	ETALLIC CONDUIT (EMPTY)			CNC				
STEEL COMBINATION MAST ARM	R	0		SYSTEM ITEM			S	S	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM,		C _{III} —•	c _l l →
ASSEMBLY AND POLE WITH PTZ CAMERA	門到	配		INTERSECTION I	TEM		I	IP	OR (S) SERVICE	DOE		
SIGNAL POST	RO	0	•	REMOVE ITEM RELOCATE ITEM		R RL			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
TEMPORARY WOOD POLE (CLASS 5 OR BETTER) 45 FOOT (13.7m) MINIMUM	R⊗	\otimes	•	ABANDON ITEM		A			STEEL MAST ARM POLE AND	RMF		
GUY WIRE	>R	>	>		AFFIC SIGNAL SECTION		R	R	FOUNDATION TO BE REMOVED	0		
SIGNAL HEAD	R ~	\rightarrow	-						ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
SIGNAL HEAD CONSTRUCTION STAGES (NUMBERS INDICATE THE CONSTRUCTION STAGE)			→ ²		D WITH 8" (200mm) EEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF O-X		
SIGNAL HEAD WITH BACKPLATE	+DR	+	+-				R	R	FOUNDATION TO BE REMOVED	O A		
SIGNAL HEAD OPTICALLY PROGRAMMED	Rp	— ▷ b	- > "P"	SIGNAL FACE				G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RPF		
FLASHER INSTALLATION (S DENOTES SOLAR POWER)	O-D"F"	O-D"F"	•>"F"				• 0	∢Y ∢G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR			IS
PEDESTRIAN SIGNAL HEAD	R	-0	-1				R	R	SAMPLING (SYSTEM) DETECTOR		[5]	S
PEDESTRIAN PUSHBUTTON DETECTOR	R (iii)		•	SIGNAL FACE W	ITH BACKPLATE. PROGRAMMED HEAD			Y	QUEUE DETECTOR		[0]	
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTO	R @ APS	@APS	@ APS	"RB" INDICATES	REFLECTIVE BACKPLATE		• 6	4 Y 4 G			tot	
ILLUMINATED SIGN "NO LEFT TURN"	R	8	9	12" (300mm) PF	DESTRIAN SIGNAL HEAD		"P"	"P"	PREFORMED QUEUE DETECTOR PREFORMED INTERSECTION AND SAMPLING		Paj	PO
ILLUMINATED SIGN	R	100		WALK/DON'T WA			W		(SYSTEM) DETECTOR		PIS	PIS
"NO RIGHT TURN"		8			DESTRIAN SIGNAL HEAD SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		PS	PS
DETECTOR LOOP, TYPE 1				Cartestalante (del constitue de co				(A)				
PREFORMED DETECTOR LOOP		PI	P	INTERNATIONAL	DESTRIAN SIGNAL HEAD SYMBOL, SOLID		K	*	RAILROAD	SYMB(OLS	
MICROWAVE VEHICLE SENSOR	RMD	M	M		NAL HEAD, INTERNATIONAL COUNTDOWN TIMER		C C	C * D			EXISTING	PROPOSED
VIDEO DETECTION CAMERA	RVI	[VÞ	₩	RADIO INTERCON	NECT	##*O	-1111-0		RAILROAD CONTROL CABINET			▶ • €
VIDEO DETECTION ZONE						**			RAILROAD CANTILEVER MAST ARM		XOX X	XeX X X
DAN THE TOOL OF THE	R			RADIO REPEATER		RERR	ERR	RR	FLASHING SIGNAL	,	XoX	X-X
PAN, TILT, ZOOM CAMERA	PIZ)	PIZD		CABLE NO. 14, I	R OF CONDUCTORS, ELECTRIC JNLESS NOTED OTHERWISE, LOOP CABLE TO BE SHIELDED		<u>—</u> 5	-(5)-	CROSSING GATE		X0X>	X-X-
WIRELESS DETECTOR SENSOR	RW	W	W	GROUND CABLE			~	~	CROSSBUCK		X	*
WIRELESS ACCESS POINT				NO. 6 SOLID CO				(1)				-
LE NAME = USER NAME = footomj \pw.work\pwidot\footomj\d0108315\tx85.6gr		SIGNED - DAG/BCK AWN - BCK	REVISED -	DAG 1-1-14	STATE	OF ILLINOIS	2		DISTRICT ONE	F.A.P. RTE.	SECTION	COUNTY TOTAL SHE
PLOT SCALE = 50.0000		ECKED - DAD	REVISED -		DEPARTMENT				STANDARD TRAFFIC SIGNAL DESIGN DETAILS	0866	12-00999-25-TL TS-05	CONTRACT NO. 61A7


LOOP DETECTOR NOTES

- 1. EACH PAIR OF LOOP WIRES SHALL BE PLACED IN A SEPARATE EMPTY COILABLE NONMETALLIC CONDUIT FROM THE EDGE OF PAVEMENT TO THE HANDHOLE. SPACING BETWEEN THE HOLES DRILLED IN THE PAVEMENT SHALL NOT BE LESS THAN 6" (150 mm). EMPTY COILABLE NONMETALLIC CONDUIT SHALL BE INCLUDED IN THE COST OF THE LOOP WIRE.
- 2. THE NUMBER OF LOOP TURNS SHALL BE AS RECOMMENDED BY THE AMPLIFIER MANUFACTURER. ALL ADJACENT SIDES OF THE LOOPS SHALL BE INSTALLED IN SUCH A WAY THAT THE CURRENT FLOW IS IN THE SAME DIRECTION TO REINFORCE ITS MAGNETIC FIELDS FOR SMALL VEHICLE DETECTION.
- 3. EACH LOOP LEAD-IN SHALL BE IDENTIFIED AND PERMANENTLY TAGGED IN THE HANDHOLE. EACH LEAD-IN CABLE TAG SHALL INDICATE THE LOCATION OF THE LOOP, LOOP ROTATION (CLOCKWISE/COUNTERCLOCKWISE), LOOP LEAD-IN DIRECTION (IN OR OUT), LOOP CABLE NUMBER AND LOCATION IN CABINET, AND NUMBER OF TURNS IN THE DETECTOR LOOPS IN WATER PROOF INK AS INDICATED ON THE DISTRICT 1 STANDARD TRAFFIC SIGNAL DESIGN DETAIL. THE CONTRACTOR SHALL MARK LOOP LOCATIONS ON RECORD DRAWINGS AND PRESENT TO THE ENGINEER AFTER FINAL INSPECTION. LOOPS SHALL BE MARKED BY LANE AND LOOP NUMBER. SEE DETAIL BELOW.
- 4. ALL LOOP CABLE SHALL BE FASTENED WITH PLASTIC TIE WRAP TO THE HANDHOLE HOOKS.
- 5. IN ASPHALT PAVEMENT, LOOPS SHOULD BE PLACED IN THE BINDER AND DIVEHOLES MARKED AT THE CURB WITH A SAW-CUT. THE SAW-CUT SHALL BE CUT IN ACCORDANCE WITH LOCAL AND E.P.A. DUST CONTROL REQUIREMENTS. DETECTOR LOOP(S) SHALL NOT BE INSTALLED IN WET CONDITIONS AND THE SAW-CUTS MUST BE FREE OF DEBRIS AND RESIDUE SUCH AS DUST AND WATER WHICH IS TO BE ACHIEVED BY THE USE OF COMPRESSED AIR, WIRE BRUSHING AND HEAT DRYING ACCORDING TO SEALANT MANUFACTURER REQUIREMENTS. THE DETECTOR WIRE SHALL BE HELD IN PLACE BY THE USE OF FORM WEDGES. WEDGES SHALL BE SPACED NO MORE THAN 18" (450 mm) APART.
- 6. LOOP SPLICES SHALL BE SOLDERED USING A SOLDERING IRON. BLOW TORCHES OR OTHER DEVICES WHICH OXIDIZE COPPER CABLE SHALL NOT BE ALLOWED FOR SOLDERING OPERATIONS. SEE DETAIL BELOW RIGHT.
- 7. PREFORMED DETECTOR LOOPS SHALL BE USED, AS SHOWN ON THE PLANS, WHERE NEW CONCRETE PAVEMENT IS PROPOSED. THE INSTALLATION OF PREFORMED LOOPS SHALL BE IN ACCORDANCE WITH THE DISTRICT 1 SPECIFICATIONS OR AS DIRECTED BY THE ENGINEER.

LOOP LEAD-IN CABLE TAG





- A. LANE 1 IS THE LANE CLOSEST TO THE CENTERLINE OF THE ROADWAY
- B. LOOP "1 IS THE LOOP IN THE LANE CLOSEST TO THE INTERSECTION.
- C. LABEL LOOP CABLE "IN" OR LOOP CABLE "OUT".
- D. LABEL LOOP CABLE CLOCKWISE OR LOOP CABLE COUNTERCLOCKWISE.



DETECTOR LOOP WIRING SCHEMATIC

- . LOOPS SHALL BE SPLICED IN SERIES.
- " SAW-CUTS SHALL BE A MINIMUM WIDTH OF 5/16" (8 mm).
- SAW-CUT DEPTHS SHALL BE 3" (75 mm). IF IN CONCRETE, THE SAW-CUT DEPTH SHALL BE TO THE TOP OF THE REINFORCEMENT.
- " LOOP CORNERS SHALL BE DRILLED WITH A 2" (50 mm) DIAMETER CORE.





LOOP DETECTOR SPLICE

- 1 WESTERN UNION SPLICE SOLDERED WITH ROSIN CORE FLUX. ALL EXPOSED SURFACES OF THE SOLDER SHALL BE SMOOTH. THE WESTERN UNION SPLICES SHALL BE STAGGERED.
- 2) WCSMW 30/100 HEAT SHRINK TUBE, MINIMUM LENGTH 3" (75 mm), UNDERWATER GRADE.
- 3 WCS 200/750 HEAT SHRINK TUBE, MINIMUM LENGHT 6" (150 mm), UNDERWATER GRADE.

SCALE: NONE

(4) NO. 14 2/C TWISTED, SHIELDED CABLE.


- 5 LOOP CONDUCTOR WITH FLEXIBLE PLASTIC TUBE.
- 6 PRE-FORMED LOOP
- 7 XL POLYOLEFIN 2 CONDUCTOR BREAKOUT SEALS. TYCO CBR-2 OR APPROVED EQUAL

FILE NAME =	USER NAME = Footemj	DESIGNED	-	DAD	REVISED - DAG 1-1-14
c:\p*.work\pwidot\footemj\d0108315\ts05.	ign I	DRAWN		BCK	REVISED -
S	PLOT SCALE = 50.8000 '/ in.	CHECKED		DAD	REVISED -
	PLOT DATE = 1/13/2014	DATE	-	10-28-09	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


DISTRICT ONE	F.A.P.	SECTION	COUNTY	TOTAL	SHEE NO.
STANDARD TRAFFIC SIGNAL DESIGN DETAILS		12-00999-25-TL	LAKE	61	55
STANDARD TRAFFIC SIGNAL DESIGN DETAILS		TS-05	CONTRACT	NO.	61A74
SHEET NO 2 OF 7 SHEETS STA TO STA	Tree me	o nick tip t by those fro	ALD DOG TOT		-

TRAFFIC SIGNAL MAST ARM AND SIGNAL POST MAST ARM MOUNTED SIGNALS IN EXISTING, PROPOSED OR FUTURE SIDEWALKBICYCLE PATH AREA. INTERSECTION SHOWN WITH PEDESTRIAN SIGNALS AND PEDESTRIAN PUSHBUTTON DETECTORS.




- 2. REFER TO THE TRAFFIC SIGNAL EQUIPMENT OFFSET TABLE.
- PROVIDE A LEVEL ALL-WEATHER SURFACE (CONCRETE SIDEWALK, ASPHALT BICYCLE PATH SURFACE OR MATCHING MATERIAL TO THE ADJACENT SURFACE) UP TO THE MAST ARM SHAFT OR THE SIGNAL POST.
- THE FACE OF THE PEDESTRIAN PUSHBUTTON SHALL BE PARALLEL TO THE CROSSWALK TO BE USED.
- 5. THE LOCATIONS AND INSTALLATION OF PEDESTRIAN SIGNAL HEADS AND PEDESTRIAN PUSHBUTTONS SHALL MEET THE REQUIREMENTS OF THE MUTCD AND INFORMATION FOUND IN THE "AMERICANS WITH DISABILITIES ACT ACCESSIBILITY GUIDELINES FOR BUILDINGS AND FACILITIES."

PEDESTRIAN SIGNAL POST AND PEDESTRIAN PUSH BUTTON POST



NOTES:

- 1. REFER TO THE TRAFFIC SIGNAL EQUIPMENT OFFSET TABLE.
- PROVIDE A LEVEL ALL-WEATHER SURFACE (CONCRETE SIDEWALK, ASPHALT BICYCLE PATH SURFACE OR MATCHING MATERIAL TO THE ADJACENT SURFACE) UP TO THE PEDESTRIAN SIGNAL POST OR THE PEDESTRIAN PUSH BUTTON POST.
- THE FACE OF THE PEDESTRIAN PUSHBUTTON SHALL BE PARALLEL TO THE CROSSWALK TO BE USED.
- 4. THE LOCATIONS AND INSTALLATION OF PEDESTRIAN SIGNAL HEADS AND PEDESTRIAN PUSHBUTTONS SHALL MEET THE REQUIREMENTS OF THE MUTCD AND INFORMATION FOUND IN THE "AMERICANS WITH DISABILITIES ACT ACCESSIBILITY GUIDELINES FOR BUILDINGS AND FACILITIES."



- * WHERE THERE ARE CONSTRAINTS THAT MAKE IT IMPRACTICAL TO PLACE THE PEDESTRIAN PUSHBUTTON BETWEEN 1.5 FT (0.45 m) AND 6 FT (1.8 m) FROM THE EDGE OF THE CURB, SHOULDER, OR PAVEMENT, IT SHOULD NOT BE FURTHER THAN 10 FT (3 m) FROM THE EDGE OF CURB, SHOULDER, OR PAVEMENT.
- ** WHERE THERE ARE CONSTRAINTS ON A PARTICULAR CORNER THAT MAKE IT IMPRACTICAL TO PROVIDE THE 10 FT (3 m) SEPERATION BETWEEN THE TWO PEDESTRIAN PUSHBUTTONS, THE PUSHBUTTONS MAY BE PLACED CLOSER TOGETHER OR ON THE SAME POLE.

NOTES:

- PEDESTRIAN SIGNAL HEADS SHALL BE MOUNTED WITH THE BOTTOM OF THE SIGNAL HOUSING INCLUDING BRACKETS NOT LESS THAN 8 FT (2.4 m) OR MORE THAN 10 FT (3 m) ABOVE SIDEWALK LEVEL, AND SHALL BE POSITIONED AND ADJUSTED TO PROVIDE MAXIMUM VISIBILITY AT THE BEGINNING OF THE CONTROLLED CROSSWALK.
- 2. THE BOTTOM OF THE SIGNAL HOUSING (INCLUDING BRACKETS) OF A VEHICULAR SIGNAL FACE THAT IS NOT LOCATED OVER A HIGHWAY SHALL BE AT LEAST 8 FT (2.4 m) BUT NOT MORE THAN 19 FT (5.8 m) ABOVE THE SIDEWALK OR, IF THERE IS NO SIDEWALK, ABOVE THE PAVEMENT GRADE AT THE CENTER OF THE ROADWAY
- 3. THE BOTTOM OF THE SIGNAL HOUSING AND ANY RELATED ATTACHMENTS TO A SIGNAL FACE LOCATED OVER ANY PORTION OF A HIGHWAY SHALL BE ACCORDING TO CURRENT STATE STANDARDS 877001, 877002, 877006, 877011 AND 877012 WITH A MINIMUM OF 16 FT (5.0 m) AND A MAXIMUM OF 18 FT. (5.5 m) FROM THE HIGHEST POINT OF PAVEMENT.
- 4. THE BOTTOM OF THE TEMPORARY SPAN WIRE MOUNTED SIGNAL HOUSING AND ANY RELATED ATTACHMENTS TO A SIGNAL FACE LOCATED OVER ANY PORTION OF A HIGHWAY SHALL BE ACCORDING TO CURRENT STATE STANDARD 880001 WITH A MINIMUM OF 17 FT (5.18 m) FROM THE HIGHEST POINT OF PAVEMENT.
- THE TOP OF THE SIGNAL HOUSING OF A SIGNAL FACE LOCATED OVER ANY PORTION OF A HIGHWAY SHALL NOT BE MORE THAN 25.6 FT (7.8 m) ABOVE THE PAVEMENT.

TRAFFIC SIGNAL EQUIPMENT OFFSET

	THAT TO STONAL EGOTI MENT	0.1321					
TRAFFIC SIGNAL EQUIPMENT	COMBINATION CONCRETE CURB AND GUTTER (MINIMUM DISTANCE FROM BACK OF CURB TO CENTERLINE OF FOUNDATION)	SHOULDER/NON-CURBED AREA (MINIMUM DISTANCE FROM EDGE OF PAVEMENT TO CENTERLINE OF FOUNDATION)					
TRAFFIC SIGNAL MAST ARM POLE	6 FT (1.8m)	SHOULDER WIDTH + 2 FT (0.6m), MINIMUM 10 FT (3.0m)					
TRAFFIC SIGNAL POST	4 FT (1,2m)	SHOULDER WIDTH + 2 FT (0.6m), MINIMUM 10 FT (3.0m)					
PEDESTRIAN SIGNAL POST	4 FT (1.2m)	SHOULDER WIDTH + 2 FT (0.6m), MINIMUM 10 FT (3.0m)					
PEDESTRIAN PUSHBUTTON POST	4 FT (1.2m)	SHOULDER WIDTH + 2 FT (0.6m), MINIMUM 10 FT (3.0m)					
TEMPORARY WOOD POLE	6 FT (1.8m)	SHOULDER WIDTH + 2 FT (0.6m), MINIMUM 10 FT (3.0m)					
CONTROLLER CABINET	6 FT (1.8m) MINIMUM DISTANCE SEE NOTE 2	SHOULDER WIDTH + 6 FT (1.8m), MINIMUM 16 FT (4.9m) SEE NOTE 3.					
SERVICE INSTALLATION, GROUND MOUNT	6 FT (1.8m) MINIMUM DISTANCE SEE NOTE 2	SHOULDER WIDTH + 6 FT (1.8m), MINIMUM 16 FT (4.9m) SEE NOTE 3.					

NOTES:


- 1. CONTACT THE "AREA TRAFFIC SIGNAL MAINTENANCE AND OPERATIONS ENGINEER" FOR ASSISTANCE IN LOCATING THE TRAFFIC SIGNAL EQUIPMENT WHEN THERE ARE CONFLICTS WITH DITCHES OR THE MINIMUM OFFSET DISTANCES CANNOT BE MET.
- 2. MINIMUM DISTANCE FROM THE BACK OF CURB TO THE ROADWAY SIDE OF THE FOUNDATION.
- 3. MINIMUM DISTANCE FROM THE EDGE OF PAVEMENT TOTHE ROADWAY SIDE OF THE FOUNDATION.
- 4. ANY CHANGES TO THE OFFSETS OF THE FOUNDATIONS, FROM THE MINIMUM DISTANCES LISTED IN THE "TRAFFIC SIGNAL EQUIPMENT OFFSET" CHART AND THE TRAFFIC SIGNAL INSTALLATION PLAN, COULD EFFECT THE PLACEMENT OF THE SIGNAL HEADS, PEDESTRIAN SIGNAL HEADS AND THE PEDESTRIAN PUSHBUTTONS. THE SIGNAL HEAD PLACEMENT ON THE MAST ARMS SHALL REMAIN AS PER THE TRAFFIC SIGNAL INSTALLATION PLAN AND THE "TRAFFIC SIGNAL MAST ARM AND SIGNAL POST" DETAIL ABOVE. THE PROPOSED MAST ARM LENGTHS MAY NEED TO BE REVISED TO MEET THE ABOVE REQUIREMENTS. THE PEDESTRIAN SIGNAL HEADS AND PEDESTRIAN PUSHBUTTONS MUST MEET THE REQUIREMENTS UNDER THE DETAILS ON THIS SHEET.


SCALE: NON


FILE NAME :	USER NAME = footem_j	DESIGNED	-	DAD	REVISED - DAG 1-1-14	
o:\pw.work\pwidot\footemj\d0108315\ts05.	ign	DRAWN -	>-	BCK	REVISED -	S
	PLOT SCALE = 50.0000 '/ in.	CHECKED -	-	DAD	REVISED -	DEPARTM
	PLOT DATE = 1/13/2014	DATE	-	10-28-09	REVISED -	

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

	0	ISTRICT O	NE		F.A.P.	SECTION	COUNTY	TOTAL	SHEET NO.	
	STANDARD TRAF	EIC PICNA	DECICAL DET	AHC	0866	12-00999-25-TL	LAKE	61	56	
	STANDARD TRAFFIC SIGNAL DESIGN DETAILS					TS-05		CONTRACT NO. 6		
NE	SHEET NO. 3 OF 7	SHEETS	STA.	TO STA.	FED. ROA	D DIST. NO. 1 ILLINOIS FED.	AID PROJECT			







	(1621)1111
SEE NOTE 5-	49" (SEE NOTE 3) (1245mm)
	44" 16"
2"(5)Imi	(406mm)
1	
2 2	(64mm)
12.56. 7.00.00	(64mm) - 100 to
31," (787mm) 5650mm)	(125mm)
, · · ×	
, E	2" × 6"
2" (SImm)	(51mm x 152mm) WOOD FRAMING (TYP.)
100	7
	T
TRAFFIC SIGNAL	
CONTROLLER CABINET	
	l ⊔PS
	CABINET
3/4" (19mm) TREATED	
PHYWOOD DECK	
	
2" x 6" (51mm x 152mm) TREATED WOOD	• •
TARATED WOOD	<u> </u>
NIN	
.22" MIN (305mm)	
20	137 DX7 157
= = I	× 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
48" MIN 0219mm	
- 118 8 ×	
4 0	i'i !'!
-1-17-	1 1-4
6" x 6" (152mm x 152mm) TREATED WOOD POSTS	L_J
NOTES:	
. BASED ON CONTROLLER CABINET TYPE IV WITH E	BASE DIMENSIONS OF 26" x 44" (660mm x 1118mm). IMENSIONS BEING SUPPLIED
ADJUST PLATFORM SIZE TO FIT CABINET BASE OF	(NET WITH BASE DIMENSIONS OF 16" x 25" (406mm x 635mm), INMENSIONS BEING SUPPLIED.
DI ATEORN SIZE FOR CONTROLLER CARINET TYPE	tv

- 3. PLATFORM SIZE FOR CONTROLLER CABINET TYPE IV.
- 4. PLATFORM SIZE FOR CONTROLLER CABINET TYPE IV AND UNINTERRUPTIBLE POWER SUPPLY CABINET.
- 5. DRILLED HOLES THROUGH THE PLATFORM BASE TO MATCH THE CONTROLLER CABINET BOLT TEMPLATE, FASTEN THE CONTROLLER CABINET TO THE PLATFORM WITH CARRIAGE BOLTS, WASHERS AND NUTS.
- 6. FASTEN ALL SUPPORT WOOD FRAMING TO THE WOOD POSTS WITH 2 LAG SCREWS FOR EACH CONNECTION.

TEMPORARY SIGNAL CONTROLLER WOOD SUPPORT PLATFORM

CABLE SLACK LENGTH	FEET	METER
HANDHOLE	6.5	2.0
DOUBLE HANDHOLE	13.0	4.0
SIGNAL POST	2.0	0,6
MAST ARM	2.0	0.6
CONTROLLER CABINET	1.5	0.5
FIBER OPTIC AT CABINET	13.0	4.0
ELECTRIC SERVICE AT (CABINET OR SERVICE LOCATION)	1.5	0.5
GROUND CABLE (SIGNAL POST, MAST ARM, CABINET)	1.5	0.5
GROUND CABLE (BETWEEN FRAME AND COVER)	5.0	1.6

CABLE SLACK

VERTICAL CABLE LENGTH		
MAST ARM POLE (MAST ARM MOUNTED SIGNAL HEAD) (L = MAST ARM LENGTH - DISTANCE TO SIGNAL HEAD FROM END OF ARM)	20.0+L	6.0+L
BRACKET MOUNTED (MAST ARM POLE OR SIGNAL POLE)	13.0	4.0
PEDESTRIAN PUSH BUTTON	6.0	2,0
SERVICE INSTALLATION POLE MOUNT TO SERVICE DROP	13.5	4.1
SERVICE INSTALLATION POLE MOUNT TO GROUND	13.5	4.1
SERVICE INSTALLATION GROUND MOUNT	6.0	2.0
FOUNDATION (SIGNAL POST, MAST ARM POLE, CONTROLLER CABINET, SERVICE-GROUND MOUNT)	3.0	1.0

WEDT	TOAL	CADIE	LENGTH
VERI	ILAL	LADLE	I P INT I P

FOUNDATION	DEPTH
TYPE A - Signal Post	4'-0" (1,2m)
TYPE C - CONTROLLER W/ UPS	4'-0" (1.2m)
TYPE D - CONTROLLER	4'-0" (1.2m)
SERVICE INSTALLATION, GROUND MOUNT, TYPE A - SQUARE	4'-0" (1.2m)


DEPTH OF FOUNDATION

Mast Arm Length	① Foundation Depth	Foundation Diameter	Spiral Diameter	Quantity of Rebars	Size of Rebars
Less than 30' (9.1 m)	10'-0" (3.0 m)	30" (750mm)	24" (600mm)	8	6(19)
Greater than or equal to	13'-6" (4.1 m)	30" (750mm)	24" (600mm)	8	6(19)
30' (9.1 m) and less than 40' (12.2 m)	11'-0" (3.4 m)	36" (900mm)	30" (750mm)	12	7(22)
Greater than or equal to 40' (12.2 m) and less than 50' (15.2 m)	13'-0" (4.0 m)	36" (900mm)	30" (750mm)	12	7(22)
Greater than or equal to 50' (15.2 m) and up to 55' (16.8 m)	15'-0" (4.6 m)	36" (900mm)	30" (750mm)	12	7(22)
Greater than or equal to 56' (16.8 m) and less than 65' (19.8 m)	21'-0" (6.4 m)	42" (1060mm)	36" (900mm)	16	8(25)
Greater than or equal to 65' (19.8 m) and up to 75' (22.9 m)	25'-0" (7.6 m)	42" (1060mm)	36" (900mm)	16	8(25)

- These foundation depths are for sites which have cohesive soils (clayey silt, sandy clay, etc.) along
 the length of the shaft, with an average Unconfined Compressive Strength (0u) > 1.0 tsf (100 kpc).
 This strength shall be verified by boring data prior to construction or with testing by the Enginee
 during foundation drilling. The Bureau of Bridges & structures should be contacted for a revised
 design if other conditions are encountered.
- 2. Combination mast arm assemblies under 55 feet (16.8 m) shall use 36" (900 mm) diameter foundations.
- Combination most arm assembles under 56 feet (16.8 m) through 75 feet (22.9 m) shall use 42" (1060 mm) diameter foundations
- 4. For most arm assemblies with dual arms refer to state standard 878001..

DEPTH OF MAST ARM FOUNDATIONS, TYPE E


FILE NAME =	USER NAME = Footemj	DESIGNED - DAG	REVISED - DAG 1-1-14	ATATE OF WILLIAM		DISTRICT ONE	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEET SHEETS NO.
cr\ps.scrk\psidot\footem_j\d2108315\ts05	dgn	DRAWN - BCK	REVISED -	STATE OF ILLINOIS			0866	12-00999-25-TL	LAKE	61 58
	PLOT SCALE = 50.0000 '/ in.	CHECKED - DAD	REVISED -	DEPARTMENT OF TRANSPORTATION		STANDARD TRAFFIC SIGNAL DESIGN DETAILS		TS-05	CONTRAC	CT NO. 61A74
	PLOT DATE = 1/13/2014	DATE - 10-28-09	REVISED -		SCALE: NONE	SHEET NO. 5 OF 7 SHEETS STA. TO STA.	EED DO		AID DRO FCT	





NOTES

- 1. CONDUIT DEPTH SHALL BE A MINIMUM OF 30" (760mm) BELOW THE BOTTOM OF THE DRAINAGE DITCH OR ANY SLOPING CROUND
- 2. THE MINIMUM CONDUIT DEPTH APPLIES TO ALL CONDUIT PLACED UNDER ROADWAY PAVEMENT, MULTI-USE PATHS, SIDEWALKS AND SOIL SURFACES.
- 3. THE MINIMUM CONDUIT DEPTH APPLIES TO ALL HANDHOLES, HEAVY DUTY HANDHOLES AND DOUBLE HANDHOLES.

HANDHOLE WITH MINIMUM CONDUIT DEPTH








MODIFY EXISTING TYPE "D" FOUNDATION TO TYPE "C" FOUNDATION

(NOT TO SCALE)

ITEM NO. IDENTIFICATION 1 OUTLET BOX- GALV. 21 CU.IN. (0.000344 CU-M) 2 LAMP HOLDER AND COVER 3 OUTLET BOX COVER 4 RUBBER COVER GASKET 5 REDUCING BUSHING 6 ½"(19 mm) CLOSE NIPPLE 7 ½"(19 mm) LOCKNUT 8 ½"(19 mm) HOLE PLUG 9 SADDLE BRACKET - CALV. 10 6 WATT PAR 38 LED FLOOD LAMP 11 DETECTOR UNIT 12 POST CAP [18 FT. (5.4 m) POST MIN.]

NOTES:

- ALL ELECTRICAL ITEMS, EXCEPT ITEMS *2 AND *11 SHALL BE ALUMINUM OR GALVANIZED
- 2, ITEM "1- OZ/GEDNEY FSX-1-50 OR EQUIVALENT ITEM "2- MULBERRY CON-O-SHADE LAMP SHIELD OR EQUIVALENT ITEM "9- "BAND-IT" SADDLE BRACKET OR EQUIVALENT
- 3. WHEN POST MOUNTING IS SPECIFIED, ITEM *9 SHALL NOT BE REQUIRED. THE DETECTION UNIT SHALL BE MOUNTED DIRECTLY ON TOP OF THE CAP BY DRILLING AND TAPPING A 3/4 "(19 mm) HOLE WITTH PIPE THREADS. THE POST CAP SHALL EITHER BE SCREWED TO THE TOP OF THE POST OR A MINIMUM OF 3 TIGHTENING SCREWS SHALL BE REQUIRED ON EACH CAP.





Α	В	С	HEIGHT	WEIGHT
VARIES	9.5"(241mm)	19"(483mm)	7" (178mm) - 12" (300mm)	53 lbs (24kg)
VARIES	10.75"(273mm)	21.5"(546mm)	7" (178mm) - 12" (300mm)	68 lbs (31 kg)
VARIES	13.0"(330mm)	26"(660mm)	7" (178mm) - 12" (300mm)	81 lbs (37 kg)
VARIES	18.5"(470mm)	37"(940mm)	7" (178mm) - 12" (300mm)	126 lbs (57 kg)

SHROUD

NOTES:

- DIMENSION "A" IS EQUAL TO THE DIAMETER OF THE MAST ARM POLE AT THE TOP OF THE SHROUD.
 THE SHROUD SHALL BE TIGHT TO THE MAST ARM POLE.
- 2. THE SUPPLIER SHALL VERIFIED THE ABOVE DIMENSIONS BASED ON MAST ARM REQUIREMENTS.
- 3. THE HEIGHT OF THE SHROUD SHALL COVER THE ANCHOR BOLTS, NUTS AND MAST ARM POLE BASE.





NOTES:


- 1. HANDHOLE CONSTRUCTED PER STATE STANDARD 814001.
- REMOVAL OF THE EXISTING CONDUIT FROM THE HANDHOLE AND THE INSTALLATION OF THE CONDUIT BUSHINGS SHALL BE INCLUDED WITH THE COST OF THE HANDHOLE.

HANDHOLE TO INTERCEPT EXISTING CONDUIT

LAKE

CONTRACT NO. 61A74

DESIGNED DAD REVISED DAG 1-1-14 DISTRICT ONE STATE OF ILLINOIS DRAWN BCK REVISED STANDARD TRAFFIC SIGNAL DESIGN DETAILS CHECKED DAD REVISED **DEPARTMENT OF TRANSPORTATION** TS-05 DATE REVISED SCALE: NONE PLOT DATE = 1/13/2014 10-28-09 SHEET NO. 6 OF 7 SHEETS STA.



SECTION


12-00999-25-TL

TS-05

COUNTY

CONTRACT NO. 61A74

LAKE



TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS

NOTES:

- A. FOR NO LANE RESTRICTION ON THE SIDE ROAD OR DRIVEWAYS
- SIDE ROAD WITH A SPEED LIMIT OF 40 MPH (60 km/h) OR LESS AS SHOWN ON THE DRAWING AND AS DIRECTED BY THE ENGINEER;
- Q) ONE ROAD CONSTRUCTION AHEAD SIGN 36 x 36 (900x900) WITH A FLASHER AND FLAG MOUNTED ON IT APPROXIMATELY 200' (60 m) IN ADVANCE OF THE MAIN ROUTE.
- b) THE CLOSED PORTION OF THE MAIN ROUTE SHALL BE PROTECTED BY BLOCKING WITH TYPE I, TYPE II OR TYPE III BARRICADES, 1/3 OF THE CROSS SECTION OF THE CLOSED PORTION.
- 2. SIDE ROAD WITH A SPEED LIMIT GREATER THAN 40 MPH (60 km/h)
 AS SHOWN ON THE DRAWING AND AS DIRECTED BY THE ENGINEER:
- O) ONE ROAD CONSTRUCTION AHEAD SIGN 48 x 48 (1.2 m x 1.2 m) WITH A FLASHER MOUNTED ON 1T APPROXIMATELY 500' (150 m) IN ADVANCE OF THE MAIN ROLITE.
- b) THE CLOSED PORTION OF THE MAIN ROUTE SHALL BE PROTECTED BY BLOCKING WITH TYPE III BARRICADES, 1/2 OF THE CROSS SECTION OF THE CLOSED PORTION.
- WHEN THE SIDE ROAD LIES BETWEEN THE BEGINNING OF THE MAINLINE SIGNING AND THE WORK ZONE, A SINGLE HEADED ARROW (MG-1) SHALL BE USED IN LIEU OF THE DOUBLE HEADED ARROW (MG-4).

SCALE: NONE

- B. FOR A LANE CLOSURE ON A SIDE ROAD OR DRIVEWAY:
- USE APPLICABLE PORTIONS OF THE TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES (STD. 701501, STD. 701606 OR THE APPROPRIATE STANDARD). THE SPACING OF SIGNS AND BARRICADES SHALL BE ADJUSTED FOR FIELD CONDITIONS AS DIRECTED BY THE ENGINEER. THE DIRECTIONAL ARROW SHALL BE COVERED OR REMOVED WHEN NO LONGER CONSISTENT WITH THE SIDE ROAD LANE CLOSURE.
- C. ADVANCE WARNING SIGNS ARE TO BE OMITTED ON DRIVEWAY UNLESS OTHERWISE NOTED.
- D. THE TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS SHALL BE INCIDENTAL TO THE COST OF SPECIFIED TRAFFIC CONTROL STANDARDS OR ITEMS.

All dimensions are in millimeters (inches) unless otherwise shown.

FILE NAME =	USER NAME = geglienobt	DESIGNED - LHA	REVISED - J. OBERLE 10-18-95
Wi\diststd\22x34\tcl0.dgn		DRAWN -	REVISED - A. HOUSEH 03-06-96
	PLOT SCALE = 52.020 */ IN.	CHECKED -	REVISED - A, HOUSEH 10-15-96
	PLOT DATE = 1/4/2008	DATE - 06-89	REVISED -T. RAMMACHER 01-06-00

STATE	OF	ILLINOIS
DEPARTMENT	OF '	TRANSPORTATION

TRAFFIC CONTROL AND PROTECTION	FOR	F.A.P. RTE.	
SIDE ROADS, INTERSECTIONS, AND DRIVE	0866	12-0	
TIPE HONDO, HETEROCOTTORO, ARED DINA	·MAIO		1
HEFT NO 1 OF 1 SHEETS STA	TO CTA	www.wwi	

F.A.P. RTE.	SEC	TION	COUNTY	TOTAL	SHEET NO.
0866	12-0099	9-25-TL	LAKE	61	61
	TC-1	0	CONTRACT	NO. 6	ATH
FED. ROA	D DIST. NO. 1	ILLINOIS FED.	AID PROJECT		