

**SB MAINLINE RESURFACING SCHEDULE**

LOCATION				LENGTH	POLY BIT. MAT' L (PRIME COAT)	BIT. MAT' L (PRIME COAT)	SUBBASE GRANULAR MATERIAL, TYPE A, 12"	SHLD RUMBLE STRIPS, 16"	HMA SURFACE REMOVAL - BUTT JOINT	TEMP RAMP
STATION TO STATION										
				FEET	POUND	POUND	SQ YD	FEET	SQ YD	SQ YD
SOUTHBOUND										
1542+30.00		TO	1556+00.00	1370.00	2877	2980	4567	2740	0	273
1556+00.00		TO	1572+91.61	BK 1691.61	3045	3426	4511	3383	0	0
00+00.00	AH	TO	01+00.79		100.79	181	204	269	202	0
01+00.79		TO	02+55.79		155.00	186	318	413	310	0
02+55.79		TO	17+65.41	BK 1509.62	1812	2831	0	3019	0	0
17+82.93	AH	TO	39+20.00		2137.07	2564	4007	0	4274	0
39+20.00		TO	43+10.00		390.00	468	800	1040	780	0
43+10.00		TO	51+00.00		790.00	948	1481	0	1580	0
51+00.00		TO	53+00.00		200.00	240	450	0	400	0
61+98.00		TO	63+53.00		155.00	1264	3080	2808	2106	0
63+53.00		TO	66+52.00		299.00	0	0	0	0	0
66+52.00		TO	68+07.00		155.00	898	2188	1995	1496	0
74+00.00		TO	76+00.00		200.00	240	450	0	400	0
76+00.00		TO	92+58.36	BK 1658.36	1990	3109	0	3317	0	0
92+39.80	AH	TO	170+31.62	BK 7791.82	9350	14610	0	15584	0	0
170+47.27	AH	TO	215+39.65	BK 4492.38	5391	8423	0	8985	0	0
215+35.61	AH	TO	218+25.55	BK 289.94	348	544	0	580	0	0
217+83.13	AH	TO	261+15.00		4331.87	5198	8122	0	8664	0
261+15.00		TO	265+35.00		420.00	504	861	1120	840	0
265+35.00		TO	361+90.00		9655.00	11586	18103	0	19310	0
361+90.00		TO	366+19.00		429.00	515	879	1144	858	0
366+19.00		TO	409+00.00		4281.00	5137	8027	0	8562	0
409+00.00		TO	413+20.00		420.00	504	861	1120	840	0
413+20.00		TO	434+45.00		2125.00	2550	3984	0	4250	0
434+45.00		TO	438+80.00		435.00	522	892	1160	870	0
438+80.00		TO	462+04.07		2324.07	2789	4358	0	4648	191
<b>SB MAINLINE SUBTOTAL</b>					<b>61107</b>	<b>94987</b>	<b>20146</b>	<b>97997</b>	<b>191</b>	<b>811</b>