



CLASS WILL BE REQUIRED ON THIS PROJECT AT THE LOCATION SHOWN ON THE PLANS.

AGGREGATE DITCH FOR FLEXIBLE DITCH LINING

DESIGNER NOTES:

- 1) CLASS A3 OR A4 CAN BE USED FOR DITCH LINING. USE A4 FOR VELOCITIES GREATER THAN 12 FPS. A3 MAY BE USED AS AN ALTERNATE TO FIBERMAT.
- 2) INCLUDE PAY ITEM FOR FILTER FABRIC FOR USE WITH RIPRAP. NOTE THE SPECIFICATION BOOK DOES NOT REQUIRE FABRIC ON A3 BUT INCLUDE IT WHEN USING THIS STANDARD.
- 3) EXAMPLE: CLASS A4 MEANS A QUALITY AND GRADATION RR 3. SEE ARTICLE 1005.01 FOR SIZE.
- 4) REMEMBER TO FILL IN THE DIMENSIONS ON THE DITCH SECTION ABOVE.
- 5) ADD THE CLASS A3 OR A4 TO THE NOTE ON THE BOTTOM RIGHT.

283-1

MODEL: det 3 det31b
 FILE: \\nrcs-pw01\share\benley.com\PI\DOT\Documents\DOT_Offices\Dir\det_3\Projects-Carcy-Detail\03_Detail_Revision\2023\200-299_EARTHWORK - LANDSCAPING - EROSION.dgn

USER NAME = Anthony.Grunstad	DESIGNED -	REVISED -
	DRAWN -	REVISED -
PLOT SCALE = 100,000 ' / in.	CHECKED -	REVISED -
PLOT DATE = 9/26/23	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

SCALE: SHEET OF SHEETS STA. TO STA.

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CONTRACT NO.				
ILLINOIS FED. AID PROJECT				