

Effective: October 23, 2006

Revised: January 1, 2022

Designer Note: This General Note should be added to all contract plans using Hot-Mix Asphalt.

HOT-MIX ASPHALT MIXTURE REQUIREMENTS

Consult the District Mixtures Control Engineer for guidance in choosing hot-mix asphalt mixture types to use for your specific project. See Materials mixture requirements. Don't forget to fill in the MTD right-of-way with a "Yes" or "No". This should match your QNOS Table for the MTD.

HOT-MIX ASPHALT MIXTURE REQUIREMENTS

The following mixture requirements are applicable for this project:

Mixture Use(s):	
AC/PG:	
Design Air Voids:	
Mixture Composition (Gradation Mixture):	
Friction Aggregate:	
Quality Management:	
Material Transfer Device	Yes or No

Notes:

- 1) Individual lift thicknesses of each mix will be no less than three (3) times nominal maximum aggregate size and no more than five (5) times nominal aggregate maximum size, unless otherwise approved by the Engineer.
- 2) For design purposes, mixture weight for all mixes is determined to be 112.0 lb./sq. yard/in., unless otherwise noted.
- 3) Sublot sizes for PFP and QCP mixes will be 1,000 tons, unless otherwise agreed to by the Engineer and the paving Contractor.