

Illinois Department of Transportation

Memorandum

То:	*
From:	Nicole Fayant By: Kevin Horst KH
Subject:	Special Provision Changes
Date:	January 17, 2023

The following special provsions have been revised for the April 28, 2023 and June 16, 2023 lettings: Please revise your special provision books as indicated.

Recurring Special Provisions

Adopted January 1, 2023

Revised designer notes and numbering to match the 2023 Recurring Special Provision Book.

Interim Special Provisions (BDE) **ISP Number** Description Alphabetic ISP Index · Remove existing alphabetic index and insert revised index. (Revised) Numerical ISP Index Remove existing numberic index and insert revised index. (Revised) 106.01 (New) "Source of Supply and Quality Requirements (BDE)" New special to be inserted into all federal aid contracts. 406.11 (Revised) "Surface Testing of Pavements - IRI (BDE)" Only Designer Note revised; Special Provision was not revised. 109.13 (Revised) "Submission of Payroll Records (BDE)" Only Designer Note revised; Special Provision was not revised. 701.00 (Revised) "Automated Flagger Assistance Devices" Revised to allow the use of Red/Yellow Lens AFADs, in addition to STOP/SLOW AFADs that are currently allowed, and to eliminate redundancies with the MUTCD. **District Special Provisions** "Protective Coat (Special)" 503.19 (Revised) Revised Designer Note and elongation at break in paragraph "A." NF:KH:tdp:s:\MGR2\WINWORD\Special Provisions\PL_Completed SP\Special Provisions Memo Changes.docx Attachment(s)

CC: *	Hydraulics T. Phillips	Team 3 Team 4	Team 7 Team8	Team 11 Team 12	Local Roads (T. Sassine) Materials (S. Worsfo <u>ld)</u>
	Team 1	Team 5	Team 9	Geometrics-13	Materials (D. Parish)
	Team 2	Team 6	Team 10	Bridges	S&P Engineer (M. Otten)

Special Provisions Generated Checklist Generated – 01/17/2023 4:18 PM

April 28, 2023 & June 16, 2028 Letting

Designer:		Route (FAP, etc.):	
Contract No.:		Section:	
Lettings:	April 28, 2023 & June 16, 2023	County(ies):	

\checkmark	Dir	File Name	Spec Title	Spec Dates
	BRG\	APSLRP-1.docx	Approach Slab Repair	E 3/13/97
	DES\	00000.docx	STATE OF ILLINOIS	
	DES\	10500.docx	Construction Station Layout	E 7/30/10
	DES\	10501.docx	Construction Layout Responsibility	E 4/26/15 R 1/1/22
	DES\	10502.docx	Construction Layout Utilizing GPS Equipment	E 4/26/15 R 1/1/22
	DES\	<u>10503.docx</u>	Construction Layout Equipment	E 4/26/15 R 11/6/15
	DES\	<u>10507.docx</u>	Removal of Abandoned Underground Utilities	E 1/15/96 R 11/21/96
	DES\	<u>10507a.docx</u>	Status of Utilities/Utilities To Be Adjusted	E 1/21/05 R 1/1/22
	DES\	<u>10507b.docx</u>	Utilities - Locations/Information on Plans	E 11/8/13
	DES\	<u>10712.docx</u>	Requirements When Working with the Railroad	E 4/1/16 R 4/1/22
	DES\	<u>10713a.docx</u>	Protection of the Illinois River	E 8/1/22 R 10/1/22
	DES\	<u>10713b.docx</u>	Maintenance of Navigation	E 8/1/22 R 10/1/22
1	DES\	<u>10731.docx</u>	Location of Underground State Maintained Facilities	E 8/3/07 R 7/31/09
	DES\	<u>10732.docx</u>	Right-of-Way Restrictions	E 7/1/94
	DES\	<u>10805a.docx</u>	Date of Completion	E 3/1/90 R 4/25/08
	DES\	<u>10805b.docx</u>	Date of Completion (Plus Working Days)	E 3/1/90 R 8/3/18
	DES\	20500.docx	Geotechnical Reinforcement	E 6/10/93 R 1/1/07
	DES\	20504.docx	Embankment (Restrictions)	E 1/21/05 R 8/5/22
	DES\	<u>25000.docx</u>	Seeding, Minor Areas	E 7/1/90 R 4/1/19
	DES\	<u>25006a.docx</u>	Mowing	E 12/11/01 R 8/2/13
	DES\	<u>25006b.docx</u>	Mowing	E 12/11/01 R 8/2/13
	DES\	25300b.docx	Seedlings	E 5/5/00 R 8/1/19
	DES\	<u>28100.docx</u>	Grout for Use With Riprap	E 7/30/10
	DES\	<u>30101.docx</u>	Proof Rolling	E 4/23/04 R 1/1/07
	DES\	<u>30103.docx</u>	Subgrade Treatment	E 7/1/90 R 1/1/22
	DES\	<u>30200.docx</u>	Soil Modification	E 7/1/90 R 1/1/22
÷	DES\	<u>31100.docx</u>	Rock Fill	E 10/15/95 R 4/26/13
	DES\	<u>35300.docx</u>	Sawcutting of PCC Base Course and Base Course Widening	E 1/1/16
	DES\	<u>35500d.docx</u>	Temporary Pavement	E 10/1/95 R 4/24/20
	DES\	<u>35600.docx</u>	Temporary Base Course Widening	E 4/26/13 R 4/24/20
	DES\	<u>40600.docx</u>	Clean Existing Pavement Edge Joint	E 1/3/00 R 4/24/20
	DES\	40604a.docx	Hot-Mix Asphalt Surface Course Surface Tests	E 11/1/03 R 1/1/07
	DES\	40607.docx	Hot-Mix Asphalt -Tack Coat (Special) Options	E 8/1/19 R 11/8/19
	DES\	40713.docx	Grooved-In Rumble Strip	E 11/16/07 R 7/30/10
	DES\	42401.docx	Sidewalk Drains	E 3/1/91 R 1/1/07
	DES\	42402.docx	Temporary Sidewalks	E 3/1/91 R 2/1/96

Designer:		Route (FAP, etc.):	
Contract No.:		Section:	
Lettings:	April 28, 2023 & June 16, 2023	County(ies):	

DES\	44000.docx	Partial Depth Patching	E 4/26/13 R 11/6/20
DES\	44002.docx	Longitudinal Joint Repair	E 4/26/13 R 7/31/20
DES\	44003.docx	Protection of Frames and Lids of Utility Structures	E 3/6/91 R 1/1/07
DES\	44003a.docx	Hot-Mix Asphalt Surface Removal, **" (** mm)	E 3/1/93 R 1/1/22
DES\	44003b.docx	Hot-Mix Asphalt Surface Removal, **" (** mm)	E 2/5/93 R 1/1/22
DES\	44003d.docx	Pavement Drainage After Cold Milling	E 3/15/96 R 11/8/19
DES\	44003e.docx	Pavement Patching with Hot-Mix Asphalt Surface Removal	E 3/1/97 R 1/1/07
DES\	44004.docx	Hot-Mix Asphalt Joint Trimming	E 8/5/22
DES\	48205.docx	Hot-Mix Asphalt Shoulder Resurfacing Required to be Constructed Simultaneously with Mainline Paving	E 4/23/10 R 8/4/17
DES\	48206.docx	Hot-Mix Asphalt Shoulder Resurfacing Constructed Simultaneously with Mainline Paving	E 1/22/01 R 1/1/07
DES\	<u>50103.docx</u>	Concrete Headwall Removal	E 7/1/90
DES\	<u>50104.docx</u>	Concrete Handrail Removal	E 7/1/90 R 1/1/07
DES\	50301.docx	Granular Backfill for Structures	E 8/4/17 R 11/6/20
DES\	50302.docx	Surface Filler (Special)	E 4/23/10 R 8/1/22
DES\	<u>50307.docx</u>	PCC Placement by Pump Requirements	E 1/1/22
DES\	50312.docx	Plug Existing Deck Drains	E 1/1/96 R 11/6/20
DES\	<u>50312a.docx</u>	Floor Drain Extension	E 3/22/01 R 11/6/20
DES\	50319.docx	Protective Coat (Special)	E 4/23/10 R 4/1/23
DES\	54200.docx	Seepage Collar	E 12/1/96
DES\	<u>54201.docx</u>	Remove and Relay Pipe Culvert (Special)	E 7/1/90 R 11/6/20
DES\	<u>54202.docx</u>	Pipe Culverts (Jacked)	E 1/1/14
DES\	<u>54204e.docx</u>	Backfill - Pipe Culverts	E 10/15/95 R 1/1/07
DES\	55000.docx	Storm Sewer, (Water Main Quality Pipe)	E 1/1/11 R 1/1/21
DES\	<u>55007.docx</u>	Backfill, Building Removal	E 8/20/91 R 1/1/07
DES\	55200.docx	Steel Pipe Culvert, Special (Jacked) * inches (* mm)	E 7/1/94 R 1/1/07
DES\	55201.docx	(*Storm Sewer/Pipe Culvert) Jacked in Place, ** inches (** mm)	E 7/1/94 R 1/1/07
DES\	<u>56100.docx</u>	Steel Casings * Inches	E 7/1/90 R 1/1/13
DES\	<u>56101.docx</u>	Steel Casings * Inches	E 7/1/90 R 1/1/13
DES\	<u>59300.docx</u>	Slope Wall Slurry Pumping	E 7/31/20
DES\	60200a.docx	Inlets, Type G-1	E 10/1/95 R 1/1/07
DES\	60200b.docx	Inlets, Type G-1, Special	E 10/1/95 R 1/1/07
DES\	60200c.docx	Inlets, Type G-1, Double, Special	E 10/1/95 R 1/1/07
DES\	60200d.docx	Inlet Manhole, Type G-1, 4' (1.2 m) Diameter	E 10/1/95 R 1/1/07
DES\	60200e.docx	Inlet-Manhole, Type G-1, 4' (1.2 m) Diameter, Special	E 10/1/95 R 1/1/07

Designer:		Route (FAP, etc.):	
Contract No.: Lettings:	April 28, 2023 & June 16, 2023	Section: County(ies):	

	DES\	60200f.docx	Inlet-Manhole, Type G-1, 5' (1.5 m) Diameter	E 10/1/95 R 1/1/07
	DES\	60200g.docx	Inlet-Manhole, Type G-1, 5' (1.5 m) Diameter, Special	E 10/1/95 R 1/1/07
	DES\	60200h.docx	Inlet-Manhole, Type G-1, 5' (1.5 m) Diameter, Double, Special	E 10/1/95 R 1/1/07
	DES\	<u>60200i.docx</u>	Inlet-Manhole, Type G-1, 8' (2.4 m) Diameter, Double, Special	E 10/1/95 R 1/1/07
	DES\	60200j.docx	Manhole to be Adjusted with New Type G-1 Frame and Grate	E 10/1/95 R 1/1/07
	DES\	60200k.docx	Temporary Inlet Drainage Treatment	E 1/1/97
	DES\	602001.docx	Inlets, Type G-2	E 11/1/03 R 1/1/07
	DES\	60200m.docx	Inlets, Type G-1, Double	E 7/31/09
	DES\	60200n.docx	Inlets, Type " * ", With Special Frame and Grate	E 8/2/13
	DES\	60200o.docx	Manhole, Type A, of the Diameter Specified with Special Frame and Grate	E 8/2/13
	DES\	60504.docx	Filling Existing Inlets	E 7/1/90 R 7/1/94
	DES\	60504a.docx	Filling Existing Culverts	E 10/15/95 R 4/1/17
	DES\	60504b.docx	Filling Drainage Structures	E 10/15/95 R 4/1/17
	DES\	60608.docx	Island Pavement Constructed on Existing Pavement	E 1/1/97 R 1/1/07
	DES\	60612.docx	Drainage Holes	E 7/1/90 R 1/1/07
	DES\	63001.docx	Guardrail Aggregate Erosion Control	E 2/1/93 R 1/1/07
	DES\	63111c.docx	Traffic Barrier Terminals	E 2/1/96 R 11/5/04
	DES\	63200.docx	Guard Post Removal	E 7/1/90 R 1/1/07
	DES\	63500.docx	Flexible Delineator Maintenance	E 5/5/92 R 1/1/94
	DES\	63501.docx	Flexible Delineators	E 10/1/95 R 1/1/07
	DES\	63502.docx	Recoverable Delineators	E 4/26/15 R 11/1/18
	DES\	66704.docx	Permanent Survey Marker, Type 1, Bridge Placement	E 7/1/90 R 3/11/11
	DES\	66802.docx	Permanent Survey Ties	E 4/1/91 R 4/27/12
	DES\	67005.docx	Equipment Vault for Nuclear Testing Equipment	E 6/24/93 R 11/8/19
	DES\	68000.docx	Railroad Track Removal	E 11/1/94 R 1/1/07
	DES\	68000a.docx	Railroad Ties Removal and Disposal	E 11/1/94 R 10/1/95
	DES\	68300.docx	Mortared Stone Wall	E 3/1/91 R 1/1/07
\checkmark	DES\	70100.docx	Traffic Control Plan	E R
	DES\	70101.docx	Flaggers	E 8/3/18
	DES\	70108b.docx	Traffic Control and Protection Standard 701331 (Special)	E 10/15/95 R 7/31/09
	DES\	70114.docx	Width Restriction Signing	E 11/1/07 R 1/1/19
	DES\	70120.docx	Traffic Control and Protection BLR 21	E 4/25/08 R 4/24/20
	DES\	70121.docx	Traffic Control and Protection BLR 22	E 4/25/08 R 4/24/20
	DES\	70400.docx	Temporary Concrete Barrier, State Owned	E 5/1/91 R 4/1/19
	DES\	70400a.docx	Temporary Concrete Barrier Reflectors	E 1/21/05 R 11/6/20

Designer:		Route (FAP, etc.):	
Contract No.:	•	Section:	
Lettings:	April 28, 2023 & June 16, 2023	County(ies):	

DES\	73300.docx	Re-Tightening Anchor Bolts for Cantilever Sign Structures	E 4/25/14
DES\	<u>78201.docx</u>	Linear Delineartor Panels, 4 Inch	E 10/1/22
DES\	81500.docx	Trench & Backfill, Special for Conduit Installation Beneath Bituminous Shoulders	E 3/21/94 R 11/6/20
DES\	88600a.docx	Detector Loops, Type 1	E 3/1/96 R 11/6/20
DES\	<u>88601.docx</u>	Adjust Existing Detector Loop Riser	E 11/7/14 R 11/6/20
DES\	88602.docx	Miscellaneous Electrical Work	E 8/5/22
DES\	<u>100400.docx</u>	PCC Slipform Paving Aggregate Optimization	E 8/3/12 R 1/1/22
DES\	<u>100402.docx</u>	PCC Superstructure Aggregate Optimization	E 8/4/06 R 1/1/22
DES\	<u>100403b.docx</u>	Coarse Aggregate for Bituminous Courses, Class A	E 6/29/93 R 1/1/07
DES\	<u>100404.docx</u>	Aggregate Quality	E 7/1/90 R 4/26/13
DES\	<u>102013.docx</u>	Membrane Curing Method	E 7/29/16 R 11/17/17
DES\	<u>110300.docx</u>	PCC QMP Electronic Report Submittals	E 1/13/22
DES\	<u>110303.docx</u>	PCC Automatic Batching Equipment	E 4/23/10 R 11/7/14

BDE Special Provisions Checklist

April 28, 2023 & June 16, 2023 Lettings

BDE SPECIAL PROVISIONS For the April 28, 2023 and June 16, 2023 Lettings

The following special provisions indicated by a "check mark" are applicable to this contract and will be included by the Project Coordination and Implementation Section of the Bureau of Design & Environment (BDE).

Fil	e Name	#		Special Provision Title	Effective	Revised
	80099			Accessible Pedestrian Signals (APS)	April 1, 2003	Jan. 1, 2022
	80274	2		Aggregate Subgrade Improvement	April 1, 2012	April 1, 2022
	80192	3		Automated Flagger Assistance Devices	Jan. 1, 2008	April 1, 2023
	80173	4		Bituminous Materials Cost Adjustments	Nov. 2, 2006	Aug. 1, 2017
	80426	5		Bituminous Surface Treatment with Fog Seal	Jan. 1, 2020	Jan. 1, 2022
	80436	6		Blended Finely Divided Minerals	April 1, 2021	
*	80241	7		Bridge Demolition Debris	July 1, 2009	
*	5053I	8		Building Removal	Sept. 1, 1990	Aug. 1, 2022
*	5026I	9		Building Removal with Asbestos Abatement	Sept. 1, 1990	Aug. 1, 2022
	80384	10	\boxtimes	Compensable Delay Costs	June 2, 2017	April 1, 2019
*	80198	11		Completion Date (via calendar days)	April 1, 2008	
*	80199	12		Completion Date (via calendar days) Plus Working Days	April 1, 2008	
	80261	13		Construction Air Quality – Diesel Retrofit	June 1, 2010	Nov. 1, 2014
	80434	14		Corrugated Plastic Pipe (Culvert and Storm Sewer)	Jan. 1, 2021	
*	80029	15	\boxtimes	Disadvantaged Business Enterprise Participation	Sept. 1, 2000	Mar. 2, 2019
	80229	16		Fuel Cost Adjustment	April 1, 2009	Aug. 1, 2017
	80447	17		Grading and Shaping Ditches	Jan. 1, 2023	-
	80433	18		Green Preformed Thermoplastic Pavement Markings	Jan. 1, 2021	Jan. 1, 2022
	80443	19		High Tension Cable Median Barrier Removal	April 1, 2022	
	80446	20		Hot-Mix Asphalt - Longitudinal Joint Sealant	Nov. 1, 2022	
	80438	21		Illinois Works Apprenticeship Initiative – State Funded Contracts	June 2, 2021	Sept. 2, 2021
	80045	22		Material Transfer Device	June 15, 1999	Jan. 1, 2022
	80441	23		Performance Graded Asphalt Binder	Jan. 1, 2023	
*	34261	24		Railroad Protective Liability Insurance	Dec. 1, 1986	Jan. 1, 2022
	80445	25		Seeding	Nov. 1, 2022	
	80448	26		Source of Supply and Quality Requirements	Jan. 2, 2023	
	80340			Speed Display Trailer	April 2, 2014	Jan. 1, 2022
	80127			Steel Cost Adjustment	April 2, 2004	Jan. 1, 2022
	80397		\boxtimes	Subcontractor and DBE Payment Reporting	April 2, 2018	
	80391	30	\boxtimes	Subcontractor Mobilization Payments	Nov. 2, 2017	April 1, 2019
	80437		\boxtimes	Submission of Payroll Records	April 1, 2021	Nov. 1, 2022
	80435	32		Surface Testing of Pavements – IRI	Jan. 1, 2021	Jan. 1, 2023
		33		Traffic Spotters	Jan. 1, 2019	
*	20338			Training Special Provisions	Oct. 15, 1975	Sept. 2, 2021
	80429	35		Ultra-Thin Bonded Wearing Course	April 1, 2020	Jan. 1, 2022
	80439	36		Vehicle and Equipment Warning Lights	Nov. 1, 2021	Nov. 1, 2022
	80440	37		Waterproofing Membrane System	Nov. 1, 2021	
		38	\boxtimes	Weekly DBE Trucking Reports	June 2, 2012	Nov. 1, 2021
-	80427		\boxtimes	Work Zone Traffic Control Devices	Mar. 2, 2020	
*	80071	40		Working Days	Jan. 1, 2002	

Highlighted items indicate a new or revised special provision for the letting.

An * indicates the special provision requires additional information from the designer, which needs to be submitted separately. The Project Coordination and Implementation Section will then include the information in the applicable special provision.

The following special provisions have been deleted from use.

<u>File Name</u>	Special Provision Title	<u>Effective</u>	Revised
50481	Building Removal-Case II (Non-Friable Asbestos)	Sept. 1, 1990	April 1, 2010
50491	Building Removal-Case III (Friable Asbestos)	Sept. 1, 1990	April 1, 2010

The following special provisions are in the 2023 Supplemental Specifications and Recurring Special Provisions.

<u>File Name</u> 80293	<u>Special Provision Title</u> Concrete Box Culverts with Skews > 30	New Location(s) Articles 540.04 & 540.06	Effective	Revised
00293	Degrees and Design Fills ≤ 5 Feet	Anicles 540.04 & 540.06	April 1, 2012	July 1, 2016
80311	Concrete End Sections for Pipe Culverts	Articles 540.07, 542.01, 542.02, 542.07, 542.11 & 542.12	Jan. 1, 2013	April 1, 2016
80422	High Tension Cable Median Barrier	Articles 644.02, 644.05, 782.01, 782.04, 782.07 & 1097.02	Jan. 1, 2020	Jan. 1, 2022
80442	Hot-Mix Asphalt	Articles 1030.09 & 1030.10	Jan. 1, 2022	Aug. 1, 2022
80444	Hot-Mix Asphalt – Patching	Errata – Article 442.08(b)	April 1, 2022	0
80411	Luminaires, LED	Articles 801.05(a), 821.02(d), 821.03, 821.08 & 1067.01-1067.06	April 1, 2019	Jan. 1, 2022
80418	Mechanically Stabilized Earth Retaining Walls	Articles 1003.07 & 1004.06	Nov. 1, 2019	Nov. 1, 2020
80430	Portland Cement Concrete – Haul Time	Article 1020.11(a)(7)	July 1, 2020	
80395	Sloped Metal End Section for Pipe Culverts	Articles 540.07, 542.01, 542.02, 542.07, 542.11 & 542.12	Jan. 1, 2018	
80318	Traversable Pipe Grate for Concrete End Sections	Articles 540.04, 540.07, 540.08 & 542.01, 542.02, 542.07, 542.11 & 542.12	Jan. 1, 2013	Jan. 1, 2018

,

Designer Notes Recurring Special Provisions

:

Designer Notes for January 1, 2023 Recurring Special Provisions (April 28, 2023 & June 16, 2023 Lettings)

- 1. Designer Note: This check sheet is required in <u>all</u> contracts that involve Federal funds.
- 2. Designer Note: This check sheet is required in <u>all</u> Federal contracts.
- 3. Designer Note: This check sheet is required in <u>all</u> contracts.
- 4. Designer Note: This check sheet is required in all contracts involving State funds <u>only</u>.
- 5. Designer Note: This check sheet is required in all contracts involving State funds <u>only</u>.
- 6. Designer Note: Include in all contracts where Asbestos Bearing Pad Removal is part of the structure work.
- 7. Designer Note: Include in all contracts where the existing bridge deck HMA surface is to be removed and the waterproofing membrane contains asbestos and will be removed. The designer must have in the project files a completed "Asbestos Determination Certificate" for every bridge within the project limits. The District Bridge Maintenance Engineer and/or the District Hydraulics Engineer can provide copies of these certificates. If your project has any bridge deck containing asbestos, insert this special provision as well as the General Notes entitled, "Asbestos Bridge Wearing Surface Removal".
- 8. Designer Note: This check sheet will be required for those contracts that will involve Contractor work on haul road stream crossings, other temporary stream crossings, and in stream work pads. Contracts that would generally involve this type of work would be bridges/structures, new or rebuilt, and contracts involving earth excavation, embankment or borrow excavation. Discuss these types of work operations and any other stream related work with your Project Engineer. Any in-stream crossing or other work will require an individual 404 Permit from the Corps of Engineers. Be sure to let the Hydraulics Engineer know as soon as possible that a Corps permit will be needed. The permit has a lead-time and is required for the project to proceed to letting.
- 9. Designer Note: Depending on IDOT manpower needs, this check sheet will be included as a pay item when the Contractor will be required to do <u>all contract staking</u>, including <u>bridges</u>. This check sheet should be used for a large box culvert or a multi pipe that will require a structure number. This would be a structure that will have a span length along survey line of more than 6 meters (20 feet).

Discuss this check sheet with the Bureau of Project Implementation (Construction) as to what manpower sources are available.

10. Designer Note: This special provision specifies the requirements for geotextile fabric for use on railroad crossings.

Include <u>only</u> on projects where the railroad crossing is a contract pay item. Also may be required for temporary crossings.

Railroad crossings are generally (99%) handled by the Railroad through an agreement and not part of our contract. If in doubt as to how to handle, discuss with Project Support. 11. Designer Note: Use this check sheet where existing pavement is being reconstructed and voids are evident under the existing pavement that can be filled by grouting. Discuss with Maintenance Field Engineer responsible for the area.

NOTE: A detail of the slab movement detection device is included in CADD and this drawing must be included in your contract plans.

- 12. Designer Note: This check sheet will be required on a contract where cold milling is required but where the cold milled area will not be overlaid. Include CADD Standard 440001 in your plans. If your contract is to be cold milled and the area overlaid, you should use one of the two District special provisions on this subject, **not** this check sheet.
- 13. Designer Note: This check sheet requires that once a lift of bituminous resurfacing is placed on a lane of pavement, any adjoining bituminous shoulder shall be resurfaced with an equal thickness before any other lane is resurfaced for each lift of resurfacing. Insert this special on resurfacing projects which meet the following criteria: All four lane interstates and freeways, all four lane expressways, four lane highways with ADT > 25,000 or peak one-way VPH > 1,700, two lane highways with ADT > 10,000 or peak one-way VPH > 800.
- 14. Designer Note: Intended to remove thick bituminous overlay so that the original pavement can be examined and then patched, if necessary. It also further defines specific pay items for work involved.
- 15. Designer Note: This check sheet was developed by Materials and Physical Research as an alternate to replacing Preformed Joint Sealer and Neoprene Expansion Joints up to 65 mm (2¹/₂" inches). Include with any projects that have "POLYMER CONCRETE" as a pay item.
- 16. Reserved.
- 17. Designer Note: This check sheet was developed to obtain the desired pipe coating on bike racks. Use on all projects with bike racks.
- 18. Designer Note: This special provision is for use on bridge contracts where staging is required, and the District wants the Contractor to have an option to post-mounting the temporary bridge and traffic signals. Discuss use with the District Traffic Control Technician.
- 19. Designer Note: This check sheet should be included for all projects containing roadway lighting. The designer should also include CADD Standard 701301-D4 in the plans.
- 20. Designer Note: This check sheet was developed to address difficulties with obtaining metric sized bolts. Include in all metric projects, which contain or could contain any type of bolted connection.
- 21. Designer Note: This special provision not to be used in District Four. Not recommended for use on recently constructed pavements or bridge decks. This is not recommended when there is steel in the patches due to the corrosion the calcium chloride causes.
- 22. Designer Note: Do not use Check Sheet #22 unless requested by Materials.
- 23. Designer Note: Use in all contracts involving cast-in-place concrete.
- 24. Reserved.
- 25. Reserved.

- 26. Designer Note: Insert into preventative maintenance contracts using cape seals or bituminous surface treatments.
- 27. Design Note: Insert into contracts using high-density expanding polyurethane foam or restoring the elevation of settled bridge approach pavements.
- 28. Designer Note: Insert into contracts using PCC inlays or overlays. Use in accordance with Chapter 53 of the *BDE Manual*.
- 29. Designer Note: Use on resurfacing projects to address areas which need repair, but do not warrant full depth repair. Joints and cracks, which exhibit environmental distresses, such as, spalling and "D" cracking or contains maintenance patching, are eligible for using this method of repair. Joints and cracks which exhibit load related stresses, such as pumping, alligator cracking, corner breaks, compression failures, subgrade failures, or punch-outs should not use this method on repair. Discuss use with your Project Engineer.
- 30. Designer Note: Consider using on contracts with longitudinal partial depth patching. There is a District Special Provision (Longitudinal Joint Repair, 440.02) that D4 prefers to use because it has different requirements. If using the BDE version and you cannot allow the milled trench to be left open overnight, specify the holes shall be filled every night.
- 31. Designer Note: Insert in projects with cast-in-place concrete. It is an interim measure to allow districts to transition from department mix designs to contractor mix designs.
- 32. Design Note: Use on all HMA overlay, Full-Dept HMA paving, and PCC pavement projects in District 4.

s:\mgr2\winword\special provisions\recurring sp_designer notes\recurring designer notes.doc

-3-

First Page & Index for Supplemental Specifications and Recurring Special Provisions

Current Lettings

(April 28, 2023 & June 16, 2028 Letting)

STATE OF ILLINOIS

SPECIAL PROVISIONS

The following Special Provisions supplement the "Standard Specifications for Road and Bridge Construction, adopted January 1, 2022 (revised January 1, 2023)", the latest edition of the "Manual on Uniform Traffic Control Devices for Streets and Highways", and the "Manual of Test Procedures for Materials" in effect on the date of invitation for bids, and the "Supplemental Specifications and Recurring Special Provisions" indicated on the Check Sheet included herein, and the "Recommended Standards for Water Works", (Ten State Standards), latest edition, which apply to and govern the construction of

and in case of conflict with any part, or parts, of said Specifications, the said Special Provisions shall take precedence and shall govern.

LOCATION OF PROJECT

DESCRIPTION OF PROJECT

INDEX FOR

SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS

Adopted January 1, 2023

This index contains a listing of SUPPLEMENTAL SPECIFICATIONS and frequently used RECURRING SPECIAL PROVISIONS.

ERRATA Standard Specifications for Road and Bridge Construction

(Adopted 1-1-22) (Revised 1-1-23)

SUPPLEMENTAL SPECIFICATIONS

Std. Spec. Sec.	Page No.
202 Earth and Rock Excavation	1
204 Borrow and Furnished Excavation	2
207 Porous Granular Embankment	
211 Topsoil and Compost	4
407 Hot-Mix Asphalt Pavement (Full-Depth)	5
420 Portland Cement Concrete Pavement	6
502 Excavation for Structures	7
509 Metal Railings	
540 Box Culverts	
542 Pipe Culverts	
586 Granular Backfill for Structures	
644 High Tension Cable Median Barrier	35
782 Reflectors	
801 Electrical Requirements	
821 Roadway Luminaires	40
1003 Fine Aggregates	41
1004 Coarse Aggregates	
1020 Portland Cement Concrete	
1030 Hot-Mix Asphalt	
1067 Luminaire	
1097 Reflectors	

RECURRING SPECIAL PROVISIONS

٠

The following RECURRING SPECIAL PROVISIONS indicated by an "X" are applicable to this contract and are included by reference:

CHECK SH	EET#	AGE NO.
1	Additional State Requirements for Federal-Aid Construction Contracts	. 53
2	Subletting of Contracts (Federal-Aid Contracts)	
3	EEO	
4	Specific EEO Responsibilities Non Federal-Aid Contracts	. 67
5	Required Provisions - State Contracts	
6	Asbestos Bearing Pad Removal	. 78
7	Asbestos Waterproofing Membrane and Asbestos HMA Surface Removal	
8	Temporary Stream Crossings and In-Stream Work Pads	. 80
9	Construction Layout Stakes	
10	Use of Geotextile Fabric for Railroad Crossing	. 84
11 .	Subsealing of Concrete Pavements	. 86
12	Hot-Mix Asphalt Surface Correction	. 90
13	Pavement and Shoulder Resurfacing	. 92
14	Patching with Hot-Mix Asphalt Overlay Removal	. 93
15	Polymer Concrete	
16	Reserved	. 97
17	Bicycle Racks	. 98
18	Temporary Portable Bridge Traffic Signals	
19	Nighttime Inspection of Roadway Lighting	. 102
20	English Substitution of Metric Bolts	
21	Calcium Chloride Accelerator for Portland Cement Concrete	. 104
22	Quality Control of Concrete Mixtures at the Plant	. 105
23	Quality Control/Quality Assurance of Concrete Mixtures	. 113
24	Reserved	. 129
25	Reserved	. 130
26	Temporary Raised Pavement Markers	. 131
27	Restoring Bridge Approach Pavements Using High-Density Foam	. 132
28	Portland Cement Concrete Inlay or Overlay	. 135
29	Portland Cement Concrete Partial Depth Hot-Mix Asphalt Patching	. 139
30	Longitudinal Joint and Crack Patching	. 142
31	Concrete Mix Design – Department Provided	. 144
32	Station Numbers in Pavements or Overlays	145

BDE Special Provisions

Numeric Index

REVISED INDEX

NUMERIC DESIGN INTERIM SPECIAL PROVISIONS (ISP's)

Get a copy of the current check list from the Program Development Secretary, indicate which ISP's are to be included in your set of special provisions, fill in any blanks as indicated on the check list, and include with your set of special provisions to be sent to Springfield where they will be inserted.

	1 1	
<u>Standard</u> Spec. No.	PC No.	Item
106.01	10601	Source of Supply and Quality Requirements
107.01	10701	Construction Air Quality – Diesel Retrofit
107.11a	10711a	Railroad Protective Liability Insurance
107.19a	10719a	Building Removal with Asbestos Abatement
107.19d	10719d	Building Removal
107.38	10738	Bridge Demolition Debris
107.40	10740	Compensable Delay Costs
108.05	10805	Working Days
108.05a	10805a	Completion Date (Via Calendar Days)
108.05b	10805b	Completion Date (Via Calendar Days) Plus Working Days
108.06	10806	Training Special Provision
108.06a	10806a	Disadvantaged Business Enterprise Participation
108.06b	10806b	Weekly DBE Trucking Reports
108.06c	10806c	Illinois Works Apprenticeship Initiative – State Funded Contracts
109.00a	10900a	Steel Cost Adjustment
109.01	10901	Bituminous Materials Cost Adjustments
109.03	10903	Fuel Cost Adjustment
109.13	10913	Submission of Payroll Records
109.14	10914	Subcontractor and DBE Payment Reporting
109.12	10912	Subcontractor Mobilization Payments
214.03	21403	Grading and Shaping Ditches
250.07	25007	Seeding

NUMERIC DESIGN INTERIM SPECIAL PROVISIONS (ISP's)

<u>Standard</u> Spec. No.	PC No.	Item
303.00	30300	Aggregate Subgrade Improvement
403.00	40300	Bituminous Surface Treatment with Fog Seal
405.50	40550	Ultra-Thin Bonded Wearing Course
406.00f	40600f	Material Transfer Device
406.06	40606	Hot-Mix Asphalt – Longitudinal Joint Sealant
406.11	40611	Surface Testing of Pavements - IRI
542.03	54203	Corrugated Plastic Pipe (Culvert and Storm Sewer)
632.00	63200	High Tension Cable Median Barrier Removal
701.00	70100	Automated Flagger Assistance Devices
701.03	70103	Work Zone Traffic Control Devices
701.08	70108	Vehicle and Equipment Warning Lights
701.13	70113	Traffic Spotters
701.15	70115	Speed Display Trailer
780.14	78014	Green Preformed Thermoplastic Pavement Markings
888.00	88800	Accessible Pedestrian Signals (APS)
1010.01	101001	Blended Finely Divided Minerals
1032.05	103205	Performance Graded Asphalt Binder
1061.05	106105	Waterproofing Membrane System

s:\mgr1\winword\progdev\special provisions\interim spec provs\isp numeric index.doc

BDE Special Provisions

Alphabetic Index

REVISED INDEX

ALPHABETIC LIST OF DESIGN INTERIM SPECIAL PROVISIONS (ISP's)

Get a copy of the current check list from the Program Development Secretary, indicate which ISP's are to be included in your set of special provisions, fill in any blanks as indicated on the check list, and include with your set of special provisions to be sent to Springfield where they will be inserted.

<u>Standard</u> Spec. No.	PC No.	ltem
888.00	88800	Accessible Pedestrian Signals (APS)
303.00	30300	Aggregate Subgrade Improvement
701.00	70100	Automated Flagger Assistance Devices
109.01	10901	Bituminous Materials Cost Adjustment
403.00	40300	Bituminous Surface Treatment with Fog Seal
1010.01	101001	Blended Finely Divided Minerals
107.38	10738	Bridge Demolition Debris
107.19a	10719a	Building Removal with Asbestos Abatement
107.19d	10719d	Building Removal
107.40	10740	Compensable Delay Costs
108.05a	10805a	Completion Date (Via Calendar Days)
108.05b	10805b	Completion Date (Via Calendar Days) Plus working Days
107.01	10701	Construction Air Quality – Diesel Retrofit
542.03	54203	Corrugated Plastic Pipe (Culvert and Storm Sewer)
108.06a	10806a	Disadvantaged Business Enterprise Participation
109.03	10903	Fuel Cost Adjustment
214.03	21403	Grading and Shaping Ditches
780.14	78014	Green Preformed Thermoplastic Pavement Markings
632.00	63200	High Tension Cable Median Barrier Removal
406.06	40606	Hot-Mix Asphalt – Longitudinal Joint Sealant
108.06c	10806c	Illinois Works Apprenticeship Initiative – State Funded Contracts

,

.

REVISED INDEX

ALPHABETIC LIST OF DESIGN INTERIM SPECIAL PROVISIONS (ISP's)

<u>Standard</u> Spec. No.	<u>PC</u> <u>No.</u>	<u>ltem</u>
406.00f	40600f	Material Transfer Device
1032.05	103205	Performance Graded Asphalt Binder
107.11	10711a	Railroad Protective Liability Insurance
250.07	25007	Seeding
106.01	10601	Source of Supply and Quality Requirements
701.15	70115	Speed Display Trailer
109.00	10900a	Steel Cost Adjustment
109.14	10914	Subcontractor and DBE Payment Reporting
109.12	10912	Subcontractor Mobilization Payments
109.13	10913	Submission of Payroll Records
406.11	40611	Surface Testing of Pavements – IRI
701.13	70113	Traffic Spotters
108.06	10806	Training Special Provision
405.50	40550	Ultra-Thin Bonded Wearing Course
701.08	70108	Vehicle and Equipment Warning Lights
1061.05	106105	Waterproofing Membrane System
108.06b	10806b	Weekly DBE Trucking Reports
108.05	10805	Working Days
701.03	70103	Work Zone Traffic Control Devices

s:\mgr1\winword\progdev\special provisions\interim spec provs\isp alpha index.doc

-2-

District Special Provisions

Numeric Index

<u>Standard</u> Specifications	Item/Description	<u>Doc. #</u>
105.00	CONSTRUCTION STATION LAYOUT	10500
105.01	CONSTRUCTION LAYOUT RESPONSIBILITY	10501
105.02	CONSTRUCTION LAYOUT UTILIZING GPS EQUIPMENT	10502
105.03	CONSTRUCTION LAYOUT EQUIPMENT	10503
105.07	REMOVAL OF ABANDONED UNDERGROUND UTILITIES	10507
105.07a	STATUS OF UTILITIES/UTILITIES TO BE ADJUSTED	10507a
105.07b	UTILITIES - LOCATION/INFORMATION ON PLANS	10507b
107.12	REQUIREMENTS WHEN WORKING WITH THE RAILROAD	10712
107.13a	PROTECTION OF THE ILLINOIS RIVER	10713a
107.13b	MAINTENANCE OF NAVIGATION	10713b
107.31	LOCATION OF UNDERGROUND STATE MAINTAINED FACILITIES	10731
107.32	RIGHT-OF-WAY RESTRICTIONS	10732
108.05a	DATE OF COMPLETION	10805a
108.05b	DATE OF COMPLETION (PLUS WORKING DAYS)	10805b

<u>Standard</u> Specifications	Item/Description	<u>Doc. #</u>
205.00	GEOTECHNICAL REINFORCEMENT	20500
205.04	EMBANKMENT RESTRICTIONS	20504
250.00	SEEDING, MINOR AREAS	25000
250.06a	MOWING	25006a
250.06b	MOWING	250.06b
253.00b	SEEDLINGS	25300b
281.00	GROUT FOR USE WITH RIPRAP	28100

<u>Standard</u> Specifications	Item/Description	<u>Doc. #</u>
301.01	PROOF ROLLING	30101
301.03	SUBGRADE TREATMENT	30103
302.00	SOIL MODIFICATION	30200
311.00	ROCKFILL	31100
353.00	SAWCUTTING OF PCC BASE COURSE AND BASE COURSE WIDENING	35300
355.00	TEMPORARY PAVEMENT	35500
356.00	TEMPORARY BASE COURSE WIDENING	35600

District Special Provisions

<u>Standard</u> Specifications	Item/Description	Doc. #
406.00	CLEAN EXISTING PAVEMENT EDGE JOINT	
400.00	CLEAN EXISTING PAVEMENT EDGE JOINT	40600
406.04a	HOT-MIX ASPHALT SURFACE COURSE SURFACE TESTS	40604a
406.07	HOT-MIX ASPHALT – TACK COAT (SPECIAL) OPTIONS	40607
407.13	GROOVED-IN RUMBLE STRIP	40713
424.01	SIDEWALK DRAINS	42401
424.02	TEMPORARY SIDEWALKS	42402
440.00	PARTIAL DEPTH PATCHING	44000
440.02	LONGITUDINAL JOINT REPAIR	44002
440.03	PROTECTION OF FRAMES AND LIDS OF UTILITY STRUCTURES	44003
440.03a	HOT-MIX ASPHALT SURFACE REMOVAL, **" (** MM)	44003a
440.03b	HOT-MIX ASPHALT SURFACE REMOVAL, **" (** MM)	44003b
440.03d	PAVEMENT DRAINAGE AFTER COLD MILLING	44003d
440.03e	PAVEMENT PATCHING WITH HOT-MIX ASPHALT SURFACE REMOVAL	44003e
440.04	HOT-MIX ASPHALT JOINT TRIMMING	44004
482.05	HOT-MIX ASPHALT SHOULDER RESURFACING REQUIRED TO BE CONSTUCTED SIMULTANEOUSLY WITH MAINLINE PAVING	48205
482.06	HOT-MIX ASPHALT SHOULDER RESURFACING CONSTRUCTED SIMULTANEOUSLY WITH MAINLINE PAVING	48206

•

<u>Standard</u> Specifications	Item/Description	Doc. #
501.03	CONCRETE HEADWALL REMOVAL	<u>50103</u>
501.04	CONCRETE HANDRAIL REMOVAL	50104
503.01	GRANULAR BACKFILL FOR STRUCTURES	50301
503.02	SURFACE FILLER, SPECIAL (GALLON)	50302
503.07	PCC PLACEMENT BY PUMP REQUIREMENTS	50307
503.12a	FLOOR DRAIN EXTENSIONS	50312a
503.12	PLUG EXISTING DRAINS	50312
503.19	PROTECTIVE COAT (SPECIAL)	50319
542.00	SEEPAGE COLLAR	54200
542.01	REMOVE AND RELAY PIPE CULVERT (SPECIAL)	54201
542.02	PIPE CULVERTS (JACKED)	54202
542.04e	BACKFILL - PIPE CULVERTS	54204e
550.00	STORM SEWER (WATER MAIN QUALITY PIPE)	55000
550.07	BACKFILL, BUILDING REMOVAL	55007
552.00	STEEL PIPE CULVERT, SPECIAL (JACKED) *" (* MM)	55200
552.01	(*STORM SEWER/PIPE CULVERT) JACKED IN PLACE, *" (* MM)	55201
561.00	STEEL CASINGS (*") INCHES	56100
561.01	STEEL CASINGS (*") INCHES	56101
593.00	SLOPE WALL SLURRY PUMPING	59300

<u>Standard</u> Specifications	Item/Description	<u>Doc. #</u>
602.00a	INLETS, TYPE G-1	60200a
602.00b	INLETS, TYPE G-1, SPECIAL	60200b
602.00c	INLETS, TYPE G-1, DOUBLE, SPECIAL	60200c
602.00d	INLET-MANHOLE, TYPE G-1, 4' (1.2 M) DIAMETER	60200d
602.00e	INLET-MANHOLE, TYPE G-1, 4' (1.2 M) DIAMETER, SPECIAL	60200e
602.00f	INLET-MANHOLE, TYPE G-1, 5' (1.5 M) DIAMETER	60200f
602.00g	INLET-MANHOLE, TYPE G-1, 5' (1.5 M) DIAMETER, SPECIAL	60200g
602.00h	INLET-MANHOLE, TYPE G-1, 5' (1.5 M) DIAMETER, DOUBLE, SPECIAL	60200h
602.00i	INLET-MANHOLE, TYPE G-1, 8' (2.4 M) DIAMETER, DOUBLE, SPECIAL	60200i
602.00j	MANHOLE TO BE ADJUSTED WITH NEW TYPE G-1 FRAME AND GRATE	60200j
602.00k	TEMPORARY INLET DRAINAGE TREATMENT	60200k
602.001	INLETS, TYPE G-2	602001
602.00m	INLETS, TYPE G-1, DOUBLE	60200m
602.00n	INLETS, TYPE "*", WITH SPECIAL FRAME AND GRATE	60200n
602.000	MANHOLE, TYPE A, OF THE DIAMETER SPECIFIED WITH SPECIAL FRAME AND GRATE	60200o
605.04	FILLING EXISTING INLETS	60504
605.04a	FILLING EXISTING CULVERTS	60504a
605.04b	FILLING DRAINAGE STRUCTURES	60504b
606.08	ISLAND PAVEMENT CONSTRUCTED ON EXISTING PAVEMENT	60608
606.12	DRAINAGE HOLES	60612

District Special Provisions

<u>Standard</u>		
Specifications	Item/Description	<u>Doc. #</u>
630.01	GUARDRAIL AGGREGATE EROSION CONTROL	63001
631.11c	TRAFFIC BARRIER TERMINALS	63111c
632.00	GUARD POST REMOVAL	63200
635.00	FLEXIBLE DELINEATOR MAINTENANCE	63500
635.01	FLEXIBLE DELINEATORS	63501
635.02	RECOVERABLE DELINEATORS	63502
667.04	PERMANENT SURVEY MARKER, TYPE I, BRIDGE PLACEMENT	66704
668.02	PERMANENT SURVEY TIES	66802
670.05	EQUIPMENT VAULT FOR NUCLEAR TESTING EQUIPMENT	67005
680.00a	RAILROAD TIES REMOVAL AND DISPOSAL	68000a
680.00	RAILROAD TRACK RAIL REMOVAL	68000
683.00	MORTARED STONE WALL	68300

District Special Provisions

Standard Specifications	Item/Description	<u>Doc. #</u>
701.00	TRAFFIC CONTROL PLAN	70100
701.01	FLAGGERS	70101
701.08b	TRAFFIC CONTROL AND PROTECTION STANDARD 701331 (SPECIAL)	70108b
701.14	WIDTH RESTRICTION SIGNING	70114
701.20	TRAFFIC CONTROL AND PROTECTION STANDARD BLR 21 AND BLR 21 (SPECIAL)	70120
701.21	TRAFFIC CONTROL AND PROTECTION STANDARD BLR 22 AND BLR 22 (SPECIAL)	70121
704.00a	TEMPORARY CONCRETE BARRIER REFLECTORS	70400a
704.00	TEMPORARY CONCRETE BARRIER, STATE OWNED AND TEMPORARY CONCRETE BARRIER TERMINAL SECTIONS, STATE OWNED	70400
733.00	RE-TIGHTENING ANCHOR BOLTS FOR CANTILEVER SIGN STRUCTURES	73300
782.01	LINEAR DELINEATOR PANELS, 4 INCH	78201

District Special Provisions

<u>Standard</u> Specifications	Item/Description	<u>Doc. #</u>
815.00	TRENCH & BACKFILL, SPECIAL FOR CONDUIT INSTALLATION BENEATH BITUMINOUS SHOULDERS	81500
886.00a	DETECTOR LOOPS, TYPE 1	88600a
886.01	ADJUST EXISTING DETECTOR LOOP RISER	88601
886.02	MISCELLANEOUS ELECTRICAL WORK	88602

District Special Provisions

<u>Standard</u> Specifications

Item/Description

<u>Doc. #</u>

<u>Standard</u> Specifications	Item/Description	<u>Doc. #</u>
1004.00	PCC SLIPFORM PAVING AGGREGATE OPTIMIZATION	100400
1004.02	PCC SUPERSTRUCTURE AGGREGATE OPTIMIZATION	100402
1004.03b	COARSE AGGREGATE FOR BITUMINOUS COURSES, CLASS A	d100403b
1004.04	AGGREGATE QUALITY	d100404
1020.13	MEMBRANE CURING METHOD	102013
1103.00	PCC QMP ELECTRONIC REPORTS SUBMITTAL	110300
1103.03	PCC AUTOMATIC BATCHING EQUIPMENT	110303

District Special Provisions

Alphabetic Index
.

Item/Description	Standard Specification	<u>Filename</u>
ADJUST DETECTOR LOOP RISER	886.01	88601
AGGREGATE QUALITY	1004.04	100404
BACKFILL - PIPE CULVERTS	542.04e	54204e
BACKFILL, BUILDING REMOVAL	550.07	55007
CLEAN EXISTING PAVEMENT EDGE JOINT	406.00	40600
COARSE AGGREGATE FOR BITUMINOUS COURSES, CLASS A	1004.03b	100403b
CONCRETE HANDRAIL REMOVAL	501.04	50104
CONCRETE HEADWALL REMOVAL	501.03	50103
CONSTRUCTION LAYOUT RESPONSIBILITY	105.01	10501
CONSTRUCTION LAYOUT UTILIZING GPS EQUIPMENT	105.02	10502
CONSTRUCTION LAYOUT EQUIPMENT	105.03	10503
CONSTRUCTION STATION LAYOUT	105.00	10500
DATE OF COMPLETION	108.05a	10805a
DATE OF COMPLETION (PLUS WORKING DAYS)	108.05b	10805b
DETECTOR LOOPS, TYPE 1	886.00a	88600a
DRAINAGE HOLES	606.12	60612
EMBANKMENT RESTRICTIONS	205.04	20504
EQUIPMENT VAULT FOR NUCLEAR TESTING EQUIPMENT	670.05	67005
FILLING EXISTING CULVERTS	605.04a	60504a
FILLING DRAINAGE STRUCTURES	605.04b	60504b
FILLING EXISTING INLETS	605.04d	60504d
FLAGGERS	701.01	70101
FLEXIBLE DELINEATOR MAINTENANCE	635.00	63500
FLEXIBLE DELINEATORS	635.01	63501

Item/Description	Standard Specification	<u>Filename</u>
FLOOR DRAIN EXTENSION	503.12a	50312a
GEOTECHNICAL REINFORCEMENT	205.00	20500
GRANULAR BACKFILL FOR STRUCTURES	503.01	50301
GROOVED-IN RUMBLE STRIP	407.13	40713
GROUT FOR USE WITH RIPRAP	281.00	28100
GUARD POST REMOVAL	632.00	63200
GUARDRAIL AGGREGATE EROSION CONTROL	630.01	63001
HOT-MIX ASPHALT JOINT TRIMMING	440.04	44004
HOT-MIX ASPHALT SHOULDER RESURFACING CONSTRUCTED SIMULTANEOUSLY WITH MAINLINE PAVING	482.06	48206
HOT-MIX ASPHALT SHOULDER RESURFACING REQUIRED TO BE CONSTRUCTED SIMULTANEOUSLY WITH MAINLINE PAVING	482.05	48205
HOT-MIX ASPHALT SURFACE COURSE SURFACE TESTS	406.04a	40604a
HOT-MIX ASPHALT SURFACE REMOVAL, **" (** MM)	440.03a	44003a
HOT-MIX ASPHALT SURFACE REMOVAL, **" (** MM)	440.03b	44003b
HOT-MIX ASPHALT – TRACKLESS TACK COAT (SPECIAL) OPTIONS	406.07	40607
INLET-MANHOLE, TYPE G-1, 4' (1.2 M) DIAMETER	602.00d	60200d
INLET-MANHOLE, TYPE G-1, 4' (1.2 M) DIAMETER, SPECIAL	602.00e	60200e
INLET-MANHOLE, TYPE G-1, 5' (1.5 M) DIAMETER	602.00f	60200f
INLET-MANHOLE, TYPE G-1, 5' (1.5 M) DIAMETER, DOUBLE, SPECIAL	602.00h	60200h
INLET-MANHOLE, TYPE G-1, 5' (1.5 M) DIAMETER, SPECIAL	602.00g	60200g
INLET-MANHOLE, TYPE G-1, 8' (2.4 M) DIAMETER, DOUBLE, SPECIAL	602.00i	60200i
INLETS, TYPE G-1	602.00a	60200a
INLETS, TYPE G-1, DOUBLE	602.00m	60200m
INLETS, TYPE G-1, DOUBLE, SPECIAL	602.00c	60200c
INLETS, TYPE G-1, SPECIAL	602.00b	60200b

Item/Description	Standard Specification	<u>Filename</u>
INLETS, TYPE G-2	602.001	602001
INLETS, TYPE "*", WITH SPECIAL FRAME AND GRATE	602.00n	60200n
ISLAND PAVEMENT CONSTRUCTED ON EXISTING PAVEMENT	606.08	60608
LINEAR DELINEATOR PANELS, 4 INCH	782.01	78201
LOCATION OF UNDERGROUND STATE MAINTAINED FACILITIES	107.31	10731
LONGITUDINAL JOINT REPAIR	440.02	44002
MAINTENANCE OF NAVIGATION	107.13b	1 0713 b
MANHOLE TO BE ADJUSTED WITH NEW TYPE G-1 FRAME AND GRATE	602.00j	60200j
MANHOLE, TYPE A, OF THE DIAMETER SPECIFIED WITH SPECIAL FRAME AND GRATE	602.000	60200o
MEMBRANE CURING METHOD	1020.13	102013
MISCELLANEOUS ELECTRICAL WORK	886.02	88602
MORTARED STONE WALL	683.00	68300
MOWING	250.06a	250.06a
MOWING	250.06b	250.06b
PARTIAL DEPTH PATCHING	440.00	44000
PAVEMENT DRAINAGE AFTER COLD MILLING	440.03c	44003c
PAVEMENT PATCHING WITH HOT-MIX ASPHALT SURFACE REMOVAL	440.03e	44003e
PCC AUTOMATIC BATCHING EQUIPMENT	1103.03	110303
PCC PLACEMENT BY PUMP REQUIREMENTS	503.07	50307
PCC QMP ELECTRONIC REPORTS SUBMITTAL	1103.00	110300
PCC SLIPFORM PAVING AGGREGATE OPTIMIZATION	1004.00	100400
PCC SUPERSTRUCTURE AGGREGATE OPTIMIZATION	1004.02	100402
PERMANENT SURVEY MARKER, TYPE I, BRIDGE PLACEMENT	667.04	66704
PERMANENT SURVEY TIES	668.02	66802

Item/Description	Standard Specification	<u>Filename</u>
PIPE CULVERTS (JACKED)	542.02	54202
PLUG EXISTING DRAINS	503.12	50312
PROOF ROLLING	301.01	30101
PROTECTION OF FRAMES AND LIDS OF UTILITY STRUCTURES	440.03	44003
PROTECTION OF THE ILLINOIS RIVER	107.13a	10713a
PROTECTIVE COAT (SPECIAL)	503.19	50319
RAILROAD TIES REMOVAL AND DISPOSAL	680.00a	68000a
RAILROAD TRACK RAIL REMOVAL	680.00	68000
RECOVERABLE DELINEATORS	635.02	63502
REMOVAL OF ABANDONED UNDERGROUND UTILITIES	105.07	10507
REMOVE AND RELAY PIPE CULVERT (SPECIAL)	542.01	54201
REQUIREMENTS WHEN WORKING WITH THE RAILROAD	107.12	10712
RE-TIGHTENING ANCHOR BOLTS FOR CANTILEVER SIGN STRUCTURES	733.00	73300
RIGHT-OF-WAY RESTRICTIONS	107.32	10732
ROCKFILL	311.00	31100
RUMBLE STRIP	407.14	40714
SAWCUTTING OF PCC BASE COURSE AND BASE COURSE WIDENING	353.00	35300
SEEDING, MINOR AREAS	250.00	25000
SEEDLINGS	253.00b	15300b
SEEPAGE COLLAR	542.00	54200
SIDEWALK DRAINS	424.01	42401
SLOPE WALL SLURRY PUMPING	593.00	59300
SOIL MODIFICATION	302.00	30200
STATUS OF UTILITIES/UTILITIES TO BE ADJUSTED	105.07	10507

ALPHABETIC INDEX OF DISTRICT SPECIAL PROVISIONS

	· · ·	
Item/Description	Standard Specification	<u>Filename</u>
STEEL CASINGS (*") INCHES	561.00	56100
STEEL CASINGS (*") INCHES	561.01	56101
STEEL PIPE CULVERT, SPECIAL (JACKED) *" (* MM)	552.00	55200
STORM SEWER/PIPE CULVERT) JACKED IN PLACE **" (** MM)	552.01	55201
STORM SEWER (WATER MAIN QUALITY PIPE)	550.00	55000
SUBGRADE TREATMENT	301.03	30103
SURFACE FILLER (SPECIAL)	503.02	50302
TEMPORARY BASE COURSE WIDENING	356.00	35600
TEMPORARY CONCRETE BARRIER REFLECTORS	704.00a	70400a
TEMPORARY CONCRETE BARRIER, STATE OWNED & TEMPORARY CONCRETE BARRIER TERMINAL SECTIONS, STATE OWNED	704.00d	70400d
TEMPORARY INLET DRAINAGE TREATMENT	602.00k	60200k
TEMPORARY PAVEMENT	355.00	35500
TEMPORARY SIDEWALKS	424.02	42402
TRAFFIC BARRIER TERMINALS	631.11c	63111c
TRAFFIC CONTROL AND PROTECTION STANDARD 701331 (SPECIAL)	701.08b	70108b
TRAFFIC CONTROL AND PROTECTION STANDARD BLR 21 AND BLR 21 (SPECIAL)	701.20	70120
TRAFFIC CONTROL AND PROTECTION STANDARD BLR 22 AND BLR 22 (SPECIAL)	701.21	701.21
TRAFFIC CONTROL PLAN	701.00	70100
TRENCH & BACKFILL, SPECIAL FOR CONDUIT INSTALLATION BENEATH BITUMINOUS SHOULDERS	815.00	81500
UTILITIES – LOCATIONS/INFORMATION ON PLANS	105.07b	10507b
WIDTH RESTRICTION SIGNING	701.14	70114

s:\mgr1\winword\progdev\special provisions\district spec provs\district spec prov alpha list.doc

BDE Special Provisions

Designer Note: Insert into all federal-aid contracts.

SOURCE OF SUPPLY AND QUALITY REQUIREMENTS (BDE)

Effective: January 2, 2023

Add the following to Article 106.01 of the Standard Specifications:

"The final manufacturing process for construction materials and the immediately preceding manufacturing stage for construction materials shall occur within the United States. Construction materials shall include an article, material, or supply that is or consists primarily of the following.

- (a) Non-ferrous metals;
- (b) Plastic and polymer-based products (including polyvinylchloride, composite building materials, and polymers used in fiber optic cables);
- (c) Glass (including optic glass);
- (d) Lumber;
- (e) Drywall.

Items consisting of two or more of the listed construction materials that have been combined through a manufacturing process, and items including at least one of the listed materials combined with a material that is not listed through a manufacturing process shall be exempt."

Designer Note: This special provision should be inserted into federal and nonfederal aid contracts on the state letting.

SUBMISSION OF PAYROLL RECORDS (BDE)

Effective: April 1, 2021 Revised: November 1, 2022

<u>FEDERAL AID CONTRACTS</u>. Revise the following section of Check Sheet #1 of the Recurring Special Provisions to read:

"STATEMENTS AND PAYROLLS

The payroll records shall include the worker's name, the worker's address, the worker's telephone number when available, the worker's social security number, the worker's classification or classifications, the worker's gross and net wages paid in each pay period, the worker's number of hours worked each day, and the worker's starting and ending times of work each day. However, any Contractor or subcontractor who remits contributions to a fringe benefit fund that is not jointly maintained and jointly governed by one or more employers and one or more labor organization must additionally submit the worker's hourly wage rate, the worker's hourly overtime wage rate, the worker's hourly fringe benefit rates, the name and address of each fringe benefit fund, the plan sponsor of each fringe benefit, if applicable, and the plan administrator of each fringe benefit, if applicable.

The Contractor and each subcontractor shall certify and submit payroll records to the Department each week from the start to the completion of their respective work, except that full social security numbers shall not be included on weekly submittals. Instead, the payrolls shall include an identification number for each employee (e.g., the last four digits of the employee's social security number). In addition, starting and ending times of work each day may be omitted from the payroll records submitted. The submittals shall be made using LCPtracker Pro software. The software is web-based and can be accessed at https://lcptracker.com/. When there has been no activity during a work week, a payroll record shall still be submitted with the appropriate option ("No Work", "Suspended", or "Complete") selected."

<u>STATE CONTRACTS</u>. Revise Item 3 of Section IV of Check Sheet #5 of the Recurring Special Provisions to read:

"3. Submission of Payroll Records. The Contractor and each subcontractor shall, no later than the 15th day of each calendar month, file a certified payroll for the immediately preceding month to the Illinois Department of Labor (IDOL) through the Illinois Prevailing Wage Portal in compliance with the State Prevailing Wage Act (820 ILCS 130). The portal can be found on the IDOL website at <u>https://www2.illinois.gov/idol/Laws-Rules/CONMED/Pages/Prevailing-Wage-Portal.aspx</u>. Payrolls shall be submitted in the format prescribed by the IDOL.

In addition to filing certified payroll(s) with the IDOL, the Contractor and each subcontractor shall certify and submit payroll records to the Department each week from the start to the completion of their respective work, except that full social security numbers

shall not be included on weekly submittals. Instead, the payrolls shall include an identification number for each employee (e.g., the last four digits of the employee's social security number). In addition, starting and ending times of work each day may be omitted from the payroll records submitted. The submittals shall be made using LCPtracker Pro software. The software is web-based and can be accessed at https://cptracker.com/. When there has been no activity during a work week, a payroll record shall still be submitted with the appropriate option ("No Work", "Suspended", or "Complete") selected."

Designer Note: This special provision should be inserted with contracts involving new concrete pavement, PCC overlays, hot-mix asphalt pavement (full-depth), or HMA overlays with a minimum of 2.25 inches total thickness of new HMA material and at least two activities. An activity is defined as either milling or a lift of HMA (binder or surface).

SURFACE TESTING OF PAVEMENTS - IRI (BDE)

Effective: January 1, 2021 Revised: January 1, 2023

<u>Description</u>. This work shall consist of testing the ride quality of the finished surface of pavement sections with new concrete pavement, PCC overlays, full-depth HMA; and HMA overlays with at least 2.25 in. (57 mm) total thickness of new HMA combined with either HMA binder or HMA surface removal, according to Illinois Test Procedure 701, "Ride Quality Testing Using the International Roughness Index (IRI)". Work shall be according to Sections 406, 407, or 420 of the Standard Specifications, except as modified herein.

Hot-Mix Asphalt (HMA) Overlays

Add the following to Article 406.03 of the Standard Specifications:

Revise Article 406.11 of the Standard Specifications to read:

"406.11 Surface Tests. Prior to HMA overlay pavement improvements, the Engineer will measure the smoothness of the existing high-speed mainline pavement. The Contractor shall measure the smoothness of the finished high-speed mainline, low-speed mainline, and miscellaneous pavements after the pavement improvement is complete but within the same construction season. Testing shall be performed in the presence of the Engineer and according to Illinois Test Procedure 701. The pavement will be identified as high-speed mainline, low-speed mainline, or miscellaneous as follows.

(a) Test Sections.

- (1) High-Speed Mainline Pavement. High-speed mainline pavement consists of pavements, ramps, and loops with a posted speed limit greater than 45 mph. These sections shall be tested with an inertial profiling system (IPS).
- (2) Low-Speed Mainline Pavement. Low-speed mainline pavement consists of pavements, ramps, and loops with a posted speed limit of 45 mph or less. These sections shall be tested using a 16 ft. (5 m) straightedge or with an IPS analyzed using the rolling 16 ft. (5 m) straightedge simulation in ProVAL.
- (3) Miscellaneous Pavement. Miscellaneous pavement are segments that either cannot readily be tested by an IPS or conditions beyond the control of the Contractor preclude the achievement of smoothness levels typically achievable with mainline pavement construction. This may include the following examples or as determined by the Engineer.

- Pavement on horizontal curves with a centerline radius of curvature of less than or equal to 1,000 ft. (300 m) and the pavement within the superelevation transition of such curves;
- b. Pavement on vertical curves having a length less than or equal to 200 ft. (60 m) in combination with an algebraic change in tangent grade greater than or equal to 3 percent as may occur on urban ramps or other constricted-space facilities;
- c. The first and last 50 ft. (15 m) of a pavement section where the Contractor is not responsible for the adjoining surface;
- d. Intersections and the 25 ft. (7.6 m) before and after an intersection or end of radius return;
- e. Variable width pavements;
- f. Side street returns, to the end of radius return;
- g. Crossovers;
- h. Pavement connector for bridge approach slab;
- i. Bridge approach slab;
- j. Pavement that must be constructed in segments of 600 ft. (180 m) or less;
- k. Pavement within 25 ft. (7.6 m) of manholes, utility structures, at-grade railroad crossings, or other appurtenances;
- I. Turn lanes; and
- m. Pavement within 5 ft. (1.5 m) of jobsite sampling locations for HMA volumetric testing that fall within the wheel path.

Miscellaneous pavement shall be tested using a 16 ft. (5 m) straightedge.

- (4) International Roughness Index (IRI). An index computed from a longitudinal profile measurement using a quarter-car simulation at a simulation speed of 50 mph (80 km/h).
- (5) Mean Roughness Index (MRI). The average of the IRI values for the right and left wheel tracks.
 - a. MRIo. The MRI of the existing pavement prior to construction.
 - b. MRI_I. The MRI value that warrants an incentive payment.
 - c. MRI_F. The MRI value that warrants full payment.
 - d. MRI_D. The MRI value that warrants a financial disincentive.
- (6) Areas of Localized Roughness (ALR). Isolated areas of roughness, which can cause significant increase in the calculated MRI for a given sublot.

- (7) Sublot. A continuous strip of pavement 0.1 mile (160 m) long and one lane wide. A partial sublot greater than or equal to 264 ft. (80 m) will be subject to the same evaluation as a whole sublot. Partial sublots less than 264 ft. (80 m) shall be included with the previous sublot for evaluation purposes.
- (b) Corrective Work. Corrective work shall be completed according to the following.
 - (1) High-Speed Mainline Pavement. For high-speed mainline pavement, any 25 ft. (7.6 m) interval with an ALR in excess of 200 in./mile (3,200 mm/km) will be identified by the Engineer and shall be corrected by the Contractor. Any sublot having a MRI greater than MRI_D, including ALR, shall be corrected to reduce the MRI to the MRI_F, or replaced at the Contractor's option.
 - (2) Low-Speed Mainline Pavement. Surface variations in low-speed mainline pavement which exceed the 5/16 in. (8 mm) tolerance will be identified by the Engineer and shall be corrected by the Contractor.
 - (3) Miscellaneous Pavements. Surface variations in miscellaneous pavement which exceed the 5/16 in. (8 mm) tolerance will be identified by the Engineer and shall be corrected by the Contractor.

Corrective work shall be completed with pavement surface grinding equipment or by removing and replacing the pavement. Corrective work shall be applied to the full lane width. When completed, the corrected area shall have uniform texture and appearance, with the beginning and ending of the corrected area perpendicular to the centerline of the paved surface.

Upon completion of the corrective work, the surface of the sublot(s) shall be retested. The Contractor shall furnish the data and reports to the Engineer within 2 working days after corrections are made. If the MRI and/or ALR still do not meet the requirements, additional corrective work shall be performed.

Corrective work shall be at no additional cost to the Department.

(c) Smoothness Assessments. Assessments will be paid to or deducted from the Contractor for each sublot of high-speed mainline pavement per the Smoothness Assessment Schedule. Assessments will be based on the MRI of each sublot prior to performing any corrective work unless the Contractor has chosen to remove and replace the pavement. For pavement that is replaced, assessments will be based on the MRI determined after replacement.

The upper MRI thresholds for high-speed mainline pavement are dependent on the MRI of the existing pavement before construction (MRI₀) and shall be determined as follows.

MRI Thresholds (High-Speed		eed, HMA Overlay)
Upper MRI Thresholds ^{1/}	MRI₀ ≤ 125.0 in./mile (≤ 1,975 mm/km)	MRl ₀ > 125.0 in./mile ^{1/} (> 1,975 mm/km)
Incentive (MRII)	45.0 in./mile (710 mm/km)	0.2 × MRI ₀ + 20
Full Pay (MRI _F)	75.0 in./mile (1,190 mm/km)	0.2 × MRI ₀ + 50
Disincentive (MRI _D)	100.0 in./mile (1,975 mm/km)	0.2 × MRI ₀ + 75

1/ MRI₀, MRI_I, MRI_F, and MRI_D shall be in in./mile for calculation.

Smoothness assessments for high-speed mainline pavement shall be determined as follows.

SMOOTHNESS ASSESSMENT SCHEDULE (High-Speed, HMA Overlay)	
Mainline Pavement MRI Range	Assessment Per Sublot ^{1/}
MRI ≤ MRI _I	+ (MRI _I – MRI) × \$20.00 ^{2/}
MRI₁ < MRI ≤ MRI _F	+ \$0.00
MRI _F < MRI ≤ MRI _D	– (MRI – MRI _F) × \$8.00
MRI > MRI _D	- \$200.00

1/ MRI, MRI, MRIF, and MRID shall be in in./mile for calculation.

2/ The maximum incentive amount shall not exceed \$300.00.

Smoothness assessments will not be paid or deducted until all other contract requirements for the pavement are satisfied. Pavement that is corrected or replaced for reasons other than smoothness, shall be retested as stated herein."

Hot-Mix Asphalt (HMA) Pavement (Full-Depth)

Revise the first paragraph of Article 407.03 of the Standard Specifications to read:

"407.03 Equipment. Equipment shall be according to Article 406.03."

Revise Article 407.09 of the Standard Specifications to read:

"407.09 Surface Tests. The finished surface of the pavement shall be tested for smoothness according to Article 406.11, except as follows:

The testing of the existing pavement prior to improvements shall not apply and the smoothness assessment for high-speed mainline pavement shall be determined according to the following table.

SMOOTHNESS ASSESSMENT SCHEDULE (High-Speed, Full-Depth HMA)	
Mainline Pavement MRI, in./mile (mm/km)	Assessment Per Sublot ^{1/}
≤ 45.0 (710)	+ (45 – MRI) × \$45.00 ^{2/}
> 45.0 (710) to 75.0 (1,190)	+ \$0.00
> 75.0 (1,190) to 100.0 (1,580)	– (MRI – 75) × \$20.00
> 100.0 (1,580)	- \$500.00

1/ MRI shall be in in./mile for calculation.

2/ The maximum incentive amount shall not exceed \$800.00."

Portland Cement Concrete Pavement

Delete Article 420.03(i) of the Standard Specifications.

Revise Article 420.10 of the Standard Specifications to read:

"420.10 Surface Tests. The finished surface of the pavement shall be tested for smoothness

according to Article 406.11, except as follows.

The testing of the existing pavement prior to improvements shall not apply. The Contractor shall measure the smoothness of the finished surface of the pavement after the pavement has attained a flexural strength of 250 psi (3,800 kPa) or a compressive strength of 1,600 psi (20,700 kPa).

Membrane curing damaged during testing shall be repaired as directed by the Engineer at no additional cost to the Department.

(a) Corrective Work. No further texturing for skid resistance will be required for areas corrected by grinding. Protective coat shall be reapplied to areas ground according to Article 420.18 at no additional cost to the Department.

Jointed Portland cement concrete pavement corrected by removal and replacement, shall be corrected in full panel sizes.

(b) Smoothness Assessments. Smoothness assessment for high-speed mainline pavement shall be determined as follows.

SMOOTHNESS ASSESSMENT SCHEDULE (High-Speed, PCC)	
Mainline Pavement MRI, in./mile (mm/km) ^{3/}	Assessment Per Sublot 1/
≤ 45.0 (710)	+ (45 – MRI) × \$60.00 ^{2/}
> 45.0 (710) to 75.0 (1,190)	+ \$0.00
> 75.0 (1,190) to 100.0 (1,580)	– (MRI – 75) × \$37.50
> 100.0 (1,580)	- \$750.00

- 1/ MRI shall be in in./mile for calculation.
- 2/ The maximum incentive amount shall not exceed \$1200.00.
- 3/ If pavement is constructed with traffic in the lane next to it, then an additional 10 in./mile will be added to the upper thresholds."

Removal of Existing Pavement and Appurtenances

Revise the first paragraph of Article 440.04 of the Standard Specifications to read:

"440.04 HMA Surface Removal for Subsequent Resurfacing. The existing HMA surface shall be removed to the depth specified on the plans with a self-propelled milling machine. The removal depth may be varied slightly at the discretion of the Engineer to satisfy the smoothness requirements of the finished pavement. The temperature at which the work is performed, the nature and condition of the equipment, and the manner of performing the work shall be such that the milled surface is not torn, gouged, shoved or otherwise damaged by the milling operation. Sufficient cutting passes shall be made so that all irregularities or high spots are eliminated to the satisfaction of the Engineer. When tested with a 16 ft. (5 m) straightedge, the milled surface shall have no surface variations in excess of 3/16 in. (5 mm)."

General Equipment

Revise Article 1101.04 of the Standard Specifications to read:

"1101.04 Pavement Surface Grinding Equipment. The pavement surface grinding device shall have a minimum effective head width of 3 ft. (0.9 m).

- (a) Diamond Saw Blade Machine. The machine shall be self-propelled with multiple diamond saw blades.
- (b) Profile Milling Machine. The profile milling machine shall be a drum device with carbide or diamond teeth with spacing of 0.315 in. (8 mm) or less and maintain proper forward speed for surface texture according to the manufacturer's specifications."

Designer Note: This special provision should be used on two-lane highways where two-way traffic will be maintained over one lane of pavement in segments where no sideroads or entrances require deployment of additional flaggers. Applications include rural milling and/or resurfacing projects, bridge maintenance projects, haul road crossings, pavement patching, or other similar projects with slow moving or stationary operations where the use of a flagger is required. AFADs should not be used on projects with numerous intersections where additional flaggers are required to control traffic.

AUTOMATED FLAGGER ASSISTANCE DEVICES (BDE)

Effective: January 1, 2008 Revised: April 1, 2023

<u>Description</u>. This work shall consist of furnishing and operating automated flagger assistance devices (AFADs) as part of the work zone traffic control and protection for two-lane highways where two-way traffic is maintained over one lane of pavement in segments where no sideroads or entrances require deployment of additional flaggers. Use of these devices shall be at the option of the Contractor.

<u>Equipment</u>. AFADs shall be the STOP/SLOW or Red/Yellow Lens type mounted on a trailer or moveable cart meeting the requirements of the MUTCD and NCHRP 350 or MASH 2016, Category 4.

<u>General</u>. AFADs shall be placed at each end of the traffic control, where a flagger is shown on the plans. The AFAD shall be setup within five degrees of vertical.

Flagger symbol signs as shown on the plans shall be replaced with "BE PREPARED TO STOP" signs when the AFAD is in operation.

Personal communication devices shall not be used to operate the AFAD.

<u>Flagging Requirements</u>. Flaggers and flagging requirements shall be according to Article 701.13 of the Standard Specifications and the following.

Each AFAD shall be operated by a flagger trained to operate the specific AFAD to be deployed. A minimum of two flaggers shall be on site at all times during operation. Each flagger shall be positioned outside the lane of traffic and near each AFAD's location.

Flagging equipment required for traditional flagging shall be available near each AFAD location in the event of AFAD equipment malfunction/failure.

For nighttime flagging, the AFAD and flagger shall be illuminated according to Article 701.13 of the Standard Specifications.

When not in use, AFADs will be considered non-operating equipment and shall be stored according to Article 701.11 of the Standard Specifications.

<u>Basis of Payment</u>. This work will not be paid for separately but shall be considered as included in the cost of the various traffic control items included in the contract.

District Special Provisions

•

Designer Note: Use this special when applying the acrylic paint listed below to the parapets of an existing structure. Do not use unless requested by the Bridge Maintenance Engineer. This is **NOT** the standard Boiled Linseed Oil item.

PROTECTIVE COAT (SPECIAL)

Effective April 23, 2010 Revised April 1, 2023

This work consist of applying a protective coat system as specified herein, on concrete parapet surfaces as shown on the plans and as directed by the Engineer.

Materials. The concrete coating shall meet the following material requirements:

Color – Grey Texture – Smooth Type – One-component, elastomeric, crack-bridging, anti-carbonation, water vapor permeable, acrylic protective coating.

Weather Resistance – The product shall be intended for exterior applications.

Acceptance of the product will be based on the Manufacturer's Technical Data Sheet or a letter from the Manufacturer stating the product meets the Department's material specifications.

- A. Properties of the elastomeric acrylic coating:
 - 1. Pot Life: indefinite.
 - 2. Moisture Vapor permeability (ASTM E96) 14.5 perms.
 - Tensile Properties (ASTM D-412 Modified) Elongation at break 625% min at 73°F (23°C) 225% min at 0°F (-18°C)
 - 4. Resistance to wind-driven rain (TT-C-555B): No passage of water through coating.
 - 5. Weathering (ASTM G-23) 10,000 hours excellent, no chalking or cracking.

<u>Construction</u>. The concrete surface to be coated shall be sound, dry and clean of any foreign material. Surface Preparation shall be according to the Manufacturer's specifications, except blast cleaning or power washing (3,000 psi min.) will be required. If the surface becomes soiled as determined by the Engineer, after either the initial cleaning or after the first coating, the Contractor shall clean the surface at no additional cost to the Department. Crack and surface defect repairs to the existing concrete parapet shall be performed prior to coating according to the Special Provision for "Surface Filler, Special". Mixing, application, and curing of the coating shall be according to the manufacturer's specifications, except application by spraying will not be allowed. A manufacturer's technical representative shall be present on the first day of the surface preparation operations and the first day of coating operations to ensure correct interpretation of the Manufacturer's specifications.

Do not apply material if it is raining or snowing, or if such conditions are imminent. Minimum application temperature 40°F (5°C) and rising.

The protective coat shall be applied in two coats. The application rate per coat shall produce a dry film thickness between 200-280 microns (8-11 mils). The final dry film thickness of protective coat system shall be between 400-560 microns (16 and 22 mils). Any additional coatings or removal of

coatings to stay within the total system range shall be the Contractors responsibility and shall be accomplished at no additional cost to the Department.

The Contractor shall protect pedestrian, vehicular, watercraft, or other traffic upon or underneath the structure and/or roadway and also all portions of the structure and/or roadway against damage or disfigurement during surface preparation and protective coat operations. When doing surface preparation or applying the protective coat over waterways, the Contractor shall implement such controls as are necessary to avoid contamination of the water, spills into the water, or films from collecting on the water surface during operations. If the Engineer determines that the protection methods are not effective, the Engineer will withdraw approval of operations until such time when protective measures are approved.

<u>Method of Measurements</u>. This work will be measured for payment and the area computed in Square Meters (Square Yards) of parapet wall surface covered, complete in place.

Basis of Payment. The protective coat will be paid for at the contract unit price per Square Yard for PROTECTIVE COAT (SPECIAL).