

F.A.P. RTE.	SECTION		COUNTY	TOTAL	SHEET NO
326	*		VICHENRY	502	284
STA.			TO ST	Α.	
FED. ROAD DIST. NO		ILLINGIS	FED.	AID PROJECT:	

# TEMPORARY SEQUENCE OF OPERATION

MOVEMENT						5—	1							₽	1	P 6 1			5	<b>↑</b>	>				F	2	— 6 — 6	)					P	<u> </u>	<b>&gt;</b>			<b>-</b>	<b>↑</b>   P	AMPAIRA GORDON AND AND AND AND AND AND AND AND AND AN		F
PHASE					1	+	. [	5						1	+	6			2	+5						2	+6							3					4			L
INTERVAL		1	2A	2B	3 A	3B	3C	3D	4A 4	B 4	C 4	D	5 (	6 7A	A 75	B 7C	7D	8	9	10A	10B	11	12	13A 1	3B 130	13D	14A	14B   1	5A 15	5B 15	C 15	D 16	17	18A	18B	19	20	21A	21B 2	21C :	21D	А
CHANGE TO			1+	-6		2+5	5			2+6			Ø/	Ø	-	2+6	-1.	\$	ø	2-	+6				3, 4 1+5		1-	-6		2+5				4 1+ 1+ 2+ 2+	+6 +5				1+5 1+6 2+5 2+6	6 5		S
ILLINOIS ROUTE 47 NEAR RIGHT AND FAR RIGHT SPAN WIRE SIGNALS	N/B	R	R	R	R	R	R	R	R	R	R	R	R	RI	R	R R	R	G	G	G	G	G	G	Y	R R	R	Υ	R	G	G	G G	R	R	R	R	R	R	R	R	R	R	R
ILLINOIS ROUTE 47 TWO FAR LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	N/B	<b>←</b> G	<b>←</b> Y	◆R	<b>←</b> G	<b>←</b> G·	<b>←</b> G	<b>←</b> G	<b>←</b> Y ◆	R ◆	⊦R ◀	⊦R  •	+R •	-R F	R <b>←</b>	R ◆R	◆R	<b>+</b> G	<b>◆</b> G	<b>◆</b> Υ	◆R	◆R	◆R	<b>←</b> R <b>←</b>	R <b>←</b> R	◆R	<b>←</b> R	<b>←</b> R <b>←</b>	R <b>◆</b> F	R ←	R <b>←</b> R	<b>←</b> R	◆R	◆R	◆R	◆R	◆R	<b>,</b> ←R	◆R ◆	<b>←</b> R •	<b>4</b> R <b>4</b>	-R
ILLINOIS ROUTE 47, NORTH OF TRACK RIGHT LOW MOUNT AND TWO RIGHT SPAN WIRE SIGNALS	S/B	R	R	R	R	R	R	R	R	3 1	R	R	G	G C	3 (	G G	G	R	R	R	R	G	G	Υ	R R	R	G	G	Y	R	RR	R	R	R	R	R	R	R	R	R	R	R
ILLINOIS ROUTE 47, NORTH OF TRACK LOW MOUNT IN BARREL (ON LEFT) AND TWO LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	S/B	<b>←</b> G	<b>+</b> G	<b>←</b> G •	rΥ	◆R	◆R	◆R	•Y •	R 🛧	- R •	- R •	+ G ◆	-G +	-Y <b>4</b>	R <b>←</b> R	◆ R	◆R	<b>←</b> R	◆R	◆R	◆R	<b>←</b> R	<b>←</b> R •	R +R	<b>+</b> R	◆R	<b>←</b> R •	-R •	R +	R ◆F	₹ <b>4</b> R	◆R	◆R	◆R	◆R	◆R	◆R	◆R •	<b>←</b> R ·	<b>←</b> R •	←R
ILLINOIS ROUTE 47, SOUTH OF TRACK NEAR RIGHT AND TWO FAR RIGHT SPAN WIRE SIGNALS	S/B	R	R	R	R	R	R	R	R f	R F	R	R	G	G G	; (	G G	G	3	R	R	R	G	G	G	G Y	R	G	G	G G	3	/ R	R	R	R	R	R	R	R	R	R	R	R
ILLINOIS ROUTE 47, SOUTH OF TRACK TWO FAR LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	S/B	<b>←</b> G	<b></b> G	<b>←</b> G	<b>←</b> G	<b>←</b> G	<b>◆</b> Y	◆R	<b>←</b> G <b>←</b>	- G 👍	- Y 👍	R .	<b>←</b> G <b>←</b>	- G 🔸	G ←	G ← Y	<b>∙</b> R	<b>-</b> R	◆R	◆R	◆R	◆R	<b>+</b> R	<b>+</b> R <b>+</b>	R <b>←</b> R	◆R	◆R	◆R ·	-R -	R +	R ←R	+R	◆R	◆R	<b>◆</b> R	◆R	◆R	◆R	◆R •	◆R	<b>+</b> R <b>•</b>	◆R
MAIN STREET NEAR SIDE SPAN WIRE SIGNAL	E/B	R	R	R	R	R	R	R	R	R	R	R	R	R F	7 F	R R	R	R	R	R	R	R	R	R F	₹ R	R	R	R	R F	7	R R	G	G	Y	R	R	R	R	R	R	R	R
MAIN STREET FAR SPAN WIRE SIGNALS	E/B	R	R	R	R	R	R	R	R	R	R	R	R	R F	R F	R R	R	R	R	R	R	R	R	R F	R R	R	R	R	R F	₹	RR	G <del>4</del> (	G G ←G	Y	R	R	R	R	R	R	R	R
MAIN STREET, EAST OF TRACK LOW MOUNT IN BARREL (ON LEFT), SPAN WIRE, AND RIGHT LOW MOUNT SIGNALS	W/B	R	R	R	R	R	R	R	R	R	R	R	R	R F	R F	R R	R	R	R	R	R	R	R	R f	R R	R	R	R	R F	7 1	R R	R	R	R	R	G	G	Y	R	R	R	R
MAIN STREET, WEST OF TRACK FAR SPAN WIRE SIGNALS	W/B	R	R	R	R	R	R	R	R	R	R	R	R	R F	R F	R R	R	R	R	R	R	R	R	R F	R	R	R	R	R F	R F	R R	R	R	R	R	G <b>←</b> G	G <b>←</b> G	G <b>←</b> G	G <b>←</b> G	Y	R	R
PEDESTRIAN SIGNAL CROSSING MAIN STREET ON EAST SIDE OF ILLINOIS ROUTE 47		Н	Н	Н	-	Н	Н	Н	Н	Н	Н	Н	Н	Н	+ +	Н	Н	* P	** FH	Н	Н	* P	* * FH	Н	НН	Н	Н	н	НЬ	Н	H H	Н	Н	Н	Н	Н	F	Н	Н	Н	Н	ORRA
PEDESTRIAN SIGNAL CROSSING MAIN STREET ON WEST SIDE OF ILLINOIS ROUTE 47	7	Н	Н	Н	Н	н	Н	Н	Н	Н	Н	Н	* * P F	* H F	H.   F	Н	Н	Н	Н	Н	Н		* * FH	Н	Н	Н	Н	н	Н	н	4 H	Н	H	Н	Н	Н	Н	Н	Н	Н	H	NRX-
PFDESTRIAN SIGNAL CROSSING ILLINOIS ROUTE 47 ON NORTH SIDE	E	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	H	+   +	НН	Н	Н	Н	Н	Н	Н	Н	Н	НН	Н	Н	Н	4 1	Н	Н	Н	Н	Н	Н	* P	* * FH	Н	Н	Н	H	ORPH
PEDESTRIAN SIGNAL CROSSING ILLINOIS ROUTE 47 ON SOUTH SIDE	E	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	-l	НН	Н	Н	Н	Н	Н	Н	Н	Н	н Н	Н	Н	Н	Н	Н	Н	* P	* * FH	Н	Н	Н	Н	Н	Н	Н	Н	ORRY

P = ILLUMINATED PERSON = WALK

FH = ILLUMINATED FLASHING HAND = FLASHING DON'T WALK

H = ILLUMINATED SOLID HAND = DON'T WALK

PHASE 2 + 6 SHALL BE PLACED ON RECALL.

- \* TO APPEAR ONLY UPON PUSHBUTTON ACTUATION.
- \*\* FLASHING " 10 " IS TO TERMINATE AT THE COMPLETION OF THE PEDESTRIAN INTERVAL CLEARANCE.
- THIS "圈" OR FLASHING "③" INTERVAL MAY FINISH
   TIMING IN THE BI-DIRECTIONAL STRAIGHT THROUGH MOVEMENT IF
   THE LEFT ARROW TIME IS NOT SUFFICIENT TO COMPLETE "厦"
   OR FLASHING "⑤" INTERVALS. "厦" AND FLASHING "⑥" TIMINGS TO BE SET ONLY
   ON THE PHASES WHERE "厦" AND FLASHING "⑥" ARE INDICATED IN

  THE SECULATION OF ORDER TIME. THE SEQUENCE OF OPERATION.

THE TRAFFIC SIGNAL CONTROL EQUIPMENT FOR THIS PROJECT SHALL BE "EAGLE" TO MATCH THE EXISTING ADJACENT SYSTEM.

ILLINOIS DEPARTMENT OF TRANSPORTATION TEMPORARY SEQUENCE OF OPERATION ILLINOIS ROUTE 47 AT MAIN STREET REVISIONS PRE-STAGE, STAGE 1, STAGE 1B, STAGE 1C, STAGE 2, STAGE 2B, STAGE 2C, AND AFTER ALL THE 12/21/2009 PROPOSED ROADWAY GEOMETRICS ARE BUILT AND OPEN TO TRAFFIC. (SHEET 1 OF 2) DRAWN BY: MAA
DESIGNED BY: PKG/RRM
CHECKED BY: PKG/RRM SCALE: NONE

DATE: APRIL 17, 2009

CANDHIAND ASSOCIATES, INC. ENGINEERS AND PLANNERS 6035 N. MORTHWEST HIGHWAY SUITE 306 CHICAGO, ILLINOIS 60631TEL. (773) 774-5910

F.A.P. RTE.	SECTION		COUNTY	TOTAL, SHEETS	SHEET NO
326	*		McHENRY	502	285
STA.			TO ST	Α.	
FED. ROAD DIST. N	0.	ILLINOIS	FED.	AID PROJECT:	

*	(105X	&	106)	WRS-2

TEMPORARY	<b>EMERGENCY</b>	VEHICLE	PREEMPTION	SEQUENCE	OF	OPERATION

TEMF	PORA	νRΥ	EMI	ERG	iEN(	CY V	/EHI	CLE	PF	REEN	ИРΤΙ	ION	SE	EQU	ENC	Œ	OF	OPF	ER/	ΑΤΙΟ	Ν	-	_7							/A\	\									. [
																					<u>:</u>									7						PREEMPTOR NUMBER 3	PREEMPTOR NUMBER 4	PREEMPTOR	PREEMPTOR NUMBER 6	
CHANGE FROM NORMAL SEQUENCE OF						A						· · · · · · · · · · · · · · · · · · ·									/															NOMBER 3	NOMBER 4	NOMBEN 3	NOMBEN	
OPERATION INTERVAL NUMBER			1		1		1			5		5	8	8			11			11			11				16		16			19			19					CLEAR
EMERGENCY VEHICLE PRE-EMPTION SEQUENCE OF OPERATION INTERVAL NUMBER	1,	A 1B	1C 1	D 1E	1F	1G 1H	1J	1K 1L	1M	1N 1	P 10	1R	1S 1	T 1U	1V 1	LW 1	X 1Y	1Z 1	AA 1F	BB 1CC	1DD: 18	EE 1FF	1GG	1HH	1JJ	1KK 1	LL	1MM	1NN /	1PP	1QQ	1RR	1SS	1TT	1VV	2	3	4	5	TO
CHANGE TO EMERGENCY VEHICLE PRE-EMPTION SEQUENCE OF OPERATION INTERVAL NUMBER	16	3 1C	1D	2 1F	4	1F 1G	1K	3, 5 1N	1 1N	1P 1	Q 2, 3	3 4	2 1	J 1V	3 .	1X 1	Y 1Z	1AA	2 10	CC 1DD	4 11	FF 1GC	3 1H⊢	1JJ 3	3, 5	ĪLL	1MM 2	2, 4, 5	(3)	100	1RR	1SS	1TT	2, 3	5					SEQUENCE
ILLINOIS ROUTE 47 NEAR RIGHT AND FAR RIGHT SPAN WIRE SIGNALS	N/B F	R R	R	R R	R	R R	R	RR	R	R	R R	R	G (	3 Y	R	G (	G G	G	G (	G Y	R	G Y	R	R	R	R	R	R	R	R	R	R	R	R	R	G	R	R	R	$\Diamond$
	N/B ◀	G <b>∢</b> -G	<b>4</b> G <b>4</b>	-G <b>←</b> `	′ <b>∢</b> -R -	<b>←</b> Y <b>←</b> F	R ←R	<b>←</b> R <b>←</b> I	R ←R	<b>←</b> R <b>←</b>	-R <b>←</b> R	<b>+</b> R •	+G <b>←</b>	G <b>←</b> Y	R <	+R ◆	R ←R	<b>€</b> R ∢	+R <b>∢</b>	-R <b>←</b> R	<b>←</b> R •	-R <b>←</b> R	R <b>←</b> R	<b>←</b> R •	<b>←</b> R	◆R	<b>←</b> R	<b>◆</b> R	<b>←</b> R	<b>←</b> R	<b>4</b> −R	<b>∢</b> R	<b>←</b> R	◆R	<b>←</b> R	◆G	◆R	<b>←</b> R	<b>←</b> R	
	S/B .			_	+_+		-					1																						1	-					<del></del>
RIGHT LOW MOUNT AND TWO RIGHT SPAN WIRE SIGNALS		R R	K	R	2	RR	R	R G	Y	R	RR	G	R F	R	R	G ,	YR	R	R	G G	G	G Y	R	R	R	R	R	R	R	R	R	R	R	R	R	R	R	G .	R	◊
	S/B			_		Ţ.		_																														_		
LOW MOUNT IN BARREL (ON LEFT) AND TWO LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	4	Y   ◆ R	<b>4</b>	- K 🐠	G   <b>←</b> G   •	+Y   <b>4</b> -F	₹ <b> </b> ← R	<b>←</b> R  <b>←</b> (	3 <b>←</b> Y	<b>4</b> -R   <b>4</b>	·R   <b>∢</b> -R	<b>4</b> 6 •	+R  <b>→</b>	R∣←R	<b>4</b> -R <b>4</b>	-R   <b>←</b>	·R∣◆R	<b>←</b> R <b>←</b>	rR ◀	-R <b>∢</b> -R	<b>◆</b> R   <b>◆</b>	-R   <b>←</b> R	₹ <b>4</b> R	+R   •	<b>←</b> R	<b>∢</b> -R	<b>◆</b> R	<b>←</b> R	◆R	<b>◆</b> R	◆R	◆R	◆R	◆R	◆R	◆R	◆R	<b>◆</b> G	<b>◆</b> R	
	S/B _			<del></del>	++		-			-		-			-			-				-								-					-					
NEAR RIGHT AND TWO FAR RIGHT SPAN WIRE SIGNALS	,	R	R	RR	R	RR	R	R G	G	G	YR	G	R F	R	R	G	G [ G	, Y /	R	G G	G C	G G	G	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	G	R	
ILLINOIS ROUTE 47, SOUTH OF TRACK TWO FAR LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	S/B <b>←</b>	G←G	<b>←</b> Y <b>←</b>	Y <b>4</b> (	G <b>4</b> -G •	<b>⊢</b> G <b>←</b> (	G <b>←</b> Y	<b>←</b> R <b>←</b>	G <b>←</b> G	<b>←</b> G <b>←</b>	-Y <b>∢</b> R	<b>←</b> G •	+R <b>←</b>	R <b>←</b> R	<b>←</b> R <b>◆</b>	-R <b>∢</b>	Ri <b>∢</b> R	<b>←</b> R <b>∢</b>	<b>+</b> R <b>←</b>	-R <b>∢</b> -R	<b>4</b> -R <b>4</b>	-R <b>∢</b> -R	₹ <b>4</b> R •	⊦R •	<b>←</b> R	◆R	<b>∢</b> R	<b>←</b> R	◆R	<b>←</b> R	<b>4</b> −R	<b>←</b> R	<b>←</b> R	<b>◆</b> R	<b>←</b> R	◆R	◆R	<b>◆</b> G	<b>←</b> R	
	E/B ,						+_+	R R	-		_						_	_	-			-						_						<b>+</b> -	-					^
NEAR SIDE RIGHT SPAN WIRE SIGNAL	F	K	H	K K	11	KK	R	RR	K	R	7   K	R	R	K   K	H	RIF	?   R	, R   '	RF	RR	R	RR	R	R	R	U	Ť	R	G	R	R	R	R	R	R	R	G .	R	R	$\downarrow$
	E/B F	R	R	R R	R	RR	R	R R	R	R	2 R	R	R F	R	ą	D [	2 D	D	D .	D D	В	D D	D	B	R	G	Y	R	G <b>←</b> G	R	p	R	R	P	R	B	G <b>◆</b> G	R	R	
FAR SPAN WIRE SIGNALS MAIN STREET, EAST OF TRACK					1,,1		11	14 14		- ' '	1 11	11	11	`   '\	.,	Λ   1	7 17		N   r	Λ Λ	Π	N N	11/	11	11	<b>◆</b> -G		11	<b>←</b> G	1 11	11			L	11	11	<b>←</b> G			<u> </u>
LOW MOUNT IN BARREL (ON LEFT),	W/B	, p	ь			D 3		RR	_ n	ь .	, ,	ь	Б			_   .				D D				D .		_	P			6		R	B	] =			B		G	
SPAN WIRE, AND RIGHT LOW MOUNT SIGNALS		,   ,	I IX	7   7	"	7. 71	K	K	14	K !	7   17	K	R	K K	~	KI	4   R	RI	KIF	RIRI	R	RIR	K	K	R	K	K	K	R	U	Ť	11	'`	'	G	R	K '	K	6	V
	W/B _		R		$\pm \pm \pm$											_			-				1							G	G	G		-	G				G	
FAR SPAN WIRE SIGNALS		K	K	KKK	R	RIR	R	RIR	R	R	7   R	R	RF	R	R	R	?   R	, R   r	R   F	RR	R	RR	R	R	R	R	R	R	R	<b>∢</b> G	G <b>←</b> G	<b>€</b> G	Y	R	G <b>←</b> G	R	R	R	G <b>∢</b> -G	
PEDESTRIAN SIGNALS CROSSING	_	4 Н	н		Н	шш	н	u u	LI	L.I.	НН		cu c	11 11		-11				-11		11 11	1											T	1,					
MAIN STREET. ON EAST SIDE OF ILLINOIS ROUTE 47.		1 11	- ' '	П	П	ППП	п	п	н			1 1		н н	m   r	Н	ч н	H	HIL	н	HF	н	H	Н	Н	Н	Н	Н	Н	H	Н	Н	Н	H	H	H	H	Н	Н	
PEDESTRIAN SIGNALS CROSSING MAIN STREET. ON WEST SIDE OF ILLINOIS ROUTE 47.	1	i H	Н	н н	Н	н	Н	H FH	н	Н	н	FH	Н	н	н	=H	- Н	н	HF	НН	H F	Н	H	Н	Н	Н	Н	Н	Н	H	H	Н	Н	Н	Н	Н	Н	Н	Н	$\Diamond$
PEDESTRIAN SIGNALS CROSSING	I.	- H	н	и п		ы п		н		Ш	ш	ш	ш	J L		н	ч н	H	HT	н н	Н	н н	TH	Н	Н	н	Н	Н	Н	EH	Н	Н	Н	Н	FH	Н	Н	Н	Н	
ILLINOIS ROUTE 47. ON NORTH SIDE OF MAIN STREET.		1 11			''		П.	17   M		П	П	П	ri i	1 1																FH					1 11		ļ			
PEDESTRIAN SIGNALS CROSSING ILLINOIS ROUTE 47. ON SOUTH SIDE OF MAIN STREET.		Н	Н	Н	Н	н	Н	н	н	Н	н	Н	Н	Н	Н	Н	- Н	н	H	н	н	н	Н	Н	Н	FH	Н	Н	FH	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	\
																																				*		L		

TEMPORARY RAILROAD PREEMPTI	UN	5E	اںلی	=INC	上	<u>UF</u>	OF	'EK	AH	<u>ON</u>							PREEM NUMB		PREEN NUMB				MPTOR BER 6		PREEMPTOI NUMBER 2			Ź	A
HANGE FROM NORMAL SEQUENCE OF PERATION INTERVAL NUMBER		1		5		8	1	1	1	16			19																
HANGE FROM EMERGENCY VEHICLE PREEMPTION SEQUENCE NTERVAL NUMBER			\$ 1 \$ 1 \$ 1												2		3	5	4	į			5		:		/		
AILROAD PREEMPTION SEQUENCE OF OPERATION NTERVAL NUMBER	1A	18	3 10	1D	1E	1F	1G	1H	1J	1K	1L	1M	1N	1P	10	1R	1S	17	1U	1٧	1W	1X	1Y	1Z	2/	3	4	5	CLEAR
HANGE TO RAILROAD PREEMPTION SEQUENCE OF OPERATION	1B	2	10	2	1F	2	1H	2	1K	2	1M	1N	1P	2 (	1R	γ Λ <sup>2</sup>	1T	γ <sub>2</sub> Λ	įν	2 /	1X	1Y	1Z	2	3	4	5		NORMAL SEQUENC
LINOIS ROUTE 47 EAR RIGHT AND FAR RIGHT SPAN WIRE SIGNALS	/B R	R	R	R	Y	R	Y	R	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	Δ
LINOIS ROUTE 47 N WO FAR LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	/B ←\	4	? <b>∢</b> F	₹ 4-6	<b>◆</b> Y	<b>◆</b> R	<b>∢</b> R	<b>∢</b> R	<b>◆</b> R	<b>◆</b> R	<b>◆</b> -R	<b>←</b> R	<b>∢</b> R	<b>←</b> R	<b>←</b> Y	<b>4</b> -R	<b>◆</b> R	<b>←</b> R	<b>∢</b> -R	<b>∢</b> R	<b>∢</b> R	<b>∢</b> R	<b>d</b> -R	<b>4</b> -R	<b>←</b> R	◆R	<b>◆</b> R	<b>←</b> R	Δ
IGHT LOW MOUNT AND TWO RIGHT SPAN WIRE SIGNALS .	∕B R	R	Y	R	R	R	Y	R	R	R	R	R	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	R	R	Δ
LINDIS ROUTE 47, NORTH OF TRACK Ow mount in barrel (on left) nd two left span wire signals with left turn arrows	/B <b>←</b> \	<b>+</b>	₹ 🛧	′ 4-5	<b>←</b> R	<b>←</b> R	<b>←</b> R	<b>∢</b> R	<b>4</b> -R	<b>4</b> -R	<b>∢</b> -R	<b>∢</b> -R	<b>∢</b> -R	<b>←</b> R	<b>∢</b> -R	<b>←</b> R	<b>∢</b> R	<b>←</b> R	<b>4</b> -Y	<b>←</b> R	<b>←</b> R	<b>←</b> R	<b>←</b> R	<b>←</b> R	<b>∢</b> R	◆R	<b>∢</b> R	<b>∢</b> R	Δ
	/B R	R	G	G	R	R	G	G	R	R	R	R	R	R	R	R	R	R	G	G	R	R	R	R	G	Y	R	R	Δ
LINOIS ROUTE 47, SOUTH OF TRACK  S WO FAR LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	/B <b>←</b> 0	4	G <b>4</b> -(	<b>4</b> -G	<b>√</b> R	<b>∢</b> -R	◆R	<b>∢</b> -R	<b>←</b> R	<b>◆</b> R	<b>◆</b> R	<b>◆</b> R	<b>←</b> R	<b>∢</b> R	<b>◆</b> R	<b>←</b> R	<b>∢</b> R	<b>←</b> R	<b>←</b> G	<b>←</b> G	◆R	<b>◆</b> R	◆R	<b>◆</b> R	<b>←</b> G	<b>←</b> Y	<b>←</b> R	R	Δ
AIN STREET. E Ear side right span wire Signal	/B F	F	R	R	R	R	R	R	Υ	R	R	R	R	R	R	R	Υ	R	R	R	R	R	R	R	R	R	R	R	Δ
AIN STREET, EAST OF TRACK E Ar span wire signals	/B F	F	R	R	R	R	R	R	Υ	R	R	R	R	R	R	R	Υ	R	R	R	R	2	R	R	R	R	R	R	Δ
AIN STREET, EAST OF TRACK W DW MOUNT IN BARREL (ON LEFT), PAN WIRE, AND RIGHT LOW MOUNT SIGNALS	/B	F	R	R	R	R	R	R	R	R	Υ	R	R	R	R	R	R	R	R	R	Υ	R	R	R	R	R	R	G	Δ
AIN STREET, WEST OF TRACK W AR SPAN WIRE SIGNALS	∕B R	R	R	R	R	R	R	R	R	R	G <b>4</b> G	G <b>◆</b> G	Υ	R	R	R	R	R	R	R	G <b>4</b> -G	G <b>◆</b> -G	Υ	R	R	R	R	G <b>←</b> G	Δ
EDESTRIAN SIGNALS CROSSING AIN STREET, ON EAST SIDE OF ILLINOIS ROUTE 47,	Н	Н	Н	Н	FH	Н	FH	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Δ
DESTRIAN SIGNALS CROSSING AIN STREET, ON WEST SIDE OF ILLINOIS ROUTE 47,	Н	Н	FH	Н	Н	Н	FH	Н	Н	Н	Н	Н	Н	Н	L	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Δ
DESTRIAN SIGNALS CROSSING LINOIS ROUTE 47. ON NORTH SIDE OF MAIN STREET.	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	FH	Н	Н	Н	H	Н	Н	Н	Н	Н	Н	Н	Н	-	Н	Н	Н	Н	Δ
EDESTRIAN SIGNALS CROSSING LINOIS ROUTE 47, ON SOUTH SIDE OF MAIN STREET.	Н	Н	Н	Н	Н	Н	н	Н	FH	Н	Н	Н	Н	Н	Η	Н	Н	Н	Н	Н	Н	Н	Н	H	Н	Н	Н	Н	Δ

- ♦ EMERGENCY VEHICLE SEQUENCE SHALL PROVIDE THE PROPER CLEARANCE INTERVAL TO RESUME THE NORMAL SEQUENCE OF OPERATION OR PROPER CLEARANCE INTERVAL TO DISPLAY A DIFFERENT EMERGENCY VEHICLE INTERVAL ATTER EMERGENCY VEHICLE INTERVAL 2, 3, 4, OR 5 IS TERMINATED.
- A RAILROAD PREEMPTION SEQUENCE SHALL PROVIDE THE PROPER CLEARANCE INTERVAL TO RESUME THE NORMAL SEQUENCE OF OPERATION OR PROPER CLEARANCE INTERVAL TO DISPLAY AN EMERGENCY VEHICLE INTERVAL (IF APPLICABLE) AFTER RAILROAD PREEMPTION INTERVAL 5 IS TERMINATED.

THE TRAFFIC SIGNAL CONTROL EQUIPMENT FOR THIS PROJECT SHALL BE "EAGLE" TO MATCH THE EXISTING ADJACENT SYSTEM.



GANDHIAND ASSOCIATES, INC.
ENGINEERS AND PLANNERS
SUITE 300
OUT 1, 100
OUT 1,

ILLINOIS DEPARTMENT OF TRANSPORTATION TEMPORARY EMERGENCY VEHICLE PREEMPTION SEQUENCE OF OPERATION REVISIONS
NAME DATE ILLINOIS ROUTE 47 AT MAIN STREET O N S

DATE

PRE-STAGE, STAGE 1, STAGE 1B, STAGE 1C, STAGE 2,

12/21/2003

STAGE 2B, STAGE 2C, AND AFTER ALL THE PROPOSED

ROADWAY GEOMETRICS ARE BUILT AND OPEN TO


TRAFFIC.


PRAWN BY: MAA

DATE: APRIL 17, 2009

ADDENDUM A

TRAFFIC.
(SHEET 2 OF 2) DRAWN BY: MAA
DESIGNED BY: PKG/RRM
CHECKED BY: PKG/RRM





F.A.P. RTE.	SECTION		COUNTY	SHEETS	SHEET
326	*		MCHENRY	502	288
STA.			TO STA		
FED. ROAD DIST. NO.		ILLINOIS	FED.	ALD PROJECT:	

# TEMPORARY SEQUENCE OF OPERATION (LEAD-LAG)

												$\frac{A}{1}$																						
MOVEMENT		5—— 2———	<b>♦</b>	P					2 –	6	,								P	<b>•</b>	– 6 – 1					P	<b>,</b>			4	P			F L
PHASE		2 -	+ 5						2	+ 6	$ \overline{} $	Y	V	$\overline{}$	Y	7	V		1	V <sub>+</sub>	¥	V	7		$\bigvee$	$\sqrt{3}$	V		Y	V	4 Y			)
INTERVAL	1	2	3A	3B	4	5 6	A 6	B 60	36	7A	7B	8.8	8B	8C	8D	9	10 1	1A 1	1B   11	C 111	124	. 12B	12C	12D	13	14 1	5A 1	5B 1	6 1	7 184	18B	18C	18D	) H
CHANGE TO	ø	Ø/	2	16	$\Lambda$			3, 4	1	1+	-6		2+	-5	< 5				2+6	\(\)		3,	4		A	1	4 1+6 2+5 2+6	,   ,			2	+6 +5 +6		
ILLINOIS ROUTE 47 N/B NEAR RIGHT AND TWO FAR RIGHT SPAN WIRE SIGNALS	G	G	G	G	G	G .	Y F	R R	R	Y	R	G	G	G	G	R	RI	R	R F	R	R	R	R	R	\R	R	R	R	RF	: R	R	R	R	R
ILLINOIS ROUTE 47 N/B TWO FAR LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	<b>←</b> G	<b>+</b> G	<b>←</b> Y	◆R	<b>←</b> R <b>←</b>	+R <b>←</b>	R <b>←</b> F	₹ <b>+</b> R	◆R	₹R	◆R	◆R	◆R	<b>4</b> R ⋅	◆R ·	•) <sub>R</sub> •	+R ←	R +F	₹ +F	<b>←</b> F	₽R	◆R	◆R	<b>◆</b> R<	←R ·	•R ◀	⊦R ◀	-R •	R 📲	? <b>←</b> R	◆R	◆R	<b>∢</b> R	◆R
ILLINOIS ROUTE 47, NORTH OF TRACK S/B RIGHT LOW MOUNT TWO RIGHT SPAN WIRE SIGNALS	R	R	R	R	G	G	Y F	R	R	(LG	G	Y	R	R	R	)G	G	G (	3. (	G	(y	R	R	R	R	R	R	R F	R R	R	R	R	R	R
ILLINOIS ROUTE 47, NORTH OF TRACK S/B LOW MOUNT IN BARREL (ON LEFT) TWO LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	◆R	◆R	◆R	◆R	<b>+</b> R <b>•</b>	-R •	R. +	R <b>←</b> F	? ← [-	<b>√</b> R	◆R	◆R	◆R	◆R	•R≺	<b>+</b> G ⋅	+G <b></b>	-Y •	R 📲	R <b>∢</b> R	<b>+</b> Y	◆R	<b>←</b> R	◆R	₽R .	+R •	+R ◀	-R •	R +F	R ◆R	<b>←</b> R	◆R	<b>←</b> R	∙R
ILLINOIS ROUTE 47, SOUTH OF TRACK S/B NEAR RIGHT AND TWO FAR RIGHT SPAN WIRE SIGNALS	R	R	R	R	G	G	G (	G Y	R	G	G	G	G	Y	R	G	G	G	G (	G G	G	G	Υ	R	) R	R	R	R	R F	R	R	R	R	R
ILLINOIS ROLTE 47, SOUTH OF TRACK TWO FAR LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	◆R	◆R	◆R	<b>∢</b> R	<b>←</b> R <b>◆</b>	-R ◆	R +	R <b>◆</b> F	₹ 4-6	₹ <b>4</b> R	◆R	◆R	◆R	◆R	◆R-<	₹G .	+G <b>∢</b>	-G +	G +	Y +F	<b>→</b> G	<b>←</b> G	<b>◆</b> Y	◆R	Y-R	∙R •	-R	-R •	R 📲	? <b>←</b> R	◆R	◆R	<b>←</b> R	∙R
MAIN STREET E/B NEAR SIDE SPAN WIRE SIGNAL	R	R	R	R	R	R	RI	R R	R	R	R	R	R	R	R	R	R	R	RII	₹ F	R	R	R	R	G	G	Υ	R	R F	R	R	R	7	R
MAIN STREET E/B FAR SPAN WIRE SIGNALS	R	R	R	R	R	R	RI	RR	R	R	R	R	R	R	R	)R	R	R	R	₹ F	: SR	R	R	R≺	)G ◆G	G <b>◆</b> G	Υ	R	R F	RR	R	R	R	R
MAIN STREET, EAST OF TRACK LOW MOUNT IN BARREL (ON LEFT), SPAN WIRE, AND RIGHT LOW MOUNT SIGNALS	R	R	R	R	R	R	RI	R R	R	R	R	R	R	R	R	)R	R	R	R	R F	R	R	R	R_	R	R	R	R	G G	Y	R	R	R	R
MAIN STREET, WEST OF TRACK W/B FAR SPAN WIRE SIGNALS	R	R	7	R	R	R	7 1	R R	R	R	R	R	R	R	R	\R	R	R	RI	? F	R	R	R	R	R	R	R		G +G ◆		G G ◆G	Υ	R	R
PEDESTRIAN SIGNAL CROSSING MAIN STREET ON EAST SIDE OF ILLINOIS ROUTE 47	* P	** FH	Н	Н		* * FH	н	н н	Н	Н	Н	Н	Н	Н	н≺	H	Н	н	Н	1 F	(н	Н	Н	Н	)н	Н	Н		H F		Н	Н	Н	ARY
PEDESTRIAN SIGNAL CROSSING MAIN STREET ON WEST SIDE OF ILLINOIS ROUTE 47	Н	Н	Н	Н		* * - H	н	4 H	Н	Н	Н	Н	Н	Н	Н		* * FH	Н	Н	1 F	H	-1	Н	Н	\H	Н	н	Н	Н	Н	Н	Н	Н	· VARY
PEDESTRIAN SIGNAL CROSSING ILLINOIS ROUTE 47 ON NORTH SIDE OF MAIN STREET	Н	. H	Н	Н	Н	Н	н	Н	Н	Ун	Н	Н	Н	Н	Н	)H	Н	Н	Н	1 -	H	Н	Н	н	H	Н	Н	Н	* * F	* H	Н	Н	Н	)ARY
PEDESTRIAN SIGNAL CROSSING ILLINOIS ROUTE 47 ON SOUTH SIDE OF MAIN STREET	Н	Н	Н	Н	Н	Н	H	- Н	Н	Н	Н	Н	Н	Н	Н	)H	Н	Н	H I	1 -	H	H	Н	Н	)*	** FH	Н	Н	НН	Н	Н	Н	Н	) ARY

P = ILLUMINATED PERSON = WALK

FH = ILLUMINATED FLASHING HAND = FLASHING DON'T WALK

H = ILLUMINATED SOLID HAND = DON'T WALK

PHASE 2 + 6 SHALL BE PLACED ON RECALL.

- \* TO APPEAR ONLY UPON PUSHBUTTON ACTUATION.
- \*\* FLASHING " @ " IS TO TERMINATE AT THE COMPLETION OF THE PEDESTRIAN INTERVAL CLEARANCE.

夕 THIS "碅" OR FLASHING "圈" INTERVAL MAY FINISH TIMING IN THE BI-DIRECTIONAL STRAIGHT THROUGH MOVEMENT IF THE LEFT ARROW TIME IS NOT SUFFICIENT TO COMPLETE " @ "
OR FLASHING " @ " INTERVALS. " @ " AND FLASHING " @ " TIMINGS TO BE SET ONLY ON THE PHASES WHERE " # " AND FLASHING " " ARE INDICATED IN THE SEQUENCE OF OPERATION.

THE TRAFFIC SIGNAL CONTROL EQUIPMENT FOR THIS PROJECT SHALL BE "EAGLE" TO MATCH THE EXISTING ADJACENT SYSTEM.

ILLINOIS DEPARTMENT OF TRANSPORTATION

TEMPORARY SEQUENCE OF OPERATION ILLINOIS ROUTE 47 AT MAIN STREET STAGE 3, STAGE 3B, AND STAGE 3C. (SHEET 1 OF 2)

DRAWN BY: MAA

SCALE: NONE

REVISIONS

ADDENDUM A

DESIGNED BY: PKG/RRM CHECKED BY: PKG/RRM DATE: APRIL 17, 2009

GANDHI AND ASSOCIATES, INC.
ENGINEERS AND PLANNERS
6035 N. NORTHWEST HIGHWAY
SUITE 306
CHICAGO, ILLINOIS 60631 TEL. (1773) 774-5910

F.A.P. RTE.	SECTION		COUNTY	SHEETS	SHEET NO
326	*		MCHENRY	502	289
STA.			TO STA		
FED. ROAD DIST, NO	).	ILLINOIS	FED. A	ID PROJECT:	

TEMPORARY	<b>EMERGENCY</b>	VEHICLE	PREEMPTION	SEQUENCE	OF	OPERATION
I LIVII OI U II II		V LI II O L L		OLGOLIVOL	OI.	

						<del></del>	· · · · · · · · · · · · · · · · · · ·										~~									$\nearrow$		PREEMPTOF NUMBER 3		PREEMPTOR NUMBER 5	PREEMPTOR NUMBER 6	
CHANGE FROM NORMAL SEQUENCE OF OPERATIONS INTERVAL NUMBER		1	1			4			4				4			(	9	7	9	1	7 13	Y	3 7	,	7 7 16	,	16	No. College				CLEAR
EMERGENCY VEHICLE PREEMPTION SEQUENCE OF OPERATION INTERVAL NUMBERS		1A 1	IB 1C	1D	1E 1F	1G	1H	1J :	1K 1I	. 1N	I IN	1P	1Q 1	R 1S	1T	10	1W	1)	TY	1Z 17	AA 1f	3B 10	C 10	D 1EE	1FF	1GG 1	HH IJJ	2	3	4	5	TO NORMAL
CHANGE TO EMERGENCY VEHICLE PREEMPTION SEQUENCE OF OPERATION INTERVAL NUMBER		2	1C 1D	3 4, 5	1F 10	G 1H	1J	2	1L 1	A 4	1P	1Q	1R 1	S 3, 5	1U	1V	1W 13	( 2, 5	3 4	1AA 1	BB 2,	4, 5	3 1E	E 1FF	1GG	1HH 2	, 3 5					SEQUENCE
ILLINOIS ROUTE 47, NEAR RIGHT AND FAR RIGHT SPAN WIRE SIGNALS	N/B	G	G Y	R	G G	G	G	G	G Y	R	G	Y	R F	₹ R	R :	R	R F	R	R	R	R	R I	₹ R	R	R	R	R R	G	R	R	R	$\Diamond$
ILLINOIS ROUTE 47 TWO FAR LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	N/B	<b>4</b> -G <b>4</b>	-G <b>∢</b> Y	R .	<b>+</b> R <b>◆</b> I	R ←R	<b>←</b> R •	<b>←</b> R ◀	⊦R <b>←</b>	R <b>←</b> f	₹	<b>←</b> R <b>←</b>	<b>+</b> R <b>←</b>	R ←R	<b>4</b> -R •	<b>-</b> R <b>-</b>	-R <b>∢</b> -l	R <b>←</b> F	R ←R	<b>◆</b> R <b>◆</b>	⊢R ◀	+R ◆	-R <b>←</b>	R <b>←</b> R	<b>←</b> R •	<b>←</b> R <b>∢</b>	-R <b>←</b> R	<b>←</b> G	<b>←</b> R	◆R	<b>∢</b> R	$\Diamond$
ILLINOIS ROUTE 47, NORTH OF TRACK RIGHT LOW MOUNT AND TWO RIGHT SPAN WIRE SIGNALS	S/B	R	R R	R	G Y	R R	R	R	G C	G	G	Y	R F	R R	G	Υ	R F	R	G	R	R	R F	7 R	R	R	R	R R	R	R	G	R	$\Diamond$
ILLINOIS ROUTE 47, NORTH OF TRACK LOW MOUNT IN BARREL (ON LEFT) AND TWO LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	S/B	<b>←</b> R <b>←</b>	⊢R ∢-R	<b>4</b> R	<b>←</b> R <b>←</b>	R ←R	<b>←</b> R	<b>←</b> R ◀	⊦R ←	R <b>←</b> f	R ←R	<b>←</b> R •	<b>←</b> R <b>←</b>	-R <b>←</b> R	<b>←</b> G <b>←</b>	<b>←</b> Y <b>4</b>	-R <b>←</b> I	₹ ←	R <b>∢</b> G	<b>←</b> R ◆	+R ◀	+R <b>∢</b>	-R <b>←</b>	R <b>←</b> F	≀ <b>←</b> R ·	<b>←</b> R <b>←</b>	-R ←R	<b>←</b> R	<b>4</b> ∄	<b>←</b> G	<b>4</b> -R	<b>♦</b>
ILLINOIS ROUTE 47, SOUTH OF TRACK NEAR RICHT AND TWO FAR RIGHT SPAN WIRE SIGNALS	S/B	R	R R	R	G G	G	Y	R	G G	G	G	G	G Y	r R	G	G	G Y	R	G	R	R	R F	R R	R	R	R	R R	R	R	G	R	$\Diamond$
ILLINOIS ROUTE 47, SOUTH OF TRACK TWO FAR LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	S/B	<b>4</b> -R <b>4</b>	-R <b>∢</b> -R	<b>←</b> R •	<b>-</b> R <b>-</b> 1	R <b>∢</b> -R	<b>←</b> R •	+R ◀	⊦R <b>←</b>	R <b>4</b> -F	R ←R	<b>←</b> R <b>◆</b>	<b>-</b> R <b>-</b>	R <b>←</b> R	<b>4</b> -G •	<b>4</b> -G <b>∢</b>	-G <b>←</b>	Y <b>4</b> -F	? <b>∢</b> -G	<b>←</b> R <b>◆</b>	⊢R ◀	+R ◆	R 🛧	R <b>←</b> R	<b>←</b> R	<b>←</b> R <b>←</b>	-R <b>∢</b> -R	←R	←R	<b>←</b> G	<b>←</b> R	$\Diamond$
MAIN STREET. NEAR SIDE RIGHT SPAN WIRE SIGNAL	E/B	R	R R	R	R R	: R	R	R	R R	R	R	R	R F	R R	R	R	R R	R	R	G	Y	R C	3 R	R	: R	R	R R	R	G	R	R	$\Diamond$
MAIN STREET, EAST OF TRACK FAR SPAN WIRE SIGNALS	E/B	R	R R	R	R R	R	R	R	RR	R	R	R	RF	R R	R	R	R R	R	R	G <b>←</b> G	Y F	R G	G R	R	R	R	R R	R	G <b>←</b> G	R	R	$\Diamond$
MAIN STREET, EAST OF TRACK LOW MOUNT IN BARREL (ON LEFT), SPAN WIRE, AND RIGHT LOW MOUNT SIGNALS	W/B	R	R R	R	R R	l R	R	R	R R	R	R	R	R F	R R	R	R	R R	3	R	R	R	R F	۲ G	Y	R	R	R G	R	R	R	G	• ♦
MAIN STREET, WEST OF TRACK FAR SPAN WIRE SIGNALS	W/B	R	R R	R	R R	R	R	R	R F	R	R	R	R F	R R	R	R	R R	R	R	R	R	R F	₹ G	G G <b>4</b> -0	G G G	Y	R G ←G	R	R	R	G <b>◆</b> G	$\Diamond$
PEDESTRIAN SIGNAL CROSSING MAIN STREET ON EAST SIDE OF ILLINOIS ROUTE 47		FH F	FH H	Н	FH H	Н	Н	H F	-н н	Н	FH	Н	Н	н	Н	н	н н	Н	Н	Н	Н	н н	н н	Н	Н	н	н	Н	Н	Н	Н	$\Diamond$
PEDESTRIAN SIGNAL CROSSING MAIN STREET ON WEST SIDE OF ILLINOIS ROUTE 47		Н	н	Н	FH H	1 H	Н	НГ	-H F	Н	FH	Н	НН	н	FH	Н	н н	Н	FH	Н	Н	н	Н	Н	Н	Н	нн	Н	Н	Н	Н	$\Diamond$
PEDESTRIAN SIGNAL CROSSING ILLINOIS ROUTE 47 ON NORTH SIDE OF MAIN STREFT		Н	НН	Н	н н	Н	Н	Н	н	Н	Н	Н	Н	н н	н	Н	н н	Н	Н	Н	Н	Н	1 FF	н н	Н	Н	H FH	H	Н	Н	Н	$\Diamond$
PEDESTRIAN SIGNAL CROSSING ILLINOIS ROUTE 47 ON SOUTH SIDE OF MAIN STREET		Н	НН	Н	НН	H	Н	Н	H F	Н	Н	Н	Н	н	Н	Н	Н Н	Н	Н	FH	Н	Н Е	н н	Н	Н	Н	НН	Н	Н	H .	Н	$\Diamond$

TEMPORARY RAILROA	D PREEN	/IPT	ION	I S	EQ	ÙΕΙ	VCI	E (	)F	OP	ER/	ATI(	I NC	DDEEN	PTOP	DDEEN	IDTOD	DDEEM	DTAD		PREE	MDTOE	5	PREEMPTOR	1			
							V	~	$\overline{}$	$\overline{}$				NUMB	ER 3	NUMB	ER 4	NUMBI	ER 5		NUME	BER 6		NUMBER 2				
CHANGE FROM NORMAL SEQUENCE OF OPERATION INTERVAL NUMBER			1	4	4		9人		13人			6)													,	$\mathbb{A}$		
CHANGE FROM EMERGENCY VEHICLE PREEMPTION SEQUENCE INTERVAL NUMBER			2									-		2		3	3	۷	1		Ę	5				<del></del>		
RAILROAD PREEMPTION SEQUENCE OF OPERATION INTERVAL NUMBER		1 A	1B	1C	1D	1E	1F	1G	1H	1J	1K	1L	1V	1N	1P	10	1R	1S	1T	10	1V	1W	1X	2/	3.	4	5	CLEAR TO
CHANGE TO RAILROAD PREEMPTION SEQUENCE OF OPERATION INTERVAL NUMBER		1B	2	1D	2	1F	2	1H	2	1K	1L	1M	2 (	1P	Y 2	1R	2	Ϋ́Τ	2	1 V	1W	1X	2	7 3	4	5		NORMAL SEQUENCE
ILLINOIS ROUTE 47, NEAR RIGHT AND FAR RIGHT SPAN WIRE SIGNALS	N/B	Y	R	Y	R	R	R	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	Δ
ILLINOIS ROUTE 47 TWO FAR LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	N/B	<b>◆</b> Y	<b>←</b> R	<b>←</b> R	<b>4</b> -R	<b>4</b> -R	<b>∢</b> R	<b>←</b> R	◆R	<b>◆</b> R	<b>◆</b> R	<b>◆</b> R	<b>←</b> R	<b>◆</b> Y	<b>←</b> R	<b>◆</b> R	<b>←</b> R	<b>4</b> -R	<b>4</b> -R	◆R	<b>∢</b> -R	<b>∢</b> -R	<b>◆</b> R	◆R	<b>◆</b> R	<b>∢</b> -R	<b>4</b> -R	Δ
ILLINOIS ROUTE 47, NORTH OF TRACK RIGHT LOW MOUNT AND TWO RIGHT SPAN WIRE SIGNALS	S/B	R	R	Y	R	Y	R	R	R	R	R	R	R	R	R	R	R	Υ	R	R	R	R	R	R	R	R	R	Δ
ILLINCIS ROUTE 47, NORTH OF TRACK LOW MOUNT IN BARREL (ON LEFT) AND TWO LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	S/B	<b>←</b> R	◆R	<b>←</b> R	<b>←</b> R	<b>←</b> Y	<b>←</b> R	R <b>←</b> R	◆R	◆R	<b>←</b> R	◆R	◆R	<b>←</b> R	<b>←</b> R	<b>←</b> R	· <b>←</b> R	• <b>←</b> Y	◆R	∙R	• •R	<b>◆</b> R	◆R	<b>←</b> R	◆R	<b>←</b> R	<b>◆</b> R	Δ
ILLINOIS ROUTE 47, SOUTH OF TRACK NEAR RIGHT AND TWO FAR RIGHT SPAN WIRE SIGNALS	S/B	R	R	G	G	G	G	R	R	R	R	R	R	R	R	R	R	G	G	R	R	R	R	G	Y	R	R	Δ
ILLINOIS ROUTE 47, SOUTH OF TRACK TWO FAR LEFT SPAN WIRE SIGNALS WITH LEFT TURN ARROWS	S/B	◆R	<b>←</b> R	<b>◆</b> R	<b>4</b> -R	<b>←</b> G	<b>∢</b> G	<b>←</b> R	<b>←</b> R	<b>∢</b> -R	<b>←</b> R	<b>∢</b> -R	<b>←</b> R	<b>←</b> G	<b>4</b> -G	<b>←</b> R	<b>∢</b> -R	<b>←</b> R	<b>4</b> -R	<b>←</b> G	<b>◆</b> Y	<b>←</b> R	R	Δ				
MAIN STREET. NEAR SIDE RIGHT SPAN WIRE SIGNAL	E/B	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	R	R	R	R	Δ
MAIN STREET, EAST OF TRACK FAR SPAN WIRE SIGNALS	E/B	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	Υ	R	R	R	R	R	R	R	R	R	R	R	Δ
MAIN STREET, EAST OF TRACK LOW MOUNT IN BARREL (ON LEFT), SPAN WIRE, AND RIGHT LOW WOUNT SIGNALS	W/B	R	R	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	Δ
MAIN STREET, WEST OF TRACK FAR SPAN WIRE SIGNALS	W/B	R	R	R	R	R	R	R	R	G <b>4</b> -G	G <b>4</b> -G	Υ	R	R	R	R	R	R	R	G <b>◆</b> G	G . <b>4</b> -G	Υ	R	R	R	R	G <b>4</b> -G	Δ
PEDESTRIAN SIGNAL CROSSING MAIN STREET ON EAST SIDE OF ILLINOIS ROUTE 47	(	FH	JH.	FH	H	Н	H	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Δ
PEDESTRIAN SIGNAL CROSSING MAIN STREET ON WEST SIDE OF ILLINOIS ROUTE 47	$\wedge$	H	H	FH	H	FH	TH	Н	Н	Н	Н	Н	Н	Н	Н	H	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Δ
PEDESTRIAN SIGNAL CROSSING ILLINOIS ROUTE 47 ON NORTH SIDE OF MAIN STREET		Н	Н	Н	H/	Н	Н	Н	Н	FH	Н	Н	H	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Δ
PEDESTRIAN SIGNAL CROSSING ILLINOIS ROUTE 47 ON SOUTH SIDE OF MAIN STREET		Н	Н	Н	Н	Н	Н	FH	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Δ

- EMERGENCY VEHICLE SEQUENCE SHALL PROVIDE THE PROPER CLEARANCE INTERVAL TO RESUME THE NORMAL SEQUENCE OF OPERATION OR PROPER CLEARANCE INTERVAL TO DISPLAY A DIFFERENT EMERGENCY VEHICLE INTERVAL AFTER EMERGENCY VEHICLE INTERVAL 2, 3, 4 OR 5 IS TERMINATED.
- ↑ RAILROAD PREEMPTION SEQUENCE SHALL PROVIDE THE PROPER CLEARANCE INTERVAL TO RESUME THE NORMAL SEQUENCE OF OPERATION OR PROPER CLEARANCE INTERVAL TO DISPLAY AN EMERGENCY VEHICLE INTERVAL (IF APPLICABLE) AFTER RAILROAD PREEMPTION INTERVAL 5 IS TERMINATED.

THE TRAFFIC SIGNAL CONTROL EQUIPMENT FOR THIS PROJECT SHALL BE "EAGLE" TO MATCH THE EXISTING ADJACENT SYSTEM.

REVISIONS NAME DATE

12/21/200

ADDENDUM A

HOLD


GANDHI AND ASSOCIATES, INC. ENGINERS AND PLANNERS 6035 N. NORTHWEST HIGHWAY SUITE 306 CHICAGO, ILLINOIS 6063I TEL. (773) 774-5910


ILLINOIS DEPARTMENT OF TRANSPORTATION TEMPORARY EMERGENCY VEHICLE PREEMPTION SEQUENCE OF OPERATIONS & TEMPORARY RAILROAD PREEMPTION
SEQUENCE OF OPERATIONS
ILLINOIS ROUTE 47 AT MAIN STREET
STAGE 3, STAGE 3B, AND STAGE 3C.


SCALE: NONE DATE: APRIL 17, 2009

(SHEET 2 OF 2) DRAWN BY: MAA

DESIGNED BY: PKG/RRM
CHECKED BY: PKG/HPS









GANDHIAND ASSOCIATES, INC.

ENGINEERS AND PLANNERS 6035 N. NORTHWEST HIGHWAY SUITE 306 CHICAGO, ILLINOIS 60631 TEL. (773) 774-5910



326 * McHENRY 502	291
	60. U A
STA. TO STA.	
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT:	

\* (105X & 106) WRS-2



#### TRAFFIC SIGNAL LEGEND

	PROPOSED	EXISTING	
CONTROLLER		$\bowtie$	
SERVICE INSTALLATION	•	ф	
SIGNAL HEAD	-	$\rightarrow$	
SIGNAL HEAD WITH BACKPLATE	→▶	$+\triangleright$	
SIGNAL HEAD, PEDESTRIAN	Marin Assessment	—0	
SIGNAL POST	•	0	
MAST ARM ASSEMBLY AND POLE, STEEL	•	O	
MAST ARM ASSEMBLY AND POLE, ALUMINUM COMBINATION MAST ARM ASSEMBLY AND POLE,			
STEEL WITH LUMINAIRE	• <del>**</del>	o-¤—	
UNIT DUCT	UD		
COMMON TRENCH	СТ		
HANDHOLE			
HEAVY DUTY HANDHOLE	H	H	
DOUBLE HANDHOLE			
GALVANIZED STEEL CONDUIT IN TRENCH OR PUSHED			
PEDESTRIAN PUSHBUTTON DETECTOR	<u>•</u>	<u> </u>	
DETECTOR LOOP			
CAST IRON JUNCTION BOX	1	① "E"	
EMERGENCY VEHICLE SYSTEM DETECTOR	••	$\bowtie$	
CONFIRMATION BEACON	•(	0—0	
SIGNAL HEAD, OPTICALLY PROGRAMMED	— <b>&gt;</b> "P"	— <b>&gt;</b> ′P′′	
CONDUIT SPLICE			
WOOD POLE	$\otimes$	⊗ ′′E′′	
RACEWAY FOR MAGNETIC DETECTOR, TYPE I OR TYPE II		"E"	
VEHICLE DETECTOR, NON COMPENSATED MAGNETIC TYPE			
RAILROAD CONTROL CABINET	Ř><Ř	R''E''	
TELEPHONE CONNECTION	T	I	
ILLUM:NATED SIGN, FIBER OPTIC "NO LEFT TURN"	$\odot$	<b>™</b> "E"	
ILLUM NATED SIGN, FIBER OPTIC "NO RIGHT TURN"		(¥)′′E′′	
MICROWAVE VEHICLE SENSOR			
UPS-BATTERY BACK-UP	В	[B]	
CROSSING GATE	 <b>X⊕X</b> ►	X0X	
RAILROAD CANT,MAST ARM			
X	· X	XOX	×

THE TRAFFIC SIGNAL CONTROL EQUIPMENT FOR THIS PROJECT SHALL BE "EAGLE" TO MATCH THE EXISTING ADJACENT SYSTEM.



GANDHI AND ASSOCIATES, INC. ENGWEERS AND PLANNERS 6035 N. NORTHWEST HIGHWAY SUITE 306 CHICAGO, ILLINOIS 60631 TEL. (773) 774-5910

REVISIO	N S
NAME	DATE
ADDENDUM A	12/21/2009

#### ILLINOIS DEPARTMENT OF TRANSPORTATION

TRAFFIC SIGNAL INSTALLATION ILLINOIS ROUTE 47 AT MAIN STREET (SHEET 2 OF 2)

SCALE: 1"=20"

DATE: APRIL 17, 2009

DRAWN BY: MAA DESIGNED BY: PKG/RRM CHECKED BY: PKG/RRM

F.A.P. RTE.	SECTION		COUNTY	TOTAL SHEETS	SHEET NO
326	*		McHENRY	502	293
STA.		- '	TO STA	1.	
FED. ROAD DIST. NO.		ILI INOTS	FED.	ATO PROJECT:	

#### SCHEDULE OF QUANTITIES

QUANTITY UNIT ITEM SIGN PANEL - TYPE 132 sa Ft 104 METAL POST - TYRE A FOOT CONDUIT IN TRENCH, 2" DIA., GALVANIZED STEEL 65 FOOT CONDUIT IN TRENCH, 21/2" DIA., GALVANIZED STEEL CONDUIT IN TRENCH, 3" DIA., GALVANIZED STEEL 68 FOOT 74 FOOT CONDUIT IN TRENCH, 4" DIA., GALVANIZED STEEL 10 FOOT CONDUIT IN TRENCH, 5" DIA., GALVANIZED STEEL 462 FOOT CONDUIT PUSHED, 2" DIA., GALVANIZED STEEL 105 FOOT CONDUIT PUSHED, 21/2" DIA., GALVANIZED STEEL FOOT 958 CONDUIT PUSHED, 4" DIA., GALVANIZED STEEL EACH HANDHOLE EACH HEAVY-DUTY HANDHOLE EACH DOUBLE HANDHOLE 826 FOOT TRENCH AND BACKFILL FOR ELECTRICAL WORK FULL-ACTUATED CONTROLLER AND TYPE IV CABINET, SPECIAL EACH EACH TRANSCEIVER - FIBER OPTIC 1036 FOOT ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 2C ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C 2546 FOOT 7474 FOOT ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 5C 873 FOOT ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 7C 3389 FOOT ELECTRIC CABLE IN CONDUIT, LEAD-IN, NO. 14 1 PAIR 134 FOOT ELECTRIC CABLE IN CONDUIT, SERVICE, NO. 6 2C EACH TRAFFIC SIGNAL POST, GALVANIZED STEEL 14 FT. TRAFFIC SIGNAL POST, GALVANIZED STEEL 15 FT. EACH EACH STEEL MAST ARM ASSEMBLY AND POLE, 36 FT. EACH STEEL MAST ARM ASSEMBLY AND POLE, 50 FT. EACH STEEL MAST ARM ASSEMBLY AND POLE, 60 FT. EACH STEEL MAST ARM ASSEMBLY AND POLE, 72 FT. 28 FOOT CONCRETE FOUNDATION, TYPE A FOOT CONCRETE FOUNDATION, TYPE C 30 FOOT CONCRETE FOUNDATION, TYPE E 36-INCH DIAMETER FOOT 50 CONCRETE FOUNDATION, TYPE E 42-INCH DIAMETER EACH SIGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST ARM MOUNTED SIGNAL HEAD, LED, 1-FACE, 3-SECTION, BRACKET MOUNTED EACH SIGNAL HEAD, LED, 1-FACE, 4-SECTION, BRACKET MOUNTED EACH SIGNAL HEAD, LED, 1-FACE, 4-SECTION, MAST ARM MOUNTED SIGNAL HEAD, LED, 2-FACE, 3-SECTION, BRACKET MOUNTED EACH PEDESTRIAN SIGNAL HEAD, LED, 1-FACE, BRACKET MOUNTED WITH COUNTDOWN TIMER EACH PEDESTRIAN SIGNAL HEAD, LED, 2-FACE, BRACKET MOUNTED WITH COUNTDOWN TIMER EACH TRAFFIC SIGNAL BACKPLATE INDUCTIVE LOOP DETECTOR 12 EACH EACH LIGHT DETECTOR FACH LIGHT DETECTOR AMPLIFIER PEDESTRIAN PUSH-BUTTON FACH TEMPORARY TRAFFIC SIGNAL INSTALLATION EACH REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT EACH REMOVE EXISTING HANDHOLE EACH REMOVE EXISTING CONCRETE FOUNDATION 1375 FOOT PREFORMED DETECTOR LOOP EACH PAINT NEW TRAFFIC SIGNAL POST FACH PAINT NEW MAST ARM POLE, UNDER 40 FEET PAINT NEW MAST ARM POLE, 40 FEET AND OVER TEMPORARY TRAFFIC SIGNAL TIMING EACH EACH SERVICE INSTALLATION - POLE MOUNTED UNINTERRUPTIBLE POWER SUPPLY EACH 1511 FOOT ELECTRIC CABLE IN CONDUIT, GROUNDING, NO. 6 1C **\*** 993 FOOT ELECTRIC CABLE IN CONDUIT NO. 20 3/C, TWISTED, SHIELDED 210 FOOT ELECTRIC CABLE IN CONDUIT, RAILROAD NO. 14 3/C RAILROAD PROTECTIVE LIABILITY L SUM 182 FOOT STEEL CASINGS 8"

\* 100% COST TO VILLAGE OF HUNTLEY

THE TRAFFIC SIGNAL CONTROL EQUIPMENT FOR THIS PROJECT SHALL BE "EAGLE" TO MATCH THE EXISTING ADJACENT SYSTEM.



REVISIONS

NAME DATE

ADDENDUM A 12/21/2009

SCA

SCHEDULE OF QUANTITIES
ILLINOIS ROUTE 47
AT MAIN STREET

ILLINOIS DEPARTMENT OF TRANSPORTATION

SCALE: 1"=20" DATE: APRIL 17, 2009 DRAWN BY: MAA DESIGNED BY: PKG/RRM CHECKED BY: PKG/RRM



GANDHIAND ASSOCIATES, INC. ENGINEERS AND PLANNERS 6035 N. NORTHWEST HIGHWAY SUITE 306 CHICAGO, ILLINOIS 60631 TEL. (773) 774-5910

F.A.P. RTE.	SECTION		COUNTY		TOTAL	SHEET NO
326	*		MOHENRY		502	295
STA.			TO S	TA.		
FED. ROAD DIST. NO.		ILLINOIS	FED.	. AIC	PROJECT	

EMEDGENICY	VEHICLE	CECLIENCE	$\bigcirc$ E	ODEDATIONS
<b>EMERGENCY</b>	VEHICLE	SECUENCE	UF	OPERATIONS

		/Δ\	ΕM	ER(	iEN.	CY '	VEH	ICLE	SI	EQU	ENC	ΕО	FC	)PEF	RATIO	ONS																			2255112742		PREFMETOR	Toossuos	
		7																																	PREEMPTOR NUMBER 3	PREEMPTOR NUMBER 4	NUMBER 5		
CHANGE FROM NORMAL SEQUENCE OF OPERATION INTERVAL NUMBER			1		1		1			5		5	3	8		1	11		11			11				16	20.00	16			19			19					CLEAR
EMERGENCY VEHICLE PRE-EMPTION SEQUENCE OF OPERATION INTERVAL NUMBER		1A 1B	\1C	1D 1E	E 1F	1G 1	H 1J	1K 1	L IN	1 1N	1P 1Q	1R 1	S 1T	1U 1	IV 1W	1X 1	Y 1Z	Z IAA	IBB 1CC	1DD 11	EE 1FF	1GG	1HH	1JJ	1KK	1LL	1MM	1NN	1PP	100	1RR	155	1TT	100	2	3	4	5	TO NORMAL
CHANGE TO EMERGENCY VEHICLE PRE-EMPTION SEQUENCE OF OPERATION INTERVAL NUMBER		1B 1C	10	2 1	= 4	1H 1	J 1K	3, 5 1	M 1N	1P :	10 <sup>2, 3</sup>	4	2 10	1V 3/4	, 5 1X	1Y 12	Z 1A	A 2	.CC 1DD	4 1	FF 1G0	1HH	1JJ	3, 5	IL- I	1MM 2	, 4, 5	3	100	1RR	1SS	1TT	2, 3	5			6		SEQUENCE
ILLINOIS ROUTE 47, NEAR RIGHT, RIGHT AND MID MAST ARM SIGNALS	N/B	R R	R	\R F	R	R	RR	R	RR	R	R R	R	G	Υ	R G	G C	G G	G	G Y	R	G Y	R	R	R	R	R	R	R	R .	R	R	R	R	R	G	R	R	R	$\Diamond$
ILLINOIS ROUTE 47. FAR LEFT AND END MAST ARM SIGNALS		<b>4</b> G <b>4</b> G	<b>4</b> -G •	<b>+</b> G ←	Y ←R	<b>←</b> Y <b>←</b>	-R <b>←</b> R	<b>←</b> R <b>←</b>	R►F	R ← R ←	⊦R <b>∢</b> -R	<b>←</b> R <b>←</b>	G <b>←</b> G	<b>4</b> -Y	R <b>←</b> R	<b>←</b> R <b>←</b>	-R <b>∢</b> f	R ←R	•R •R	<b>←</b> R <b>◆</b>	-R <b>←</b> F	₹R	<b>←</b> R	<b>←</b> R	<b>←</b> R	◆R	<b>←</b> R	<b>∢</b> R	<b>←</b> R	<b>∢</b> -R	<b>◆</b> R	<b>←</b> R	<b>←</b> R	<b>←</b> R	<b>←</b> G	<b>←</b> R	◆R	<b>∢</b> R	$\Diamond$
ILLINOIS ROUTE 47, NORTH OF TRACK RIGHT LOW MOUNT AND TWO RIGHT CANTILEVER SIGNALS		RK		۱ '	1						17 17	G	, ] ,,	1 1		YR		1	-   -	"	G Y	R	R	R	R	R	R	R	R	R	R	R	R ·	R	R	R	G	R	$\Diamond$
ILLINOIS ROUTE 47, NORTH OF TRACK MEDIAN LOW MOUNT AND TWO MEDIAN CANTILEVER SIGNALS											-R <b>←</b> R	<b>←</b> G <b>←</b>	R ←R	<b>←</b> R <b>←</b>	⊢R ←R	<b>←</b> R. <b>←</b>	R ◀ F	R ←R	+R ←R	<b>4</b> -R <b>4</b>	-R <b>←</b> F	₹R	<b>←</b> R	<b>◆</b> R	<b>←</b> ₹	◆R	<b>4</b> -R	<b>∢</b> -R	<b>←</b> R	<b>←</b> R	◆R	<b>4</b> -R	<b>←</b> R	◆R	◆R	<b>∢</b> R	<b>←</b> G	<b>←</b> R	$\Diamond$
ILLINOIS ROUTE 47, SOUTH OF TRACK NEAR RIGHT, RIGHT AND MID MAST ARM SIGNALS		RR			-	/						G I						1 ''		G			Υ	R	R	R	R	R	R	R	R	R	R	R	R	R	G	R	$\Diamond$
ILLINOIS ROUTE 47, SOUTH OF TRACK FAR LEFT AND END MAST ARM SIGNALS					V	/					1				⊢R ←R	-R -	-R <b>←</b> F	R <b>∢</b> R ·	+R <b>∢</b> R	<b>4</b> -R <b>4</b>	-R <b>∢</b> -F	<b>←</b> R	<b>←</b> R	<b>◆</b> R	<b>←</b> R	<b>4</b> ∃	<b>←</b> R	<b>◆</b> R	<b>←</b> R	<b>←</b> R	<b>←</b> R	<b>4</b> -R	<b>←</b> R	<b>◆</b> R	<b>∢</b> R	<b>←</b> R	<b>←</b> G	<b>←</b> R	$\Diamond$
MAIN STREET. RIGHT AND MID MAST ARM SIGNALS	E/B	RR	R	R F	R	RI	₹ R	R	R R	R	RR	RI	R	R	RR	R F	R R	R	RR	R	RR	R	R	R	G	Y	R	G	R	R	R	R	R	R	R	G	R	R	$\Diamond$
MAIN STREET. FAR LEFT AND END MAST ARM SIGNALS	E/B	R R	R	R F	RR	R	₹ R	R	R	R	RR	RI	R	R	RR	RR	R R	R	R R	R	R R	R	R	R .	G <b>4</b> -G	Y	R	G <b>←</b> G	R	R	R	R	R	R	R	G <b>∢</b> -G	R	R	$\Diamond$
MAIN STREET, EAST OF TRACK RIGHT LOW MOUNT, MEDIAN LOW MOUNT AND CANTILEVER SIGN	NALS	R R	R	R F	R	R	R R	R	R	R	RR	RI	R	R	RR	R F	R	R	RR	R	RR	R	R	R	R	R	R	R	G	Υ	R	R	R	G	R	R	R	G	$\Diamond$
MAIN STREET, WEST OF TRACK RIGHT AND MID MAST ARM SIGNALS	W/B	R R	R	R F	R	R F	R R	R	R	R	RR	RF	R	R	RR	R R	R R	R	RR	R	R R	R	R	R	R	R	R	R	G	G	G	Y	R	G	R	R	R	G	$\Diamond$
MAIN STREET, WEST OF TRACK FAR LEFT AND END MAST ARM SIGNALS	W/B	RR	R	R F	R	R F	R R	R	R R	R	RR	R	R	R	RR	R F	R	R	RR	R	R R	R	R	R	R	R	R	R	G <b>←</b> G	G <b>←</b> G	G <b>←</b> G	Y	R	G <b>←</b> G	R	R	R	G <b>∢</b> G	$\Diamond$
PEDESTRIAN SIGNALS CROSSING MAIN STREET, ON EAST SIDE OF ILLINOIS ROUTE 47.		НН	Н	НЬ	1 H	Н	Н	Н	Н	Н	НН	H F	H FH	Н	H FH	H F	н	Н	FH H	4 F	НН	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	$\Diamond$
PEDESTRIAN SIGNALS CROSSING MAIN STREET. ON WEST SIDE OF ILLINOIS ROUTE 47.		НН	Н	H F	H	н	Н	H F	Н	Н	НН	FH I	Н	Н	H FH	НН	н н	Н	FH H	НF	НН	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	H	Н	Н	$\Diamond$
PEDESTRIAN SIGNALS CROSSING ILLINOIS ROUTE 47. ON NORTH SIDE OF MAIN STREET.		НН	Н	H F	1 H	Н	Н	Н	Н	Н	Н	Н	4 H	Н	нН	НН	н	Н	Н	Н	НН	Н	Н	Н	Н	Н	Н	Н	FH	Н	Н	Н	Н	FH	Н	Н	Н	Н	$\Diamond$
PEDESTRIAN SIGNALS CROSSING ILLINOIS ROUTE 47. ON SOUTH SIDE OF MAIN STREET.		н	Н	H	H	Н	Н	Н	4   H	Н	н	Н	н н	Н	Н	<del> </del>	н	Н	н	Н	Н	Н	Н	Н	FH	Н	Н	FH	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	$\Diamond$

	RAILROAD PR	EEI	MPT	ΠΟΝ	l S	3EC	QUE	NC	E (	OF_	OF	PEF	RAT∣	NOI	<u> </u>		PTOR P						PREEN NUMB	MPTOR		PREEMPTOR NUMBER 2	]		A	\
CHANGE FROM NORMAL SEQUENCE OF											T					NUMBE	L C 7	NUMBE	7 4	NUMDE	7 2		MUMB	O 7.30		NUMBER Z				<del>-</del>
OPERATION INTERVAL NUMBER		1		5		8		11		16	5		1	9	ı															
CHANGE FROM EMERGENCY VEHICLE PREEMPTION SEQUENCE INTERVAL NUMBER													-			2		3		4			5	)						
RAILROAD PREEMPTION SEQUENCE OF OPERATION INTERVAL NUMBER		1A	18	1C 1	LD	1E	1F	1G	1H	1N	1P	1J	1K	1L	1M	10	1R	15	17	10	1V	1W	1X	1Y	1Z	2	3	4	5	CLEAR
CHANGE TO RAILROAD PREEMPTION SEQUENCE OF OPERATION INTERVAL NUMBER		1B	2	1D	2	1F	2	1H	2	1P	2	1K	1L	1M	2 (	1R	2	1T	2	1V	2	ĺχ	1Y	1Z	2	3	4	5		NORMAL SEQUENCE
ILLINOIS ROUTE 47. NEAR RIGHT, RIGHT AND MID MAST ARM SIGNALS	N/B	R	R	R	R	Υ	R	Y	R	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	R	R	R	R	R	R	Δ
ILLINOIS ROUTE 47. FAR LEFT AND END MAST ARM SIGNALS	N/B	<b>←</b> Y	<b>←</b> R	<b>←</b> R •	←R ·	<b>←</b> Y	<b>←</b> R	◆R	<b>∢</b> -R	<b>∢</b> -R	<b>4</b> -R	<b>∢</b> R	<b>←</b> R	<b>∢</b> R	<b>←</b> R	<b>←</b> Y	<b>←</b> R •	<b>←</b> R •	<b>←</b> R	<b>←</b> R	<b>←</b> R •	∙R	<b>←</b> R	<b>◆</b> R	<b>∢</b> -R	<b>←</b> R	◆R	<b>←</b> R	<b>←</b> R	Δ
ILLINOIS ROUTE 47, NORTH OF TRACK RIGHT LOW MOUNT AND TWO RIGHT CANTILEVER SIGNALS	S/B	R	R	Y	R	R	R	Y	R	R	R	R	R	R	R	R	R	R	R	Υ	R	R	R	R	R	R	R	R	R	Δ
ILLINOIS ROUTE 47, NORTH OF TRACK MEDIAN LOW MOUNT AND TWO MEDIAN CANTILEVER SIGNALS	S/B	<b>◆</b> Y	<b>←</b> R	<b>←</b> Y •	<b>⊢</b> R ·	◆R	<b>◆</b> R	<b>←</b> R	<b>←</b> R	◆R	<b>←</b> R	<b>◆</b> R	<b>←</b> R	<b>←</b> R	<b>4</b> -R	<b>←</b> R	<b>←</b> R	<b>←</b> R •	<b>←</b> R	<b>←</b> Y •	<b>←</b> R •	€R	<b>4</b> -R	◆R	◆R	<b>←</b> R	<b>←</b> R	<b>←</b> R	<b>←</b> R	Δ
ILLINOIS ROUTE 47, SOUTH OF TRACK NEAR RIGHT. RIGHT AND MID MAST ARM SIGNALS	S/B	R	R	G	G	R	R	G	G	R	R	R	R	R	R	R	R	R	R	G	G	R	R	R	R	G	Y	R	R	Δ
ILLINOIS ROUTE 47, SOUTH OF TRACK FAR LEFT AND END MAST ARM SIGNALS	S/B	<b>←</b> G	<b>←</b> G	<b>←</b> G <b>←</b>	<b>⊢</b> G ·	<b>∢</b> -R	<b>←</b> R	<b>∢</b> R	<b>∢</b> -R	<b>◆</b> R	<b>◆</b> R	◆R	<b>←</b> R	<b>←</b> R	◆R	◆R	<b>←</b> R •	<b>←</b> R •	<b>∢</b> R ·	<b>←</b> G •	<b>←</b> G •	<b>←</b> R	<b>4</b> -R	<b>4</b> -R	<b>4</b> -R	<b>←</b> G	<b>←</b> Y	<b>←</b> R	<b>◆</b> R	Δ
MAIN STREET. RIGHT AND MID MAST ARM SIGNALS	E/B	R	R	R	R	R	R	R	2	Y	R	R	R	R	R	R	R	Υ	R	R	R	R	R	R	R	R	R	R	R	Δ
MAIN STREET. FAR LEFT AND END MAST ARM SIGNALS	E/B	R	R	R	R	R	R	R	R	Υ	R	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	R	R	R	R	Δ
MAIN STREET, EAST OF TRACK RIGHT LOW MOUNT, MEDIAN LOW MOUNT AND CANTILEVER SIGNALS	W/B	R	R	R	R	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	R	R	Y	R	R	R	R	R	R	R	Δ
MAIN STREET, WEST OF TRACK RIGHT AND MID MAST ARM SIGNALS	W/B	R	R	R	R	R	R	R	R	R	R	G	G	Υ	R	R	R	R	R	R	R	G	G	Y	R	R	R	R	G	Δ
MAIN STREET, WEST OF TRACK FAR LEFT AND END MAST ARM SIGNALS	W/B	R	R	R	R	R	R	R	R	R	R	G <b>←</b> G	G <b>←</b> G	Υ	R	R	R	R	R	R	R		G <b>4</b> -G	Y	R	R	R	R	G <b>←</b> G	Δ
PEDESTRIAN SIGNALS CROSSING MAIN STREET, ON EAST SIDE OF ILLINOIS ROUTE 47.		Н	Н	Н	Н	FH	н	FH	Н	Н	Н	Н			Н	Н	н	Н	Н	Н				Н	Н	Н	Н	Н	Н	Δ
PEDESTRIAN SIGNALS CROSSING MAIN STREET, ON WEST SIDE OF ILLINOIS ROUTE 47,		Н	Н	FH	Н	Н	Н	FH	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	Δ
PEDESTRIAN SIGNALS CROSSING ILLINOIS ROUTE 47, ON NORTH SIDE OF MAIN STREET.		Н	Н	Н	н	Н	Н	н	Н	Н	Н	FH	Н	Н	Н	н	н	н	н	Н	н	н	Н	Н	Н	Н	Н	Н	н	Δ
PEDESTRIAN SIGNALS CROSSING ILLINOIS ROUTE 47, ON SOUTH SIDE OF MAIN STREET.		Н	Н	Н	Н	Н	Н	н	Н	FH	Н	Н	Н	Н	Н	Н.	н	Н	Н	Н	н	Н	Н	Н	н	H	Н	Н	Н	Δ

♦ EMERGENCY VEHICLE SEQUENCE SHALL PROVIDE THE PROPER CLEARANCE INTERVAL TO RESUME THE NORMAL SEQUENCE OF OPERATION OR PROPER CLEARANCE INTERVAL TO DISPLAY A DIFFERENT EMERGENCY VEHICLE INTERVAL AFTER EMERGENCY VEHICLE INTERVAL 2, 3, 4 OR 5 IS TERMINATED.

A RAILROAD PREEMPTION SEQUENCE SHALL PROVIDE THE PROPER CLEARANCE INTERVAL TO RESUME THE NORMAL SEQUENCE OF OPERATION OR PROPER CLEARANCE INTERVAL TO DISPLAY AN EMERGENCY VEHICLE INTERVAL (IF APPLICABLE) AFTER RAILROAD PREEMPTION INTERVAL 5 IS TERMINATED.

THE TRAFFIC SIGNAL CONTROL EQUIPMENT FOR THIS PROJECT SHALL BE "EAGLE" TO MATCH THE EXISTING ADJACENT SYSTEM.



GANDHI AND ASSOCIATES, INC. ENGINEERS AND PLANNERS 6035 N. NORTHWEST HIGHWAY SUITE 306 CHICAGO, ILLINOIS 60631TEL. (7773) 774-5910

ILLINOIS DEPARTMENT OF TRANSPORTATION

EMERGENCY VEHICLE
SEQUENCE OF OPERATION &

NAME CATE
ADDENDUM A 12/21/22009


EMERGENCY VEHICLE
SEQUENCE OF OPERATION &


RAILROAD PREEMPTION SEQUENCE OF OPERATAION


ILLINOIS ROUTE 47 AT MAIN STREET

SCALE; NONE
DATE: APRIL 17, 2009

DRAWN BY: MAA DESIGNED BY: PKG/RRM CHECKED BY: PKG/HPS







#### STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

### INDEX OF DRAWINGS

11

12

Sheet No.	Title
1	General Plan & Elevation
2	General Notes & Total Bill of Material
3	Removal
4	Culvert Details 1 of 5
5	Culvert Details 2 of 5
6	Culvert Details 3 of 5
7	Culvert Details 4 of 5
8	Culvert Details 5 of 5
9	Wingwall (T-Type Elevations and Section)
10	Temporary Geotextile Wall Construction Sequence

Bar Splicer Assembly Details

Soil Boring Logs

Soil Boring Logs

#### GENERAL NOTES

- 1. Reinforcement bars shall conform to the requirements of ASTM A 706 Gr 60 (IL Modified). See Special Provisions.
- 2. Reinforcement bars designated (E) shall be epoxy coated.
- 3. A cantilevered sheet piling design does not appear feasible and additional members or other retention systems may be necessary. The Contractor shall submit a temporary soil retention system design including plan details and calculations for review and acceptance by the Engineer.
- 4. Excavation behind existing abutment walls shall be performed to balance front and back soil pressure before removing the existing superstructure. The Contractor shall sawcut the upper portion of the existing abutment at the stage removal line before Stage I removal to ensure the remaining portion will not be prematurely damaged.


## HORIZONTAL CURVE DATA

(Curve 2) P.I. Sta. 28+09.68 △ = 15°29′27" D = 2°16′24" R = 2520.38' L = 681.43' T = 342.81' E = 23.21'P.C. Sta. 24+66.88 P.T. Sta 31+48.31 S.E. = 0.029 '/'



PROFILE GRADE (IL Route 47)

DESIGNED	- NDR
CHECKED	- DSE
DRAWN	- RTT
CHECKED	- DSE
DATE	- Aug. 5, 2009



@ Northbound and Southbound

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NG.	SHEET NO. 2
FAP 326	*	McHENRY	502	331	13 SHEETS
FED. ROAD DIST	. NO. 1	ILLINOIS FED. AID PR	ојест- 326	;	

Contract No. 62882 ★ (105X & 106)WRS-2

#### TOTAL BILL OF MATERIAL

TOTAL DILL OF MATTER	_	,
ITEM	UNIT	TOTAL
Granular Embankment, Special	Cu Yd	389.3
Geotechnical Fabric for Ground Stabilization	Sq Yd	800.0
Removal of Existing Structures	Each	1.0
Removal and Disposal of Unsuitable Material for Structures	Cu Yd	651.0
Reinforcement Bars	Pound	97,450
Reinforcement Bars, Epoxy Coated	Pound	610
Bar Splicers	Each	148
Name Plates	Each	1
Concrete Box Culverts	Cu Yd	414.9
Geotextile Retaining Wall	Sq Ft	161.0
Temporary Soil Retention System	Sq Ft	706.0 i

# WATERWAY INFORMATION

			11/1/2	-////////	2111 01111	77 1011				
Drainage Are	Exist. Low Grade Elev. 879.10  Drainage Area = 12.0 mi <sup>2</sup> Prop. Low Grade Elev. 880.30 © Sta. 25+25									
Flood	Freq.	Q	Opening	Sq. Ft.	Appx. Nat.	U.S. Nat.	Head	- Ft.	Headw	ater El.
7 7000	Yr.	C.F.S.	Exist.	Prop.	H.W.E.	H.W.E.	Exist.	Prop.	Exist.	Prop.
	10	459	166.8	179.2	871.82	871.81	0.03	0.00	871.85	871.44
Design	50	839	210.0	229.9	873.55	873.55	0.07	0.00	873.62	873.12
Base	100	1043	227.3	253.4	874.26	874.26	0.11	0.00	874.37	873.89
Overtopping	I									
Max. Calc.	500	1438	263.1	293.8	875.40	875.39	0.50	0.00	875.90	875.23
							Freet	ooard	5.5	7.2

# DESIGN SCOUR ELEVATION TABLE

Decian Son	ir Elevation	(f+)	Upstream	Downstream
Design 3000	esign Scour Elevation (ft)	(11)	861.62	861.48




www.stanleyconsultants.com Illinois Firm Registration No.: 1184-001533

GENERAL NOTES & TOTAL BILL OF MATERIAL IL ROUTE 47 OVER S. BRANCH KISHWAUKEE RIVER

F.A.P. 326 - SECT. (105X & 106)WRS-2 McHENRY COUNTY STATION 25+24.62

STRUCTURE NO. 056-0085





DESIGNED - NDR

CHECKED DSE

CHECKED DSE

DRAWN

- RTT

#### BILL OF MATERIAL

ITEM	UNIT	TOTAL
Removal of Existing Structures	Each	1
Temporary Soil Retention System	Sq Ft	706
	Â	

REMOVAL IL ROUTE 47 OVER S. BRANCH KISHWAUKEE RIVER F.A.P. 326 - SECT. (105X & 106)WRS-2 MCHENRY COUNTY

STATION 25+24.62 STRUCTURE NO. 056-0085


SHEET NO. 3


332 13 SHEETS

# STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

		- 9	
02	8"	32′-5″	8"
<i>a</i> <sub>3</sub>	8"	35′-0"	8"

# BARS a2 & a3





# FIELD CUTTING DIAGRAM

Order bars full length, cut to fit as shown and place at one end of the dimension line shown on the plan. use remainder of bars at opposite end of the dimension line.

ROUTE NO.	SECTION	COUNTY		TOTAL SHEETS	SHEET NG.	SHEET	NO.	8
FAP 326	*	McHENRY		502	337	<i>13</i> sн	EETS	
FED. ROAD DIST. NO. 1 ILLINOIS		FEO. AID PRO	олест- <i>326</i>					

Contract No. 62882 ★ (105X & 106)WRS-2

# BILL OF MATERIAL


Bar	No.	Size	Length	Shape
a1	424	#7	32'-5"	
a2	424	#6	33′-9"	
аЗ	112	#6	36′-4"	
a4	112	#7	35′-0"	
d1	86	#4	5′-6"	
U1	00	# <del>4</del>	מי כ	
h1	444	#5	22'-1"	
h2	444	#5	25'-6"	
hЗ	4	#6	35′-3"	
h4	14	#6	<i>35′-10"</i>	
h5	8	#4	6'-0"	
h6	12	#6	35′-8"	
v1	1092	#4	2'-8"	
v2	1092	#4	8'-0"	
v3	8	#4	8'-9"	
v4	8	#4	5′-10"	
	cement E	Pound	95,560	
Bar Spi	icers	Each	148	
	e Box Cu	Cu. Yd.	381.6	
Geotext.	ile Retair	ning Wall	Sq. Ft.	161



www.stanleyconsultants.com Illinois Firm Registration No.: 1184-001533

CULVERT DETAILS

IL ROUTE 47 OVER S. BRANCH KISHWAUKEE RIVER F.A.P. 326 - SECT. (105X & 106)WRS-2 MCHENRY COUNTY STATION 25+24.62 STRUCTURE NO. 056-0085



#### STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION



13 SHEETS

Contract No. 62882 ★ (105X & 106)WRS-2

#### <u>NOTES</u>

Bar splicer assemblies shall be of an approved type and shall develop in tension at least 125 percent of the yield strength of the lapped reinforcement bars.

Splicer rods shall be of minimum 60 ksi yield strength, threaded or coiled full length. All reinforcement bars shall be lapped and tied to the splicer rods or dowel bars. Bar splicer assemblies shall be epoxy coated according to the requirements for

reinforcement bars. Other systems of similar design may be submitted to the Engineer for approval. Approval


shall be based on certified test results from an approved testing laboratory that the proposed bar splicer assembly satisfies the following requirements:

Minimum Capacity (Tension in kips) = 1.25 x fy x  $A_t$ 

Minimum \*Pull-out Strength =  $0.66 \times fy \times A_t$ (Tension in kips)

Where fy = Yield strength of lapped reinforcement bars in ksi.  $A_t$  = Tensile stress area of lapped reinforcement bars. \* = 28 day concrete

	BAR SPLICER ASSEMBLIES								
			Strength Requirements						
<u>^</u>	Bar Size to be Spliced	Splicer Rod or Dowel Bar Length		Min. Pull-Out Strength kips - tension					
	#4	1'-8''	14.7	7.9					
	#5	2'-2"!	23.0	12.3					
A	#6	2'-7''	33.1	17.4					
	#7	3′-5″	45.1	23.8					
	#8	4'-6''	58.9	31.3					
	#9	5′-9′′	75.0	39.6					
	#10	7'-3"	95.0	50.3					
	#11	9'-0"	117 4	618					




# STANDARD

No. Assemblies Required	Location
148	Culvert Stage Construction Line
	Required




Illinois Firm Registration No.: 1184-001533

BAR SPLICER ASSEMBLY DETAILS *IL ROUTE 47 OVER* S. BRANCH KISHWAUKEE RIVER F.A.P. 326 - SECT. (105X & 106)WRS-2 MCHENRY COUNTY STATION 25+24.62 STRUCTURE NO. 056-0085



## INSTALLATION AND SETTING METHODS

"A" :Set bar splicer assembly by means of a template bolt. "B" :Set bar splicer assembly by nailing to wood forms or cementing to steel forms. (E): Indicates epoxy coating.



# FOR INTEGRAL OR SEMI-INTEGRAL ABUTMENTS

ROLLED THREAD DOWEL BAR

\*\* ONE PIECE

WELDED SECTIONS

BAR SPLICER ASSEMBLY ALTERNATIVES

\*\*Heavy Hex Nuts conforming to ASTM

A 563, Grade C, D or DH may be used.

Bridge Deck

Threaded or Coil

Loop Couplers (E)

- Wire Connector

*TOTO* 

The diameter of this part is

equal or larger than the

diameter of bar spliced.

	Bai	Splicer	for	#5	bar		
Min.	Capacity	= 23.0	kips	- 1	ensio	n	
Min.	Pull-out	Strength	) = 12	2.3	kips	-	tension
No.	Required	=					

DESIGNED	-	
CHECKED	-	
DRAWN	-	RTT
CHECKED	-	DSE
DATE	-	Aug. 5, 2009

Reinforcement

Bars

The diameter of this part

is the same as the diameter

of the bar spliced.

	Bar Splicer for #5 bar	
Min.	Capacity = 23.0 kips - tension	
Min.	Pull-out Strength = 12.3 kips - tension	n
No.	Required =	_

	Bar Splicer for #5 bar
Min.	Capacity = 23.0 kips - tension
Min.	Pull-out Strength = 12.3 kips - tension

FOR STUB ABUTMENTS

Threaded or Coil

Loop Couplers (E)

