



**RECESSED REFLECTIVE PAVEMENT MARKERS**

**GENERAL NOTES:**

1. INSTALLATION SHALL CONFORM TO IDOT DISTRICT ONE DETAIL (TC-11) OR LATEST FOR MARKER REPLACEMENT.
2. IDOT DISTRICT ONE DETAIL (TC-11) SHALL BE MODIFIED TO REFLECT RECESSED PAVEMENT MARKERS INSTEAD OF RAISED PAVEMENT MARKERS.

**INSTALLATION NOTES:**

1. Saw cut to dimensions shown.
2. Sawcut areas to be dry and free of material that adversely affects the adhesive bond.
3. Install the reflector with an approved two-component epoxy adhesive. Epoxy should not obscure or block the lens.
4. Install top of reflector 1/2 to 1/4 inch below the pavement surface.
5. Reflector shall be 3M Series 190.

Plotted: October 16, 2009 @ 10:39 AM By: Terri Seider-Johnson - Tab: 15 Recessed Markers 22x34

COPYRIGHT © 2009 ENGINEERING ENTERPRISES, INC.

**Engineering Enterprises, Inc.**  
CONSULTING ENGINEERS  
52 Wheeler Road  
Sugar Grove, Illinois 60554  
630.466.6700 / www.eeiweb.com

**CITY OF WARRENVILLE**  
DUPAGE COUNTY, ILLINOIS

NO.	DATE	REVISIONS

**BATAVIA ROAD**  
LAPP IMPROVEMENTS

**RECESSED REFLECTIVE**  
PAVEMENT MARKER

DATE: OCTOBER 2009  
PROJECT NO: WV0902  
FILE: WV0902-CVR  
SHEET **15** OF **27**

Path: H:\S056PROJ\W0902\DWG\W0902\DWG\FINAL\_ENC\W0902-CVR