



GENERAL NOTES

GENERAL NOTES AND CONDITIONS

All earthwork, grading and paving shall be performed in accordance with the "Standard Specifications for Road and Bridge Construction, State of Illinois Department of Transportation, adopted January 1, 2007"; the "Supplemental Specifications and Recurring Special Provisions" (current addition), and all revisions and supplements thereto, and the requirements and specifications of the County of Winnebago.

DISCRIPTION OF WORK

UTILITIES

Exact horizontal and vertical locations of existing utilities shall be determined by the Contractor at no additional cost to the contract. Locations and depths shown on these plans are only schematic representation.

The Contractor shall be responsible for protecting utility property during construction operations as outlined in Article 107.31 of the Standard Specifications. The phone number for J.U.L.I.E. is 800-892-0123. The utilities located within the project limits or immediately adjacent to the project construction limits are members of J.U.L.I.E.

Commonwealth Edison
123 Energy Ave.
Rockford, IL 61109
Phone - (815) 490-2869

Nicor Gas
300 W. Terra Cotta
Crystal Lake, IL 60014
Phone - (815) 455-0271

South Beloit Sewer
R.H. Batterman & Co., Inc.
2857 Bartells Dr,
Beloit, WI. 53511
Phone - (815) 387-7660

SBC
301 E. Milwaukee St.
Janesville, WI. 53545
Phone - (608) 5589

North Park Water District
1350 Turret Drive
Machesney Park, IL. 61115
Phone - (815) 633-5461

Charter Communication
1348 Plainfield Ave.
Janesville, WI
Phone - (608) 373-7537

Abandoned underground utilities that conflict with construction or have the potential for creating future problems shall be disposed of outside the limits of the right-of-way according to Article 202.03 of the standard specifications and as directed by the Engineer.

The Contractor is responsible for maintaining positive drainage at the conclusion of each working day.

All private entrances and side road approaches shall be bladed and rolled, as directed by the Engineer, prior to placing Hot Mix Asphalt. This work shall not be paid for separately but shall be considered incidental to INCIDENTAL HMA SURFACING. As provided in the plan quantities and shall be used only as needed and as directed by the Engineer.

HOT-MIX ASPHALT

The following Mixture requirements are applicable for this project:

MIXTURE USE(S):	SURFACE	BINDER
PG:	PG 64-22	PG 64-22
DESIGN AIR VOIDS:	4.0 @ N70	4.0 @ N50
MIXTURE COMPOSITION (GRADATION MIXTURE):	IL 9.5 or 12.5	IL 19.0
FRICITION AGGREGATE:	N	N/A
20 YEAR ESAL:	0.7	0.7
MIX UNIT WEIGHT	112 lbs/sy/in	

SHORT TERM PAVEMENT MARKING

Striping removal shall be incidental to SHORT TERM PAVEMENT MARKING. This work will not be paid for separately and shall be considered incidental to the contract and no additional compensation shall be allowed.