



WIRING DETAIL

NO SCALE

GENERAL NOTES

All taped splices shall use 2 layers of electrical tape over 3 layers of rubber tape as required by the Standard Specifications. Coat the finished taped splice with bonding compound.

All cable splices shall be taped unless another method has been specifically approved by the Engineer.

For example purposes the pole is shown on an anchor base. If the pole is required to be set on a breakaway base, consult the Standard Specifications.

All dimensions are in millimeters (inches) unless otherwise shown.

FILE NAME =	USER NAME = Ander00846	DESIGNED - PJG	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	POLE HANDHOLE WIRING NORTHMOOR ROAD STAGE 3 IMPROVEMENT			F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.		
I:\09\Jobs\09L0027B\CADD\Elec\Sheet\09-008.dgn		DRAWN - ANC	REVISED -		SCALE: NONE	SHEET NO. 9 OF	SHEETS	STA.	TO STA.	6647	08-00302-00-PV	PEORIA	85	54
		CHECKED - RDN	REVISED -								09-00047-01-PV	CONTRACT NO. 89526		
		PLOT DATE = 10/16/2009	DATE - 10/16/09								FED. ROAD DIST. NO.	ILLINOIS FED. AID PROJECT	ARA-M-5093(139)	