

SCHEDULE OF QUANTITIES

EPOXY PAVEMENT MARKING LINE, 4" & PAVEMENT MARKING REMOVAL

LOCATION STA. TO STA.	PVMT. MRKG. LINE, 4"		PVMT. MRKG. REM.	
	WHITE LENGTH (FOOT)	YELLOW LENGTH (FOOT)	WHITE EDGELINE (SQ.FT.)	YELLOW SKIP DASH (SQ.FT.)
JOBSITE				
TOTAL	1165		388	

TEMPORARY TRAFFIC SIGNALS

LOCATION	TRAFFIC SIGNALS (EACH)
JOBSITE	1
TOTAL	1

PAVEMENT MIX SPECIFICATION

The following mixture requirements are applicable as replacement for the existing HMA Surface Removal quantity on the bridge deck.

MIXTURE USE(S):	**SURFACE COURSE
AC/PG:	SBS or SBR 70-22
RAP% (MAX):	10% Max
Design Air Voids:	4.0% @ N=70
Mixture Composition: (Graduation Mixture)	IL. 9.5 or 12.5
Friction Aggregate:	Mixture D (dolomite only)

** Individual lift thickness will be no less than 3x nominal maximum and no more than 6x nominal maximum aggregate size.

PAVEMENT MARKING TAPE TYPE III, 4" & WORKZONE PAVEMENT MARKING REMOVAL

LOCATION STA. TO STA.	PVMT. MRKG. TAPE, 4"		PVMT. MRKG. REM.
	WHITE LENGTH (FOOT)	YELLOW LENGTH (FOOT)	WORK ZONE PVMT. MRKG. REM. (FT.)
JOBSITE			
TOTAL	1965		1965

PPC DECK BEAMS (33" DEPTH)

LOCATION	BEAMS (SQ.FT.)
REMOVAL	2408
REPLACEMENT	2402

BRIDGE DECK CONSTRUCTION (STAGE 1 = NORTH SIDE)

REMOVING & RE-ERECTING EXISTING RAILING			
NORTH EDGE OF DECK	FOOT	SOUTH EDGE OF DECK	FOOT
Sta. 637+82 to Sta. 639+14.9	134.4	Sta. 639+14.9 to Sta. 639+81.5	66.6
TOTAL			201
HMA SURFACE REMOVAL			
STAGE 1 AREA	SQ.YD.	STAGE 2 AREA	SQ.YD.
Sta. 637+82 to Sta. 639+14.9	9.2	Sta. 639+14.9 to Sta. 639+81.5	12.8
TOTAL			22
PORTLAND CEMENT FAIRING COURSE			
STAGE 1 AREA	FOOT	STAGE 2 AREA	FOOT
Sta. 637+82 to Sta. 639+14.9	361.4	Sta. 639+14.9 to Sta. 639+81.5	507.6
TOTAL			869
WATERPROOFING MEMBRANE SYSTEM			
STAGE 1 AREA	SQ.YD.	STAGE 2 AREA	SQ.YD.
Sta. 637+82 to Sta. 639+14.9	118.9	Sta. 639+14.9 to Sta. 639+81.5	186.4
TOTAL			285.3
HMA SURFACE COURSE			
STAGE 1 AREA	TON	STAGE 2 AREA	TON
Sta. 637+82 to Sta. 639+14.9	14.5	Sta. 639+14.9 to Sta. 639+81.5	19.9
TOTAL			34.4

SILICONE JOINT SEALER

LOCATION	FOOT
BRIDGE JOINTS	132
TOTAL	132

POLYMER CONCRETE

LOCATION	CUFT
BRIDGE JOINTS	34.3
TOTAL	34.3

TRAFFIC CONTROL

LOCATION STA. TO STA.	TEMP. CONC. BARRIER (FT)	IMPACT ATTEN. TEMP. (EACH)	T.C.&P. STANDARD 701321 (EACH)	T.C.&P. STANDARD 701201 (EACH)	CHANGEABLE MESSAGE SIGN
Sta. 637+62 (Stage 1)	430				
(Stage 2) Sta. 640+01.5	654				
JOBSITE		2	1	1	2
TOTAL	654	2	1	1	2

SN. 036-0028 US. 34
over S.Henderson Crk.