

CODE NO.	ITEM	UNIT	TOTAL QUANTITY	CONSTRUCTION CODE							
				90% FED 10% STATE	100% STATE	90% FED 10% STATE					
				ROADWAY	SAFETY	BRIDGE	ROADWAY	LIGHTING	TRAFFIC SIGNALS		
				0004	0005	0013	0021	0021	0021	0021	0021
				URBAN	URBAN	SN 016-0098	IDOT	CDOT	CONGRESS	VAN BUREN	
44201761	CLASS D PATCHES, TYPE I, 10 INCH	SQ YD	30	30							
44201765	CLASS D PATCHES, TYPE II, 10 INCH	SQ YD	30	30							
44201769	CLASS D PATCHES, TYPE III, 10 INCH	SQ YD	104	104							
50101500	REMOVAL OF EXISTING SUPERSTRUCTURES	EACH	1					1			
50102400	CONCRETE REMOVAL	CU YD	202.4				202.4				
50157300	PROTECTIVE SHIELD	SQ YD	2,633			2633					
50300225	CONCRETE STRUCTURES	CU YD	193.7			193.7					
50300255	CONCRETE SUPERSTRUCTURE	CU YD	1,069.4			1,069.4					
50300260	BRIDGE DECK GROOVING	SQ YD	1,332				1,332				
50300300	PROTECTIVE COAT	SQ YD	3,508				3,508				
50301350	CONCRETE SUPERSTRUCTURE (APPROACH SLAB)	CU YD	251			251					
50500105	FURNISHING AND ERECTING STRUCTURAL STEEL	L SUM	1				1				
50500505	STUD SHEAR CONNECTORS	EACH	19,773			19,773					
50800205	REINFORCEMENT BARS, EPOXY COATED	POUND	319,490			319,490					


X = SPECIALTY ITEM

3 REVISED SHEET 1/7/2026

2 REVISED SHEET 1/5/2026

GENERAL NOTES:

- Fasteners shall be ASTM F3125 Grade A325 Type 1. Fasteners shall be hot dip galvanized. See special provision for "Hot Dip Galvanizing for Structural Steel". Bolts $\frac{7}{8}$ " Ø, holes $1\frac{3}{16}$ " Ø, unless otherwise noted.
- Calculated weight of structural steel:
Grade 50 = 706,180 lbs
Grade 36 = 54,070 lbs
- All structural steel shall be galvanized. See special provision for "Hot Dip Galvanizing for Structural Steel."
- No field welding is permitted except as specified in the contract documents.
- Reinforcement bars designated (E) shall be epoxy coated.
- The finishing machine rails shall be placed on the top of the top flange of the exterior beams within the deck pour. Beam blocks shall be placed between beams at all tie locations in each bay for the full width of the deck pour.
- If the Contractor elects to use cantilever forming brackets on the exterior beams or girders, the brackets shall be placed at the same locations as required for the hardwood blocks in Article 503.06(b) of the Standard Specifications. If additional cantilever forming brackets are required, hardwood blocking shall be wedged between the exterior and first interior beam at each of these additional bracket locations.
- Slipforming of the parapets is not allowed.
- Bearing seat surfaces shall be constructed or adjusted to the designated elevations within a tolerance of $\frac{1}{8}$ " (0.01 ft.). Adjustment shall be made either by grinding the surface or by shimming the bearings.
- Film forming concrete sealer shall be applied on horizontal surfaces, and penetrating concrete sealer shall be applied on vertical surfaces. Concrete Sealer shall be applied to new abutment and pier beam seats prior to setting bearings or structural steel. Concrete Sealer shall be applied to new concrete diaphragms, structural concrete repairs, and to existing abutment and pier faces adjacent to I-290.
- Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.
- The existing structural steel coating contains lead. The Contractor shall take appropriate precautions to deal with the presence of lead on this project.
- The existing utilities attached to the bridge may contain asbestos. The Contractor shall take appropriate precautions to address the presence of asbestos on this project. The removal procedure shall comply with City of Chicago, State, and Federal regulations.
- The Contractor shall salvage the existing aluminum Bridge Railing including all posts, railings, all attachments and the aluminum Pedestrian Fence and Railing. The aluminum Bridge Railing and aluminum Pedestrian Fence and Railing shall be transported and unloaded by the Contractor to the District Bridge Yard in Elk Grove Village at 1101 Biesterfield Road during the week days Monday-Friday, and between the hours of 8 am and 2 pm. The Contractor shall notify the District Bridge Office 48 hours in advance of the delivery at (847) 956-1444. Cost included in Removal of Existing Structure.
- Cost of removal of existing protective shield is included in the pay item "Removal of Existing Superstructure" and shall not be paid for separately.
- Bridge Fence Railing, Curved shall be galvanized.
- The Contractor shall submit Full Construction Process Plan to CTA for review and approval. Contractor shall minimize impacts to Rail Operations. See Special Provisions.



EXIST. EB I-290 PROFILE GRADE
(Along EB I-290 Alignment)

INDEX OF SHEETS

S-1	General Plan and Elevation
S-2	General Notes, Index of Sheets, and Total Bill of Material
S-3 - S-4	Stage Construction Details
S-5	Stage Construction Details - Approach Slab
S-6	Temporary Concrete Barrier
S-7	Superstructure Removal
S-8	Temporary Soil Retention System
S-9	Suggested Beam Erection Plan
S-10 - S-15	Top of Slab Elevations
S-16	Top of South Approach Slab Elevations
S-17	Top of North Approach Slab Elevations
S-18	Superstructure
S-19	Superstructure Details I
S-20	Superstructure Details II
S-21	Concrete Diaphragm Details
S-22	Parapet Reveal Details
S-23 - S-27	Bridge Approach Slab Details
S-28 - S-29	Bridge Fence Railing, Curved
S-30	Aluminum Railing Type L
S-31	Bridge Drainage System
S-32	Drainage Scuppers, DS-11
S-33	Steel Framing Plan and Details
S-34	Moment and Reaction Table
S-35 - S-36	Structural Steel Details
S-37 - S-38	Bearing Details
S-39	South Abutment Repairs and Removal
S-40	South Abutment Concrete Extension
S-41	South Abutment Details
S-42	North Abutment Repairs and Removal
S-43	North Abutment Concrete Extension
S-44	North Abutment Details
S-45	Wingwall Removal and Repairs
S-46	Wingwall Modification
S-47	Pier 1 Repairs
S-48	Pier 1 Cap Concrete Extension
S-49	Pier 2 Repairs
S-50	Pier 2 Cap Concrete Extension
S-51	Pier 3 Repairs
S-52	Pier 3 Cap Concrete Extension
S-53	Bar Splicer Assembly Details
S-54 - S-56	Soil Boring Logs

TOTAL BILL OF MATERIAL




ITEM	UNIT	SUPER	SUB	TOTAL
REMOVAL OF EXISTING SUPERSTRUCTURES	EACH	1		1
CONCRETE REMOVAL	CU YD		202.4	202.4
PROTECTIVE SHIELD	SQ YD	2,633	2,633	
CONCRETE STRUCTURES	CU YD	193.7	193.7	
CONCRETE SUPERSTRUCTURE	CU YD	1,069.4	1,069.4	
BRIDGE DECK GROOVING	SQ YD	1,332	1,332	
PROTECTIVE COAT	SQ YD	3,508	3,508	
CONCRETE SUPERSTRUCTURE (APPROACH SLAB)	CU YD	251.0	251.0	
FURNISHING AND ERECTING STRUCTURAL STEEL	L SUM	1		1
STUD SHEAR CONNECTORS	EACH	19,773	19,773	
REINFORCEMENT BARS, EPOXY COATED	POUND	296,920	22,570	319,490
BAR SPLICERS	EACH	1,641	52	1,693
ALUMINUM RAILING, TYPE L	FOOT	180		180
BRIDGE FENCE RAILING, CURVED	FOOT	526		526
NAME PLATES	EACH	1		1
ELASTOMERIC BEARING ASSEMBLY, TYPE I	EACH	52		52
ANCHOR BOLTS, 3/4"	EACH	130		130
TEMPORARY SOIL RETENTION SYSTEM	SQ FT	654		654
DRAINAGE SYSTEM FOR STRUCTURES	L SUM	1		1
GRANULAR BACKFILL FOR STRUCTURES	CU YD	142		142
CONCRETE SEALER	SQ FT	5,743		5,743
EPOXY CRACK INJECTION	FOOT	34		34
GEOCOMPOSITE WALL DRAIN	SQ YD	192		192
PIPE UNDERDRAINS FOR STRUCTURES 4"	FOOT	422		422
GRAFTITI REMOVAL	SQ YD	13		13
LIGHTWEIGHT CELLULAR CONCRETE FILL	CU YD	2,640		2,640
BAR TERMINATORS	EACH	946		946
DRAINAGE SCUPPERS, DS-11	EACH	10		10
STRUCTURAL REPAIR OF CONCRETE (DEPTH EQUAL TO OR LESS THAN 5 INCHES)	SQ FT	1,245		1,245
STRUCTURAL REPAIR OF CONCRETE (DEPTH GREATER THAN 5 INCHES)	SQ FT	251		251
REMOVING AND REPLACING EXPANSION JOINT	FOOT	24		24




STATION 402+31.73
RE-BUILT 202 BY
STATE OF ILLINOIS
F.A.U. RT. 2856
SEC. 2019-191-B-R
LOADING HL-93
STRUCTURE NO. 016-0098

NAME PLATE

See Std. 515001

Existing Name Plate shall be cleaned and relocated next to new Name Plate. Cost included with Name Plate.







SUPERSTRUCTURE BILL OF MATERIAL				
Bar	No.	Size	Length	Shape
a(E)	908	#5	48'-10"	
a1(E)	908	#5	38'-10"	
a2(E)	548	#5	17'-9"	
a3(E)	274	#5	7'-8"	
a4(E)	588	#6	8'-4"	
a5(E)	160	#5	1'-6"	
a6(E)	274	#5	8'-8"	
b(E)	1152	#5	37'-6"	
b1(E)	522	#6	23'-2"	
b3(E)	33	#5	42'-3"	
b4(E)	30	#5	38'-0"	
b5(E)	10	#5	31'-9"	
c(E)	274	#5	3'-4"	
c1(E)	274	#5	1'-4"	
c2(E)	274	#5	1'-5"	
c4(E)	274	#5	1'-5"	
d(E)	266	#4	4'-11"	
d1(E)	266	#6	3'-10"	
d2(E)	684	#4	2'-6"	
d3(E)	9	#6	4'-0"	
d4(E)	21	#6	8'-11"	
d5(E)	292	#4	6'-2"	
d6(E)	292	#6	5'-2"	
e(E)	32	#4	15'-0"	
e1(E)	128	#4	13'-9"	
e2(E)	64	#4	9'-9"	
e3(E)	8	#4	18'-7"	
e4(E)	8	#4	18'-11"	
e5(E)	48	#4	16'-9"	
e6(E)	16	#4	7'-9"	
m10(E)	4	#4	37'-4"	
m11(E)	44	#6	6'-5"	
m12(E)	44	#6	6'-5"	
m13(E)	10	#6	37'-4"	
m14(E)	4	#4	47'-4"	
m15(E)	10	#6	47'-4"	
m16(E)	4	#6	4'-10"	
m17(E)	4	#6	4'-10"	
m18(E)	4	#6	1'-8"	
m19(E)	4	#6	1'-8"	
m20(E)	8	#6	0'-11"	
m21(E)	8	#6	0'-11"	
m22(E)	224	#5	1'-6"	
s10	140	#5	7'-3"	
s11	140	#5	8'-8"	
u(E)	140	#4	2'-2"	
v100(E)	178	#5	3'-3"	
x(E)	172	#5	4'-1"	
Concrete Superstructure				Cu Yd 1,040.8
Protective Coat				Sq Yd 2,857
Reinforcement Bars, Epoxy Coated				Pound 190,540
Bridge Deck Grooving				Sq Yd 1,092

CTA ENTRANCE BILL OF MATERIAL

Removing and Replacing Expansion Joint	Foot	24
--	------	----

- The $\frac{3}{16}$ min. aluminum sheet shall be ASTM B 209 alloy 3003-H14 and coated with 5 mils of either bitumen paint or epoxy paint to minimize reaction with wet concrete. Cost included with Concrete Superstructure.
- The polyurethane sealant shall be according to Article 1050.04 of the Std. Spec. and the color shall be gray.
- Bar terminators paid for separately. See Total Bill of Material.
- Bars indicated thus 1 x 2-#4 etc. indicates 1 line of bars with 2 lengths per line.



SECTION D-D AT CTA STATION JOINT

(Contractor to submit to CTA for review and approval prior to Construction.)

REVISED SHEET 1/7/2026

