TEMPORARY TRAFFIC SIGNAL NOTES

- 1. ALL CONTROL EQUIPMENT INCLUDING EMERGENCY PRE-EMPTION AND COMMUNICATION DEVICES FOR THE TEMPORARY TRAFFIC SIGNAL(S) SHALL BE FURNISHED BY THE CONTRACTOR
- 2. ONLY CONTROLLERS SUPPLIED BY ONE OF THE DISTRICT APPROVED CLOSED LOOP EQUIPMENT MANUFACTURERS WILL BE APPROVED FOR USE AT TEMPORARY SIGNAL LOCATIONS. ALL CONTROLLERS USED FOR TEMPORARY TRAFFIC SIGNALS SHALL BE FULLY ACTUATED NEMA MICROPROCESSOR BASED WITH RS232 DATA ENTRY PORTS COMPATIBLE WITH EXISTING MONITORING SOFTWARE APPROVED BY IDOT DISTRICT 1, INSTALLED IN A NEMA TS2 CABINET. ONLY ONE BRAND OF CONTROLLER WILL BE ACCEPTED FOR ANY ONE CONTRACT.
- 3. ALL TRAFFIC SIGNAL SECTIONS AND PEDESTRIAN SIGNAL SECTIONS SHALL BE 12 INCHES (300 MM). TRAFFIC SIGNAL SECTIONS SHALL BE LED WITH EXPANDABLE VIEW, UNLESS OTHERWISE APPROVED BY THE ENGINEER. PEDESTRIAN SIGNAL HEADS SHALL BE LIGHT EMITTING DIODE (LED) PEDESTRIAN COUNTDOWN SIGNAL HEADS EXCEPT WHEN TEMPORARY TRAFFIC SIGNAL IS INSTALLED AT AN INTERSECTION INTERCONNECTED WITH A RAILROAD GRADE CROSSING. WHEN A TEMPORARY TRAFFIC SIGNAL IS INSTALLED AT AN INTERSECTION INTERCONNECTED WITH A RAILROAD GRADE CROSSING, LIGHT EMITTING DIODE (LED) PEDESTRIAN SIGNAL HEADS SHALL BE FURNISHED. THE TEMPORARY TRAFFIC SIGNAL HEADS SHALL BE PLACED AS INDICATED ON THE TEMPORARY TRAFFIC SIGNAL PLAN OR AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHALL FURNISH ENOUGH EXTRA CABLE LENGTH TO RELOCATE HEADS TO ANY POSITION ON THE SPAN WIRE OR AT LOCATIONS ILLUSTRATED ON THE PLANS FOR CONSTRUCTION STAGING. THE TEMPORARY TRAFFIC SIGNAL SHALL REMAIN IN OPERATION DURING ALL SIGNAL HEAD RELOCATIONS. EACH TEMPORARY TRAFFIC SIGNAL HEAD SHALL HAVE ITS OWN CABLE FROM THE CONTROLLER CABINET TO THE SIGNAL HEAD.
- 4. ALL EXISTING STREET NAMES AND INTERSECTION REGULATORY SIGNS SHALL BE REMOVED FROM EXISTING POLES, RELOCATED AND SECURELY FASTENED TO THE SPAN WIRE OR WOOD POLE AS DIRECTED BY THE ENGINEER.
- 5. ANY TEMPORARY SIGNAL WITHIN AN EXISTING CLOSED LOOP TRAFFIC SIGNAL SYSTEM SHALL BE INTERCONNECTED TO THAT SYSTEM USING SIMILAR BRAND CONTROL EQUIPMENT AT NO ADDITIONAL COST TO THE CONTRACT.
- 6. THE TEMPORARY TRAFFIC SIGNAL SHALL HAVE THE SIGNAL HEAD DISPLAYS, SIGNAL HEAD PLACEMENTS AND CONTROLLER PHASING MATCH THE EXISTING TRAFFIC SIGNAL, AT THE TIME OF THE TURN ON, IF NO TRAFFIC STAGING IS IN PLACE OR WILL NOT BE STAGED ON THE DAY OF THE TURN ON.
- 7. ALL TEMPORARY TRAFFIC SIGNAL INSTALLATIONS SHALL HAVE UNINTERRUPTIBLE POWER SUPPLY (UPS). THE UPS CABINET SHALL BE MOUNTED TO THE TEMPORARY TRAFFIC SIGNAL CABINET AND MEET THE REQUIREMENTS OF UNINTERRUPTABLE POWER SUPPLY IN DIVISIONS 800 AND 1000 OF THESE SPECIFICATIONS.
- 8. TRAFFIC SIGNAL MANAGEMENT SYSTEMS SHALL BE MAINTAINED IN OPERATION AS INDICATED ON THE PLANS OR AS DIRECTED BY THE ENGINEER. REQUIRED EQUIPMENT SHALL BE AS SHOWN ON THE PLANS AND THE CONTRACTOR SHALL PLACE THE EQUIPMENT IN OPERATION TO THE SATISFACTION OF THE ENGINEER AND THE AGENCY RESPONSIBLE FOR THE TRAFFIC SIGNAL MANAGEMENT SYSTEM.
- 9. DETECTION AT TEMPORARY TRAFFIC SIGNALS SHALL BE INCLUDED FOR ALL APPROACHES OF THE INTERSECTION UNLESS INDICATED OTHERWISE ON THE PLANS. PEDESTRIAN PUSH BUTTONS SHALL BE PROVIDED FOR ALL PEDESTRIAN SIGNAL HEADS/PHASES AS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER. THE DETECTION SYSTEM MUST MEET THE SPECIFICATIONS OF DISTRICT 1 AND THE CONTRACTOR SHALL PLACE THE DETECTORS INTO OPERATION TO THE SATISFACTION OF THE ENGINEER. DETECTION SHALL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN TEMPORARY TRAFFIC SIGNAL INSTALLATION PAY ITEM.
- 10. WHEN PAN, TILT, ZOOM CAMERAS ARE INSTALLED AT THE EXISTING INTERSECTION OR ARE CALLED FOR IN THE PLANS, THE CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLING AND MAINTAINING THE CAMERAS TO THE SATISFACTION OF THE ENGINEER AND THE AGENCY RESPONSIBLE FOR THE CAMERAS.

TRAFFIC SIGNAL GENERAL NOTES

- 1. IF THIS CONTRACT REQUIRES THE SERVICES OF AN ELECTRICAL CONTRACTOR, THE CONTRACTOR SHALL BE RESPONSIBLE AT HIS/HER OWN EXPENSE FOR LOCATING EXISTING IDOT ELECTRICAL FACILITIES PRIOR TO PERFORMING ANY WORK, IF THIS CONTRACT DOES NOT REQUIRE THE SERVICES OF AN ELECTRICAL CONTRACTOR, THE CONTRACTOR MAY REQUEST ONE FREE LOCATE FOR EXISTING IDOT ELECTRICAL FACILITIES FROM THE DISTRICT ONE ELECTRICAL MAINTENANCE CONTRACTOR PRIOR TO THE START OF ANY WORK, ADDITIONAL REQUESTS MAY BE AT THE EXPENSE OF THE CONTRACTOR. THE LOCATION OF UNDERGROUND TRAFFIC FACILITIES DOES NOT RELIEVE THE CONTRACTOR OF THEIR RESPONSIBILITY TO REPAIR ANY FACILITIES DAMAGED DURING CONSTRUCTION AT THEIR EXPENSE.
- 2. THE MASTER CONTROLLERS FOR TWO IDOT SIGNAL SYSTEMS ARE CURRENTLY LOCATED AT THE INTERSECTION OF U.S. ROUTE 30 AND WESTERN AVENUE IN TWO SEPARATE CABINETS. BOTH SYSTEMS SHALL BE MAINTAINED DURING CONSTRUCTION USING SEPARATE MASTER CONTROLLERS BOTH LOCATED IN THE TEMPORARY TRAFFIC SIGNAL CABINET. A SUPER "R" CABINET, TYPE V SHALL BE INSTALLED AT THE INTERSECTION CONTAINING NEW MASTER CONTROLLERS FOR BOTH SYSTEMS.
- 3. RESTORATION OF THE TRAFFIC SIGNAL WORK AREA SHALL BE INCIDENTAL TO THE RELATED PAY ITEM SUCH AS FOUNDATION, CONDUIT, HANDHOLE, ETC., AND NO EXTRA COMPENSATION SHALL BE ALLOWED. ALL ROADWAY SURFACES SUCH AS SHOULDER, MEDIAN, SIDEWALKS, PAVEMENT, ETC. SHALL BE REPLACED IN KIND. ALL DAMAGE TO MOWED LAWNS SHALL BE REPLACED WITH AN APPROVED SOD, AND ALL DAMAGE TO UNMOWED FIELDS SHALL BE SEEDED IN ACCORDANCE WITH STANDARD SPECIFICATIONS 252 AND 250 RESPECTIVELY.
- 4. THE TRAFFIC SIGNAL CONTROLLER EQUIPMENT FOR THIS PROJECT SHALL BE "ECONOLITE" TO MATCH THE EXISTING ADJACENT SYSTEMS.

FILE NAME =	USER NAME = jimenezjl	DESIGNED -	REVISED -			
c:\pw_work\pwidot\jimenezjl\d0274265\P102812-Design.dgn		DRAWN -	REVISED -			
	PLOT SCALE = 100.0000 ' / in.	CHECKED -	REVISED -			
Default	PLOT DATE = 10/17/2013	DATE -	REVISED -			

STATI	E 01	F ILLINOIS
DEPARTMENT	0F	TRANSPORTATION

SCALE:

TEMPORARY TRAFFIC SIGNAL GENERAL NO	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
U.S. RTE. 30 (LINCOLN HWY) & WESTERN /	353	23N-2	COOK	75	36	
0.3. III L. 30 (LINGOLIN IIVVI) & VVLSTEIIN 7			CONTRAC	T NO. 6	OT19	
SHEET OF SHEETS STA.	TO STA.	TILLINOIS FED. AID PROJECT				