

RESURFACING TABLE										
LOCATION	WIDTH	LENGTH	AREA	HOT-MIX ASPHALT SURFACE REMOVAL		TEMPORARY RAMP	BITUMINOUS PRIME COAT	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE MIX "E", N50		
				BUTT JOINT	1.5"			1.5"		
				FT	FT			SQ YD	SQ YD	SQ YD
County Highway 6										
6+59 TO 09+81	VARIABLE	322	1341.8	26.7	840.0	13.3	0.5	112.7		
10+15 TO 11+50	VARIABLE	135	686.7	33.3	632.8	16.7	0.3	65.4		
IL ROUTE 9										
809+25 TO 813+25	26	400	1508.6	57.8	1097.8	28.9	0.8	126.7		
TOTALS							1.6	304.8		

PRIME COAT APPLICATION RATES	
SURFACE TYPE	BITUMINOUS PRIME COAT
	(GAL/SQ YD)
ON GRANULAR BASE	0.5
ON COLD MILLED SURFACE	0.1
EXISTING PAVEMENT	0.05
FOG COAT ON NEW BINDER	0.03
0.004 TONS PER GALLON FOR BITUMINOUS PRIME COAT	

HMA AND COARSE AGGREGATE APPLICATION RATES	
HMA SURFACE AND BINDER	112 LB/SQ YD IN
ALL OTHER HMA	112 LB/SQ YD IN
COARSE AGGREGATE	2.05 TONS/CU YD