

STAGE II CONSTRUCTION LINE

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Appr. Bent	98+84.17	6.75	570.16	570.16
A	98+94.17	6.75	570.16	570.17
B	99+04.17	6.75	570.16	570.17
Bk. N. Abut.	99+11.75	6.75	570.16	570.16
⊕ Brq N. Abut.	99+12.67	6.75	570.16	570.16
C	99+22.67	6.75	570.16	570.18
D	99+32.67	6.75	570.15	570.18
E	99+42.67	6.75	570.15	570.19
F	99+52.67	6.75	570.15	570.19
G	99+62.67	6.75	570.15	570.18
H	99+72.67	6.75	570.15	570.17
I	99+82.67	6.75	570.14	570.15
J	99+92.67	6.75	570.13	570.13
⊕ Exist. Pier	100+03.17	6.75	570.12	570.12
K	100+13.17	6.75	570.10	570.11
L	100+23.17	6.75	570.09	570.12
M	100+33.17	6.75	570.07	570.12
N	100+43.17	6.75	570.04	570.12
O	100+53.17	6.75	570.02	570.11
P	100+63.17	6.75	569.99	570.09
Q	100+73.17	6.75	569.96	570.04
R	100+83.17	6.75	569.92	569.99
S	100+93.17	6.75	569.89	569.92
⊕ Brq S. Abut.	101+05.92	6.75	569.83	569.83
Bk. S. Abut.	101+06.83	6.75	569.83	569.83
T	101+16.83	6.75	569.79	569.80
U	101+26.83	6.75	569.74	569.75
Bk. S. Appr. Bent	101+34.42	6.75	569.71	569.71

BEAM 6 (BEAM 5*)

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Appr. Bent	98+84.40	7.94	570.14	570.14
A	98+94.40	7.94	570.14	570.15
B	99+04.40	7.94	570.14	570.15
Bk. N. Abut.	99+11.98	7.94	570.14	570.14
⊕ Brq N. Abut.	99+12.86	7.75	570.14	570.14
C	99+22.86	7.75	570.14	570.16
D	99+32.86	7.75	570.14	570.16
E	99+42.86	7.75	570.14	570.17
F	99+52.86	7.75	570.14	570.17
G	99+62.86	7.75	570.14	570.17
H	99+72.86	7.75	570.13	570.15
I	99+82.86	7.75	570.13	570.14
J	99+92.86	7.75	570.12	570.12
⊕ Exist. Pier	100+03.36	7.75	570.10	570.10
K	100+13.36	7.75	570.09	570.10
L	100+23.36	7.75	570.07	570.10
M	100+33.36	7.75	570.05	570.10
N	100+43.36	7.75	570.03	570.10
O	100+53.36	7.75	570.00	570.10
P	100+63.36	7.75	569.97	570.07
Q	100+73.36	7.75	569.94	570.03
R	100+83.36	7.75	569.91	569.97
S	100+93.36	7.75	569.87	569.90
⊕ Brq S. Abut.	101+06.11	7.75	569.82	569.82
Bk. S. Abut.	101+07.06	7.94	569.81	569.81
T	101+17.06	7.94	569.77	569.78
U	101+27.06	7.94	569.72	569.73
Bk. S. Appr. Bent	101+34.65	7.94	569.69	569.69

BEAM 7 (BEAM 6*)

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Appr. Bent	98+85.91	15.88	570.01	570.01
A	98+95.91	15.88	570.01	570.02
B	99+05.91	15.88	570.01	570.02
Bk. N. Abut.	99+13.49	15.88	570.01	570.01
⊕ Brq N. Abut.	99+14.34	15.50	570.02	570.02
C	99+24.34	15.50	570.02	570.04
D	99+34.34	15.50	570.02	570.04
E	99+44.34	15.50	570.02	570.05
F	99+54.34	15.50	570.02	570.05
G	99+64.34	15.50	570.02	570.05
H	99+74.34	15.50	570.01	570.03
I	99+84.34	15.50	570.00	570.01
J	99+94.34	15.50	570.00	570.00
⊕ Exist. Pier	100+04.84	15.50	569.98	569.98
K	100+14.84	15.50	569.97	569.98
L	100+24.84	15.50	569.95	569.98
M	100+34.84	15.50	569.93	569.98
N	100+44.84	15.50	569.90	569.98
O	100+54.84	15.50	569.88	569.97
P	100+64.84	15.50	569.85	569.95
Q	100+74.84	15.50	569.82	569.90
R	100+84.84	15.50	569.79	569.85
S	100+94.84	15.50	569.75	569.78
⊕ Brq S. Abut.	101+07.59	15.50	569.70	569.70
Bk. S. Abut.	101+08.57	15.88	569.69	569.69
T	101+18.57	15.88	569.65	569.66
U	101+28.57	15.88	569.60	569.61
Bk. S. Appr. Bent	101+36.16	15.88	569.56	569.56

BEAM 8 (BEAM 7*)

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Appr. Bent	98+87.43	23.81	569.88	569.88
A	98+97.43	23.81	569.88	569.89
B	99+07.43	23.81	569.88	569.89
Bk. N. Abut.	99+15.01	23.81	569.88	569.88
⊕ Brq N. Abut.	99+15.82	23.25	569.90	569.90
C	99+25.82	23.25	569.90	569.92
D	99+35.82	23.25	569.89	569.92
E	99+45.82	23.25	569.89	569.93
F	99+55.82	23.25	569.89	569.93
G	99+65.82	23.25	569.89	569.92
H	99+75.82	23.25	569.89	569.91
I	99+85.82	23.25	569.88	569.89
J	99+95.82	23.25	569.87	569.87
⊕ Exist. Pier	100+06.32	23.25	569.86	569.86
K	100+16.32	23.25	569.84	569.86
L	100+26.32	23.25	569.83	569.86
M	100+36.32	23.25	569.81	569.86
N	100+46.32	23.25	569.78	569.86
O	100+56.32	23.25	569.76	569.85
P	100+66.32	23.25	569.73	569.83
Q	100+76.32	23.25	569.70	569.78
R	100+86.32	23.25	569.66	569.73
S	100+96.32	23.25	569.63	569.66
⊕ Brq S. Abut.	101+09.07	23.25	569.57	569.57
Bk. S. Abut.	101+10.09	23.81	569.56	569.56
T	101+20.09	23.81	569.52	569.53
U	101+30.09	23.81	569.47	569.48
Bk. S. Appr. Bent	101+37.68	23.81	569.43	569.43

BEAM 9 (WEST CURTAIN WALL*)

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Appr. Bent	98+88.95	31.75	569.72	569.72
A	98+98.95	31.75	569.72	569.73
B	99+08.95	31.75	569.72	569.73
Bk. N. Abut.	99+16.53	31.75	569.72	569.72
⊕ Brq N. Abut.	99+17.30	31.00	569.73	569.73
C	99+27.30	31.00	569.73	569.75
D	99+37.30	31.00	569.73	569.76
E	99+47.30	31.00	569.73	569.77
F	99+57.30	31.00	569.73	569.77
G	99+67.30	31.00	569.73	569.76
H	99+77.30	31.00	569.73	569.75
I	99+87.30	31.00	569.72	569.73
J	99+97.30	31.00	569.71	569.71
⊕ Exist. Pier	100+07.80	31.00	569.70	569.70
K	100+17.80	31.00	569.68	569.70
L	100+27.80	31.00	569.66	569.70
M	100+37.80	31.00	569.64	569.70
N	100+47.80	31.00	569.62	569.70
O	100+57.80	31.00	569.60	569.69
P	100+67.80	31.00	569.57	569.67
Q	100+77.80	31.00	569.54	569.62
R	100+87.80	31.00	569.50	569.57
S	100+97.80	31.00	569.46	569.50
⊕ Brq S. Abut.	101+10.55	31.00	569.41	569.41
Bk. S. Abut.	101+11.61	31.75	569.39	569.39
T	101+21.61	31.75	569.35	569.36
U	101+31.61	31.75	569.31	569.32
Bk. S. Appr. Bent	101+39.20	31.75	569.27	569.27

* Denotes description variations for Approach Spans associated with Main Span callouts.