# STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

## соок ILLINOIS CONTRACT NO. 61F36

FOR INDEX OF SHEETS AND HIGHWAY STANDARDS, SEE SHEET NO. 2

IMPROVEMENTS LOCATED IN THE **VILLAGE OF OAK PARK** 

#### LAKE STREET (FAU 1405)

MINOR ARTERIAL NOT A TRUCK ROUTE
EXISTING ADT (2014) = 6,250 TO 9,200
PROPOSED ADT (2025) = 11,600
DESIGN SPEED = 30 MPH
POSTED SPEED = 25 MPH



 $\bigcirc$ 

DATE: 11/15/19 EXP. 11/30/21 THOMAS ENGINEERING GROUP, LLC SHEETS: 1-154, 171-184, 272-344



SCHAUMBURG,

P.E.

**ENGINEER: CARMEN** 

**PROGRAM** 

AID

SCOTT FRERES, PLA DATE: 11/15/19 EXP. 11/30/21 THE LAKOTA GROUP SHEETS: 155-170, 185-225




Mohammed K. Rashed MOHAMMED RASHED, PE DATE: 11/15/19 EXP. 11/30/21 TRANSMART/EJM CORPORATION SHEETS: 258-271



GREGORY GEDEMER, PE, PTOE DATE 11/15/19 EXP 11/30/21 TRANSMART/EJM CORPORATION SHEETS: 226-257

STA.10 + 27




FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.

JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION 1-800-892-0123 OR 811

# PLANS FOR PROPOSED FEDERAL AID HIGHWAY

F.A.U. 1405 (LAKE STREET) IL ROUTE 43 (HARLEM AVENUE) TO EUCLID AVENUE STREETSCAPE PROJECT **SECTION 16-00264-00-PV** PROJECT JCKZ(724) **VILLAGE OF OAK PARK COOK COUNTY** C-91-100-17



**NET LENGTH = 3,388 FT. = 0.642 MILE** 

LOCATION OF SECTION INDICATED THUS: - -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 10/9/18 **APPROVED** VILLAGE OF OAK PARK, VILLAGE ENGINEER **PASSED RELEASING FOR BID BASED ON LIMITED** 

thomas engineering group, Ilc 55 w. 22nd street lombard, il 60148

PRINTED BY THE AUTHORITY OF THE STATE OF ILLINOIS

**CONTRACT NO. 61F36** 

## **INDEX OF SHEETS**

1	COVER SHEET
2	INDEX OF SHEETS AND LIST OF STANDARDS
3	GENERAL NOTES
4 - 18	SUMMARY OF QUANTITIES
19 - 25	TYPICAL SECTIONS
26 - 32	SCHEDULE OF QUANTITIES
33 - 35	ALIGNMENT, TIES AND BENCHMARKS
36 - 39	REMOVAL PLAN SHEETS
40 - 46	PLAN AND PROFILE SHEETS
47 - 52	EDGE OF PAVEMENT PROFILE SHEETS
53 - 65	PROPOSED GEOMETRIC LAYOUT SHEETS
66 - 70	PROPOSED INTERSECTION LAYOUT SHEETS
71 - 85	PROPOSED ADA RAMP LAYOUT SHEETS
86 - 118	SUGGESTED MAINTENANCE OF TRAFFIC SHEETS
119 - 122	EROSION AND SEDIMENT CONTROL PLAN SHEETS
123 - 131	DRAINAGE AND UTILITY PLAN SHEETS
132 - 154	PLAT OF HIGHWAYS SHEETS
155 - 170	IRRIGATION PLAN SHEETS
171 - 174	PAVEMENT MARKING PLAN SHEETS
175 - 184	SIGNING PLAN SHEETS
185 - 197	LANDSCAPE PLAN SHEETS
198 - 210	MATERIAL AND AMENITIES PLAN SHEETS
211	PLANTING DETAILS SHEET
212 - 224	STREETSCAPE DETAIL SHEETS
225	STREETSCAPE GENERAL NOTES & PLANTING SCHEDULE SHEET
226 - 257	TRAFFIC SIGNAL PLAN SHEETS
258 - 271	LIGHTING PLAN SHEETS
272 - 278	CONSTRUCTION DETAILS SHEETS
279 - 300	SOIL BORING LOGS SHEETS
301 - 311	IDOT DISTRICT ONE DETAIL SHEETS
312 - 344	CROSS SECTION SHEETS

#### **COMMITMENTS**

- 1. AT LEAST ONE DOOR OF THE DOUBLE DOORS AT THE GAP AND PIER 1 STORE
- 2. DUE TO THE EXISTING SIDEWALK VAULT, ADA COMPLIANCE CANNOT BE FULLY MET DUE TO THE EXISTING SIDEWALK VAULT, ADA COMPLIANCE CANNOT BE FULLY MET FOR THE NORTHEAST CORNER OF HARLEM AVENUE AND LAKE STREET. ADA DESIGN HAS BEEN DESIGNED TO MAXIMUM EXTENT PRACTICABLE (MEP). REFER TO THE SUBMITTED MEP FORM FOR MORE INFORMATION. ONCE THE EXISTING SIDEWALK VAULT IS EXPOSED THE CONTRACTOR SHALL CONFIRM THE VAULT LIMITS AND ELEVATIONS. THE ADA DESIGN SHALL THEN BE REFINED IN THE FIELD BY THE CONTRACTOR AND ENGINEER TO BE FULLY COMPLIANT WITH ALL ADA REQUIRMENTS OR TO THE THE MAXIMUM EXTENT PRACTICABLE.

#### LIST OF IDOT DISTRICT ONE DETAILS

BD-01

	AND FACE OF CURB & EDGE OF SHOULDER >= 15'
BD-02	DRIVEWAY DETAILS DISTANCE BETWEEN ROW AND FACE OF CURB < 15'
BD-08	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING
BD-22	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
BD-24	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT
BD-32	BUTT JOINT AND HMA TAPER DETAILS
BD-36	FIRE HYDRANT TO BE MOVED
BE-300	LIGHTPOLE FOUNDATION 30' TO 35' MaH. 11 1/2" BOLT CIRCLE
TC-13	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
TC-16	SHORT TERM PAVEMENT MARKING LETTERS AND SYMBOLS
TC-26	DRIVEWAY ENTRANCE SIGNING

DRIVEWAY DETAILS - DISTANCE BETWEEN R.O.W.

#### **LIST OF HIGHWAY STANDARDS**

LIGI OI	IIIdiiWAI GIAWDAIIDG
000001-07	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
420001-09	PAVEMENT JOINTS
420701-03	PAVEMENT WELDED WIRE REINFORCEMENT
424001-11	PERPENDICULAR CURB RAMPS FOR SIDEWALKS
424006-04	DIAGONAL CURB RAMPS FOR SIDEWALKS
424011-04	CORNER PARALLEL CURB RAMPS FOR SIDEWALKS
424016-05	MID-BLOCK CURB RAMPS FOR SIDEWALKS
424021-05	DEPRESSED CORNER FOR SIDEWALKS
424026-03	ENTRANCE / ALLEY PEDESTRIAN CROSSINGS
442101-09	CLASS B PATCHES
442201-03	CLASS C AND D PATCHES
604001-05	FRAME AND LIDS TYPE 1
606001-07	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
701006-05	OFF-RD OPERATIONS, 2L, 2W, 15' TO 24' FROM PAVEMENT EDGE
701301-04	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701311-03	LANE CLOSURE 2L, 2W, MOVING OPERATIONS - DAY ONLY
701501-06	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
701502-09	URBAN LANE CLOSURE, 2L, 2W, WITH BIDIRECTIONAL LEFT TURN LANE
701701-10	URBAN LANE CLOSURE, MULTILANE INTERSECTION
701801-06	SIDEWALK, CORNER OR CROSSWALK CLOSURE
701901-08	TRAFFIC CONTROL DEVICES
720001-01	SIGN PANEL MOUNTING DETAILS
720006-04	SIGN PANEL ERECTION DETAILS
720016-04	MAST ARM MOUNTED STREET NAME SIGNS
731001-01	BASE FOR TELESCOPING STEEL SIGN SUPPORT
780001-05	TYPICAL PAVEMENT MARKINGS
805001-01	ELECTRICAL SERVICE INSTALL DETAILS
814001-03	HANDHOLES
814006-02	DOUBLE HANDHOLES
862001-01	UPS
873001-02	TRAFFIC SIGNAL GROUND AND BOND
876001-04	PEDESTRIAN PUSHBUTTON POST
877001-08	STEEL MAST ARM ASSEMBLY AND POLE 16' THROUGH 55'
877011-10	STEEL COMBO MAST ARM ASSEMBLY AND POLE 16' THROUGH 55'
878001-10	CONCRETE FOUNDATION DETAILS
880001-01	SPAN WIRE MOUNTED SIGNALS
880006-01	TRAFFIC SIGNAL MOUNTING DETAILS - POST AND BRACKET MOUNT
886001-01	DETECTOR LOOP INSTALLATION
886006-01	TYPICAL LAYOUTS FOR DETECTION LOOPS

ENTRANCES SHALL BE ACCESSIBLE AT ALL TIMES DURING CONSTRUCTION.

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

								F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
								1405	16-00264-00-PV	COOK	344	2	
										CONTRACT	NO. 6	1F36	
	SCALE:	NTS	SHEET	1	OF	1	SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT			

#### **GENERAL NOTES**

- 1. ALL IMPROVEMENTS SHALL BE IN ACCORDANCE WITH THE IDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND THE SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS, LATEST EDITION, ANY REFERENCE TO STANDARDS IN THE PLANS OR SPECIAL PROVISIONS SHALL BE INTERPRETED TO BE LATEST STANDARDS OF IDOT.
- 2. THE CONTRACTOR SHALL GIVE NOTICES AND COMPLY, WITH APPLICABLE LAWS, ORDINANCES, RULES, REGULATIONS, AND LAWFUL ORDERS OF ALL PUBLIC AUTHORITIES BEARING ON SAFETY OR PERSONS OR PROPERTY ON THEIR PROTECTION FROM DAMAGE, INJURY, OR LOSS.
- 3. THE CONTRACTOR SHALL COORDINATE ALL THE ACTIVITIES WITH THE VILLAGE OF OAK PARK, THIS APPLIES TO PROVIDING ADVANCE NOTICE TO ALLOW THE VILLAGE TO REMOVE PARK BENCHES, PARKING METER HEADS, ETC., PRIOR TO THE START OF CONSTRUCTION.
- 4. WHERE SECTION OR SUBSECTION MONUMENTS OR PROPERTY IRONS ARE ENCOUNTERED, THE ENGINEERS SHALL BE NOTIFIED BEFORE THESE MONUMENTS ARE REMOVED. THE CONTRACTOR SHALL CAREFULLY PRESERVE ALL PROPERTY MARKS AND MONUMENTS UNTIL THE OWNER, AUTHORIZED SURVEYOR, OR AGENT HAS WITNESSED OR OTHERWISE REFERENCED THEIR LOCATION.
- 5. ALL UTILITY TRENCHES UNDER AND WITHIN TWO FEET OF PAVEMENT, SIDEWALK, CURB AND GUTTER, ETC. SHALL BE BACKFILLED WITH CLEAN CA-6 CRUSHED STONE TRENCH BACK FILL.
- 6. NO EXTRA WORK OF ANY NATURE SHALL BE UNDERTAKEN WITHOUT FIRST OBTAINING WRITTEN APPROVAL FROM THE ENGINEER.
- 7. THE CONTRACTOR IS RESPONSIBLE FOR FURNISHING ALL STAKING AND LAYOUT OF THE GRADING, UNDERGROUND, AND PAVING IMPROVEMENTS.
- 8. THE ENGINEER SHALL NOT HAVE THE AUTHORITY OVER, OR THE RESPONSIBILITY FOR, THE CONTRACTOR'S MEANS, METHODS, PROCEDURES OF CONSTRUCTION, THE JOB SITE'S SAFETY PROCEDURES AND PRECAUTIONS, OR FOR ANY FAILURE OF THE CONTRACTOR TO COMPLY WITH RULES, REGULATIONS, OR ORDINANCES APPLICABLE TO THE CONTRACTOR'S WORK AND ACTIVITIES.
- 9. WHENEVER THE CONTRACTOR ENCOUNTERS FACILITIES AND APPURTENANCES WITHIN THE LIMITS OF THE IMPROVEMENTS DURING TRENCHING OPERATIONS, THEY WILL BE REQUIRED TO HAND TRENCH IN THAT AREA IN ORDER NOT TO DAMAGE THESE FACILITIES.
- 10. THE CONTRACTOR SHALL NOTIFY AFFECTED RESIDENTS AND BUSINESSES 48 HOURS IN ADVANCE OF DRIVEWAY REMOVAL OPERATIONS.
- 11. THE CONTRACTOR SHALL PROVIDE WRITTEN NOTICE TO PACE AND CTA A MINIMUM OF 14 DAYS PRIOR TO CONSTRUCTION AND SHALL ALSO PROVIDE WRITTEN NOTICE 7 DAYS PRIOR TO STAGING CHANGES HIGHLIGHTING ROADWAY CLOSURES.
- 12. THE CONTRACTOR SHALL EXCAVATE SUCH TRENCHES THAT WILL HAVE SEWER INSTALLED AND BE BACK FILLED DURING THE DAY. NO SUCH TRENCHES SHALL BE LEFT OPEN AT THE END OF THE WORKING DAY.
- 13. THE CONTRACTOR SHALL TAKE ALL NECESSARY PRECAUTIONS FOR THE PROTECTION OF CORPORATE OR PUBLIC PROPERTY, SUCH AS WALLS AND FOUNDATIONS, VAULTS UNDERGROUND AND OVERHEAD STRUCTURES, TREES, SHRUBBERY, CROPS AND FENCES CONTIGUOUS TO THE WORK, FOR WHICH THE CONTRACTOR DOES NOT PROVIDE FOR REMOVAL OR SPECIFY PRECAUTIONS. WHENEVER PUBLIC OR PRIVATE PROPERTY IS SO DAMAGED OR DESTROYED, THE CONTRACTOR SHALL RESTORE SUCH PROPERTY TO A CONDITION EQUAL OF THAT EXISTING BEFORE THE DAMAGE WAS DONE BY REPAIRING, REBUILDING, OR REPLACING AS DIRECTED BY THE ENGINEER.
- 14. COMBINATION CONCRETE CURB AND GUTTER SHALL BE CONSTRUCTED WITH A VARIABLE CURB HEIGHT (3" 9"). THE ENGINEER MUST APPROVE ANY LOCATIONS THAT MAY REQUIRE A 9" CURB HEIGHT. 9" CURB MAY NOT BE USED ADJACENT TO PARKING STALLS. REFER TO THE SPECIAL PROVISIONS FOR COMBINATION CURB AND GUTTER TYPE B-6.12 (MODIFIED) OR (SPECIAL) FOR MORE INFO.
- 15. BEFORE SETTING THE TOP OF CURB ELEVATIONS, THE CONTRACTOR SHALL CHECK THE EXISTING ELEVATION AT THE ADJACENT PROPERTY LINE, AND IF NECESSARY, THE CONTRACTOR SHALL VARY THE CURB EXPOSURE AND/OR GUTTER ELEVATION IN ORDER TO MORE CLOSELY FOLLOW THE PROPER LINE AND GRADES. THE PROPOSED CURB EXPOSURE SHALL VARY IN HEIGHT FROM 3 INCHES (MIN) TO 9 INCHES (MAX), HOWEVER, 9 INCHES MUST BE APPROVED BY THE ENGINEER.
- 16. A PROTECTIVE COAT SHALL BE APPLIED TO ALL GUTTER FLAGS, FACE OF CURB AND CONCRETE DRIVEWAYS AND SIDEWALK IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.
- 17. SILANE SURFACE SEALER (PENETRATING SEALER) SHALL BE APPLIED AT THE MAXIMUM APPLICATION RATE ON ALL DECORATIVE CONRETE CURBS, ALL BLUESTONE PAVERS, ALL BRICK PAVERS, AND ALL COLORED CONCRETE PAVEMENTS.
- 18. THE CONTRACTOR SHALL PROTECT EXISTING AND PROPOSED DECORATIVE MATERIALS FROM JULIE PAINT MARKINGS AND SHALL USE THE JOINT MEET PROCESS TO PROVIDE DETAILED UTILITY LOCATING INSTRUCTIONS FOR ANY UNDERGROUND LOCATES IN THESE AREAS.
- 19. THE SUBGRADE STABILITY SHALL BE VERIFIED BY PROOF ROLLING WITH A FULLY LOADED TANDEM-AXLE TRUCK.
- 20. AGGREGATE SUBGRADE IMPROVEMENT (CU YD) HAS BEEN PROVIDED FOR USE AT THE LOCATIONS INDICATED FOR SOILS THAT TEND TO BE UNSTABLE AND/OR UNSUITABLE. THE ACTUAL NEED FOR REMOVAL AND REPLACEMENT WITH ASI WILL BE DETERMINED IN THE FIELD AT THE TIME OF CONSTRUCTION BY THE GEOTECHNICAL ENGINEER. ALL POTENTIALLY UNSTABLE SOILS SHOULD BE TESTED WITH A STATIC OR DYNAMIC CONE PENETROMETER AND TREATED IN ACCORDANCE WITH ARTICLE 301.04 OF THE SSRBC AND IDOT SUBGRADE STABILITY MANUAL. IF UNSTABLE AND/OR UNSUITABLE SOILS ARE NOT ENCOUNTERED, THEN THE QUANTITY SHALL BE DEDUCTED AND NO ADDITIONAL COMPENSATION WILL BE DUE TO THE CONTRACTOR.
- 21. ANY AGGREGATE SUBGRADE IMPROVEMENT CONTAMINATED AND/OR DAMAGED BY THE CONTRACTOR'S VEHICLES AND/OR EQUIPMENT IS TO BE REMOVED AND REPLACED AS DIRECTED BY THE ENGINEER AT THE CONTRACTOR'S EXPENSE.
- 22. BACKFILLING STORM SEWER CONSTRUCTED UNDER THE ROADWAY SPECIFIED UNDER ARTICLE 550.07(B, C) OF THE SSRBC WILL NOT BE ALLOWED. METHOD 1 WILL BE THE ONLY APPROVED METHOD OF BACKFILLING.

Ingomos
engineering group
service at the highest grade⊗

USER NAME = TEG	DESIGNED - VJM	REVISED -	
	DRAWN - JBH	REVISED -	
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -	
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -	

07117011 110770	F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
GENERAL NOTES	1405	16-00264-00-PV	соок	344	3
			CONTRACT	NO. 6	1F36
SCALE: N.T.S. SHEET 1 OF 1 SHEETS STA. TO STA.	ILLINOIS FED. AID PROJECT				

						80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY ITEM	SPECIAL PROVISION	CODE NO.	ITEM	UNIT	TOTAL QUANTITY	0004 RDWY RECON	0005 RDWY RESURF	0021 SAFETY	0031 LANDSCAPE	0042 TRAINEES	COMMUNICATION FIBER OPTIC
4		20100110	TREE REMOVAL (6 TO 15 UNITS DIAMETER)	UNIT	395				395		
		20101000	TEMPORARY FENCE	FOOT	100		100				
		20200100	EARTH EXCAVATION	CU YD	2,965		2,965				
		20201200	REMOVAL AND DISPOSAL OF UNSUITABLE MATERIAL	CU YD	540	540					
		20800150	TRENCH BACKFILL	CU YD	250		250				
		21001000	GEOTECHNICAL FABRIC FOR GROUND STABILIZATION	SQ YD	6,476		6,476				
		21101615	TOPSOIL FURNISH AND PLACE, 4"	SQ YD	136		136				
								i			
+		25200100	SODDING	SQYD	136				136		
		28000250	TEMPORARY EROSION CONTROL SEEDING	POUND	3		3				
		28000400	PERIMETER EROSION BARRIER	FOOT	250		250				
				-							
		28000510	INLET FILTERS	EACH	64		64				
		28001100	TEMPORARY EROSION CONTROL BLANKET	SQYD	136		136				
	Х	30300001	AGGREGATE SUBGRADE IMPROVEMENT	CU YD	540	540					
	Х	30300112	AGGREGATE SUBGRADE IMPROVEMENT 12"	SQ YD	6,476	6,476					
		31101200	SUBBASE GRANULAR MATERIAL, TYPE B 4"	SQYD	7,249		7,249				
		35300100	PORTLAND CEMENT CONCRETE BASE COURSE 6"	SQYD	92		92				
		35300515	PORTLAND CEMENT CONCRETE BASE COURSE 10 3/4"	SQYD	168		168				
:											
		35301200	HIGH-EARLY-STRENGTH PORTLAND CEMENT CONCRETE BASE COURSE 9"	SQYD	1,983	1,983					
			:								
	×	35301400	PORTLAND CEMENT CONCRETE BASE COURSE (VARIABLE DEPTH)	SQYD	386		386				

th@mas.
engineering group
service at the highest grade.

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
 PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATI	E OF	ILLINOIS
DEPARTMENT	OF	TRANSPORTATION

			SUI	VIM.	ARY	OF QUA	ANTITIES			
SCALE:	NTS	SHEET	1	OF	15	SHEETS	STA.	TO	STA.	

F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
1405	16-00264-00-PV	COOK	344	4
		CONTRACT	NO. 6	1F36
	ILLINOIS FED. A	D PROJECT		

0021

1AME = sht-S00,don

											0021
						80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY	SPECIAL	CODE	ITEM	UNIT	TOTAL	0004	0005	0021	0031	0042	COMMUNICATION
ITEM	PROVISION	NO.			QUANTITY	RDWY RECON	RDWY RESURF	SAFETY	LANDSCAPE	TRAINEES	FIBER OPTIC
		40600290	BITUMINOUS MATERIALS (TACK COAT)	POUND	5,448		5,448				
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			5,7.0		-,				
		40600400	MIXTURE FOR CRACKS, JOINTS, AND FLANGEWAYS	TON	20		20				
		40000408	WINDLE FOR GRACKS, JOHNTS, AND I DANGEWAYS	1014	20		20				
		40000000	HOTHIN ACCUMENTS DEMONAL PUTT IONIT	50.48	474		174				
		40600982	HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT	SQ YD	174		174				
		1000000					004				
		40603200	POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-4.75, N50	TON	621		621				
					. 0.7		4.047				
		40604062	HOT-MIX ASPHALT SURFACE COURSE, IL-9.5, MIX "D", N70	TON	1,017		1,017				
						!					
		40700100	BITUMINOUS MATERIALS (TACK COAT)	POUND	4,148		4,148				
		40701881	HOT-MIX ASPHALT PAVEMENT (FULL-DEPTH), 10"	SQ YD	3,165	3,165					
		42001300	PROTECTIVE COAT	SQYD	3,589		3,589				
***************************************	~~~~										
	Х	42300400	PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 8 INCH	SQ YD	136		136				
	X	42400200	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	SQ FT	22,597		22,597				
	х	42400410	PORTLAND CEMENT CONCRETE SIDEWALK 8 INCH	SQ FT	696		696				
		44000100	PAVEMENT REMOVAL	SQYD	6,536		6,536				
		44000158	HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/4"	SQYD	5,013		5,013				
		44000200	DRIVEWAY PAVEMENT REMOVAL	SQ YD	131		131				
		44000500	COMBINATION CURB AND GUTTER REMOVAL	FOOT	4,852		4,852				
		44000600	SIDEWALK REMOVAL	SQFT	44,441		44,441				
		44201298	DOWEL BARS 1 1/4"	EACH	500		500			·	
		44200948	CLASS B PATCHES, TYPE I, 9 INCH	SQYD	36	36					
		44200956	CLASS B PATCHES, TYPE II, 9 INCH	SQYD	103	103					

th@mas.
engineering group
service at the highest grade.

USER NAME = TEG	DESIGNED	-	VJM	REVISED	-	_
	DRAWN	-	ЈВН	REVISED	-	
PLOT SCALE = 2.0000 '/ in.	CHECKED	-	BLP	REVISED	-	
PLOT DATE = 11/15/2019	DATE	-	11/15/2019	REVISED	-	

STATE	: OF	ILLINOIS	
DEPARTMENT	0F	TRANSPORTATION	

	F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
SUMMARY OF QUANTITIES	1405	16-00264-00-PV	COOK	344	5
		***************************************	CONTRAC	T NO. 6	1F36
SCALE: NTS SHEET 2 OF 15 SHEETS STA. TO STA.		ILLINOIS FED.	AID PROJECT		

				UF QUANT							01
						80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY	SPECIAL	CODE	ITEM	UNIT	TOTAL	0004	0005	0021	0031	0042	COMMUNICATION
ITEM	PROVISION	NO.	4.00		QUANTITY	RDWY RECON	RDWY RESURF	SAFETY	LANDSCAPE	TRAINEES	FIBER OPTIC
		44200962	CLASS B PATCHES, TYPE III, 9 INCH	SQYD	134	134					
		44200964	CLASS B PATCHES, TYPE IV, 9 INCH	SQYD	353	353					
		44201761	CLASS D PATCHES, TYPE I, 10 INCH	SQYD	66		66				
		44201765	CLASS D PATCHES, TYPE II, 10 INCH	SQ YD	204		204				
		44201769	CLASS D PATCHES, TYPE III, 10 INCH	SQYD	246		246				
		44201771	CLASS D PATCHES, TYPE IV, 10 INCH	SQYD	587		587				
					:						
		44213204	TIE BARS 3/4"	EACH	250		250				
		55100200	STORM SEWER REMOVAL 6"	FOOT	20		20				
		55100300	STORM SEWER REMOVAL 8"	FOOT	65		65				
		55100400	STORM SEWER REMOVAL 10"	FOOT	20		20				
+	х	56200300	WATER SERVICE LINE 1"	FOOT	100		100				
*											
+	х	56200700	WATER SERVICE LINE 2"	FOOT	100		100				
4-	x	56201400	CORPORATION STOPS 1"	EACH	1		1				
•											
alput.	х	56201800	CORPORATION STOPS 2"	EACH	1		1				
4-	х	56400500	FIRE HYDRANTS TO BE REMOVED	EACH	2		2				
+	х	56400825	FIRE HYDRANT WITH AUXILIARY VALVE, VALVE BOX AND TEE	EACH	2		2				
+	х	56500600	DOMESTIC WATER SERVICE BOXES TO BE ADJUSTED	EACH	47		47				
		60234200	INLETS, TYPE A, TYPE 1 FRAME, OPEN LID	EACH	3		3				
	x	60250400	CATCH BASINS TO BE ADJUSTED WITH NEW TYPE 1 FRAME, OPEN LID	EACH	17		17				

th@mas.
e <u>ngineering grou</u> p
service of the highest grade-

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE	E OF	FILLINOIS
DEPARTMENT	OF	TRANSPORTATION

											F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	SUMMARY OF QUANTITIES						[	1405   16-00264-00-PV		COOK	344	6			
													CONTRAC	T NO. 6	1F36
SCALE: N	NTS	SHEET	3	OF	15	SHEETS	STA.	TO	STA.		ILLINOIS FED. AID PROJECT				

						80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY ITEM	SPECIAL PROVISION	CODE NO.	ITEM	UNIT	TOTAL QUANTITY	0004 RDWY RECON	0005 RDWY RESURF	0021 SAFETY	0031 LANDSCAPE	0042 TRAINEES	COMMUNICATION FIBER OPTIC
	х	60265700	VALVE VAULTS TO BE ADJUSTED	EACH	7		7				
	х	60300405	VALVE BOX FRAMES TO BE ADJUSTED	EACH	44		44				
		60600605	CONCRETE CURB, TYPE B	FOOT	265	,	265				
	х	60604100	COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12 (MODIFIED)	FOOT	1,904		1,904				
	х	61139900	STORM SEWERS (SPECIAL), 6"	FOOT	20		20				
	х	61140000	STORM SEWERS (SPECIAL), 8"	FOOT	226		226				
	Х	61140100	STORM SEWERS (SPECIAL), 10"	FOOT	20		20				
+		66900200	NON SPECIAL WARTE DISPOSAL	CU YD	400		400				
+		66900530	SOIL DISPOSAL ANALYSIS	EACH	2		2				
+		66901001	REGULATED SUBSTANCES PRE-CONSTRUCTION PLAN	LSUM	1		1				
+		66901003	REGULATED SUBSTANCES FINAL CONSTRUCTION REPORT	LSUM	1		1				
+		66901006	REGULATED SUBSTANCES MONITORING	CAL DA	30		30			:	
		67100100	MOBILIZATION	L SUM	1		1				
		70103815	TRAFFIC CONTROL SURVEILLANCE	CAL DA	233		233				
		70107025	CHANGEABLE MESSAGE SIGN	CAL DA	720		720				
			S. F. T. S. L. M. E. G. T. G.	3,201	. 20		. 20				
		70300100	SHORT TERM PAVEMENT MARKING	FOOT	1,430		1,430				
			S. S	100,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		.,, 100				
		70300150	SHORT TERM PAVEMENT MARKING REMOVAL	SQ FT	477		477				
		10200130	STORT TERMI FAVENIENT MAINING NEMOVAL	3QF1	7//		711				
		70300540	DAVIENENT MADRING TARE TYPE III LETTERS AND SYMPOLIS	90 FT	1 026		1 025				
		70300510	PAVEMENT MARKING TAPE, TYPE III - LETTERS AND SYMBOLS	SQ FT	1,936		1,936				
		70000-	SAVEURITAN PRINCE TARE TYPE III.	5007	20.005		00.005				
		70300520	PAVEMENT MARKING TAPE, TYPE III 4"	FOOT	22,895		22,895			L	

thomac
e <u>ngineering grou</u> p
service at the highest grade.

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED
PLOT SCALE = 2.0000 ' / in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE	E OF	ILLINOIS
DEPARTMENT	OF	TRANSPORTATION

Ī									F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
ı			SU	MM/	<b>ARY</b>	OF QU	ANTITIES		1405	16-00264-00-PV	COOK	344	7
١											CONTRAC	T NO. 6	1F36
I	SCALE: NTS	SHEET	4	OF	15	SHEETS	STA.	TO STA.		ILLINOIS FED. A	ID PROJECT		

						80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY ITEM	SPECIAL PROVISION	CODE NO.	ITEM	UNIT	TOTAL QUANTITY	0004 RDWY RECON	0005 RDWY RESURF	0021 SAFETY	0031 LANDSCAPE	0042 TRAINEES	COMMUNICATION FIBER OPTIC
										,	
		70300540	PAVEMENT MARKING TAPE, TYPE III 6"	FOOT	1,530		1,530				
		70300560	PAVEMENT MARKING TAPE, TYPE III 12"	FOOT	538		538	-			
		70300570	PAVEMENT MARKING TAPE, TYPE III 24"	FOOT	554		554	*****			
								***************************************			
+		72000100	SIGN PANEL - TYPE 1	SQ FT	632			632			
+		72000200	SIGN PANEL - TYPE 2	SQ FT	62			62			
+		72400100	REMOVE SIGN PANEL ASSEMBLY - TYPE A	EACH	20			20			
+		72400310	REMOVE SIGN PANEL - TYPE 1	SQ FT	285			285			
-1		72400500	RELOCATE SIGN PANEL ASSEMBLY TYPE A	EACH	6			6			
+		72400710	RELOCATE SIGN PANEL - TYPE 1	SQ FT	145			145			
+		78000100	THERMOPLASTIC PAVEMENT MARKING - LETTERS AND SYMBOLS	SQ FT	725			725			
+		78000200	THERMOPLASTIC PAVEMENT MARKING - LINE 4"	FOOT	13,471			13,471			
+		78000400	THERMOPLASTIC PAVEMENT MARKING - LINE 6"	FOOT	2,563			2,563			
+		78000600	THERMOPLASTIC PAVEMENT MARKING - LINE 12"	FOOT	1,464			1,464			
·											
+		78000650	THERMOPLASTIC PAVEMENT MARKING - LINE 24"	FOOT	445			445			
•											
+		78008300	POLYUREA PAVEMENT MARKING TYPE II - LETTERS AND SYMBOLS	SQ FT	138			138			
-											
+		78008310	POLYUREA PAVEMENT MARKING TYPE II - LINE 4"	FOOT	200			200		•	
+		78008330	POLYUREA PAVEMENT MARKING TYPE II - LINE 6"	FOOT	126			126			
.1		. 300000		. 331							
JI-		78008370	POLYUREA PAVEMENT MARKING TYPE II - LINE 24"	FOOT	42			42			
+			- STATE OF THE ET		76			, <u>-</u>			
1	×	80400100	ELECTRIC SERVICE INSTALLATION	EACH	2			2			
+	^	00400100	ELECTRIC SERVICE INSTALLATION	LAOIT							

``°
e <u>ngineering grou</u> p
respice of the highest grade.

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE OI	F ILLINOIS
DEPARTMENT OF	TRANSPORTATION

T			F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
١		SUMMARY OF QUANTITIES	1405	16-00264-00-PV	соок	344	8
					CONTRACT	NO. 6	1F36
١	SCALE: NTS	SHEET 5 OF 15 SHEETS STA. TO STA.		ILLINOIS FED. A	ID PROJECT		

			SUIVIIVIARY	OI GOAIVI	IIILU						0021
						80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY ITEM	SPECIAL PROVISION	CODE NO.	ITEM	UNIT	TOTAL QUANTITY	0004 RDWY RECON	0005 RDWY RESURF	0021 SAFETY	0031 LANDSCAPE	0042 TRAINEES	COMMUNICATION FIBER OPTIC
+	Х	80500020	SERVICE INSTALLATION - POLE MOUNTED	EACH	2			2			
+	х	81028200	UNDERGROUND CONDUIT, GALVANIZED STEEL, 2" DIA.	FOOT	5,316			2,903			2,413
+	х	81028220	UNDERGROUND CONDUIT, GALVANIZED STEEL, 3" DIA.	FOOT	1,253			1,253			
+	х	81028240	UNDERGROUND CONDUIT, GALVANIZED STEEL, 4" DIA.	FOOT	2,335			2,335			
+		81028720	UNDERGROUND CONDUIT, COILABLE NONMETALLIC CONDUIT, 1" DIA.	FOOT	2,283			2,283			
+		81028730	UNDERGROUND CONDUIT, COILABLE NONMETALLIC CONDUIT, 1 1/4" DIA.	FOOT	2,332	,		2,332			
	-										
+		81028750	UNDERGROUND CONDUIT, COILABLE NONMETALLIC CONDUIT, 2" DIA.	FOOT	315			315			
+		81028770	UNDERGROUND CONDUIT, COILABLE NONMETALLIC CONDUIT, 3" DIA.	FOOT	1,385			1,385			
+	х	81400100	HANDHOLE	EACH	19			19			
+	x	81400300	DOUBLE HANDHOLE	EACH	5			5			
+		81400730	HANDHOLE, COMPOSITE CONCRETE	EACH	5			5			
+		81603040	UNIT DUCT, 600V, 2-1C NO.6, 1/C NO.8 GROUND, (XLP-TYPE USE), 1" DIA. POLYETHYLENE	FOOT	2,450			2,450			
+		81603112	UNIT DUCT, 600V, 2-1C NO.6, 1/C NO.8 GROUND, (XLP-TYPE USE), 1 1/4" DIA. POLYETHYLENE	FOOT	2,450			2,450			
			TO ELEMENT								
+		81702110	ELECTRIC CABLE IN CONDUIT, 600V (XLP-TYPE USE) 1/C NO. 10	FOOT	4,856			4,856			
+		81702120	ELECTRIC CABLE IN CONDUIT, 600V (XLP-TYPE USE) 1/C NO. 8	FOOT	4,685			4,685			
+		81702130	ELECTRIC CABLE IN CONDUIT, 600V (XLP-TYPE USE) 1/C NO. 6	FOOT	9,370			9,370			
+	×	83600200	LIGHT POLE FOUNDATION, 24" DIAMETER	FOOT	364			364			
+	x	84200500	REMOVAL OF LIGHTING UNIT, SALVAGE	EACH	79			79			
+	х	84200804	REMOVAL OF POLE FOUNDATION	EACH	77			77			
					<u> </u>				1	L	

th@mas.
engineering group

USER NAME = TEG	DESIGNED	-	MLV	REVISED	-
	DRAWN	-	ODII	REVISED	-
PLOT SCALE = 2,0000 '/ in.			BLP	REVISED	-
PLOT DATE = 11/15/2019	DATE	_	11/15/2019	REVISED	_

Ī	OURANDO OF OURANTITIES								F.A.U. RTE.	SECTION			SHEET NO.		
١	SUMMARY OF QUANTITIES						1405	16-00264-00-PV	COOK	344	9				
l													CONTRACT	NO. 6	1F36
l	SCALE: NTS SHEET 6 OF 15 SHEETS STA. TO STA.							ILLINOIS FED. A	AID PROJECT						

SUMMARY OF QUANTITIES												
						80% FEDERAL	80% FEDERAL	0% FEDERAL	0% FEDERAL	80% FEDERAL	0% FEDERAL	
SPECIALTY	SPECIAL	CODE	. ITEM	UNIT	TOTAL	20% LOCAL 0004	20% LOCAL 0005	100% LOCAL 0021	100% LOCAL 0031	20% LOCAL 0042	100% LOCAL COMMUNICATION	
ITEM	PROVISION	NO.	116,99	OHI	QUANTITY	RDWY RECON	RDWY RESURF	SAFETY	LANDSCAPE	TRAINEES	FIBER OPTIC	
+		84400105	RELOCATE EXISTING LIGHTING UNIT	EACH	2			2				
T			NEEDS/NE ZACING DO/MIC SAN		-							
+		84500110	REMOVAL OF LIGHTING CONTROLLER	EACH	1			1				
-												
+		84500120	REMOVAL OF ELECTRIC SERVICE INSTALLATION	EACH	1			1				
						-						
+		84500130	REMOVAL OF LIGHTING CONTROLLER FOUNDATION	EACH	1			1				
+	х	85000200	MAINTENANCE OF EXISTING TRAFFIC SIGNAL INSTALLATION	EACH	2			2				
+	,	85100100	PAINT EXISTING TRAFFIC SIGNAL EQUIPMENT	EACH	3			3				
+		85100500	PAINT NEW TRAFFIC SIGNAL POST	EACH	16			16				
+		86400100	TRANSCEIVER - FIBER OPTIC	EACH	4		:	4				
+	х	87300010	GROUNDING EXISTING HANDHOLE FRAME AND COVER	EACH	10			10				
+	х	87300925	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1C	FOOT	8,728			3,728			5,000	
+	Х	87301215	ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 2C	FOOT	6,990			6,990				
+	Х	87301225	ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C	FOOT	9,890			9,890				
+	×	87301245	ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 5C	FOOT	9,200			9,200				
_		07004055	ELECTRIC CARLE IN CONDUIT CICAMA NO 44 TO	FOOT	5,230			5,230				
+	×	87301255	ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 7C		5,230			5,230				
	×	87301305	ELECTRIC CABLE IN CONDUIT, LEAD-IN, NO. 14 1 PAIR	FOOT	1,180			1,180				
+	^		ELECTION OF THE PROPERTY OF TH		.,100			.,,,,,,,				
+	x	87301790	ELECTRIC CABLE IN CONDUIT, SERVICE, NO. 2 2 C	FOOT	1,030			1,030				
x .								-				
+	x	87301805	ELECTRIC CABLE IN CONDUIT, SERVICE, NO. 6 2 C	FOOT	310			310				
-												
+		87301900	ELECTRIC CABLE IN CONDUIT, EQUIPMENT GROUNDING CONDUCTOR, NO. 6 1C	FOOT	5,530			5,530				
+	х	87502500	TRAFFIC SIGNAL POST, GALVANIZED STEEL 16 FT.	EACH	14			14				

th@mas.
engineering group

	USER NAME = TEG	DESIGNED - VJM	REVISED -
		DRAWN - JBH	REVISED -
	PLOT SCALE = 2,0000 '/ in.	CHECKED - BLP	REVISED -
1	PLOT DATE = 11/15/2019	DATE = 11/15/2019	REVISED -

STATI	E OI	FILLINOIS
DEPARTMENT	0F	TRANSPORTATION

	F.A.U. RTE.	SECTION	COUNTY	TOTAL	SHEET NO.	
SUMMARY OF QUA	1405	16-00264-00-PV	COOK	344	10	
SCALE: NTS SHEET 7 OF 15 SHEETS	STA. TO STA.	ILLINOIS FED. AID PROJECT				

			20ININIARY C	JI QUANI	IIILO						0021
						80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY	SPECIAL	CODE	ITEM	UNIT	TOTAL	0004	0005	0021	0031	0042	COMMUNICATION
ITEM	PROVISION	NO.	TIEW	ONII	QUANTITY	RDWY RECON	RDWY RESURF	SAFETY	LANDSCAPE	TRAINEES	FIBER OPTIC
+	X	87502520	TRAFFIC SIGNAL POST, GALVANIZED STEEL 18 FT.	EACH	1			1			
+	Х	87800100	CONCRETE FOUNDATION, TYPE A	FOOT	68			68			
+	X	87800150	CONCRETE FOUNDATION, TYPE C	FOOT	4			4			
+	Х	87800400	CONCRETE FOUNDATION, TYPE E 30-INCH DIAMETER	FOOT	10			10			
+	x	87800415	CONCRETE FOUNDATION, TYPE E 36-INCH DIAMETER	FOOT	142			142			
+		87900200	DRILL EXISTING HANDHOLE	EACH	38			36			2
+	X	88030020	SIGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST-ARM MOUNTED	EACH	26			26			
+	Х	88030050	SIGNAL HEAD, LED, 1-FACE, 3-SECTION, BRACKET MOUNTED	EACH	26			26			
+	X	88030100	SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED	EACH	12			12			
+	х	88030110	SIGNAL HEAD, LED, 1-FACE, 5-SECTION, MAST-ARM MOUNTED	EACH	10			10			
+	X	88055150	OPTICALLY PROGRAMMED SIGNAL HEAD, LED, 1-FACE, 3-SECTION, BRACKET MOUNTED	EACH	1			1			
			MOONED								
+	х	88055160	OPTICALLY PROGRAMMED SIGNAL HEAD, LED, 1-FACE, 3-SECTION, MAST ARM MOUNTED	EACH	1			1			
+	X	88055190	OPTICALLY PROGRAMMED SIGNAL HEAD, LED, 1-FACE, 5-SECTION, BRACKET MOUNTED	EACH	2			2			
+	Х	88055200	OPTICALLY PROGRAMMED SIGNAL HEAD, LED, 1-FACE, 5-SECTION, MAST ARM MOUNTED	EACH	2			2			
+	Х	88102717	PEDESTRIAN SIGNAL HEAD, LED, 1-FACE, BRACKET MOUNTED WITH	EACH	42			42			
•			COUNTDOWN TIMER								
+	х	88200410	TRAFFIC SIGNAL BACKPLATE, LOUVERED, FORMED PLASTIC	EACH	39			39			
+		88500100	INDUCTIVE LOOP DETECTOR	EACH	6			6			
•											
+	X	88600600	DETECTOR LOOP REPLACEMENT	FOOT	420			420			
±	X	89000100	TEMPORARY TRAFFIC SIGNAL INSTALLATION	EACH	3			3			
+	^	09100060	TEME CONTE TRAFFIC SIGNAL INSTALLATION	EACH	3						

th@mas.
e <u>ngineering grou</u> p
engineering group

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SCALE: NTS

							F.A.U. RTE.	SECTION	COUNTY	TOTAL	SHEET NO.		
	SUMMARY OF QUANTITIES						1405	16-00264-00-PV	COOK	344	11		
									CONTRACT	NO. 6	1F36		
SHEET	8	OF	15	SHEETS	STA.	TO STA.		ILLINOIS FED. AID PROJECT					

			SUMMARY U	r uuaivi	IIIES						0001
						80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY	SPECIAL	CODE	ITEM	UNIT	TOTAL	0004	0005	0021	0031 LANDSCAPE	0042 TRAINEES	COMMUNICATION
ITEM	PROVISION	NO.			QUANTITY	RDWY RECON	RDWY RESURF	SAFETY	LANDSCAPE	IRAINEES	FIBER OPTIC
+	x	89501400	RELOCATE EXISTING EMERGENCY VEHICLE PRIORITY SYSTEM, DETECTOR UNIT	EACH	10			10			
+	X	89501410	RELOCATE EXISTING EMERGENCY VEHICLE PRIORITY SYSTEM, PHASING UNIT	EACH	10			10			
······											
+	X	89502210	MODIFY EXISTING CONTROLLER CABINET	EACH	4			4			
•											
+		89502300	REMOVE ELECTRIC CABLE FROM CONDUIT	FOOT	65,704			65,704			
+	X	89502375	REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT	EACH	5			5			
+	х	89502376	REBUILD EXISTING HANDHOLE	EACH	3			3			
+	х	89502380	REMOVE EXISTING HANDHOLE	EACH	38			38			
+	х	89502382	REMOVE EXISTING DOUBLE HANDHOLE	EACH	3			3			
+		89502385	REMOVE EXISTING CONCRETE FOUNDATION	EACH	42			42			
+	х	A 2000324	TREE, ACER MIYABEI MORTON (STATE STREET MIYABE MAPLE), 3" CALIPER.	EACH	6		:		6		
			BALLED AND BURLAPPED								
+	х	A2002502	TREE, CARPINUS BETULUS FASTIGIATA (COLUMNAR EUROPEAN HORNBEAM), 3" CALIPER, BALLED AND BURLAPPED	EACH	5				5		
			CAUPEN, BALLED AND BURLAFFED	* * *							
+	Х	A2004424	TREE, GINKGO BILOBA (GINKGO), 3" CALIPER, BALLED AND BURLAPPED	EACH	6				6		
+	х	A 2004824	TREE, GLEDITSIA TRIACANTHOS INERMIS SKYLINE (SKYLINE THORNLESS COMMON HONEYLOCUST), 3" CALIPER, BALLED AND BURLAPPED	EACH	5				5		
			COMMON FONE (COOCS), 3 CABPER, BALLED AND BURGAFFED								
+	x	A2005024	TREE, GYMNOCLADUS DIOICUS (KENTUCKY COFFEETREE), 3" CALIPER, BALLED AND BURLAPPED	EACH	4				4		
			AND BOILEAFFED								
+	х	A 2005960	TREE, PLATANUS X ACERIFOLIA MORTON CIRCLE (EXCLAMATION! LONDON PLANETREE), 2-1/2" CALIPER, BALLED AND BURLAPPED	EACH	6				6		
			TO THE TIME! STEEL ON THE EN, DOLLED AND DUNLAFFED								
+	х	A 2006524	TREE, QUERCUS BICOLOR (SWAMP WHITE OAK), 3" CALIPER, BALLED AND BURLAPPED	EACH	8				8		
			SOURCE TEST								
+	х	A2008453	TREE, ULMUS ACCOLADE (HYBRID ELM), 3" CALIPER, BALLED AND BURLAPPED	EACH	8				8		
+	х	C2C01024	SHRUB, BUXUS MICROPHYLLA WINTERGREEN (WINTERGREEN LITTLELEAF BOXWOOD), 2' HEIGHT, CONTAINER	EACH	234				234		
			Source Spire Training Source Training								
+	х	C2C03432	SHRUB, HYDRANGEA QUERCIFOLIA (OAKLEAF HYDRANGEA), 2' HEIGHT, CONTAINER	EACH	13				13		-
			O (III)		l	1	L	1	<u></u>	I	

th@mas.
engineering group

USER NAME = TEG		DESIGNED	-	MLV	REVISED	-	
		DRAWN	-	JBH	REVISED	-	
PLOT SCALE = 2.00		CHECKED	-	BLP	REVISED	-	
PLOT DATE = 11/1	5/2019	DATE	_	11 /15 /2019	DEVISED	_	

								F.A.U. RTE.	SECTION	COUNTY	TOTAL	SHEE NO.	
SUMMARY OF QUANTITIES						1405	16-00264-00-PV	COOK	344	12			
											CONTRACT	T NO. 6	1F36
SCALE:	NTS	SHEET	9	OF	15	SHEETS	STA.	TO STA.		ILLINOIS FED. A	ID PROJECT		

			SUMMANT (								0.401
						80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY	SPECIAL	CODE	ITEM	UNIT	TOTAL	0004	0005	0021	0031	0042	COMMUNICATION
ITEM	PROVISION	NO.		OIII.	QUANTITY	RDWY RECON	RDWY RESURF	SAFETY	LANDSCAPE	TRAINEES	FIBER OPTIC
+	X	K0012970	PERENNIAL PLANTS, BULB TYPE	UNIT	3				3		
т	^	K0012970	FERENMETERNO, BOLD TIFE	OINII	3				, , , , , , , , , , , , , , , , , , ,		
+	X	K0012980	PERENNIAL PLANTS, ORNAMENTAL TYPE, QUART POT	UNIT	3				3		
•											
+	x	K0012990	PERENNIAL PLANTS, ORNAMENTAL TYPE, GALLON POT	UNIT	3				3		
+	x	K0012993	PERENNIAL PLANTS, ORNAMENTAL TYPE, 3-GALLON POT	UNIT	1				1		
+	х	K1001988	IRRIGATION SYSTEM SPECIAL	L SUM	1				1		
	· x	X0300635	PLANTER	EACH	104				104		
+	х	X0320060	GATEWAY MONUMENT SIGN COMPLETE	EACH	1				1		
+	х	X0320837	EMERGENCY VEHICLE PRIORITY SYSTEM DUEL DETECTOR UNIT	EACH	5			5			
	x	X0322463	CONNECTION TO EXISTING SEWER	EACH	14		14				
	x	X0324045	SEDIMENT CONTROL, STABILIZED CONSTRUCTION ENTRANCE REMOVAL	EACH	6		6				
+	х	X0324085	EMERGENCY VEHICLE PRIORITY SYSTEM LINE SENSOR CABLE, NO. 20 3/C	FOOT	2,480			2,480			
+	X	X0324599	ROD AND CLEAN EXISTING CONDUIT	FOOT	1,547			1,547			
					_						
+	Х	X0324603	CIRCUIT BREAKER, 1-POLE, 20 AMP, 120V IN EXISTING TSC CABINET	EACH	2			2			
	x	X0324775	SEDIMENT CONTROL, STABILIZED CONSTRUCTION ENTRANCE MAINTENANCE	SQ YD	300		300				
	^	70324770	SEDIMENT CONTROL, STABILIZED CONSTRUCTION ENTRANCE MAINVELVANCE	30(1)	300		300				
+	х	X0325040	FIBER OPTIC INNERDUCT 1 1/4" DIA.	FOOT	4,000						4,000
I <sup>-</sup>	,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		. 50,	.,000	1					.,500
	х	X0326443	SILANE SURFACE SEALER	SQYD	7,581		7,581				
***************************************					· · · · · · · · · · · · · · · · · · ·						
+	х	X0326498	GFCI 20 AMP DUPLEX RECEPTACLE	EACH	46			46			
+	х	X0326654	ORNAMENTAL LIGHT UNIT, COMPLETE	EACH	26			26			
+	х	X0326657	RELOCATE SIGN, SPECIAL	EACH	6			6			

th	@r	n	as.
engin	eerir	9 9	<u>rou</u> p
e <u>n gin</u>	eerir	9 9	roup

USER NAME = TEG	DESIGNED - VJM	REVISED ~
	DRAWN - JBH	REVISED -
PLDT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE	0F	ILLINOIS
DEPARTMENT (	DF T	TRANSPORTATION

			F.A.U. RTE.	TOTAL	SHEET NO.			
1		SUMMARY OF QUANTITIES	1405	16-00264-00-PV	COOK	344	13	
1						CONTRACT	NO. 6	1F36
	SCALE: NTS	SHEET 10 OF 15 SHEETS STA.	TO STA.		ILLINOIS FED. A	D PROJECT		

						80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY ITEM	SPECIAL PROVISION	CODE NO.	ITEM	UNIT	TOTAL QUANTITY	0004 RDWY RECON	0005 RDWY RESURF	0021 SAFETY	0031 LANDSCAPE	0042 TRAINEES	COMMUNICATION FIBER OPTIC
	х	X0326806	WASHOUT BASIN	L SUM	. 1		1				
+	х	X0326885	VIDEO DETECTION SYSTEM	EACH	4			4			
+	х	X0327009	REMOVE SIGN (SPECIAL)	EACH	12			12			
	х	X0327404	DRINKING FOUNTAIN REMOVAL AND REPLACEMENT	EACH	2		2				
	х	X0327552	TREE GRATE REMOVAL	EACH	42		42				
	Х	X0327611	REMOVE AND REINSTALL BRICK PAVER	SQ FT	47		47				
	Х	X0327727	PLANTER REMOVAL	L SUM	1		1				
	х	X0327980	PAVEMENT MARKING REMOVAL - WATER BLASTING	SQ FT	4,609		4,609				
	х	X0327989	REMOVE EXISTING BRICK PAVERS	SQ FT	17,598		17,598				
	х	X0350810	BOLLARD REMOVAL	EACH	20		20				
	х	X0426200	DEWATERING	L SUM	1		1				
	х	X0540000	BRICK PAVERS	SQ FT	18,669	18,669					
	х	X0900021	TEMPORARY BRIDGE	EACH	85		85				
	х	X1200160	CONNECTION TO EXISTING DRAINAGE STRUCTURE	EACH	3		3				
+	х	X1400107	FULL-ACTUATED CONTROLLER AND TYPE SUPER P CABINET	EACH	1			1			
+	х	X1400326	RECTANGULAR RAPID FLASHING BEACON ASSEMBLY (COMPLETE)	EACH	2			2			
	x	X1700021	BRICK PAVER REMOVAL AND REINSTALLATION, SPECIAL	SQ FT	1,553		1,553				
+	x	X1800003	PLANTING SOIL MIX FURNISH AND PLACE	CU YD	227				227		
					-						
	x	X2130010	EXPLORATION TRENCH, SPECIAL	FOOT	300		300				

th@mas.
engineering group

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

	i Rī								F.A.U. RTE.	SECTION	COUNTY	SHEE NO.	
SUMMARY OF QUANTITIES						1405	16-00264-00-PV	COOK	344	14			
											CONTRACT	NO. 6	31F36
LE:	NTS	SHEET	11	OF	15	SHEETS	STA.	TO STA.		ILLINOIS FED. A	D PROJECT		

				OF QUANT	· · · · · · · · · · · · · · · · · · ·						0021
						80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY	SPECIAL	CODE	ITEM	UNIT	TOTAL	0004 RDWY RECON	0005 RDWY RESURF	0021 SAFETY	0031 LANDSCAPE	0042 TRAINEES	COMMUNICATION FIBER OPTIC
ITEM	PROVISION	NO.			QUANTITY	ROWTRECON	KDWI KESOKI	SAFETT	LANDSCAFE	TOUNEES	TIBER OF IIC
	x	X4021000	TEMPORARY ACCESS (PRIVATE ENTRANCE)	EACH	1		1				
			,								
	x	X4022000	TEMPORARY ACCESS (COMMERCIAL ENTRANCE)	EACH	13		13				
	X	X4240430	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH, SPECIAL	SQ FT	4,604		4,604				
		7,12,0,100			,,,,,		,				
	x	X4240460	PORTLAND CEMENT CONCRETE SIDEWALK 8 INCH, SPECIAL	SQ FT	160			160			
		74240465	TOTAL DEMENT SONOTELE SIZE VICE VINES, OF EDITE	July 1	100			1,55			
	X	X4240800	DETECTABLE WARNINGS (SPECIAL)	SQ FT	647		647				
	^	74240000	DETECTABLE VARIANTOS (GELGAL)	July	04/		047	***************************************			
•	х	X4401198	HOT-MIX ASPHALT SURFACE REMOVAL, VARIABLE DEPTH	SQYD	6,618		6,618	***************************************			
	^	A4401196	NOT-WINASPRALI SURFACE REMOVAL, VARIABLE DEPTH	3010	- 0,010		0,010				
		1/500000		E1011			2				
+	X	X5630006	CUT AND CAP EXISTING 6" WATER MAIN	EACH	2		2				
		\/0000005	ALTOUR DIEGO A MINISTER TYPE I FRANC ORFINIO REFORM	F4011	45		45				
	Х	X6022805	CATCH BASINS, TYPE A, 4*DIAMETER, TYPE 1 FRAME, OPEN LID, SPECIAL	EACH	15		15				
	Х	X6026050	SANITARY MANHOLES TO BE ADJUSTED	EACH	13		13				
	X	X6030310	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)	EACH	23		23				
	Х	X6064200	COMBINATION CONCRETE CURB AND GUTTER, TYPE 8-6.12 (SPECIAL)	FOOT	3,136			3,136			
	Х	X6700405	ENGINEER'S FIELD OFFICE, TYPE A (MODIFIED)	CAL MO	9		9				
	х	X7010216	TRAFFIC CONTROL AND PROTECTION, (SPECIAL)	L SUM	1		1	<del></del>		***************************************	
	х	X7030005	TEMPORARY PAVEMENT MARKING REMOVAL	SQ FT	11,902		11,902				
+	х	X7280105	TELESCOPING STEEL SIGN SUPPORT (SPECIAL)	FOOT	517			517			
+	х	X7310110	BASE FOR TELESCOPING SIGN SUPPORT, SPECIAL	EACH	44			44			
+	х	X8100863	INTERCEPT EXISTING CONDUIT	EACH	15			14			1
+	х	X8110551	CONDUIT, FLEXIBLE NON-METALLIC, WEATHERPROOF, 1.0" DIAMETER	FOOT	358			358			
+	х	X8250505	LIGHTING CONTROLLER, SPECIAL	EACH	1			1			

th@mas.
engineering group

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

٦										F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
				SUI	MM/	ARY	OF QUA	ANTITIES		1405	16-00264-00-PV	COOK	344	15
												CONTRACT	NO. 6	1F36
	SCALE:	NTS	SHEET	12	OF	15	SHEETS	STA.	TO STA.	***************************************	ILLINOIS FED. A	ID PROJECT		

			OHIMA	INT UF QUAIN	TITLO						
	·					80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	002\ 0% FEDERAL 100% LOCAL
SPECIALTY ITEM	SPECIAL PROVISION	CODE NO.	ITEM	UNIT	TOTAL QUANTITY	0004 RDWY RECON	0005 RDWY RESURF	0021 SAFETY	0031 LANDSCAPE	0042 TRAINEES	COMMUNICATION FIBER OPTIC
+	х	X8570215	FULL-ACTUATED CONTROLLER IN EXISTING CABINET	EACH	2			2			
+	х	X8620200	UNINTERRUPTABLE POWER SUPPLY, SPECIAL	EACH	3			3			
+	Х	X8710024	FIBER OPTIC CABLE IN CONDUIT, NO. 62.5/125, MM12F SM24F	FOOT	3,728			3,728		***************************************	
+	х	X8710039	FIBER OPTIC CABLE 144 FIBERS, SINGLE MODE	FOOT	4,470						4,470
+	х	X8760055	PEDESTRIAN PUSH-BUTTON POST, TYPE A	EACH	2			2			
+	Х	X8760200	ACCESSIBLE PEDESTRIAN SIGNALS	EACH	42			42			
•				2,0,1	72						
	Х	X8780105	CONCRETE FOUNDATIONS (SPECIAL)	EACH	42			*^			
+	^	7,07,001,00	Solution (of Edit)	EACH	42			42			
	х	X8870300	EMERGENOV VETURI E PRIGRITA OVOTEVA								
+	^	X00/U3UU	EMERGENCY VEHICLE PRIORITY SYSTEM	EACH	5			5			
+	X	X8900100	TEMPORARY TRAFFIC SIGNAL INSTALLATION (SPECIAL)	EACH	1			1			
+	×	X8950130	MODIFY EXISTING LIGHTING CONTROLLER	EACH	1			1			
	Х	XX000959	TRASH RECEPTACLES	EACH	36				36		
+	Х	XX005043	ORNAMENTAL SIGN POST	EACH	5				5		
+	х	XX005735	PLANTER CURB	FOOT	280				280		
		- 1011									
+	х	XX006901	TREE GRATE ASSEMBLY, COMPLETE	EACH	36				36		
	Х	XX007215	CONCRETE PLANTER WALL	CU YD	25				25		
	х	XX007217	PAVER BLOCKS, SPECIAL	SQ FT	35,129	:	35,129				
	Х	XX007324	RECYCLING RECEPTACLE	EACH	36				36		
									-		
	x	XX007454	RAISED PLANTER REMOVAL	FOOT	592		592				
	Х	XX007466	BENCH 6'	EACH	11				14		
				LAUIT	11				11		

th@mas.
engineering group

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2,0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

CHAMADA DV OF CHANTITIES										SECTION	COUNTY	TOTAL	SHEE NO.
SUMMARY OF QUANTITIES							1405	16-00264-00-PV	COOK	344	16		
		,									CONTRACT	NO. 6	31F36
SCALE:	NTS	SHEET	13	0F	15	SHEETS	STA.	TO STA.		ILLINOIS FED.	ID PROJECT		

			SOWINA	KY UF QUANI	IIILO						0021
						80% FEDERAL	80% FEDERAL	0% FEDERAL	0% FEDERAL	80% FEDERAL	0% FEDERAL
SPECIALTY	SPECIAL	CODE	ITEM	UNIT	TOTAL	20% LOCAL 0004	20% LOCAL 0005	100% LOCAL 0021	100% LOCAL 0031	20% LOCAL 0042	100% LOCAL COMMUNICATION
ITEM	PROVISION	NO.	11EW	ON!	QUANTITY	RDWY RECON	RDWY RESURF	SAFETY	LANDSCAPE	TRAINEES	FIBER OPTIC
+	×	XX007468	PEDESTRIAN ST LIGHT	EACH	26			26			
		70001400	1 EDECTION OF ECT	LAGIT	20						
	X	XX007810	UTILITY PIPE REMOVAL	FOOT	192		192				
		,,,,,,,,,,,									
	x	XX007877	BICYCLE RACKS - FURNISH	EACH	5				5		
+	х	XX008034	SEATWALL 20" HT.	FOOT	183				183		
	x	XX008232	BICYCLE RACKS TO BE MOVED	EACH	25		25				
+	×	XX008356	STRUCTURAL SOIL	CU YD	804				804		
	х	XX008553	RETAINING WALL, SPECIAL	FOOT	78		78				
	×	XX008751	PORTLAND CEMENT CONCRETE BASE COURSE 5"	SQYD	3,904		3,904				
+	×	Z0003850	BENCHES	EACH	8				8		
+	×	Z0003855	BICYCLE RACKS	EACH	44				44		
	Х	Z0004002	BOLLARDS	EACH	16				16		
	×	Z0013796	SEDIMENT CONTROL, STABILIZED CONSTRUCTION ENTRANCE	SQ YD	300		300				
	Х	Z0013798	CONSTRUCTION LAYOUT	L SUM	1		1				
	Х	Z0015000	CURB STOPS 1"	EACH	5		5				
	Х	Z0015300	CURB STOPS 2"	EACH	5		5				
		70010700									
	X	Z0018700	DRAINAGE STRUCTURE TO BE REMOVED	EACH	9		9				
		70010000	DUST CONTROL WATERING	UNIT	300		300				
	Х	Z0019600	DUST CONTROL WATERING	UNII	300		300				
	X	Z0030850	TEMPORARY INFORMATION SIGNING	SQ FT	490	•	490				
	^	25050050	TELL STANT BY CHEATON COUNTY	Juli	750		-,50				
+	Х	Z0033028	MAINTENANCE OF LIGHTING SYSTEM	CAL MO	6			6			
т	^		The state of the s	J. C. INIO	<u> </u>	<u></u>		-			

th@mas.	
engineering group	

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

									F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
			SUI	VIM/	<b>NRY</b>	OF QUA	ANTITIES		1405	16-00264-00-PV	COOK	344	17
											CONTRACT	T NO. 6	1F36
SCALE:	NTS	SHEET	14	OF	15	SHEETS	STA.	TO STA.		ILLINOIS FED. A	ID PROJECT		


			SUIVIIVIARY	UF QUANT	IIIE9						
		_				80% FEDERAL 20% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL	0% FEDERAL 100% LOCAL	80% FEDERAL 20% LOCAL	0% FEDERAL 100% LOCAL
SPECIALTY ITEM	SPECIAL PROVISION	CODE NO.	ITEM	TINU	TOTAL QUANTITY	0004 RDWY RECON	0005 RDWY RESURF	0021 SAFETY	0031 LANDSCAPE	0042 TRAINEES	COMMUNICATION FIBER OPTIC
·											
+	х	Z0033044	RE-OPTIMIZE TRAFFIC SIGNAL SYSTEM LEVEL 1	EACH	1			1			
	X	Z0033700	LONGITUDINAL JOINT SEALANT	FOOT	9,541		9,541				
	X	Z0036700	PARKING METER POSTS TO BE REMOVED	EACH	60		60				
	X	Z0040530	PIPE UNDERDRAIN REMOVAL	FOOT	994		994	<del></del>			
+	х	Z0044600	PRESSURE CONNECTION 6" X 10"	EACH	2		2				
	х	Z0062458	TEMPORARY PAVEMENT (VARIABLE DEPTH)	TON	10		10				
+	Х	Z0073510	TEMPORARY TRAFFIC SIGNAL TIMING	EACH	4			4			
	Х	Z0076600	TRAINEES	HOUR	2,500					2,500	
	Х	Z0076604	TRAINEES TRAINING PROGRAM GRADUATE	HOUR	2,500					2,500	
+	х	xx00934/	ROD AND TRACE EXISTING SANITARY SERVICES	EACH	48		48				
		,,									
	x	XX009342	COLORED PORTLAND CEMENT CONCRETE CROSSWALK, 13 INCH	SQFT	5,828			5,828			
		7,7,000									
+	х	XX069343	WATER MAIN LEAK DETECTION SURVEY AND REPORT	LSUM	1			1			
		,									
+	Х	XX609344	ORNAMENTAL LUMINAIRE, LED, VERTICAL MOUNT, LOW WATTAGE	EACH	14			14			
+	Х	XX009345	STEEL MAST ARM ASSEMBLY AND POLE (INSTALL ONLY)	EACH	5			5			
		,									
+	X	XX009346	STEEL COMBINATION MAST ARM ASSEMBLY AND POLE (INSTALL ONLY)	EACH	11			11			
		110-010									
l		L			L	<u> </u>	<u> </u>		L		

th@mas.
engineering group

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2,0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -


STATE	E OI	FILLINOIS
DEPARTMENT	0F	TRANSPORTATION

_										F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEE NO.
				SU	VIM/	ARY	OF QU	ANTITIES		1405	16-00264-00-PV	COOK	344	18
												CONTRACT	NO. 6	51F36
	SCALE: NTS SHEET 15 OF 15 SHEETS STA. TO STA.							ILLINOIS FED. A	ID PROJECT					



#### **EXISTING TYPICAL SECTION 1**

STA 10+26.74 TO STA 19+72.50, LAKE STREET (HARLEM AVENUE TO SPEED TABLE)



#### **NOTES**

- LOCATIONS OF INTERMITTENT COMB CONC CURB AND GUTTER REMOVAL AND REPLACEMENT, PCC SIDEWALK REMOVAL AND REPLACEMENT, AND PAVEMENT PATCHING SHALL BE DETERMINED IN THE FIELD DURING CONSTRUCTION BY THE ENGINEER.
- 2. REFER TO GEOTECHNICAL SERVICES REPORT FOR MORE INFORMATION ON PAVEMENT CORES AND TROLLY TRACKS.

# **EXISTING LEGEND**

- A HMA PAVEMENT, 10"

  B AGGREGATE BASE COURSE, 14"

  C COMB CONC CURB & GUTTER, TYPE B-6.12

  D COMB CONC CURB & GUTTER, DEPRESSED

  E SIDEWALK

  F FURNITURE ZONE COMB CONC CURB & GUTTER, TYPE B-6.12

thamas
engineering group

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 10.00000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

FOR AREAS OF SIDEWALK REMOVAL OMISSIONS\*

STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	


**EXISTING TYPICAL SECTION 2** STA 19+72.50 TO STA 21+50, LAKE STREET

(SPEED TABLE TO FOREST AVENUE)

								F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
			F	уіст	ING	IAKE	CTRFFT		1405	16-00264-00-PV	COOK	344	19
	EXISTING LAKE STREET										CONTRACT	NO. 6	1F36
SCALE:	NTS	SHEET	1	OF	7	SHEETS	STA.	TO STA.		ILLINOIS FED. A	D PROJECT		




#### **REMOVALS – REFER TO REMOVAL SHEETS**



#### **EXISTING TYPICAL SECTION 3**

STA 21+50 TO STA 23+50, LAKE STREET (WITHIN BOTH INTERSECTIONS OF FOREST AVENUE)



#### **NOTES**

- LOCATIONS OF INTERMITTENT COMB CONC CURB AND GUTTER REMOVAL AND REPLACEMENT, PCC SIDEWALK REMOVAL AND REPLACEMENT, AND PAVEMENT PATCHING SHALL BE DETERMINED IN THE FIELD DURING CONSTRUCTION BY THE ENGINEER.
- REFER TO GEOTECHNICAL SERVICES REPORT FOR MORE INFORMATION ON PAVEMENT CORES AND TROLLY TRACKS.

### **EXISTING TYPICAL SECTION 4**

STA 23+50 TO STA 38+70, LAKE STREET (FOREST AVENUE TO OAK PARK AVENUE)

#### **EXISTING LEGEND**

A HMA PAVEMENT, 10"
B AGGREGATE BASE COURSE, 14"
C HMA PAVEMENT COURSE, 8"

AGGREGATE BASE COURSE, 16" E HMA PAVEMENT COURSE, 3.25'
F PCC BASE COURSE, 8.5"

G AGGREGATE SUB-BASE COURSE, 12"

⊞ COMB CONC CURB & GUTTER, TYPE B-6.12

Ⅲ SIDEWALK

COUNTY TOTAL SHEET NO. COOK 344 20


CONTRACT NO. 61F36

J FURNITURE ZONE

Thabhas
e <u>ngineering grou</u> p
service at the highest grade.

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 10.00000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

	TYPICAL SECT	F.A.U. RTE.	SECTION	COUNTY	
	EXISTING LAKE	1405	16-00264-00-PV	COOK	
				CONTRA	
SCALE: NTS	SHEET 2 OF 7 SHEETS	STA. TO STA.		ILLINOIS FED.	AID PROJECT



## **EXISTING TYPICAL SECTION 5**

STA 38+70 TO STA 44+15, LAKE STREET (OAK PARK AVENUE TO EUCLID AVENUE)

#### **NOTES**

- LOCATIONS OF INTERMITTENT COMB CONC CURB AND GUTTER REMOVAL AND REPLACEMENT, PCC SIDEWALK REMOVAL AND REPLACEMENT, AND PAVEMENT PATCHING SHALL BE DETERMINED IN THE FIELD DURING CONSTRUCTION BY THE ENGINEER.
- 2. REFER TO GEOTECHNICAL SERVICES REPORT FOR MORE INFORMATION ON PAVEMENT CORES AND TROLLY TRACKS.

#### **EXISTING LEGEND**

- A HMA PAVEMENT SURFACE COURSE, 2"

  B HMA PAVEMENT BINDER COURSE, 3"

  C PCC BASE COURSE, 8"

  D AGGREGATE SUB-BASE COURSE, 4"

  E HMA PAVEMENT SURFACE COURSE, 1.5"

  F HMA PAVEMENT BINDER COURSE, 8"

  G COMB CONC CURB & GUTTER, TYPE B-6.12

  H SIDEWALK


  I FURNITURE ZONE


thomas	USE
engineering group	PLO
service at the highest grade	PLO

JSER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 10.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE	OF ILLINOIS	
DEPARTMENT (	OF TRANSPORTATION	


TYPICAL SECTIONS	F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
EXISTING LAKE STREET	1405	16-00264-00-PV	COOK	344	21
LAISTING LAKE STILLT			CONTRACT	NO. 6	1F36
SCALE: NTS   SHEET 3 OF 7 SHEETS   STA. TO STA.		ILLINOIS FED. A	D PROJECT		






#### PROPOSED TYPICAL SECTION 1

STA 10+26.74 TO STA 12+97, LAKE STREET (HARLEM AVENUE TO MAPLE AVE)





\*SEE PROPOSED GEOMETRIC LAYOUT SHEETS FOR AREAS OF BLUESTONE OMISSIONS\*

## PROPOSED TYPICAL SECTION 2

STA 12+97 TO STA 21+27, LAKE STREET (MAPLE AVE TO FOREST AVE)

#### NOTES

- GEOTECHNICAL FABRIC FOR GROUND STABILIZATION IS PLACED BENEATH AGGREGATE SUBGRADE IMPROVEMENT 12"
- 2. SEE PLAT OF HIGHWAYS FOR ROW INFORMATION.
- 3. SEE CROSS SECTIONS FOR GRADING INFORMATION.
- SEE CROSS SECTIONS FOR VARIABLE DEPTH MILL INFORMATION.
- LONGITUDINAL JOINT SEALANT SHALL BE INSTALLED UNDER THE SURFACE LIFT FOR HMA OVERLAYS.
- LONGITUDINAL JOINT SEALANT SHALL BE INSTALLED UNDER THE SURFACE LIFT AND UNDER THE TOP BINDER LIFT FOR FULL-DEPTH HMA PAVEMENT.
- 7. LOCATIONS OF INTERMITTENT PAVEMENT PATCHING SHALL BE DETERMINED IN THE FIELD DURING CONSTRUCTION BY THE ENGINEER. DOWEL BARS AND TIE BARS SHALL BE USED FOR CLASS B PATCHES AS DIRECTED BY THE ENGINEER.

STRUCTURAL DESIGN TRAFFIC 2028 PV = 8,859 SU = 1,160 MU = 527

ROAD STREET CLASSIFICATION: PERCENT OF STRUCTURAL DESIGN TRAFFIC IN DESIGN LANE: PV = <u>50%</u> SU = <u>50%</u> MU = <u>50%</u>

TRAFFIC FACTOR: ACTUAL TF 3.35 AC TYPE = PG 64-22 MINIMUM TF N/A SURFACE = PG 64-22 AC GRADE: BINDER = PG 64-22

SUBGRADE SUPPORT RATINGS SSR = <u>POOR</u>

#### PROPOSED LEGEND

- 1 PORTLAND CEMENT CONCRETE SIDEWALK
  - A PCC SIDEWALK, 5"
- B SUBBASE GRAN MATERIAL, TY B 4" 2 PORTLAND CEMENT CONCRETE SIDEWALK, SPECIAL
- A PCC SIDEWALK 5", SPECIAL
- B SUBBASE GRAN MATERIAL, TY B 4"
- (3) THERMAL CUT BLUESTONE SIDEWALK
- A PAVER BLOCKS, SPECIAL
  - (B) 1" SAND SETTING BED (INC IN PAVER BLOCK, SP)
  - © PCC BASE COURSE, 5"
  - D SUBBASE GRAN MATERIAL, TY B 4"
- © GEOTECHNICAL FABRIC (INC IN PAVER BLOCK, SP) 4 BRICK PAVER INTERSECTIONS
  - (A) BRICK PAVERS (3" X 9" X 3") B ¾" BITUMINOUS SETTING BED (INC IN BRICK PAVERS)
  - © HES PCC BASE COURSE, 9"
- D AGGREGATE SUBGRADE IMPROVEMENT, 12"
- (5) WEEP HOLES (REFER TO DETAILS)
- (6) GEOTECHNICAL FABRIC FOR GROUND STABILIZATION
- 7 COMB CONC CURB & GUTTER, TYPE B-6.12 (MODIFIED)
- (8) COMB CONC CURB & GUTTER, TYPE B-6.12 (SPECIAL)

- 9 HMA MILL AND RESURFACE (HMA SURF REMOVAL, 21/4")
  - (A) HMA SURFACE COURSE, IL-9.5, MIX "D", N70,  $1\frac{1}{2}$ " B LONGITUDINAL JOINT SEALANT (REFER TO NOTES)
- © POLY HMA BINDER COURSE, IL-4.75, N50, 3/4" (10) HMA SURFACE REMOVAL, VARIABLE DEPTH
- $\triangle$  HMA SURFACE COURSE, IL-9.5, MIX "D", N70,  $1\frac{1}{2}$ "
- (B) LONGITUDINAL JOINT SEALANT (REFER TO NOTES) © POLY HMA BINDER COURSE, IL-4.75, N50, 3/4" MIN
- 11) PCC BASE COURSE, VARIABLE DEPTH 12 HMA PAVEMENT (FULL DEPTH), 101
  - (A) HMA SURFACE COURSE, IL-9.5, MIX "D", N70, 2" B LONGITUDINAL JOINT SEALANT (REFER TO NOTES)
  - © HMA BINDER COURSE, IL-19.0, N70, 8"
- (D) AGGREGATE SUBGRADE IMPROVEMENT, 12" (3) SILANE SURFACE SEALER (PENETRATING SEALER)
- 14 PROTECTIVE COAT
- (5) CLASS B PATCHES, 9" (SEE NOTE 7)
- 6 DOWEL BARS 11/4" AS DIRECTED BY THE ENGINEER
- ① TIE BARS ¾" AS DIRECTED BY THE ENGINEER (B) EPOXY COATED TIE BARS ¾" PER STANDARD 606001
- (9) CLASS D PATCHES, 10" (SEE NOTE 7)


e<u>ngineering grou</u>p

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 10.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 


			PF			L SECTI	IONS STREET	
SCALE:	NTS	SHEET	4	OF	7	SHEETS	STA.	TO STA.


SECTION COUNTY 344 22 1405 16-00264-00-PV COOK CONTRACT NO. 61F36



#### PROPOSED TYPICAL SECTION 3

STA 23+80 TO STA 30+00. LAKE STREET (FOREST AVE TO KENILWORTH)





#### PROPOSED TYPICAL SECTION 4

STA 31+98 TO STA 38+00, LAKE STREET (KENILWORTH AVE TO OAK PARK AVE)

#### NOTES

- GEOTECHNICAL FABRIC FOR GROUND STABILIZATION IS PLACED BENEATH AGGREGATE SUBGRADE IMPROVEMENT 12"
- 2. SEE PLAT OF HIGHWAYS FOR ROW INFORMATION.
- 3. SEE CROSS SECTIONS FOR GRADING INFORMATION.
- SEE CROSS SECTIONS FOR VARIABLE DEPTH MILL INFORMATION.
- LONGITUDINAL JOINT SEALANT SHALL BE INSTALLED UNDER THE SURFACE LIFT FOR HMA OVERLAYS.
- LONGITUDINAL JOINT SEALANT SHALL BE INSTALLED UNDER THE SURFACE LIFT AND UNDER THE TOP BINDER LIFT FOR FULL-DEPTH HMA PAVEMENT.
- 7. LOCATIONS OF INTERMITTENT PAVEMENT PATCHING SHALL BE DETERMINED IN THE FIELD DURING CONSTRUCTION BY THE ENGINEER. DOWEL BARS AND TIE BARS SHALL BE USED FOR CLASS B PATCHES AS DIRECTED BY THE ENGINEER.

#### STRUCTURAL DESIGN TRAFFIC 2028 PV = 8,859 SU = 1,160 MU = 527

ROAD STREET CLASSIFICATION: PERCENT OF STRUCTURAL DESIGN TRAFFIC IN DESIGN LANE: PV = <u>50%</u> SU = <u>50%</u> MU = <u>50%</u>

TRAFFIC FACTOR: ACTUAL TF 3.35 AC TYPE = PG 64-22 MINIMUM TF N/A AC GRADE: BINDER = PG 64-22 SURFACE = <u>PG 64-22</u>

SUBGRADE SUPPORT RATINGS SSR = <u>POOR</u>

#### PROPOSED LEGEND

- 1 PORTLAND CEMENT CONCRETE SIDEWALK
  - A PCC SIDEWALK, 5"
- B SUBBASE GRAN MATERIAL, TY B 4"
- (2) PORTLAND CEMENT CONCRETE SIDEWALK, SPECIAL
- A PCC SIDEWALK 5", SPECIAL
- B SUBBASE GRAN MATERIAL, TY B 4"
- (3) THERMAL CUT BLUESTONE SIDEWALK
- A PAVER BLOCKS, SPECIAL
- (B) 1" SAND SETTING BED (INC IN PAVER BLOCK, SP)
- © PCC BASE COURSE, 5"
- D SUBBASE GRAN MATERIAL, TY B 4"
- © GEOTECHNICAL FABRIC (INC IN PAVER BLOCK, SP)
- 4 BRICK PAVER INTERSECTIONS
  - (A) BRICK PAVERS (3" X 9" X 3")  $\textcircled{B} rac{3}{4}$ " BITUMINOUS SETTING BED (INC IN BRICK PAVERS)
  - © HES PCC BASE COURSE, 9"
- D AGGREGATE SUBGRADE IMPROVEMENT, 12"
- (5) WEEP HOLES (REFER TO DETAILS)
- (6) GEOTECHNICAL FABRIC FOR GROUND STABILIZATION
- 7 COMB CONC CURB & GUTTER, TYPE B-6.12 (MODIFIED) (8) COMB CONC CURB & GUTTER, TYPE B-6.12 (SPECIAL)

- 9 HMA MILL AND RESURFACE (HMA SURF REMOVAL, 21/4") (A) HMA SURFACE COURSE, IL-9.5, MIX "D", N70,  $1\frac{1}{2}$ "
  - B LONGITUDINAL JOINT SEALANT (REFER TO NOTES)
- © POLY HMA BINDER COURSE, IL-4.75, N50, 3/4" (10) HMA SURFACE REMOVAL, VARIABLE DEPTH
- $\triangle$  HMA SURFACE COURSE, IL-9.5, MIX "D", N70,  $1\frac{1}{2}$ " (B) LONGITUDINAL JOINT SEALANT (REFER TO NOTES)
- © POLY HMA BINDER COURSE, IL-4.75, N50, 3/4" MIN 11) PCC BASE COURSE, VARIABLE DEPTH
- 12 HMA PAVEMENT (FULL DEPTH), 10"
  - (A) HMA SURFACE COURSE, IL-9.5, MIX "D", N70, 2" B LONGITUDINAL JOINT SEALANT (REFER TO NOTES)
- © HMA BINDER COURSE, IL-19.0, N70, 8"
- (D) AGGREGATE SUBGRADE IMPROVEMENT, 12" (3) SILANE SURFACE SEALER (PENETRATING SEALER)
- 14 PROTECTIVE COAT
- (5) CLASS B PATCHES, 9" (SEE NOTE 7)
- 6 DOWEL BARS 11/4" AS DIRECTED BY THE ENGINEER ① TIE BARS ¾" AS DIRECTED BY THE ENGINEER
- (B) EPOXY COATED TIE BARS ¾" PER STANDARD 606001

(9) CLASS D PATCHES, 10" (SEE NOTE 7)





USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 10.00000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

TYPICAL SECTIONS								
			PF	ROPO	SED	LAKE	STREET	
SCALE:	NTS	SHEET	5	OF	7	SHEETS	STA.	TO STA.


SECTION COUNTY 344 23 1405 16-00264-00-PV COOK CONTRACT NO. 61F36






#### PROPOSED TYPICAL SECTION 5

STA 39+07 TO STA 44+15, LAKE STREET (OAK PARK AVENUE TO EUCLID AVENUE)





\*SEE PROPOSED INTERSECTION LAYOUT PLANS FOR CROSS SLOPE INFORMATION\*

#### PROPOSED TYPICAL SECTION 6

BRICK PAVER INTERSECTIONS MARION ST, FOREST AVE, OAK PARK AVE

#### NOTES

- GEOTECHNICAL FABRIC FOR GROUND STABILIZATION IS PLACED BENEATH AGGREGATE SUBGRADE IMPROVEMENT 12"
- 2. SEE PLAT OF HIGHWAYS FOR ROW INFORMATION.
- 3. SEE CROSS SECTIONS FOR GRADING INFORMATION.
- 4. SEE CROSS SECTIONS FOR VARIABLE DEPTH MILL INFORMATION.
- LONGITUDINAL JOINT SEALANT SHALL BE INSTALLED UNDER THE SURFACE LIFT FOR HMA OVERLAYS.
- LONGITUDINAL JOINT SEALANT SHALL BE INSTALLED UNDER THE SURFACE LIFT AND UNDER THE TOP BINDER LIFT FOR FULL-DEPTH HMA PAVEMENT.
- 7. LOCATIONS OF INTERMITTENT PAVEMENT PATCHING SHALL BE DETERMINED IN THE FIELD DURING CONSTRUCTION BY THE ENGINEER. DOWEL BARS AND TIE BARS SHALL BE USED FOR CLASS B PATCHES AS DIRECTED BY THE ENGINEER.

STRUCTURAL DESIGN TRAFFIC 2028 PV = 8,859 SU = 1,160 MU = 527

ROAD STREET CLASSIFICATION: CLASS II PERCENT OF STRUCTURAL DESIGN TRAFFIC IN DESIGN LANE: SU = <u>50%</u> MU = <u>50%</u>

TRAFFIC FACTOR: ACTUAL TF 3.35 AC TYPE = PG 64-22 MINIMUM TF N/A SURFACE = PG 64-22 AC GRADE: BINDER = PG 64-22

SUBGRADE SUPPORT RATINGS SSR = <u>POOR</u>

## PROPOSED LEGEND

- 1 PORTLAND CEMENT CONCRETE SIDEWALK
- A PCC SIDEWALK, 5"
- B SUBBASE GRAN MATERIAL, TY B 4"
- 2 PORTLAND CEMENT CONCRETE SIDEWALK, SPECIAL
  - A PCC SIDEWALK 5", SPECIAL B SUBBASE GRAN MATERIAL, TY B 4"
- (3) THERMAL CUT BLUESTONE SIDEWALK
- A PAVER BLOCKS, SPECIAL
- (B) 1" SAND SETTING BED (INC IN PAVER BLOCK, SP)
- © PCC BASE COURSE, 5" D SUBBASE GRAN MATERIAL, TY B 4"
- © GEOTECHNICAL FABRIC (INC IN PAVER BLOCK, SP)
- 4 BRICK PAVER INTERSECTIONS

SCALE: NTS SHEET

- (A) BRICK PAVERS (3" X 9" X 3") B ¾" BITUMINOUS SETTING BED (INC IN BRICK PAVERS)
- © HES PCC BASE COURSE, 9"
- (D) AGGREGATE SUBGRADE IMPROVEMENT, 12"
- (5) WEEP HOLES (REFER TO DETAILS)
- 6 GEOTECHNICAL FABRIC FOR GROUND STABILIZATION
- 7 COMB CONC CURB & GUTTER, TYPE B-6.12 (MODIFIED) (8) COMB CONC CURB & GUTTER, TYPE B-6.12 (SPECIAL)

- (9) HMA MILL AND RESURFACE (HMA SURF REMOVAL, 21/4")
- (A) HMA SURFACE COURSE, IL-9.5, MIX "D", N70,  $1\frac{1}{2}$ " B LONGITUDINAL JOINT SEALANT (REFER TO NOTES)
- © POLY HMA BINDER COURSE, IL-4.75, N50, 3/4"
- (10) HMA SURFACE REMOVAL, VARIABLE DEPTH
  - $\triangle$  HMA SURFACE COURSE, IL-9.5, MIX "D", N70,  $1\frac{1}{2}$ "
  - (B) LONGITUDINAL JOINT SEALANT (REFER TO NOTES)
- © POLY HMA BINDER COURSE, IL-4.75, N50, 3/4" MIN
- 11) PCC BASE COURSE, VARIABLE DEPTH
- (2) HMA PAVEMENT (FULL DEPTH), 10"
  - (A) HMA SURFACE COURSE, IL-9.5, MIX "D", N70, 2"
  - B LONGITUDINAL JOINT SEALANT (REFER TO NOTES)
  - © HMA BINDER COURSE, IL-19.0, N70, 8"
- (D) AGGREGATE SUBGRADE IMPROVEMENT, 12"
- (3) SILANE SURFACE SEALER (PENETRATING SEALER) 14 PROTECTIVE COAT
- 15 CLASS B PATCHES, 9" (SEE NOTE 7)
- 6 DOWEL BARS 11/4" AS DIRECTED BY THE ENGINEER
- ① TIE BARS ¾" AS DIRECTED BY THE ENGINEER (B) EPOXY COATED TIE BARS ¾" PER STANDARD 606001
- (9) CLASS D PATCHES, 10" (SEE NOTE 7)

th@mas e<u>ngineering grou</u>p

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 10.00000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

TYPICAL SECTIONS		F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
PROPOSED LAKE STREET		1405	16-00264-00-PV	COOK	344	24
				CONTRACT	NO. 6	1F36
C OF 7 CHEFTS STA	TO STA		T T. O.C. EED. A.	O DDO FOT		

HOT-MIX ASPHALT MIXTURE REQUIREMENTS						
	MIXTURE TYPE	AIR VOIDS @ N <sup>DES</sup>				
HOT-MIX ASPHALT PAVEMENT (FULL-DEPTH), 10"	HOT-MIX ASPHALT SURFACE COURSE, IL-9.5, MIX "D", N70, 2"	4% @ 70 Gyr.				
LAKE STREET	HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N70, 8"	4% @ 70 Gyr.				
TEMPORARY PAVEMENT (VARIABLE DEPTH) LAKE STREET	HOT-MIX ASPHALT SURFACE COURSE, IL-9.5, MIX "D", N70	4% @ 70 Gyr.				
HMA PAVEMENT RESURFACING	HOT-MIX ASPHALT SURFACE COURSE, IL-9.5, MIX "D", N70, 11/2"	4% <b>©</b> 70 Gyr.				
LAKE STREET	POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-4.75, N50, 3/4" MINIMUM	3.5% @ 50 Gyr.				
CLASS D PATCHES, 10 INCH	HOT-MIX ASPHALT SURFACE COURSE, IL-9.5, MIX "D", N70, 2"	4% ⊚ 70 Gyr.				
LAKE STREET	HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N70, 8"	4% <b>@</b> 70 Gyr.				

#### NOTES

THE UNIT WEIGHT USED TO CALCULATE ALL HOT-MIX ASPHALT SURFACE MIXTURES IS 112 LBS/SQ YD/IN.

FOR USE OF RECYCLED MATERIALS SEE DISTRICT ONE SPECIAL PROVISIONS.

THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 76-22"

AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALL BE PG 64-22 UNLESS

MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS. FOR HMA FULL DEPTH "AC TYPE"

SEE SPECIAL PROVISIONS.

thama	10
	3.
	®
	<u>u</u> p
service at the highest gr	ade⊗

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 10.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE OF	ILLINOIS
DEPARTMENT OF	TRANSPORTATION

									F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
				IYP	'ICA	L SECT	IONS		1405	16-00264-00-PV	соок	344	25
											CONTRACT	NO. 6	1F36
SCALE:	NTS	SHEET	7	OF	7	SHEETS	STA.	TO STA.		ILLINOIS FED. A	ID PROJECT		

#### ROADWAY REMOVAL COMB CURB AND GUTTER REMOVAL STATION STATION LOCATION (44000500) LAKE STREET 10+27.29 10+48.33 LT 31.6 10+27.38 10+27.29 LT 15.0 10+27.46 10+63.70 RT 63.8 10+45.32 12+40.11 LT 95.0 10+48.33 11+45.32 LT 97.0 10+63.70 11+45.46 RT 81.8 11+45.46 12+41.37 RT 96.1 12+40.11 12+93.89 LT 54.2 12+41.37 12+60.94 RT 36.1 12+59.05 19+76.01 RT 17.0 12+93.89 12+97.33 5.5 12+95.86 13+22.70 LT 26.9 12+97.33 12+97.26 LT 15.7 13+27.42 13+09.83 LT 29.5 13+27.42 15+72.29 LT 244.9 14+77.02 14+31.50 RT 45.5 14+77.02 15+27.44 RT 50.5 15+27.44 15+71.72 RT 44.3 15+71.72 15+76.88 RT 6.9 15+72.29 15+82.07 LT 12.6 15+76.88 15+84.50 8.3 15+82.07 16+18.02 LT 36.0 15+84.50 16+55.46 RT 71.0 16+18.02 16+41.37 LT 37.0 16+41.37 16+41.35 LT 39.7 16+74.37 LT 30.0 16+74.61 16+74.37 LT 47.1 16+97.17 17+65.88 68.7 LT 17+65.88 17+71.66 6.1 17+71.66 17+77.06 LT 8.3 17+77.06 18+21.01 LT 43.9 17+82.34 18+20.11 37.8 RT 18+20.11 18+94.37 RT 74.3 18+21.01 18+79.49 58.5 LT 60.2 18+94.37 19+35.87 RT 41.5 19+35.87 19+59.05 RT 24.8 19+39.70 19+58.42 20.9 19+58.42 20+40.47 LT 82.1 19+76.01 19+96.10 RT 40.4 20+19.53 19+76.01 RT 43.5 20+06.92 20+07.50 13.6 20+07.50 20+19.53 RT 20.8 20+19.53 20+61.81 42.3 20+40.47 21+17.98 LT 77.5 20+40.47 20+58.51 19.6 LT 20+58.51 21+00.50 42.0 20+61.81 21+19.21 RT 57.5 21+17.98 21+00.50 LT 19.2 21+17.98 21+28.49 10.5

ROADWAY REMOVAL					
STATION	STATION	LOCATION	PAVEMENT REMOVAL (SQ YD) (44000100)		
LAKE STR	EET				
10+26.70	12+45.30	LT/RT	47		
12+53.30	12+87.21	LT/RT	41		
12+98.03	15+78.44	LT/RT	73		
15+81.76	19+58.36	LT/RT	665		
19+77.05	23+83.98	LT/RT	1,626		
27+75.00	32+05.00	LT/RT	241		
36+80.00	44+15.00	LT/RT	3,737		
TEMPORAR'	Y PAVEMEN	IT REMOVAL	106		
PF	ROJECT TOT	AL	6,536		

STATION	STATION	LOCATION	COMB CURB AND GUTTER REMOVAL
STATION	STATION	LOCATION	(FT)
			(44000500)
21+19.21	21+41.98	RT	36.7
21+28.49	21+40.00	LT	11.5
21+41.98	21+41.82	RT	30.2
21+81.36	22+14.82	RT	57.1
22+14.82	22+96.24	RT	81.4
22+96.24	23+68.56	RT	72.4
23+68.56	24+16.20	RT	47.6
25+65.21	25+94.65	RT	29.5
26+25.89	26+55.17	LT	29.3
26+47.59	26+55.17	LT	18.2
26+55.17	26+92.72	LT	37.6
26+56.15	26+80.71	RT	24.5
27+75.00	30+04.03	LT	229.0
27+75.92	31+22.42		
30+04.03	30+36.93	RT	346.5
	30+36.93	LT	50.7
30+70.57		LT	19.1
30+70.91	30+80.51	LT	15.2
30+80.51	32+05.00	LT	124.5
31+22.42	31+32.18	RT	20.3
31+32.18	31+32.28	RT	9.6
31+69.04	31+83.03	RT	21.6
31+69.12	31+69.04	RT	12.1
31+83.03	31+97.63	RT	14.6
34+88.27	35+01.42	RT	13.2
36+80.86	38+29.70	RT	148.8
38+00.00	38+19.45	LT	19.5
38+19.45	38+40.21	LT	31.9
38+29.70	38+46.29	RT	25.3
38+40.21	38+38.60	LT	32.6
38+46.29	38+46.89	RT	9.6
38+89.75	38+90.28	LT	8.3
38+90.28	39+04.76	LT	26.4
38+96.37	39+11.04	RT	29.3
38+96.84	38+96.37	RT	7.3
39+04.76	39+40.48	LT	35.7
39+11.04	43+33.90	RT	422.9
39+40.48	39+84.08	LT	43.7
39+84.08	41+02.14	LT	118.1
41+02.14	41+02.14		
	41+07.21	LT	8.6
41+02.14		LT	31.6
41+07.21	41+07.05	LT	9.2
41+25.45	41+33.75	LT	19.6
41+33.75	42+11.66	LT	77.9
42+11.66	42+18.34	LT	6.7
43+33.90	43+51.90	RT	24.3
43+51.90	43+52.63	RT	12.2
43+78.55	44+15.00	LT	53.0
	4414400	RT	43.3
43+86.81	44+14.96	KI	10.0

ROADWAY REMOVAL

COMB CURB AND

	ROAD	WAY REMOV	/AL
STATION	STATION	LOCATION	HMA SURFACE REMOVAL, VARIABLE DEPTH (SQ YD) (X4401198)
LAKE STR	EET		
10+22.58	12+42.50	LT/RT	823
12+62.50	16+26.00	LT/RT	1,570
16+42.82	16+72.82	LT	130
17+35.00	19+56.50	LT/RT	948
19+88.50	21+23.00	LT/RT	318
21+43.95	21+84.26	RT	105
23+10.62	23+45.26	LT	31
27+75.00	32+05.00	LT/RT	2,310
36+80.86	38+23.00	RT	383
PF	ROJECT TOT	AL	6,618

#### **SCHEDULE OF QUANTITIES**

SOILEBOLE OF GOARTHILS				
	ROAD	WAY REMOV	/AL	
STATION	STATION	LOCATION	SIDEWALK REMOVAL (SQ FT) (44000600)	
LAKE STR	EET			
10+27.95	12+60.42	RT	4,114.9	
10+28.02	12+96.72	LT	2,828.6	
10+70.56	11+02.95	LT	50.3	
11+09.98	11+40.51	LT	52.3	
11+77.02	12+22.20	LT	83.4	
11+77.45	12+22.93	RT	89.4	
13+10.60	15+87.21	LT	2,430.0	
13+12.93	13+18.15	LT	13.9	
14+31.56	16+55.38	RT	1,671.9	
16+17.38	16+33.26	LT	76.7	
16+30.56	16+40.52	LT	258.9	
16+75.17	16+85.36	LT	395.6	
17+41.07	21+77.88	LT	3,242.3	
17+82.02	19+95.04	RT	1,687.7	
20+08.13	21+04.98	RT	557.5	
20+23.54	20+98.96	RT	196.6	
21+82.55	31+31.58	RT	7,313.4	
26+48.47	30+31.99	LT	2,800.5	
30+71.80	32+05.01	LT	1,064.0	
31+70.31	31+97.64	RT	284.1	
32+22.71	32+34.77	RT	86.5	
32+37.03	32+47.08	LT	69.6	
32+70.12	32+76.25	RT	42.4	
32+89.61	33+01.88	LT	89.1	
32+91.34	33+04.10	RT	91.4	
33+13.25	33+18.31	LT	41.4	
33+58.69	33+76.87	LT	171.9	
33+68.73	33+82.78	RT	98.1	
34+11.88	34+27.81	RT	121.0	
34+55.10	34+67.12	RT	116.8	
34+55.52	34+80.73	LT	311.2	
34+88.46	35+05.68	RT	151.8	
34+89.44	35+02.62	LT	145.5	
35+38.16	35+56.03	LT	196.2	
35+50.06	35+55.15	RT	52.6	
35+73.57	35+85.59	RT	130.3	
35+77.01	35+89.01	LT	133.9	
36+20.06	36+26.15	RT	67.8	
36+27.69	36+33.84	LT	68.9	
36+39.69	36+63.84	LT	280.4	
36+40.82	38+46.23	RT	2,568.7	
36+71.84	36+76.05	LT	47.7	
37+10.39	37+22.58	LT	146.7	
37+29.96	37+36.15	LT	74.3	
37+62.60	37+68.68	LT	75.7	
37+99.92	38+39.45	LT	753.3	
38+90.58	41+06.67	LT	2,128.4	
38+97.08	43+51.40	RT	5,218.0	
	39+40.42	LT	20.1	
39+33 /a		LT	1,238.6	
39+33.75 41+26.30	42+18 18			
41+26.30	42+18.18 43+31.52			
41+26.30 43+20.56	43+31.52	LT	69.3	
41+26.30				

	ROAD	WAY REMOV	/AL
STATION	STATION	LOCATION	HMA SURFACE REMOVAL, 2 1/4" (SQ YD) (44000158)
LAKE STR	EET		
23+84.00	27+75.00	RT/LT	2,091
32+05.00	38+23.00	RT/LT	2,922
PF	5,013		

	ROADWAY REMOVAL					
STATION	STATION	LOCATION	REMOVE EXISTING BRICK PAVERS (SQ FT) (X0327989)			
LAKE STR	REET					
10+70.60	11+02.99	LT	187.1			
10+70.60	10+96.69	RT	132.1			
11+09.40	11+39.76	RT	162.3			
11+10.04	11+40.48	LT	171.2			
11+46.82	11+77.59	RT	370.9			
11+47.62	11+77.14	LT	350.3			
11+84.17	12+15.03	LT	209.4			
11+84.84	12+15.33	RT	199.2			
12+22.10	12+42.30	LT	323.7			
12+56.20	12+96.62	LT	461.4			
12+22.83	12+41.95	RT	307.1			
12+45.16	12+53.13	LT/RT	214.2			
12+98.17	13+16.42	LT	223.8			
13+10.50	13+20.63	LT	29.4			
13+13.02	13+33.65	LT	107.7			
13+40.57	13+66.23	LT	157.0			
13+73.18	14+03.33	LT	183.7			
14+10.25	14+77.45	LT	406.8			
14+31.49	14+76.95	RT	370.4			
14+83.99	15+17.33	RT	224.9			
15+24.61	15+47.39	RT	127.2			
15+54.57	16+55.48	RT	1,065.1			
15+54.90	16+40.52	LT	1,361.5			
16+75.07	17+86.64	LT	1,676.1			
17+93.80	18+21.34	LT	144.5			
18+28.48	18+58.74	LT	186.4			
18+65.83	18+93.73	LT	214.6			
18+74.12	18+94.04	RT	147.4			
19+00.94	19+29.45	LT	224.8			
19+01.12	19+30.26	RT	227.3			
19+36.56	21+78.36	LT	2.542.5			
19+37.17	19+95.04	RT	822.0			
19+58.36	19+77.05	LT/RT	433.1			
20+08.17	20+23.59	RT	221.9			
20+30.33	20+91.44	RT	391.7			
20+30.33	21+41.27	RT	1,048.7			
39+17.49	40+01.82	RT	495.2			
39+20.22	40+01.62	LT	706.5			
41+77.13 42+12.67	42+06.75 42+37.79	RT RT	183.8 152.2			
42+12.67	42+37.79	RT	152.2			
42+72.91 43+01.42	42+95.62	RT RT	135.6			
43+01.42	43+26.15	LT	144.6			
43+84.47	43+87.66		6.2			
	44+00.62	LT	3.8			
PF	ROJECT TOT	AL	17,598			

	ROAD	WAY REMOV	AL	
STATION	STATION	LOCATION	DRIVEWAY PAVEMENT REMOVAL (SQ YD) (44000200)	
LAKE STR	EET			
19+88.84	20+11.43	RT	36	
25+69.57	25+90.44	RT	9	
26+25.79	26+50.38	LT	31	
26+59.38	26+77.17	RT	4	
26+74.37	26+88.51	LT	11	
28+30.77	28+46.56	LT	11	
41+07.45	41+27.18	LT	29	
PF	OJECT TOT	AL	131	

	PIPE UN	IDERDRAIN R (Z0040530)	EWOVAL	
STATION	OFFSET (FT)	STATION	OFFSET (FT)	QUANTITY (FT)
LAKE STRE	ET			
10+66.89	25.3' LT	12+16.24	25.6' LT	129.5
10+71.78	20.6' RT	12+37.04	22.0' RT	165.3
11+96.40	25.2' LT	11+96.06	15.8' LT	9.4
11+96.40	25.2' LT	12+16.24	25.6' LT	19.8
12+37.04	22.0' RT	12+41.28	12.3' RT	10.5
13+37.66	26.5' LT	13+61.71	27.0' LT	24.1
13+61.71	27.0' LT	13+69.44	27.2' LT	7.7
14+08.71	25.6' LT	14+08.88	22.6' LT	3.0
14+80.49	27.0' RT	15+82.72	27.8' RT	102.2
14+81.87	28.3' LT	15+50.34	27.7' LT	69.7
15+50.34	27.7' LT	15+53.12	24.4' LT	4.3
15+50.34	27.7' LT	15+81.67	27.3' LT	31.3
15+82.72	27.8' RT	15+85.44	20.7' RT	7.6
17+57.50	21.2' LT	17+87.24	27.1' LT	30.3
17+87.24	27.1' LT	19+31.11	25.9' LT	143.9
18+70.98	24.5' RT	19+32.25	24.2' RT	61.3
19+32.25	24.2' RT	19+34.94	21.2' RT	4.0
19+35.48	25.6' LT	19+49.79	16.5' LT	16.9
20+26.68	24.0' RT	20+61.84	24.1' RT	35.2
20+61.84	24.1' RT	20+61.96	4.9' RT	19.3
20+61.84	24.1' RT	20+94.83	23.9' RT	33.0
20+74.18	25.1' LT	21+40.02	25.0' LT	65.3
	PROJEC	T TOTAL	•	994

STORM SEWER REMOVAL, 8" (55100300)				
STATION	OFFSET (FT)	STATION	OFFSET (FT)	QUANTITY (FT)
LAKE STREE	T			
14+08.88	22.6' LT	14+08.96	19.5' LT	9.2
15+71.21	23.3' RT	15+85.44	20.7' RT	14.5
17+56.89	16.1' LT	17+57.5	9.9' LT	6.1
19+34.90	21.2' RT	19+34.90	12.3' RT	8.9
20+61.90	12.2' RT	20+62.00	4.9' RT	7.2
22+45.53	29.7' RT	22+45.66	17.1' RT	12.6
30+90.53	24.5' RT	30+90.40	18.0' RT	6.5
PROJECT TOTAL				65

<b>4</b> 1. ~
(\(\frac{1}{2}\) \(\frac{1}{2}\)
engineering group
convice at the bighest grade

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

	F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
SCHEDULE OF QUANTITIES		16-00264-00-PV	соок	344	26
			CONTRACT	NO. 6	1F36
SCALE: NTS   SHEET 1 OF 7 SHEETS   STA. TO STA.		ILLINOIS FED. A	ID PROJECT		

#### FRAMES AND LIDS TO BE ADJUSTED (SPECIAL) (X6030310) OFFSET QUANTITY STATION (EACH) (FT) SANITARY MANHOLES 10+48 1.1' LT 12+68 0.4' LT 13+42 0.7' RT 19+32 0.2' RT 25+29 2.3' LT 27+30 1.0' LT 29+03 1.8' LT 30+39 41.8' LT 30+54 0.6' LT 31+25 2.0' LT 32+86 0.8' RT 34+52 6.0' RT 34+86 3.9' RT 36+78 1.1' RT 38+67 49.9' LT VALVE VAULTS 12+82 13+17 4.8 15+90 30+67 30+83 13.2 31+66 22.9 31+81 9.5 34+46 12.7 PROJECT TOTAL

SANITARY MANHOLES TO BE ADJUSTED (X6026050)				
STATION	OFFSET	QUANTITY		
017111011	(FT)	(EACH)		
LAKE STREE	ĒΤ			
13+95	30.0 LT	1		
16+42	52.5 LT	1		
16+53	3.1 LT	1		
17+03	1.5 RT	1		
21+59	1.7 LT	1		
23+28	1.2 RT	1		
38+70	0.0 RT	1		
38+72	33.2 RT	1		
38+73	46.6 RT	1		
41+17	0.0 LT	1		
43+49	0.0 RT	1		
43+68	35.3 RT	1		
43+82	19.0 LT	1		
PROJECT TOTAL 13				

VALVE VAULTS TO BE ADJUSTED (60265700)				
STATION	OFFSET	QUANTITY		
OTATION	(FT)	(EACH)		
LAKE STREE	ĒΤ			
21+55	12.6 RT	1		
23+57	8.9 RT	1		
38+40	10.0 RT	1		
38+55	12.2 RT	1		
39+11	10.0 RT	1		
43+57	5.7 LT	1		
43+78	10.0 RT	1		
PROJECT TOTAL 7				

DOMESTIC WATER SERVICE BOXES TO BE ADJUSTED (56500600)			
STATION	OFFSET	QUANTITY	
	(FT)	(EACH)	
LAKE STREE			
11+12	27.2 RT	1	
11+87	29.7 LT	1	
11+87	28.8 LT	1	
11+91	28.5 RT	1	
12+53	29.4 LT	1	
13+44	31.9 LT	1	
13+45	32.0 LT	1	
13+46	32.2 LT	1	
13+47	32.0 LT	1	
13+48	31.8 LT	1	
14+36	31.7 RT	1	
14+47	29.1 LT	1	
14+84	30.1 RT	1	
14+86	30.0 LT	1	
14+86	29.0 LT	1	
15+02	30.7 RT	1	
15+08	30.4 RT	1	
15+15	30.1 RT	1	
15+15	29.7 RT	1	
15+38	29.6 RT	1	
15+45	31.0 LT	1	
15+63	28.0 RT	1	
15+89	29.1 RT	1	
16+76	62.8 LT	1	
17+69	28.6 LT	1	
17+97	27.1 RT	1	
18+39	29.2 LT	1	
18+39	27.9 LT	1	
18+60	28.8 RT	1	
18+63	27.1 RT	1	
18+64	29.4 RT	1	
18+68	28.6 LT	1	
19+22	27.4 RT	1	
19+28	29.0 LT	1	
19+29	27.8 LT	1	
20+78	28.6 RT	1	
20+78	27.4 RT	1	
25+26	26.6 RT	1	
26+37	27.3 RT	1	
28+51	27.9 RT	1	
28+62	27.9 RT 27.3 RT	1	
		-	
33+78	32.3 RT	1	
34+55	35.3 RT	1	
36+30	30.2 RT	1	
38+02	26.8 LT	1	
40+66	29.5 LT	1	
40+88	28.5 LT	1 47	

PROJECT TOTAL

	• •	
STATION	OFFSET	QUANTITY
	(FT)	(EACH)
LAKE STRE		
11+00	22.3 RT	1
11+12	26.5 RT	1
11+76	30.4 LT	1
11+78	2.4 RT	1
12+87	29.6 LT	1
12+87	2.8 RT	1
12+91	34.1 LT	1
12+93	26.2 RT	1
13+22	32.5 LT	1
13+25	4.2 RT	1
13+34	32.4 LT	1
13+35	5.7 RT	1
14+23	19.6 RT	1
16+58	1.3 RT	1
16+79	62.1 LT	1
17+12	7.6 RT	1
17+43	2.8 RT	1
17+44	25.7 LT	1
17+49	18.6 RT	1
17+62	5.6 RT	1
19+79	3.6 RT	1
19+80	28.9 LT	1
19+83	28.4 LT	1
19+83	3.5 RT	1
20+93	4.1 RT	1
20+94	28.9 LT	1
23+64	27.2 RT	1
24+18	25.7 RT	1
24+10	28.4 RT	1
26+52	26.9 RT	1
26+93	26.7 LT	1
28+85	27.7 RT	1
29+02	27.7 KT	1
29+02	26.5 RT	1
		1
33+81	22.8 LT	1
34+72	30.5 RT	
38+18	27.9 RT	1
38+91	54.6 LT	1
39+04	12.4 LT	1
40+77	29.1 LT	1
41+41	27.2 RT	1
42+02	28.9 LT	1
43+29	28.5 LT	1
44+12	11.6 LT	1
PROJEC	T TOTAL	44

## **SCHEDULE OF QUANTITIES**

BICYCLE RACKS TO BE MOVED (XX008232)			
STATION	OFFSET (FT)	QUANTITY (EACH)	
LAKE STRE	ET		
11+06.45	28.62' LT	1	
11+68.95	24.29' RT	1	
11+73.23	24.34' RT	1	
12+06.17	26.77' RT	1	
14+14.98	26.33' LT	1	
14+55.53	26.89' LT	1	
14+58.69	26.94' LT	1	
17+61.37	21.46' LT	1	
17+67.63	21.97' LT	1	
19+03.63	26.00' RT	1	
19+07.33	26.18' RT	1	
20+98.36	26.73' LT	1	
21+01.28	20.49' RT	1	
21+01.18	26.7' LT	1	
21+04.15	26.7' LT	1	
21+07.01	26.7' LT	1	
21+09.66	26.7' LT	1	
21+12.33	26.6' LT	1	
30+72.42	27.87' RT	1	
30+98.20	28.25' RT	1	
39+18.13	32.44' LT	1	
39+53.31	30.13' LT	1	
40+22.92	30.43' RT	1	
40+79.32	30.13' RT	1	
42+16.16	28.67' RT	1	
PROJECT TOTAL 25			

BOLLARD REMOVAL (X0350810)			
STATION	OFFSET (FT)	QUANTITY (EACH)	
LAKE STREE	ĒΤ		
12+36.28	18.5' LT	1	
12+62.20	18.3' LT	1	
14+89.20	27.86' LT	1	
14+92.13	27.79' LT	1	
14+95.55	27.87' LT	1	
15+61.75	26.52' RT	1	
15+65.93	26.31' RT	1	
15+74.25	26.43' RT	1	
15+77.46	26.44' RT	1	
15+98.27	25.70' RT	1	
16+10.72	25.70' RT	1	
19+61.77	17.87' LT	1	
19+62.17	17.73' RT	1	
19+75.60	17.62' RT	1	
19+75.82	17.86' LT	1	
19+82.62	15.61' LT	1	
19+92.73	15.59' LT	1	
20+03.03	15.64' LT	1	
21+20.67	20.3' RT	1	
21+38.92	40.67' RT	1	
PROJEC	20		

INC	(X0327552)	, , AL
STATION	OFFSET (FT)	QUANTITY (EACH)
LAKE STRE	ET	
10+67.56	22.87' LT	1
11+07.45	22.36' LT	1
11+43.73	22.16' RT	1
11+44.23	22.82' LT	1
11+81.19	27.78' LT	1
11+81.36	26.40' RT	1
12+18.47	26.98' LT	1
12+18.65	26.28' RT	1
12+93.86	26.98' LT	1
13+36.59	24.98' LT	1
13+69.41	25.70' LT	1
14+06.41	26.39' LT	1
14+80.42	28.28' LT	1
14+80.66	26.05' RT	1
15+21.08	25.41' RT	1
15+51.01	26.19' RT	1
15+52.14	28.14' LT	1
15+83.38	26.87' LT	1
17+58.31	26.83' LT	1
17+89.53	27.56' LT	1
18+25.64	27.38' LT	1
18+62.66	27.63' LT	1
18+70.54	26.35' RT	1
18+97.79	27.53' LT	1
18+97.86	25.08' RT	1
19+33.18	26.38' LT	1
19+33.84	25.44' RT	1
20+26.74	25.50' RT	1
20+61.89	25.28' RT	1
20+72.54	26.04' LT	1
20+94.47	26.47' RT	1
21+26.33	26.35' LT	1
39+45.61	30.76' LT	1
39+48.27	30.84' RT	1
40+33.22	31.18' LT	1
40+51.35	30.50' RT	1
40+63.21	30.11' LT	1
40+91.89	31.09' RT	1
42+09.79	28.67' RT	1
42+40.64	28.28' RT	1
42+70.31	28.26' RT	1
	1	

CATCH BASINS TO BE ADJUSTED WITH					
NEW TY	NEW TYPE 1 FRAME, OPEN LID				
	(60250400)				
STATION	OFFSET	QUANTITY			
SIATION	(FT)	(EACH)			
LAKE STREE	T				
12+41	12.2 RT	1			
15+53	24.4 LT	1			
18+14	24.1 RT	1			
19+50	16.5 LT	1			
30+34	36.5 LT	1			
30+70	41.7 LT	1			
31+33	41.0 RT	1			
31+69	40.7 RT	1			
37+34	25.4 RT	1			
38+12	23.6 LT	1			
38+14	24.7 RT	1			
38+89	47.2 LT	1			
40+16	24.6 RT	1			
41+02	24.0 LT	1			
41+18	24.0 RT	1			
43+53	47.1 RT	1			
43+86	43.3 RT	1			
PROJEC	17				

42+98.79 28.04' RT PROJECT TOTAL

	(20100110) OFFSET	QUANTITY
STATION	(FT)	(UNIT)
LAKE STREE		, , , , , , ,
10+67.56	22.87' LT	8
11+07.45	22.36' LT	8
11+43.73	22.16' RT	8
11+44.23	22.82' LT	8
11+81.19	27.78' LT	9
11+81.36	26.40' RT	10
12+18.47	26.98' LT	8
12+18.65	26.28' RT	12
12+93.86	26.98' LT	14
13+36.59	24.98' LT	6
13+69.41	25.70' LT	6
14+06.41	26.39' LT	6
14+80.66	26.05' RT	10
15+21.08	25.41' RT	10
15+51.01	26.19' RT	11
15+52.14	28.14' LT	12
15+83.38	26.87' LT	10
17+58.31	26.83' LT	12
17+89.53	27.56' LT	10
18+25.64	27.38' LT	12
18+62.66	27.63' LT	8
18+70.54	26.35' RT	9
18+97.79	27.53' LT	10
18+97.86	25.08' RT	10
19+33.18	26.38' LT	-
19+33.84	25.44' RT	11
20+26.74	25.50' RT	12
20+61.89	25.28' RT	13
20+72.54	26.04' LT	13
20+94.47	26.47' RT	12
21+26.33	26.35' LT	7
21+38.27	88.10' RT	9
23+30.05	29.60' RT	12
39+45.61	30.76' LT	13
39+48.27	30.84' RT	13
40+33.22	31.18' LT	-
40+51.35	30.50' RT	10
40+63.21	30.11' LT	15
40+91.89	31.09' RT	9
42+40.64	28.28' RT	6
42+70.31	28.26' RT	7
42+98.79	28.04' RT T TOTAL	6 <b>395</b>

42+70.31         28.26' RT         7           42+98.79         28.04' RT         6           PROJECT TOTAL         395           DRAINAGE STRUCTURE TO BE REMOVED (Z0018700)           STATION         OFFSET (FT)         QUANTITY (EACH)           LAKE STREET           11+96         15.8 LT         1           14+09         22.6 LT         1           15+71         23.2 RT         1           17+57         16.1 LT         1           19+35         21.2 RT         1           20+62         12.2 RT         1           22+46         29.7 RT         1           22+46         25.2 RT         1           30+91         24.6 RT         1           PROJECT TOTAL         9			
PROJECT TOTAL         395           DRAINAGE STRUCTURE TO BE REMOVED (Z0018700)           STATION         OFFSET (FT)         QUANTITY (EACH)           LAKE STREET         11-96         15.8 LT         1           14+09         22.6 LT         1         1           15+71         23.2 RT         1         1           17+57         16.1 LT         1         1           19+35         21.2 RT         1         1           20+62         12.2 RT         1         1           22+46         29.7 RT         1         1           22+46         25.2 RT         1         30+91         24.6 RT         1	42+70.31	28.26' RT	7
DRAINAGE STRUCTURE TO BE REMOVED (Z0018700)  STATION OFFSET (FT) QUANTITY (EACH)  LAKE STREET  11+96 15.8 LT 1 14+09 22.6 LT 1 15+71 23.2 RT 1 17+57 16.1 LT 1 19+35 21.2 RT 1 20+62 12.2 RT 1 22+46 29.7 RT 1 22+46 25.2 RT 1 30+91 24.6 RT 1	42+98.79	28.04' RT	6
(Z0018700)           STATION         OFFSET (FT)         QUANTITY (EACH)           LAKE STREET           11+96         15.8 LT         1           14+09         22.6 LT         1           15+71         23.2 RT         1           17+57         16.1 LT         1           19+35         21.2 RT         1           20+62         12.2 RT         1           22+46         29.7 RT         1           22+46         25.2 RT         1           30+91         24.6 RT         1	PROJEC	T TOTAL	395
(Z0018700)           STATION         OFFSET (FT)         QUANTITY (EACH)           LAKE STREET           11+96         15.8 LT         1           14+09         22.6 LT         1           15+71         23.2 RT         1           17+57         16.1 LT         1           19+35         21.2 RT         1           20+62         12.2 RT         1           22+46         29.7 RT         1           22+46         25.2 RT         1           30+91         24.6 RT         1			
(Z0018700)           STATION         OFFSET (FT)         QUANTITY (EACH)           LAKE STREET           11+96         15.8 LT         1           14+09         22.6 LT         1           15+71         23.2 RT         1           17+57         16.1 LT         1           19+35         21.2 RT         1           20+62         12.2 RT         1           22+46         29.7 RT         1           22+46         25.2 RT         1           30+91         24.6 RT         1	DRAINAGE ST	RUCTURE TO	BE REMOVED
STATION         OFFSET (FT)         (EACH)           LAKE STREET         11+96         15.8 LT         1           14+09         22.6 LT         1           15+71         23.2 RT         1           17+57         16.1 LT         1           19+35         21.2 RT         1           20+62         12.2 RT         1           22+46         29.7 RT         1           22+46         25.2 RT         1           30+91         24.6 RT         1	5.0		52 NE.110 V EB
11+96 15.8 LT 1 14+09 22.6 LT 1 15+71 23.2 RT 1 17+57 16.1 LT 1 19+35 21.2 RT 1 20+62 12.2 RT 1 22+46 29.7 RT 1 22+46 25.2 RT 1 30+91 24.6 RT 1	STATION	OFFSET (FT)	
14+09 22.6 LT 1 15+71 23.2 RT 1 17+57 16.1 LT 1 19+35 21.2 RT 1 20+62 12.2 RT 1 22+46 29.7 RT 1 22+46 25.2 RT 1 30+91 24.6 RT 1	LAKE STREE	Т	
15+71 23.2 RT 1 17+57 16.1 LT 1 19+35 21.2 RT 1 20+62 12.2 RT 1 22+46 29.7 RT 1 22+46 25.2 RT 1 30+91 24.6 RT 1	11+96	15.8 LT	1
17+57 16.1 LT 1 19+35 21.2 RT 1 20+62 12.2 RT 1 22+46 29.7 RT 1 22+46 25.2 RT 1 30+91 24.6 RT 1	14+09	22.6 LT	1
19+35 21.2 RT 1 20+62 12.2 RT 1 22+46 29.7 RT 1 22+46 25.2 RT 1 30+91 24.6 RT 1	15+71	23.2 RT	1
20+62 12.2 RT 1 22+46 29.7 RT 1 22+46 25.2 RT 1 30+91 24.6 RT 1	17+57	16.1 LT	1
22+46 29.7 RT 1 22+46 25.2 RT 1 30+91 24.6 RT 1	19+35	21.2 RT	1
22+46 25.2 RT 1 30+91 24.6 RT 1	20+62	12.2 RT	1
30+91 24.6 RT 1	22+46	29.7 RT	1
24.01(1	22+46	25.2 RT	1
PROJECT TOTAL 9	30+91	24.6 RT	1
	PROJEC	T TOTAL	9

	METER POST	
STATION	OFFSET (FT)	QUANTITY (EACH)
LAKE STREE	ΕT	
13+49.28	24.14' LT	1
13+52.20	23.70' RT	1
13+92.30	23.70' RT	1
13+90.83	24.23' LT	1
14+34.68	24.89' LT	1
14+54.14	23.15' LT	1
14+77.16	26.49' LT	1
14+99.84	24.8' RT	1
15+47.04 17+94.00	26.11' RT	1
	27.39' LT	
18+34.61	26.68' LT 24.92' LT	1
18+76.94 19+15.15	24.92 LT 24.29' RT	1
19+15.15	24.29 KT 24.44' LT	1
20+79.23	22.56' LT	1
24+53.87	26.33' RT	1
24+53.67	26.53 RT 26.59' RT	1
25+42.09	26.46' RT	1
26+16.20	28.07' RT	1
27+08.78	27.98' RT	1
27+14.84	27.90' LT	1
27+30.30	28.02' RT	1
27+54.66	27.89' LT	1
27+70.38	27.87' RT	1
27+98.61	27.97' LT	1
28+49.62	28.17' RT	1
29+31.32	27.66' RT	1
29+63.43	27.92' RT	1
29+74.10	27.80' LT	1
32+03.21	27.10' LT	1
32+29.25	28.86' RT	1
32+43.02	26.87' LT	1
32+73.87	27.11' RT	1
33+16.34	24.80' LT	1
33+60.99	23.33' LT	1
35+41.55	25.48' LT	1
35+77.10	29.27' RT	1
35+85.67	25.91' LT	1
36+21.58	30.09' RT	1
36+29.75	26.14' LT	1
36+65.46	29.63' RT	1
36+73.92	26.60' LT	1
37+09.25	29.33' RT	1
37+17.85	26.78' LT	1
39+55.26	27.27' RT	1
39+76.42	27.03' RT	1
39+92.18	27.06' LT	1
40+19.21 40+31.79	27.46' RT 27.34' LT	1
40+31.79 40+63.40	27.54 LT 27.61' RT	1
40+75.98	27.01 KT	1
41+07.43	27.44' RT	1
41+40.47	27.44 KT	1
41+79.78	25.67' LT	1
41+89.43	27.04' RT	1
42+02.83	27.19' LT	1
42+33.53	26.98' RT	1
42+45.86	27.40' RT	1
42+77.24	27.45' RT	1
42+93.23	27.50' LT	1
PROJEC	T TOTAL	60

th@mas
e <u>ngineering grou</u> p
service at the highest grade.

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

	F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
SCHEDULE OF QUANTITIES	1405	16-00264-00-PV	COOK	344	27
			CONTRACT	NO. 6	1F36
SCALE: NTS   SHEET 2 OF 7 SHEETS STA. TO STA.		ILLINOIS FED. AI	D PROJECT		

				PROPOSED	SIDEWALK			
STATION	STATION	LOCATION	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH (SQ FT) (42000200)	PORTLAND CEMENT CONCRETE SIDEWALK 8 INCH (SQ FT) (42000410)	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH, SPECIAL (SQ FT) (X4240430)	PORTLAND CEMENT CONCRETE SIDEWALK 8 INCH, SPECIAL (SQ FT) (X4240460)	PAVER BLOCKS, SPECIAL (BLUESTONE PAVERS) (SQ FT) (XX007217)	SUBBASE GRANULAR MATERIAL, TYPE B 4" (SQ YD) (31101200)
HARLEM A	VENUE TO	MAPLE AVE	NUE				, ,	
10+27.95	12+60.30	RT	5,491.0					610.1
10+28.41	12+96.58	LT	4,790.9					532.3
MAPLE AV	ENUE TO M	ARION STRI	ET				•	•
13+10.66	16+40.41	LT					4803.0	533.7
14+31.52	16+55.43	RT					3241.0	360.1
15+14.62	15+30.53	LT				34.7		3.9
15+32.91	15+51.34	LT				42.7		4.7
16+15.16	16+31.51	LT				82.5		9.2
16+30.72	16+40.44	LT			97.6			10.8
MARION S	TREET TO F	OREST AVE	NUE					
16+75.40	21+40.05	LT					8769.0	974.3
16+75.61	16+85.34	LT			96.7			10.7
17+82.02	19+94.52	RT					2948.0	327.6
20+08.06	21+41.37	RT					1857.7	206.4
21+36.35	21+41.37	RT	631.0					70.1
FOREST A	VENUE TO I	KENILWORT	H AVENUE					
21+82.24	23+86.88	RT	1,986.3					220.7
23+87.38	24+10.40	RT		101.5				11.3
24+10.90	25+69.22	RT	1,341.3					149.0
25+69.70	25+90.25	RT		89.2				9.9
25+90.73	26+60.15	RT	496.3					55.1
26+28.05	26+47.83	LT		74.6				8.3
26+48.28	26+73.29	LT	330.0					36.7
26+60.65	26+77.19	RT		68.4				7.6
26+73.68	26+88.51	LT		59.1				6.6
26+77.67	27+96.86	RT	856.4					95.2
26+89.01	28+30.27	LT	996.8					110.8
27+97.34	28+19.06	RT		92.4				10.3
28+19.54	28+82.06	RT	450.0					50.0
28+30.77	28+46.81	LT		64.1				7.1
28+47.31	28+73.97	LT	193.0					21.4
28+74.47	28+88.06	LT		54.2				6.0
28+82.56	29+04.86	RT		92.1				10.2
28+88.53	30+31.44	LT	1,181.0					131.2
29+05.34	31+31.42	RT	2,150.0					238.9

				PROPOSED	SIDEWALK			
STATION	STATION	LOCATION	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH (SQ FT) (42000200)	PORTLAND CEMENT CONCRETE SIDEWALK 8 INCH (SQ FT) (42000410)	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH, SPECIAL (SQ FT) (X4240430)	PORTLAND CEMENT CONCRETE SIDEWALK 8 INCH, SPECIAL (SQ FT) (X4240460)	PAVER BLOCKS, SPECIAL (BLUESTONE PAVERS) (SQ FT) (XX007217)	SUBBASE GRANULAR MATERIAL, TYPE B 4" (SQ YD) (31101200)
KENILWO	RTH AVENU	E TO OAK PA	ARK AVENUE					
30+71.57	32+05.04	LT	1,427.5					158.6
31+70.71	31+97.64	RT	274.6					30.5
32+22.71	32+34.77	RT			86.5			9.6
32+37.03	32+47.08	LT			69.7			7.7
32+70.25	32+76.25	RT			42.4			4.7
32+89.61	33+01.63	LT			89.2			9.9
32+91.47	33+04.10	RT			91.4			10.2
33+13.28	33+18.28	LT			41.4			4.6
33+58.69	33+76.68	LT			171.9			19.1
33+69.21	33+82.78	RT			98.1			10.9
34+11.88	34+27.83	RT			121.4			13.5
34+55.10	34+67.10	RT			116.8			13.0
34+55.73	34+80.73	LT			262.6			29.2
34+88.46	35+05.68	RT			151.4			16.8
34+89.63	35+02.62	LT			131.8			14.6
35+35.13	35+55.06	RT			208.3			23.1
35+38.16	35+56.03	LT			195.7			21.7
35+73.57	35+85.57	RT			130.3			14.5
35+83.15	35+89.15	LT			67.1			7.5
36+20.06	36+90.75	RT			822.2			91.4
36+27.84	36+63.84	LT			419.0			46.6
36+72.05	36+76.05	LT			47.7			5.3
36+90.31	38+45.62	RT					1926.7	214.1
37+10.58	37+22.58	LT			147.2			16.4
37+30.15	37+36.15	LT			74.3			8.3
37+62.68	37+68.68	LT			75.7			8.4
38+00.00	38+37.90	LT					718.5	79.8
38+33.07	38+37.84	LT			31.6			3.5
38+41.80	38+45.56	RT			40.9			4.5
		O EUCLID A	VENUE	I				7.0
38+90.49	39+00.09	LT			68.3		077.4.0	7.6
38+91.04	41+06.19	LT			4:0		2774.6	308.3
38+96.91	39+00.63	RT			44.9		0057.0	5.0
38+96.91	43+51.00	RT					6657.2	739.7
41+26.32	42+18.18	LT					1317.3	146.4
43+26.59	43+39.94	LT			0.15		115.7	12.9
43+40.18	43+50.99	RT			94.5			10.5
43+80.16	44+09.00	LT			281.6			31.3
43+88.65	44+10.04	RT			185.0	400	95.55	20.6
PF	OJECT TOT	AL	22,597	696	4,604	160	35,129	7,021

SCALE: NTS

DETECTABI	LE WARNINGS (X4240800)	(SPECIAL)
STATION	OFFSET (FOOT)	AREA (SQ FT)
HARLEM AV	E TO MAPLE A	
10+28.42	39.0' LT	13.6
10+31.31	28.1' LT	14.8
10+30.82	49.5' RT	36.9
12+48.50	13.6' LT	16.0
12+48.04	15.0' RT	16.0
12+60.07	30.3' RT	16.0
MAPLE AVE	TO FOREST A	VE
16+31.00	17.1' RT	16.0
16+30.56	22.5' LT	32.7
16+75.76	36.4' LT	13.5
17+21.00	17.1' LT	16.0
19+67.50	12.6' LT	20.0
19+67.50	12.6' RT	20.0
20+49.50	25.1' RT	10.0
21+28.50	23.2 RT	30.1
21+28.39	13.5' LT	10.0
21+91.08	42.3' RT	25.0
23+73.50	25.8' RT	10.0
FOREST AVI	E TO OAK PAR	K AVE
26+60.14	28.7' RT	8.2
26+77.69	28.7' RT	8.3
30+05.25	17.6' RT	11.0
30+05.50	25.6' LT	10.0
30+25.28	29.2' LT	16.6
30+73.60	28.5' LT	10.0
31+26.66	28.3' RT	16.1
31+70.71	34.7' RT	33.7
31+79.50	17.6' LT	10.0
34+68.73	22.5' LT	12.0
	VE TO EUCLI	
38+30.11	27.6' LT	26.2
38+30.91	26.1' RT	29.1
38+92.04	42.0' LT	33.7
38+99.11	34.8' RT	24.5
43+31.10	21.9' LT	10.0
43+31.50	21.2' RT	10.0
43+49.51	33.8' RT	10.0
43+80.16	38.9' LT	11.1
43+91.78	33.8' RT	11.8
43+93.68	26.0' LT	14.6
43+98.34	28.2' RT	13.2
PROJEC	T TOTAL	647

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

							F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	SC	HEDU	JLE	OF QUA	ANTITIES	i	1405	16-00264-00-PV	COOK	344	28
									CONTRACT	NO. 6	1F36
SHEET	3	OF	7	SHEETS	STA.	TO STA.		ILLINOIS FED. A	ID PROJECT		

STATION	OFFSET (FT)	STATION	OFFSET (FT)	COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12 (MODIFIED) (FT) (60604100)
HARLEM A	VENUE TO	MAPLE AVE	NUE	
10+27.58	64.5' RT	10+74.58	18.0' RT	73.3
10+27.82	53.6' LT	10+27.83	38.0' LT	15.7
10+27.83	38.0' LT	10+46.83	19.0' LT	29.8
10+46.83	19.0' LT	11+34.67	19.0' LT	87.8
10+74.58	18.0' RT	11+85.04	18.0' RT	110.5
11+34.67	19.0' LT	11+44.67	26.5' LT	12.5
11+38.78	19.6' LT	11+71.22	19.6' LT	32.4
11+44.67	26.5' LT	11+65.33	26.5' LT	20.7
11+65.33	26.5' LT	11+75.33	19.0' LT	12.5
11+75.33	19.0' LT	11+85.05	19.0' LT	9.7
11+85.04	18.0' RT	12+40.19	13.4' RT	55.3
11+85.05	19.0' LT	12+45.05	13.0' LT	60.3
12+40.19	13.4' RT	12+60.77	32.4' RT	31.5
12+45.05	13.4 KT	12+64.85	13.0' LT	19.8
12+45.05		12+60.88		5.5
	38.3' RT		43.8' RT	
12+60.77	32.4' RT	12+60.74	38.3' RT	5.9
12+64.85	13.0' LT	12+89.85	20.5' LT	26.1
12+89.85	20.5' LT	12+93.17	20.5' LT	3.3
		ARION STRI		
16+40.99	71.1' LT	16+41.05	81.1' LT	10.0
		OREST AVE		
16+75.05	80.9' LT	16+74.99'	70.9' LT	9.9
21+41.96	52.1' RT	21+41.91	70.0' RT	17.9
		KENILWORT		
21+81.51	67.8' RT	21+87.63	46.0' RT	23.0
21+81.56	70.0' RT	21+81.51	67.8' RT	2.2
23+83.50	25.2' RT	24+16.16	25.2' RT	32.7
25+65.22	23.9' RT	25+94.74	23.9' RT	29.5
26+25.90	25.1' LT	26+92.73	25.3' LT	66.8
26+47.84	39.8' LT	26+55.53	25.1' LT	18.3
26+56.15	25.0' RT	26+81.67	25.0' RT	25.5
27+75.00	25.0' RT	29+80.19	25.0' RT	205.2
27+75.00	25.4' LT	28+00.01	25.0' LT	25.0
28+00.01	25.0' LT	30+12.85	25.0' LT	212.8
29+80.19	25.0' RT	30+00.19	17.0' RT	21.5
30+00.19	17.0' RT	30+34.91	17.0' RT	34.7
30+12.78	25.0' LT	30+36.78	49.1' LT	38.0
30+34.91	17.0' RT	30+74.91	24.5' RT	40.7
30+36.78	49.1' LT	30+36.79	54.1' LT	5.0
30+74.91	24.5' RT	31+18.00	24.5' RT	43.1
21+10 00	24.5' RT	31+32.00	38.5' RT	22.0
J1718.00				
31+18.00	38.5' RT	31+32.00	I 50.0'RT	11.5
31+32.00	38.5' RT	31+32.00 E TO OAK PA		11.5
31+32.00 KENILWO	RTH AVENU	TO OAK P	ARK AVENU	E
31+32.00 <b>KENILW O</b> 30+70.57	54.0' LT	30+70.98	33.9' LT	20.1
31+32.00 <b>KENILW O</b> 30+70.57 30+70.98	54.0' LT 33.9' LT	30+70.98 30+79.98	33.9' LT 25.0' LT	20.1 14.0
31+32.00 <b>KENILWO</b> 30+70.57 30+70.98 30+79.98	54.0' LT 33.9' LT 25.0' LT	30+70.98 30+79.98 31+20.25	33.9' LT 25.0' LT 25.0' LT	20.1 14.0 40.3
31+32.00 <b>KENILWO</b> 30+70.57 30+70.98 30+79.98 31+20.25	54.0' LT 33.9' LT 25.0' LT 25.0' LT	30+70.98 30+79.98 30+79.98 31+20.25 31+35.25	33.9' LT 25.0' LT 25.0' LT 17.0' LT	20.1 14.0 40.3 17.0
31+32.00 <b>KENILWO</b> 30+70.57 30+70.98 30+79.98 31+20.25 31+35.25	54.0' LT 33.9' LT 25.0' LT 25.0' LT 17.0' LT	30+70.98 30+79.98 30+79.98 31+20.25 31+35.25 31+89.76	33.9' LT 25.0' LT 25.0' LT 25.0' LT 17.0' LT	20.1 14.0 40.3 17.0 54.5
31+32.00 <b>KENILWO</b> 30+70.57 30+70.98 30+79.98 31+20.25 31+35.25 31+69.24	54.0' LT 33.9' LT 25.0' LT 25.0' LT 17.0' LT 50.0' RT	30+70.98 30+79.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT	20.1 14.0 40.3 17.0 54.5 10.5
31+32.00 <b>KENILWO</b> 30+70.57 30+70.98 30+79.98 31+20.25 31+35.25 31+69.24 31+69.24	754.0' LT 33.9' LT 25.0' LT 25.0' LT 25.0' LT 17.0' LT 50.0' RT 39.5' RT	30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT	20.1 14.0 40.3 17.0 54.5 10.5 22.0
31+32.00 <b>KENILWO</b> 30+70.57 30+70.98 30+79.98 31+20.25 31+35.25 31+69.24 31+69.24 31+83.24	754.0' LT 33.9' LT 25.0' LT 25.0' LT 17.0' LT 50.0' RT 39.5' RT 25.5' RT	30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+97.64	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT	20.1 14.0 40.3 17.0 54.5 10.5 22.0
31+32.00 <b>KENILWO</b> 30+70.57 30+70.98 30+79.98 31+20.25 31+35.25 31+69.24 31+69.24 31+83.24 31+89.76	754.0' LT 33.9' LT 25.0' LT 25.0' LT 17.0' LT 50.0' RT 39.5' RT 25.5' RT 17.0' LT	30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+97.64 32+05.01	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4
31+32.00 KENILW O 30+70.57 30+70.98 30+79.98 31+20.25 31+35.25 31+69.24 31+69.24 31+83.24 31+89.76 34+62.75	754.0' LT 33.9' LT 25.0' LT 25.0' LT 17.0' LT 39.5' RT 25.5' RT 17.0' LT 25.9' LT	30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+97.64 32+05.01 34+80.74	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT 22.0' LT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0
31+32.00 <b>KENILWO</b> 30+70.57 30+70.98 30+79.98 31+20.25 31+35.25 31+69.24 31+69.24 31+83.24 31+89.76 34+62.75 34+88.46	754.0' LT 33.9' LT 25.0' LT 25.0' LT 17.0' LT 39.5' RT 25.5' RT 17.0' LT 20.9' LT 28.4' RT	30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+97.64 32+05.01 34+80.74 35+01.42	33.9' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT 28.3' RT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0
31+32.00 <b>KENILWO</b> 30+70.57 30+70.98 30+79.98 31+20.25 31+69.24 31+69.24 31+89.76 34+62.75 34+88.46 36+80.87	74.0 P. C.	30+70.98 30+79.98 31+20.25 31+35.25 31+35.25 31+69.24 31+83.24 31+97.64 32+05.01 34+80.74 35+01.42 36+90.74	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 17.0' LT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 26.8' RT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9
31+32.00 <b>KENILWO</b> 30+70.57 30+70.98 30+79.98 31+20.25 31+69.24 31+69.24 31+89.76 34+62.75 34+88.46 36+80.87 38+38.60	75.8' LT 25.8' LT 25.9' LT 25.0' LT 25.0' LT 17.0' LT 25.0' RT 39.5' RT 17.0' LT 25.9' LT 26.8' RT 75.8' LT	TO OAK PA 30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+97.64 32+05.01 34+80.74 35+01.42 36+90.74 38+38.28	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 82.3' LT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9 6.5
31+32.00 <b>KENILWO</b> 30+70.57 30+70.98 30+79.98 31+20.25 31+69.24 31+69.24 31+89.76 34+62.75 34+88.46 36+80.87 38+38.60 38+46.14	75.8' LT 29.4' RT 25.8' LT 25.9' LT 25.0' LT 25.0' LT 25.0' RT 39.5' RT 25.5' RT 17.0' LT 20.9' LT 28.4' RT 26.8' RT 39.4' RT	TO OAK PA 30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+97.64 32+05.01 34+80.74 35+01.42 36+90.74 38+38.28 38+46.79	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 26.8' RT 82.3' LT 50.1' RT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9
31+32.00  KENILWO 30+70.57 30+70.98 30+79.98 31+20.25 31+69.24 31+69.24 31+89.76 34+62.75 34+88.46 36+80.87 38+38.60 38+46.14 OAK PARK	75.8' LT 26.8' RT 275.8' LT 275.8' LT 275.9' LT	30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+97.64 32+05.01 34+80.74 35+01.42 36+90.74 38+38.28 38+46.79 O EUCLID A	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 82.3' LT 50.1' RT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 9.9 6.5
31+32.00  KENILWO 30+70.57 30+70.98 30+79.98 31+20.25 31+69.24 31+69.24 31+89.24 31+89.76 344+62.75 344+88.46 36+80.87 38+38.60 38+46.14  OAK PARK 38+89.91	75.8' LT  25.0' LT  25.0' LT  25.0' LT  25.0' LT  25.0' RT  39.5' RT  25.5' RT  17.0' LT  20.9' LT  28.4' RT  26.8' RT  75.8' LT  39.4' RT	TO OAK PA 30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+97.64 32+05.01 34+80.74 35+01.42 36+90.74 38+38.28 38+46.79 O EUCLID AV	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 26.8' RT 82.3' LT 50.1' RT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9 6.5 10.7
31+32.00  KENILWO 30+70.57 30+70.98 30+79.98 31+20.25 31+69.24 31+69.24 31+83.24 31+89.76 34+62.75 34+88.46 36+80.87 38+36.00 38+46.14  OAK PARK 38+89.91 38+97.01	8TH AVENUI 54.0' LT 33.9' LT 25.0' LT 17.0' LT 50.0' RT 39.5' RT 25.5' RT 17.0' LT 20.9' LT 28.4' RT 26.8' RT 75.8' LT 39.4' RT 4 AVENUE T 55.4' LT 54.9' RT	TO OAK PA 30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+87.64 32+05.01 34+80.74 35+01.42 36+90.74 38+38.28 38+46.79 O EUCLID AV	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 82.3' LT 50.1' RT 47.9' LT 43.0' RT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9 6.5 10.7
31+32.00  KENILWO 30+70.57 30+70.98 30+79.98 31+20.25 31+69.24 31+69.24 31+83.24 31+83.24 31+83.60 38+46.275 344+88.46 36+80.87 38+38.60 38+46.14  OAK PARI 38+89.91 38+97.01 43+51.58	8TH AVENUI 54.0' LT 33.9' LT 25.0' LT 17.0' LT 50.0' RT 39.5' RT 17.0' LT 20.9' LT 17.0' LT 26.8' RT 17.6' LT 26.8' RT 39.4' RT 40.8' RT 55.4' LT 54.9' RT 38.7' RT	30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+87.64 32+05.01 34+80.74 35+01.42 36+90.74 38+38.28 38+46.79 0 EUCLID A 38+90.46 38+96.32 43+52.49	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 26.8' RT 82.3' LT 50.1' RT 47.9' LT 43.0' RT 50.0' RT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9 6.5 10.7
31+32.00  KENILWO 30+70.57 30+70.98 30+79.98 31+20.25 31+69.24 31+69.24 31+83.24 31+89.76 34+62.75 34+88.46 36+80.87 38+36.60 38+46.14  OAK PARI 38+89.91 38+97.01 43+51.58 43+78.65	8TH AVENUI 54.0' LT 33.9' LT 25.0' LT 17.0' LT 50.0' RT 39.5' RT 17.0' LT 28.4' RT 26.8' RT 75.8' LT 39.4' RT 4 AVENUE T 54.9' RT 38.7' RT 50.1' LT	30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+97.64 32+05.01 34+80.74 35+01.42 36+90.74 38+38.28 38+46.79 O EUCLID AV 38+90.46 38+96.32 43+79.28	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 26.8' RT 82.3' LT 50.1' RT 47.9' LT 43.0' RT 50.0' RT 41.0' LT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9 6.5 10.7  7.5 12.0 11.3 9.1
31+32.00  KENILWO 30+70.57 30+70.98 31+20.25 31+35.25 31+69.24 31+89.76 34+62.75 34+88.46 36+80.87 38+36.01 38+46.14  OAK PARI 38+97.01 43+51.58 43+78.65	8TH AVENUI 54.0' LT 33.9' LT 25.0' LT 17.0' LT 50.0' RT 39.5' RT 17.0' LT 20.9' LT 29.4' RT 26.8' RT 75.8' LT 39.4' RT 40.8' RT 55.4' LT 54.9' RT 38.7' RT 50.1' LT 41.0' LT	30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+97.64 32+05.01 34+80.74 35+01.42 36+90.74 38+38.28 38+46.79 O EUCLID A\( 38+90.46 38+90.46 38+96.32 43+79.28 43+96.31	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT 28.3' RT 26.8' RT 82.3' LT 50.1' RT 47.9' LT 43.0' RT 50.0' RT 41.0' LT 25.2' LT	E 20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9 6.5 10.7 7.5 12.0 11.3 9.1 25.6
31+32.00  KENILWO 30+70.57 30+70.98 31+20.25 31+35.25 31+35.24 31+69.24 31+89.76 34+62.75 34+88.46 36+80.87 38+36.01 38+46.14 OAK PARN 38+97.01 43+51.58 43+78.65 43+79.28	75.8 LT 25.9 LT 25.0 RT 39.5 RT 25.5 RT 17.0 LT 28.4 RT 26.8 RT 75.8 LT 39.4 RT 40.4 RT 38.7 RT 54.9 RT 38.7 RT 50.1 LT 41.0 LT	TO OAK PA 30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+97.64 32+05.01 34+80.74 36+90.74 38+38.28 38+46.79 O EUCLID A 38+90.46 38+96.32 43+79.28 43+96.31 43+87.07	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 26.8' RT 82.3' LT 50.1' RT 47.9' LT 43.0' RT 41.0' LT 25.2' LT 47.4' RT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9 6.5 10.7  7.5 12.0 11.3 9.1 25.6 2.5
31+32.00  KENILWO 30+70.57 30+70.98 31+20.25 31+35.25 31+35.24 31+89.76 34+62.75 34+88.46 36+80.87 38+36.00 38+461.40  OAK PARN 38+97.01 43+51.58 43+79.28 43+86.87 43+86.87	74.0° LT  75.0° LT  75.0° LT  75.0° LT  75.0° LT  75.0° LT  75.0° LT  75.5° RT  75.8° LT  75.8° LT	TO OAK PA 30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+87.04 32+05.01 34+80.74 35+01.42 36+90.74 38+38.28 38+46.79 O EUCLID AV 38+90.46 38+96.32 43+52.49 43+79.28 43+96.31 43+87.07 44+08.03	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 17.0' LT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 26.8' RT 82.3' LT 50.1' RT 47.9' LT 43.0' RT 50.0' RT 41.0' LT 25.2' LT 47.4' RT 25.2' LT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9 6.5 10.7  7.5 12.0 11.3 9.1 25.6 2.5 34.2
31+32.00  KENILWO 30+70.57 30+70.98 30+79.98 31+20.25 31+35.25 31+69.24 31+89.76 34+62.75 34+88.46 36+80.87 38+38.60 38+46.14 OAK PARI 38+89.91 38+97.01 43+51.58 43+79.28 43+86.87 43+86.87 43+86.87 43+87.07 43+96.31	74.4 RT AVENUE  754.0' LT  754.0' LT  755.0' LT  750.0' RT  755.5' RT  75.8' LT  75.8' LT  75.4' LT  75.4' LT  75.4' RT  75.4' LT  75.4' RT  75.7' RT  75.7' RT  75.7' RT  75.7' RT  75.7' RT	TO OAK PA 30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+87.04 32+05.01 34+80.74 35+01.42 36+90.74 38+38.28 38+46.79 O EUCLID A 38+90.46 38+96.32 43+52.49 43+79.28 43+96.31 43+87.07 44+08.03 44+15.00	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 39.5' RT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 26.8' RT 82.3' LT 50.1' RT 47.9' LT 43.0' RT 41.0' LT 25.2' LT 47.4' RT 25.2' RT 25.2' RT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9 6.5 10.7  7.5 12.0 11.3 9.1 25.6 2.5 34.2
31+32.00  KENILWO 30+70.57 30+70.98 31+20.25 31+35.25 31+35.24 31+89.76 34+62.75 34+88.46 36+80.87 38+36.00 38+461.40  OAK PARN 38+97.01 43+51.58 43+79.28 43+86.87 43+86.87	74.0° LT  75.0° LT  75.0° LT  75.0° LT  75.0° LT  75.0° LT  75.0° LT  75.5° RT  75.8° LT  75.8° LT	TO OAK PA 30+70.98 30+79.98 31+20.25 31+35.25 31+89.76 31+69.24 31+83.24 31+87.04 32+05.01 34+80.74 35+01.42 36+90.74 38+38.28 38+46.79 O EUCLID AV 38+90.46 38+96.32 43+52.49 43+79.28 43+96.31 43+87.07 44+08.03	33.9' LT 25.0' LT 25.0' LT 17.0' LT 17.0' LT 17.0' LT 25.5' RT 25.5' RT 24.4' LT 22.0' LT 28.3' RT 26.8' RT 82.3' LT 50.1' RT 47.9' LT 43.0' RT 50.0' RT 41.0' LT 25.2' LT 47.4' RT 25.2' LT	20.1 14.0 40.3 17.0 54.5 10.5 22.0 14.4 17.0 18.0 13.0 9.9 6.5 10.7  7.5 12.0 11.3 9.1 25.6 2.5 34.2

PROPOSED CONCRETE CURB AND GUTTER

STATION

(FT)

MAPLE AVENUE TO MARION STREET 12+93.17 20.5' LT 12+97.17 24.5' LT 12+97.17 24.5' LT 12+97.17 38.8' LT

12+97.28 21.7' LT 13+15.95 21.9' LT

12+98.17 37.8' LT 13+09.09 37.8' LT

13+10.08 38.8' LT 13+10.12 34.4' LT

13+10.12 34.4' LT 13+24.12 20.5' LT

13+24.12 20.5' LT 14+59.94 20.5' LT 14+31.50 21.4' RT 14+59.97 21.3' RT

14+59.94 20.5' LT 15+03.94 25.5' LT

14+59.97 21.3' RT 15+03.97 24.0' RT

15+03.94 25.5' LT 15+70.25 25.5' LT 15+03.97 24.0' RT 15+70.24 24.0' RT

15+70.24 24.0' RT 15+85.24 16.5' RT

15+70.25 25.5' LT 15+85.25 17.5' LT

15+85.24 16.5' RT 16+55.48 16.5' RT

15+85.25 | 17.5' LT | 16+16.82 | 17.5' LT

16+16.82 17.5' LT 16+40.82 41.4' LT

16+40.82 41.4' LT 16+40.99 71.1' LT

16+98.81 16.5' LT 17+64.76 16.5' LT

17+64.76 16.5' LT 17+79.76 24.0' LT

17+79.76 24.0' LT 18+50.05 24.0' LT

17+82.27 25.0' RT 18+50.05 25.0' RT

18+50.05 25.0' RT 19+00.05 19.5' RT

18+50.05 24.0' LT 19+00.04 19.5' LT

19+00.04 19.5' LT 19+44.24 19.5' LT

19+00.05 19.5' RT 19+44.24 19.5' RT 19+44.24 19.5' RT 19+59.24 12.0' RT

19+44.24 19.5' LT 19+59.24 12.0' LT

19+59.24 12.0' RT 19+81.10 12.0' RT

19+59.24 12.0' LT 19+84.50 12.0' LT

19+60.50 11.0' LT 19+60.50 11.0' RT

19+81.10 12.0' RT 19+95.10 26.0' RT

19+84.50 11.0' LT 19+84.50 11.0' RT

19+84.50 12.0' LT 20+39.76 12.0' LT

19+89.82 12.6' RT 20+12.76 12.6' RT

19+95.10 26.0' RT 19+95.10 41.5' RT

19+96.10 41.5' RT 20+06.48 41.5' RT

20+07.48 41.5' RT 20+07.48 26.2' RT

20+07.48 26.2' RT 20+14.05 14.1' RT

20+14.05 14.1' RT 20+16.36 14.3' RT

20+16.36 14.3' RT 20+29.15 24.5' RT

20+17.45 12.6' RT 20+71.89 12.6' RT

20+29.15 24.5' RT 20+74.80 24.5' RT

20+39.76 | 12.0' LT | 20+54.76 | 19.5' LT

20+45.40 12.6' LT 21+04.60 12.6' LT

20+54.76 19.5' LT 20+95.24 19.5' LT

20+71.89 12.6' RT 20+86.28 14.6' RT

20+74.80 24.5' RT 20+90.03 14.5' RT

20+90.03 14.5' RT 21+16.98 18.3' RT

20+95.24 19.5' LT 21+10.21 12.0' LT

21+10.21 | 12.0' LT | 21+45.06 | 13.8' LT 21+16.98 18.3' RT 21+41.97 47.1' RT

21+41.97 47.1' RT 21+41.96 52.1' RT

MARION STREET TO FOREST AVENUE 16+74.81 40.6' LT 16+98.81 16.5' LT 16+74.99 70.9' LT 16+74.81 40.6' LT

STATION

OFFSET

(FT)

COMBINATION CONCRETE

TYPE B-6.12 (SPECIAL) (FT)

14.3

18.7

10.9

4.4

21.8

28.5

44.3

44.1

66.3

16.8

17.0

70.2

31.6

37.6

29.7

30.3

65.9

16.8

70.3

67.8

50.3

50.2

44.2

16.8

16.8

21.9

25.3

22.0

22.0

22.0

55.3

22.9

15.5

10.4

15.3

14.3

2.5

16.4

54.4

45.6

16.8

59.2

40.5

14.5

18.2

27.2

16.7 34.9

41.6

5.0

	PROPO	SED CONCR	ETE CURB A	AND GUTTER
STATION	OFFSET (FT)	STATION	OFFSET (FT)	COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12 (SPECIAL) (FT) (X6064200)
FOREST A	VENUE TO I	KENILWORT	H AVENUE	•
21+87.63	46.0' RT	22+20.50	28.0' RT	39.1
22+20.50	28.0' RT	23+00.02	28.0' RT	79.5
23+00.02	28.0' RT	23+66.02	25.3' RT	66.1
23+66.02	25.3' RT	23+83.50	25.2' RT	17.5
KENILWO	RTH AVENU	E TO OAK P	ARK AVENU	Ē
36+90.74	26.8' RT	38+31.98	25.5' RT	151.2
38+00.00	24.3' LT	38+21.16	24.6' LT	21.2
38+21.16	24.6' LT	38+40.05	44.6' LT	30.8
38+31.98	25.5' RT	38+46.10	38.6' RT	21.2
38+40.05	44.6' LT	38+38.60	75.8' LT	31.2
38+46.10	38.6' RT	38+46.14	39.4' RT	0.8
OAK PARI	AVENUE T	O EUCLID A	/ENUE	•
38+90.46	47.9' LT	39+11.55	27.0' LT	32.9
38+96.32	43.0' RT	39+15.32	24.5' RT	29.3
39+11.55	27.0' LT	39+65.05	27.0' LT	53.5
39+15.32	24.5' RT	42+96.18	24.5' RT	380.9
39+65.05	27.0' LT	39+90.05	24.5' LT	25.1
39+90.05	24.5' LT	40+98.25	24.5' LT	108.2
40+98.25	24.5' LT	41+06.77	40.0' LT	20.4
41+05.10	25.1' LT	41+28.15	25.1' LT	23.0
41+07.81	39.0' LT	41+24.81	39.0' LT	17.0
41+25.74	40.0' LT	41+35.21	24.5' LT	20.7
41+35.25	24.5' LT	42+18.18	24.5' LT	82.9
42+96.18	24.5' RT	43+11.18	19.0' RT	16.0
43+11.18	19.0' RT	43+27.97	19.0' RT	16.8
43+27.97	19.0' RT	43+51.58	38.7' RT	33.4
	PROJEC	T TOTAL		3,136

	PROPO	SED CONCR	ETE CURB A	AND GUTTER							
STATION	STATION OFFSET (FT)		OFFSET (FT)	CONCRETE CURB, TYPE B (FT) (60600605)							
FOREST AVENUE TO KENILWORTH AVENUE											
23+85.31	25.8' RT	23+86.88	35.1' RT	9.7							
24+10.90	35.1' RT	24+12.61	25.7' RT	9.9							
25+67.71	25.6' RT	25+69.22	32.8' RT	7.7							
25+90.73	32.8' RT	25+92.28	25.5' RT	7.8							
26+58.66	25.7' RT	26+60.15	35.0' RT	9.7							
26+71.46	25.8' LT	26+72.97	39.8' LT	14.7							
26+77.67	32.8' RT	26+79.24	25.7' RT	7.6							
26+88.85	39.8' LT	26+90.73	25.9' LT	14.5							
27+95.33	25.6' RT	27+96.86	32.8' RT	7.7							
28+19.54	32.8' RT	28+21.11	25.6' RT	7.7							
28+28.70	25.6' LT	28+30.27	33.0' LT	7.9							
28+47.31	33.0' LT	28+48.88	25.6' LT	7.9							
28+72.40	25.6' LT	28+73.97	32.9' LT	7.8							
28+80.48	25.6' RT	28+82.06	32.8' RT	7.7							
28+88.53	32.8' LT	28+90.10	25.6' LT	7.7							
29+05.34	32.8' RT	29+06.91	25.6' RT	7.7							
30+16.74	22.1' RT	30+34.72	22.1' RT	48.0							
31+40.48	22.3' LT	31+70.48	22.3' LT	73.0							
	PROJEC	T TOTAL		265							

			PROPOSED DR	IVEWAY ENTRANCES	i	
STATION	STATION	LOCATION	BRICK PAVERS (SQ FT) (X0540000)	PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 8 INCH (SQ YD) (42300400)	PORTLAND CEMENT CONCRETE BASE COURSE 6" (SQ YD) (35300100)	SUBBASE GRANULAR MATERIAL, TYPE B 4" (SQ YD) (31101200)
LAKE STR	EET					
12+97.28	13+15.95	LT	215		23.9	23.9
19+89.27	20+13.31	RT	352		39.1	39.1
23+86.49	24+11.29	RT		12.7		12.7
25+68.80	25+91.09	RT		7.1		7.1
25+69.72	25+90.44	RT		9.0		9.0
26+25.78	26+50.81	LT		11.6		11.6
26+28.80	26+46.85	LT		10.3		10.3
26+59.80	26+78.06	RT		5.7		5.7
26+60.65	26+77.17	RT		4.0		4.0
26+72.79	26+89.47	LT		5.6		5.6
26+73.47	26+88.35	LT		11.1		11.1
27+96.45	28+19.96	RT		7.5		7.5
27+97.34	28+19.04	RT		4.8		4.8
28+29.95	28+47.70	LT		6.3		6.3
28+30.77	28+46.81	LT		10.2		10.2
28+73.62	28+88.91	LT		5.2		5.2
28+74.47	28+88.03	LT		6.0		6.0
28+81.69	29+05.74	RT		8.0		8.0
28+82.56	29+04.84	RT		9.9		9.9
41+04.46	41+28.79	LT	261		29.0	29.0
PF	ROJECT TOT	AL	828	136	92	228

				PRO.	JECT T
	حا	$\sim$		_	-
	n	(I(V))	m		15
•	• •	410	' '		
e n	air	eeri	n a	ard	quo
		at the			

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

									F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
			SC	HEDU	JLE	OF QUA	ANTITIES		1405	16-00264-00-PV	соок	344	29
											CONTRACT	NO. 6	1F36
SCALE:	NTS	SHEET	4	OF	7	SHEETS	STA.	TO STA.		ILLINOIS FED. A	ID PROJECT		

							PAVEMENT PATCH	IING				
STATION	OFFSET	OFFSET	CLASS B, TY I, 9" (SQ YD) (44200948)	CLASS B, TY II, 9" (SQ YD) (44200956)	CLASS B, TY III, 9" (SQ YD) (44200962)	CLASS B, TY IV, 9" (SQ YD) (44200964)	CLASS D, TY I, 10" (SQ YD) (44201761)	CLASS D, TY II, 10" (SQ YD) (44201765)	CLASS D, TY III, 10" (SQ YD) (44201769)	CLASS D, TY IV, 10" (SQ YD) (44201771)	PCC BASE COURSE 10 3/4" (SQ YD) (35300515)	NOTES
LAKE STREET	1					1	1		1	1		
12+07	14.4' LT	0.0' LT						8.7				PATCH FOR PROPOSED STORM SEWER
12+08	2.0' LT	13.3' RT						7.8				PATCH FOR PROPOSED STORM SEWER
12+45	12.0' LT	12.6' RT									11.0	PATCH FOR PROPOSED CROSSWALK
12+61	12.0' LT	22.7' RT									15.3	PATCH FOR PROPOSED CROSSWALK
14+06	19.5' LT	13.3' LT					3.9					PATCH FOR PROPOSED CATCH BASIN AND STORM SEWER
15+57	1.9' LT	23.1' RT							15.9			PATCH FOR PROPOSED CATCH BASIN AND STORM SEWER
15+71	24.5' LT	7.8' RT							18.8			PATCH FOR FIRE HYDRANT LEAD
15+95	16.5' LT	8.0' RT						14.0				PATCH FOR PROPOSED 2" WATER SERVICE
16+07	16.4' LT	8.0' RT							15.1			PATCH FOR CUTTING AND CAPPING EXISTING MAIN
16+28	19.3' LT	15.5' RT									15.4	PATCH FOR PROPOSED CROSSWALK
16+42	40.0' LT	40.0' LT									14.3	PATCH FOR PROPOSED CROSSWALK
17+33	15.5' LT	16.6' RT									14.3	PATCH FOR PROPOSED CROSSWALK
17+54	16.3' LT	9.9' LT					4.0					PATCH FOR PROPOSED CATCH BASIN AND STORM SEWER
19+32	12.4' RT	20.4' RT						5.1				PATCH FOR PROPOSED CATCH BASIN AND STORM SEWER
19+39	6.8' RT	19.1' RT						6.9				PATCH FOR PROPOSED FIRE HYDRANT LEAD
19+51	6.8' RT	14.5' RT					4.1					PATCH FOR CUTTING AND CAPPING EXISTING MAIN
19+58	11.0' LT	11.0' RT									9.8	PATCH FOR PROPOSED CROSSWALK
19+86	11.0' LT	11.0' RT									16.5	PATCH FOR PROPOSED CROSSWALK AND STORM SEWER
20+54	11.7' LT	0.5' LT						6.6				PATCH FOR PROPOSED CATCH BASIN AND STORM SEWER
20+59	4.8' RT	11.4' RT					4.3					PATCH FOR PROPOSED CATCH BASIN AND STORM SEWER
21+25	11.8' LT	19.5' RT									14.0	PATCH FOR PROPOSED CROSSWALK
21+42	43.0' RT	43.0' RT									20.0	PATCH FOR PROPOSED CROSSWALK
22+43	17.1' RT	30.0' RT						8.2				PATCH FOR PROPOSED CATCH BASIN AND STORM SEWER
23+11	45.0' LT	45.0' LT									15.3	PATCH FOR PROPOSED CROSSWALK
23+82	24.0' LT	24.2' RT									21.4	PATCH FOR PROPOSED CROSSWALK
29+77	1.2' LT	24.3' RT			16.2							PATCH FOR PROPOSED CATCH BASIN AND STORM SEWER
30+30	12.9' RT	16.0' RT	1.8									PATCH FOR PROPOSED 1" WATER SERVICE
30+88	18.0' RT	24.6' RT	4.2									PATCH FOR PROPOSED CATCH BASIN AND STORM SEWER
31+17	1.9' LT	24.1' LT		14.5								PATCH FOR PROPOSED CATCH BASIN AND STORM SEWER
	•						19.5					ASSUMED 10% OF RESURFACING LIMITS (5% TYPE I)
GENE	RAL RESURFACING A	AREAS						58.4				ASSUMED 10% OF RESURFACING LIMITS (15% TYPE II)
S	TA 10+26 TO STA 21+	78							77.8			ASSUMED 10% OF RESURFACING LIMITS (20% TYPE III)
										233.5		ASSUMED 10% OF RESURFACING LIMITS (60% TYPE IV)
												ASSUMED 7.5% OF RESURFACING LIMITS (5% TYPE I)
GENE	RAL RESURFACING A	AREAS		88.2								ASSUMED 7.5% OF RESURFACING LIMITS (15% TYPE II)
s	TA 23+80 TO STA 38+	23			117.6							ASSUMED 7.5% OF RESURFACING LIMITS (20% TYPE III)
						352.8						ASSUMED 7.5% OF RESURFACING LIMITS (60% TYPE IV)
							29.4					ASSUMED 7.5% OF RESURFACING LIMITS (5% TYPE I)
GENE	RAL RESURFACING A	AREAS						88.2				ASSUMED 7.5% OF RESURFACING LIMITS (15% TYPE II)
S	TA 23+80 TO STA 38+	23							117.6			ASSUMED 7.5% OF RESURFACING LIMITS (20% TYPE III)
										352.8		ASSUMED 7.5% OF RESURFACING LIMITS (60% TYPE IV)
	PROJECT TOTAL		36	103	134	353	66	204	246	587	168	

engineering group
service at the highest grade.

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

									F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
			SC	HEDU	ILE	OF QUA	ANTITIES		1405	16-00264-00-PV	СООК	344	30
											CONTRACT	NO. 6	1F36
SCALE:	NTS	SHEET	5	OF	7	SHEETS	STA.	TO STA.		ILLINOIS FED. A	ID PROJECT		

STATION	CUT (SF)	AVERAGE	LENGTH	TOTAL	TOTAL (CY)
10+25	0.0	7.1	25.0	177.1	6.6
10+50	14.2			346.2	
10+75	13.5	13.8	25.0		12.8
11+00	8.5	11.0	25.0	275.2	10.2
11+25	9.4	9.0	25.0	223.8	8.3
11+50	11.9	10.7	25.0	267.0	9.9
		10.9	25.0	271.6	10.1
11+75	9.8	9.0	25.0	225.6	8.4
12+00	8.3	10.3	25.0	256.6	9.5
12+25	12.3	21.4	25.0	534.7	19.8
12+50	30.5	18.9	25.0	472.0	17.5
12+75	7.3	3.6	25.0	90.8	3.4
13+00	0.0				
13+25	0.0	0.0	25.0	0.0	0.0
13+50	7.7	3.8	25.0	96.1	3.6
13+75	8.9	8.3	25.0	207.4	7.7
14+00	7.7	8.3	25.0	208.1	7.7
14+25	7.2	7.5	25.0	186.4	6.9
		12.2	25.0	305.8	11.3
14+50	17.3	17.1	25.0	426.7	15.8
14+75	16.8	17.3	25.0	432.6	16.0
15+00	17.8	16.2	25.0	404.1	15.0
15+25	14.6	14.8	25.0	370.5	13.7
15+50	15.1	15.7	25.0	391.4	14.5
15+75	16.2				
16+00	33.2	24.7	25.0	617.5	22.9
16+25	29.4	31.3	25.0	781.6	28.9
16+50	18.8	24.1	25.0	602.1	22.3
16+75	2.6	10.7	25.0	267.5	9.9
17+00	21.5	12.0	25.0	300.6	11.1
	17.7	19.6	25.0	489.1	18.1
17+25		16.1	25.0	402.6	14.9
17+50	14.5	11.5	25.0	288.4	10.7
17+75	8.5	11.0	25.0	275.6	10.2
18+00	13.5	14.7	25.0	367.9	13.6
18+25	15.9	16.6	25.0	415.4	15.4
18+50	17.3	16.6	25.0	414.2	15.3
18+75	15.8				
19+00	17.2	16.5	25.0	412.5	15.3
19+25	17.8	17.5	25.0	436.8	16.2
19+50	34.8	26.3	25.0	657.3	24.3
19+75	23.9	29.4	25.0	734.3	27.2
		25.0	25.0	626.2	23.2
20+00	26.2	31.5	25.0	788.5	29.2

CUT										
STATION 20+25	CUT (SF) 36.9	AVERAGE	LENGTH	TOTAL	TOTAL (CY)					
		38.7	25.0	966.3	35.8					
20+50	40.4	37.5	25.0	938.6	34.8					
20+75	34.7	31.9	25.0	796.4	29.5					
21+00	29.0									
21+25	39.2	34.1	25.0	852.6	31.6					
21+50	22.4	30.8	25.0	769.4	28.5					
		25.0	25.0	625.1	23.2					
21+75	27.6	28.5	25.0	711.9	26.4					
22+00	29.3	28.2	25.0	703.8	26.1					
22+25	27.0	20.8	25.0	520.2	19.3					
22+50	14.6									
22+75	27.9	21.3	25.0	531.9	19.7					
23+00	15.0	21.5	25.0	537.0	19.9					
		14.1	25.0	353.6	13.1					
23+25	13.3	11.4	25.0	284.7	10.5					
23+50	9.5	9.2	25.0	228.8	8.5					
23+75	8.8	6.9	25.0	171.6	6.4					
24+00	4.9									
24+25	3.0	4.0	25.0	99.1	3.7					
24+50	3.1	3.1	25.0	76.7	2.8					
24+75	2.7	2.9	25.0	73.4	2.7					
		2.4	25.0	59.0	2.2					
25+00	2.0	1.8	25.0	46.0	1.7					
25+25	1.7	1.7	25.0	42.6	1.6					
25+50	1.7									
25+75	2.1	1.9	25.0	47.5	1.8					
26+00	2.1	2.1	25.0	52.9	2.0					
		2.1	25.0	53.6	2.0					
26+25	2.1	5.9	25.0	148.2	5.5					
26+50	9.7	10.8	25.0	270.9	10.0					
26+75	12.0									
27+00	3.7	7.8	25.0	195.7	7.2					
27+25	4.4	4.0	25.0	100.8	3.7					
27+50	3.9	4.1	25.0	103.7	3.8					
		4.1	25.0	102.8	3.8					
27+75	4.3	5.8	25.0	145.8	5.4					
28+00	7.4	5.6	25.0	139.1	5.2					
28+25	3.8	3.8		95.7	3.5					
28+50	3.9		25.0							
28+75	9.4	6.7	25.0	166.4	6.2					
29+00	9.8	9.6	25.0	239.9	8.9					
		7.2	25.0	178.9	6.6					
29+25	4.5	4.2	25.0	104.3	3.9					
29+50	3.8	3.9	25.0	98.4	3.6					
29+75	4.1									
30+00	5.0	4.5	25.0	112.9	4.2					
		2.8	25.0	70.3	2.6					

		cu	Т		
STATION 30+25	0.7	AVERAGE	LENGTH	TOTAL	TOTAL (CY)
30+50	2.0	1.3	25.0	32.8	1.2
		2.1	25.0	52.4	1.9
30+75	2.2	3.5	25.0	86.3	3.2
31+00	4.7	3.2	25.0	79.8	3.0
31+25	1.7	1.6	25.0	40.7	1.5
31+50	1.6	1.5	25.0	37.1	1.4
31+75	1.4	1.7	25.0	43.0	1.6
32+00	2.0	2.3	25.0	56.8	2.1
32+25	2.5				
32+50	0.0	1.3	25.0	31.4	1.2
32+75	2.5	1.2	25.0	30.7	1.1
33+00	6.3	4.4	25.0	109.0	4.0
33+25	0.0	3.1	25.0	78.3	2.9
33+50	0.0	0.0	25.0	0.0	0.0
33+75	6.0	3.0	25.0	74.6	2.8
34+00	0.0	3.0	25.0	74.6	2.8
		1.4	25.0	34.2	1.3
34+25	2.7	1.4	25.0	34.2	1.3
34+50	0.0	2.1	25.0	53.2	2.0
34+75	4.3	6.1	25.0	152.3	5.6
35+00	7.9	4.0	25.0	99.0	3.7
35+25	0.0	3.6	25.0	89.1	3.3
35+50	7.1	5.2	25.0	130.7	4.8
35+75	3.3	1.7	25.0	41.6	1.5
36+00	0.0				
36+25	3.8	1.9	25.0	47.2	1.7
36+50	8.9	6.3	25.0	158.7	5.9
36+75	8.3	8.6	25.0	215.7	8.0
37+00	6.7	7.5	25.0	188.0	7.0
37+25	6.3	6.5	25.0	162.2	6.0
37+50	4.9	5.6	25.0	140.1	5.2
37+75	4.9	4.9	25.0	122.6	4.5
38+00	13.8	9.3	25.0	232.9	8.6
		12.7	25.0	317.8	11.8
38+25	11.7	33.6	25.0	840.1	31.1
38+50	55.5	76.1	25.0	1,901.9	70.4
38+75	96.6	71.5	25.0	1,787.8	66.2
39+00	46.4	44.1	25.0	1,101.8	40.8
39+25	41.7	42.4	25.0	1,058.9	39.2
39+50	43.0	41.6	25.0	1,040.8	38.5
39+75	40.3				
40+00	42.1	41.2	25.0	1,029.5	38.1
		42.5	25.0	1,062.8	39.4

STATION	CUT (SF)	AVERAGE	LENGTH	TOTAL	TOTAL (C
40+25	42.9				
		46.1	25.0	1,153.5	42.7
40+50	49.3				
		55.3	25.0	1,383.7	51.2
40+75	61.4				
		58.9	25.0	1,471.5	54.5
41+00	56.4				
		56.9	25.0	1,421.5	52.6
41+25	57.4				
		57.0	25.0	1,426.1	52.8
41+50	56.7				
		51.5	25.0	1,288.4	47.7
41+75	46.3		25.0		
10:00	20.0	53.6	25.0	1,340.9	49.7
42+00	60.9	54.3	25.0	4.057.4	50.3
40.05	47.7	54.3	25.0	1,357.4	50.3
42+25	47.7	48.2	25.0	1,203.9	44.6
42+50	48.6	40.2	25.0	1,203.9	44.0
42+30	40.0	48.9	25.0	1.223.2	45.3
42+75	49.2	40.9	25.0	1,223.2	45.5
42173	43.2	49.4	25.0	1,233.9	45.7
43+00	49.5	40.4	20.0	1,200.0	40.7
40.00	10.0	46.6	25.0	1,164.7	43.1
43+25	43.7			.,	
		41.9	25.0	1,046.5	38.8
43+50	40.0				
		37.1	25.0	928.7	34.4
43+75	34.2				
		26.7	25.0	667.1	24.7
44+00	19.1				
		9.6	25.0	239.0	8.9
44+25	0.0				
				TOTAL	2,158.7

ROADWAY EXCAVATION	2,158.7 CUBIC YARDS
STRUCTURAL SOIL EXCAVATION	804 CUBIC YARDS
TOTAL PROEJCT EXCAVATION	2,962.7 CUBIC YARDS

engineering group
corrido at the biobact grade

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATI	E 01	F ILLINOIS
DEPARTMENT	OF	TRANSPORTATION

										F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
SCHEDULE OF QUANTITIES							1405	16-00264-00-PV	СООК	344	31			
									CONTRACT	NO. 6	1F36			
	SCALE: NTS SHEET 6 OF 7 SHEETS STA. TO STA.							ILLINOIS FED. A	ID PROJECT					

STATION	FILL (SF)	FIL AVERAGE	LENGTH	TOTAL	TOTAL (CY)
10+25	0.0	0.2	25.0	5.9	0.2
10+50	0.5				
10+75	0.3	0.4	25.0	10.2	0.4
11+00	0.2	0.3	25.0	7.3	0.3
11+25	0.2	0.2	25.0	5.8	0.2
11+50	0.1	0.2	25.0	4.5	0.2
11+75	0.0	0.1	25.0	1.6	0.1
12+00	0.1	0.0	25.0	1.1	0.0
12+25	0.0	0.1	25.0	1.5	0.1
		0.2	25.0	3.8	0.1
12+50	0.3	0.6	25.0	13.9	0.5
12+75	0.8	0.4	25.0	10.6	0.4
13+00	0.0	0.0	25.0	0.0	0.0
13+25	0.0	0.0	25.0	0.0	0.0
13+50	0.0	0.1	25.0	2.6	0.1
13+75	0.2	0.4	25.0	8.9	0.3
14+00	0.5	0.6	25.0	16.2	0.6
14+25	0.8				
14+50	0.9	0.9	25.0	21.5	0.8
14+75	0.4	0.6	25.0	16.2	0.6
15+00	0.0	0.2	25.0	4.6	0.2
15+25	0.0	0.0	25.0	0.0	0.0
15+50	0.0	0.0	25.0	0.0	0.0
15+75	0.0	0.0	25.0	0.0	0.0
16+00		0.0	25.0	0.0	0.0
	0.0	0.0	25.0	0.0	0.0
16+25	0.0	0.1	25.0	2.3	0.1
16+50	0.2	1.0	25.0	25.1	0.9
16+75	1.8	1.4	25.0	34.0	1.3
17+00	0.9	0.6	25.0	15.7	0.6
17+25	0.4	0.2	25.0	4.5	0.2
17+50	0.0	0.1	25.0	2.7	0.1
17+75	0.2	0.1	25.0	3.3	0.1
18+00	0.0	0.0	25.0	0.6	0.0
18+25	0.0				
18+50	0.0	0.0	25.0	0.0	0.0
18+75	0.0	0.0	25.0	0.0	0.0
19+00	1.2	0.6	25.0	15.0	0.6
19+25	1.4	1.3	25.0	32.8	1.2
19+50	0.0	0.7	25.0	17.8	0.7
19+75	0.0	0.0	25.0	0.6	0.0
		0.0	25.0	0.6	0.0
20+00	0.0	0.6	25.0	15.3	0.6

20+25 20+50 20+75 21+00 21+25 21+50 21+75 22+00	1.2 2.5 3.6 4.3	1.9 3.1 4.0	25.0 25.0	46.5	1.7
20+75 21+00 21+25 21+50 21+75	3.6	3.1			1.7
21+00 21+25 21+50 21+75	4.3		25.0	70.0	
21+25 21+50 21+75		4.0		76.8	2.8
21+25 21+50 21+75			25.0	99.5	3.7
21+50	0.0	2.2	25.0	53.9	2.0
21+75		3.9	25.0	97.6	3.6
	7.8	5.8	25.0	144.1	5.3
22+00	3.7	3.7	25.0	92.1	3.4
50	3.6				
22+25	5.9	4.8	25.0	119.2	4.4
22+50	4.8	5.3	25.0	133.0	4.9
22+75	3.2	4.0	25.0	99.6	3.7
		2.6	25.0	66.1	2.4
23+00	2.1	1.4	25.0	34.6	1.3
23+25	0.7	0.5	25.0	12.7	0.5
23+50	0.3	0.2	25.0	5.4	0.2
23+75	0.1				
24+00	0.0	0.1	25.0	1.4	0.1
24+25	0.0	0.0	25.0	0.0	0.0
		0.0	25.0	0.0	0.0
24+50	0.0	0.0	25.0	0.0	0.0
24+75	0.0	0.0	25.0	0.0	0.0
25+00	0.0	0.0	25.0	0.0	0.0
25+25	0.0				
25+50	0.0	0.0	25.0	0.0	0.0
25+75	0.0	0.0	25.0	0.0	0.0
		0.0	25.0	0.0	0.0
26+00	0.0	0.0	25.0	0.0	0.0
26+25	0.0	0.0	25.0	0.0	0.0
26+50	0.0	0.0	25.0	0.0	0.0
26+75	0.0				
27+00	0.0	0.0	25.0	0.0	0.0
27+25	0.0	0.0	25.0	0.0	0.0
27+50	0.0	0.0	25.0	0.0	0.0
		0.0	25.0	0.0	0.0
27+75	0.0	0.0	25.0	0.0	0.0
28+00	0.0	0.0	25.0	0.0	0.0
28+25	0.0	0.0		0.0	0.0
28+50	0.0		25.0		
28+75	0.0	0.0	25.0	0.0	0.0
29+00	0.0	0.0	25.0	0.0	0.0
		0.0	25.0	0.0	0.0
29+25	0.0	0.0	25.0	0.0	0.0
29+50	0.0	0.0	25.0	0.0	0.0
29+75	0.0	2.0	25.0	49.3	1.8
30+00	3.9	4.5	25.0	112.2	4.2

STATION	FILL (SF)	AVERAGE	LENGTH	TOTAL	TOTAL (CY)
30+25	5.0	4.0	25.0	100.9	3.7
30+50	3.0	1.8	25.0	44.0	1.6
30+75	0.5	0.5	25.0	12.5	0.5
31+00	0.5				
31+25	1.3	0.9	25.0	22.5	0.8
31+50	4.8	3.0	25.0	75.4	2.8
31+75	4.0	4.4	25.0	109.0	4.0
32+00	1.4	2.7	25.0	66.9	2.5
32+25	0.0	0.7	25.0	17.4	0.6
32+50	0.0	0.0	25.0	0.0	0.0
		0.0	25.0	0.0	0.0
32+75	0.0	0.0	25.0	0.0	0.0
33+00	0.0	0.0	25.0	0.0	0.0
33+25	0.0	0.0	25.0	0.0	0.0
33+50	0.0	0.0	25.0	0.0	0.0
33+75	0.0	0.0	25.0	0.0	0.0
34+00	0.0	0.0	25.0	0.0	0.0
34+25	0.0				
34+50	0.0	0.0	25.0	0.0	0.0
34+75	0.0	0.0	25.0	0.0	0.0
35+00	0.0	0.0	25.0	0.0	0.0
35+25	0.0	0.0	25.0	0.0	0.0
35+50	0.0	0.0	25.0	0.0	0.0
35+75	0.0	0.0	25.0	0.0	0.0
36+00	0.0	0.0	25.0	0.0	0.0
		0.0	25.0	0.0	0.0
36+25	0.0	0.0	25.0	0.0	0.0
36+50	0.0	0.0	25.0	0.0	0.0
36+75	0.0	0.0	25.0	0.0	0.0
37+00	0.0	0.0	25.0	0.0	0.0
37+25	0.0	0.0	25.0	0.0	0.0
37+50	0.0	0.0	25.0	0.0	0.0
37+75	0.0				
38+00	0.0	0.0	25.0	0.0	0.0
38+25	0.0	0.0	25.0	0.0	0.0
38+50	0.0	0.0	25.0	0.0	0.0
38+75	0.0	0.0	25.0	0.0	0.0
39+00	0.0	0.0	25.0	0.2	0.0
		0.2	25.0	4.4	0.2
39+25	0.3	0.4	25.0	10.1	0.4
39+50	0.5	0.8	25.0	20.4	0.8
39+75	1.2	1.3	25.0	31.8	1.2
40+00	1.4	1.3	25.0	33.5	1.2

SCALE:


FILL							
STATION	FILL (SF)	AVERAGE	LENGTH	TOTAL	TOTAL (CY)		
40+25	1.3						
		0.7	25.0	17.9	0.7		
40+50	0.1						
		0.1	25.0	2.4	0.1		
40+75	0.1						
		0.1	25.0	1.7	0.1		
41+00	0.1						
		0.1	25.0	2.5	0.1		
41+25	0.1	<b>_</b>					
		0.1	25.0	2.7	0.1		
41+50	0.1						
==		0.1	25.0	1.9	0.1		
41+75	0.1		25.0				
10.00	0.4	0.1	25.0	1.8	0.1		
42+00	0.1	0.4	25.0	2.0	0.1		
42+25	0.1	0.1	25.0	2.8	0.1		
42+25	0.1	0.5	25.0	11.8	0.4		
42+50	0.8	0.5	25.0	11.0	0.4		
42+30	0.0	0.8	25.0	19.8	0.7		
42+75	0.8	0.0	20.0	10.0	0.7		
42.70	0.0	1.4	25.0	35.1	1.3		
43+00	2.0		20.0	00.1	1.0		
10 100		2.7	25.0	67.7	2.5		
43+25	3.4						
		1.8	25.0	44.1	1.6		
43+50	0.1						
		0.6	25.0	14.4	0.5		
43+75	1.0						
		2.8	25.0	70.8	2.6		
44+00	4.6						
		2.3	25.0	58.1	2.2		
44+25	0.0						
				TOTAL	90.9		


<b>4</b> 10 0 100 010
engineering group
service at the highest grade.


USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE OF ILLINOIS									
DEPARTMENT	OF	TRANSPORTATION							

									SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
SCHEDULE OF QUANTITIES							1405	16-00264-00-PV	COOK	344	32		
										CONTRACT	NO. 6	1F36	
NTS	SHEET	7	OF	7	SHEETS	STA.	TO STA.		ILLINOIS FED. AID PROJECT				







#### **BENCHMARKS:**


- . SE BOLT ON HYDRANT AT SOUTHEAST CORNER OF HARLEM AVE AND LAKE STREET.
- 2. SOUTHEAST FLANGE BOLT ON HYDRANT ACROSS FROM 1128 LAKE STREET SOUTH ROW. FL = 53.64
- NORTHWEST FLANGE BOLT ON HYDRANT AT NORTHWEST CORNER OF MARION STREET AND LAKE STREET. EL = 52.96
- 4. SOUTHEAST FLANGE BOLT ON HYDRANT AT 1025 LAKE STREET EL = 52.46
- 5. NORTHWEST FLANGE BOLT ON HYDRANT AT CENTERLINE OF FOREST AVENUE AND LAKE STREET, NORTH ROW. EL = 52.39
- 6. SOUTHEAST BOLT ON HYDRANT AT SOUTHEAST CORNER OF FOREST AVENUE AND LAKE STREET. EL = 53.08
- 7. NORTHWEST FLANGE BOLT ON HYDRANT AT CALVARY MEMORIAL CHURCH SOUTH ROW ON LAKE STREET. EL = 53.27
- 8. SOUTHEAST FLANGE BOLT ON HYDRANT AT THE WEST END OF POST OFFICE, SOUTH ROW ON LAKE STREET. EL = 52.94
- NORTHEAST BOLT ON HYDRANT AT THE SOUTHEAST CORNER OF KENILWORTH AVENUE AND LAKE STREET. EL = 51.68
- 10. SOUTHEAST FLANGE BOLT WITH TAG ON HYDRANT ON THE SOUTH ROW OF LAKE STREET AT US BANK.
  FI = 48.48
- 11. FIRST BOLT PAST -> ON HYDRANT AT THE NORTHEAST CORNER OF OAK PARK AVENUE AND LAKE STREET. EL = 45.55
- 12. SOUTHEAST BOLT ON HYDRANT AT THE SOUTHWEST CORNER OF OAK PARK AVENUE AND LAKE STREET. EL = 43.97
- 13. NORTHWEST FLANGE BOLT ON HYDRANT AT THE NORTHWEST CORNER OF EUCLID AVENUE AND LAKE STREET. EL = 43.89


DATUM IS THE CHICAGO CITY DATUM (AS PROVIDED BY THE VILLAGE OF OAK PARK)


USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 20.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -


SCALE:

			ALI	GNI	MENTS,	TIES		F.A.U. RTE.	SEC.	TION		COUNTY	TOTAL SHEETS	SHEET NO.
	AND BENCHMARKS					1405	16-00264-00-PV		COOK	344	35			
AND BLINGHINIAHKS											CONTRACT	NO. 6	1F36	
NTS	SHEET	3	OF	3	SHEETS	STA.	TO STA.			ILLINOIS	FED. AI	D PROJECT		









0 10 20 40


HORIZONTAL SCALE IN FEET


COUNTY TOTAL SHEETS NO.
COOK 344 39


CONTRACT NO. 61F36





USER NAME = TEG	DESIGNED - VJM	REVISED -	_
	DRAWN - JBH	REVISED -	
PLOT SCALE = 40.0000 ' / in.	CHECKED - BLP	REVISED -	
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -	































































BUILDING FACE

| | | | | | EX STRUCTURAL VAULT

PR CURB HEAD HEIGHT

PR & EX C ELEVATIONS



STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

PROPOSED GEOMETRIC LAYOUT SCALE: 1"=10" SHEET 10 OF 13 SHEETS STA. 36+00 TO STA. 38+00

COUNTY TOTAL SHEETS NO.

COOK 344 62 SECTION 16-00264-00-PV 1405 CONTRACT NO. 61F36

HORIZONTAL SCALE IN FEET

USER NAME = TEG

PLOT SCALE = 20.0000 '/ in.

PLOT DATE = 11/15/2019

DRAWN - JBH


CHECKED - BLP


DATE - 11/15/2019


REVISED


REVISED


REVISED

































### **NOTES**

- ALL SLOPES SHOWN ARE RUNNING SLOPES. NO CROSS SLOPES ARE TO EXCEED 2.0%. NO RUNNING SLOPES ARE TO EXCEED 5% FOR TYPICAL SIDEWALK OR 8.2% FOR CURB RAMPS.
- 2. SIDE CURBS ARE TO BE CONSTRUCTED AS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER AND SHALL BE PAID FOR AS PCC SIDEWALK, 5 INCH. REFER TO IDOT STANDARDS: 424001, 424011, 424026.
- 3. SIDEWALK THROUGH PR DRIVEWAYS ARE TO BE CONSTRUCTED AND PAID FOR AS PCC SIDEWALK, 8"
- 4. REFER TO SPECIAL PROVISIONS AND DETAILS FOR DETECTABLE WARNING INSTALLATION

DEPRESSED ADA C&G

LAKE	LAKE STREET ACCESSIBLE PARKING				
POINT	STA	OFFSET	ELEV		
A1	20+44.50	23.50' RT	50.86		
A2	20+44.50	25.08' RT	51.30		
B1	20+49.50	23.50' RT	50.84		
B2	20+49.50	25.08' RT	50.90		
B3	20+49.50	31.08' RT	51.30		
B4	20+49.50	35.08' RT	51.35		
C1	20+54.50	23.50' RT	50.83		
C2	20+54.50	25.08' RT	50.89		
C3	20+54.50	31.08' RT	51.29		
C4	20+54.50	35.08' RT	51.34		
D1	20+59.50	23.50' RT	50.81		
D2	20+59.50	25.08' RT	51.25		







HORIZONTAL SCALE IN FEET



SER NAME = TEG	DESIGNED - VJM	REVISED -	
	DRAWN - JBH	REVISED -	
LOT SCALE = 10.0000 '/ in.	CHECKED - BLP	REVISED -	
LOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -	





STATE OF ILLINOIS

**DEPARTMENT OF TRANSPORTATION** 

DESIGNED - VJM

DRAWN - JBH

CHECKED - BLP

- 11/15/2019

DATE

USER NAME = TEG

PLOT SCALE = 10.0000 '/ in.

PLOT DATE = 11/15/2019

REVISED

REVISED

REVISED

REVISED

TOTAL SHEET NO.
344 76

CONTRACT NO. 61F36

COUNTY

COOK

SECTION

16-00264-00-PV


1405


TO STA.


PROPOSED ADA RAMP LAYOUT


LAKE STREET AND FOREST AVENUE


SCALE: 1"=5" SHEET 7 OF 16 SHEETS STA.















PLOT SCALE = 10.0000 '/ in. CHECKED - BLP REVISED PLOT DATE = 11/15/2019 DATE - 11/15/2019 REVISED

**DEPARTMENT OF TRANSPORTATION** 

LAKE STREET SCALE: 1"=5" SHEET 13 OF 16 SHEETS STA. TO STA. CONTRACT NO. 61F36



SCALE: 1"=5" SHEET 14 OF 16 SHEETS STA.

TO STA.

e<u>ngineering grou</u>p

PLOT DATE = 11/15/2019

DATE


- 11/15/2019

REVISED


### NOTES

- ALL SLOPES SHOWN ARE RUNNING SLOPES. NO CROSS SLOPES ARE TO EXCEED 2.0%. NO RUNNING SLOPES ARE TO EXCEED 5% FOR TYPICAL SIDEWALK OR 8.2% FOR CURB RAMPS.
- SIDE CURBS ARE TO BE CONSTRUCTED AS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER AND SHALL BE PAID FOR AS PCC SIDEWALK, 5 INCH. REFER TO IDOT STANDARDS: 424001, 424011, 424026.
- 3. SIDEWALK THROUGH PR DRIVEWAYS ARE TO BE CONSTRUCTED AND PAID FOR AS PCC SIDEWALK, 8"
- 4. REFER TO SPECIAL PROVISIONS AND DETAILS FOR DETECTABLE WARNING INSTALLATION

L	AKE STREET	ALLEY APRO	N			
POINT	STA	OFFSET	ELEV			
A1	41+07.78	40.00' LT	42.56			
A2	41+06.19	40.00' LT	42.55			
A3	41+01.01	39.97' LT	42.73			
A4	40+96.01	39.94' LT	42.79			
B1	41+07.59	30.58' LT	42.42			
B2	41+05.92	30.58' LT	42.41			
B3	41+01.06	30.58' LT	42.68			
B4	40+96.06	30.58' LT	42.74			
C1	41+05.24	26.58' LT	42.32			
C2	41+04.09	27.67' LT	42.57			
D1	41+24.73	40.00' LT	42.70			
D2	41+26.32	40.00' LT	42.69			
D3	41+32.12	40.00' LT	42.76			
D4	41+37.12	40.00' LT	42.75			
E1	41+25.67	30.58' LT	42.56			
E2	41+27.34	30.58' LT	42.55			
E3	41+32.20	30.58' LT	42.61			
E4	41+37.20	30.58' LT	42.60			
F1	41+28.02	26.57' LT	42.43			
F2	41+29.16	27.67' LT	42.55			



LAKE STREET






USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 10.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

PROPOSED ADA RAMP LAYOUT LAKE STREET SCALE: 1"=5" SHEET 15 OF 16 SHEETS STA. TO STA.

COUNTY | TOTAL SHEET NO. | COOK | 344 | 84 | CONTRACT NO. 61F36 F.A.U. RTE. 1405 SECTION 16-00264-00-PV



SCALE: 1"=5" SHEET 16 OF 16 SHEETS STA.

TO STA.

CONTRACT NO. 61F36

e<u>ngineering grou</u>p

PLOT DATE = 11/15/2019

DATE

- 11/15/2019

REVISED

### MAINTENANCE OF TRAFFIC — GENERAL NOTES

- 1. THE CONTRACTOR SHALL NOTIFY THE VILLAGE OF OAK PARK AT LEAST 2 WEEKS IN ADVANCE OF BEGINNING WORK AND SHALL COORDINATE CONSTRUCTION OPERATIONS WITH THE LAKE STREET SEWER AND WATER IMPROVEMENTS PROJECT AND ADJACENT RESURFACING PROJECT.
- 2. THE CONTRACTOR SHALL NOTIFY IDOT AND RIVER FOREST AT LEAST 2 WEEKS IN ADVANCE OF CLOSING LANES ON HARLEM AVENUE AND LAKE STREET WEST OF HARLEM.
- 3. THE CONTRACTOR SHALL NOT FULLY CLOSE ANY SECTION OF LAKE STREET UNTIL THE SEWER AND WATER IMPROVEMENTS PROJECT HAS COMPLETED WORK AT THE LAKE STREET AND OAK PARK AVE INTERSECTION AND OPENED ALL NORTHBOUND AND SOUTHBOUND LANES ON OAK PARK AVE AT LAKE STREET. DAILY CLOSURES WILL BE ALLOWED WITH THE APPROVAL OF THE ENGINEER.
- 4. ALL TEMPORARY CONSTRUCTION SIGNING TO BE IN ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES. THE SUGGESTED MAINTENANCE OF TRAFFIC IS THE MINIMUM REQUIRED. THE CONTRACTOR SHALL PROVIDE ADDITIONAL TRAFFIC CONTROL MEASURES AS REQUIRED BY THE ENGINEER. THIS WORK WILL BE INCLUDED IN THE COST OF TRAFFIC CONTROL AND PROTECTION (SPECIAL).
- 5. THE CONTRACTOR SHALL INSTALL TEMPORARY INFORMATION SIGNING OF 2'X2' PANELS STATING "BUSINESSES OPEN DURING CONSTRUCTION", AS DIRECTED BY THE ENGINEER. THE NUMBER OF SIGNS AND LOCATIONS SHALL BE DETERMINED BY THE ENGINEER. THE ENGINEER SHALL HAVE AUTHORITY TO DIRECT THE CONTRACTOR TO FABRICATE ADDITIONAL TEMPORARY INFORMATION SIGNS WITH OTHER MESSAGES, IF NECESSARY, AT LOCATIONS DETERMINED BY THE ENGINEER.
- 6. THE CONTRACTOR SHALL PROVIDE AND MAINTAIN ONE THROUGH LANE IN EACH DIRECTION ON LAKE STREET EXCEPT AS OTHERWISE INDICATED ON THE PLANS. DAILY LANE CLOSURES WILL BE ALLOWED FOR CONSTRUCTION ACTIVITY ONLY AS APPROVED BY THE ENGINEER.
- 7. THE CONTRACTOR SHALL PROVIDE ALL SIGNS, VERTICAL PANELS, TYPE III BARRICADES, CHANNELIZATION DRUMS, TYPE II BARRICADES, ALL TEMPORARY CONCRETE BARRIERS, AND PROTECTION NECESSARY FOR WORK ZONE TRAFFIC CONTROL AND PROTECTION, OR AS DIRECTED BY THE ENGINEER.
- 8. THE CONTRACTOR SHALL INSTALL AND MAINTAIN PROPOSED AND TEMPORARY DRAINAGE SYSTEMS, EROSION CONTROL, AND SEDIMENT CONTROL THROUGHOUT STAGE CONSTRUCTION DURING THE DURATION OF THE PROJECT.
- 9. THE CONTRACTOR SHALL PROVIDE AND MAINTAIN CLEARLY DELINEATED AND SAFE PEDESTRIAN ACCESS ROUTES ALONG EACH SIDE OF LAKE STREET AND THROUGH SIGNALIZED INTERSECTIONS AT ALL TIMES DURING CONSTRUCTION UNLESS OTHERWISE APPROVED BY THE ENGINEER. AT LEAST ONE SIDE OF LAKE STREET SIDEWALK ACCESS SHALL BE PCC SIDEWALK, EITHER EXISTING OR NEW. THE CONTRACTOR SHALL MAINTAIN PEDESTRIAN ACCESS TO ALL CROSSING STREETS ALONG LAKE STREET AND PROVIDE AT LEAST ONE CROSSWALK CROSSING LAKE STREET AT EACH INTERSECTION. AT LEAST TWO CORNERS OF AN INTERSECTION SHALL BE OPEN AT ALL TIMES AND SHALL BE PCC, EITHER EXISTING OR NEW. THIS WORK SHALL BE INCLUDED IN THE COST OF TRAFFIC CONTROL AND PROTECTION (SPECIAL).
- 10. THE CONTRACTOR SHALL MAINTAIN THE EXISTING MIDBLOCK CROSSINGS AT MAPLE AVENUE AND AT THE LAKE STREET THEATRE AT ALL TIMES EXCEPT WHEN WORK IS OCCURRING DIRECTLY AT THE CROSSING AREA. AT THOSE TIMES, THE CONTRACTOR SHALL INSTALL TEMPORARY CROSSINGS ADJACENT TO THE EXISTING CROSSWALKS.
- 11. THE CONTRACTOR SHALL MAINTAIN PEDESTRIAN ACCESS TO ALL PROPERTIES, SUCH AS BUSINESSES OR RESIDENTIAL BUILDINGS, ALONG THE LAKE STREET CORRIDOR THROUGHOUT CONSTRUCTION UTILIZING TEMPORARY BRIDGES. SEE SPECIAL PROVISION FOR TEMPORARY BRIDGE.
- 12. AT NO TIME SHALL ACCESS TO EMERGENCY OR FIRE EXITS BE DISRUPTED WITHOUT PRIOR APPROVAL FROM THE VILLAGE OF OAK PARK FIRE DEPARTMENT. ALTERNATIVE ACCESS POINTS SHALL BE COORDINATED AND ACCOMMODATED WITH ALL RESIDENTIAL/COMMERCIAL BUILDINGS AND THE FIRE DEPARTMENT PRIOR TO THE APPROVAL OF A TEMPORARY BRIDGE STRUCTURE AND SUBSEQUENT CONSTRUCTION ACTIVITIES.
- 13. AT THE END OF EACH WORK DAY, THE CONTRACTOR SHALL BACKFILL OR COVER ALL TRENCHES AND OPEN EXCAVATION HOLES FOR TEMPORARY PAVEMENT, PROPOSED PAVEMENT, PROPOSED STORM SEWER, DRAINAGE STRUCTURES, AND WATER MAINS IN ORDER TO PROVIDE SAFE CONDITION FOR MOTORISTS AND THE PUBLIC DURING NON-WORKING HOURS. THE CONSTRUCTION OF THIS WORK SHALL BE INCLUDED IN THE COST OF TRAFFIC CONTROL AND PROTECTION (SPECIAL).
- 14. PORTABLE CHANGEABLE MESSAGE SIGNS SHALL BE LOCATED ON APPROACHES TO THE PROJECT LIMITS ON LAKE STREET WEST OF HARLEM AVE AND EAST OF RIDGELAND AVE AT LEAST 7 DAYS PRIOR TO COMMENCEMENT OF WORK. THE CONTRACTOR WILL PROVIDE ANOTHER SIGN TO BE PLACED AT A LOCATION DESIGNATED BY THE ENGINEER. PORTABLE CHANGEABLE MESSAGE SIGNS SHALL REMAIN THROUGHOUT THE DURATION OF THE PROJECT. THE ENGINEER SHALL PROVIDE THE CONTRACTOR WITH THE MESSAGE TO BE DISPLAYED ON EACH SIGN. THE CONTRACTOR SHALL CHANGE THE MESSAGE DISPLAYED ON EACH SIGN AS STAGING NECESSITATES OR AS DIRECTED BY THE ENGINEER. THIS WORK SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER CALENDAR DAY FOR "CHANGEABLE MESSAGE SIGN".
- 15. TEMPORARY SIGNS SHALL BE INSTALLED IN ADVANCE OF CONSTRUCTION AND SHALL BE COVERED. UNCOVERING OF TEMPORARY SIGNAGE AND REMOVAL OF EXISTING SIGNAGE SHALL BE COORDINATED TO AVOID CONFLICTING SIGNAGE. ALL EXISTING GUIDE SIGNS (I.E. STREET NAME SIGNS, ADVANCE STREET NAME SIGNS, ETC.) SHALL BE MAINTAINED AND VISIBLE TO TRAFFIC DURING CONSTRUCTION. THE CONTRACTOR WILL BE REQUIRED TO RELOCATE OR REMOVE AND REPLACE ALL ROADWAY SIGNS WHICH INTERFERE WITH CONSTRUCTION OPERATIONS AND TEMPORARILY RESET ALL SUCH SIGNS DURING ALL STAGES OF CONSTRUCTIONS. THIS WORK WILL BE INCLUDED IN THE CONTRACT UNIT PRICE FOR TRAFFIC CONTROL AND PROTECTION, (SPECIAL). ALL WORK INVOLVING SIGNS SHALL BE GOVERNED BY THE FOLLOWING:
  - A. SIGNS SHALL NOT BE REMOVED UNTIL NECESSITATED BY THE PROGRESS OF THE WORK.
  - B. EVERY SIGN REMOVED MUST BE RE-ERECTED AT A TEMPORARY LOCATION IN A WORKMANLIKE MANNER AND VISIBLE TO THE TRAFFIC FOR WHICH IT IS INTENDED.
  - C. ALL SIGNS MUST BE MAINTAINED STRAIGHT AND CLEAN FOR THE DURATION OF THE TEMPORARY SETTING.
- 16. IN THE CASE WHEN WEATHER OR TEMPERATURE IS FOUND TO BE OUTSIDE OF THE MANUFACTURER'S SPECIFICATIONS FOR THE INSTALLATION OF PAVEMENT MARKING TAPE, THE CONTRACTOR SHALL USE AN ALTERNATE MATERIAL FOR TEMPORARY PAVEMENT MARKINGS AT NO ADDITIONAL COST TO THE CONTRACT WITH APPROVAL FROM THE ENGINEER. INSTALLATION AND REMOVAL OF THE ALTERNATE TEMPORARY PAVEMENT MARKING TAPE SHALL BE PAID FOR AS PAVEMENT MARKING TAPE, TYPE III OF THE WIDTH SPECIFIED AND TEMPORARY PAVEMENT MARKING REMOVAL, RESPECTIVELY. NO ADDITIONAL COMPENSATION WILL BE PROVIDED TO THE CONTRACTOR.
- 17. WORKERS SIGNS (W21-1(0)) SHALL BE REMOVED OR COVERED WHEN WORKERS ARE NOT PRESENT FOR MORE THAN ONE HOUR.
- 18. THE CONTRACTOR SHALL NOTIFY THE PROPERTY OWNER OR MANAGER AT LEAST 48 HOURS BEFORE CLOSING A DRIVEWAY. THE CONTRACTOR WILL BE REQUIRED TO COORDINATE WITH THE PROPERTY OWNER OR MANAGER AND THE ENGINEER TO MINIMIZE IMPACT OF DRIVEWAY CLOSURES. THE CONTRACTOR SHALL PLAN DRIVEWAY CLOSURE, REMOVAL, AND NEW DRIVEWAY CONSTRUCTION IN SUCH A WAY AS TO MINIMIZE THE DURATION OF THE DRIVEWAY CLOSURE. REFER TO SPECIAL PROVISIONS FOR MORE INFORMATION.

### CLOSURE RESTRICTIONS AND INTERIM COMPLETION DATES

STAGE 1 MAY OCCUR CONCURRENTLY WITH EITHER STAGE 1A, 1B, OR STAGE 1C. STAGE 1A, STAGE 1B, AND STAGE 1C SHALL NOT OCCUR CONCURRENTLY.

THE LAKE STREET AND MARION AVE INTERSECTION CLOSURE, SHOWN IN STAGE 2 OF THE SUGGESTED MAINTENANCE OF TRAFFIC, SHALL HAVE A DURATION OF NO MORE THAN 14 CALENDAR DAYS AFTER.


THE LAKE STREET AND FOREST AVE INTERSECTION CLOSURE, SHOWN IN STAGE 3A, SHALL HAVE A DURATION OF NO MORE THAN 14 CALENDAR DAYS.

THE LAKE STREET AND FOREST AVE INTERSECTION CLOSURE, SHOWN IN STAGE 3B, SHALL HAVE A DURATION OF NO MORE THAN 10 CALENDAR DAYS.


THE LAKE STREET AND OAK PARK AVE INTERSECTION CLOSURE, SHOWN IN STAGE 4D, SHALL HAVE A DURATION OF NO MORE THAN 3 CALENDAR DAYS.


SHOULD THE CONTRACTOR FAIL TO COMPLETE THE WORK AND RE-OPEN THE CLOSURES WITHIN THE SPECIFIED DURATION, THE CONTRACTOR SHALL BE LIABLE AND SHALL PAY THE VILLAGE OF OAK PARK AN AMOUNT ACCORDING TO ARTICLE 108.09 OF THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION IN ILLINOIS (2016).


ALL REQUIRED WORK AS SHOWN AND DESCRIBED IN STAGES 1, 1A, 1B, 1C, 2, 3A, AND 3B SHALL BE COMPLETED AND TRAFFIC SHIFTED INTO STAGE 4 BY THE INTERIM COMPLETION DATE OF AUGUST 7, 2020. SHOULD THE CONTRACTOR FAIL TO COMPLETE THIS WORK BY AUGUST 7, 2019, THE CONTRACTOR SHALL BE LIABLE AND SHALL PAY THE VILLAGE OF OAK PARK AN AMOUNT ACCORDING TO ARTICLE 108.09 OF THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION IN ILLINOIS (2016).



	SUGGESTED MAINTENANCE OF TRAFFIC GENERAL NOTES		F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
			1405	16-00264-00-PV	СООК	344	86
ı	ULIVERAL NOTES				CONTRACT	NO. 6	1F36
	SCALE: NTS	SHEET 1 OF 33 SHEETS STA. TO STA.		ILLINOIS FED. A	ID PROJECT		







thomas.

engineering group
service at the highest grade.

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

Ī	SUGGESTED MAINTENANCE OF TRAFFIC DETOUR PLAN		SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
ı			16-00264-00-PV	соок	344	87
L				CONTRACT	NO. 6	1F36
ı	SCALE: NTS   SHEET 2 OF 33 SHEETS   STA. TO STA.		ILLINOIS FED. A	ID PROJECT		

### **DETOUR GENERAL NOTES**

- 1. ALL SIGNING SHALL BE IN ACCORDANCE WITH THE APPLICABLE PROVISIONS OF THE STATE OF ILLINOIS "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION ADOPTED JAN. 1, 2016", "THE QUALITY STANDARD FOR WORK ZONE TRAFFIC CONTROL DEVICES ADOPTED 2010", THE DETAILS IN THESE PLANS, THE LATEST EDITION OF THE STATE OF ILLINOIS "MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES", AND THE SPECIAL PROVISIONS FOR TRAFFIC CONTROL AND PROTECTION. ALL LABOR, TOOLS, EQUIPMENT, AND MATERIALS NECESSARY TO INSTALL, MAINTAIN, RELOCATE AND REMOVE THE DETOUR SIGNING AS SHOWN BELOW, SHORT TERM LOCAL ROAD DETOURS NOT SHOWN, OR AS DIRECTED BY THE ENGINEER SHALL BE PAID FOR AS TRAFFIC CONTROL AND PROTECTION (SPECIAL).
- THE ENGINEER SHALL BE NOTIFIED IN WRITING AT LEAST THREE WEEKS PRIOR TO THE DAY THE DETOUR IS TO BE IN EFFECT. THE ENGINEER SHALL DETERMINE THE HOUR OF CLOSURE. THE ENGINEER WILL CONTACT THE APPROPRIATE LOCAL AGENCIES AND INTERESTED PARTIES.
- 3. IF REQUESTED BY THE CONTRACTOR IN WRITING AT LEAST THREE WEEKS PRIOR TO THE DAY THE DETOUR IS TO BE IN EFFECT THE ENGINEER WILL FIELD LOCATE THE POSITIONS OF ANY SIGNS.
- 4. LONGITUDINAL DIMENSIONS SHOWN ON THESE PLANS MAY BE ADJUSTED TO FIT FIELD CONDITIONS, WITH THE APPROVAL OF THE ENGINEER.
- 5. THE ROAD SHALL NOT BE CLOSED UNTIL ALL SIGNING IS ERECTED IN ACCORDANCE WITH THE DETOUR PLAN AND INSPECTED AND APPROVED BY THE ENGINEER.
- 6. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT ALL BARRICADES, SIGNS, LIGHTS, AND OTHER DEVICES INSTALLED BY HIM ARE IN PLACE AND OPERATING 24 HOURS EACH DAY INCLUDING SUNDAYS AND HOLIDAYS DURING THE TIME THE DETOUR IS IN EFFECT.
- 7. THE TRAFFIC CONTROL SHOWN ON THE DETOUR PLAN IS THE MINIMUM NECESSARY TO ENSURE THIS ROAD CLOSURE. ALL CHANGES IN TRAFFIC CONTROL THAT ARE DEEMED NECESSARY SHALL BE APPROVED BY THE ENGINEER.
- 8. ALL EXISTING SIGNING THAT IS NOT APPLICABLE WHILE THE DETOUR IS IN EFFECT SHALL BE COMPLETELY COVERED BY THE CONTRACTOR, IN A MANNER APPROVED BY THE ENGINEER.
- 9. ALL DETOUR SIGNING SHALL BE POST MOUNTED.
- 10. ALL DETOUR SIGNING, EXCEPT REGULATORY SIGNS, SHALL HAVE BLACK LEGENDS WITH 6" MINIMUM LETTER HEIGHT ON FLUORESCENT ORANGE SHEETING THAT SHALL MEET THE REQUIREMENTS OF SECTION 1091 OF THE STANDARD SPECIFICATIONS.

- 11. THE SIZES OF ALL SIGNS NOT SPECIFIED IN THESE PLANS SHALL BE AS REQUIRED BY THE ILLINOIS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
- 12. PRIOR TO INSTALLING POST MOUNTED SIGNS, THE CONTRACTOR SHALL CONTACT J.U.L.LE.
- 13. ALL DETOUR SIGNING SHALL BE NEW
  OR LIKE NEW CONDITION. THE ENGINEER SHALL BE THE
  SOLE JUDGE OF THE CONDITION OF THE SIGNS.
- 14. WHEN REQUIRED THE MINIMUM DIMENSIONS OF THE ORANGE WARNING FLAGS SHOWN IN THESE PLANS ARE 18" × 18"
- 15. ALL BARRICADES SHALL HAVE REFLECTORIZED STRIPING ON BOTH SIDES OF THE BARRICADES. THE TYPE III BARRICADES USED AT THE POINT OF CLOSURE TO THRU TRAFFIC SHALL NOT EXCEED 8 FEET IN WIDTH EACH, FOR A SINGLE APPROACH LANE.
- 16. THE "ROAD CLOSED" (R11-2), THE "ROAD CLOSED XX MILES AHEAD LOCAL TRAFFIC ONLY" (R11-3) AND THE "ROAD CLOSED TO THRU TRAFFIC" (R11-4) SIGNS SHALL BE MOUNTED ABOVE THE TOP OF THE BARRICADE.
- 18. DURING NON-WORKING HOURS AT THE POINT OF ROAD CLOSURE TO ALL TRAFFIC THE CONTRACTOR SHALL PROVIDE A MEANS TO RESTRAIN THE BARRICADES FROM EASY MOVEMENT BY VANDALS. THE CHOSEN METHOD SHALL BE APPROVED BY THE ENGINEER.
- 19. CONSTRUCTION EQUIPMENT SHALL NOT BE PARKED IMMEDIATELY BEHIND THE TYPE III BARRICADES DURING NON-WORKING HOURS. IN ANY EVENT ARTICLE 701.04 OF THE STANDARD SPECIFICATIONS SHALL APPLY.
- 20. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING THE VISIBILITY OF ALL DETOUR AND CONSTRUCTION SIGNING, INCLUDING BRUSHING BACK VEGETATION IF DEEMED NECESSARY BY THE ENGINEER.
- 21. THE CONTRACTOR SHALL PLACE PORTABLE CHANGEABLE MESSAGE SIGNS TWO WEEKS IN ADVANCE OF PLANNED DETOUR TYPE III BARRICADES SHALL HAVE TWO (2) AMBER TYPE A-LOW INTENSITY FLASHING LIGHTS SPACED NEAR THE CENTERLINE OF THE SUPPORTS.
- 17. THE ROAD NAME SIGN SHALL HAVE A BLACK LEGEND ON FLUORESCENT ORANGE REFLECTIVE SHEETING. THE SIGN BLANK SHALL BE A 9" X VARIABLE OR A 12" X VARIABLE WITH DESIGN SERIES C LETTERS. THE CAPITAL LETTERS SHALL BE 6" WITH 5" LOWER CASE.

### **DETOUR ROUTE INFORMATION**

LAKE STREET (WEST OF HARLEM)
JURISDICTION: IDOT
MAINTAINED BY RIVER FOREST
2 LANE UNDIVIDED


LAKE STREET (EAST OF HARLEM)
JURISDICTION: OAK PARK
2 LANE UNDIVIDED

HARLEM AVENUE
JURISDICTION: IDOT
4 LANE UNDIVIDED
TRAVEL DISTANCE: 0.40 MILES

CHICAGO AVENUE
JURISDICTION: VILLAGE OF OAK PARK
2 LANE UNDIVIDED
TRAVEL DISTANCE: 1.05 MILES

RIDGELAND AVENUE
JURISDICTION: IDOT
MAINTAINED BY VILLAGE OF OAK PARK
2 LANE UNDIVIDED
TRAVEL DISTANCE: 0.40 MILES

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -



### **ESTIMATED STAGING DURATIONS**

STAGE 1 - EARLY APRIL 2020 TO LATE JUNE 2020

STAGE 2 - LATE JUNE 2020 TO EARLY JULY 2020

STAGE 3 - EARLY JULY 2020 TO EARLY AUGUST 2020

STAGE 4 - EARLY AUGUST 2020 TO MID-SEPTEMBER 2020 STAGE 5 - MID-SEPTEMBER 2020 TO EARLY NOVEMBER 2020

STAGE 6 - EARLY NOVEMBER 2020 TO LATE NOVEMBER 2020

ADJACENT UTILITY CONTRACT - MID-MARCH 2020 TO MID-MAY 2020

ADJACENT RESURFACING CONTRACT - EARLY MAY 2020 TO MID-AUGUST 2020

\*REFER TO SPECIAL PROVISIONS FOR DETAILED DURATIONS AND COMPLETION DATES\*

### **BUSINESS DISTRICTS**

DOWNTOWN OAK PARK (DTOP) LAKE STREET FROM HARLEM AVE TO FOREST AVE MARION STREET FROM NORTH BLVD TO ONTARIO STREET


HEMINGWAY

SCALE: NTS SHEET 4 OF 33 SHEETS STA.

TO STA.

LAKE STREET FROM GROVE AVE TO EUCLID AVE OAK PARK AVE FROM PLEASANT ST TO ONTARIO STREET

CONTRACT NO. 61F36



PLOT DATE = 11/15/2019

DATE - 11/15/2019

REVISED

### PRE-STAGE

TRAFFIC

DAILY LANE CLOSURES AS NEEDED.

CONSTRUCTION

INSTALL TEMPORARY TRAFFIC SIGNALS AT MARION ST, FOREST AVE, KENILWORTH AVE, AND OAKPARK AVE.

### STAGE 1

INSTALL THE LONG TERM DETOUR AS SHOWN IN THE PLANS. INSTITUTE A FULL-CLOSURE OF LAKE STREET BETWEEN HARLEM AVE AND MARION ST. INSTITUTE A FULL-CLOSURE OF LAKE STREET BETWEEN MARION ST AND FOREST AVE. THE HARLEM/LAKE, MARION/LAKE, AND FOREST/LAKE INTERSECTIONS SHOULD REMAIN OPEN WITH THE FOLLOWING LANE CLOSURES:

- CLOSE THE SOUTHBOUND LEFT-TURN LANE AT HARLEM AVE & LAKE STREET.
- CLOSE THE EASTBOUND THROUGH LANE ON THE WEST LEG OF HARLEM AVE & LAKE STREET.
- SHIFT TRAFFIC AWAY FROM THE EDGE OF PAVEMENT AND CONVERT SOUTHBOUND MARION ST APPROACHING LAKE ST TO A SINGLE THROUGH ONLY
- CONVERT NORTHBOUND MARION ST APPROACHING LAKE ST TO A THROUGH ONLY
- SHIFT NORTHBOUND TRAFFIC ON THE NORTH LEG OF MARION ST AT LAKE ST AWAY FROM THE FDGF OF PAVEMENT
- CLOSE THE NORTHBOUND LEFT-TURN LANE ON THE SOUTH LEG OF FOREST AVE.
  SHIFT TRAFFIC TO THE EAST ON THE SOUTH LEG OF FOREST AVE
- CLOSE THE LEFT TURN LANE ON THE NORTH LEG OF FOREST AVE SHIFT TRAFFIC TO THE EAST ON THE NORTH LEG OF FOREST AVE
- CLOSE THE THROUGH LANE FOR WESTBOUND TRAFFIC AT FOREST AVE

REMOVE EXISTING CURB & GUTTER, SIDEWALK, AND LIGHTING EQUIPMENT. REMOVE AND INSTALL DRAINAGE AND UTILITIES. INSTALL IRRIGATION SYSTEM. CONSTRUCT PROPOSED CURB AND GUTTER. INSTALL PROPOSED LIGHTING AND TRAFFIC SIGNAL EQUIPMENT. CONSTRUCT SIDEWALK AND STREETSCAPE ELEMENTS. PERFORM VARIABLE DEPTH MILL. ADJUST STRUCTURES AND PERFORM ANY NECESSARY PAVEMENT PATCHING. CONSTRUCT CROSSWALKS AT MAPLE AVE AND THE WEST LEG OF THE MARION INTERSECTION. CONSTRUCT SPEED TABLE AT STATION 19+70. PLACE HMA BINDER AND SURFACE. PLACE PERMANENT PAVEMENT MARKINGS FROM HARLEM TO FOREST.

### STAGE 1A

TRAFFIC

CLOSE THE PARKING LANES IN THE EASTBOUND DIRECTION. SHIFT EASTBOUND TRAFFIC TO THE NORTH AT THE KENILWORTH INTERSECTION. CONVERT THE EASTBOUND LEFT-TURN LANE AT THE KENILWORTH INTERSECTION TO A SHARED THROUGH/LEFT/RIGHT LANE, ALL MOVEMENTS WILL STILL BE PERMITTED AT THE KENILWORTH INTERSECTION

CONSTRUCTION

REMOVE EXISTING SIDEWALK AND CURB & GUTTER ALONG THE SOUTH SIDE OF LAKE STREET. CONSTRUCT CURB & GUTTER, SIDEWALK, STREETSCAPE ELEMENTS AND LIGHTING.

### STAGE 1B

CLOSE THE PARKING LANES IN THE WESTBOUND DIRECTION. SHIFT WESTBOUND TRAFFIC TO THE SOUTH AT THE KENILWORTH INTERSECTION. CONVERT THE WESTBOUND LEFT-TURN LANE AT THE KENILWORTH INTERSECTION TO A SHARED THROUGH/LEFT/RIGHT LANE. ALL MOVEMENTS WILL STILL BE PERMITTED AT THE KENILWORTH INTERSECTION

CONSTRUCTION

REMOVE EXISTING SIDEWALK AND CURB & GUTTER ALONG THE NORTH SIDE OF LAKE STREET. CONSTRUCT CURB & GUTTER, SIDEWALK, STREETSCAPE ELEMENTS AND LIGHTING.

### STAGE 1C

MOVING CLOSURES ALONG LAKE STREET AS NECESSARY.

MILL LAKE STREET BETWEEN FOREST AVENUE AND STA 35+80. PERFORM PAVEMENT PATCHING AND STRUCTURE ADJUSTMENTS. PLACE HMA BINDER AND SURFACE COURSE. PLACE PERMANENT PAVEMENT MARKING LINES.

### STAGE 2

TRAFFIC

SHORT-TERM CLOSURE OF THE LAKE & MARION INTERSECTION. TEMPORARY DETOUR ROUTES SHOULD BE POSTED FOR VEHICULAR TRAFFIC. TEMPORARY PEDESTRIAN ACCESS AND CROSSINGS SHOULD BE MAINTAINED THROUGHOUT THE INTERSECTION CLOSURE AS DIRECTED BY THE ENGINEER.

REMOVE EXISTING PAVEMENT. REMOVE AND INSTALL DRAINAGE AND UTILITIES. INSTALL IRRIGATION SYSTEM. INSTALL REMAINING PROPOSED LIGHTING AND TRAFFIC SIGNAL EQUIPMENT. EXCAVATE, PLACE AGGREGATE SUBGRADE, AND FINE GRADE. ADJUST STRUCTURES. CONSTRUCT PCC BASE USING HIGH-EARLY STRENGTH CONCRETE. CONSTRUCT NORTH LEG AND SOUTH LEG CROSSWALKS USING HIGH EARLY STRENGTH CONCRETE. INSTALL BITUMINOUS SETTING BED AND BRICK PAVERS.

### STAGE 3A

SHORT-TERM CLOSURE OF THE EAST HALE OF THE LAKE & FOREST INTERSECTION, TEMPORARY DETOUR ROUTES SHOULD BE POSTED FOR VEHICULAR TRAFFIC. TEMPORARY PEDESTRIAN ACCESS AND CROSSINGS SHOULD BE MAINTAINED THROUGHOUT THE INTERSECTION CLOSURE AS DIRECTED BY THE ENGINEER

REMOVE EXISTING PAVEMENT, REMOVE AND INSTALL DRAINAGE AND UTILITIES, INSTALL REMAINING PROPOSED LIGHTING AND TRAFFIC SIGNAL EQUIPMENT. EXCAVATE, PLACE AGGREGATE SUBGRADE, AND FINE GRADE, ADJUST STRUCTURES, CONSTRUCT PCC BASE USING HIGH-EARLY STRENGTH CONCRETE. CONSTRUCT 3 OF THE FOREST AVE CROSSWALKS WITHIN THE CLOSURE USING HIGH-EARLY STRENGTH CONCRETE. INSTALL BITUMINOUS SETTING BED AND BRICK PAVERS.

### STAGE 3B

SHORT-TERM CLOSURE OF THE WEST HALF OF THE LAKE & FOREST INTERSECTION. TEMPORARY DETOUR ROUTES SHOULD BE POSTED FOR VEHICULAR TRAFFIC. TEMPORARY PEDESTRIAN ACCESS AND CROSSINGS SHOULD BE MAINTAINED THROUGHOUT THE INTERSECTION CLOSURE AS DIRECTED BY THE ENGINEER.

REMOVE EXISTING PAVEMENT. REMOVE AND INSTALL DRAINAGE AND UTILITIES. INSTALL REMAINING PROPOSED LIGHTING AND TRAFFIC SIGNAL EQUIPMENT, EXCAVATE, PLACE AGGREGATE SUBGRADE, AND FINE GRADE. ADJUST STRUCTURES. CONSTRUCT PCC BASE USING HIGH-EARLY STRENGTH CONCRETE. CONSTRUCT THE SOUTH LEG CROSSWALK USING HIGH-EARLY STRENGTH CONCRETE. INSTALL BITUMINOUS SETTING BED AND BRICK PAVERS.

### STAGE 4A

TRAFFIC

SHIFT LAKE STREET TRAFFIC TO THE SOUTH CLOSING THE WESTBOUND LANES OF LAKE STREET. SHIFT OAK PARK AVENUE TRAFFIC TO THE EAST CLOSING THE SOUTHBOUND LANES OF OAK PARK AVENUE. RESTRICT RIGHT TURNS FROM SOUTHBOUND OAK PARK AVE. TEMPORARY TRAFFIC SIGNALS WILL BE USED FOR THE OFFSET INTERSECTION CONFIGURATION. EACH LEG WILL MAINTAIN ONE THROUGH LANE IN EACH DIRECTION. ONCE THE CROSSWALK, PCC BASE, AND TEMPORARY HMA RAMPS ARE COMPLETE, CONTRACTOR SHALL UTILITIZE SHORT TERM PAVEMENT MARKINGS AND IDOT HIGHWAY STANDARD 701501-06 TO PERFORM MILL AND RESURFACE.

REMOVE EXISTING PAVEMENT, SIDEWALK, LIGHTING, AND CURB & GUTTER IN THE NW QUADRANT OF THE INTERSECTION. CONSTRUCT CURB & GUTTER, SIDEWALK, CROSSWALKS, TRAFFIC SIGNALS, STREETSCAPE ELEMENTS AND LIGHTING, CONSTRUCT 9" PCC BASE COURSE USING HIGH-EARLY STRENGTH CONCRETE. CONSTRUCT TEMPORARY HMA RAMPS WHILE ENSURING CROSS WALKS ARE PROTECTED, PERFORM MILLING, PAVEMENT PATCHING, STRUCTURE ADJUSTMENTS, AND VARIABLE DEPTH MILL AND RESURFACE FROM STA 35+80 TO STA 38+23.

### STAGE 4B

SHIFT LAKE STREET TRAFFIC TO THE NORTH CLOSING THE EASTBOUND LANES OF LAKE STREET. SHIFT OAK PARK AVENUE TRAFFIC TO THE EAST CLOSING THE SOUTHBOUND LANES OF OAK PARK AVENUE. RESTRICT RIGHT TURNS FROM EASTBOUND LAKE STREET. TEMPORARY TRAFFIC SIGNALS WILL BE USED FOR THE OFFSET INTERSECTION CONFIGURATION. EACH LEG WILL MAINTAIN ONE THROUGH LANE IN EACH DIRECTION.

CONSTRUCTION

REMOVE EXISTING PAVEMENT, SIDEWALK, LIGHTING, AND CURB & GUTTER IN THE SW QUADRANT OF THE INTERSECTION, CONSTRUCT CURB & GUTTER, SIDEWALK, CROSSWALKS, TRAFFIC SIGNALS, STREETSCAPE ELEMENTS AND LIGHTING. CONSTRUCT 9" PCC BASE COURSE USING HIGH-EARLY STRENGTH CONCRETE, CONSTRUCT TEMPORARY HMA RAMPS AND ENSURE CROSS WALKS ARE PROTECTED.

### STAGE 4C

TRAFFIC

SHIFT OAK PARK AVENUE TRAFFIC TO THE EAST CLOSING THE SOUTHBOUND LANES OF OAK PARK AVENUE. NO THROUGH TRAFFIC WILL BE ALLOWED ON LAKE STREET THROUGH THE INTERSECTION. TEMPORARY TRAFFIC SIGNALS WILL BE USED FOR THE OFFSET INTERSECTION CONFIGURATION. EACH LEG WILL MAINTAIN ONE THROUGH LANE IN EACH DIRECTION.

CONSTRUCTION

REMOVE EXISTING PAVEMENT, SIDEWALK, LIGHTING, AND CURB & GUTTER IN THE EASTERN HALF OF THE INTERSECTION, CONSTRUCT CURB & GUTTER, SIDEWALK, CROSSWALKS, TRAFFIC SIGNALS, STREETSCAPE ELEMENTS AND LIGHTING. CONSTRUCT REMAINDER OF 9" PCC BASE COURSE USING HIGH-EARLY STRENGTH CONCRETE.

### STAGE 4D

SHORT TERM CLOSURE OF THE LAKE STREET AND OAK PARK AVE INTERSECTION.

REMOVE TEMPORARY HMA RAMPS, PLACE BITUMINOUS SETTING BED AND SET BRICK PAVERS. PLACE PERMANENT PAVEMENT MARKINGS ON LAKE STREET FROM STA 35+80 TO 38+23 AND ON OAK PARK FROM 397+60 TO 402+15.

### STAGE 5

TRAFFIC

INSTITUTE A FULL-CLOSURE OF LAKE STREET FROM EAST OF OAK PARK AVENUE TO WEST OF EUCLID AVENUE. PLACE "ROAD CLOSED" SIGNS ON THE EAST LEG OF OAK PARK AVENUE & LAKE TO PREVENT TRAFFIC FROM GOING ONTO THE EAST LEG OF LAKE STREET. PLACE "ROAD CLOSED" SIGNS ON THE WEST LEG OF EUCLID AVENUE & LAKE TO PREVENT TRAFFIC FROM GOING ONTO THE WEST LEG OF LAKE STREET, BOTH THE OAK PARK/LAKE AND EUCLID/LAKE INTERSECTIONS SHOULD REMAIN OPEN WITH THE FOLLOWING LANE CLOSURES:

- CLOSE THE SOUTHBOUND LEFT-TURN LANE AT OAK PARK AVE & LAKE STREET.
- CONVERT THRU/RIGHT TURN LANE TO RIGHT-TURN ONLY

TEMPORARY DETOUR ROUTES SHOULD BE POSTED FOR VEHICULAR TRAFFIC. TEMPORARY PEDESTRIAN ACCESS AND CROSSINGS SHOULD BE MAINTAINED THROUGHOUT THE INTERSECTION CLOSURE.

REMOVE EXISTING PAVEMENT, SIDEWALK AND CURB & GUTTER. CONSTRUCT PAVEMENT, CURB & GUTTER, SIDEWALK, STREETSCAPE ELEMENTS AND LIGHTING.

### STAGE 6A

CLOSE THE WESTERN PORTION OF EUCLID AVENUE. PROVIDE ROAD CLOSED SIGNAGE TO PREVENT THROUGH TRAFFIC ON LAKE STREET. CLOSE THE SOUTHBOUND LANES OF EUCLID AVENUE. EUCLID AVENUE WILL BE ONE-WAY NORTHBOUND ONLY.

REMOVE EXISTING PAVEMENT, SIDEWALK, LIGHTING, AND CURB & GUTTER ON THE WESTERN PORTION OF THE EUCLID INTERSECTION. CONSTRUCT CURB & GUTTER, SIDEWALK, STREETSCAPE ELEMENTS

### STAGE 6B

CLOSE THE EASTERN PORTION OF EUCLID AVENUE. PROVIDE ROAD CLOSED SIGNAGE TO PREVENT THROUGH TRAFFIC ON LAKE STREET. SHIFT TRAFFIC ON EUCLID AVENUE TO THE WEST. EUCLID AVENUE WILL BE ONE-WAY NORTHBOUND ONLY UTILIZING THE WESTERN PORTION OF THE ROAD THROUGH THE INTERSECTION.

REMOVE EXISTING PAVEMENT, SIDEWALK, LIGHTING, AND CURB & GUTTER ON THE EASTERN PORTION OF THE EUCLID INTERSECTION. CONSTRUCT CURB & GUTTER, SIDEWALK, TRAFFIC SIGNAL EQUIPMENT, STREETSCAPE ELEMENTS AND LIGHTING.

### STAGE 6C

UTILIZE MOVING LANE CLOSURES FROM THE EAST SIDE OF OAK PARK AVE TO THE EAST PROJECT LIMIT.

PAVE HMA SURFACE COURSE FROM THE EAST SIDE OF OAK PARK AVE TO THE EAST PROJECT LIMIT.


### <u>NOTES</u>


- THE SEQUENCING DESCRIBED ON THIS SHEET IS SUPPLEMENTAL INFORMATION, INFORMATION SHOWN ON STAGING SHEETS SHALL TAKE PRECEDENCE.
- ALL SHORT TERM TEMPORARY DETOUR ROUTES FOR LOCAL ROAD CLOSURES SHALL BE INSTALLED, MAINTAINTED, AND REMOVED AS DIRECTED BY THE ENGINEER. ALL LABOR, TOOLS, EQUIPMENT, AND MATERIAL REQURIED TO COMPLETE THIS WORK SHALL BE INCLUDED IN THE COST OF TRAFFIC CONTROL AND PROTECTION (SPECIAL).

USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 2.00000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

_	SUGGESTED MAINTENANCE OF TRAFFIC SEQUENCE OF CONSTRUCTION		SECTION	COUNTY	TOTAL SHEETS	SHEE NO.
			16-00264-00-PV	COOK	344	90
				CONTRACT	NO. 6	1F36
	SCALE: NTS   SHEET 5 OF 33 SHEETS   STA. TO STA.		ILLINOIS FED. AI	D PROJECT		







DRAWN - JBH REVISED CHECKED - BLP REVISED PLOT DATE = 11/15/2019 DATE - 11/15/2019 REVISED


STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

LAKE STREET - STAGE 1 SCALE: 1"=20" SHEET 7 OF 33 SHEETS STA. TO STA.

16-00264-00-PV СООК 1405 CONTRACT NO. 61F36










USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 40.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -




### NOTE

 ALL TEMPORARY PAVEMENT MARKINGS AND SIGNS INSTALLED DURING STAGE 1 SHALL REMAIN IN PLACE FOR STAGE 1A, UNLESS OTHERWISE NOTED.

# TEMPORARY PAVEMENT MARKING LEGEND A PAVEMENT MARKING TAPE, TYPE III - LETTERS & SYMBOLS (70300510) B PAVEMENT MARKING TAPE, TYPE III - LINE 4", SOLID WHITE (70300520) C PAVEMENT MARKING TAPE, TYPE III - LINE 4", YELLOW SKIP-DASH (70300520) D PAVEMENT MARKING TAPE, TYPE III - LINE 4", DOUBLE YELLOW (70300520) E PAVEMENT MARKING TAPE, TYPE III - LINE 6", SOLID WHITE (70300540) F PAVEMENT MARKING TAPE, TYPE III - LINE 6", WHITE DOTTED (70300540) G PAVEMENT MARKING TAPE, TYPE III - LINE 4", YELLOW DOTTED (70300520) H PAVEMENT MARKING TAPE, TYPE III - LINE 24", SOLID WHITE (70300570) I PAVEMENT MARKING TAPE, TYPE III - LINE 4", SOLID YELLOW (70300560) K PAVEMENT MARKING TAPE, TYPE III - LINE 12", SOLID YELLOW (70300560)








HORIZONTAL	SCALE	IN	FEET	
	00.122			



JSER NAME = TEG	DESIGNED - VJM	REVISED -	
	DRAWN - JBH	REVISED -	
PLOT SCALE = 40.0000 '/ in.	CHECKED - BLP	REVISED -	
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -	





Ω	10	20	40
ĭ	ĭ	٦	٦٢

HORIZONTAL SCALE IN FEET



USER NAME = TEG	DESIGNED - VJM	REVISED -
	DRAWN - JBH	REVISED -
PLOT SCALE = 40.0000 '/ in.	CHECKED - BLP	REVISED -
PLOT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -





DESIGNED - VJM REVISED DRAWN - JBH REVISED PLOT SCALE = 40.0000 '/ in. CHECKED - BLP REVISED PLOT DATE = 11/15/2019 - 11/15/2019 REVISED

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

SUGGESTED MAINTENANCE OF TRAFFIC LAKE STREET - STAGE 1B SCALE: 1"=20" SHEET 14 OF 33 SHEETS STA. TO STA.

COUNTY TOTAL SHEET NO.

COOK 344 99 SECTION 16-00264-00-PV CONTRACT NO. 61F36

1405



## TEMPORARY PAVEMENT MARKING LEGEND A PAVEMENT MARKING TAPE, TYPE III - LETTERS & SYMBOLS (70300510)

B PAVEMENT MARKING TAPE, TYPE III - LINE 4", SOLID WHITE (70300520)

C PAVEMENT MARKING TAPE, TYPE III - LINE 4", YELLOW SKIP-DASH (70300520)

PAVEMENT MARKING TAPE, TYPE III - LINE 4", DOUBLE YELLOW (70300520)

E PAVEMENT MARKING TAPE, TYPE III - LINE 6", SOLID WHITE (70300540)

F PAVEMENT MARKING TAPE, TYPE III - LINE 6", WHITE DOTTED (70300540)

PAVEMENT MARKING TAPE, TYPE III - LINE 4", YELLOW DOTTED (70300520)

PAVEMENT MARKING TAPE, TYPE III - LINE 24", SOLID WHITE (70300570)

PAVEMENT MARKING TAPE, TYPE III - LINE 4", SOLID YELLOW (70300520)


PAVEMENT MARKING TAPE, TYPE III - LINE 12", SOLID YELLOW (70300560)

K PAVEMENT MARKING TAPE, TYPE III - LINE 12", SOLID WHITE (70300560)

## MAINTENANCE OF TRAFFIC LEGEND WORK ZONE AREA TEMPORARY SIGN ON PORTABLE OR PERMANENT SUPPORT DRUM OR TYPE II BARRICADE TRAFFIC CONTROL DEVICE SPACING 50° C-C ON TANGENTS


25' C-C ON TAPERS OR LANE SHIFTS

TYPE III BARRICADE 12' C-C ON RADII



### NOTE

 ALL TEMPORARY PAVEMENT MARKINGS AND SIGNS INSTALLED DURING STAGE 1 AND 1A SHALL REMAIN IN PLACE FOR STAGE 1B, UNLESS OTHERWISE NOTED.



HORIZONTAL SCALE IN FEE



SER NAME = TEG	DESIGNED - VJM	REVISED -	
	DRAWN - JBH	REVISED -	
OT SCALE = 40.0000 '/ in.	CHECKED - BLP	REVISED -	
OT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -	
OT DATE = 11/15/2019	DATE - 11/15/2019	REVISED -	