







ILLINOIS TOLLWAY LEGEND PROPOSED

- 1 PORTLAND CEMENT CONCRETE PAVEMENT 10" (JOINTED)
- 2 PORTLAND CEMENT CONCRETE PAVEMENT 12" (JOINTED)
- 3 CONTINUOUSLY REINFORCED P.C.C. PAVEMENT 12"
- 4 SUBGRADE AGGREGATE, 12"
- 5 SUBGRADE AGGREGATE SPECIAL, 6"
- G DRILLED AND GROUTED IN PLACE, TIE BARS 3/4" X 24" AT 24" CTS. (INCLDED IN COST OF PAVEMENT)
- 7 GUTTER, TYPE G-2
- 8 GUTTER, TYPE G-2 MODIFIED
- [9] HOT-MIX ASPHALT SHOULDERS, 6"
- [10] STABILIZED SUBBASE HOT-MIX ASPHALT, 4"
- 11) AGGREGATE SHOULDERS, TYPE B
- [12] AGGREGATE SHOULDERS SPECIAL, TYPE C
- [13] GALVANIZED STEEL PLATE BEAM GUARDRAIL, 6' POSTS
- [14] SOLDIER PILE RETAINING WALL WITH 42" CONCRETE BARRIER
- [15] TOPSOIL EXCAVATION AND PLACEMENT, 8"
- 16 SEEDING
- 17 PIPE UNDERDRAINS, FABRIC LINED TRENCH 6"
- 18 SLOPE WALL (SEE BRIDGE DRAWINGS)
- 19 PORTLAND CEMENT CONCRETE SHOULDER 8"
- 20 RIGHT OF WAY FENCE, 6'
 - COMBINATION CONCRETE CURB & GUTTER, TYPE B-6.24 (SEE NOTE 5)
- [22] AGGREGATE SHOULDERS, TYPE A 10"
- NO. 6 TIE BAR AT 24" LONG, DEFORMED (EPOXY COATED) AT 24" CTS. (INCLUDED IN THE COST OF THE PROPOSED CURB AND GUTTER)

NOTES

- 1. SEE CROSS SECTIONS FOR GRADING INFORMATION.
- 2. SEE LANDSCAPING PLANS FOR SEEDING AND SODDING INFORMATION.
- 3. SEE PLANS FOR PLACEMENT OF GUARDRAIL
- 4. SEE UNDERDRAIN PLANS FOR PLACEMENT OF UNDERDRAINS
- 5. LIMITS OF CURB & GUTTER ARE FROM STA. 1002+46.3 TO STA. 1003+56 SEE PLANS FOR ADDITIONAL INFORMATION.
- 6. R.O.W. FENCES ARE SHOWN OFF R.O.W. FOR CLARITY, FENCES SHALL BE PLACED ALONG THE R.O.W.

FILE NAME =	USER NAME = \$USER\$	DESIGNED PJO	REVISED -		TYPICAL SECTIONS I—88 RAMP A			F.A.P. RTE	SECTION	COUNTY	TOTAL SHEET
\$FILEL\$		DRAWN KES	REVISED -	STATE OF ILLINOIS				338	(112 & 113) WRS-5	DUPAGE	963 58
	PLOT SCALE = \$SCALE\$	CHECKED JCM	REVISED -	DEPARTMENT OF TRANSPORTATION						CONTRACT	F NO. 60I31
	PLOT DATE = \$DATE\$	DATE 10/15/2012	REVISED -		SCALE:	SHEET NO. 12 OF 17 SHEETS	STA. TO STA.		ILLINOIS FED. AID PROJECT		