



STORMPIPES					
NO.	TYPE	LENGTH (LF)	DIA (IN)	SLOPE	TBF (CY)
P-18	SS, CLA, TYPE 1	9	12	2.00%	1.6
P-19	SS (WATER MAIN REQUIREMENTS)	11	12	5.00%	2.9
P-20	SS, CLA, TYPE 1	11	12	2.00%	1.5
P-21	SS (WATER MAIN REQUIREMENTS)	24	12	2.00%	4.9
P-22	SS (WATER MAIN REQUIREMENTS)	12	12	5.00%	3.3
P-22A	SS (WATER MAIN REQUIREMENTS)	4	12	1.75%	0.8
P-23	SS, CLA, TYPE 1	11	12	6.09%	1.5

STORMSTRUCTURES						
NO.	STATION	OFFSET	TYPE	FRAME	RIM/EP	INVERTS
IN-17	214+02	22.4' RT	INLET, TYPE A	TY 1 FR, CLUD	641.61 RIM	638.98 15" W (EX); 12" S (EX-FIELD VERIFY); 639.00 12" SE
IN-16	213+96	29.5' RT	INLET, TYPE A	TY 24 F&G	641.48 EP	639.18 12" NW
EX CB-12	213+99	28.8' LT	EX CATCH BASIN	TY 1 FR, CLUD	-	634.87 18" S (EX); 635.32 18" E (EX); 636.85 12" W
CB-17	213+98	40.5' LT	CATCH BASIN, TYPE C	TY 24 F&G	641.25 EP	637.40 12" E
EX CB-13	215+03	18.9' RT	EX CATCH BASIN	TY 1 FR, CLUD	-	638.41 12" NE (EX); 636.76 12" W (EX); 638.35 12" SE
IN-18	214+94	29.5' RT	INLET, TYPE A	TY 24 F&G	641.20 EP	638.57 12" NW
EX MH-4	215+45	28' LT	EX MANHOLE	EXISTING	-	633.08 10" NW (EX); 630.18 21" NE (EX); 631.98 42" N (EX); 629.38 42" S (EX); 636.92 12" S
CB-19	215+21	32' LT	CATCH BASIN, TYPE C	TY 24 F&G	640.83 EP	637.38 12" N
EX CB-15	216+46	23.5' LT	EX CATCH BASIN	TY 1 FR, CLUD	-	636.23 12" W (EX); 636.27 12" E (EX); 636.39 12" NW
CB-20	216+56	29.3' LT	CATCH BASIN, TYPE C	TY 24 F&G	640.95 EP	637.35 12" W; 637.00 12" SE
IN-1	216+57	35' LT	INLET, TYPE A	TY 8 GRATE	640.70 RIM	637.77 6" W (EX); 637.42 12" E
EX CB-16	216+45	19' RT	EX CATCH BASIN	TY 1 FR, CLUD	-	636.88 12" W (EX); 638.33 12" NE
IN-21	216+50	29.4' RT	INLET, TYPE A	TY 24 F&G	640.95 EP	639.00 12" SW

# PLEASANT LANE WAUKEGAN ROAD (IL-43)

