

NOTES:

- 1. DELINEATORS, SPECIAL shall be constructed of 4" \times 4" \times 6' (100 \times 100 \times 1.83 m) treated timber.
- 2. Each post shall be buried a minimum of 36(900) deep.
- 3. Timber shall be treated in accordance with Article 1007.12 of the Standard Specifications. Waterborne Preservatives, ASA and CCA, shall have A 0.40 lbs/ft³(6.4 kg/m³) minimum retention.
- 4. Amber Reflectors shall meet the requirements of Article 1097.03 of the Standard Specifications.

All slope ratios are expressed as units of vertical displacement to units of horizonal displacement (V:H).

All dimensions are in inches (millimeters) unless otherwise noted.

01-01-97 RENUM. E-10.01, METRICS, NEW REVISION BOX, ADDED T.P.	8-8-12 REVISED NOTES R.D.				F.A.P SI	ECTION	COUNTY	TOTAL SHEET
DESIGNER NOTE, REVISED GENERAL NOTES, REVISED		STATE OF ILLINOIS	DELINEATORS-SPECIAL		313 7-	2 : 6-1	HENDERSON	976 570
TITLE BOX		DEPARTMENT OF TRANSPORTATION				•	CONTRACT	NO. 68409
10-16-06 REVISED TO 2007 SPEC. M.A.			NOT TO SCALE	CADD STD. 635001-D4	FED. ROAD DIST. NO.	ILLINOIS FED. A		