

GENERAL NOTES

THE THICKNESS OF HOT-MIX ASPHALT MIXTURE SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HOT-MIX ASPHALT MIXTURE IS PLACED.

FACTORS USED FOR ESTIMATING PLAN QUANTITIES ARE AS FOLLOWS:

ALL HOT MIX ASPHALT	2.016 TONS/CU YD
BITUMINOUS MATERIALS ON PAVEMENT:	0.09 GAL /SQ YD
AGGREGATE (PRIME COAT)	0.0015 GAL /SQ YD
ALL AGGREGATE	2.05 TON /SQ YD
RIP RAP	1.50 TON /SQ YD

PLAN DIMENSIONS AND DETAILS RELATIVE TO THE EXISTING STRUCTURE HAVE BEEN TAKEN FROM EXISTING PLANS AND ARE SUBJECT TO NOMINAL CONSTRUCTION VARIATIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY SUCH DIMENSIONS AND DETAILS IN THE FIELD AND MAKE NECESSARY APPROVED ADJUSTMENTS PRIOR TO CONSTRUCTION OR ORDERING OF MATERIALS. SUCH VARIATIONS SHALL NOT BE CAUSE FOR ADDITIONAL COMPENSATION FOR A CHANGE IN THE SCOPE OF THE WORK. THE CONTRACTOR, HOWEVER, WILL BE PAID FOR THE ACTUAL QUANTITY FURNISHED AT THE UNIT PRICE BID FOR THE WORK. CONSTRUCTION PLANS ARE AVAILABLE FOR REVIEW AT THE DISTRICT 9 OFFICE.

IN ADDITION TO THE REQUIREMENTS OF ARTICLE 107.16 THE CONTRACTOR SHALL PROTECT THE SURFACE OF ALL BRIDGE DECK AND BRIDGE APPROACH PAVEMENTS IN A MANNER SATISFACTORY TO THE ENGINEER BEFORE ANY EQUIPMENT IS ALLOWED TO CROSS THE STRUCTURE. PROTECTION SHALL BE PROVIDED FOR ALL EQUIPMENT AS DEFINED IN ARTICLE 101.17 REGARDLESS IF TRACK MOUNTED OR WHEELED.

AT ALL LOCATIONS WHERE HOT MIX ASPHALT OR CONCRETE PAVEMENT JOINS AN EXISTING HOT MIX ASPHALT OR CONCRETE PAVEMENT, A SAWED JOINT SHALL BE CONSTRUCTED. THE COST OF THIS JOINT SHALL BE INCLUDED IN THE TYPE OF PAVEMENT BEING CONSTRUCTED.

REMOVAL OF THE EXISTING 10 1/2 " MINIMUM AND VARIABLE THICK BRIDGE APPROACH PAVEMENTS, RESURFACED CONCRETE PAVEMENT AND WIDENING ARE INCLUDED IN THE QUANTITY FOR "PAVEMENT REMOVAL - SQ YD".

TREES SHALL BE PRESERVED THROUGHOUT THIS SECTION AS SHOWN ON THE PLANS AND AS DIRECTED BY THE ENGINEER. GENERALLY, TREES OUTSIDE THE CONSTRUCTION LIMITS, AND WHICH DO NOT INTERFERE WITH CONSTRUCTION, SHALL NOT BE DISTURBED.

IT WILL BE THE CONTRACTOR'S RESPONSIBILITY TO REMOVE ANY DEBRIS OR DIRT CAUSED BY CONSTRUCTION ACTIVITY THAT COVERS THE NEW RIP RAP AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.

ALL TEMPORARY EROSION CONTROL MEASURES SHALL BE LEFT IN PLACE UNTIL REMOVAL IS REQUIRED TO CONSTRUCT FINAL GRADE LINES.

PRIOR TO PLACEMENT OF THE FINAL PAVEMENT MARKINGS THE RESIDENT ENGINEER SHOULD CONTACT THE BUREAU OF OPERATIONS AND ARRANGE FOR INSPECTION AND APPROVAL OF THE PAVEMENT MARKING LAYOUT.

COST OF REMOVING HOT MIX ASPHALT BASE COURSE WIDENING, 10" USED FOR STAGE I TRAFFIC IS INCLUDED IN THE QUANTITY FOR "PAVED SHOULDER REMOVAL - SQ YD".

THE ADVANCE DETECTOR LOOPS ARE TYPICALLY LOCATED 275 FEET IN ADVANCE OF THE STOP BAR. THE BUREAU OF OPERATIONS SHOULD APPROVE THE LOOP LOCATIONS PRIOR TO INSTALLATION.

THE CENTERLINE PAVEMENT MARKING SHOULD BE REMOVED FROM THE STOP BAR TO THE SAND ATTENUATORS OR DRUMS. EDGE LINE PAVEMENT MARKING SHOULD BE REMOVED IF A 10 FOOT LANE WIDTH CANNOT BE MAINTAINED. TEMPORARY EDGE LINES SHOULD BE INSTALLED WHEN THE EDGE LINES ARE REMOVED.

THE BARRIER WALL AND GUARDRAIL REFLECTORS AS SHOWN ON STANDARD 701321 SHALL BE INSTALLED PRIOR TO OPENING TO TRAFFIC.

ANY TIME THE CONCRETE BARRIER IS NOT IN THE PROPER POSITION, FLAGGERS SHALL BE IN PLACE TO CONTROL TRAFFIC. THE TEMPORARY TRAFFIC SIGNALS SHALL BE SET TO FLASH ALL RED.

TRIM EDGES OF EXISTING HOT MIX ASPHALT SURFACE FLUSH WITH EXISTING PAVEMENT PRIOR TO CONSTRUCTING NEW BASE COURSE WIDENING.

THE HOT MIX ASPHALT BASE COURSE WIDENING, 10" CONSTRUCTED IN PRE-STAGE 1 MAY BE INCORPORATED INTO THE FINAL HOT MIX ASPHALT SHOULDERS, 8" DURING STAGE II CONSTRUCTION IF APPROVED BY THE ENGINEER. SUCH CHANGE WILL NOT BE CAUSE FOR ADDITIONAL COMPENSATION, BUT THE CONTRACTOR WILL BE PAID FOR THE ACTUAL QUANTITY FURNISHED AT THE UNIT PRICE BID FOR THE WORK.

THE REMOVAL OF THE EXISTING CONCRETE SLOPE WALLS IS INCLUDED IN THE QUANTITY OF "REMOVAL OF EXISTING STRUCTURES - EACH".

THE PROPOSED BRIDGE APPROACH PAVEMENT CURB SHALL EXTEND OVER THE BRIDGE APPROACH PAVEMENT CONNECTOR FROM STA. 227+30 RT. TO STA. 227+36 RT. AND IS INCLUDED IN THE QUANTITY OF "TYPE E INLET BOX, STANDARD 610001 - EACH".

COMMITMENTS:

SEE THE CONTRACT SPECIAL PROVISIONS FOR ENVIRONMENTAL COMMITMENTS.

STANDARDS

000001-06	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001001-02	AREAS OF REINFORCEMENT BARS
280001-07	TEMPORARY EROSION CONTROL SYSTEMS
420001-07	PAVEMENT JOINTS
420401-09	BRIDGE APPROACH PAVEMENT CONNECTOR
515001-03	NAME PLATE FOR BRIDGES
542401-01	METAL END SECTION FOR PIPE CULVERTS
610001-06	SHOULDER INLET WITH CURB
630001-10	STEEL PLATE BEAM GUARDRAIL
630201-06	PCC/BITUMINOUS STABILIZATION AT STEEL PLATE BEAM GUARDRAIL
630301-06	SHOULDER WIDENING FOR TYPE I (SPECIAL) GUARDRAIL TERMINALS
631031-11	TRAFFIC BARRIER TERMINAL, TYPE 6
635006-03	REFLECTOR AND TERMINAL MARKER PLACEMENT
635011-02	REFLECTOR MARKER AND MOUNTING DETAILS
701006-04	OFF-RD OPERATIONS, 2L, 2W, 15' TO 24" AWAY, FOR SPEEDS ≥ 45 MPH
701201-04	LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS ≥ 45 MPH
701301-04	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS, FOR SPEEDS ≥ 45 MPH
701321-13	LANE CLOSURE, 2L, 2W, BRIDGE REPAIR WITH BARRIER
701326-04	LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING, FOR SPEEDS ≥ 45 MPH
701901-03	TRAFFIC CONTROL DEVICES
704001-07	TEMPORARY CONCRETE BARRIER
780001-03	TYPICAL PAVEMENT MARKINGS
781001-03	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

MIXTURE REQUIREMENTS

LOCATIONS(S):	BASE COURSE WIDENING
MIXTURE USE(S):	HOT-MIX ASPHALT BINDER COURSE, N90, IL-19.0
TYPICAL AC/PG:	PG64-22
RAP % (MAX):	10
DESIGN AIR VOIDS:	4.0 %, 90 GYRATION DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL-19.0 mm
FRICITION AGGREGATE:	NONE
LOCATIONS(S):	HOT-MIX ASPHALT SHOULDERS
MIXTURE USE(S):	HOT-MIX ASPHALT SHOULDERS
TYPICAL AC/PG:	PG58-22
RAP % (MAX):	50
DESIGN AIR VOIDS:	2.0 %, 30 GYRATION DESIGN
MIXTURE COMPOSITION: (GRADATION MIXTURE)	HMA SHOULDERS
FRICITION AGGREGATE:	NONE

Prepared By:	<i>Joe Zamboniewicz</i> DISTRICT STUDIES & PLANS ENGINEER
Examined By:	<i>Joe Zamboniewicz</i> DISTRICT LAND ACQUISITION ENGINEER
Examined By:	<i>Conrad Kelly</i> DISTRICT PROGRAM DEVELOPMENT ENGINEER
Examined By:	<i>Keith Kelly</i> DISTRICT OPERATIONS ENGINEER
Examined By:	<i>Douglas McElroy</i> DISTRICT CONSTRUCTION ENGINEER
Examined By:	<i>Bruce Panko</i> DISTRICT MATERIALS ENGINEER
Approved By:	<i>James O'Connor</i> DEPUTY DIRECTOR OF HIGHWAYS, REGION 5 ENGINEER
	Oct 15 2012 DATE

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SIGNATURES, INDEX OF SHEETS, GENERAL NOTES, AND STANDARDS

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
885	11B-1	HARDIN	50	2
				CONTRACT NO. 78152
ILLINOIS FED. AID PROJECT				

FILE NAME: c:\pwworkspace\100824231\78152-11b-1\100824231-11b-1.dgn

USER NAME: portera	DESIGNED: _____	REVISED: _____
PLOT SCALE: 1/8" = 1'	DRAWN: _____	REVISED: _____
PLOT DATE: 10/15/2012	CHECKED: _____	REVISED: _____
	DATE: _____	REVISED: _____

SCALE: _____ SHEET NO. _____ OF _____ SHEETS STA. _____ TO STA. _____