



DEWATERING IMPOUNDMENTS:
 ALL DEWATERING SHALL BE IN ACCORDANCE WITH SECTION 614.
 POND D SHALL BE COMPLETELY DEWATERED PRIOR TO PLACEMENT OF FILL.
 PONDS A, B, AND C MAY BE PARTIALLY OR COMPLETELY DEWATERED AS THE CONTRACTOR REQUIRES TO FACILITATE EARTH MOVING OPERATIONS.

POINT OF INTERSECTION
 N: 1,057,050
 E: 2,227,900

BEGIN BASELINE
 N: 1,056,027
 E: 2,227,900

Stone Riprap RR3
 11' Wx32' L (38 S.Y.)

Temporary haul road.
 Creek crossing required.

Perform Special Excavation (See detail 13)

Install Mine Opening Marker. (See detail 13)
 Exact location to be marked by the Engineer.

Aggregate surface course, Type B - 6" thick

Pntno: 905(R)
 E=2227501.87
 N=1056695.94
 Z=612.00

Legend

- 500 — EXISTING CONTOUR
- 500 — PROPOSED CONTOUR
- - - - - EDGE OF MINE REFUSE
- - - - - CONSTRUCTION LIMITS
- - - - - EDGE OF ROAD
- — — — — TREELINE
- — — — — EDGE OF WATER
- ⊕ SURVEY CONTROL POINT

Aley Mine

0 40 50
 SCALE IN FEET

State of Illinois
 Department of Natural Resources

Aley Mine
 Reclamation Project
 AML-GStE-0605
 Scott County

Drawn By: _____
 Checked By: _____
 Date: _____

Existing and Proposed
 Conditions
 Sheet
 4 of 13