



UNSUITABLE MATERIAL TO BE REMOVED AND PLACED IN LOWER LAYER OF FILL AT BASE OF HIGHWALL (APPROX. 2,440 C.Y.)

EXISTING PARSHALL FLUME & PIPE CULVERT TO BE REMOVED (INCIDENTAL TO EARTH EXCAVATION)

UNSUITABLE MATERIAL TO BE REMOVED AND PLACED IN LOWER LAYER OF FILL AT BASE OF HIGHWALL (APPROX. 2,440 C.Y.)

EXISTING ACIDIC IMPOUNDMENT TO BE NEUTRALIZED & DEWATERED (INCIDENTAL TO EARTH EXCAVATION) VOLUME APPROX. 72,145 GALLONS pH 3.4

MONITORING WELL MW-2B TO REMAIN

MONITORING WELLS MW-3, MW-2A, AND MW-5B TO BE REMOVED (INCIDENTAL EARTH EXCAVATION)

EXISTING HIGHWALL TO BE BACKFILLED ANY LOOSE ROCK OR OVERHANGS TO BE REMOVED PRIOR TO BACKFILLING (INCIDENTAL TO EARTH EXCAVATION)

EXISTING IMPOUNDMENT TO BE DEWATERED (INCIDENTAL TO EARTH EXCAVATION) VOLUME APPROX. 96,640 GALLONS pH 7.7

Legend

- - - - - EXISTING CONTOUR
- 500 — PROPOSED CONTOUR
- - - - - CONSTRUCTION LIMITS
- — — — — EDGE OF ROAD
- ~~~~~ TREELINE
- - - - - EDGE OF WATER
- ◆ B-# - BORING
- ▲ AS-# - ACID SEEP
- ⊙ SURVEY CONTROL POINT

Tab Simco Phase III

0 50 100
SCALE IN FEET

Date: _____

Drawn By: _____

Checked By: _____