


PROPOSED TYPICAL SECTION
STA. 259+77.73 TO STA. 265+99.88

- * 0' @ STA. 259+77.73 TO 7.01' @ STA. 261+94.35
- 0' @ STA. 261+94.35 TO 7.01' @ STA. 265+99.88
- ** 6' FROM STA. 259+77.73 TO STA. 261+94.35
- 6' @ STA. 261+94.35 TO 4.05' STA. 265+99.88
- ③ TRANSITION CROSS SLOPE FROM 2% TO 1.7% FROM STA. 265+00 TO STA. 266+00

REMOVAL AND DISPOSAL OF UNSUITABLE MATERIAL *		
STATION RANGE	WIDTH	DEPTH BELOW SUB-GRADE
STA. 222+55.00 TO STA. 225+20.00	33.58' - 45.58' RT. TO 33.58' LT.	2.00'
STA. 238+10.00 TO STA. 240+27.00	33.58' RT. TO 33.58' LT.	2.00'
STA. 240+27.00 TO STA. 244+20.00	EX. LT. EOP TO 33.58' LT.	1.00' **
STA. 244+20.00 TO STA. 247+82.00	33.58' RT. TO 33.58' LT.	2.00'
STA. 247+82.00 TO STA. 253+72.00	EX. LT. EOP TO 33.58' LT.	0.67' **
STA. 253+72.00 TO STA. 259+77.00	33.58' RT. TO 33.58' LT.	2.00' **
STA. 259+77.00 TO STA. 260+95.00	41.17' RT. TO 41.17' LT.	2.00'

* ALL EXCAVATED MATERIAL FROM THE NATURAL GROUND SURFACE TO DEPTH BELOW SUBGRADE AS SHOWN IS UNSUITABLE AND IS TO BE WASTED OFF SITE, WITH THE EXCEPTION OF TOPSOIL EXCAVATION.

** UNDERCUT AREA TO BE REPLACED WITH APPROVED EMBANKMENT MATERIAL OR AS DIRECTED BY THE ENGINEER.



PROPOSED TYPICAL SECTION
STA. 265+99.88 TO STA. 270+78.11

- * 13.01' @ STA. 265+99.88 TO 0' @ STA. 269+39.12
- ** 7.01' @ STA. 265+99.98 TO 0' STA. 267+07.92