

PIPE UNDERDRAIN 4"	
STATION	LENGTH
RT. STA. 1527+70 TO 1531+14	344 FT
RT. STA. 1531+14 TO 1534+58	344 FT
RT. STA. 1534+58 TO 1538+00	342 FT
RT. STA. 1545+60 TO 1549+30	370 FT
RT. STA. 1549+30 TO 1553+00	370 FT
RT. STA. 992+50 TO 995+00	250 FT
TOTALS	2,020 FT

PIPE UNDERDRAIN 4" (SPECIAL)		
STATION	OFFSET	LENGTH
RT. STA. 1527+70	20 FT	20 FT
RT. STA. 1531+14	20 FT	20 FT
RT. STA. 1534+58	20 FT	20 FT
RT. STA. 1538+00 *	20 FT	20 FT
RT. STA. 1545+60	20 FT	20 FT
RT. STA. 1549+30	20 FT	20 FT
RT. STA. 1553+00 *	20 FT	20 FT
RT. STA. 992+50 *	20 FT	20 FT
RT. STA. 995+00	20 FT	20 FT
TOTALS		180 FT

* TO BE CONNECTED TO EXIST.
PIPE UNDERDRAIN

NOTES:

STATIONS ARE APPROXIMATE.

CONCRETE HEADWALLS FOR PIPE DRAINS	
STATION	OFFSET
RT. STA. 1527+70	20 FT
RT. STA. 1531+14	20 FT
RT. STA. 1534+58	20 FT
RT. STA. 1538+00 *	20 FT
RT. STA. 1545+60	20 FT
RT. STA. 1549+30	20 FT
RT. STA. 1553+00 *	20 FT
RT. STA. 992+50 *	20 FT
RT. STA. 995+00	20 FT

* TO BE CONNECTED TO EXIST.
PIPE UNDERDRAIN

MIXTURE REQUIREMENTS		
THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT		
MIXTURE USE(S):	H.M.A. SHLD, TOP 2"	H.M.A. SHLD, LOWER LIFTS
AC/PG	PG 64-22	PG 58-22
DESIGN AIR VOIDS:	4.0% @ N DESIGN = 50	2.0% @ N DESIGN = 30
MIXTURE COMP:	IL 9.5 OR 12.5	BAM
FRICITION AGG:	MIX C	N/A

SCHEDULES
VARIOUS
SECTION D6 SHOULDER REPAIR 2012
PIKE COUNTY