

GENERAL NOTES

- Fasteners shall be AASHTO M164 Type 1, mechanically galvanized bolts. Bolts 7/8 in. ϕ , holes 1 1/8 in. ϕ , unless otherwise noted.
- Calculated weight of Structural Steel = 1,551,450 pounds (AASHTO M270 Grade 50, Both Structures) = 106,360 pounds (AASHTO M270 Grade 36, Both Structures)
- No field welding is permitted except as specified in the contract documents.
- Reinforcement bars shall conform to the requirements of ASTM A 706 Gr 60. See Special Provisions.
- Reinforcement bars designated (E) shall be epoxy coated.
- If the Contractor elects to use cantilever forming brackets on the exterior beams or girders, the brackets shall be placed at the same locations as required for the hardwood blocks in Article 503.06(b) of the Standard Specifications. If additional cantilever forming brackets are required, hardwood blocking shall be wedged between the exterior and first interior beam at each of these additional bracket locations.
- Bearing seat surfaces shall be constructed or adjusted to the designated elevations within a tolerance of 1/8 inch (0.01 ft.). Adjustment shall be made either by grinding the surface or by shimming the bearings.
- The existing structural steel coating contains lead. The Contractor shall take appropriate precautions to deal with the presence of lead on this project.
- The Inorganic Zinc Rich Primer / Acrylic / Acrylic Paint System shall be used for shop and field painting of new structural steel except where otherwise noted. The color of the final finish coat for all interior steel surfaces shall be gray, Munsell No. 5B 7/1. The color of the final finish coat for the exterior and bottom flange of the fascia beams shall be gray, Munsell No. 5B 7/1. See Standard Specifications.
- The embankment configuration shown shall be the minimum that must be placed and compacted prior to construction of the abutments.
- Two 1/8 in. adjusting shims shall be provided for each bearing in addition to all other plates or shims and placed as shown on bearing details.
- The Contractor is advised that the existing structure contains members that are in a deteriorated condition with reduced load carrying capacity. It is the Contractor's responsibility to account for the condition of the existing structure when developing construction procedures for the complete or partial removal, or replacement of the structure. An Existing Structure Information Package is available upon request as noted in the special provisions.

TOTAL BILL OF MATERIAL

ITEM	UNIT	SUPER	SUB	TOTAL
Subbase Granular Material, Type C	CU YD	230		230
Removal of Existing Structures No. 1	EACH			1
Removal of Existing Structures No. 2	EACH			1
Protective Shield	SQ YD	592		592
Structure Excavation	CU YD		506	506
Concrete Structures	CU YD		753.0	753.0
Concrete Superstructure	CU YD	1.099		1.099
Bridge Deck Grooving	SQ YD	2,960		2,960
Protective Coat	SQ YD	3,695		3,695
Precast Concrete Bridge Slab	SQ FT	5,020		5,020
Furnishing and Erecting Structural Steel	L SUM	1		1
Stud Shear Connectors	EACH	10,440		10,440
Reinforcement Bars, Epoxy Coated	POUND	306,090	149,210	455,300
Mechanical Splicers	EACH		512	512
Slope Wall 4"	SQ YD		32	32
Furnishing Steel Piles HP12x53	FOOT		7,366	7,366
Driving Piles	FOOT		7,366	7,366
Test Pile Steel HP12x53	EACH		6	6
Pile Shoes	EACH		132	132
Name Plates	EACH	2		2
Elastomeric Bearing Assembly, Type I	EACH		10	10
Elastomeric Bearing Assembly, Type II	EACH		10	10
Anchor Bolts, 1"	EACH		20	20
Anchor Bolts, 1/2"	EACH		40	40
Geocomposite Wall Drain	SQ YD		230	230
Temporary Mechanically Stabilized Earth Retaining Wall	SQ FT		7,228	7,228
Porous Granular Embankment, Special	CU YD		333	333
Concrete Wearing Surface, 5"	SQ YD	558		558
Drainage Scupper, DS-II	EACH		1	1
Drainage System	L SUM		1	1
Temporary Sheet Piling	SQ FT		1,458	1,458
Mechanically Stabilized Earth Retaining Wall	SQ FT		674	674
Pipe Underdrains for Structures, 4"	FOOT		180	180
Bituminous Coated Aggregate Slope Wall 6"	SQ YD		1,168	1,168

INDEX OF SHEETS

- S-1. General Plan
- S-2. General Notes, B.O.M. & Index of Sheets
- S-3. Foundation Plan
- S-4. Temporary MSE Walls
- S-5. Stage Construction Deck Sections
- S-6. Temporary Concrete Barrier
- S-7. Deck Elevation Plan Eastbound
- S-8. Deck Elevations Eastbound
- S-9. Deck Elevations Eastbound
- S-10. Deck Elevation Plan Westbound
- S-11. Deck Elevations Westbound
- S-12. Deck Elevations Westbound
- S-13. West E.B. Approach Slab Elevations
- S-14. East E.B. Approach Slab Elevations
- S-15. West W.B. Approach Slab Elevations
- S-16. East W.B. Approach Slab Elevations
- S-17. Deck Plan Eastbound
- S-18. Deck Cross Section Eastbound
- S-19. Deck Plan Westbound
- S-20. Deck Cross Section Westbound
- S-21. West Superstructure Details
- S-22. East Superstructure Details
- S-23. Parapet Elevations, Details & B.O.M. Eastbound
- S-24. Parapet Elevations, Details & B.O.M. Westbound
- S-25. Drainage Scupper, DS-II
- S-26. Drainage System
- S-27. West Approach Slab Plan Eastbound
- S-28. East Approach Slab Plan Eastbound
- S-29. West Approach Slab Plan Westbound
- S-30. East Approach Slab Plan Westbound
- S-31. Eastbound Approach Slab Details
- S-32. Westbound Approach Slab Details
- S-33. Precast Concrete Bridge Slab
- S-34. Framing Plan & Girder Elevation
- S-35. Steel Details-Splices
- S-36. Steel Details & Moment Table
- S-37. Camber Diagram
- S-38. Bearings Details, Type I and Fixed
- S-39. Bearing Details, Type II
- S-40. West Abutment Plan and Elevation Eastbound
- S-41. East Abutment Plan and Elevation Eastbound
- S-42. West Abutment Plan and Elevation Westbound
- S-43. East Abutment Plan and Elevation Westbound
- S-44. Abutment Details
- S-45. Pier Plan and Elevation Eastbound
- S-46. Pier Details Eastbound
- S-47. Pier Plan and Elevation Westbound
- S-48. Pier Details Westbound
- S-49. Non-Structure Number Mechanically Stabilized Earth Retaining Wall
- S-50. Bar Splicer Assembly and Mechanical Splicer Details
- S-51. HP Pile Details
- S-52. Concrete Parapet Slipforming Option
- S-53. Boring Logs
- S-54. Boring Logs
- S-55. Boring Logs
- S-56. Boring Logs
- S-57. Boring Logs
- S-58. Boring Logs
- S-59. Boring Logs
- S-60. Boring Logs
- S-61. Boring Logs
- S-62. Boring Logs

CURRENT RATINGS ON FILE FOR EXISTING WESTBOUND STRUCTURE

Inventory: HS 25
 Operating: HS 41.8
 Live Load Restrictions: No


Inventory and Operating Ratings and Live Load Restrictions are provided for information only. Inventory and Operating Ratings are based on HS loading and configuration. Live Load Restrictions are based on Illinois legal loads and configurations. The Ratings and Live Load Restrictions are not necessarily representative of capacities to support the Contractor's equipment.

STATION 706+32.12
 BUILT 20L BY
 STATE OF ILLINOIS
 F.A.P. RT. 103 SEC. 27-1-VHB-1
 LOADING HL-93
 STRUCTURE NO. 082-0117


NAME PLATE (E.B.)
 See Std. 515001

STATION 706+32.12
 BUILT 20L BY
 STATE OF ILLINOIS
 F.A.P. RT. 103 SEC. 27-1-VHB-1
 LOADING HL-93
 STRUCTURE NO. 082-0118

NAME PLATE (W.B.)
 See Std. 515001




SECTION A-A



SECTION THRU EAST SLOPEWALL

**Slopewall 4" shall be reinforced with welded wire fabric, 6" x 6" - W4.0 x W4.0, weighing 58 lbs. per 100 sq. ft.



SECTION THRU WEST SLOPEWALL

FILE NAME = 0820117-0118-7684-022-GenNotes.dgn



USER NAME = krokm	DESIGNED - BTO	REVISED Δ 1/6/2012 RAB
PLOT SCALE = 0:2.0000 "/ IN.	CHECKED - JAN	REVISED -
PLOT DATE = 01/06/2012	DRAWN - RAB	REVISED -
	CHECKED - SAB	REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**GENERAL NOTES, B.O.M. & INDEX OF SHEETS
 STRUCTURE NO. 082-0117 (E.B.) & 082-0118 (W.B.)**

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
103	27-1-VHB-1	ST. CLAIR	277	117
			CONTRACT NO. 76884	
ILLINOIS FED. AID PROJECT				

SHEET NO. S-2 OF S-62 SHEETS