



**NOTE:**  
OVERHEAD SIGNALS SHALL HAVE  
A MINIMUM CLEARANCE OF  
15'-0" ABOVE PAVEMENT GRADE.

**NOTE:** ALL HOLES ARE TO BE DRILLED IN POLES OR POSTS.  
CARE SHOULD BE TAKEN TO SEE THAT NO MORE THAN  
TWO HOLES ARE DRILLED IN THE SAME HORIZONTAL  
PLANE SO AS NOT TO WEAKEN THE OVERALL  
STRENGTH OF THE MATERIAL.

DATE	REVISION
WORK ORDER NO.	DATE
EXIST ALLOCATION ACCOUNT	
APPROPRIATION ACCOUNT	MATERIAL LABOR
<b>TYPICAL TRAFFIC SIGNAL MOUNTING DETAILS</b>	
<b>CITY OF CHICAGO</b> DEPT. OF STREET AND SANITATION DIVISION OF ELECTRICITY OFFICE OF ELECTRICAL ENGINEERING	
DESIGNED BY: <i>R. F. ...</i>	CHECKED BY: <i>M. ...</i>
DATE OF DESIGN: <i>...</i>	DATE OF CHECK: <i>...</i>
ENGINEER OF ELECTRICITY: <i>...</i>	DATE OF FIELD CHECK: <i>...</i>
DATE OF FIELD CHECK: <i>...</i>	DATE OF FIELD CHECK: <i>...</i>
DATE: <i>...</i>	DATE: 12-10-84

REVISIONS	NAME	DATE

M:\P\40468\CVIN\4-CIT\94\064-Traffic\999-SIGNALS\BOE - ST AN\BOE064TS32A.DWG 10/25/2004 03:54:14 PM