

## NOTES

Anchor Concrete Barrier during Stage II Construction per Standard 704001.

Cost of anchorage is included with Temporary Concrete Barrier.

## SECTIONS THRU PAVEMENT, SLAB OR DECK BEAM

- \*\*\* Dimension shown is minimum required embedment into concrete.

  If hot-mix asphalt wearing surface is present, minimum embedment shall be in addition to wearing surface depth.
- \*\*\*\* If existing deck beam is to remain in place after stage construction, embedment shall only be into wearing surface and not into existing deck beam concrete.

Applied Technologies

| FILE NAME = CONCRETE BARRIER.DGN | USER NAME = RDS      | DESIGNED - | JRF  | REVISED - | STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION | TEMPORARY CONCRETE BARRIER FOR STAGE CONSTRUCTION | F.A.P.<br>RTE.            | SECTION | COUNTY | TOTAL SH<br>SHEETS | ET<br>O. |
|----------------------------------|----------------------|------------|------|-----------|--|---|---------------------------|---------|--------|--------------------|----------|
|                                  |                      | CHECKED -  | PAT2 | REVISED - |  | STRUCTURE NO. 016-0525                            | 343                       | 98-B    | соок   | 65                 | 0G       |
|                                  | PLOT SCALE = 1* = 1' | DRAWN -    | RDS  | REVISED - |  |   |                           |         |        | CT NO. 60H         | 20       |
|                                  | PLOT DATE = 12-15-10 | CHECKED -  | RCJ  | REVISED - |  | SHEET NO. 8 OF 9 SHEETS                           | ILLINOIS FED. AID PROJECT |         |        |                    |          |

EXISTING DECK BEAM