



- LEGEND**
- ① PROPOSED PORTLAND CEMENT CONCRETE SHOULDER, 12 1/4" (48300705)
  - ② PROPOSED STABILIZED SUBBASE - HOT-MIX ASPHALT, 4 1/2" (31200502)
  - ③ PROPOSED AGGREGATE SUBGRADE, 12" (20001050)
  - ④ PROPOSED CONCRETE BARRIER, DOUBLE FACE, 42 INCH HEIGHT (63700275)
  - ⑤ PROPOSED CONCRETE BARRIER, VARIABLE CROSS SECTION, 42" HEIGHT (X6370250)
  - ⑥ PROPOSED CONCRETE BARRIER, DOUBLE FACE (SPECIAL) (X0326445)
  - ▨ CLASS A PATCHES, 12 1/4"

**NOTES:**  
 SHOULDER CROSS-SLOPES INDICATED AT STATIONS ENDING IN +00 AND +50 THROUGHOUT SHOULDER WARPING AREAS.

TOP OF WALL	768+00	769+00	770+00	771+00	772+00	773+00	774+00	775+00	776+00	777+00	778+00	779+00	780+00	781+00	782+00	783+00
685	685.00	685.00	685.00	685.00	685.00	685.00	685.00	685.00	685.00	685.00	685.00	685.00	685.00	685.00	685.00	685.00
680	680.00	680.00	680.00	680.00	680.00	680.00	680.00	680.00	680.00	680.00	680.00	680.00	680.00	680.00	680.00	680.00
675	675.00	675.00	675.00	675.00	675.00	675.00	675.00	675.00	675.00	675.00	675.00	675.00	675.00	675.00	675.00	675.00
670	670.00	670.00	670.00	670.00	670.00	670.00	670.00	670.00	670.00	670.00	670.00	670.00	670.00	670.00	670.00	670.00
WB PCL	675.42	675.06	675.11	675.15	675.32	675.32	675.34	675.47	675.53	675.55	675.72	675.72	675.88	675.88	676.01	676.01
EB PCL	675.42	675.06	675.11	675.15	675.32	675.32	675.34	675.47	675.53	675.55	675.72	675.72	675.88	675.88	676.01	676.01
WB PCL	674.74	674.97	675.08	675.15	675.32	675.32	675.34	675.47	675.53	675.55	675.72	675.72	675.88	675.88	676.01	676.01
EB PCL	674.74	674.97	675.08	675.15	675.32	675.32	675.34	675.47	675.53	675.55	675.72	675.72	675.88	675.88	676.01	676.01