TRAFFIC SIGNAL LEGEND

\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	DRA		REVISED -	THE CONTROL OF THE PARTY OF THE	E OF ILLINOIS OF TRANSPORTATION			DISTRICT 1 STANDARD TRAFFIC SIGNAL DESIGN DETAILS		SECTION (58&59) WRS-3	DuPAGE 466 CONTRACT NO. 624
LE NAME = USER NAME = kanthaphixa		IGNED - DAG/BCK	REVISED -	NO. 6 SOLID COPPER (GREEN)		~			F.A. RTE.	SECTION	COUNTY TOTAL SHEETS
WIRELESS ACCESS POINT	R			GROUND CABLE IN CONDUIT		(1)	(1)	CROSSBUCK		≥	*
VIRELESS DETECTOR SENSOR	RW	(W)	(W)	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED			(5)	CROSSING GATE		X0X>	X0X=
AN, TILT, ZOOM CAMERA	R Frzh	Przh	<u> </u>	DENOTES NUMBER OF CONDUCTORS, ELECTRIC	LEKK	EKK	RR	FLASHING SIGNAL		$\times \Theta \times$	X ⊕ X
IDEO DETECTION ZONE				RADIO REPEATER	R ERR	ERR	•	RAILROAD CANTILEVER MAST ARM	:	XOX X	X eX X
IDEO DETECTION CAMERA	R V	Ŷ	V	RADIO INTERCONNECT	#I ^R O	##+0		RAILROAD CONTROL CABINET		B X	
ICROWAVE VEHICLE SENSOR	R MD	(M)	M	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		C C	C AD			EXISTING	PROPOSED
REFORMED DETECTOR LOOP		[P]	Р	INTERNATIONAL SYMBOL, SOLID	()	*	RAILROAD SYMBOLS				
DETECTOR LOOP, TYPE I				12" (300mm) PEDESTRIAN SIGNAL HEAD							
'NO RIGHT TURN''	0	®	®	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		[PS]	PS
'NO LEFT TURN'' LLUMINATED SIGN	⊚ R	8	9	12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		ÓW W		PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		PIS	PIS
ILLUMINATED SIGN	R					"P"	"P"	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT	OR	[PP]	
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R	@aps	@ APS	, INDICATES INCOMARMILD READ			∢ Y ∢ G	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT	OR ·	[P]	
PEDESTRIAN PUSHBUTTON DETECTOR	R (6)	<u> </u>	<u>-</u> (6)	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD			Y	EXISTING INTERSECTION LOOP DETECTOR			2
PEDESTRIAN SIGNAL HEAD	R -TI	-0	-8			R	R	(SYSTEM) DETECTOR SAMPLING (SYSTEM) DETECTOR		[s]	S
LASHER INSTALLATION S DENOTES SOLAR POWER)	0-f>"F"	O-D″F″	• • "F"			*	◆ Y ◆ G	INTERSECTION & SAMPLING		ĪĪS	IS
IGNAL HEAD OPTICALLY PROGRAMMED	R □>"P"	[>″p″	- ₩ "P"	SIGNAL FACE			G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF		
IGNAL HEAD WITH BACKPLATE	+ R	+C>	+			R	R	FOUNDATION TO BE REMOVED	0- X		
IGNAL HEAD CONSTRUCTION STAGES NUMBERS INDICATE THE CONSTRUCTION STAGE)			2	YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF		
IGNAL HEAD	R D	-⊳		12" (300mm) RED WITH 8" (200mm)			<u></u>	ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
ETTER) 45 FOOT (13.7m) MINIMUM UY WIRE	>R	>	>-	ABANDON ITEM 12" (300mm) TRAFFIC SIGNAL SECTION	А	R	R	STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	O		
EMPORARY WOOD POLE (CLASS 5 OR	R⊗	\otimes	•	RELOCATE ITEM	RL				RMF		
ASSEMBLY AND POLE WITH PTZ CAMERA SIGNAL POST	R	0	•	REMOVE ITEM	R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
STEEL COMBINATION MAST ARM	R	Pizh	€ PīZ ≰	INTERSECTION ITEM		ı	IP	(H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE		C III	c III
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE	R _{O→X}	0-×	● ★	COILABLE NONMETALLIC CONDUIT (EMPTY) SYSTEM ITEM		S	CNC S	ROUND ROD AT (C) CONTROLLER,		,	
ALUMINUM MAST ARM ASSEMBLY AND POLE	R	0		COMMON TRENCH			СТ	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE		- Ø-	
(P) POLE OR (G) GROUND MOUNT STEEL MAST ARM ASSEMBLY AND POLE	R	0		TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	R			NO. 62.5/125, MM12F SM12F		-(24F)-	(24F)
TELEPHONE CONNECTION	R	P	P	GALVANIZED STEEL CONDUIT IN TRENCH (T) OR PUSHED (P)		PROBLEM AND ADMINISTRATION VISIONS		NO. 62.5/125, MM12F FIBER OPTIC CABLE			
SERVICE INSTALLATION, P) POLE OR (G) GROUND MOUNT	R	-D ^P	- P	JUNCTION BOX	R 📵	0	ø	NO. 18 3 PAIR TWISTED, SHIELDED FIBER OPTIC CABLE		<u> </u>	
UNINTERRUPTIBLE POWER SUPPLY	UPS R	EUPS	MMC UPS	DOUBLE HANDHOLE	R			COPPER INTERCONNECT CABLE,		<u> </u>	-6-
MASTER CONTROLLER MASTER MASTER CONTROLLER		EMMC	MC	HEAVY DUTY HANDHOLE	R	H	H	VENDOR CABLE FOR CAMERA			(v)
COMMUNICATIONS CABINET	[cc] ^R	ECC	CC	HANDHOLE	R ⊠			COAXIAL CABLE			—©—
RAILROAD CONTROL CABINET		Reserved.		CONFIRMATION BEACON	R _{o-()}	0(]	•(d	
CONTROLLER CABINET	⊠ ^R	\bowtie	M	EMERGENCY VEHICLE LIGHT DETECTOR	R≪	\ll	•	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE			(1)
ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED